

GOOD HOUSEKEEPING PRACTICES

- **CONDUCT A WEEKLY LEAK DETECTION AND REPAIR PROGRAM TO INSPECT ALL DRYCLEANING EQUIPMENT FOR LEAKS THAT ARE OBVIOUS BY SIGHT, SMELL OR TOUCH.**
- **CONDUCT ENHANCED LEAK DETECTION WITH HALOGENATED HYDROCARBON DETECTOR AT LEAST ONCE PER MONTH.**
- **REPAIR LEAKS WITHIN 24 HOURS AFTER THEY ARE FOUND, OR ORDER REPAIR PARTS WITHIN 2 WORKING DAYS AFTER DETECTING A LEAK THAT NEEDS REPAIR PARTS. INSTALL THE REPAIR PARTS BY 5 WORKING DAYS AFTER THEY ARE RECEIVED.**
- **KEEP A LOG OF THE RESULTS OF THE LEAK DETECTION AND REPAIR PROGRAM.**
- **FOR MACHINES EQUIPPED WITH REFRIGERATED CONDENSERS, MONITOR REFRIGERATED CONDENSER HIGH/LOW PRESSURE OR EXIT TEMPERATURE ONCE PER WEEK**
- **FOR MACHINES EQUIPPED WITH A SECONDARY CARBON ADSORBER, MONITOR PERC CONCENTRATION IN DRUM HEADSPACE AT END OF CYCLE ONCE PER WEEK.**
- **FOLLOW GOOD HOUSEKEEPING PRACTICES, WHICH INCLUDE KEEPING ALL PERC AND WASTE CONTAINING PERC IN COVERED CONTAINERS WITH NO LEAKS. DRAINING CARTRIDGE FILTERS IN CLOSED CONTAINERS, AND KEEPING MACHINE DOORS SHUT WHEN CLOTHING IS IS NOT BEING TRANSFERRED.**
- **OPERATE AND MAINTAIN ALL DRYCLEANING EQUIPMENT ACCORDING TO MANUFACTURER'S INSTRUCTIONS.**

REQUIRED RECORDS

- **A LOG OF THE RESULTS OF THE LEAK DETECTION AND REPAIR PROGRAM.**
- **A LOG OF THE AMOUNT OF PERC PURCHASED IN THE LAST 12 MONTHS, CALCULATED EVERY MONTH.**
- **THE MONITORING RESULTS.**
- **THE OPERATION AND MAINTENANCE MANUALS FOR ALL DRY CLEANING EQUIPMENT AT THE FACILITY.**