

## Seventeen Mile River Watershed Management Plan

The preparation of this document was financed in part through a grant from the U.S. Environmental Protection Agency under the Provisions of Section 319(h) of the Federal Water Pollution Control Act, as amended.

Prepared by Resource Management Strategies under contract with the Seven Rivers Resource, Conservation and Development Council, Inc.







#### ACKNOWLEDGMENTS

Seven Rivers RC&D Eugene Dyal, Program Coordinator Brenda Hallman, Program Administrator

Watershed Advisory Committee Atkinson County Public Health Department Coffee County Public Health Department Georgia Forestry Commission GA DNR, Environmental Protection Division, Denisse Hernandez GA DNR, Wildlife Resources Division, Fisheries Management, Bert Deener Georgia Soil & Water Conservation Commission Jeff Davis County Public Health Department Satilla River Keeper Satilla River Soil and Water Conservation District South Georgia Regional Commission Suwannee-Satilla Regional Water Planning Council University of Georgia, Cooperative Extension USDA Natural Resource Conservation Service Ware County Public Health Department

### TABLE OF CONTENTS

I. Introduction <u>1</u>
II. Stream Selection
III. Formation of a Watershed Advisory Committee.
IV. Source Assessment <u>6</u>
V. Assessment and Characterization of Current Conditions. 7   Overview. 7   Climate. 8   Habitat. 8   Wildlife. 9   Physical and Natural Features. 10   Topography. 10   Stream Buffers. 10   Soils. 11   Flooding. 13   Water Resources. 14   Hydrology. 14   Groundwater Recharge Areas and Pollution Susceptibility. 14   Floridian Aquifer. 15   Land Use. 15   Demographics. 15   Land Use. 15   Demographics. 16   Stiviculture. 17   LAS/NPDES Permits. 17   Water Supply and Severage System. 18   Impervious Surface. 20   Unpaved Rural Roads. 21   Stormwater. 21   Waterbody and Watershed Conditions. 22   Visual Survey. 22
Seventeen Mile River Watershed Management Plan, May 2018

Water Quality Monitoring Data.   Otter Creek at Highway 32.   Seventeen Mile River at Georgia Highway 158 and Georgia Highway 64.	<u>23</u> 25 25
Seventeen Mile River at Highway 135. Seventeen Mile River at Highway 32. Otter Creek at Sand Hill Church Road Twentynine Mile Creek at Raccoon Bridge Road	25 26 26 27
Seventeen Mile River at Highway 64	<u>27</u> 27
Healthy Watersheds.	<u>28</u>
Land Management Ordinances and Activities	<u>32</u>
VI. Recommended Management Practices	<u>37</u>
Recommended Management Practice Effectiveness	<u>38</u>
Agriculture.	<u>38</u>
Individual Septic System.	<u>40</u> 40
Stormwater System.	41
VII. Working With The Public	<u>46</u>
Outreach Goals.	<u>46</u>
VIII. Long-Term Monitoring Plan	<u>48</u>
IX. Implementation, Evaluation, and Revision	49
Management Strategies	49
Priority Areas for Management Practices	<u>10</u>
Implementation Plan and Interim Milestones	<u>47</u>
	<u>49</u>
Indicators to Measure Progress.	<u>55</u>
Long-term Plan Implementation	<u>55</u>
V Appandix	_ /
	<u>56</u> 57
Map 1 Base	<u>57</u> 58
Map 3 Soils	<u>59</u>
Map 5 Pollution Susceptibility	<u>60</u> 41
Map 6 Groundwater Recharge Areas.	<u>01</u> 62
· · · · · · · · · · · · · · · · · · ·	
Seventeen Mile River Watershed Management Plan, May 2018	iii

Map 7 Wetlands
Map 8 Existing Land Use
Map 9 Zoning
Map 10 Future Land Use
Map 11 Sewerage Service Area
Map 12 Impervious Surface
Metadata
Water Quality Monitoring Data
Georgia FY 2017 EQIP Policy

### I. Introduction

The purpose of the Seventeen Mile River Watershed Management Plan, HUC-10 #0307020105, is to provide a tool that demonstrates a holistic approach to water quality management by actively engaging stakeholders within the watershed in the selection of management strategies that will be implemented to solve identified problems.

This Plan, builds on the Satilla River Basin Management Plan 2002 by supporting the following basin-wide goals and objectives, specifically:

- ! Goals
  - ' Protect, maintain, and where appropriate and practicable, identify opportunities to enhance water quality and river base flows.
  - " Identify opportunities to manage stormwater to improve water quantity and quality.
  - " Identify and implement actions to better measure and share water use data and information.
- ! Objectives
  - " protecting water quality in lakes, rivers, estuaries, and coastal water through attainment of water quality standards and support for designated use, and
  - " preserving habitat suitable for the support of healthy aquatic and riparian ecosystems.

This Plan also supports implementation of milestone activities in the 2014 Georgia Non-point Source Management Plan regarding green infrastructure, education, reduction of agricultural and urban nonpoint source pollution through implementation of best management practices, education and outreach, partnership development, and targeted water quality monitoring.

Achieving the goals and objectives of this Plan is the responsibility of State and federal agencies, local government, non-profit organizations, industry, and local citizens.

This document is not regulatory. Its preparation process engages stakeholders to recognize issues and provide feedback on how to deal with them, as well as to develop momentum and contribute to the restoration effort.

PLAN GOAL: Develop a nine-element watershed management plan (WMP) for Seventeen Mile River Watershed that:

- addresses water quality impairments in stream segments identified as not supporting their designated uses based on the 2014 Georgia Integrated 305(b)/303(d) List of Waters: and
- identifies implementation policies and activities that will reduce impairments and improve water quality to meet targeted Total Maximum Daily Loads (TMDL) established by the Georgia Environmental Protection Division (EPD) and long-term, meet State water quality standards.



### II. Stream Selection

In 2002, the Georgia Environmental Protection Division (GA EPD) developed a Total Maximum Daily Load (TMDL) Implementation Plan for Seventeen Mile River<sup>1</sup>. The Implementation Plan addressed two impaired segments of the river;

- ! Twenty Mile Creek, north of Douglas, to Otter Creek, south of General Coffee State Park (7 miles in Coffee County), and
- ! Twentynine Mile Creek to the Satilla River (13 miles in Coffee, Atkinson, and Ware counties).

The designated use of the Seventeen Mile River is fishing. The Implementation Plan found that the sevenmile segment did not support, and the thirteen-mile segment only partially supported, its designated use due to fecal coliform and dissolved oxygen impairments. (See Map 1). However, by 2006, the thirteenmile segment was also found to not support its designated use.<sup>2</sup>

A TMDL establishes the allowable pollutant loadings or other quantifiable parameters for a water body based on the relationship between pollutant sources and instream water quality conditions. Water quality standards for fecal coliform and dissolved oxygen limit the amount of pollution allowed to load into a river or stream. If a stream does not meet water quality standards, a TMDL is established for that pollutant. Implementation tools, such as watershed-based plans, are then developed to reduce the pollutants loading into the stream from various (point and nonpoint) sources and restore the water body so that it meets water quality standards.

To meet State water quality standards, the 2002 TMDL Implementation Plan notes that a 64% reduction in nonpoint/point source fecal loads is necessary in the seven-mile segment and a 68% reduction is necessary in the thirteen-mile segment. The 2002 TMDL Implementation Plan was followed with a TMDL Evaluation in 2006<sup>3</sup> and 2011<sup>4</sup>, with the latter indicating a 65% reduction is necessary on the thirteen-mile segment.

<sup>1</sup> TMDL Implementation Plan, Satilla River Basin, Georgia Environmental Protection Division, 2002, p.1.

<sup>2</sup>2006 305(b)/303(d) Rivers/Streams Not Fully Supporting Designated Uses, Georgia Environmental Protection Division, p.110.

<sup>3</sup>Total Maximum Daily Load Evaluation for Eighteen Stream Segments in the Satilla River Basin for fecal coliform, Georgia Environmental Protection Division, January 2006.

<sup>4</sup>Total Maximum Daily Load Evaluation for Ten Stream Segments in the Satilla River Basin for fecal coliform, Georgia Environmental Protection Division, March 2011, p. vi.

To address dissolved oxygen in the River, both the seven- and thirteen-mile segments require a 24% point source load reduction and an 11% - 54% nonpoint source load reduction.<sup>5</sup>

The above-discussed plans attribute both point and nonpoint sources to fecal coliform contamination. The sole point source is the City of Douglas Water Pollution Control Plant, NPDES permit GA0024431. Nonpoint sources include uncovered manure piles, farm animal waste, access to waterways by livestock, urban and rural development, poultry industry runoff, spills/discharge of raw sewage, pet excrement, and leaking septic systems.

These same contamination sources also contribute to dissolved oxygen impairment. Additional sources of oxygen-demanding substances include surface storm water runoff of chemicals and fertilizers from agricultural areas; industrial, residential, and urban stormwater runoff; automotive care products; improper methods of trash collection and disposal; land disturbing activities; and organic material from lawns and city or county rights-of-way.

In addition to the non-supporting streams, the 2016 Integrated 305(b)/303(d) List of Waters identifies two stream segments in the watershed meeting water quality standards and are therefore designated as supporting segments:

- ! Otter Creek (Tiger Creek to Seventeen Mile River), 2 miles in Coffee County;
- ! Seventeen Mile River (Otter Creek to Twenty-nine Mile Creek), 8 miles in Coffee County.

During development of the Watershed Management Plan, specific actions were identified and designed to meet the specific objectives thus insuring that the proposed actions could objectively achieve the goals of the Seventeen Mile River Watershed Management Plan.

#### OBJECTIVES:

- Establish a Watershed Partnership (WP) as long-term committee charged with working with the Seven Rivers RC&D to implement Watershed Management Plan.
- Long-term monitoring to provide current data to support decision-making.
- Identification of potential contaminant sources.
- Implementation of management practices to reduce fecal coliform contamination from identified sources.
- Implementation of management practices to facilitate dissolved oxygen levels to meet state standards.
- Manage growth and land use activities so that they do not negatively effect overall water quality or improvements made through implementation of this watershed management plan.
- Promotion of public awareness, understanding, and stewardship through public education and training opportunities for the general population and government agencies.

p.27.

<sup>&</sup>lt;sup>5</sup>Seventeen Mile River Dissolved Oxygen TMDLs, Satilla River Basin (HUC 03070201), June 2002,

### III. Formation of a Watershed Advisory Committee

This Plan's development relied upon the participation of a Watershed Advisory Committee (WAC) which represented the Seventeen Mile River watershed and consisted of stakeholders that would assist with plan implementation. (See Appendix). Meetings were held with the WAC on the following dates to engage the public in the process of designing an implementation plan: October 6, 2017 and March 23, 2018. Meetings focused on gathering input concerning potential problems and solutions, developing priorities, evaluating what BMPs might be met with the best public reception, and obtaining insight on the watershed management plan. Finally, approval was sought for the document to serve as the plan on which implementation efforts will follow to restore and maintain the watershed.

Based on the TMDL Evaluations, TMDL Implementation Plans, current water quality monitoring, visual survey, land use, tax assessor data, and WAC input, the potential causes of water quality impairment were determined as follows:

Seventeen Mile River Watershed Potential Sources of Contamination				
Identified Impairment	Potential Source/Cause			
	Agricultural operations			
	Livestock access to waterways and/or inadequate buffers between fenced livestock and river			
Fecal Coliform	Unpaved roads that cross the river or end at river's edge and associated runoff			
	Failing/leaking individual septic systems			
	Public Sewerage system leaks and overflows			
	City of Douglas Wastewater Treatment Plant			
	Wildlife			
	Runoff of agricultural fertilizer and animal waste			
	Storm water runoff			
Dissolved Oxygen	Sanitary sewer overflows			
	Industrial facilities			
	City of Douglas wastewater treatment plant			

### Overview

The Seventeen Mile River HUC-10 watershed contains 98,182 acres of agricultural and forested land primarily in Coffee, Atkinson, Ware, and Jeff Davis counties and residential, commercial, and industrial lands in and adjacent to the City of Douglas.

The watershed is comprised of five major streams, Big Branch, Tiger, Otter, Cat, and Twentynine Mile creeks, each fed by numerous first- and second-order tributaries.

Seventeen Mile River's headwaters begin north-east of Ambrose in Coffee County. From there, it meanders south-east through agricultural and to a lesser extent, forest land in unincorporated Coffee County to just north of Douglas where it accepts runoff from residential and commercial land uses, to General Coffee State Park where it turns south to its confluence with the Satilla River, flowing through primarily through agricultural and forest land.

Based on water quality monitoring data, GA EPD identified two healthy streams in the watershed, Otter Creek and the segment of Seventeen Mile River from Otter Creek to its confluence with Twenty-nine Mile Creek. A healthy watershed is one in which natural land cover supports:

- ! dynamic hydrologic and geomorphologic processes within their natural range of variation;
- ! habitat of sufficient size and connectivity to support native aquatic and riparian species; and
- ! physical and chemical water quality conditions able to support healthy biological communities.

A healthy watershed has the structure and function in place to support healthy aquatic ecosystems. Key components of a healthy watershed include:

- ! intact and functioning headwater streams, floodplains, riparian corridors, biotic refuge, instream habitat, and biotic communities;
- ! natural vegetation in the landscape; and
- ! hydrology, sediment transport, fluvial geomorphology, and disturbance regimes expected for its location.

Based on water quality monitoring data, GA EPD identified two impaired stream segments in the watershed:

- Seventeen Mile River (Twenty Mile Creek north of Douglas to Otter Creek downstream Gen. Coffee St. Park) 7 miles in Coffee County;
- ! Seventeen Mile River (Twenty-nine Mile Creek to Satilla River), 13 miles in Coffee, Atkinson, and Ware counties;

The non-supporting segments are so identified due to non-point source fecal coliform contamination and dissolved oxygen impairment. The designation of these segments as "not supporting" are based on fecal coliform sampling data from 2003 and 2004, and 2008 and 1998 dissolved oxygen data. Sampling was conducted by the Georgia Department of Natural Resources, Environmental Protection Division's (GA EPD) and United States Geological Survey (USGS) at the following locations:

- ! Seventeen Mile River at State Route 32 near Douglas (GA EPD)
- ! Seventeen Mile River at Highway 64 near Pearson (GA EPD)
- ! Seventeen Mile River at Highway 158 (USGS)

### Climate

The Satilla River basin, which includes the Seventeen Mile River watershed, is characterized by mild winters and hot summers. Mean annual precipitation ranges from 46 to 54 inches per year. Rainfall is fairly evenly distributed throughout the year, but a distinct dry season occurs from mid-summer to late fall. Rainfall is usually greatest in March and least in October. The mean annual temperature is about 68 degrees Fahrenheit.<sup>6</sup>

### Habitat

The Satilla River basin, which includes the Seventeen Mile River HUC-10 watershed, supports a diverse and rich mix of terrestrial and aquatic habitats and is home to several federally and state-protected species; however, there is no list of such species and habitats specifically for the Seventeen Mile River watershed.

The watershed is largely rural with fair wildlife habitat in predominantly cropland and woodland settings. Major plants of importance to terrestrial wildlife include greenbrier, bush and annual lespedeza, panic grass, croton, ragweed, partridge pea, paspalum, tickclover, and sumac. Understory and overstory woodland plants of importance are sweetgum, oak, hackberry, button bush, and maple. Domestic plants of importance to wildlife include peanuts, corn, soybeans, bahiagrass, and small grains. Cropland and pastureland, interspersed with pine plantations and hardwood forests, provide habitat for white-tailed deer, mourning dove, raccoons, gray squirrel, opossum, fox, and other wildlife. Rabbit and bobwhite quail populations are good in areas which have suitable food an cover.

Unmanaged pasture, old fields, pine plantations, and thinned woodlands produce numerous native woody and herbaceous plants important as food and cover for white-tailed deer, rabbit, fox, quail, and other wildlife species.

Continued land use trends toward extensive clearing of woodland for agriculture and urban development and the introduction of irrigation adversely affect fish and wildlife populations. Removal of crop residue from fields, removal of hedgerows and odd areas, and increased siltation have an adverse effect on fish

<sup>&</sup>lt;sup>6</sup>Satilla River Basin Management Plan, GA DNR, EPD, 2002, Section 2, pg. 2-3.

Seventeen Mile River Watershed Management Plan, May 2018

and wildlife habitat. Many of the chemicals used to increase agricultural production have severe affects on small birds and animals. The most seriously affected game species is quail.

Restoring hedgerows, field borders, windbreaks, and odd areas in fields will improve habitat for wildlife as well as prescribed burning in pine plantations and retaining mast-producing trees such as oaks.

Wetland habitats support a variety of furbearers including otter, beaver, bobcat, racoon, and waterfowl. The best wetland habitat is bottomland hardwoods along several rivers in the Satilla Basin, including Seventeen Mile River.

Important fresh water sport fish include largemouth bass, crappie, channel catfish, bluegill, and redear sunfish. Anadromous sport fish species include striped bass and shad.

Because of the fragile habitat requirements of fish, special efforts are needed to restrict and retard both point and nonpoint sources of water pollution in the watershed.<sup>7</sup>

### Wildlife

According to the Georgia Department of Natural Resources, Wildlife Resources Division (GA WRD), the impact of wildlife on fecal coliform contamination varies widely. The animals that spend a large portion of their time in or around aquatic habitats are the most important wildlife sources of fecal coliform. Waterfowl, most notably ducks and geese, are considered to potentially be the greatest contributors of fecal coliform. This is because they are typically found on the water surface, often in large numbers, and deposit their feces directly into the water. Other potentially important animals regularly found around aquatic environments include racoons, beavers, muskrats, and to a lesser extent, river otters, and mink. Population estimates of these animal species in Georgia are not available.

White-tailed deer are abundant in the watershed. According to GA WRD, fecal coliform bacteria contributions to water bodies from deer are generally considered less significant than that of waterfowl, racoon, and beaver due to a greater portion of their time being spent in terrestrial habitats. This is also true for other terrestrial mammals such as squirrels and rabbits, and terrestrial birds. While feces deposited on the land surface can result in the introduction of fecal coliform to streams during runoff from storm events, in the warm, humid environments typical of the southeast, there may be considerable decomposition of the fecal matter. This may result in a decrease in the associated fecal coliform numbers introduced from to streams during runoff from storm events.

Rapidly expanding feral swine populations have become a significant presence in the floodplain areas of major rivers in Georgia. Wild hogs are reported west of the Seventeen Mile River watershed with only minor migration of the species into Atkinson and Ware counties. None have been reported in Coffee County.

<sup>&</sup>lt;sup>7</sup>Soil Survey of Atkinson, Bacon, and Coffee Counties, Georgia, USDA, SCS, April 1988, pp. 49-51.

### **Physical and Natural Features**

#### Topography

Elevations in the watershed range from 35 to 75 feet above sea level.

#### **Streambanks**

Streambanks on the impaired and healthy streams evidence little erosion and are generally well vegetated.

#### Stream Buffers

To help protect water quality, the state mandates wooded stream buffers of at least 25' on each side of the stream bank. Based on a review of 2017 aerial photographs, natural vegetated buffers (see Map 2) are adequate throughout much of the watershed, along the main channel as well as its tributaries with the exception of the following:

- ! portions of Douglas County Country Club; and,
- ! major transportation crossings.





Douglas County Country Club

Highway 64





Railroad crossing

Highway 32 East

#### Soils

The Seventeen Mile River watershed is contained two Major Land Resource Areas (MLRA): the Atlantic Coast Flatwood and the Southern Coastal Plain.

The dominant soil orders in Atlantic Coast Flatwood MLRA are Spodosols and Ultisols. The soils are generally are very deep, well drained to very poorly drained, and loamy or clayey.<sup>8</sup>

The dominant soil orders in the Southern Coastal Plain MLRA are Ultisols, Entisols and Inceptisols. These soils generally are very deep, somewhat excessively drained to poorly drained, and loamy.<sup>9</sup> Soils in this MLRA are dominated by nearly level and very gently sloping Tifton, Leefield, and Fuquay soils on uplands and nearly level Pelham soils along drainageways and floodplains. Tifton soils are well drained upland soils that have a sandy surface layer and a yellowish brown or strong brown, loamy subsoil. The surface layer is normally loamy sand and is about 10 inches thick. The subsoil is mostly sandy clay loam. Fuquay and Leefield soils have a thicker sandy surface than Tifton, and Leefield soils have a water table is higher. Characteristic of these soils is a layer of plinthite in the subsoil at a depth of about 30 inches. Plinthite is an iron-rich mixture of clay with quartz and other constituents that can perc water during wet seasons. Pelham soils are nearly level and poorly drained. They have a sandy surface layer 20 to 40 inches thick over a loamy subsoil. Water tables are commonly at or near the surface during wet seasons, and the soils are subject to flooding.

<sup>8</sup>Georgia Soil Survey 153A – Atlantic Coast Flatwoods, USDA, NRCS, Georgia.

<sup>9</sup>Georgia Soil Survey 133A - Southern Coastal Plain, USDA, NRCS, Georgia.

Major resource concerns are erosion, maintenance of the content of organic matter and productivity of the soils, control of surface water, artificial drainage, and management of surface compaction and soil moisture.

The predominate soils in the watershed are:

- Kinston and Johnston, generally found on floodplains, and are very poorly to poorly drained. The soils are well-suited to growing pine trees, are poorly suited to field crops, hay, and pasture and severely limited for non-farm uses.
- Leefield, somewhat poorly drained and generally found on smooth, upland areas with a slope of 0 to 2 percent including the City of Douglas. This soil is moderately suited to urban uses and recreational development but, due to wetness, can limit uses where septic systems are required. This limitation can be overcome by special design and application.
- Pelham soils are poorly drained and generally found on in broad, smooth areas and near drainways and depressions. The soils are well-suited to growing pine trees, poorly suited to field crops, hay, pasture, and recreational development due to wetness and flooding which also severely restricts urban uses.

The following table depicts the Seventeen Mile River watershed generalized soils and provides a general description of the soil associations found in the watershed. See Map 3.

Seventeen Mile River Watershed Soils						
Soil Name	Acreage	Percent	Characteristics			
Ailey	441.62	0.46%	well drained			
Albany	5305.62	5.52%	poorly drained			
Bayboro	226.87	0.24%	very poor			
Blanton	801.39	0.83%	moderately well drained			
Bonifay	1410.39	1.47%	well drained			
Cainhoy	6.94	0.01%	Excessively well drained			
Carnegie	6599.03	6.87%	well drained			
Clarendon	3638.58	3.79%	moderately well drained			
Cowarts-Sunsweet	176.56	0.18%	well drained			
Dothan	1382.44	1.44%	well drained			
Esto	216.23	0.23%	well drained			
Fuquay	5139.79	5.35%	well drained			
Kershaw	6290.08	6.55%	excessively well drained			
Kinston and Johnston	14184.12	14.77%	poorly/very poorly drained			
Leefield	11092.1	11.55%	poorly drained			
Leon	17.46	0.02%	poorly /very poorly drained			
Mascotte	111.7	0.12%	poorly/very poorly drained			
Meldrim	49.4	0.05%	moderately well drained			
Olustee	308.92	0.32%	somewhat poorly drained			
Pelham	19022	19.80%	poorly drained			
Rigdon	2567.44	2.67%	poorly drained			
Sapelo	4974.72	5.18%	poorly drained			
Stilson	2071.43	2.16%	moderately well drained			
Surrency	4606.87	4.80%	poorly drained			
Tifton	4783.23	4.98%	well drained			
Troup-Ailey	193.61	0.20%	well drained			
Wahee	201.53	0.21%	poorly drained			
Water	116.77	0.12%	NA			
Wicksburg	115.8	0.12%	well drained			

Source: - U.S. Department of Agriculture, Natural Resources Conservation Service, 2015; Soil Survey of Atkinson, Bacon, and Coffee Counties, USDA NRCS; April 1988. Web Soil Survey (Ware County) https://websoilsurvey.nrcs.usda.gov/app/. Survey Geographic (SSURGO) Database.

#### Flooding

Flooding in the watershed is associated with Otter and Tiger creeks, Seventeen Mile River, the lower half of Twentynine Mile Creek, and an unnamed tributary of Seventeen Mile River north of Highway 158 (E. Baker Hwy.). See Map 4.

### Water Resources

#### Hydrology

The Seventeen Mile River HUC-10 watershed includes 144 miles of perennial and intermittent streams, 369 acres of lakes, and 26.576 acres of wetlands.

#### Groundwater Recharge Areas and Pollution Susceptibility

Groundwater is among the Nation's most important natural resources. It provides drinking water to urban and rural communities, supports irrigation and industry, sustains the flow of streams and rivers, and maintains riparian and wetland ecosystems. In many areas of the Nation, the future sustainability of ground-water resources is at risk from over use and contamination. Because groundwater systems typically respond slowly to human actions, a long-term perspective is needed to manage this valuable resource. It is therefore essential to the health, safety, and welfare of the public that the quality of subsurface public drinking water be maintained.

Groundwater resources exist in underground reservoirs known as aquifers. These aquifers are zones of rock beneath the earth's surface that are capable of providing water for a well. They occupy vast regions of the subsurface and are replenished by infiltration of surface water runoff in zones of the surface, known as groundwater recharge areas. Groundwater is susceptible to contamination when development occurs within groundwater recharge areas. Certain land use activities, such as septic tanks, underground tanks, and chemical spills, pose a significant threat to the quality of groundwater supplies. Therefore, it is necessary to manage land uses within groundwater recharge areas in order to ensure that pollution threats and development impacts are minimized.

The Georgia Department of Natural Resources mapped areas of high, average (or medium), and low susceptibility of groundwater to pollution in Georgia. This map is commonly known as Hydrologic Atlas 20 or the Groundwater Pollution Susceptibility Map of Georgia. The Seventeen Mile River watershed is located in a "average" to "high" groundwater pollution susceptibility area. (See Map 5). However, within a pollution susceptibility area are also significant groundwater recharge areas. These areas are mapped on the Hydrologic Atlas 18 or the Groundwater Recharge Area Map of Georgia. (See Map 6). Four groundwater recharge areas are located in the Seventeen Mile River watershed; two of which intersect impaired segments.

The significant groundwater recharge areas in the watershed are subject to pollution from spills, discharges, leaks, impoundments, applications of chemicals, injections and other human activities in the watershed. Once in the aquifer, pollutants can spread uncontrollably to other parts of the aquifer thereby decreasing or endangering water quality for an entire region. Once polluted, it is almost impossible for a groundwater source to be cleaned up.

#### Floridian Aquifer

Groundwater resources in the Satilla River basin, which includes the Seventeen Mile River watershed, are supplied by the Floridan aquifer system is highly permeable and one of the most productive

ground water reservoirs in the United States. The system supplies about 50 percent of the ground water used in the state and is a major water source throughout most of South Georgia.

#### **Wetlands**

Extensive wetlands are found throughout the watershed. See Map 7.

### Land Use and Demographics

#### Land Use

The predominant existing land use in the watershed is agricultural, 59%, followed by forestry, 28%. Urbanized land use accounts for less than 10% of the watershed and most is devoted to residential use in Douglas and the surrounding area and north of Ga Highway 32. See Maps 8 and 9.

Existing Land Use, 2007				
Land Use Classification	Acreage	Percent		
Agriculture	58496.05	58.82%		
Commercial	516.97	0.52%		
Industrial	132.43	0.13%		
Forestry	28643.8	28.80%		
Park/Recreation/Conservation	2841.4	2.86%		
Public/Institutional	583.19	0.59%		
Residential	8241.45	8.29%		

Source: South Georgia Regional Commission

By 2027, the predominate land use will continue to be agriculture and forestry. Current forested land is expected to transition primarily to residential land use and comprise about 14 percent of the watershed. Residential development is anticipated along Tiger Creek, between Highway 158 and Seventeen Mile River, and adjacent to Twentynine Mile Creek. See Map 10.

Future Land Use, 2027				
Classification	Acreage	Percent		
Agriculture	146920	81.36		
Commercial	2149	1.19		
Park/Recreation/Conservation	2838	1.57		
Public/Institutional	3118	1.73		
Residential	25548	14.15		
Total	180573			

Source: South Georgia Regional Commission

#### Demographics

From 2000 - 2010, Atkinson, Coffee, and Ware counties population grew by a combined 29.79 percent and Douglas, 9.58 percent. Estimated county population growth from 2020 to 2030 show the majority growth will occur in Coffee County. No population data exists solely for the Seventeen Mile River watershed.

Total Population and Percent Change, 2000 – 2030							
County/City	2000	2010	% change 2000-2010	2020	% change 2010–202 0	2030	% change 2020-2030
Atkinson	7609	8365	9.93	8890	6.27	9377	5.47
Coffee	37413	42738	14.23	52825	23.60	65233	23.49
Ware	35483	36366	2.63	35811	-1.53	35974	0.46
Douglas, City	10639	11659	9.58				

Source: US Census Bureau, 2000, 2010; Carl Vinson Institute of Government, 2020, 2030.

#### Agriculture

As the majority of the watershed is in Coffee County, and to a lesser extent, Atkinson and Ware counties, data will focus on only these three counties. Agricultural land in the watershed covers 58,496.05 acres, or 58.82 percent of the watershed. County-wide, the average farm size from 203 acres in Ware County, 286 acres in Coffee County, and 448 acres Atkinson County. The majority of farms are between 10 and 499 acres. Top crop products in Atkinson, Coffee, and Ware counties are corn for grain, tobacco, soybeans, cotton, peanuts, and vegetables. Land devoted to blueberry orchards increased in Coffee County by 92% from 2007 to 2017 and totals 458 acres.<sup>10</sup>

The number of poultry animals increased between 2007 and 2012 while all other animal numbers decreased. During the same time frame, Coffee and Atkinson counties experienced an increase in acres devoted to crop production, particularly in cotton, peanuts, tobacco, and soybeans

The majority of the intensive agricultural uses in the watershed are currently located in Coffee County and consist of cattle, swine, and poultry operations. Agricultural operations in the Tiger and Otter creek subwatershed consist primarily of crops/pasture and some swine. Agricultural operations in the Twentynine Mile Creek subwatershed consist primarily of poultry and beef cattle.

Agricultural BMPs previously installed on poultry operations in the Twentynine Mile Creek subwatershed include stackhouses and incinerators. One poultry operation plans to install a stackhouse and composter in 2018. Other practices installed in the Seventeen Mile River watershed

<sup>&</sup>lt;sup>10</sup>Census of Agriculture, USDA, National Agricultural Statistics Service, 2007 and 2012.

include conservation tillage, cattle practices, tree planting, and cover crops. However, water quality monitoring data indicates that contamination continues in the Twentynine Mile Creek subwatershed. A possible source is cattle operations where dry poultry litter is spread on the pastures.

#### Silviculture

The majority of soil erosion from forested land occurs during timber harvesting and the period immediately following, and during reforestation. Once the forest is re-established, very little soil erosion occurs. Timber harvesting includes the layout of access roads, log decks, and skid trails, the construction and stabilization of these areas, and the cutting of trees.

According to the 2015 Georgia Forestry Commission Survey, statewide, correct implementation of forestry best management practices (BMPs) was 91.13 percent, a 1.20 percent improvement in BMP implementation from 2013. By ownership, the percentage of BMP implementation was 93.62 percent on corporate lands, 96.21 percent on public lands and 89.74 percent on private lands. BMP implementation for 2015, improved significantly for streamside management zones from the 2013 survey by 7.7

percentage points, to a score of 94.20 percent in 2015. Of particular interest is the fact that the number of Water Quality Risks observed decreased from 100 to 63 for an improvement of 37% over 2013.<sup>11</sup>

#### LAS/NPDES Permits

Point sources are defined as discharges of treated wastewater to the river and its tributaries, regulated under the National Pollutant Discharge Elimination System (NPDES). These are divided into two main types—permitted wastewater discharges, which tend to be discharged at relatively stable rates, and permitted storm water discharges, which tend to be discharged at highly irregular, intermittent rates, depending on precipitation.

GA EPD implements a permit for land application systems (LAS); a nondischarging waste disposal system which is not intended to discharge treated effluent to surface waters. LAS are means of disposing liquid wastewater sludge that has gone through treatment process onto the land.

LAS permits also regulate the disposal of wet manure and processed wastewater from new and existing animal feeding operations (AFOs) on a land treatment system within the State of Georgia for owners of existing, new, and expanding AFOs.

Operations in the watershed that hold LAS permits are:

• Roscoe Meeks Farm - Swine operation located on New Forest Highway, the farm holds general industrial LAS AFO (300 to 1000 animal units) permit #GAG920005.

<sup>&</sup>lt;sup>11</sup>Results of Georgia's 2015 Silvicultural Best Management Practices Implementation and Compliance Survey, Georgia Forestry Commission, December 10, 2015.

- Tim Meeks Farm Swine operation located on Danny Kirkland Road, the farm holds general industrial permit LAS AFO (>1000 animal units) permit #GAG940004.
- Tom Meeks Farm Swine operation located on Whisperwood Road, the farm holds an industrial permit GAG940003 General LAS AFO (> 1000 animal units) permit #GAG94003.

The EPD NPDES permit establishes specific effluent limitations and specifies compliance schedules that must be met by the point-source discharger. Effluent limitations are designed to achieve water quality standards in the receiving water and are reevaluated at least every 5 years.

There are also a number of poultry operations in the watershed. Because these operations utilize dry manure, no LAS permit is required.

Municipal wastewater treatment plants are among the most significant point sources regulated under the NPDES program in the Satilla River basin as they account for the majority of the total point source effluent flow (exclusive of cooling water). These plants collect, treat, and discharge large volumes of treated wastewater into nearby surface waters (receiving streams). Pollutants associated with treated wastewater include pathogens, nutrients, oxygen-demanding waste, metals, and chlorine residuals.

The City of Douglas Southeast WPCP holds the only municipal NPDES permit (#GA0024431) in the watershed.

#### Water Supply and Sewerage System

#### Water Supply System

Douglas is the only jurisdiction in the watershed that offers public water supply service. The system operates under permit GA0690002 and primarily serves the City of Douglas. Residents outside the service area rely on private wells or community wells.

Douglas' water comes from six municipal groundwater wells approximately 700 feet deep. The water source is the Upper Floridian Aquifer. Wells pump an average of 4.8 million gallons per day and serve a population of 18,172 comprised of 4,700 households and 1683 commercial uses.

Active wells are located on city-owned property. These properties are protected from activities that could potentially cause contamination of these water sources. The city performs treatment at each of these wells to include chlorine disinfection and fluoridation. Additionally, the city has four, half-million gallon elevated storage tanks. The average daily demand is 0.700 mgd with a peak demand of 0.900 mgd.

#### Sanitary Sewer System

Douglas is also the only jurisdiction in the watershed operating a sanitary sewer and disposal system. See Map 11. The system serves the developed area inside the Loop (Bowens Mill Road SW and SE) with the exception of about 15 homes that remain on individual septic systems, an area along Highway 158, the west side of Highway 135, and the east side of US 441-S near the airport. The residential and commercial area in the northeast portion of city between Highway 135 and Seventeen Mile River is not served by public sewer.

The City of Douglas operates its Southeast water pollution control plant (WPCP) under permit GA0024431. The plant located at 622 Iron Road discharges up to 6.0 MGD of treated wastewater to an unnamed tributary to Seventeen Mile River.

#### Discharges and spills

The WPCP has experienced a number of spills. Georgia defines a "spill" as any discharge of raw sewage by a publically owned sewage treatment plant to the waters of the State. In general, a "major spill" is any discharge of raw sewage that exceeds 10,000 gallons or results in water quality violations in waters of the State. "Major Spill" monitoring lasts for a period of one year beginning with daily monitoring for the first week and then once/week monitoring for weeks 2-4 following the initial spill. Then once/week throughout the third month from the initial spill date and then once week on the twelfth month from the original spill date. See Appendix for monitoring data.

- March 1, 2017 Approximately 9,000 gallons of wastewater was spilled. The minor spill was due to blockage of a sewer lateral a pipe that goes to individual homes. The sewage overflowed into a storm drain that discharges to an unnamed tributary of the Seventeen Mile River.
- April 6, 2017 A minor wastewater spill occurred in an unnamed tributary to Seventeen Mile River due to a sanitary sewer overflow from a manhole located inside the Southeast Water Pollution Control. Approximately 7,000 gallons were spilled due to localized flooding from heavy rains which caused overloading of the sewer beyond its design capacity due to inflow and infiltration of water. Year-long monitoring is not required although the city will voluntarily conduct monitoring.
- August 23-24, 2017 Approximately 720,000 gallons of wastewater was spilled into the Seventeen Mile River from a lift station located on Ridge Lane. The cause of this major wastewater spill was "an improper drive setting in conjunction with a faulty alarm float during upgrades to the lift station." As a result of the spill, water quality sampling was initiated on August 24, 2017 on Seventeen Mile River up and downstream of the spill at Highway 135 and Coffee State Park, respectively. At the time of the spill, the lift station was under renovation. The station has since been completed and a diesel pump was installed to serve as a backup in case of failure of the primary pump.

Based on water quality monitoring data, there was no long-term water quality impairment to the Seventeen Mile River from these spills.

The City of Douglas has been fined twice since 2016 under GA EPD Enforcement Orders.

• Enforcement Order EPD-WQ-8005, was executed January 26, 2016 for Spills to waters of the state; violations of NPDES Permit, and Pretreatment Program; exceeded weekly average Permit limitations; and, failure to maintain proper usage records. The City was required to submit to GA EPD a Corrective Action Plan/schedule, including review and assessment of City's Pretreatment

Program, inspect all Industrial Users for bypass lines with plans to address lines; implement plan; provide final progress report outlining activities accomplished, as required; comply with all monitoring frequencies required in Permit including any adjustments, and report findings on monthly Discharge Monitoring Report. The settlement amount was \$30,000.00.

• Enforcement Order EPD-WP-8419, was executed January 30, 2018 for a lift station overflow which discharged pollutants into wasters of the state. The City was required to submit to GA EPD a plan to prevent sewage spills or overflows during lift station rehabilitation; and, submit documentation demonstrating the Respondent's commitment to purchase and install a natural gas or diesel powered bypass pump at the Bojo lift station. The settlement amount was \$5,000.00.

A portion of current SPLOST funds are earmarked for station upgrades and decreasing 'points of inflow' where storm waters are able to flow into the sewer system. System upgrades should be completed by 2019.

#### Private Septic Systems

County Boards of Health and the Geogia Department of Human Resources regulate the siting and installation of septic systems up to 10,000 gallon tank capacity. Larger systems are permitted by GA EPD. However, property owners are responsible for properly operating and maintaining the septic system to increase life expectancy and prevent failures.

Outside of the sewer service area in the city, residents rely on community systems or individual septic systems. Residents in the unincorporated areas of the watershed rely on individual or community septic systems.

The Coffee County Health Department indicates there have been past problems with septic systems in the residential/commercial area in northeast Douglas bounded by Highway 135 and the Seventeen Mile River and in the area of Old Axson Road. Further, the Coffee County Health Department reports that most problems with septic systems are reported in the winter months when the water table is high.

The WAC noted concerns with older systems in the northern portion of the watershed and the need for septic system maintenance education.

#### Impervious Surface

A significant portion of rainfall in forested watersheds is absorbed into soils (infiltration), is stored as ground water, and is slowly discharged to streams through seeps and springs. Flooding is less significant in these conditions because some of the runoff during a storm is absorbed into the ground, thus lessening the amount of runoff into a stream during the storm. However, as watersheds are urbanized, much of the vegetation is replaced by impervious surfaces, thus reducing the area where infiltration to ground water can occur. Thus, more stormwater runoff occurs - runoff that must be collected by extensive drainage systems that combine curbs, storm sewers, and ditches to carry stormwater runoff directly to streams. More simply, in a developed watershed, much more water

arrives into a stream much more quickly, resulting in an increased likelihood of more frequent and more severe flooding.

Impervious surface in the watershed includes roads, parking lots, and buildings, most of which are located in Douglas and to a lesser extent, northeast of Douglas along Highway 135. See Map 12.

As more development occurs in the watershed, the amount of impervious surface will increase leading to more urban runoff and potential for water quality contamination.

#### Unpaved Rural Roads

Roads are a major source of stormwater runoff but have a varied impact on sedimentation, depending on their surface. Primitive, unimproved or soil surface roads have the greatest impact, with gravel or stone roads, the next greatest impact. Erosion from unpaved roadways can be a significant sediment source to creeks. Road erosion occurs when soil particles are loosened and carried from the roadway, ditch or road bank by water, wind, or traffic.

The water use classifications of fishing, recreation, and drinking water are potentially threatened in waterbodies by erosion and loading of sediment which can alter stream morphology, impact habitat, and reduce water clarity. Potential sources include urban runoff and development (particularly construction), unpaved rural roads, forestry practices, and agriculture. In 2002, GA EPD did not identify any stream segments in any Satilla River subbasin, including the Seventeen Mile River watershed, that had sediment loading concerns.<sup>12</sup>

However, the WAC indicated sediment contamination concerns with unpaved roads that cross the river or are near the river's edge. There has been little water quality testing for turbidity and total suspended solids (TSS) in the watershed. To confirm the validity of this concern and degree of contamination, regular turbidity and TSS monitoring is required. Regardless whether there is monitoring, the counties can implement the guidelines presented in Georgia Better Back Roads Field Manual available at

http://www.tworiversrcd.org/forms/Georgia%20Better%20Back%20Roads%20Field%20Manual%20fi nal.pdf. The manual presents "better" practices that reduce or eliminate contamination from unpaved roads.

#### <u>Stormwater</u>

Stormwater is a leading cause of water pollution. It runs off solid surfaces and collects pollutants such as oil, pesticides, sediments, bacteria, and other chemicals, and then deposits them into our waterways thus degrading water quality. Flooding increases as impervious surfaces replace natural vegetation, because water is unable to slowly filter into the landscape.

<sup>&</sup>lt;sup>12</sup> Satilla River Basin Management Plan 2002, Georgia Department of Natural Resources, Environmental Protection Division, p.6-3.

Stormwater deposits sediment that decreases the depth of waterways, further increasing flooding. During storms, these pollutants are washed off and drain to storm drains and then directly into streams, rivers and lakes. Pollutant levels are typically much higher in the first inch of runoff, commonly referred to as the "first flush." Some studies have found that approximately 90% of the pollutant loading is contained in the "first flush" of a one-inch rainfall. Therefore, effective water quality protection requires the treatment of the "first flush" through the use of various preventive and control measures. The Center for Watershed Protection's research has demonstrated that as little as eight percent impervious coverage of a watershed can result in degradation of the water quality. At 25% impervious coverage, the waterways have lost most of their biological diversity and have significant impairments. A two-acre single home lot has about 12% impervious cover and a shopping center has over 90% impervious cover. Although low-density development reduces impervious surfaces in that area it leads to increased impervious surfaces elsewhere, because of more roads and parking that sprawling development requires. Roads and parking lots can account for more than 60% of a low-density development's impervious area. Although large lawns might seem capable of absorbing runoff from adjacent surfaces, they are typically compacted by construction equipment and can generate up to 90% as much runoff as pavement.

Douglas' system is partially mapped and the city is in the process of developing a Storm Discharge Master Plan. The city's current storm water management ordinance establishes minimum stormwater management requirements for land development projects and promotes traditional structural management to capture and treat stormwater.<sup>13</sup> The ordinance does not provide for green infrastructure, development practices that can reduce stormwater and its impact on watershed streams and rivers.

Green infrastructure is a cost-effective, resilient approach to managing wet weather impacts that provides many community benefits. While single-purpose gray stormwater infrastructure—conventional piped drainage and water treatment systems—is designed to move urban stormwater away from the built environment, green infrastructure reduces and treats stormwater at its source while delivering environmental, social, and economic benefits.

### Waterbody and Watershed Conditions

#### Visual Survey

A visual survey of the Seventeen Mile River watershed was conducted March 24, 2017.

The purpose of a visual survey is to determine if there are observable problems in the river and streams and to characterize the environment through which the river flows. The visual survey helps pinpoint areas that may be the source of water quality impairments and determine the overall condition of the stream. Results of the visual survey did not indicate any obvious source(s) of water quality impairment.

<sup>&</sup>lt;sup>13</sup> Unified Land Development Code, Chapter 6.

Throughout the watershed, most of the stream channels are shady with occasional open areas adjacent to bridge or road crossings. Additionally, there was one area observed at the Douglas Country Club where there is no buffer and managed turf extends to the river's edge. Otherwise, vegetative buffers adjacent to the stream meet the state-mandated standard, 25', and in most cases, are much wider.

### Water Quality Monitoring Data

Extensive water quality monitoring has been conducted for pH, dissolved oxygen (DO), and fecal coliform at three stations in the watershed; Otter Creek at Georgia Highway 32 (2010), Seventeen Mile River at Georgia Highway 158 (2003), and Seventeen Mile River at Georgia Highway 64 (1991 – 2010). Additionally, the Seven Rivers RC&D conducted water quality monitoring at the following six sites in the watershed during the period June – October 2017. Parameters measured were e-coli, dissolved oxygen, pH, and conductivity at the following sites:

- ! Seventeen Mile River at Hwy 135
- ! Otter Creek at Sand Hill Church Road
- ! Otter Creek at Hwy 32
- ! Twentynine Mile Creek at Raccoon Bridge Road
- ! Seventeen Mile River at Highway 64
- ! Seventeen Mile River at Taylor Church Road

Following, is information on each parameter monitored and its general impact on water quality.

! DO – Potential point source affecting in-stream DO concentrations includes wastewater treatment plants, industrial facilities, combined sewer overflows, sanitary sewer overflows, and stormwater runoff.

Nonpoint sources of oxygen demanding substances are separated into urban and rural components. In urban settings, potential loading sources are stormwater runoff, failing septic systems, and leakage and overflows from sanitary sewer systems. In rural areas potential sources may include diffuse runoff of agricultural fertilizer and animal wastes (from manure application or grazing animals), erosion of sediments, and runoff from concentrated animal operations.

The relationship between dissolved oxygen and water temperature is critical for aquatic life in a stream, river or lake. More dissolved oxygen is present in water with a lower temperature compared to water with a higher temperature. DO levels below 3 ppm are stressful to most aquatic organisms. DO levels below 2 or 1 ppm will not support fish; levels of 5 to 6 ppm are usually required for growth and activity.

State standard is an average of 5.0 mg/l and no less than 4.0 mg/l at all times.

- pH In Georgia streams, pH ranges between 6.5 and 8.2 though black-water streams can be found as low as 3.5 mg/l. Temperature has a measurable yet very slight effect on the pH of water. As the water temperature increases, pH value decreases. The converse is also true: colder water has a higher pH value.
- Fecal coliform Georgia's water quality standards set a maximum number of 200 colonies per 100 milliliters of water from May through October, or 1000 colonies per 100 milliliters from November through April. Values in excess are in violation of the State bacteria water quality standard. In addition, a single sample in excess of 4000 colonies per 100 milliliters from November through April or a single sample in excess of 4000 colonies per 100 milliliters from May through October.
- I Turbidity and Total Suspended Solids (TSS) Turbidity and Total Suspended Solids (TSS) Total suspended solids (TSS) concentrations and turbidity both indicate the amount of solids suspended in the water, whether mineral (e.g., soil particles) or organic (e.g., algae). However, the TSS test measures an actual weight of material per volume of water, while turbidity measures the amount of light scattered by particles of dirt or organic matter floating in a sample (more suspended particles cause greater scattering). Measuring TSS and turbidity is valuable since high readings can be used as "indicators" of other potential pollutants. Additionally, concentrations of particulate matter can cause increased sedimentation and siltation in a stream, which in turn can ruin important habitat areas for fish and other aquatic life as well as impact recreational values (fishing, boating, swimming) in a waterbody.

Turbidity - In general, a turbidity reading below 5 NTU appears clear, while a reading of 55 NTU will start to look cloudy and a reading over 500 NTU will appear completely opaque.<sup>14</sup> During the monitoring period turbidity was below 8.0 NTU thus confirming that sediment is not presently a contaminant of concern in the watershed.

TSS (Total Suspended Solids) - Georgia has no numerical standard for turbidity but instead requires "All watersheds shall be free from material related to municipal, industrial or other discharges which produce turbidity, color, odor or other objectionable conditions which interfere with legitimate water uses.<sup>15</sup> A TSS concentration below 20 mg/L appears clear, while levels over 40 mg/L may begin to appear cloudy.

Biological Oxygen Demand (BOD) - Biological oxygen demand is a measure of the quantity of oxygen used by microorganisms (e.g., aerobic bacteria) in the oxidation of organic matter. Natural sources of organic matter include plant decay and leaf fall. However, plant growth and decay may be unnaturally accelerated when nutrients and sunlight are overly abundant due to human influence. Urban runoff carries pet wastes from streets and sidewalks; nutrients from lawn fertilizers; leaves, grass clippings, and paper from residential areas, which increase oxygen demand. When BOD levels are high, dissolved oxygen (DO) levels decrease because the oxygen that is available in the water is being consumed by the bacteria. Since less dissolved oxygen is

<sup>&</sup>lt;sup>14</sup> Turbidity, Total Suspended Solids and Water Clarity." Fundamentals of Environmental Measurements. Fondriest Environmental, 13 Jun. 2014.

<sup>&</sup>lt;sup>15</sup> Water Use Classification and Water Quality Standards, §391–3-6-.03.

available in the water, fish and other aquatic organisms may not survive. A BOD level of 1-2 ppm indicates very good water quality and there will not be much organic waste present in the water supply. A level of 3-5 indicates fair (moderately clean) water quality.

#### Otter Creek at Highway 32

Based on EPD-collected water quality data obtained from February through July, 2010, Otter Creek was determined to support its designated use of fishing. Data indicate the following:

- DO DO was within acceptable parameters during the sample period.
- pH Of the eleven samples events, pH was low only three times. In each case water temperature had increased and this was likely due to an increase in water temperature from the previous sampling event.
- Fecal coliform Samples were collected in March and April. Geometric mean was 132 colonies/100 mL and 171 colonies/100mL respectively, well below both the State summer and standard.
- During the monitoring period, TSS ranged from 4.4 10 mg/L indicating little sediment contamination. The volume of suspended solids generally correlates to the amount of rain received. No rain was received during the monitoring period.
- BOD levels measured during the sampling period indicate generally very good water quality.

#### Seventeen Mile River at Georgia Highway 158 and Georgia Highway 64

Water quality data is available for two monitoring stations location along the supporting stream segment; Seventeen Mile River at Highway 158 and Seventeen Mile River at Highway 64. EPD-collected water quality data was obtained in 2003 at Highway 158, and from 1991 - 2010 at Highway 64. In 2006, based on this data, the segment of Seventeen Mile River from Otter Creek to its confluence with Twentynine Mile Creek was determined to support its designated use of fishing in. Data indicate the following:

- DO DO fluctuated throughout the monitoring period with generally higher levels during the winter months. However, overall water quality data indicates that DO was within acceptable parameters during the sample period and met the State standard.
- pH pH was within acceptable limits throughout the sampling period.
- Fecal coliform Over a ten-year sampling period, only three times did the geometric mean exceed state standards and two were marginally above the standard. Generally, geometric mean was well-below the state standard.

#### Seventeen Mile River at Highway 135

DO met State standard.

Fecal coliform counts exceeded state standards 150 % to 233 % three out of the four months sampled during a period of no rainfall. This site is influenced by stormwater runoff and human activities from the Douglas' urbanized area including the Douglas County Club. Additionally, while much of the urbanized area is served by public sewer, the residential and commercial area in north-east Douglas

bounded by Highway 135 and the Seventeen Mile River are served by individual septic systems. Although non-point source pollution has a significant effect on bacterial levels in runoff water and in water resources, this effect would be the result of factors other than just rainfall.

The WAC noted concerns with operations upstream of this sampling point but outside the watershed that may contribute to contamination at this monitoring location.

Likely contamination sources:

- ! Failing/leaking septic tanks.
- ! Stormwater runoff.
- ! Facilities upstream of sampling point but outside the watershed.

#### Seventeen Mile River at Highway 32

DO and pH were within acceptable parameters.

Fecal coliform counts were elevated at each sampling event and three of the four sampling event counts were consistent with elevated counts upstream at Seventeen Mile River at Highway 135. This creek segment flows entirely through forested land though likely receives some runoff from residential and commercial development around Highway 135. Wildlife could also account for some of the elevated counts.

Likely contamination sources:

- ! Failing/leaking septic tanks
- ! Stormwater runoff from the Douglas urbanized area,
- ! Wildlife.

#### Otter Creek at Sand Hill Church Road

This sampling site is just below the confluence of Otter and Tiger creeks. The segment of Otter Creek below its confluence with Tiger Creek is identified as a supporting segment. RC&D sampling in June and August demonstrated fecal coliform counts exceeded state standards 844 percent and 97 percent, respectively. Dissolved oxygen and pH were within acceptable parameters.

Without further water quality testing, it is difficult to determine the potential source of the fecal coliform contamination or whether the fecal coliform spikes are indicative of ongoing non-point source contamination. However, both Otter and Tiger creeks are similarly developed with agriculture and forest uses though the Tiger Creek subwatershed has more agricultural ponds in addition to residential areas on Hill Road and Haley Court, that are adjacent to the stream. Homes in these subdivision are served by individual septic systems and could be a possible source of the contamination.

Likely contamination sources:

- ! Leaking/failing septic systems
- ! Agricultural uses.

#### Twentynine Mile Creek at Raccoon Bridge Road

Twentynine Mile Creek has not been previously monitored but was selected for monitoring due to the large-scale agriculture uses in the subwatershed as well as its confluence at the mostdownstream point of the supporting segment of Seventeen Mile River.

Dissolved oxygen levels were below 2.0 ppm three of the four months sampled with a four-month average of 2.15 ppm. A low dissolved oxygen level indicates a demand on the oxygen in the system. Low dissolved oxygen (DO) primarily results from excessive algae growth caused by phosphorus. Phosphorus is a common constituent of agricultural fertilizers, manure, and organic wastes in sewage and industrial effluent. Nitrogen is another nutrient that can contribute to algae growth. As the algae die and decompose, the process consumes dissolved oxygen. This can result in insufficient amounts of dissolved oxygen available for fish and other aquatic life. Die-off and decomposition of submerged plants also contribute to low dissolved oxygen. Sources of phosphorus include discharges from municipal and private wastewater treatment, cropland, urban storm water runoff, and natural decay of vegetation.

Fecal coliform counts were above state standard two of the four months monitored. July's count was 566 percent above state standard, and October's, 150 percent. pH levels were within acceptable range.

Likely contamination sources:

- ! Agricultural uses, particularly cattle operations where dry poultry litter is spread on fields.
- ! Leaking/failing septic tanks.

#### Seventeen Mile River at Highway 64

This site was monitored by both GA EPD from 1991 - 2010 and the RC&D in 2017. Dissolved oxygen and pH were within acceptable range. During both monitoring periods, the fecal coliform geometric mean exceeded State standard only once.

Land in this portion of the watershed is primarily forest, with some agriculture but extensive vegetated buffers or 1,000 feet or greater.

#### Seventeen Mile River at Taylor Church Road

This segment was first monitored in 2017 by the RC&D. Dissolved oxygen and pH are within acceptable limits though fecal coliform counts were elevated in June and July, above state standard by 38 percent and 205 percent, respectively. The potential source of the two spikes are unknown as this portion of the watershed is mostly forested and buffers are extensive, generally 1,000 feet or greater though there is some agricultural use and associated ponds that could potentially contribute to contamination. Further monitoring of this site is recommended to better determine water quality concerns, if any. If trends show fecal colifom consistently above State standard, installation of Agricultural BMPs should be pursued, as appropriate.

Likely contamination sources:

Possibly agricultural uses though additional monitoring is recommended as a first step.

### Healthy Watersheds

GA EPD identifies Otter Creek and Seventeen Mile River from Otter Creek to Twenty-nine Mile Creek as Category 1 streams indicating that they are meeting water quality standards and are therefore, healthy watersheds. As such, steps should be taken locally to insure that water quality in the healthy watershed is not degraded by human activity.

US EPA defines a healthy watershed as a watershed where structure and function are in place to support healthy aquatic ecosystems. Key components of a healthy watershed include:

- ! intact and functioning headwater streams, floodplains, riparian corridors, instream habitat, and biotic communities;
- ! natural vegetation in the landscape; and
- ! hydrology, sediment transport, fluvial geomorphology, and disturbance regimes expected for its location.

The systems approach to healthy watersheds assessment and protection is based on an integrated evaluation of:

- ! Landscape Condition
- ! Habitat
- ! Hydrology
- ! Geomorphology
- ! Water Quality
- ! Biological Condition.

Ecological processes and natural disturbance regimes are addressed in the context of these six components.

Landscape Condition – Landscape condition assessments examine the condition and configuration of natural land cover in the landscape. Natural vegetative cover stabilizes soil, regulates watershed hydrology and provides habitat to terrestrial and riparian species. The type, quantity, and structure of the natural vegetation within a watershed have important influences on aquatic habitats. Natural land cover provides connectivity among riparian habitats and between terrestrial and aquatic ecosystems.

Many aquatic organisms depend on being able to move through connected systems to habitats in response to variable environmental conditions. Forested riparian zones are often some of the best remaining corridors for connecting habitat patches on the landscape. Vegetated landscapes cycle nutrients, retain sediments, and regulate surface and ground water hydrology. Natural disturbances on the landscape, such as fire, help to regulate nutrient and organic matter input to aquatic ecosystems.

Habitat – Freshwater habitats are comprised of flowing (i.e., streams and rivers) and standing (i.e., lakes, ponds, and wetlands) waters. Habitat extent and quality are directly related to landscape condition and hydrologic and geomorphic processes. Habitat quality is also affected by the physical and chemical characteristics of the water (e.g., water temperature). The number and distribution of different habitat types and their connectivity influence species population health.

*Geomorphology* – Watershed inputs (water, sediment and organic matter) and valley characteristics (valley slope and width, bedrock and surficial geology, soils and vegetation) determine a river channel's form (pattern, profile and dimension). Although watershed inputs and channel form vary over time, they are balanced in natural systems. This natural balance is termed "dynamic equilibrium" and refers to sediment size and volume being in balance with stream slope and discharge.

Any time one of these variables changes, the other variables will respond to bring the stream back to a dynamic equilibrium. Disturbances such as floods or forest fires are natural, episodic events that cause a stream to become unbalanced. After such disturbances, the stream will "seek" equilibrium conditions through adjustment of the other components until the stream is once again in a form that allows it to efficiently perform its functions of water and sediment discharge.

These periodic disturbances, of natural intensity and frequency, can increase aquatic biodiversity by creating opportunities for some species and scaling back the prevalence of others. When disturbances are of extreme intensity or frequency, as many human disturbances are, a stream channel will undergo adjustment to a new form. This can result in habitat degradation and threats to public safety and infrastructure.

*Hydrology* – Watershed hydrology is driven by climatic processes; surface and subsurface characteristics such as topography, vegetation, and geology and human activities such as water and land use. Aquatic ecosystems are dependent on surface and/or ground water hydrology. For example, groundwater-dependent ecosystems rely on water that infiltrates to the subsurface discharging to nearby streams or recharging to an aquifer and then discharging to springs, seeps, wetlands, streams, and lakes.

Hydrologic regimes (flows in rivers and water levels in lakes and wetlands) create habitat and are important to aquatic species life histories (e.g., providing cues for spawning and migration during discrete times of the year). Natural flow regimes are composed of seasonally varying environmental flow components, including high flows, base flows, pulses and floods that can be characterized in terms of their magnitude, frequency, duration, timing and rate of change. Natural lake levels will vary depending on precipitation, evaporation and/or ground and surface water hydrology.

*Water Quality* – Aquatic ecosystems are substantially affected by the quality of their water, but also by the chemical and physical characteristics of the air, surrounding watershed soils and sediment transported through the aquatic system. EPA and states have established water quality criteria for freshwater ecosystems that address important ecological constituents. Chemical and physical constituents include:

- concentrations of organic and inorganic constituents, such as nutrients, trace metals and dissolved organic matter;
- additional chemical parameters indicative of habitat suitability, such as pH and dissolved oxygen; and
- physical parameters, including water temperature and turbidity.

Many of these parameters are dynamic and related to natural watershed processes. For example, dissolved oxygen fluctuations in streams are related to nutrient cycling, biotic activity, stream flow and temperature.

*Biological Condition* – Freshwater aquatic biodiversity refers to the richness of native species (e.g., fish, invertebrates and plants), genetic variety, and multiple habitats and ecosystems types (e.g., lakes, ponds, and reservoirs, rivers and streams, groundwater and wetlands). The biological condition of an aquatic ecosystem is often thought of as the ultimate indicator of watershed health, as aquatic organisms and communities reflect the cumulative conditions of all other watershed components.

Biological condition is measured in a variety of ways. For example, multimetric indices measure the presence, numbers and condition of aquatic organisms and communities in an aquatic ecosystem. They are intended to represent the biological condition of an aquatic ecosystem relative to some regionally-defined reference condition. RIVPACS (River Invertebrate Prediction and Classification System) models quantify biological condition by comparing the observed (O) taxa at a site to expected (E) taxa in the absence of human-caused stress. The O/E ratio is the index of biological integrity and measures loss of native taxa or biodiversity. Biodiversity is also measured by presence of rare, threatened and endangered (RTE) species. State natural heritage programs have inventories of aquatic RTE.

The US Environmental Protection Agency Office of Water's Healthy Watersheds Program (HWP) develops assessments of watershed health and vulnerability to support states' efforts to identify and protect watersheds that are in good condition. During 2016, the HWP assessed the health and vulnerability of small scale watersheds (HUC-12, averaging 36 sq mi in area) in each of the conterminous 48 states. This Preliminary Healthy Watersheds Assessment (PHWA) followed an established HWP assessment methodology adapted for the HUC-12 scale and the use of nationally consistent indicator data.

Georgia's Preliminary Healthy Watersheds Assessment (PHWA) assessed HUC-12 watersheds at both the statewide and ecoregional scale, resulting in paired Watershed Health and Watershed Vulnerability scores per HUC12 watershed (i.e., one set of statewide scores and one set of ecoregional scores per watershed). Together, these scores provide insights on a watershed's condition relative to others within the state, as well as those watersheds sharing similar ecological characteristics across the ecoregion.

Statewide and ecoregional index scores are presented as both raw scores ("Score", between 0 and 1) and percentiles (0 to 100%).
The 2016 Preliminary Healthy Watershed Assessment (PHWA) Watershed Index Survey for Otter Creek provided the following:

PHWA Watershed	WATERSHED HEALTH INDEX				WATERSHED VULNERABILITY INDEX			
Index Summary	STA	ATEWIDE ECOREGIONAL		EGIONAL	STATEWIDE		ECOREGIONAL	
	Score	Percentile	Score	Percentile	Score	Percentile	Score	Percentile
Otter Creek	0.68	50.1	0.67	28.9	0.31	61.5	0.29	64.1

Relative to other HUC-12 watersheds in the state, as well as those watersheds sharing similar ecological characteristics across the ecoregion, Otter Creek ranks in the middle, statewide, and approximately in the upper 25 percentile its ecoregion for watershed health. Otter Creek's potential for future degredation or vulnerability index is in the 60<sup>th</sup> percentile statewide, and 64<sup>th</sup> percentile for its ecoregion meaning that it is at some risk for degradation. (The higher the percentile, the greater the risk, comparatively, for degradation.)

The Otter Creek HUC-12 watershed (headwaters to its confluence with Seventeen Mile River) is comprised Otter Creek, a second-order stream, and several tributaries, including Tiger Creek. The HUC-12 watershed evidences limited, low-density disturbance, primarily forestry and agricultural (crops/pasture). Vegetative buffers tend to be heavily wooded and extensive, generally exceeding 200' on each side of the creek banks. Residential and commercial uses are scattered, low-density, and typically well outside the vegetive buffers. Particularly, in the lower half of the stream, extensive inter-connected wetlands are situated adjacent to the Creek. Overall, this is a relatively undisturbed watershed. Lack of disturbance coupled with an absence of merging degraded streams largely accounts for its health. However, 2017 monitoring data indicates that development in the adjacent Tiger Creek HUC-12 may be impacting the water quality of the downstream portion of Otter Creek.

Future land use in this HUC-12 watershed anticipates that the primary land use will continue to be agriculture/silviculture with only scattered residential development through 2027. Lack of intense development coupled with Coffee County's ordinances should allow the subwatershed to remain healthy for the foreseeable future. However, continued water quality monitoring is recommended, particularly on Tiger Creek above its confluence with Otter Creek.

The Seventeen Mile River supporting segment subwatershed, upstream of its confluence with Twentynine Mile Creek, is a third-order stream with several first- and second-order tributaries. The watershed evidences limited, low-density disturbance, primarily forestry and agricultural (crops/pasture), and one large-scale poultry operation. Vegetative buffers tend to be heavily wooded and extensive, generally exceeding 300' on each side of the river's banks. With the exception of a residential area south of Highway 158, residential and commercial uses are scattered, low-density, and typically well outside the vegetive buffers. Extensive inter-connected wetlands are situated adjacent to the River. Overall, this is a relatively undisturbed watershed and future land use through 2027 indicates this subwatershed will see little additional development. Lack of disturbance coupled with an absence of degraded tributaries and Coffee County's development ordinances largely account for its designation as a healthy watershed.

No PHWA index survey has been completed for Seventeen Mile River segment above Twentynine Mile Creek.

Seventeen Mile River Watershed Management Plan, May 2018

### Land Management Ordinances and Activities

A suite of land management ordinances are used by jurisdictions in the watershed, though ordinances are only as effective as their enforcement. Coffee and Jeff Davis counties, as well as the City of Douglas, have a number of ordinances that indirectly address water quality though development and infrastructure siting restrictions. A number of ordinances are model ordinances developed by the State of Georgia and require stream buffers, protection of wetlands, larger lot sizes in groundwater recharge areas where there is no public sewer, regulating land-disturbing activities, etc.

The portion of the watershed most affected by current and future development is located in Douglas and Coffee County.

Douglas has a number of ordinances that apply to land development, either directly or indirectly, and five that specifically facilitate water quality; soil erosion and sedimentation, river corridor protection, stormwater management, unified land development code, and wetlands protection. The river corridor protection ordinance mandates a 100 foot natural vegetative buffer on each side of the river and prohibits construction within the buffer. All ordinances, except the unified land development code are State-mandated model codes and can be effective provided there is adequate review, inspection, and enforcement. The unified land development code permits pervious pavement which allows stormwater to infiltrate the soil rather than simply running off the hard surface. The code also permits planned development in order to provide "natural features and open spaces" though neither term is defined nor quantified so it is difficult to assess its impact on water quality.

Recommendation:

- ! Update the unified land development code to define natural features and open spaces and provide guidance on how to prioritize for conservation.
- Require green infrastructure as a method to handle stormwater in new development and opportunities to retrofit older development. Green infrastructure is an approach to water management that protects, restores, or mimics the natural water cycle thus reducing the impact of stormwater on streams. In particular, the WP advised that the proposed Wal-Mart Distribution Facility would be an excellent development to utilize green infrastructure.

Coffee County has a number of ordinances that apply to land development, either directly or indirectly, and four that specifically facilitate water quality; soil erosion and sedimentation, groundwater recharge, wellhead, and wetlands protection. All ordinances, except the unified land development code are State-mandated model codes and can be effective provided there is adequate review, inspection, and enforcement. Chapter 6 of the Land Development Code notes the chapter's purpose is to protect natural resources in Coffee County and to implement policies in the comprehensive plan, and specifically states that Chapter 6 includes protection for groundwater recharge areas and river corridors. The Comprehensive Plan was amended to include river corridor protection but no ordinance has been adopted to implement protection.

The Seventeen Mile River is not listed as a "protected river" by GA DNR thus there is no requirement that the County require a 100 foot buffer along the river. The State-mandated minimum river buffer is 25 feet and concern has been expressed by the WAC that the 100 foot buffer recommended in the Coffee County Comprehensive Plan is not feasible on agricultural properties due to economic loss. At present, buffer depth is not a cause of contamination as most buffers far exceed 100 feet.

Recommendation:

! The Land Development Code requires set aside of 25% of development as open space in Planned Development though there are no guidelines for determining what constitutes open space. To best benefit water quality, open space should be undeveloped. Update the Land Development Code to define provide guidance for identifying and prioritizing open spaces for conservation.

Seventeen Mile River W	atershed Land Management Ordinances (2017)
ATKINSON COUNTY	
Regulation/Ordinance	Description
Flood Damage Prevention	Establishes minimum requirements effecting land-disturbing activities. Does not address water quality. NOTE: Ga EPD is the Local Issuing Authority meaning EPD has responsibility for enforcing ordinance.
COFFEE COUNTY	
Regulation/Ordinance	Description
Flood Damage Prevention	Establishes minimum standards for new construction in flood hazard areas to reduce damage from flooding. Does not address water quality.
Groundwater Recharge	Included as Chapter 6 of Land Development Code. Regulates development in groundwater recharge areas, as mapped on Georgia Hydrologic Atlas #18, for the purpose of protection public drinking water. Specifically places restrictions on septic tanks, drain fields; and spray fields; provides minimum sizes for lots requiring septic systems; and controls on landfills, above-ground chemical or petroleum tanks, agricultural waste lagoons, and certain other hazardous waste land uses. Addresses water quality.
Land Develoipment Code	Provides development design and improvement standards to ensure functional and attractive development. Includes standards for Planned Development which requires set aside of 25% of development as open space. Does not address water quality. Note: Chapter 6 for the Land Development Code notes the chapter's purpose is to protect natural resources in Coffee County and to implement policies in the comprehensive plan, and specifically states that Chapter 6 includes protection for groundwater recharge areas and river corridors. The Comprehensive Plan was amended to include river corridor protection but no ordinance has been adopted to implement protection.
Soil Erosion and Sedimentation Control Ordinance	Establishes minimum requirements effecting land-disturbing activities. Addresses water quality.
Wellhead Protections	Establishes a wellhead protection zone, 100 foot radius from center of well, surrounding the wellheads for all wells which are supply sources for the County water system. Addresses water quality.
Wetlands Protection	Wetlands Protection District adopted as component of County development regulations protecting wetlands from most types of development. Addresses water quality. NOTE: Comprehensive Plan Community Assessment 2007 notes that limited code enformcement suggests the County's wetlands may be at risk for increased housing subdivision development. Protecting existing wetlands is crucial to preserving the County's water sources especially as greater development occurs.

IEFF DAVIS COUNTY			
Regulation/Ordinance	Description		
Flood Damage Prevention	Establishes minimum standards for new construction in flood hazard areas to reduce damage from flooding. Does not address water quality.		
Soil Erosion and Sedimentation Control	Establishes minimum requirements effecting land-disturbing activities. Addresses water quality.		
Groundwater Recharge	Included as Chapter 36, Article IV, Division 2 of the Code of Ordinances. Regulates development in groundwater recharge areas, as mapped on Georgia Hydrologic Atlas #18, for the purpose of protection public drinking water. Specifically places restrictions on septic tanks, drain fields; and spray fields; provides minimum sizes for lots requiring septic systems; and controls on landfills, above-ground chemical or petroleum tanks, agricultural waste lagoons, and certain other hazardous waste land uses. Addresses water quality.		
Major River Corridor Protecton	Included as Chapter 36, Article IV, Division 2 of the Code of Ordinances. Established a river corridor protection area of 100' on each side of the river from the top of the river bank; requires 100' natural vegetative buffer on each side of river and prohbits construction within buffer. Addresses water quality.		
Wetlands Protection	Included as Chapter 36, Article IV, Division 2 of the Code of Ordinances. Protecting wetlands from most types of development. Addresses water quality.		
WARE COUNTY			
Regulation/Ordinance	Description		
Soil Erosion and Sedimentation Control	Establishes minimum requirements effecting land-disturbing activities. Addresses water quality.		
Wellhead Protections	Establishes a wellhead protection zone, 100 foot radius from center of well, surrounding the wellheads for all wells which are supply sources for the County water system. Addresses water quality.		

CITY OF DOUGLAS			
Regulation/Ordinance	Description		
Flood Damage Prevention	Establishes minimum standards for new construction in flood hazard areas to reduce damage from flooding. Does not address water quality.		
River Corridor Protection	Established a river corridor protection area of 150' on each side of the river from the top of the river bank; requires 100' natural vegetative buffer on each side of river and prohbits construction within buffer. Addresses water quality.		
Soil Erosion and Sedimentation Control	Establishes minimum requirements effecting land-disturbing activities. Addresses water quality.		
Stormwater Management	Regulates stormwater runoff from activity causing an increase on stormwater runoff for the purpose of protecting local water resources from degradation. Addresses water quality.		
Tree Ordinance	Provide for preservation and maintenance of trees on public lands and in the public rights-of-way. Requires tree protection during development.		
Unified Land Development Code	1) Provides for limit on impervious surface coverage by zoning category. 2) Allows use of pervious concrete. 3) Allows Planned Development with stated purpose for development to provide "natural features and open spaces" though neither a defined nor quantified. 4) Requires preservation of trees at least 6" dbh and historic trees (trees that have achieved 50 percent or more of the typical DBH for that species); applies to all development except single- family, manufactured homes not located in a manufactured home park, and bona fide agricultural uses and operations. Address water quality in some sections of Code.		
Wetlands Protection	Wetlands Protection District adopted as component of County development regulations protecting wetlands from most types of development. Addresses water quality.		
STATEWIDE			
Regulation/Ordinance	Description		
On-Site Sewage Management Systems	Rules established by the Georgia Department of Public Health. Applies to all on- site sewage management systems except those under the jurisdiction of and regulated by GA DNR, as well as any public or community sewage treatment system.		

# **VI. Recommended Management Practices**

Previous watershed studies identified fecal coliform and dissolved oxygen as parameters of concern in the non-supporting stream segments. Seventeen Mile River non-supporting stream segments appear to regularly meet standards for DO and are within acceptable parameters for pH. Based on historical and current sampling data, fecal coliform continues to be the contaminant of concern in the non-supporting segments. Additionally, current water quality data indicate DO and fecal coliform are contaminants of concern in the Twentynine Mile Creek subwatershed. Primary sources of likely fecal coliform pollution and low DO were identified as agricultural runoff, leaking failing septic systems, and urban runoff. WPCP spills, while somewhat frequent, appear to only have a very short-term impact on the Seventeen Mile River.

Watershed implementation priorities are:

- ! upgrades to the Douglas WPCP;
- ! repair and replacement of leaking/failing septic systems;
- ! implementation of Agricultural BMPs to address agricultural runoff particularly in the Twentynine Mile Creek and Tiger/Otter Creek subwatershed;
- ! ordinance updates; and,
- ! implementation of green infrastructure in Douglas and better management of stormwater.

The suite of potential structural and non-structural management practices identified to control the above-listed pollutant loadings are:

- ! agricultural best management practices;
- ! individual septic system repair/replacement;
- ! continued upgrades to the Douglas WPCP and sewerage system;
- ! completion and implementation of stormwater master plan; and,
- ! implementation of green infrastructure structural management to capture and treat stormwater runoff before it is discharged into streams.

The following screening criteria will be used to evaluate the suitability of a potential management practice: (Criteria are listed in descending order of importance).

- Priority Area Will the management practice be implemented effectively within the identified critical areas in the watershed?
- ! Load Reduction Will the management practice provide a significant load reduction?
- ! Ease of Implementation Will the implementation of the management practice be easy to undertake (potential legal issues, permits, etc.)
- ! Maintenance What level of maintenance is required for the practice to function optimally?
- ! Cost Effectiveness Is the practice cost-effective when compared to its impact on contamination?
- ! Unintended Impacts/Added benefits Are the any unintended impacts or added benefits that result from installation of the management practice?
- ! Social Acceptance Will the practice have public support?

## **Recommended Management Practice Effectiveness**

#### Agriculture

The implementation of systems of BMPs reduces nonpoint source pollution. BMPs are defined as structural, vegetative, or managerial conservation practices which reduce or prevent detachment, transport and delivery of nonpoint source pollutants to surface or ground waters. The BMPs result in fewer nutrients and waste being delivered to the water bodies.

The BMPs in a water quality project must be targeted to priority agriculture properties within the watershed (i.e., those that contribute runoff to adjacent hydrologic systems such as lakes, streams, ditches, wetlands and flood plains). Additional priority areas are feedlots, water storage systems, and waste management systems. Reporting of specific pollutant load reductions will be calculated for all properties where new BMPs are installed; however, a general estimated load reduction, by installed practice, is provided below to assist with the suitability evaluation of a management practice.

Agri	Agricultural Best Management Practices to Address Non-Point Source Pollution					
Practice	Practice Name	Fecal	Estimated Load	Cost*		
Number		Coliform	Reduction	0001		
313	Waste Storage Facility	Μ	96%	medium - high		
316	Animal Mortality Facility	Μ	Products from composting facilities can be incorporated into the soil and improve agronomic conditions and can also be used a part of a nutrient management plan.	moderate – high		
317	Composting Facility	Μ	70-80%	medium - high		
329, 345, 346	Conservation Tillage	М	up to 70%	varies by scope of project		
330	Contour Farming	Μ	25-50%	low		
332	Contour Buffer Strip	Μ	20-75%	low		
340	Cover Crop		40-60%	low		
342	Critical Area Planting	М	75%	high		
359	Waste Treatment Lagoon	М	80%	moderate - high		
360	Waste Facility Closure	М	reduces likelihood of residual nutrients entering water.	high – depends on scope of project		
365	Anerobic Digester - Ambient Temperature	М	90-99%	high. Requires maintenance.		
366	Anerobic Digester - Controlled Temperature	М	90-99%	high. Requires maintenance.		
367	Waste Facility Cover	М	protect integrity and capacity of storage facility and reduce overflow.	high		
382	Fence	Μ	50 - 90% in higher order streams, 99% in second order streams	low		
390	Riparian Herbaceous Cover	М	50-75%	low - moderate		
391	Riparian Forest Buffer	Μ	50-75%	moderate		
393	Filter Strip	М	50-80%	moderate, maintenance required		
472	Access Control	Μ	50 - 90% in higher order streams, 99% in second order streams	low - moderate		

Agri	Agricultural Best Management Practices to Address Non-Point Source Pollution					
Practice Number	Practice Name	Fecal Coliform	Estimated Load Reduction	Cost*		
516	Pipeline - Livestock	Μ	As part of an alternative water supply or a waste management system, pipelines indirectly reduce negative water quality impacts.	moderate		
528	Prescribed Grazing		75%	low		
578	Stream Crossing	Μ	Stream crossings reduce animal access, provide stable traffic paths and reduce the amount of nutrients and sediment entering water.	medium - high. Best to redirect around stream.		
586	Field Stripcropping	Μ	75%	low		
590	Nutrient Management	Μ	35% P, 15% N	low - moderate		
606	Tree & Shrub Establishment	М	50%	low - moderate		
634	Waste Transfer	М	promote nutrient reduction in soil	moderate		
635	Vegetated Treatment Area	М	80 - 90% in feedlots	low		
642	Water Well	Μ	No available information	varies by scope of project		

Source: Best Management Practices for Georgia Agriculture, Georgia Soil and Water Conservation Comm., Sept 2013.

\*For additional information on Practice Number costs, see Appendix, Georgia FY 2017 EQIP Policy.

#### Sanitary Sewerage System

Continue with planned upgrades to the Douglas WPCP and sewerage system.

#### Individual Septic System

Coordinate between the Coffee County Code Enforcement and Coffee County Health Department to identify and assist users of septic systems with maintenance issues though septic repair, replacement, pump-out, and/or education.

#### Stormwater System

Complete and implement Douglas stormwater master plan. Include green infrastructure in plan and associated ordinances. Install green infrastructure in new development and retrofit old development.

There are a variety of practices Douglas can implement to mitigate the impact of stormwater on water quality. These practices would be beneficial in new development and as a retrofit in older development.

Typical practices include:

• Permeable pavements systems, permeable concrete, porous asphalt

These practices percolate rainwater through the substrate paving and into the ground, reduce stormwater flow volumes and minimize the pollutants introduced into storm water runoff from impervious surfaces. They are appropriate for pedestrian areas and for very low-volume, low-speed areas such as overflow parking, residential driveways, bike paths, patios, plazas, sidewalks, alleys, and parking stalls. Depending on



Permeable Pavement System (sidewalk)

design, paving material, soil type, and rainfall, permeable paving can infiltrate as much as 70% to 80% of annual rainfall<sup>16</sup> and remove 60% of Phosphorus and Nitrogen, and 80% of fecal coliform and total suspended solids.<sup>17</sup>

Permeable pavements attenuate peak flows, improve water quality by reducing fine-grained sediment, organic matter and trace metals, and, reduce heat island effect (the phenomenon of urban areas retaining heat due to the prevalence of pavement). Such pavements are limited to slopes less than 5 percent and function poorly on sites with compacted soils.

• Rainwater harvesting

By retaining stormwater runoff for on-site use, harvesting systems reduce flow volumes and pollutant loads entering the stormwater collection system, helping to restore predevelopment hydrology and mitigate impacts on downstream water quality impacts. The impact of rainwater harvesting on pollutant load reduction varies widely. Passive rainwater harvesting systems can be fairly easy to implement but they present limited opportunity for significant

Seventeen Mile River Watershed Management Plan, May 2018

<sup>&</sup>lt;sup>16</sup> Low Impact Development Toolkit, Metropolitan Area Planning Council, <u>http://www.mapc.org/sites/default/files/LID\_Fact\_Sheet\_-Permeable\_Paving.pdf</u>

<sup>&</sup>lt;sup>17</sup> Georgia Stormwater Management Manual, volume 2, Technical Handbook, 2016 ed., p.139.

reduction in stormwater runoff due to their relatively small volume, and an inability to ensure that stormwater retention volume is available at the onset of precipitation events. Outreach campaigns are recommended on optimal use of these systems. Additionally, to achieve significant stormwater flow reduction benefit, widespread implementation is needed.

Rainwater harvesting works best where above-ground storage can be sited in a stable, flat area that cannot block paths of travel for fire safety access; and, overflow locations are designed to direct flows away from building foundations and adjacent properties.

Advantages of this system are reduced volume and peak flows of stormwater entering the sewer; low maintenance for above ground cisterns; good for sites where infiltration is not an option; and recycles water for nonpotable reuse.

Disadvantages are that the system may require pumps or valves to access stored water; roof surfaces may contain copper or materials treated with fungicides and herbicides that would contaminate water for irrigation; the stored water is prone to algal growth if it is in a warm and sunny location; and, the harvesting does not remove pollutants.

#### Rain gardens

A rain garden is a garden which takes advantage of rainfall and stormwater runoff in its design and plant selection. Usually, it is a small garden which is designed to withstand the extremes of moisture and concentrations of nutrients, particularly nitrogen and phosphorus, that are found in stormwater runoff. Rain gardens are ideally sited close to the source of the runoff and serve to slow and treat the stormwater as it travels downhill. The stormwater has



Rain Garden

more time to infiltrate, which contributes to removal of contaminants, and less opportunity to gain momentum and erosive power.

Rain gardens work well in residential yards, office and commercial storefronts, parks, rights-of-way, and parking lots. They are easy and inexpensive to install, provide a wide range of scales and site applicability, improve water and air quality, are aesthetically pleasing, and reduce runoff volume. A gentle slope is best so that excess accumulation can exit downhill.

#### • Bioswales

Bioswales are designed to manage a specified amount of runoff from a large impervious area such as a parking lot or roadway. They consist of a swaled drainage course with gently sloped sides (less than 6 percent) and filled with vegetation, compost and/or riprap. The water's flow path, along with the wide and shallow ditch, is designed to maximize the time water spends in the swale, which aids the trapping of pollutants and silt. Bioswales can reduce phosphorus and nitrogen pollutant loads by 50 percent and heavy metals, 40 percent.<sup>18</sup>



**Bioswale** 

The effectiveness of bioswales increases with increased contact time between soil and stormwater, and increased vegetative cover. This is all best achieved by using soils that can adequately slow down, infiltrate, and retain water, as well as support plant life.

Flow-through planter

These planters allow stormwater to flow and filter through vegetation, growing medium and gravel. They temporarily store stormwater runoff on top of the soil and remove sediment and pollutants as water infiltrates down through the planter. Planters do not infiltrate runoff into the ground, rather they rely on evapotranspiration and short-term storage to manage stormwater. Stormwater planters are



Flow-through planter

presumed to remove 80% of the total suspended solids (TSS) load in typical urban post-development runoff when sized, designed, constructed, and maintained in accordance with the recommended specifications. Stormwater planters also remove 60% of Phosphorus and Nitrogen, and 80% of fecal coliform and total suspended solids.

<sup>&</sup>lt;sup>18</sup> Georgia Stormwater Management Manual, volume 2, Technical Handbook, 2016 ed., p.139.

These planters work on poorly drained sites, sites with contaminated soils, and adjacent to streets where runoff from impervious surfaces may be directed for treatment. Additionally, flow-through planters work well to accept drainage from rooftop gutters. Planted vegetation helps lessen stormwater flows, traps sediment, reduces stormwater volume, removes pollutants, and provides water detention in significant rainfall events. During the dry season, irrigation may be required to maintain plants.

The initial cost of a planter averages around \$8 per square foot; however, the overall cost will vary depending on the type and size of vegetation and planters used. Maintenance costs average around \$400-\$500 per year for a 500-square-foot planter. These also vary depending on size and plant choice.<sup>19</sup>

• Urban tree canopy.

Urban tree canopy is a network of green spaces in a community where trees and other woody plants are maintained to improve air quality, stormwater management, and wildlife habitat. Mature trees provide significant stormwater quantity and rate control benefits through soil storage, interception, and evapotranspiration. A tree with a 25-foot diameter canopy and associated soil can manage the 1-inch rainfall from 2,400 square feet of impervious surface. Interception and evapotranspiration also decrease runoff volume with larger trees providing exponentially more benefit than smaller trees.<sup>20</sup>

Vegetated roof

A vegetated roof, or green roof system, is composed of multiple layers including a waterproof membrane, subsurface drainage pipes, engineered planting soils and specially selected plants. Green roofs can be installed on many types of roofs, from small slanting roofs to large, flat commercial roofs. There are two basic types of green roofs: extensive and intensive. An extensive green roof system is a thin, lighter-weight system (usually less than 6 inches deep) planted predominantly with drought-tolerant succulent plants and grasses. An intensive green roof is deeper, often 18 inches, and can support plants that require great root depth.

Vegetated roofs can reduce TSS by 80 percent, and phosphorus and nitrogen by 50 percent.

Vegetated roofs perform best on commercial, multifamily, and industrial structures, as well as single-family homes, garages and sheds and can be used for new construction or to reroof an existing building if there is sufficient structural support. Roof slopes less than 5 degrees or greater than 20 degrees are not suitable for vegetated roofs.

Advantages of vegetated roofs are a reduction in the volume and velocity of stormwater runoff from roofs by temporarily storing stormwater; added insulation and noise reduction

<sup>&</sup>lt;sup>19</sup> Georgia Stormwater Manual, volume 2, Technical Handbook, 2016 ed., p. 339.

<sup>&</sup>lt;sup>20</sup> Stormwater Trees, Technical Memorandum, US EPA, September 2016.

compared to conventional roofs; reduced urban heat island effect and lower temperature of stormwater runoff; increased biodiversity and habitat; and aesthetic amenities for building occupants or owners.

Disadvantages are that vegetated roofs are limited to roof slopes less than 20 degrees; additional structural or seismic support may be needed to bear added weight; irrigation required to establish plants and maintain them during dry periods; and, high upfront cost compared to other green infrastructure.

Extensive green roofs can range from roughly \$5-\$20 per square foot. Intensive green roofs can range from roughly \$20-\$80 per square foot. Although the cost per square foot of a green roof is notably higher than a regular roof, green roofs have been reported to save costs associated with energy consumption and increasing the life span of the roof.<sup>21</sup>



Vegetated roof

<sup>&</sup>lt;sup>21</sup> Georgia Stormwater Manual, volume 2, Technical Handbook, 2016 ed., p. 241.

# VII. Working With The Public

Public support is a key element in the implementation process. Education is extremely important for increasing public awareness of the water quality problems and offering feasible solutions for remediation and prevention of water quality degradation.

## **Outreach Goals**

The overarching goal of the outreach campaign is to engage agricultural producers, residents, and government agencies in reducing fecal coliform non-point source pollution and maintain appropriate DO levels in the watershed. This will be accomplished by developing and promoting initiatives on water quality issues in the watershed, actions that may be taken to improve water quality, and programs available to assist with water quality improvement projects.

Objectives for education include:

- ! Educating agricultural producers on non-structural and structural agricultural best management practices that could be implemented.
- ! Educating property owners utilizing individual septic system concerning septic tank maintenance.
- ! Educating developers, citizens, and city leaders on the benefits of green infrastructure.
- ! Increasing watershed residents and government agencies knowledge on the importance of water quality and controlling non-point source pollution in the Seventeen Mile River watershed.
- ! Increase K-12 education concerning water quality issues.

Goal 1: To educate the general public about the watershed plan and its implementation.

- Post permanent signs along major roads notifying travelers that they are entering the Seventeen Mile River watershed.
- ! Coordinate with the local citizens and organizations to hold periodic cleanup events to remove smaller debris from watershed streams.



Goal 2: Educate elected officials and government agencies in the watershed about the watershed plan and its implementation.

! Convene a workshop to provide information on the watershed management plan and its implementation.

Goal 3: Educate agricultural producers and users of individual septic systems in the watershed about watershed issues and solutions.

- Provide information on appropriate agricultural best management practices, their cost and effectiveness in reducing water quality impairment, and available funding assistance programs.
- Provide homeowners utilizing individual septic systems information regarding proper care and maintenance of their system.

Goal 4: Educate development community and elected officials regarding benefit of green infrastructure.

Provide Douglas City Council, staff, and development community with information on green infrastructure.

Goal 5: Increase K-12 education concerning water quality issues.

Provide demonstrations and programs at local schools regarding water quality concerns, human impact on water quality, and solutions.

# VIII. Long-Term Monitoring Plan

Instream monitoring is important to gage the recovery of streams after remediation projects are installed, and is also crucial to support partners as they engage in periodic strategic planning of remediation priorities.

Long-term monitoring associated with this watershed management plan will have the following objective:

! To verify long-term, whether water quality meets State standards for fecal coliform and dissolved oxygen following implementation of the measures outlined in this plan.

The most intractable sources of variation are likely to be changes over time. Since the primary sources of non-point source contamination in the watershed are agricultural runoff, nutrients, the sanitary and individual sewerage systems, and urban runoff, the concentration of fecal coliform and dissolved oxygen will vary seasonally and with variations in precipitation. The most important quality assurance measure will be to sample many times throughout a range of hydrologic conditions.

A long-term monitoring plan for, at a minimum, fecal coliform and DO should:

- ! measure the long-term effectiveness of management practices;
- ! analyze trends; and
- ! redefine water quality problems, if any.

Monitoring should be accomplished by Adopt-a-Stream certified personnel under a GAEPD–approved QA/QC Monitoring Plan that follows Adopt-A-Stream methodologies, and focuses, at a minimum, on the impaired segments of Seventeen Mile River, Twentynine Mile Creek, and Otter and Tiger creeks. This will give a broad picture of water quality conditions in the watershed, a rough assessment of potential pollutant sources, and a general assessment of management measure implementation and effectiveness.

# IX. Implementation, Evaluation, and Revision

## Management Strategies

The basic strategy for implementation of this watershed management plan is to create and manage a program that features both structural and non-structural controls within the watershed to address the fecal coliform and dissolved oxygen concerns. The goal of this program is to restore the watershed to the extent that the impaired segment as well as all streams in the watershed meet State water quality standards. Measures that will be utilized to accomplish the goals include increasing installation of agricultural BMPs, repair and replacement of the sanitary sewerage system, repair, if needed, to the stormwater system, implementing practices to mitigate the impact of stormwater on water quality (green infrastructure), and available educational opportunities to encourage public and governmental participation in the watershed improvement process.

## **Priority Areas for Management Practices**

While inclusion of landowners from the entire watershed will be eligible for any cost-share or grant funded projects, agricultural producers in the Twentynine Mile subwatershed, and Tiger and Otter Creek subwatersheds are designated as a priority based on water quality monitoring data. Properties served by individual septic systems are designated a priority in the Seventeen Mile River segment upstream of Highway 32, Tiger Creek, and Twentynine Mile Creek. Projects in this portion of the watershed are likely to have the greatest impact on fecal coliform load reduction and dissolved oxygen levels.

## Implementation Plan and Interim Milestones

This Watershed Management Plan anticipates an implementation period of ten years. However, specific projects may be implemented over shorter periods. This section outlines objectives that apply across the entire implementation process and measurable milestones that should reveal significant progress.

#	ACTIVITY	TIMEFRAME	RESPONSIBLE PARTY*	COST ESTIMATE	FUND SOURCE*	EVALUATION MEASURE
W	atershed Partnership					
1	Establish Watershed Partnership (WP) to assist Seven Rivers RC&D with Plan implementation and periodic Plan review.	2018-2020	Seven Rivers RC&D	0	NA	Number of members
2	Review Watershed Management Plan every 2 years and amend, as necessary.	2020, 2022, 2024, 2026, 2028	Seven Rivers RC&D	0	NA	Completion of plan review.
M	onitoring Program					
1	Update GA EPD-approved Water Monitoring Plan to provide for post-BMP monitoring for fecal coliform or e.coli, DO, and pH.	2018-2020	Seven Rivers RC&D	\$250	319(h) grant	EPD-approved plan, number and frequency of sites monitored.
2	Conduct post-BMP water quality monitoring by AAS-certified personnel under GA EPD-approved Water Quality Monitoring Plan.	2020-2025	Seven Rivers RC&D	\$400/yr assuming 5 sites per month	319(h) grant	Monthly water quality data downstream of installed BMPs on impaired segments and including Twentynine Mile Creek; 40% reduction in fecal coliform loading.
3	Hold periodic AAS training for purpose of certifying volunteers to assist with post-BMP and long-term watershed monitoring.	2020-2028	Seven Rivers RC&D WP; Georgia AAS	NA	NA	Number of individuals certified.

#	ACTIVITY	TIMEFRAME	RESPONSIBLE PARTY*	COST ESTIMATE	FUND SOURCE*	EVALUATION MEASURE
4	Undertake long-term water quality monitoring by AAS-certified personnel under GA EPD- approved monitoring plan. Note: If post–BMP monitoring demonstrates improved water quality, long-term monitoring should be for fecal coliform rather than E.coli and include geometric means in to order to potentially delist stream as non-supporting.	2025-2028	Seven Rivers RC&D certified volunteers	E.coli – \$400/yr. Fecal coliform – \$640/yr	County and/or City partner	Monthly water quality data.
Ma	anagement Practices					
1	Review nutrient management plans with agricultural producers to insure appropriate implementation.	2018-2020	Seven Rivers RC&D, NRCS	0	NA	Number of plans reviewed.
2	Contact agricultural producers for participation in cost- share programs. Priority is producers in Seventeen Mile Creek subwatershed, Seventeen Mile River below Highway 64, and Tiger Creek subwatershed.	2020-2025	Seven Rivers RC&D, NRCS, GSWCC, SWCD	0	NA	Number of producers contacted.
3	Install appropriate agricultural BMPs.	2020-2025	Seven Rivers RC&D, NRCS, GSWCC	\$300,000 - \$500,000	319(h), EQIP, FSA	Number of installed BMPs, estimated contaminant load reduction.

#	ACTIVITY	TIMEFRAME	RESPONSIBLE PARTY*	COST ESTIMATE	FUND SOURCE*	EVALUATION MEASURE
4	Coordinate with Health Department to identify failing/leaking septic systems and contact property owners for participation in cost- share program. Priority is property owners in Seventeen Mile Creek watershed between Douglas and Coffee State Park and Tiger Creek subwatershed.	2020-2025	Seven Rivers RC&D, Coffee County Health Department	\$50,000	319(h)	Number of projects installed, estimated contaminant load reduction.
5	Install green infrastructure project(s) in new development and retrofit old development in City of Douglas.	2020-2028	Seven Rivers RC&D, City of Douglas	varies by project scope and scale	319(h), TE Grant, CWSRF, GAC, CWSRF, UWSG, CDBG, developer, City of Douglas	Number of projects installed.
Ed	Education, Involvement, and Stewardship					
1	Hold workshop for elected officials and government agencies to inform of content of Watershed Management Plan and its implementation.	2018-2020	Seven Rivers RC&D, WP	0	NA	Number of participants and local governments.

#	ACTIVITY	TIMEFRAME	RESPONSIBLE PARTY*	COST ESTIMATE	FUND SOURCE*	EVALUATION MEASURE
2	Develop and expand partnerships with K-12 schools in the watershed to establish drinking water source and water conservation education, and stewardship programs for youth, including classroom and field experiences.	2018-2028	Seven Rivers RC&D, GACD, Board of Education, UGA Coop Ext.	Varies by scope of program.	USEPA EE grant, Capt. Planet Foundation, Gerald C. Corcoran Education Grant, Wal- Mart Foundation State Giving Program (outdoor classroom funding)	Number of participants.
3	Utilize brochures, videos, and web-based products to educate public about septic system maintenance.	2018-2028	Seven Rivers RC&D, Health Department	0	NA	Number of brochures distributed, number of participants at events, number of web site visits.
4	Hold annual river cleanup event.	2018-2028	Seven Rivers RC&D, WP	\$1,000	local sponsors, River's Alive, Georgia Power	Number of participants, amount and type of trash collected.
5	Provide for web-based watershed information and education on Seven Rivers RC&D web page.	2018-2028	Seven Rivers RC&D	0	NA	Number of visits to website.
6	Install watershed signage at watershed boundaries on the following roads: Highway 64, Highway 158, Highway 32, Highway 135, and others roads identified by the WP.	2020-2022	Seven Rivers RC&D, Atkinson Co, Coffee Co, Jeff Davis Co, Ware Co.	\$60/sign (purchas ed from Bureau of Prisons)	local	Number and location of signs installed.

#	ACTIVITY	TIMEFRAME	RESPONSIBLE PARTY*	COST ESTIMATE	FUND SOURCE*	EVALUATION MEASURE
7	Build partnerships with universities and other research entities to conduct, support, and share research on urban ecology, green infrastructure, and community engagement.	2020-2028	Seven Rivers RC&D, WP	0	NA	Number of partnerships.
8	Conduct educational presentations on watershed issues and activities to local civic groups, elected officials, and at festivals and events.	2020-2028	Seven Rivers RC&D, WP	\$2500/yr	Georgia Power Foundation, Robert W. Woodruff Foundation	Number of presentations and participants.

\*Responsible Party and Fund Sources:

CDBG – US Housing and Urban Development, Community Development Block Grant

CWSRF – US EPA Clean Water State Revolving Fund

EPA EE – US EPA Environmental Education Grant

GAC – US EPA Office of Sustainable Communities Greening America's Communities Program

GACD – Georgia Association of Conservation Districts

GA AAS – Georgia Adopt-a-Stream

SWCD – Soil and Water Conservation District

TE – Georgia Department of Transportation, Transportation Enhancement Grant

UWSG – EPA Urban Water Small Grants Program

WP - Watershed Partnership

### Indicators to Measure Progress

Targeted water quality monitoring is necessary to measure long-term progress of installed practices. Monitoring must take place under a GA EPD-approved QA/QC Monitoring Plan. Monthly monitoring will, at a minimum, occur at Twentynine Mile Creek at Raccoon Bridge Road, Seventeen Mile River at Highway 135, and Otter Creek at Highway 32 to provide current data and to evaluate water quality improvements in the Seventeen Mile River watershed.

For more finite objectives, the Evaluation Measure associated with each task in the Implementation Plan will reveal progress that the implementation program is gaining momentum. Referencing these should provide an indication of specific tasks needing more focus. Eligible producer and property owner participation rates will be another useful tool in determining the success of grant implementation. Education and outreach participation rates will also be analyzed to help measure progress.

Indicators identified by the WP to measure the status of the watershed management process and educational outreach outlined in this Plan are:

Indicator Type	Specific Indicator
For the new ended	E.coli/fecal coliform bacteria and DO - Direct water quality measurement
Environmental	of Seventeen Mile River, Otter and Tiger creeks, Twentynine Mile Creek.
	Number of urban and agricultural best management practices
Programmatic	implemented.
December	Number of educational initiatives accomplished and number of
Programmatic	participants.
Programmatic	Number of river cleanup events.
Social	Participation rate in outreach programs.

Of greatest importance, is the measure of how the various implementation projects have translated towards accomplishing the goal of attaining State water quality standards. Tracking the watershed management plan and its water quality improvements will best indicate progress toward reducing fecal contamination.

At a minimum of every two years, assessment of the implementation schedule and review of accomplishments are necessary to determine whether task milestones are being met.

#### Long-term Plan Implementation

Seven Rivers RC&D with counsel from the WP will be the lead agency to implement the plan. NRCS, GSWCC, UGA Ag. Extension, and the Satilla River Soil and Water Conservation District will continue to assist agricultural producers with BMP installation through their respective agency programs. However, funding for other plan implementation activities must be secured through grants, loans, or governmental agencies. Continued plan implementation will be dependent on available funding.

# X. Appendix

Seventeen Mile River Watershed Management Plan, May 2018
























# Metadata

Мар	Data Source
Base Aerial	ESRI, DigitalGlobe, GeoEye, Earthstar Geographics, CNES/Airbus DS, USDA, USGS, AeroGRID, IGN, and the GIS User Community
Soils	Soil Survey Staff, Natural Resources Conservation Service, United States Department of Agriculture. Soil Survey Geographic (SSURGO) Database.
Impaired Waters	U.S. Geological Survey, 2016, National Water Information System data available on the World Wide Web (USGS Water Data for the Nation), accessed August 12,2017, at URL [http://waterdata.usgs.gov/nwis/].
Wetlands	U.S. Geological Survey's National Hydrography Dataset (NHD), 2012
Streams/Rivers	U.S. Geological Survey, 2016, National Water Information System data available on the World Wide Web (USGS Water Data for the Nation), accessed August 12,2017, at URL [http://waterdata.usgs.gov/nwis/].
Roads	Georgia Forestry Commission- Satilla Response Maps
Existing Land use	Southern Georgia Regional Commission- 2007
County	Georgia Forestry Commission- Satilla Response Maps
Watershed Boundary	U.S. Geological Survey, 2016, National Water Information System data available on the World Wide Web (USGS Water Data for the Nation), accessed August 12,2017, at URL [http://waterdata.usgs.gov/nwis/].
Flood Areas	National Flood Hazard- FEMA
Groundwater Recharge	Georgia Planning, USGS Groundwater data, 1992
Impervious Surfaces	National Gap Analysis, USGS, Geospatial Gateway, 2008
Land Use	National Gap Analysis, USGS, Geospatial Gateway, 2008
Zoning	Southern Georgia Regional Commission
Future Land Use	Southern Georgia Regional Commission
Sewer Lines	Southern Georgia Regional Commission



Station ID: 02040E0204		Water Ousli	デフックロ		
		Otter Crk at SF	32 near Do	uglas, GA	Cyzo lo Dala
Old_Ga_Num:	USGS_NUMBE	R: <null></null>	Lat /	Lon: 31.512051, -82.743357	Print Date: 24-May-11
Collection Date/Time	DO mg/L	рH	Temp °F	Fecal mpn/100ml	
1/11/2010 10:15:00 AM	12.5	6.99	33.6		
2/22/2010 11:15:00 AM	8.68	7.03	51.7		
3/16/2010 10:00:00 AM	8.68	6,45	52.5	170	
3/22/2010 9:45:00 AM	8.04	6.49	55	80 0 m= 152	
3/24/2010 10:30:00 AM	8.85	6.95	55.1	170	
4/15/2010 10:00:00 AM	6.36	5.68	63.1	230	
4/19/2010 9:45:00 AM	4.87	5.63	60.9	130 gm=171	
4/27/2010 10:25:00 AM	6.71	6.72	63.9	220	
4/29/2010 11:00:00 AM	6.79	6.23	58.2	130	
5/18/2010 9:45:00 AM	4.58	(5.19)	70.6		
7/6/2010 10:15:00 AM	ບາ .ຜ	5.96 ¢ Ó	74.6		
Total # of Values ====>	11	11	1	7	
	8 %	11/2 HO	7 º/11	FC 0/2gm	

\*

After Creek new reach 24/2 Tiger Creek Sevention Mile River

GA EPD Station No.	Station Name						
	Otter Crk at SR 32 near						
RV_07_2972	Douglas, GA						
		PH pH	COND		TEMP_AIR		FECAL
	Date	units	umho/cm	TEMP Deg C	Deg C	DO mg/l	#/100 ml
	2010-01-11 10:15:00.0	6.99	70.0	0.87	9.0	12.5	
	2010-02-22 11:15:00.0	7.03	58.0	10.96	17.0	8.68	
	2010-03-16 10:00:00.0	6.45	55.0	11.37	17.0	8.68	170.0
	2010-03-22 09:45:00.0	6.49	60.0	12.76	13.0	8.04	80.0
	2010-03-24 10:30:00.0	6.95	60.0	12.84	21.0	8.85	170.0
	2010-04-15 10:00:00.0	5.68	58.0	17.29	19.0	6.36	230.0
	2010-04-19 09:45:00.0	5.63	63.0	16.06	20.0	4.87	130.0
	2010-04-27 10:25:00.0	6.72	59.0	17.71	19.0	6.71	220.0
	2010-04-29 11:00:00.0	6.23	60.0	14.57	22.0	6.79	130.0
	2010-05-18 09:45:00.0	5.19	54.0	21.46	27.0	4.58	
	2010-06-14 10:15:00.0				31.0		
	2010-07-06 10:15:00.0	5.96	74.0	23.64	31.0	5.3	
	Latitude						
	31.51205						
	Longitude						
	-82.743355						
	River Basin						
	SATILLA						
	Hydrologic Unit Code						
	030702010501						
	County						
	Coffee						
	Water Plan Region						
	SUWANNEE - SATILLA						
	Eco-region						
	75H						
	Water Body Type						
	Stream						
	Source: GA EPD						

GA EPD Station No.	Station Name					
	Ottor Orly at SD 22 page					
	Otter Crk at SR 32 hear					
RV_07_2972	Douglas, GA					
				TEME		
		<b>D</b> 11 11	TEMP	IEMP_		FFOAL
		РН рН	TEMP		<b>DO</b> "	FECAL
	Date	units	Deg C	Deg C	DO mg/I	#/100 mi
	2010-01-11 10:15:00.0	6.99	0.87	9.0	12.5	
	2010-02-22 11:15:00.0	7.03	10.96	17.0	8.68	170.0
	2010-03-16 10:00:00.0	6.45	11.37	17.0	8.68	170.0
	2010-03-22 09:45:00.0	6.49	12.76	13.0	8.04	80.0
	2010-03-24 10:30:00.0	6.95	12.84	21.0	8.85	170.0
	2010-04-15 10:00:00.0	5.68	17.29	19.0	6.36	230.0
	2010-04-19 09:45:00.0	5.63	16.06	20.0	4.87	130.0
	2010-04-27 10:25:00.0	6.72	17.71	19.0	6.71	220.0
	2010-04-29 11:00:00.0	6.23	14.57	22.0	6.79	130.0
	2010-05-18 09:45:00.0	5.19	21.46	27.0	4.58	
	2010-06-14 10:15:00.0			31.0		
	2010-07-06 10:15:00.0	5.96	23.64	31.0	5.3	
	Latitude					
	31.51205					
	Longitude					
	-82.743355					
	River Basin					
	SATILLA					
	Hydrologic Unit Code					
	030702010501					
	County					
	Coffee					
	Water Plan Region					
	SUWANNEE - SATILLA					
	Eco-region					
	75H	*				
	Water Body Type					
	Stream		1			İ
	Source: GA EPD		1			
k		1	1	\$	,	1



# cy03 Station# 07016101

ł

# Seventeen Mile River at SR 158 near Douglas

Collection Date/Time	DO	Hd	Temp °F	Fecal	
01/21/2003 1:05:00 PM	10.1	5.55	45		
02/03/2003 1:49:00 PM	8.91	5.61	50.6	20	
02/10/2003 3:50:00 PM	8.42	6.37	54.6	50	attr 48
02/17/2003 2:39:00 PM	8.3	5.85	52.8	270	2
02/24/2003 11:41:00 AM	7.8	5.58	52.7	<20	
03/10/2003 1:32:00 PM	6.96	6.0	61		
03/19/2003 1:50:00 PM	6.1	4.77	65.9		
04/08/2003 1:46:00 PM	5.95	6.81	67.8		
05/01/2003 11:00:00 AM	4.31	5.26	68.6	130	
05/08/2003 1:16:00 PM	4.85	6.15	76.3	210	am-149
05/14/2003 12:13:00 PM	5.53	6.08	69.7	20	D
05/19/2003 12:46:00 PM	3.74	6.24	73.3	1700	
05/21/2003 1:03:00 PM	5.88	5.72	70.5		
05/29/2003 12:31:00 PM	4.42	9	69.5	80	
07/17/2003 1:00:00 PM	4.32	5.9	77.2		
08/05/2003 12:09:00 PM	7.26	5.29	74.8	1300	
08/12/2003 1:57:00 PM	4.89	5.7	76.4	235	am= 125
08/18/2003 12:28:00 PM	4.93	6.24	77.4	20	D
08/26/2003 1:15:00 PM				40	
09/04/2003 1:47:00 PM	2.97	6.25	78.4		
10/09/2003 1:13:00 PM	4.98	6.84	69.2		
11/03/2003 2:45:00 PM		•		80 7	
11/03/2003 3:45:00 PM	6.5	6.14	65.6		om= 34
11/05/2003 1:46:00 PM	4.64	6.06	70.5	20	7
11/12/2003 3:10:00 PM	6.27	6.02	63.4	20	
11/18/2003 1:49:00 PM				40 /	
	2/24	11/24	Y24	ц	C 0/4 gm

Seventee
07016101
Station# (
cy03

,

12/11/2003 3:05:00 PM

 Seventeen Mile River at SR 158 near Douglas

 8.45
 6.55
 48.4

GEORGIA DEPARTMENT OF NATURAL RESOURCES ENVIRONMENTAL PROTECTION DIVISION

> 455 14th Street NW, Atlanta, GA 30318-7900 (404) 206-5269

### LABORATORY REPORT

TO: U.S. Geolog Trend Moni Peachtree E 3039 Amwil	gical Survey toring Program Business Ctr Ste 130 er Rd				Date Collecte Time Collecte Sample Collec Chlorination: Sample Type:	d: d: ctor:	3/1 13: PA	9/03 50 GE/BASMAJI	
Council a ID:	A E 0 4070				Received By:		TN	3	
Sample ID:	AE04679				Date Receive	d:	3/2	1/03	
Facility Name:	Seventeen Mile Crk @	Sr158			Time Receive	d:	10:0	08 AM	
Site ID:	07016101				Project:		MC		
Location ID:					Roporting Dot	<u>.</u> .	VV G	1	
Location Descr:	BRUNSWICK METAL	S			Received Terr	e. Iperatu	4/1 ' re:	0.0 <i>C</i>	· .
·	PARAMETE	R EPA			QUALIFI	FR		ANALYSIS	MCL or
ANALYTE	CODE	NOTE METHOD	RESULT	U	NITS	RL	ANALY	ST DATE	QC Range
C Batch 55970									
Suspended Solids	00530	EPA 160.2	2.7	mg/	Ľ	1.0	RH	3/24/03	
Nater Quality Metals b	y ICPMS QC Batch 55	985							
Chromium 52	01034	EPA 200.8	Not Detected	ug/l	_	5	VK	3/31/03	
√ickel 60	01067	EPA 200.8	Not Detected	ug/l	-	10	VK	3/31/03	
Copper 65	01042	EPA 200.8	Not Detected	ug/L	-	5	VK	3/31/03	
Zinc 66	01092	EPA 200.8	Not Detected	ug/L	-	10	VK	3/31/03	
Arsenic 75	01002	EPA 200.8	Not Detected	ug/L	-	5	VK	3/31/03	
Selenium 82	01147	EPA 200.8	Not Detected	ug/L	-	5	VK	3/31/03	
/lolybdenum 98	01062	EPA 200.8	Not Detected	ug/L	-	5	VK	3/31/03	
Silver 107	01077	EPA 200.8	Not Detected	ug/L	•	5	VK	3/31/03	
Cadmium 111	01027	EPA 200.8	Not Detected	ug/L		0.7	VK	3/31/03	
īn 118	01102	EPA 200.8	Not Detected	ug/L		30	VK	3/31/03	
Intimony 121	01097	EPA 200.8	Not Detected	ug/L		5	VK	3/31/03	
Barium 137	01007	EPA 200.8	34	ug/L		2	VK	3/31/03	
hallium 205	01059	EPA 200.8	Not Detected	ug/L		1	VK	3/31/03	
.ead 207	01051	EPA 200.8	1.6	ug/L		1	VK	3/31/03	
CP Metals QC Batch 5	5995								
Juminum	01105	EPA 200.7	650	ug/L		60	LA	3/31/03	
Beryllium	01012	EPA 200.7	Not Detected	ug/L		10	LA	3/31/03	
Calcium	00916	EPA 200.7	3800	ug/L		1000	LA	3/31/03	
<b>Jobalt</b>	01037	EPA 200.7	Not Detected	ug/L		10	LA	3/31/03	
on	01045	EPA 200.7	3100	ug/L		20	LA	3/31/03	
'otassium	00937	EPA 200.7	Not Detected	ug/L		5000	LA	3/31/03	
ug/L: micrograms/liter mg/L: milligrams/liter mg/kg: milligrams/kilogram ug/kg: micrograms/kilogram ug/g: micrograms/gram ppm: parts per million ppb: parts per billion org/L: organisms/liter	<: less than MCL: Maxim RL: Reporting LSPC: result USPC: result TIE: Tentativ VIOL: Violatio	um Contaminant Leg g Limit less than lower spe greater than upper ely Identified or Esti on (result exceeds M	vel cification specification mated 1CL)	Lab	oratory Conta Inorganics: Metals: Organics: GC Mass Spec: Microbiology:	<b>cts:</b> Pat Sai Mark T Danny Steve E Viola R	mmons olbert Reed 3ryan Ieynolds	404-206-5239 404-206-5240 404-206-5252 404-206-5260 404-206-5210	

	PARAMET	ER EPA		QUA	LIFIER		MCL or	
ANALYIE	CODE	NOTE METHOD	RESULT	UNITS	RL	ANALYS	T DATE	QC Range
Vlagnesium	00927	EPA 200.7	2400	ug/L	1000	LA	3/31/03	
Vanganese	01055	EPA 200.7	49	ug/L	10	LA	3/31/03	
Sodium	00929	EPA 200.7	4600	ug/L	1000	LA	3/31/03	
Fitanium	01152	EPA 200.7	Not Detected	ug/L	10	LA	3/31/03	
√anadium	01087	EPA 200.7	Not Detected	ug/L	10	LA	3/31/03	
QC Batch 55992								
Vercury	71900	EPA 245.1	Not Detected	ug/L	0.2	PB	3/25/03	2.0

ug/L: micrograms/liter       <: less than         mg/L: milligrams/liter       MCL: Maximum Contaminant Level         mg/kg: milligrams/kilogram       RL: Reporting Limit         ug/kg: micrograms/kilogram       LSPC: result less than lower specification         ug/g: micrograms/gram       USPC: result greater than upper specification         ppb: parts per billion       TIE: Tentatively Identified or Estimated         oro/L: organisms/liter       VIOL: Violation (result exceeds MCL)	Laboratory Contacts:Inorganics:Pat Sammons404-206-5239Metals:Mark Tolbert404-206-5240Organics:Danny Reed404-206-5252GC Mass Spec:Steve Bryan404-206-5260Microbiology:Viola Reynolds404-206-5210	
--	---	--

**GEORGIA DEPARTMENT OF NATURAL RESOURCES** 

**ENVIRONMENTAL PROTECTION DIVISION** 

455 14th Street NW, Atlanta, GA 30318-7900 (404) 206-5269

## LABORATORY REPORT

TO: U.S. Geolo Trend Moni Peachtree 3039 Amwi	gical Survey itoring Program Business Ctr Ste 130 Ier Rd				Date Collecte Time Collecte Sample Colle Chlorination: Sample Type	ed: ed: ctor:	5/2 14: PU	1/03 03 GH/BASMAJI	
Sample ID:	4510165				Received By:		AA	A	
Sample ID.	AETUTOD				Date Receive	d:	5/2	3/03	
Facility Name:	Seventeen Mile Crk @Sr158				Time Receive	d:	10:	23 AM	
Site ID:	07016101				Project:		WC	)	
Location ID:					Reporting Dat	e.	6/1	*	
Location Descr:	BRUNSWICK METALS				Received Ten	nperatur	e:	0.0 C	
ANALYTE	PARAMETER CODE NOTE	EPA METHOD	RESULT		QUALIFI	ER	ΔΝΔΙ Υ	ANALYSIS ST DATE	MCL or
							7007061		de nange
QC Batch 57463 Suspended Solids	00530	EPA 160.2	1.7	mg/	۲ <u>ـ</u>	1.0	RH	5/28/03	
Water Quality Metals b	by ICPMS QC Batch 57487								
Chromium 52	01034	EPA 200.8	Not Detected	ug/l	L	5	PT	5/29/03	
Nickel 60	01067	EPA 200.8	Not Detected	ug/l	_	10	PT	5/29/03	
Copper 65	01042	EPA 200.8	Not Detected	ug/L	-	5	PT	5/29/03	
Zinc 66	01092	EPA 200.8	Not Detected	ug/L	-	10	PT	5/29/03	
Arsenic 75	01002	EPA 200.8	Not Detected	ug/L	-	5	PT	5/29/03	
Selenium 82	01147	EPA 200.8	Not Detected	ug/L	-	5	PT	5/29/03	
Molybdenum 98	01062	EPA 200.8	Not Detected	ug/L	-	5	PT	5/29/03	
Silver 107	01077	EPA 200.8	Not Detected	ug/L	-	5	PT	5/29/03	
	01027	EPA 200.8	Not Detected	ug/L	-	0.7	PT	5/29/03	
Aptimopy 101	01102	EPA 200.8	Not Detected	ug/L	-	30	PT	5/29/03	
Anamony 121	01097	EPA 200.8	Not Detected	ug/L	•	5	PT	5/29/03	
Theilium 205	01007	EPA 200.8	37 Net Detected	ug/L	-	2	PI	5/29/03	
Lead 207	01051	EPA 200.0	Not Detected	ug/L	•	1	РТ	5/29/03	
ICP Metals OC Batch 5	7457	LI A 200.0	NOT Detected	սց/դ		1	FI	5/29/03	
Aluminum	01105	FPA 200 7	400	10/1		60	IΔ	5/28/03	
Beryllium	01012	EPA 200 7	Not Detected	ug/L	•	10		5/28/03	
Calcium	00916	EPA 200.7	4900	ua/L		1000	LA	5/28/03	
Cobalt	01037	EPA 200.7	Not Detected	ua/L		10	LA	5/28/03	
Iron	01045	EPA 200.7	2300	ug/L		20	LA	5/28/03	
Potassium	00937	EPA 200.7	Not Detected	ug/L		5000	LA	5/28/03	
ug/L: micrograms/liter mg/L: milligrams/liter mg/kg: milligrams/kilogram ug/kg: micrograms/kilogram ug/g: micrograms/gram ppm: parts per million ppb: parts per billion org/L: organisms/liter	<: less than MCL: Maximum Con RL: Reporting Limit LSPC: result less tha USPC: result greater TIE: Tentatively Iden VIOI - Violation (resu	taminant Le an lower spe r than upper tified or Esti	vel cification specification mated 4CL )	Lab	ooratory Conta Inorganics: Metals: Organics: GC Mass Spec: Microbiology:	e <b>cts:</b> Pat San Mark To Danny F Steve B Viola Re	nmons blbert Reed ryan eynolds	404-206-5239 404-206-5240 404-206-5252 404-206-5260 404-206-5210	

	PARAMETER	EPA	EPA		LIFIER		MCL or	
ANALYTE	CODE NO	TE METHOD	RESULT	UNITS	RL	ANALYS	T DATE	QC Range
Magnesium	00927	EPA 200.7	2600	ug/L	1000	LA	5/28/03	
Manganese	01055	EPA 200.7	50	ug/L	10	LA	5/28/03	
Sodium	00929	EPA 200.7	5300	ug/L	1000	LA	5/28/03	
Titanium	01152	EPA 200.7	Not Detected	ug/L	10	LA	5/28/03	
Vanadium	01087	EPA 200.7	Not Detected	ug/L	10	LA	5/28/03	
QC Batch 57479								
Mercury	71900	EPA 245.1	Not Detected	ug/L	0.2	PB	5/28/03	2.0

ug/L: micrograms/liter       <: less than         mg/L: milligrams/liter       MCL: Maximum Contaminant Level         mg/kg: milligrams/kilogram       RL: Reporting Limit         ug/g: micrograms/kilogram       LSPC: result less than lower specification         ug/g: micrograms/gram       USPC: result greater than upper specification         ppm: parts per million       TIE: Tentatively Identified or Estimated         org/L: organisms/liter       VIOL: Violation (result exceeds MCL)	Laboratory Contacts: Inorganics: Pat Sammons 404-206-5239 Metals: Mark Tolbert 404-206-5240 Organics: Danny Reed 404-206-5252 GC Mass Spec: Steve Bryan 404-206-5260 Microbiology: Viola Reynolds 404-206-5210	
---	---	--

-

\_

GA EPD Station	Station Name					
	Seventeen Mile River at SR					
RV_07_2973	158 near Douglas					
		PH pH	TEMP	TEMP_AI		FECAL
	Date	units	Deg C	R Deg C	DO mg/l	#/100 ml
	2003-01-21 13:05:00.0					
	2003-02-03 13:49:00.0					20.0
	2003-02-10 15:50:00.0					50.0
	2003-02-17 14:39:00.0					270.0
	2003-02-24 11:41:00.0					20.0
	2003-03-10 13:32:00.0					
	2003-03-19 13:50:00.0	4.77	18.82	27.5	6.1	
	2003-04-08 13:46:00.0					
	2003-05-01 11:00:00.0					130.0
	2003-05-08 13:16:00.0					210.0
	2003-05-14 12:13:00.0					20.0
	2003-05-19 12:46:00.0					1700.0
	2003-05-21 13:03:00.0	5.72	21.41		5.88	
	2003-05-29 12:31:00.0					80.0
	2003-06-09 15:37:00.0					
	2003-07-17 13:00:00.0	5.9	25.11	37.0	4.32	
	2003-08-05 12:09:00.0	5.29	23.77	30.0	7.26	1300.0
	2003-08-12 13:57:00.0	5.7	24.67	32.0	4.89	235.0
	2003-08-18 12:28:00.0	6.24	25.23	33.0	4.93	20.0
	2003-08-26 13:15:00.0					40.0
	2003-09-04 13:47:00.0	6.25	25.78	35.0	2.97	
	2003-10-09 13:13:00.0	6.84	20.64	25.0	4.98	
	2003-11-03 14:45:00.0					80.0
	2003-11-03 15:45:00.0	6.14	18.65	30.0	6.5	
	2003-11-05 13:46:00.0	6.06	21.4	33.0	4.64	20.0
	2003-11-12 15:10:00.0	6.02	17.42	32.0	6.27	20.0
	2003-11-18 13:49:00.0					40.0
	2003-12-11 13:05:00.0					
	2003-12-11 15:05:00.0	6.55	9.1	21.0	8.45	
	Source: GA EPD					

GA EPD Station No.	Station Name				
	Seventeen Mile River -				
	Georgia Highway 64				
R\/ 07 2076	near Pearson GA				
		PHnH	TEMP		
	Date	unite			
	1001-07-31 08:55:00 0	6.2	24.5	26 0	63
	1001 00 18 08:45:00 0	6.21	24.0	20.0	2.0
	1991-09-18 08:45:00.0	6.76	24.0	20.0	2.9
	1997-11-14 09.43.00.0	6.08	8.0	17.0	6.1
	1002 02 11 11:20:00 0	6.08	12.0	0.0	5.0
	1992-03-11 11:20:00:0	6.34	22.5	28.0	2.9
	1992-03-27 10:23:00:0	6.40	25.5	20.0	2.0
	1002 00 16 10:00:00 0	6.07	23.0	27.5	2.4
	1992-09-10 10:00:00:0	6.42	20.0	21.5	4.0
	1992-11-05 12:00:00:0	6.00	20.0	10.0	7.0
	1993-01-20 10.20.00.0	0.09	10.0	10.0	7.0
	1993-03-17 10.15.00.0	C 11	10.0	15.0	9.1
	1993-05-12 09.05.00.0	0.41	19.0	23.0	4.1
	1993-07-15 09:45:00.0	7.08	27.0	36.0	3.0
	1993-09-15 09:40:00.0	0.01	25.0	29.5	3.0
	1993-11-04 09:00:00.0	6.7	13.0	19.5	7.0
	1994-01-12 11:00:00.0	6.52	10.0	18.5	7.9
	1998-02-12 11:50:00.0	6.4	11.5	18.5	8.1
	1998-02-17 10:40:00.0	6.4	14.7	22.0	1.2
	1998-02-25 10:05:00.0	6.4	12.5	18.0	8.8
	1998-03-12 12:10:00.0	6.1	11.1	7.0	8.0
	1998-03-31 10:20:00.0	6.5	21.0	24.0	6.6
	1998-04-09 10:30:00.0	6.4	19.0	25.0	5.0
	1998-04-16 09:20:00.0	6.4	17.8	25.0	5.9
	1998-04-23 10:10:00.0	6.5	16.3	21.0	6.0
	1998-05-07 09:20:00.0	6.4	20.7	25.0	5.2
	1998-06-03 10:00:00.0	6.7	25.8	32.0	3.3
	1998-08-06 10:50:00.0	6.2	23.9	31.0	3.8
	1998-08-11 08:20:00.0	6.2	24.5	27.5	6.7
	1998-09-01 09:50:00.0	6.7	25.5	32.5	2.4
	1998-09-03 11:25:00.0	6.7	24.0	25.0	3.2
	1998-10-07 09:50:00.0	6.2	24.5	28.5	5.2
	1998-11-05 11:05:00.0	6.5	16.0	14.5	4.9
	1998-11-12 10:35:00.0	6.6	16.5	17.0	4.7
	1998-11-18 10:30:00.0	6.6	17.5	20.5	4.2
	1998-12-03 10:10:00.0	6.7	15.5	17.0	5.1
	2001-01-02 10:38:00.0				
	2001-01-02 14:00:00.0	6.5	3.5	12.0	
	2001-02-12 14:28:00.0	7.07	12.79	17.0	
	2001-02-28 12:30:00.0				
	2001-03-19 12:02:00.0	5.54	13.81	19.0	7.61
	2001-03-21 13:17:00.0				
	2001-03-26 12:32:00.0				
	2001-03-28 11:24:00.0				
	2001-04-11 11:45:00.0	6.11	21.39	35.0	4.53
	2001-05-03 14:00:00.0	6.13	17.56	32.0	4.51
	2001-05-03 15:00:00.0				
	2001-05-15 12:00:00.0				
	2001-05-23 11:55:00.0				
	2001-05-30 13:27:00.0				

GA EPD Station No.	Station Name				
	Seventeen Mile River -				
	Georgia Highway 64				
R\/ 07 2076	near Pearson GA				
107_2370		PH nH	TEMP		
	Date	unite			
	2001-06-20 13:00:00 0	6 /1	24 48	34 0	1 81
	2001-06-20 13:00:00.0	0.41	24.40	34.0	4.01
	2001-00-20 14:00:00:0	6.06	22.05	20 0	2.12
	2001-07-18 12:30:00.0	0.00	23.05	30.0	2.13
	2001-07-18 13:30:00.0	6.25	24.09	22.0	1 11
	2001-08-02 12:39:00.0	0.35	24.90	33.0	4.44
	2001-08-02 13:39:00.0	6 50	24 55	27.0	1 20
	2001-08-30 10:23:00.0	0.52	24.55	37.0	1.39
	2001-08-30 11:23:00.0	0.00	25.47	25.0	0.70
	2001-09-10 14:25:00.0	6.36	25.17	35.0	3.12
	2001-09-10 15:25:00.0				
	2001-09-19 14:21:00.0	6.22	22.82	37.0	4.33
	2001-09-19 15:16:00.0				
	2001-09-24 12:43:00.0	6.49	23.44	33.0	4.78
	2001-09-24 13:43:00.0				
	2001-10-04 11:36:00.0	6.78	17.44	32.0	4.96
	2001-10-04 12:36:00.0				
	2001-11-07 12:55:00.0	6.34	10.23	30.0	3.02
	2001-12-03 14:30:00.0	6.46	13.42	25.0	3.09
	2001-12-10 11:30:00.0	6.73	17.7	23.0	3.19
	2001-12-18 12:06:00.0	6.93	15.92	23.0	6.82
	2001-12-26 13:30:00.0	7.11	6.68	18.0	8.42
	2002-01-02 12:33:00.0				
	2002-01-10 12:37:00.0	7.07	7.53		8.8
	2002-02-04 12:37:00.0	6.91	12.12	25.0	5.95
	2002-02-27 13:19:00.0				
	2002-03-04 12:34:00.0				
	2002-03-12 11:49:00.0	6.36	15.92	29.0	6.39
	2002-03-18 12:59:00.0	6.49	23.16	34.0	5.93
	2002-04-09 13:14:00.0	6.54	19.63	32.0	5.0
	2002-05-06 12:46:00.0	6.5	21.95	37.0	0.57
	2002-06-03 12:15:00.0				
	2002-06-04 12:15:00.0	6.25	23.17	25.0	2.41
	2002-06-11 12:10:00 0	6.37	22.07	33.0	0.55
	2002-06-17 14:25:00 0	6.5	24 79	32.0	3.3
	2002-06-19 13:45:00 0	6.68	24.75	31.0	1 11
	2002-07-09 12:31:00 0	6.6	25.93	32.0	1.11
	2002-08-01 13:14:00 0	5.05	25.00	32.0	2 71
	2002-09-03 14:03:00 0	0.00	20.44	02.2	2.11
	2002-09-03 14:10:00 0	6.63	24.85	36.1	3 57
	2002-03-00 14.10.00.0	6.48	27.00	3/ /	5 11
	2002-09-10 13:23:00:0	6.46	22.15	25 5	5.11
	2002-03-10 13.41.00.0	6.38	23.20	26.7	2.02
	2002-03-24 11.30.00.0	6.44	20.00	20.1	∠.Უ <del>1</del> 2.27
	2002-10-10 11.33.00.0	0.44	16 70	21.0	2.21 5.00
	2002-11-05 13:58:00.0	0.4	10.72	20.U	0.ZZ
	2002-12-05 13:11:00.0	0.2	0.02	12.0	1.04
	2002-12-10 13:17:00.0	0.20	0.00 7.0	13.0	1.89
	2002-12-16 12:59:00.0	6.11	1.6	23.0	9.4
	2002-12-18 14:08:00.0				0 ===
	2002-12-19 14:08:00.0	6.09	9.09	20.0	9.75

GA EPD Station No.	Station Name				
	Seventeen Mile River -				
	Georgia Highway 64				
RV 07 2076	near Pearson GA				
101_2010		PH nH	TEMP		
	Date	unite			
	2002 01 21 12:22:00 0	units	Deg C	IN Deg C	DO IIIg/I
	2003-01-21 12:33:00:0	-			
	2003-02-03 13.18.00.0				
	2003-02-10 15.07.00.0				
	2003-02-17 14.08.00.0				
	2003-02-24 11.09.00.0				<u> </u>
	2003-03-10 13:03:00:0	5.01	10.70	21.0	F 09
	2003-03-19 14.30.00.0	5.01	10.73	31.0	5.90
	2003-04-08 11:49:00.0				
	2003-05-01 09:43:00.0				
	2003-05-08 12:36:00.0				
	2003-05-14 13:23:00.0				
	2003-05-19 13:15:00.0				
	2003-05-29 13:00:00.0				
	2003-06-09 16:05:00.0				
	2003-07-17 13:39:00.0	5.92	26.31	37.0	3.42
	2003-08-05 13:34:00.0	5.54	24.35	30.0	7.35
	2003-08-12 12:50:00.0	5.43	25.05	33.0	4.53
	2003-08-18 13:00:00.0	5.88	25.29	33.0	3.9
	2003-08-26 13:54:00.0				
	2003-09-04 14:19:00.0	6.17	26.61	33.0	3.25
	2003-10-09 13:48:00.0	6.56	20.89	25.0	3.92
	2003-11-03 15:27:00.0				
	2003-11-03 16:27:00.0	6.18	18.34	30.0	7.45
	2003-11-05 14:11:00.0	6.12	21.43	33.0	5.27
	2003-11-12 15:40:00.0	6.14	17.64	30.0	7.29
	2003-11-18 14:32:00.0				
	2003-12-11 15:41:00.0	6.17	9.65	21.0	8.62
	2004-01-06 14:04:00.0	7.12	13.85	20.0	8.1
	2004-01-13 13:42:00.0	7.27	6.86	21.0	11.54
	2004-01-20 12:17:00.0	7.11	7.67	21.0	10.0
	2004-02-04 12:36:00.0				İ
	2004-02-04 12:43:00.0			17.0	
	2004-03-11 11:30:00.0	6.25	10.92	23.0	9.91
	2004-04-13 13:07:00.0	6.58	19.16	28.0	3.31
	2004-04-19 11:36:00.0	6.46	13.76	34.0	4.27
	2004-04-21 13:00:00.0	6.4	14.28	35.0	1.26
	2004-04-28 13:00:00.0	6.35	16.44	32.0	1.28
	2008-01-29 11:30:00.0	6.55	7.6	16.0	9.92
	2008-02-13 11:50:00.0	6.6	14.33	15.0	5.71
	2008-03-18 11:10:00.0	6.13	16.37	22.0	6.19
	2008-03-24 11:15:00.0	6.21	14.3	12.0	6.76
	2008-03-31 10:45:00 0	6.88	14.87	13.0	4.67
	2008-04-07 10:30:00 0	6.51	19.11	21.0	3.76
	2008-05-14 10:45:00 0	6.48	18.18		1.1
	2008-05-21 11:00:00 0	6.59	22 57	29.0	3.42
	2008-06-04 10:30:00 0	6.4	25.17	31.0	1 73
	2008-06-11 11:15:00 0	6.3	25 29	32.0	1.6
	2008-07-23 11.15.00.0	6.26	25.23	29.0	24
	2008-08-25 09.30.00 0	6.43	24.21	28.0	1.82
L	2000 00 20 00.00.00.0	0.10		1-0.0	1.04

GA EPD Station No.	Station Name				
	Seventeen Mile River -				
	Georgia Highway 64				
RV_07_2976	near Pearson, GA				
		PH pH	TEMP	TEMP_AI	
	Date	units	Deg C	R Deg C	DO mg/l
	2008-09-15 11:35:00.0	6.7	25.73	31.0	0.32
	2008-09-23 11:25:00.0	6.46	22.03	27.0	0.78
	2008-09-29 11:45:00.0	6.61	19.77	31.0	0.3
	2008-10-06 11:15:00.0	6.46	19.38	28.0	2.27
	2008-11-05 10:15:00.0	5.96	15.33	16.0	4.29
	2008-12-08 11:45:00.0	6.19	7.89	15.0	9.12
	2008-12-15 13:00:00.0	6.7	12.11	24.0	8.25
	2008-12-22 11:45:00.0	6.67	10.78	6.0	6.45
	2008-12-29 10:15:00.0	7.16	16.41	18.0	4.14
	2010-01-19 12:30:00.0	6.4	11.62	19.0	8.93
	2010-02-03 12:30:00.0	6.75	10.38	16.0	9.32
	2010-03-08 10:15:00.0	6.9	8.36	15.0	9.4
	2010-04-12 09:45:00.0			18.0	
	2010-05-25 09:00:00.0	6.14	22.03	26.0	2.66
	2010-06-15 09:30:00.0	6.19	26.11	34.0	1.32
	2010-07-19 08:45:00.0	6.13	25.3	29.0	3.16
	2010-07-19 09:15:00.0				
	2010-08-09 09:15:00.0	5.94	24.94	30.0	2.81

GA EPD Station No.	Station Name					
	Seventeen Mile River -					
	Georgia Highway 64					
RV 07 2976	near Pearson, GA					
···· <u>_</u> ··	,	PH pH	TEMP	TEMP AI		FECAL
	Date	units	Dea C	R Dea C	DO ma/l	#/100 ml
	1991-07-31 08:55:00.0	6.2	24.5	26.0	6.3	630.0
	1991-09-18 08:45:00.0	6.31	24.0	28.0	2.9	
	1991-11-14 09:45:00.0	6.76	8.0	14.0	4.2	490.0
	1992-01-22 13:15:00.0	6.08	8.0	17.0	6.1	
	1992-03-11 11:20:00 0	6.08	13.0	9.0	5.9	330.0
	1992-05-27 10:25:00 0	6.34	23.5	28.0	2.8	130.0
	1992-07-15 10:40:00 0	6 4 9	25.5	30.0	2.0	1300.0
	1992-09-16 10:00:00 0	6.07	23.0	27.5	4.6	170.0
	1992-11-05 12:00:00 0	6.42	20.0	21.5	3.4	1300.0
	1993-01-20 10:20:00 0	6.00	11 0	10.0	7.8	50.0
	1993-03-17 10:15:00 0	0.03	10.0	15.0	0.1	30.0
	1993-03-17 10.13.00.0	6 / 1	10.0	22.0	9.1	1200.0
	1993-03-12 09.03.00.0	7.09	27.0	25.0	4.1	20.0
	1993-07-13 09:43:00:0	6.61	27.0	20.5	2.0	20.0
	1993-09-13 09:40:00:0	6.7	23.0	29.5	3.0	220.0
	1004 01 42 44.00.00 0	0.1	10.0	19.0	7.0	230.0
	1009 02 12 11.00.00.0	0.02	10.0	10.3	1.9 0.1	50.0
	1998-02-12 11:50:00.0	0.4	11.5	18.5	0.1	50.0
	1998-02-17 10:40:00.0	0.4	14.7	22.0	1.Z	490.0
	1998-02-25 10:05:00.0	0.4	12.5	18.0	8.8	80.0
	1998-03-12 12:10:00.0	0.1	11.1	7.0	8.0	210.0
	1998-03-31 10:20:00.0	0.5	21.0	24.0	0.0	440.0
	1998-04-09 10:30:00.0	6.4	19.0	25.0	5.0	410.0
	1998-04-16 09:20:00.0	6.4	17.8	25.0	5.9	20.0
	1998-04-23 10:10:00.0	6.5	16.3	21.0	6.0	20.0
	1998-05-07 09:20:00.0	6.4	20.7	25.0	5.2	40.0
	1998-06-03 10:00:00.0	6.7	25.8	32.0	3.3	
	1998-08-06 10:50:00.0	6.2	23.9	31.0	3.8	170.0
	1998-08-11 08:20:00.0	6.2	24.5	27.5	6.7	130.0
	1998-09-01 09:50:00.0	6.7	25.5	32.5	2.4	170.0
	1998-09-03 11:25:00.0	6.7	24.0	25.0	3.2	790.0
	1998-10-07 09:50:00.0	6.2	24.5	28.5	5.2	
	1998-11-05 11:05:00.0	6.5	16.0	14.5	4.9	160.0
	1998-11-12 10:35:00.0	6.6	16.5	17.0	4.7	170.0
	1998-11-18 10:30:00.0	6.6	17.5	20.5	4.2	330.0
	1998-12-03 10:10:00.0	6.7	15.5	17.0	5.1	330.0
	2001-01-02 10:38:00.0					330.0
	2001-01-02 14:00:00.0	6.5	3.5	12.0		
	2001-02-12 14:28:00.0	7.07	12.79	17.0		230.0
	2001-02-28 12:30:00.0					80.0
	2001-03-19 12:02:00.0	5.54	13.81	19.0	7.61	230.0
	2001-03-21 13:17:00.0					330.0
	2001-03-26 12:32:00.0					70.0
	2001-03-28 11:24:00.0					80.0
	2001-04-11 11:45:00.0	6.11	21.39	35.0	4.53	20.0
	2001-05-03 14:00:00.0	6.13	17.56	32.0	4.51	
	2001-05-03 15:00:00.0					80.0
	2001-05-15 12:00:00.0					330.0
	2001-05-23 11:55:00.0					110.0
	2001-05-30 13:27:00.0					50.0
	2001-06-20 13:00:00.0	6.41	24.48	34.0	4.81	
	2001-06-20 14:00:00.0					140.0
	2001-07-18 12:30:00.0	6.06	23.85	38.0	2.13	
	2001-07-18 13:30:00.0					310.0
	2001-08-02 12:39:00.0	6.35	24.98	33.0	4.44	
	2001-08-02 13:39:00.0					
	2001-08-30 10:23:00.0	6.52	24.55	37.0	1.39	
	2001-08-30 11:23:00.0					

GA EPD Station No.	Station Name					
	Seventeen Mile River -	e River -				
	Georgia Highway 64					
RV_07_2976	near Pearson, GA					
		PH pH	TEMP	TEMP_AI		FECAL
	Date	units	Deg C	R Deg C	DO mg/l	#/100 ml
	2001-09-19 15:16:00.0		U	U		105.0
	2001-09-24 12:43:00.0	6.49	23.44	33.0	4.78	
	2001-09-24 13:43:00.0					140.0
	2001-10-04 11:36:00.0	6.78	17.44	32.0	4.96	
	2001-10-04 12:36:00.0					260.0
	2001-11-07 12:55:00.0	6.34	10.23	30.0	3.02	
	2001-12-03 14:30:00.0	6.46	13.42	25.0	3.09	130.0
	2001-12-10 11:30:00.0	6.73	17.7	23.0	3.19	130.0
	2001-12-18 12:06:00.0	6.93	15.92	23.0	6.82	270.0
	2001-12-26 13:30:00.0	7.11	6.68	18.0	8.42	
	2002-01-02 12:33:00.0					300.0
	2002-01-10 12:37:00 0	7 07	7 53		88	80.0
	2002-02-04 12:37:00 0	6.91	12 12	25.0	5.95	00.0
	2002-02-27 13 19:00 0					
	2002-03-04 12:34:00 0					500.0
	2002-03-12 11:49:00 0	6.36	15.92	29.0	6.39	300.0
	2002-03-18 12:59:00 0	6.49	23 16	34.0	5.93	110.0
	2002-04-09 13:14:00 0	6.54	19.63	32.0	5.0	110.0
	2002-05-06 12:46:00 0	6.5	21.95	37.0	0.57	
	2002-06-03 12:15:00 0	0.0	21.00	01.0	0.01	
	2002-06-04 12:15:00 0	6 25	23 17	25.0	2 41	170.0
	2002-06-11 12:10:00.0	6.37	22.17	33.0	0.55	500.0
	2002-06-17 12:10:00:0	6.5	24.79	32.0	3 3	20.0
	2002-06-19 13:45:00 0	6.68	24.75	31.0	1 11	230.0
	2002-07-09 12:31:00 0	6.6	24.43	32.0	1.11	230.0
	2002-07-03 12:01:00:0	5.05	25.33	32.0	2 71	
	2002-00-01 13.14.00.0	5.35	23.44	52.2	2.7 1	
	2002-09-03 14:00:00 0	6 63	24.95	26.1	2.57	120.0
	2002-09-03 14.10.00.0	6.49	24.05	24.4	5.57	80.0
	2002-09-10 13:23:00:0	6 16	22.75	25.5	5.02	120.0
	2002-09-18 13:41:00:0	6.29	23.23	26.7	2.04	220.0
	2002-09-24 11:30:00.0	0.30	23.00	20.7	2.94	220.0
	2002-10-10 11:35:00.0	0.44	22.73	27.0	Z.ZI	
	2002-11-05 13:58:00.0	0.4	10.72	20.0	D.ZZ	170.0
	2002-12-05 13.11.00.0	0.2	0.52	12.0	7.04	170.0
	2002-12-10 13:17:00.0	0.20	8.00	13.0	1.89	80.0
	2002-12-16 12:59:00.0	0.11	7.0	23.0	9.4	80.0
	2002-12-18 14:08:00.0	0.00	0.00	00.0	0.75	70.0
	2002-12-19 14:08:00.0	0.09	9.09	20.0	9.10	
	2003-01-21 12:33:00.0					20.0
	2003-02-03 13:18:00.0					20.0
	2003-02-10 15:07:00.0					110.0
	2003-02-17 14:08:00.0					F0.0
	2003-02-24 11:09:00.0					50.0
	2003-03-10 13:03:00.0	E 04	40.70	01.0	F 00	
		5.01	18.73	31.0	5.98	
						470.0
	2003-05-01 09:43:00.0					170.0
	2003-05-08 12:36:00.0					50.0
	2003-05-14 13:23:00.0					70.0
	2003-05-19 13:15:00.0					70.0
	2003-05-29 13:00:00.0					80.0
	2003-06-09 16:05:00.0				0.45	
	2003-07-17 13:39:00.0	5.92	26.31	37.0	3.42	
	2003-08-05 13:34:00.0	5.54	24.35	30.0	7.35	130.0
	2003-08-12 12:50:00.0	5.43	25.05	33.0	4.53	20.0
	2003-08-18 13:00:00.0	5.88	25.29	33.0	3.9	20.0
	2003-08-26 13:54:00.0	-				40.0

GA EPD Station No.	Station Name					
	Seventeen Mile River -	1	1			
	Georgia Highway 64					
RV 07 2976	near Pearson. GA					
		PH pH	TEMP	TEMP AI		FECAL
	Date	units	Deg C	R Deg C	DO mg/l	#/100 ml
	2003-11-03 16:27:00.0	6.18	18.34	30.0	7.45	
	2003-11-05 14:11:00.0	6.12	21.43	33.0	5.27	170.0
	2003-11-12 15:40:00.0	6.14	17.64	30.0	7.29	70.0
	2003-11-18 14:32:00.0		-			40.0
	2003-12-11 15:41:00.0	6.17	9.65	21.0	8.62	
	2004-01-06 14:04:00.0	7.12	13.85	20.0	8.1	20.0
	2004-01-13 13:42:00.0	7.27	6.86	21.0	11.54	20.0
	2004-01-20 12:17:00.0	7.11	7.67	21.0	10.0	60.0
	2004-02-04 12:36:00.0					20.0
	2004-02-04 12:43:00.0			17.0		
	2004-03-11 11:30:00.0	6.25	10.92	23.0	9.91	
	2004-04-13 13:07:00.0	6.58	19.16	28.0	3.31	90.0
	2004-04-19 11:36:00.0	6.46	13.76	34.0	4.27	20.0
	2004-04-21 13:00:00.0	6.4	14.28	35.0	1.26	130.0
	2004-04-28 13:00:00.0	6.35	16.44	32.0	1.28	20.0
	2008-01-29 11:30:00.0	6.55	7.6	16.0	9.92	
	2008-02-13 11:50:00 0	6.6	14.33	15.0	5 71	
	2008-03-18 11:10:00 0	6.13	16.37	22.0	6 19	70.0
	2008-03-24 11:15:00 0	6.10	14.3	12.0	6 76	50.0
	2008-03-31 10:45:00 0	6.88	14 87	13.0	4 67	80.0
	2008-04-07 10:30:00 0	6.51	19 11	21.0	3 76	310.0
	2008-05-14 10:45:00 0	6.48	18 18	21.0	1 1	330.0
	2008-05-21 11:00:00 0	6 59	22 57	29.0	3.42	110.0
	2008-06-04 10:30:00 0	6.4	25.17	31.0	1 73	330.0
	2008-06-11 11:15:00 0	63	25.29	32.0	1.6	130.0
	2008-07-23 11:15:00 0	6.26	25.20	29.0	2.4	100.0
	2008-08-25 09:30:00 0	6.43	24.21	28.0	1.82	
	2008-09-15 11:35:00 0	6.7	25.73	31.0	0.32	1100.0
	2008-09-23 11:25:00 0	6.46	22.03	27.0	0.32	800.0
	2008-09-29 11:45:00 0	6.61	10 77	31.0	0.70	700.0
	2008-10-06 11:15:00 0	6.46	10.38	28.0	2.27	170.0
	2008-11-05 10:15:00 0	5.96	15.30	16.0	1 20	170.0
	2008 12 08 11:45:00 0	6 10	7.80	15.0	4.23	70.0
	2008-12-00 11.43.00.0	6.7	12 11	24.0	8.25	220.0
	2008-12-13 13:00:00:0	6.67	12.11	24.0	6.45	220.0
	2008-12-22 11:45:00.0	7.16	16.70	19.0	4 1 4	120.0
	2008-12-29 10.13.00.0	6.4	10.41	10.0	9.02	130.0
	2010-01-19 12:30:00.0	6.75	10.29	19.0	0.93	
	2010-02-03 12:30:00:0	6.75	10.30	16.0	9.32	
	2010-03-00 10.13.00.0	0.9	0.30	19.0	3.4	
· · · · · · · · · · · · · · · · · · ·	2010-04-12 09.43.00.0	6 1 4	22.02	10.0	2.66	
	2010-05-25 09:00:00.0	0.14	22.03	∠0.U 24.0	2.00	
	2010-00-15 09:30:00.0	0.19	20.11	34.U 20.0	1.32	
	2010-07-19 08:45:00.0	0.13	20.3	29.0	3.10	
	2010-07-19 09:15:00.0	5.04	04.04	00.0	0.04	
	2010-08-09 09:15:00.0	5.94	24.94	30.0	2.81	
	0					
1	Source: GA EPD			1	1	

### Stream Monitoring Program Report Form For A Major Spill

Name of City/County:	Douglas/C	Coffee	Spill Amount:	720000gal		
Date Spill Occurred:	8/23-8/24/	17	Date Spill Reported to	EPD:	8/24/2017	7
Spill Location:			Date of PublicNotice (F	PN):	8/24/2017	7
Name OF Receiving St	ream Affec	ted:Seventee	n Mile River			
Upstream Sampling Lo	cation:	West Green Hwy 17 mile bridge	Written Report Submit	ted to EPD: (	(Y/N)	Y
Downstream Sampling	Location:	Coffee State Park	Copy of PN Submitted	to EPD: (Y/N	۷)	Y

			Above			Below				
_	Date	DO	Temp	рН	Fcoli	Date	DO	Temp	рН	Fcoli
Day 1	8/24/2017	0.32	89.6	6.6	≥2419.6	8/24/2017	4.35	93.3	5.68	34.5
Day 2	8/25/2017	0.46	78.8	6.67	≥2419.6	8/25/2017	1.09	76.1	6.24	43.5
Day3	8/26/2017	0.88	78.8	6.79	≥2419.6	8/26/2017	1.76	75.7	6.36	435.2
Day 4	8/27/2017	1.15	79.5	6.71	≥2419.6	8/27/2017	2.11	80.8	6.53	≥2419.6
Day 5	8/28/2017	4.17	80.6	6.53	≥2419.6	8/28/2017	3.3	80.8	6.32	387.3
Day 6	8/29/2017	1.74	76.1	6.53	1046.2	8/29/2017	1.01	75.2	5.97	41.7
Day7	8/30/2017	1.16	79.3	6.58	1413.6	8/30/2017	0.8	8.17	6.19	71.7
	Week 1	Geometric	Mean		1988					152
Week 2	9/6/2017	3.65	75.7	6.47	109.2	9/6/2017	5.19	77	6.4	186
Week 3	9/18/2017	6.35	78.4	7.35	816	9/18/2017	5.88	80	7.5	145
Week 4	9/25/2017	6.91	80.2	7.2	70	9/25/2017	5.2	80.2	7.1	102
Month	1 Geometric	Mean (use	all 10 data	points)	973					149
Month 3										
Week 1	12/26/2017	7.26	52.7	7.28	187.2	12/26/2017	8.84	52.3	7.19	261.3
Week 2	1/2/2018	7.47	39.5	6.6	93.3	1/2/2018	11.03	37	7.3	143
Week3	1/9/2018	7.74	52.1	7.19	35.5	1/9/2018	9.01	52.3	7.31	110.8
Week 4	1/16/2018	8.41	60.9	7	142.1	1/16/2018	9.02	70.1	6.8	155.2
	Month 3	Geometric	Mean:		96.88					159.21
Month 12										
Week 1										
Week 2										
Week3										
Week 4										
	Month 12 Ge	eometric Me	ean							

\* Submit Site Location Map

Bill Hawthorne Phone: 912-262-7284 Fax Number: 912-262-3160 Email: bill.hawthorne@dnr.state.ga.us

authorized	official	Date:
authorized	official	Date:
authorized	official	Date:
authorized	official	Date:
additonizod	omolai	

Stream Monitoring Program Report Form For	r A Major Spill
Name of City/County: Douglas / Coffee	Spill Amount: 9,000 gal
Date Spill Occurred: 31117	Date Spill Reported to EPD: 31117
Spill Location: 231 W. Ward St.	Date of PublicNotice (PN): 3317
Name OF Receiving Stream Affected: Unnamed T	ributary of Seventeen Mile River
Upstream Sampling Location: Ashley St. Corner of	Written Report Submitted to EPD: 🕖 N)
Downstream Sampling Location: <u>231</u> W. Ward	Copy of PN Submitted to EPD: (?)N)

			Above					Below		
	Date	DO	Temp	рН	Fçoli	Date	DO	Temp	рН	Fcoli
Day 1	3/13/17	5.10	58.6'F	7.12	72419	3/13/17	7.69	59.F	7.30	1733
Day 2	3/14/17	4.18	56.5°F	7.23	866	3/14/17	7.14	55.9.6	7.12	1203
Day3	3/15/17	4.89	59'F	7.01	1046	3/15/17	7.11	58.1'F	7.14	770
Day 4	3/16/17	4.70	58.3 <sup>.6</sup>	7.04	72419	3/16/17	7.61	57.7.F	7.15	22419
Day 5	3/17/17	5.77	4°.6.4	7.11	72419	3 111 17	5.89	40.2.5	7.19	724/19
Day 6	3/1A/17	5.49	64.3'F	7.31	72419	3/18/17	6.51	63.9°F	7.06	72419
Day7	3/10/17	6.19	62.4.F	7.22	72419	3/19/17	5.71	61.3'F	7.09	72419
	Week	1 Geometric	c Mean		1853					1772
Week 2	3/22/17	7.92	( . G 70F	4.93	29419.6	3/22/17	7.95	Ul. 2"	7.17	1732.9
Week 3	3126117	496	67.20	7.28	172.5	3126117	4.95	(e4.5°	1.21	290.9
Week 4	41ain	2.71	68.70F	7.18	2613	4/2/12	243	68.108	711.	461.1
Month	1 Geometric	Mean (use	e all 10 data	points)	1234	110/1		······		647
Month 3										- <u>9-</u> 1-1
Week 1										
Week 2										
Week3										
Week 4										
······	Month 3	3 Geometric	Mean:				F	L		
Month 12		+							i	L
Week 1										
Week 2										
Week3										
Week 4									······	
£	Month 12 G	Geometric M	lean							

\* Submit Site Location Map

\_\_\_\_\_

Bill Hawthorne Phone: 912-262-7284 Fax Number: 912-262-3160 Email: bill.hawthorne@dnr.state.ga.us

Ward Spill

### Stream Monitoring Program Report Form For A Major Spill

Name of City/County:	Douglas/C	Coffee	Spill Amount:	720000gal		
Date Spill Occurred:	8/23-8/24/	17	Date Spill Reported to	EPD:	8/24/2017	7
Spill Location:			Date of PublicNotice (	PN):	8/24/2017	7
Name OF Receiving St	ream Affect	ted:Sevente	en Mile River			
Upstream Sampling Lo	cation:	West Green Hwy 17 mile bridge	e Written Report Submit	tted to EPD: (	(Y/N)	Y
Downstream Sampling	Location:	Coffee State Park	Copy of PN Submitted	to EPD: (Y/I	N)	Y

			Above					Below		
	Date	DO	Temp	рН	Fcoli	Date	DO	Temp	рН	Fcoli
Day 1	8/24/2017	0.32	89.6	6.6	≥2419.6	8/24/2017	4.35	93.3	5.68	34.5
Day 2	8/25/2017	0.46	78.8	6.67	≥2419.6	8/25/2017	1.09	76.1	6.24	43.5
Day3	8/26/2017	0.88	78.8	6.79	≥2419.6	8/26/2017	1.76	75.7	6.36	435.2
Day 4	8/27/2017	1.15	79.5	6.71	≥2419.6	8/27/2017	2.11	80.8	6.53	≥2419.6
Day 5	8/28/2017	4.17	80.6	6.53	≥2419.6	8/28/2017	3.3	80.8	6.32	387.3
Day 6	8/29/2017	1.74	76.1	6.53	1046.2	8/29/2017	1.01	75.2	5.97	41.7
Day7	8/30/2017	1.16	79.3	6.58	1413.6	8/30/2017	0.8	8.17	6.19	71.7
	Week 1	Geometric	Mean		1988					152
Week 2	9/6/2017	3.65	75.7	6.47	109.2	9/6/2017	5.19	77	6.4	186
Week 3	9/18/2017	6.35	78.4	7.35	816	9/18/2017	5.88	80	7.5	145
Week 4	9/25/2017	6.91	80.2	7.2	70	9/25/2017	5.2	80.2	7.1	102
Month	1 Geometric	Mean (use	all 10 data	points)	973					149
Month 3										
Week 1	12/26/2017	7.26	52.7	7.28	187.2	12/26/2017	8.84	52.3	7.19	261.3
Week 2	1/2/2018	7.47	39.5	6.6	93.3	1/2/2018	11.03	37	7.3	143
Week3	1/9/2018	7.74	52.1	7.19	35.5	1/9/2018	9.01	52.3	7.31	110.8
Week 4	1/16/2018	8.41	60.9	7	142.1	1/16/2018	9.02	70.1	6.8	155.2
-	Month 3	6 Geometric	Mean:		96.88					159.21
Month 12										
Week 1										
Week 2										
Week3										
Week 4										
	Month 12 Geometric Mean									

\* Submit Site Location Map

Bill Hawthorne Phone: 912-262-7284 Fax Number: 912-262-3160 Email: bill.hawthorne@dnr.state.ga.us

authorized	official	Date: _	
authorized	official	Date:	
authorized	official	Date:	
authorized	official	Date:	

Site	Monitoring Site Description		Jun-17				Jul-17						
		E.coli cfu/100 ml	Fecal Coliform cfu/100 ml	Dissolved Oxygen	Dissolved Oxygen Saturation	рН	Conductivity	E.coli cfu/100 ml	Fecal Coliform cfu/100 ml	Dissolved Oxygen	Dissolved Oxygen Saturation	рН	Conductivity
1	Seventeen Mile River at Hwy 135	300.00	500.00	5.00	60.52	6.0	100.00	400.00	666.67	3.80	52.63	6.0	100.00
2	Seventeen Mile River at Hwy. 32	300.00	500.00	4.00	49.45	6.0	90.00	300.00	500.00	5.50	76.21	6.5	90.00
3	Twentynine Mile River at Raccoon Bridge Rd.	100.00	166.67	1.50			140.00	800.00	1333.33	3.80	50.80	6.0	140.00
4	Seventeen Mile River at Hwy 64	33.30	55.50	5.00	57.71	6.0	90.00	66.00	110.00	5.00	64.35	6.0	160.00
5	Seventeen Mile River at Taylor Church Rd	366.00	610.00	4.00			90.00	166.00	276.67	5.00			80.00
6	Otter Creek at Sand Hill Church Road	1133.00	1888.33	2.50	30.59	6.0	100.00	33.00	55.00	3.80	50.69	6.0	90.00
	Rainfall - previous 24 hours (inches)	0						0					
	Monitoring Site Description			Aug-	17					Oct	-17		
		E.coli cfu/100 ml	Fecal Coliform cfu/100 ml	Dissolved Oxygen	Dissolved Oxygen Saturation	рН	Conductivity	E.coli cfu/100 ml	Fecal Coliform cfu/100 ml	Dissolved Oxygen	Dissolved Oxygen Saturation	рН	Conductivity
1	Seventeen Mile River at Hwy 135	400	666.67	4.2	54.25	6.0	120.00	100.00	166.67	3.20	37.31	6.5	90.00
2	Seventeen Mile River at Hwy. 32	160	266.67	4			80.00	333.63	556.05	2.60		6.5	90.00
3	Twentynine Mile River at Raccoon Bridge Rd.	100	166.67	1.5	17.55	6.0	140.00	300.00	500.00	1.80	20.24	5.5	130.00
4	Seventeen Mile River at Hwy 64	33	55.00	3.4	43.59	6.4	200.00	66.66	111.10	1.40		6.5	150.00
5	Seventeen Mile River at Taylor Church Rd	33	55.00	3			80.00	100.00	166.67	5.00		5.5	50.00
6	Otter Creekr at Sand Hill Church Road	233.00	388.33	3.5	48.50	6.5	120.00	33.33	55.55	2.60		6.5	120.00
	Rainfall - previous 24 hours (inches)	0.00						0.00					
			exceeds seasonal fecal coliform standard (200 May - Oct))										

### Georgia FY 2017 EQIP Policy

This Policy is based on the Final Rule (IFR) for EQIP, published 12/12/14 in Vol. 79 No. 239 of the Federal Register, 7 CFR Part 1466.

Planned conservation practices must be maintained for the lifespan of the practice, as indicated on the NRCS-CPA-1155 or -1156. All practices must also meet the minimum criteria in the Conservation Practice Standard (see the Georgia eFOTG) and the criteria listed below. Extents above the minimum necessary to meet practice criteria are not eligible for payment. Note: Payment for some practices is only authorized when used in conjunction with another practice, as detailed in the Conservation Plan of Operation (CPO), with or without payment. The applicant is responsible for the installation, use, and maintenance of all components required in the conservation management system.

Management Practices - Management practice payments are only available on acres where the practice option has not been previously applied &/or utilized, and where there will be a higher level of management required for the requested practice option. Management payments are not authorized if the conservation practice option has previously been implemented on the acres in the application, with or without financial assistance. A management practice payment is only authorized once per acre within the length of the contract period for that conservation practice. Some management practices, where noted in the practice footnotes, are limited to no more than three separate management practices combined per acre.

Structural Practices - Structural practices include conservation practices that are either structural or vegetative, and have a multi-year lifespan. Structural practices involve the establishment, construction, or installation of site-specific measures. Payments are established as a one-time payment. The landowner must be a signatory to a contract which has EQIP funds used for any structural practice. Extents above the minimum necessary to meet practice criteria are not eligible for EQIP payment. Note: Payment for some practices is only authorized when used in conjunction with another practice, as detailed in the Conservation Plan of Operation (CPO), with or without payment.

Conservation Activity Plans (CAP) - Conservation Activity Plans are conservation plans developed for producers to assist in identifying conservation practices needed to address a specific natural resource need. CAPs are completed by NRCS certified Technical Service Providers (TSP). The list of NRCS certified TSPs is available on the NRCS TSP webpage: www.nrcs.usda.gov/wps/portal/nrcs/main/national/programs/technical/tsp

Practice Code	Conservation Practice	Payment Unit	Payment Rate	Maximum Amount	HU Payment Rate	HU Maximum Amount	Lifespan
472	Access Control						
	Bat Cave Exclusion	SqFt	\$10.80		\$12.96		10 Years

Excluding people from an area in order to address identified resource concerns. This is for facilitating exclusion of people to protect or enhance natural resource values. Control will be by a gate and support posts.

Applicable to Wildlife Landuse Only. Only allowed on caves actively utilized as bat hibernacula that are in need of access control. Must receive prior approval from the NRCS State Biologist to implement this practice. Must be planned as a supporting practice in conjunction with 643 Restoration and Management of Rare and Declining Habitats.

309	Agrichemical Handling Facility				
	Open building, locked chemical storage room, concrete slab floor 1/	SqFt	\$13.14	\$15.77	

 Enclosed building, locked chemical storage room, concrete slab floor 2/
 SqFt
 \$20.79
 \$24.95
 15 Years

 1/ Includes following components of an open, post frame agrichemical handling facility: wash down station, locked chemical storage area, curbed reinforced concrete pad with collection sump area, and roof structure. Planner may add the following (if needed): critical area planting, mulch, HUA for entrance pads, and roof runoff. Building must be designed and installation certified by registered Georgia PE or Area Engineer.
 If years

2/ Includes following components of an enclosed, roofed agrichemical handling facility: wash down station, locked chemical storage area, curbed reinforced concrete pad with collection sump area, a flexible membrane beneath concrete pad, and roof structure. Planner may add the following (if needed): critical area planting, mulch, HUA for entrance pads, and roof runoff. Building must be designed and installation certified by registered Georgia PE or Area Engineer.

316	Animal Mortality Facility				
	Static pile, Wood Bin(s) 1/	SqFt	\$6.76	\$8.12	
	Composting - Small Animals 2/	LB/Day	\$13.72	\$16.47	
	Composting - Large Animals 3/	LB/Day	\$73.34	\$88.00	15 Years

If applicant has a functioning composter, incinerator, or rotary drum at the farm, they are eligible for a new composter, incinerator, or rotary drum only if the capacity of the existing animal mortality facility is not sufficient to handle the volume of mortality at the farm (for example: size of operation has increased since existing animal mortality facility was purchased or constructed). **NRCS approved Comprehensive Nutrient Management Plan required.** 

1/ Composters for animal mortality must use this scenario. Cost covers concrete floor, wooden walls, and any required excavation. Must add roofs and covers, concrete HUA access pad and critical area planting and mulch (if needed). Covers all types of composters (side shed, stand alone, and inside stackhouse). Area for payment is the area of concrete pad from post to post.

2/ Rotary drums and incinerators - Poultry. Rotary cost include rotary drum, concrete pad and concrete entrance pad. Minimum width of the pad under the composter is 10 feet, and minimum length of pad will be the length of the machine plus 4 feet on each end. Incinerator must be a Type IV. Use the calculated total pounds/day from the Cost Estimator under the "Rotary Drum & Incinerators" tab. The value for pounds/day for this item is highlighted in yellow.

### 3/ Rotary drums and incinerators - Swine. See note 2.

396	Aquatic Organism Passage						
	Concrete Dam Removal	CuYd	\$105.01		\$126.01		
	Earthen Dam Removal	CuYd	\$45.57		\$54.69		
	Blockage Removal	CuYd	\$73.31		\$87.97		
	Nature-Like Fishway	Acre	\$70,948.49		\$85,138.19		
	CMP Culvert 1/	Each	\$21,314.39		\$25,577.27		
	Bottomless Culvert 1/	Each	\$31,189.17		\$37,427.01		
	Concrete Box Culvert 1/	Each	\$37,920.58		\$45,504.70		
	Concrete Ladder	Ft	\$9,298.13		\$11,157.76		
	Low Water Crossing	CuYd	\$468.22		\$561.86		5 Year
Applicable	e to Wildlife Landuse Only. This practice shall only be used in instances where	a rare and decl	ining aquatic	species passag	e has been id	entified as a res	ource

Applicable to wildlife Landuse Only. This practice shall only be used in instances where rare and declining aquatic species passage has been identified as a resource concern (does not include low water crossing). Must receive prior approval from the State Biologist and engineer to schedule these scenarios. Landowner must secure required CWA and other necessary permits

Code	Conservation Practice	Payment Unit	Payment Rate	Maximum Amount	HU Payment Rate	HU Maximum Amount	Lifespan
1/ If used	on perennial streams must meet ACOE regional conditions and may need to submi	t a ACOE PCN.					
314	Brush Management						
_	Mechanical, Hand tools 5/	Acre	\$37.62		\$45.15		
	Mechanical Bush Hog 3/	Acre	\$27.82		\$33.38		
	Mechanical Roller Chopper 4/	Acre	\$41.42		\$49.71		
	Mechanical & Chemical, Small Shrubs, Medium Infestation 2/	Acre	\$105.03		\$126.04		
	Chemical - Ground Applied 1/	Acre	\$38.56		\$46.27		
Ameliant	Chemical, Aerial Applied 6/	Acre	\$55.39		\$66.47		10 Years
1/ Brush r	nanagement on grazed forest, or pasture thru the use of broadcast, application of m	aterial using ch	emical(s) to rec	duce or remove i	undesirable de	ciduous species (	(brush) in
uplands a	nd other areas not in or directly adjacent to streams, ponds, or wetlands.	5					(****)
2/ Remov 3/ Remov 4/ The rer 5/ The rer 6/ The re	al of small woody vegetation infestations by the use of mechanical cutter, chopper of al of brush by the use of mechanical cutter. noval of brush by the use of chopper. noval of brush by the use of hand tools on sentitive areas where mechanical equipm moval of brush by using aerial equipment.	or other light eq	uipment followe	ed by an applicat	ion of low cost	chemicals in low	v volume
5/ Applica	able to wildlife Landuse Only. Use of mechanical hand treatments for sensitive ha	abitats that could	d be damaged i	by broadcast app	Dilications of lar	ge machinery.	
672	Building Envelope Improvement					• • • • • • • • •	
	Building Envelope - Sealant 1/	Ft	\$1.05	\$ 10,000.00	\$1.26	\$ 10,000.00	
	Groonhouse - Insulate Linglated Walls 5/	SqFt	\$1.55	\$ 10,000.00	\$1.87	\$ 10,000.00	
	Tunnel Doors 3/	SaFt	\$8.93	\$ 30,000,00	\$10.20	\$ 30,000,00	
	Insulated Poultry House Door	SaFt	\$7.81	\$ 20,000.00	\$9.37	\$ 20,000.00	
	Attic Insulation 4/	SqFt	\$0.20	\$ 20,000.00	\$0.24	\$ 20,000.00	
	Building Envelope - Batt Wall Insulation 5/	SqFt	\$1.71	\$ 30,000.00	\$2.05	\$ 30,000.00	10 Year
provide m	Energy POC prior to implementation. The licensed engineer/installer will provide aterial specifications which are used for these practices in order to certify that the m	certification that aterial requirem	t the work was nents in the ene	completed in acc ergy audit are acl	cordance with lenergy	ocal codes. Land Savings for eac	downer will h practice
provide m must be in 1/ Paymen 2/ Mechar 3/ Based 4/ Based 5/ Paymen	Energy POC prior to implementation. The licensed engineer/installer will provide aterial specifications which are used for these practices in order to certify that the m neluded in the energy audit and these energy savings must be entered into protracts int for linear foot of gap sealed by professional contractor nical screens for greenhouse to control heat loss and gain. upon square foot of tunnel opening. upon a minimum R-7 insulation in addition to existing attic/ceiling; All materials oth nt based on square foot of existing wall insulated, can also include foundation wa	certification tha aterial requirem during ranking er than blown all or end walls	fiberglass insu	completed in acc rgy audit are acc ulation must be a portion of the	cordance with lineved. Energy approved by wall height is i	cal codes. Lanc / Savings for eac Area Engineer. nsulated (4 to 6')	downer will h practice
provide m must be in 1/ Paymen 2/ Mechar 3/ Based 4/ Based 5/ Paymen of the wal sheathing	Energy POC prior to implementation. The licensed engineer/installer will provide aterial specifications which are used for these practices in order to certify that the m included in the energy audit and these energy savings must be entered into protracts int for linear foot of gap sealed by professional contractor inical screens for greenhouse to control heat loss and gain. upon square foot of tunnel opening. upon a minimum R-7 insulation in addition to existing attic/ceiling; All materials other the based on square foot of existing wall insulated, can also include foundation wall where exhaust fans are located is not insulated. Only approved method of insulation.	certification tha aterial requirent during ranking er than blown all or end walls on is metal exte	t the work was nents in the energy fiberglass insu- trior, 3.5" fiberg	completed in acc rgy audit are acc ulation must be v a portion of the lass batts (R-11)	approved by wall height is i , vapor barrier,	Area Engineer. https://www.area.org/a	downer will h practice
brovide m must be in 1/ Payme 2/ Mechar 3/ Based 4/ Based 5/ Payme of the wal sheathing	Energy POC prior to implementation. The licensed engineer/installer will provide aterial specifications which are used for these practices in order to certify that the m included in the energy audit and these energy savings must be entered into protracts int for linear foot of gap sealed by professional contractor inical screens for greenhouse to control heat loss and gain. upon square foot of tunnel opening. upon a minimum R-7 insulation in addition to existing attic/ceiling; All materials oth int based on square foot of existing wall insulated, can also include foundation wa where exhaust fans are located is not insulated. Only approved method of insulation.	certification tha aterial requiren during ranking er than blown all or end walls on is metal exte	t the work was nents in the energiest fiberglass insu- . Typically only rior, 3.5" fiberg	completed in acc rgy audit are acc ulation must be / a portion of the lass batts (R-11)	approved by wall height is i	Area Engineer. % interior plywoo	downer will h practice
brovide m must be in 1/ Payme 2/ Mechar 3/ Based 4/ Based 5/ Payme of the wal sheathing 372	Energy POC prior to implementation. The licensed engineer/installer will provide aterial specifications which are used for these practices in order to certify that the m included in the energy audit and these energy savings must be entered into protracts int for linear foot of gap sealed by professional contractor inical screens for greenhouse to control heat loss and gain. upon square foot of tunnel opening. upon a minimum R-7 insulation in addition to existing attic/ceiling; All materials oth in based on square foot of existing wall insulated, can also include foundation wa where exhaust fans are located is not insulated. Only approved method of insulation. Combustion System Improvement	certification tha aterial requirent during ranking er than blown all or end walls on is metal exte	t the work was nents in the energy fiberglass insu- trior, 3.5" fiberg	completed in acc rgy audit are acc ulation must be v a portion of the lass batts (R-11)	approved by wall height is i	Area Engineer. Minimized (4 to 6') & interior plywoo	downer will th practice
brovide m must be in 1/ Paymei 2/ Mechan 3/ Based 4/ Based 5/ Paymei of the wal sheathing 372	Energy POC prior to implementation. The licensed engineer/installer will provide aterial specifications which are used for these practices in order to certify that the m included in the energy audit and these energy savings must be entered into protracts int for linear foot of gap sealed by professional contractor inical screens for greenhouse to control heat loss and gain. upon square foot of tunnel opening. upon a minimum R-7 insulation in addition to existing attic/ceiling; All materials oth in based on square foot of <b>existing</b> wall insulated, <b>can also include foundation wa</b> where exhaust fans are located is not insulated. Only approved method of insulation <b>Combustion System Improvement</b> Electric Motor/Centrifugal Pump in-lieu of IC Engine, < 100 hp 1/	er than blown all or end walls on is metal exte	t the work was nents in the energy fiberglass insu- . Typically only rior, 3.5" fiberg	completed in acc rgy audit are acc ulation must be v a portion of the lass batts (R-11)	approved by a wall height is i , vapor barrier, \$9,575.82	Area Engineer. * Savings for eac Area Engineer. * interior plywood	downer will h practice
brovide m must be in 1/ Paymen 2/ Mechan 3/ Based 4/ Based 5/ Paymen of the wal sheathing 372	Energy POC prior to implementation. The licensed engineer/installer will provide aterial specifications which are used for these practices in order to certify that the m included in the energy audit and these energy savings must be entered into protracts int for linear foot of gap sealed by professional contractor inical screens for greenhouse to control heat loss and gain. upon square foot of tunnel opening. upon a minimum R-7 insulation in addition to existing attic/ceiling; All materials oth it based on square foot of <b>existing</b> wall insulated, <b>can also include foundation wa</b> where exhaust fans are located is not insulated. Only approved method of insulation. <b>Combustion System Improvement</b> Electric Motor/Centrifugal Pump in-lieu of IC Engine, < 100 hp 1/ Electric Motor in-lieu of IC Engine, less than 100 hp 2/	er than blown all or end walls on is metal external Each Each	t the work was nents in the energiest fiberglass insu- Typically only rior, 3.5" fiberg \$7,979.85 \$5,372.29	completed in acc rgy audit are acc ulation must be a portion of the lass batts (R-11)	approved by wall height is i , vapor barrier, \$9,575.82 \$6,446.74	Area Engineer. * Savings for eac Area Engineer. sulated (4 to 6') & interior plywoo	downer will h practice
brovide m must be ir 1/ Payme 2/ Mechar 3/ Based 4/ Based 5/ Payme of the wal sheathing 372	Energy POC prior to implementation. The licensed engineer/installer will provide aterial specifications which are used for these practices in order to certify that the m included in the energy audit and these energy savings must be entered into protracts int for linear foot of gap sealed by professional contractor inical screens for greenhouse to control heat loss and gain. upon square foot of tunnel opening. upon a minimum R-7 insulation in addition to existing attic/ceiling; All materials oth it based on square foot of existing wall insulated, can also include foundation wa where exhaust fans are located is not insulated. Only approved method of insulation where exhaust fans are located is not insulated. Only approved method of insulation combustion System Improvement Electric Motor/Centrifugal Pump in-lieu of IC Engine, < 100 hp 1/ Electric Motor in-lieu of IC Engine, less than 100 hp 2/ Electric Motor in-lieu of IC Engine, greater than or equal to 100 hp 3/	er than blown all or end walls on is metal exter Each HP	fiberglass inst fiberglass inst Typically only rior, 3.5" fiberg \$7,979.85 \$5,372.29 \$70.61	completed in acc rgy audit are acc ulation must be v a portion of the ass batts (R-11)	approved by wall height is i , vapor barrier, \$9,575.82 \$6,446.74 \$84.73	Area Engineer.	downer will h practice . The portion od or OSB 10 Years
brovide m must be in 1/ Paymei 2/ Mechar 3/ Based 4/ Based 5/ Paymei of the wal sheathing 372 Documen determine Must be s engine wa Must addr 1/ Surface 2/ Well	Energy POC prior to implementation. The licensed engineer/installer will provide aterial specifications which are used for these practices in order to certify that the m necluded in the energy audit and these energy savings must be entered into protracts int for linear foot of gap sealed by professional contractor nical screens for greenhouse to control heat loss and gain. upon square foot of tunnel opening. upon a minimum R-7 insulation in addition to existing attic/ceiling; All materials oth in based on square foot of existing wall insulated, can also include foundation wall where exhaust fans are located is not insulated. Only approved method of insulation where exhaust fans are located is not insulated. Only approved method of insulation is the required in-lieu of IC Engine, less than 100 hp 2/ Electric Motor in-lieu of IC Engine, greater than or equal to 100 hp 3/ tation requirements include; picture of the pumping unit being replaced that shows the required size of the new pump and/or motor; picture of the new pumping unit should by Certified Irrigation Designer (CID), Georgia PE, or Area Engineer as destroyed or salvaged. Payment will be made for the motor size required by the of the water	er than blown all or end walls on is metal external Each Each HP the pump model, s Documentation design or to nex rical work must	t the work was nents in the energy fiberglass insu- trypically only rior, 3.5" fiberg \$7,979.85 \$5,372.29 \$70.61 I and capacity; serial number a that engine ha t largest comm meet local and	total Dynamic H nd capacity; new as been replaced tate codes.	approved by wall height is i vapor barrier, \$9,575.82 \$6,446.74 \$84.73 ead calculation pump must be and evidence pump (ie 48 h	Area Engineer. Area Engineer. sulated (4 to 6') s interior plywoo s used by the de installed on con (i.e. picture) that p would be a 50	downer will h practice . The portion od or OSB 10 Years later to lacrete pad. . an older hp motor)
Documen determine Must be ir 1/ Paymer 2/ Mechar 3/ Based 4/ Based 5/ Paymer of the wal sheathing 372 Documen determine Must be s engine wa Must addr 1/ Surface 2/ Well 3/ Well or	Energy POC prior to implementation. The licensed engineer/installer will provide aterial specifications which are used for these practices in order to certify that the m included in the energy audit and these energy savings must be entered into protracts int for linear foot of gap sealed by professional contractor inical screens for greenhouse to control heat loss and gain. upon square foot of tunnel opening. upon a minimum R-7 insulation in addition to existing attic/ceiling; All materials oth in based on square foot of existing wall insulated, can also include foundation wall where exhaust fans are located is not insulated. Only approved method of insulated where exhaust fans are located is not insulated. Only approved method of insulated is the transport of the provement Electric Motor/Centrifugal Pump in-lieu of IC Engine, < 100 hp 1/ Electric Motor in-lieu of IC Engine, less than 100 hp 2/ Electric Motor in-lieu of IC Engine, greater than or equal to 100 hp 3/ tation requirements include; picture of the pumping unit being replaced that shows the required size of the new pump and/or motor; picture of the new pumping unit sh submitted by Certified Irrigation Designer (CID), Georgia PE, or Area Engineer as destroyed or salvaged. Payment will be made for the motor size required by the or eventse Surface water	er than blown all or end walls on is metal external Each Each HP the pump mode nowing model, s Documentation design or to nex rical work must	t the work was nents in the energy fiberglass insu- trypically only rior, 3.5" fiberg \$7,979.85 \$5,372.29 \$70.61 I and capacity; serial number a n that engine ha t largest comm meet local and	total Dynamic H nd capacity; new as been replaced ercially available state codes.	approved by wall height is i vapor barrier, \$9,575.82 \$6,446.74 \$84.73 ead calculation pump must be and evidence pump (ie 48 h	Area Engineer. Area Engineer. Area Engineer. sulated (4 to 6') s interior plywoo s used by the de installed on con (i.e. picture) that p would be a 50 l	downer will h practice . The portion od or OSB 10 Years later to hcrete pad. an older hp motor)
Documen determine Must be ir 1/ Paymei 2/ Mechar 3/ Based 4/ Based 5/ Paymei of the wal sheathing 372 Documen determine Must be 3 engine wa Must addr 1/ Surface 2/ Well 3/ Well or	Energy POC prior to implementation. The licensed engineer/installer will provide aterial specifications which are used for these practices in order to certify that the m neuluded in the energy audit and these energy savings must be entered into protracts in the intervention of gap sealed by professional contractor inical screens for greenhouse to control heat loss and gain. upon square foot of tunnel opening. upon a minimum R-7 insulation in addition to existing attic/ceiling; All materials other the based on square foot of existing wall insulated, can also include foundation was where exhaust fans are located is not insulated. Only approved method of insulated. Combustion System Improvement Electric Motor/Centrifugal Pump in-lieu of IC Engine, < 100 hp 1/ Electric Motor in-lieu of IC Engine, greater than or equal to 100 hp 3/ tation requirements include; picture of the pumping unit being replaced that shows is the required size of the new pump and/or motor; picture of the new pumping unit slaubmitted by Certified Irrigation Designer (CID), Georgia PE, or Area Engineer as destroyed or salvaged. Payment will be made for the motor size required by the certified and are quality resource concern; see eFOTG. All elect as water	ertification tha aterial requirem during ranking er than blown all or end walls on is metal exter Each Each HP the pump model, s Documentation design or to nex rical work must	fiberglass insu fiberglass insu . Typically only rior, 3.5" fiberg \$7,979.85 \$5,372.29 \$70.61 I and capacity; serial number a n that engine ha t largest comm meet local and	total Dynamic H nd capacity; new as been replaced estate codes.	approved by approved by approved by available in the second state of the second state	Area Engineer. Area Engineer. Area Engineer. sulated (4 to 6') % interior plywoo s used by the de installed on con (i.e. picture) that p would be a 50 l	downer will th practice . The portion od or OSB 10 Years aler to crete pad. . an older hp motor)
Documen determine Must be ir 2/ Mechar 3/ Based 4/ Based 5/ Paymer of the wal sheathing 372 Documen determine Must be s engine wa Must addr 1/ Surface 2/ Well 3/ Well or 317	Energy POC prior to implementation. The licensed engineer/installer will provide aterial specifications which are used for these practices in order to certify that the m included in the energy audit and these energy savings must be entered into protracts in for linear foot of gap sealed by professional contractor inical screens for greenhouse to control heat loss and gain. upon square foot of tunnel opening. upon a minimum R-7 insulation in addition to existing attic/ceiling; All materials oth in based on square foot of existing wall insulated, can also include foundation was where exhaust fans are located is not insulated. Only approved method of insulation where exhaust fans are located is not insulated. Only approved method of insulation is the exhaust fans are located is not insulated. Only approved method of insulated where exhaust fans are located is not insulated. Only approved method of insulation is the rectrice Motor/Centrifugal Pump in-lieu of IC Engine, < 100 hp 1/ Electric Motor in-lieu of IC Engine, less than 100 hp 2/ Electric Motor in-lieu of IC Engine, greater than or equal to 100 hp 3/ tation requirements include; picture of the pumping unit being replaced that shows the required size of the new pump and/or motor; picture of the new pumping unit si submitted by Certified Irrigation Designer (CID), Georgia PE, or Area Engineer is destroyed or salvaged. Payment will be made for the motor size required by the exist a documented energy or an air quality resource concern; see eFOTG. All elect e water Surface water	ertification tha aterial requirem during ranking er than blown all or end walls on is metal exter Each Each HP the pump model, s Documentation design or to nex rical work must	fiberglass insu fiberglass insu . Typically only rior, 3.5" fiberg \$7,979.85 \$5,372.29 \$70.61 and capacity; serial number a that engine ha t largest comm meet local and	total Dynamic H nd capacity; new as been replaced.	approved by approved by approved by available in the second secon	Area Engineer. Area Engineer. s used by the de installed on con (i.e. picture) that p would be a 50 l	downer will h practice
Documen determine Must beir 2/ Mechar 3/ Based 4/ Based 5/ Paymer of the wal sheathing 372 Documen determine Must be s engine wa Must addr 1/ Surface 2/ Well 3/ Well or 317	Energy POC prior to implementation. The licensed engineer/installer will provide aterial specifications which are used for these practices in order to certify that the m included in the energy audit and these energy savings must be entered into protracts in for linear foot of gap sealed by professional contractor inical screens for greenhouse to control heat loss and gain. upon square foot of tunnel opening. upon a minimum R-7 insulation in addition to existing attic/ceiling; All materials oth in based on square foot of existing wall insulated, can also include foundation was where exhaust fans are located is not insulated. Only approved method of insulation where exhaust fans are located is not insulated. Only approved method of insulation is the exhaust fans are located is not insulated. Only approved method of insulation where exhaust fans are located is not insulated. Only approved method of insulation is the rectrice Motor/Centrifugal Pump in-lieu of IC Engine, < 100 hp 1/ Electric Motor in-lieu of IC Engine, less than 100 hp 2/ Electric Motor in-lieu of IC Engine, greater than or equal to 100 hp 3/ tation requirements include; picture of the pumping unit being replaced that shows the required size of the new pump and/or motor; picture of the new pumping unit sis submitted by Certified Irrigation Designer (CID), Georgia PE, or Area Engineer is destroyed or salvaged. Payment will be made for the motor size required by the cess a documented energy or an air quality resource concern; see eFOTG. All elect water Surface water	ertification tha aterial requirem during ranking er than blown all or end walls on is metal exter Each Each HP the pump mode solution besign or to nex rical work must	fiberglass insu fiberglass insu fiberglass insu . Typically only rior, 3.5" fiberg \$7,979.85 \$5,372.29 \$70.61 and capacity; serial number a that engine ha t largest comm meet local and \$5.32 \$5.32	completed in acc rgy audit are acc ulation must be v a portion of the lass batts (R-11) total Dynamic H nd capacity; new as been replaced ercially available state codes.	approved by wall height is i , vapor barrier, \$9,575.82 \$6,446.74 \$84.73 ead calculation / pump must be and evidence pump (ie 48 h	Area Engineer. Area Engineer. s used by the de installed on com (i.e. picture) that p would be a 50 l	downer will h practice
brovide m must be ir 1/ Paymei 2/ Mechar 3/ Based 4/ Based 5/ Paymei of the wal sheathing 372 Documen determine Must be s engine wa Must addr 1/ Surface 2/ Well 3/ Well or 317	Energy POC prior to implementation. The licensed engineer/installer will provide aterial specifications which are used for these practices in order to certify that the m included in the energy audit and these energy savings must be entered into protracts in for linear foot of gap sealed by professional contractor inical screens for greenhouse to control heat loss and gain. upon square foot of tunnel opening. upon a minimum R-7 insulation in addition to existing attic/ceiling; All materials oth in based on square foot of existing wall insulated, can also include foundation was where exhaust fans are located is not insulated. Only approved method of insulation where exhaust fans are located is not insulated. Only approved method of insulation is used in the otor/Centrifugal Pump in-lieu of IC Engine, < 100 hp 1/ Electric Motor/Centrifugal Pump in-lieu of IC Engine, < 100 hp 3/ Electric Motor in-lieu of IC Engine, greater than or equal to 100 hp 3/ Electric Motor in-lieu of IC Engine, greater than or equal to 100 hp 3/ Etation requirements include; picture of the pumping unit being replaced that shows the required size of the new pump and/or motor; picture of the new pumping unit st submitted by Certified Irrigation Designer (CID), Georgia PE, or Area Engineer as destroyed or salvaged. Payment will be made for the motor size required by the cess a documented energy or an air quality resource concern; see eFOTG. All elect water Surface water Composting Facility Concrete floor, outer wood wall no bins Composter, whole concrete floor, wood or concrete bins Composter, whole concrete floor, no bins organic	er than blown all or end walls on is metal external Each Each HP the pump model, s Documentation design or to nex rical work must	t the work was hents in the end fiberglass insu- fiberglass insu- trior, 3.5" fiberg \$7,979.85 \$5,372.29 \$70.61 and capacity; serial number a that engine ha t largest comm meet local and \$5.32 \$5.85 \$3.75	total Dynamic H nd capacity; new as been replaced ercially available	approved by wall height is i , vapor barrier, \$9,575.82 \$6,446.74 \$84.73 ead calculation / pump must be and evidence pump (ie 48 h	Area Engineer. Area Engineer. sulated (4 to 6') s interior plywood s used by the de installed on con (i.e. picture) that p would be a 50 l	downer will h practice . The portion od or OSB 10 Years aler to crete pad. . an older hp motor)
brovide m must be ir 1/ Paymei 2/ Mechar 3/ Based 4/ Based 5/ Paymei of the wal sheathing 372 Documen determine Must be s engine wa Must addr 1/ Surface 2/ Well 3/ Well or 3/ Well or 3/ 317	Energy POC prior to implementation. The licensed engineer/installer will provide aterial specifications which are used for these practices in order to certify that the m included in the energy audit and these energy savings must be entered into protracts int for linear foot of gap sealed by professional contractor inical screens for greenhouse to control heat loss and gain. upon square foot of tunnel opening. upon a minimum R-7 insulation in addition to existing attic/ceiling; All materials other thased on square foot of existing wall insulated, can also include foundation was where exhaust fans are located is not insulated. Only approved method of insulation was where exhaust fans are located is not insulated. Only approved method of insulation is dottor in-lieu of IC Engine, less than 100 hp 2/ Electric Motor in-lieu of IC Engine, greater than or equal to 100 hp 3/ tation requirements include; picture of the pumping unit being replaced that shows the required size of the new pump and/or motor; picture of the new pumping unit sl submitted by Certified Irrigation Designer (CID), Georgia PE, or Area Engineer, is destroyed or salvaged. Payment will be made for the motor size required by the cess a documented energy or an air quality resource concern; see eFOTG. All elect is water Surface water Composting Facility Concrete floor, outer wood wall no bins Composter, whole concrete floor, no bins, organic non animal mortality composting (manure, ag by products). Use 316 scenario ce pad. Pay based on square foot of concrete pad post to post area. NRCS approv	ertification tha aterial requirem during ranking er than blown all or end walls on is metal exter Each Each HP the pump model nowing model, s Documentation design or to nex rical work must SqFt SqFt SqFt SqFt	t the work was nents in the energy fiberglass insu- fiberglass insu- trypically only rior, 3.5" fiberg \$7,979.85 \$5,372.29 \$70.61 and capacity; serial number a that engine has t largest comm meet local and \$5.32 \$5.85 \$3.75 al composting sive Nutrient Ma	completed in acc rgy audit are acc ulation must be / a portion of the lass batts (R-11) total Dynamic H nd capacity; new as been replaced ercially available state codes.	approved by wall height is i , vapor barrier, \$9,575.82 \$6,446.74 \$84.73 ead calculation pump must be and evidence pump (ie 48 h \$6.39 \$7.02 \$4.50 eeded), critical a required, if was	Area Engineer. Area Engineer. Area Engineer. sulated (4 to 6') is interior plywood sused by the de installed on con (i.e. picture) that p would be a 50 l area planting, mu ste is generated of	downer will h practice . The portion od or OSB 10 Years aler to hcrete pad. an older hp motor) 15 Years ulch and HUA on site.
brovide m must be in 1/ Paymei 2/ Mechar 3/ Based 4/ Based 5/ Paymei of the wal sheathing 372 Documen determine Must be s engine wa sheathing 2/ Well 3/ Well or 317 Only for r for entran	Energy POC prior to implementation. The licensed engineer/installer will provide aterial specifications which are used for these practices in order to certify that the micluded in the energy audit and these energy savings must be entered into protracts and for linear foot of gap sealed by professional contractor inical screens for greenhouse to control heat loss and gain. Upon square foot of tunnel opening. Upon a minimum R-7 insulation in addition to existing attic/ceiling; All materials othen to based on square foot of existing wall insulated, can also include foundation we where exhaust fans are located is not insulated. Only approved method of insulation. Combustion System Improvement Electric Motor/Centrifugal Pump in-lieu of IC Engine, < 100 hp 1/ Electric Motor in-lieu of IC Engine, less than 100 hp 2/ Electric Motor in-lieu of IC Engine, greater than or equal to 100 hp 3/ tation requirements include; picture of the pumping unit being replaced that shows the required size of the new pump and/or motor; picture of the new pumping unit si submitted by Certified Irrigation Designer (CID), Georgia PE, or Area Engineer is a documented energy or an air quality resource concern; see eFOTG. All elect is water Composting Facility Concrete floor, outer wood wall no bins Composter, whole concrete floor, mood or concrete bins Composter, whole concrete floor, no bins, organic To animal mortality composting (manure, ag by products). Use 316 scenario ce pad. Pay based on square foot of concrete pad post to post area. NRCS approv	er than blown all or end walls on is metal external Each Each Each HP the pump model, s Documentation design or to nex rical work must SqFt SqFt SqFt SqFt	fiberglass inst fiberglass inst . Typically only rior, 3.5" fiberg \$7,979.85 \$5,372.29 \$70.61 I and capacity; serial number a that engine hat t largest comm meet local and \$5.32 \$5.85 \$3.75 al composting sive Nutrient Ma	completed in acc rgy audit are acc ulation must be / a portion of the lass batts (R-11) total Dynamic H nd capacity; new as been replaced ercially available state codes.	approved by wall height is i , vapor barrier, \$9,575.82 \$6,446.74 \$84.73 ead calculation / pump must be d and evidence pump (ie 48 h \$6.39 \$7.02 \$4.50 eeded), critical a required, if was	Area Engineer. Area Engineer. Area Engineer. sulated (4 to 6') is interior plywood installed on con (i.e. picture) that p would be a 50 l area planting, mu ste is generated	downer will th practice . The portion od or OSB 10 Years rater to acrete pad. an older hp motor) 15 Years lich and HUA on site.
brovide m must be in 1/ Paymei 2/ Mechar 3/ Based 4/ Based 5/ Paymei of the wal sheathing 372 Documen determine Must be 3 engine wa Must addr 1/ Surface 2/ Well 3/ Well or 317 Only for r for entran-	Energy POC prior to implementation. The licensed engineer/installer will provide aterial specifications which are used for these practices in order to certify that the micluded in the energy audit and these energy savings must be entered into protracts and for linear foot of gap sealed by professional contractor inical screens for greenhouse to control heat loss and gain. Upon square foot of tunnel opening. Upon a minimum R-7 insulation in addition to existing attic/ceiling; All materials othen to based on square foot of existing wall insulated, can also include foundation we where exhaust fans are located is not insulated. Only approved method of insulation. Combustion System Improvement Electric Motor/Centrifugal Pump in-lieu of IC Engine, < 100 hp 1/ Electric Motor in-lieu of IC Engine, less than 100 hp 2/ Electric Motor in-lieu of IC Engine, greater than or equal to 100 hp 3/ tation requirements include; picture of the pumping unit being replaced that shows the required size of the new pump and/or motor; picture of the new pumping unit si submitted by Certified Irrigation Designer (CID), Georgia PE, or Area Engineer is a decumented energy or an air quality resource concern; see eFOTG. All elect is water Composting Facility Concret floor, outer wood wall no bins Composter, whole concrete floor, no bins, organic Tom animal mortality composting (manure, ag by products). Use 316 scenario ce pad. Pay based on square foot of concrete pad post to post area. NRCS approv	er than blown all or end walls on is metal external Each Each Each HP the pump model, s Documentation design or to nexrical work must SqFt SqFt SqFt SqFt	t the work was nents in the energy fiberglass insu- trypically only rior, 3.5" fiberg \$7,979.85 \$5,372.29 \$70.61 I and capacity; serial number a that engine ha t largest comm meet local and \$5.32 \$5.85 \$3.75 al composting sive Nutrient Ma	completed in acc rgy audit are acc ulation must be v a portion of the lass batts (R-11) total Dynamic H nd capacity; new as been replaced ercially available state codes.	approved by wall height is i vapor barrier, \$9,575.82 \$6,446.74 \$84.73 ead calculation pump must be and evidence pump (ie 48 h \$6.39 \$7.02 \$4.50 eeded), critical a required, if war	Area Engineer. Area Engineer. Area Engineer. sulated (4 to 6') is interior plywood installed on con (i.e. picture) that p would be a 50 l area planting, mu ste is generated of	downer will h practice . The portion od or OSB 10 Years later to horete pad. an older hp motor) 15 Years lich and HUA on site.

Manach Species Mit & dimensional and the second s	Practice Code	Conservation Practice	Payment Unit	Payment Rate	Maximum Amount	HU Payment Rate	HU Maximum Amount	Lifespan
Uncloaded Species 2/ Orchard of Vehandal Alloyang         Arra         512.465         61.40.87         Veam           1: Pelineter permenent experision is of value graces, legane, their, established on any land reading permenent experision and their period.         10.20         51.20<		Monarch Species Mix 4/	Acre	\$668.26		\$801.91		
Other of Viengeral Alleyages 3/         Annu         56.16         51.01.0         Y year           1 Policitary entransmin regarding industry regarding ind		Introduced Species 2/	Acre	\$124.65		\$149.59		
I Political presentation topedate the present expected on provide a particular or end on other control permanent expectation course. Description of the presence of the provide habitat to politicators. See the based control permanent expectation course. Description of the presence of the provide habitat to politicators. See the presence of the provide habitat to politicators. See the presence of		Orchard or Vineyard Alleyways 3/	Acre	\$86.16		\$103.40		3 Years
2) The particle applies to lead entime from applicature production and on other largers ended per particular. See Parage & Bornes Planting (512) if the purpose is to ended on entime in the particip entity entity of the second per particip entity entity of the second per particip entity entity of the second per particip entity entity of the second per particip entity entity of the second per particip entity entity of the second per particip entity entity of the second per particip entity entity of the second per particip entity entity of the second per particip entity entity of the second per particip entity entity of the second per particip entity entity of the second per particip entity entity of the second per particip entity entity of the second per particip entity entity of the second per particip entity entity of the second per particip entity entity entity entity of the second per particip entity en	1/ Pollinate Job sheet	or permanent vegetation, including mix of native grasses, legume, forbs, established specification on planting mix. Limited to 1 year.	d on any land n	eeding perman	ent vegetative co	over that provid	les habitat for po	llinators. See
a) Page anyoes reacting permeant protective cover in the alinyway to reduce ground and urface water problem. Payment made after estimating the process. Alter, there integers in the significant permeant active problem in the significant permeant active the align permeant active active permeant active the align permeant active active the align permeant active active the align permeant active active the align permeant active active the align permeant active active the align permeant active active the align permeant active active the align permeant active active the align permeant active active the align permeant active active the align permeant active active the align permeant active active active active active a	2/ This pra reduce erc	actice applies to land retiring from agricultural production and on other lands needing osion and sedimentation. The document is filed alphabetically in the FOTG. Limited	g permanent production of the second se	otective cover. ment made up	See Forage & E on planting.	Biomass Plantir	ng (512) if the pu	rpose is to
44 MCMACH Species:       Exableship permanent vegetable cover for polinearts laceraring to state specifications. Typically used for and purchase benchés. Les downer de la permanent maniche habitat may debin product cover for polinearts and velotifie. Typically used for an one state specifications. The typically used for an one state specifications. The typically used for an one state specifications. The typically used for an one state specifications. The typically used for an one state specification of the main state specification. Net typically used for an one state specification of the main state specifications. Net typically used for an one state specification of the main state specification. The typically used for an one specification. The typically used for an one specification of the state specification of the main state specification of the main state specification. The typically used for an one specification of the state specification of the state specification of the state specification. The typically used for an one policing leader to a state specification of the state specification of th	3/ Pecan g legume in provided b	proves needing permanent protective cover in the alleyway to reduce ground and su the spring by using UGA's Nitrogen Avaliability Calculator, or current recommended by the legume cover. Payment applies only to area planted to conservation cover. Li	rface water poll I laboratory ana imited to 1 year	ution. Paymer lysis, in a nutri	nt made after est ent budget for pe	imating the nitr ecans. Also, no	ogen contributior te degree of wee	n from the d control
Shifts practice spically includes conversion from a clean tilled (conventional tilled) interview cropping system to permanent native vagetation (scenario includes native grass). See native grass is the see grass of the set of the	4/ MONAF covered w beneficial plantings.	RCH Species: Establish permanent vegetative cover for pollinator habitat according ith permanent monarch habitat including a mix of milkweed species, native grasses insects and wildlife. Typically, used for conventional or organic land on small, intens	to state specifi , legumes, and ive areas that a	cations. Typica forbs. Plants so are central to sp	Ily used for high own for monarch pecialty crop pro-	quality nectar a habitat may a duction. Not typ	and pollen specie lso provide cover bically used for la	es. Land for rge scale
Applicable to Wildlife Landuse Only. Only native plannings allowed as supporting practice to Restoration and Management (R4s). Usefund Clearlon (R59), Wetland Restoration (R57), Wetland Wetland Handling Habitat.         328       Conservation Crop Rotation       Acre       54.20       55.03         329       Conservation Crop Rotation       Acre       54.20       55.03         320       Conservation Crop Rotation       Acre       54.20       55.03         320       Exerce Nation Crop Rotation       Acre       54.20       55.03         320       Conservation Crop Rotation       Acre       54.20       55.03         340       Conservation Crop Rotation       Acre       52.21       55.03       1 Your         1/2 'The training crops and Non-organic 1/       Acre       52.11       50.03       1 Your         340       Cover Crop - Basice and organic Anon-Organic       Acre       56.13       93.63       1 Your         341       Cover Crop - Basice and organic Anon-Organic       Acre       56.13       93.63       1 Your         342       Cover Crop - Basice and organic Anon-Organic       Acre       56.13       93.63       1 Your         344       Cover Crop - Basice and organic Anon-Organic       Acre       551.95       1 Your       1 Your         345	5/This praci jobsheet fo	ctice typically involves conversion from a clean tilled (conventional tilled) intensive c or specific specification for planting.	ropping system	to permanent	native vegetatio	n (scenario incl	udes native gras	s).See native
328         Conservation Crop Rotation         Accord         54.20         55.00           Basic Rotation - Organic and Non-organic 2/         Accord         52.237         526.85         1         1 Year           1/2/The rotation established adds higher residue cop(s) to the rotation in order to rotace excision, improve acil quality or break post cycles. Limited to two years. Payment after deviatating veed control through haves when the purpose is to roduce weed pressure. Follow UGA directions If managing other pests. Payment after harvest when the purpose is to roduce weed pressure. Follow UGA directions If managing other pests. Payment after harvest when the purpose is to roduce weed pressure. Follow UGA directions If managing other pests. Payment time copy pays is to roduce weed pressure. Follow UGA directions If managing other pests. Payment time to purpose is to roduce weed pressure. Follow UGA directions If managing other pests. Payment indee after documentation of cover crop Multiple Species Organic and Non-Organic         Acre         521.21         Strate         1         Year           Basic (1 cereal or legune) and multiple (2 or more species). Payment limited only to establishing a cover crop in a conservation tillage system. Payment indee after documentation of cover crop Multiple Species Organic and Non-Organic (2 Acre         Strate         Strate         Strate         1 Year           Basic (1 cereal or legune) and multiple (2 or more species). Payment limited only to establishing a cover crop is a conservation tillage system. Payment made after documentation of cover crop Multiple Species Organic and Non-Organic (2 Acre         Strate         Strate         Strate <t< td=""><td>Applicable Improvement</td><td>e to Wildlife Landuse Only. Only native plantings allowed as a supporting practice ent (395), Upland Wildlife Habitat Management (645), Wetland Creation (658), Wetl</td><td>to Restoration land Restoratio</td><td>and Managem n (657), or Wet</td><td>ent of Rare or De land Wildlife Ha</td><td>eclining Habitat bitat.</td><td>is (643), Stream</td><td>Habitat</td></t<>	Applicable Improvement	e to Wildlife Landuse Only. Only native plantings allowed as a supporting practice ent (395), Upland Wildlife Habitat Management (645), Wetland Creation (658), Wetl	to Restoration land Restoratio	and Managem n (657), or Wet	ent of Rare or De land Wildlife Ha	eclining Habitat bitat.	is (643), Stream	Habitat
Basic Restiton - Organic and Non-organic 1/ Bpecialty (rops - Organic and Non-organic 2// Part - Non-organic 2// 1/2/The residue crock) to the rotation in order to roduce erosion. Improve sol quality or break, pest cycles. Limited to two years. Payment after evaluating veed control through harvest when the purpose is to reduce weed pressure. Follow UGA directions II managing other pests. Payment after harvest when the purpose is to reduce a positive effect on adi characteristics.         If year         If year           340         Cover Crop- Dover Crop- Basic and organizem organic         Acre         581.37         573.65         If year           340         Cover Crop- Dover Crop- Basic and organizem organic         Acre         581.37         573.65         If year           341         Cover Crop- Dover Crop-Basic and organizem organic         Acre         581.37         573.65         If year           342         Circle J Multiple (2 or more specie). Payment limited only to establishing a cover crop in a conservation tillage system. Payment made after documentation of cover crop biomase at termination. May not to harvested for seed. Beging and control weeds. Limited to two years.         If year           342         Circle J Acre Planting         Acre         51.968.44         52.209.25         If year           343         Circle J Acre Planting         Acre         51.968.44         52.209.25         If year           344         Circle J Acre Planting         Acre         51.968.44         52.20	328	Conservation Crop Rotation						
Specialty Crops - Organic and Non-organic 2/         Acre         922.37         926.65         1 Year           1/2 The rotation established adds higher residue crop(s) to the rotation in order to reduce erosion, improve soil quality or break peet cycles. Limited to two years. Payment after evaluating weed control through harves them the puppes is to reduce weed pressure. Follow UAG directions if managing other pests. Payment after harvest when the puppes is to reduce weed pressure. Follow UAG directions if managing other pests. Payment after harvest when the puppes is to reduce weed pressure. Follow UAG directions if managing other pests. Payment after harvest when the puppes is to reduce weed pressure. Follow UAG directions if managing other pests. Payment after harvest when the puppes is to reduce weed pressure. Follow UAG directions if managing other pests. Payment after harvest weed pressure. Follow UAG directions if managing other pests. Payment marke after harvest weed pressure. Follow UAG directions if managing other pests weed pressure. Follow UAG directions if managing other pests weed to puppe and and wen-Organic Acre Sti 137         573.65           340         Cover Crop         Acre Sti 137         Sti 137         Sti 237.57         Treat           Basic (I coreal or loguna) and multiple (2 or more species). Payment limited on too be stabilishing a cover crop in advectors production system: control soil erosoft.         Sti 137         Sti 237.57         Sti 237.57         Treat         Year           342         Critical Area Planting         Acre Sti 368.64         \$22.050.65         Sti 31.7         To Years           342         Critical Area Planting		Basic Rotation - Organic and Non-organic 1/	Acre	\$4.20		\$5.03		1
1/2/ The rotation established adds higher residue crop(s) to the rotation in order to reduce arosion, improve soil quality or break pest cycles. Limited to two years. Payment after evaluating weed control through harvest when the purpose is to reduce weed pressure. Follow UGA directions if managing other pests. Payment after harvest when the purpose is to reduce weed pressure. Follow UGA directions if managing other pests. Payment take harvest when the purpose is to reduce weed pressure. Follow UGA directions if managing other pests. Payment take harvest when the purpose is to reduce arosin. Improve Soil Payment Take Taxa Soil Soil Soil Soil Soil Soil Soil Soil		Specialty Crops -Organic and Non-organic 2/	Acre	\$22.37		\$26.85		1 Year
340       Cover Crop       Image: Cover Cove	1/ 2/ The r evaluating have a pos	otation established adds higher residue crop(s) to the rotation in order to reduce ero weed control through harvest when the purpose is to reduce weed pressure. Follow sitive effect on soil characteristics.	osion, improve s v UGA direction	soil quality or bi is if managing o	reak pest cycles. other pests. Payı	Limited to two ment after harv	years. Payment est when the pup	after oose is to
340       Cover Crop Deside and organic/hon-organic       Acre       \$61.37       \$73.65         Cover Crop Multiple Species Organic and Non-Organic       Acre       \$77.19       \$86.63       1 Year         Basic (1 coreal or legume) and multiple (2 or more species). Payment limited only to establishing a cover crop in a conservation tillage system. Payment made after documentation of cover crop biomass at termination. May not be harvested for seed. See standard jobsheet for specific data regular for each purpose in this crop production system: control soil erosion inprove soil heath, increase so dinstrue, protect water quality/manage introgen and control weeds. Limited to two years.         342       Critical Area Planting       Acre       \$1.958.64       \$2.30.36         Perennial Soci Establishment       Sigrit       \$3.02.8       \$0.28       \$0.28         Vegetation-normal tillage (organic and Non-Organic) 1/       Acre       \$535.98       \$643.17       10 Years         Payment made after establishment of seedel vegetation or planting rooted vegetation. Limited to one year.       17.17       17.17       10 Years         27. Moderate grading includes cultipacking and light tillage is the only approved payment scenario for the widife fund pool.       10 Years         362       Diversion       F1       \$1.68       \$2.02       10 Years         17. Porvides early successional Habitat by moving in forested openings where existing vegetation neeeds to the management.       10 Years								
Cover Crop - Basic and organic/hon-organic         Area         551 37         \$73 65           Basic (1 crep Multiple Species Organic and Non-Organic         Area         \$77 19         \$86 63         1 Vear           Basic (1 cread or legund) and multiple (2 or more species). Perment limited only to establishing a cover crop in a conservation tillage system. Payment made after documentation of cover crop biomess at tensor burbaces of molecule. Provide limits only one set of the set of production system: control sole ensolmment on the cover production system: control sole ensolmment of set of the set of production system: control sole ensolmment of set of the set of production system: control sole ensolmment of set of the set of th	340	Cover Crop						
Cover Crop Multiple Species Organic and Non-Organic         Acre         \$72.19         \$86.63         1 Year           Basic (1 careal or legume) and multiple (2 or more species). Payment limited only to establishing a cover crop in a conservation bulges system. Payment made after documentation of nover crop binass at termination. May not be havested for seed. See standar jobsheet for specific date required for each purpose in this crop production system: control soil erosion. Improve soil health, increase sol moisture, protect water quality/manage nitrogen and control weeds. Limited to two years.           342         Critical Area Planting         Image: Control of the system control system: control soil erosion. The protein the crop production system: control soil erosion. The protein the comp production system: control soil erosion. The protein the comp production system: control soil erosion. The protein the comp production system: control soil erosion. The protein the comp production system: control soil erosion. The protein the comp production system: control soil erosion. The protein the comp production system: control soil erosion. The protein the comp production system: control soil erosion. The protein the comp production system: control soil erosion. The protein the comp production system: control soil erosion. The protein the comp production system: control soil erosion. The protein the comp production system: control soil erosion. The protein the comp production system: control soil erosion. The protein the comp production system: control soil erosion. The protein the comp production system: control soil erosistic. The protein the comp production system: control soil erosistic. The protein the comp production system: control soil erosistic. The protein the comp production system: control soil erosistic. The protein the comp protein the control socie astanding protein th		Cover Crop - Basic and organic/non-organic	Acre	\$61.37		\$73.65		
Basic (1 cereal or legume) and multiple (2 or more species). Payment limited only to establishing a cover crop in a conservation tillage system. Payment made after documentation of cover crop biomass at termination. May not be harvested for seed. See standard jobsheet for specific data required for each purpose in this crop production system: control soil erosion. Improve soil health, increase sol mosture, protect water quality/manage nitrogen and control weeds. Limited to two years.         342         Critical Area Planting         Quarter the system of the set of the set of the set of the set of the set of the system.         Visit of the set		Cover Crop Multiple Species Organic and Non-Organic	Acre	\$72.19		\$86.63		1 Year
342       Critical Area Planting       Acre       \$1,956.64       \$2,360.36         Perennal Soci Establishment       SqFt       \$0.23       \$0.26         Vegetation-normal tillage (Organic and Non-Organic) 1/       Acre       \$2,676.0       \$3321.12         Native and Introduced Vegetation - Moderate Grading 2/       Acre       \$\$535.98       \$\$643.17       10 Years         Payment made after establishment of seeded vegetation or planting rooted vegetation. Limited to one year.       1/ Normal Illiage includes cultipacking and lipht Illage is the only approved payment scenario for the widiffe fund pool.         7/ Normal Illiage includes cultipacking and ipht Illage is the only approved payment scenario for the widiffe fund pool.       Image and the stablishment of seeded vegetation and rule in the widiffe fund pool.         362       Diversion       Ft       \$1.68       \$2.02       10 Years         Includes grading and shaping. Need to add critical area planting and mulching (if needed)       Image and the stablishment.       Image and the stablish of the stable stable stable in the stable	Basic (1 co cover crop improve so	ereal or legume) and multiple (2 or more species). Payment limited only to establish biomass at termination. May not be harvested for seed. See standard jobsheet for pil health, increase sol moisture, protect water quality/manage nitrogen and control v	ing a cover cro specific data re weeds. Limited	p in a conserva quired for each to two years.	tion tillage syste purpose in this	m. Payment m crop production	ade after docum n system: control	entation of soil erosion,
342       Critical Area Planting       Area       \$1,956.64       \$22.30.36         Perennial Sod Establishment       SqFi       \$0.23       \$0.23       \$0.23         Vegetation-normal tillage (Organic and Non-Organic) 1/       Acre       \$267.60       \$3321.12       10         Native and Introduced Vegetation - Noderate Grading 2/       Acre       \$535.98       \$643.17       10 Years         Payment made after establishment of seeded vegetation or planting rooted vegetation. Limited to one year.       1/ Normal tillage includes cutipacking and light tillage       2/         2 Moderate grading includes cutipacking and light tillage is the only approved payment scenario for the widilfe fund pool.       362       0/version       Piversion       Pites       \$1.68       \$2.02       10 Years         362       0/version       Pites       \$1.68       \$2.02       10 Years         647       Early Successional Habitat Development/ Management       Acre       \$27.89       \$33.47       Acre       \$23.55       \$33.88       1 Year         1/ Provides early successional habitat by mowing in forested openings where existing vegetation needs to be maintained for early successional habitat. May also need 314 brush management, 666 forest stand improvement, 315 herbaceous weed control, 327 Conservation Cover, or 666 forest stand improvement, 315 herbaceous weed control, 327 Conservation Cover, or 666 forest stand improvement, 315 herbaceous weed control, 327 Co								
Grass Hydroseeding 1/       Acre       \$1,958,64       \$2,350,36         Perenals Got Establishment       SQFt       \$0.23       \$0.28         Vegetation-normal tillage (Organic and Non-Organic) 1/       Acre       \$2267,60       \$321,12         Native and Introduced Vegetation - Moderate Grading 2/       Acre       \$535,98       \$643,17       10 Years         Payment made after establishment of seeded vegetation or planting rooted vegetation. Limited to one year.       17.17       17.10       10 Years         Applicable to Wildlife Landuse Only. Native seeding -light tillage is the only approved payment scenario for the widlife fund pool.       Image: Comparison of the widlife fund pool.       Image: Comparison of the widlife fund pool.         362       Diversion       Ft       \$1.68       \$2.02       10 Years         Includes grading and shaping. Need to add critical area planting and mulching (if needed)       Image: Comparison of the widlife fund pool.       Image: Comparison of the widlife for adv successional habitat Development/ Management         4/4       Early Successional Habitat Development/ Management       Acre       \$27.89       \$33.47       Image: Comparison of the widlife for adv successional habitat. May also need 314 brush management, 666 forest stand improvement, 315 herbaceous weed control, 327 Conservation Cover, or 666 forest stand improvement, 315 herbaceous weed control, 327 Conservation Cover, or 666 forest stand improvement, 315 herbaceous weed control, 327 Conservation Cover, or 666	342	Critical Area Planting						
Performation       Style       39/26         Verification-normal tillage (Organic and Non-Organic) 1/       Acre       \$267.60       \$321.12         Native and Introduced Vegetation - Moderate Grading 2/       Acre       \$533.98       \$643.17       10 Years         Payment made after establishment of seeded vegetation or planting rooted vegetation. Limited to one year.       1/ Years       1/ Years         2/ Moderate grading includes cutipacking and buildozing       Applicable to Wildlife Landuse outpacking and buildozing         Applicable to Wildlife Landuse outpacking and buildozing       Ft       \$1.68       \$2.02       10 Years         includes grading includes cutipacking and buildozing       Ft       \$1.68       \$2.02       10 Years         includes grading and shaping. Need to add critical area planting and mulching (if needed)       Ft       \$1.68       \$2.02       10 Years         Includes grading 2/3       Acre       \$27.89       \$33.47       Acre       \$27.89       \$33.47       Year         1/ Provides early successional habitat bey moving in forested openings where existing vegetation needs to be maintained for early successional habitat.       Year       Year         1/ Provides early successional habitat by fixing vegetation and creating bare ground. May also need 314 brush management.       1/ Year       Year         1/ Provides early successional habitat by disking vegetati		Grass Hydroseeding 1/	Acre	\$1,958.64		\$2,350.36		
Native and introduced Vegetation - Moderate Grading 2/       Acre       State       10 Years         Payment made after establishment of seeded vegetation or planting rooted vegetation. Limited to one year.       1/ Normal tillage includes cutipacking and light tillage       10 Years         2/ Moderate grading includes cutipacking and bulldozing         Applicable to Wildlife Landuse Only. Native seeding -light tillage is the only approved payment scenario for the widlife fund pool.         362       Diversion       Ft       \$1.68       \$2.02       10 Years         Includes rading and shaping. Need to add critical area planting and mulching (if needed)         Includes grading and shaping. Need to add critical area planting and mulching (if needed)         Moving 1/ 3/       Acre       \$27.89       \$33.47         Moving 1/ 3/       Acre       \$27.89       \$33.47         Moving 1/ 3/       Acre       \$27.89       \$33.47         I/ Provides early successional habitat. Development/ Management         Moving 1/ 3/       Acre       \$27.89       \$33.47       1       Year         1/ Provides early successional habitat by mowing in forested openings where existing vegetation needs to be maintained for early suc		Vegetation-normal tillage (Organic and Non-Organic) 1/	Acre	\$267.60		\$321.12		
Payment made after establishment of seeded vegetation or planting rooted vegetation. Limited to one year.       11/ Normal tillage includes cultipacking and light tillage         2/ Moderate grading includes cultipacking and buildozing       Applicable to Wildlife Landuse Only. Native seeding -light tillage is the only approved payment scenario for the widlife fund pool.         362       Diversion       Ft       \$16.88       \$2.02       10 Years         Includes grading and shaping. Need to add critical area planting and mulching (if needed)       Ft       \$16.88       \$2.02       10 Years         647       Early Successional Habitat Development/ Management       Acre       \$27.89       \$33.47         Mowing 11       Acre       \$22.89       \$33.47       Year         1/ Provides early successional habitat by mowing in forested openings where existing vegetation needs to be maintained for early successional habitat. May also need 314 brush management, 666 forest stand improvement, 315 herbaceous weed control, 327 Conservation Cover, or 666 forest stand improvement, 315 herbaceous weed control, 327 Conservation Cover, or 666 forest stand improvement, 315 herbaceous weed control, 327 Conservation Cover, or 666 forest stand improvement, 315 herbaceous weed control, 327 Conservation Cover, or 666 forest stand improvement, 315 herbaceous weed control, 327 Conservation Cover, or 666 forest stand improvement, 315 herbaceous weed control, 327 Conservation Cover, or 666 forest stand improvement, 315 herbaceous weed control, 327 Conservation Cover, or 666 forest stand improvement, 315 herbaceous weed control, 327 Conservation Cover, or 666 forest stand improvement, 315 h		Native and Introduced Vegetation - Moderate Grading 2/	Acre	\$535.98		\$643.17		10 Years
Payment made after establishment of seeded vegetation or planting rooted vegetation. Limited to one year.  1/ Normal tillinge includes cutipacking and bulldozing  Applicable to Wildlife Landuse Only. Native seeding -light tillage is the only approved payment scenario for the wildlife fund pool.  362 Diversion Ft \$1.68 \$2.02 10 Years Includes grading and shaping. Need to add critical area planting and mulching (if needed)  647 Early Successional Habitat Development/ Management Moxing 11 3/ Disking 21 3	_			φ000.00		φ0+0.17		TO TOULO
Angenerating and undex outligation gath undex mays         21 Moderate grading includes cultipacking and buildozing         Applicable to Wildlife Landuse Only. Native seeding -light tillage is the only approved payment scenario for the wildlife fund pool.         362       Diversion         Diversion       Ft         547       Early Successional Habitat Development/ Management         Mowing 11 3/       Acre         Disking 2/ 3/       Acre         1/ Provides early successional habitat by mowing in forested openings where existing vegetation needs to be maintained for early successional habitat. May also need 314 brush management.         2/ Provides early successional habitat by mowing in forested openings where existing vegetation cover, or 666 forest stand improvement.         2/ Provides early successional habitat by mowing in forested openings where existing vegetation cover, or 666 forest stand improvement.         2/ Provides early successional habitat by mowing in forested openings where existing vegetation cover, or 666 forest stand improvement.         2/ Provides early successional habitat by mowing in forested openings where existing vegetation cover, or 666 forest stand improvement.         3/ Applicable to Wildlife Landuse Only. Allowed when planned as a supporting practice to 643, 644,645,or 666. This practice will not disturb high quality, natural habitat.         374       Farmstead Energy Improvement.         3/ Applicable to Wildlife Landuse Only. Allowed when planned as a supporting practice to 643, 644,645,or 666. This pra	Payment r	nade after establishment of seeded vegetation or planting rooted vegetation. Limited tillage includes cutinacking and light tillage	d to one year.					
Applicable to Wildlife Landuse Only. Native seeding -light tillage is the only approved payment scenario for the widlife fund pool.         362       Diversion       10 Years         Includes grading and shaping. Need to add critical area planting and mulching (if needed)       Ft       \$1.68       \$2.02       10 Years         647       Early Successional Habitat Development/ Management       Acre       \$27.89       \$33.47       1         Mowing 1/ 3/       Disking 2/ 3/       Acre       \$26.55       \$31.86       1 Year         1/ Provides early successional habitat by mowing in forested openings where existing vegetation needs to be maintained for early successional habitat. May also need 314 brush management, 666 forest stand improvement, 315 herbaceous weed control, 327 Conservation Cover, or 666 forest stand improvement, 315 herbaceous weed control, 327 Conservation Cover, or 666 forest stand improvement, 315 herbaceous weed control, 327 Conservation Cover, or 666 forest stand improvement, 315 herbaceous weed control, 327 Conservation Cover, or 666 forest stand improvement, 315 herbaceous weed control, 327 Conservation Cover, or 666 forest stand improvement, 315 herbaceous weed control, 327 Conservation Cover, or 666 forest stand improvement, 315 herbaceous weed control, 327 Conservation Cover, or 666 forest stand improvement, 315 herbaceous weed control, 327 Conservation Cover, or 666 forest stand improvement, 315 herbaceous weed control, 327 Conservation Cover, or 666 forest stand improvement, 315 herbaceous weed control, 527 \$4,998.33         3/ Applicable to Wildlife Landuse Only. Allowed when planned as a supporting practice to 643, 644,645,or 666. This practice will not distur	2/ Modera	te grading includes cultipacking and bulldozing						
362       Diversion       Ft       \$1.68       \$2.02       10 Years         Includes grading and shaping. Need to add critical area planting and mulching (if needed)       Ft       \$1.68       \$2.02       10 Years         647       Early Successional Habitat Development/ Management Mowing 11 3/ Disking 21 3/       Acre       \$27.89       \$33.47         1/ Provides early successional habitat by mowing in forested openings where existing vegetation needs to be maintained for early successional habitat. May also need 314 brush management. 666 forest stand improvement, 315 herbaceous weed control, 327 Conservation Cover, or 666 forest stand improvement.       1 Year         2/ Provides early successional habitat by disking vegetation and creating bare ground. May also need 314 brush management, 666 forest stand improvement.       327 Conservation Cover, or 666 forest stand improvement.         3/ Applicable to Wildlife Landuse Only. Allowed when planned as a supporting practice to 643, 644,645,or 666. This practice will not disturb high quality, natural habitat.       374         # armstead Energy Improvement       Each       \$16.68       \$188.01         Ventilation - Paddle Sir Fan       Each       \$41.65.27       \$4.989.33         Plate Cooler 549 gal/hr       Each       \$4.165.27       \$4.999.33         Plate Cooler 540 - 749 gal/hr       Each       \$4.860.01       \$5.832.01         Plate Cooler 540 - 749 gal/hr       Each       \$4.927.78       \$4.9999.	Applicabl	e to Wildlife Landuse Only. Native seeding -light tillage is the only approved paym	ent scenario fo	r the widlife fun	d pool.			
362       Diversion       Ft       \$1.68       \$2.02       10 Years         Includes grading and shaping. Need to add critical area planting and mulching (if needed)       Includes grading and shaping. Need to add critical area planting and mulching (if needed)       Includes grading and shaping. Need to add critical area planting and mulching (if needed)         647       Early Successional Habitat Development/ Management       Includes grading and shaping. Need to add critical area planting and mulching (if needed)       Includes grading and shaping. Need to add critical area planting and mulching (if needed)         647       Early Successional Habitat Development/ Management       Acre       \$27.89       \$33.47         1/ Provides early successional habitat by mowing in forested openings where existing vegetation needs to be maintained for early successional habitat. May also need 314 brush management, 666 forest stand improvement, 315 herbaceous weed control, 327 Conservation Cover, or 666 forest stand improvement.       2/ Provides early successional habitat by disking vegetation and creating bare ground. May also need 314 brush management, 666 forest stand improvement.         3/ Applicable to Wildlife Landuse Only. Allowed when planned as a supporting practice to 643, 644,645,or 666. This practice will not disturb high quality, natural habitat.         374       Farmstead Energy Improvement       Each       \$16.68       \$188.01         Yentilation - Paddle Stir Fan       Each       \$4,165.27       \$4,998.33         Plate Cooler 5499 gal/hr       Each								
Diversion       Ft       \$1.68       \$2.02       10 Years         Includes grading and shaping. Need to add critical area planting and mulching (if needed)       Image: Control of the end of the	362	Diversion		<b>.</b>		<b>A</b>		
647       Early Successional Habitat Development/ Management	Includes a	Diversion	Ft	\$1.68		\$2.02		10 Years
647       Early Successional Habitat Development/ Management       Acre       \$27.89       \$33.47         Mowing 1/ 3/ Disking 2/ 3/       Acre       \$27.89       \$33.47         1/ Provides early successional habitat by mowing in forested openings where existing vegetation needs to be maintained for early successional habitat. May also need 314 brush management, 666 forest stand improvement.       1 Year         2/ Provides early successional habitat by disking vegetation and creating bare ground. May also need 314 brush management, 666 forest stand improvement, 315 herbaceous weed control, 327 Conservation Cover, or 666 forest stand improvement, 315 herbaceous weed control, 327 Conservation Cover, or 666 forest stand improvement, 315 herbaceous weed control, 327 Conservation Cover, or 666 forest stand improvement, 315 herbaceous weed control, 327 Conservation Cover, or 666 forest stand improvement.         3/ Applicable to Wildlife Landuse Only. Allowed when planned as a supporting practice to 643, 644,645,or 666. This practice will not disturb high quality, natural habitat.         374       Farmstead Energy Improvement       Improvement         Ventilation - Paddle Stir Fan       Each       \$16,668       \$188.01         Plate Cooler 500 - 749 gal/hr       Each       \$4,165.27       \$4,998.33         Plate Cooler 7,000 - 4,999 gal/hr       Each       \$5,592.60       \$6,711.12         Plate Cooler 7,000 - 4,999 gal/hr       Each       \$9,279.78       \$11,135.73         Plate Cooler 7,000 - 4,999 gal/hr       Each	moluues y							
Wowing 1/ 3/ Disking 2/ 3/       Acre       \$27.89       \$33.47         Disking 2/ 3/       Acre       \$26.55       \$31.86       1 Year         1/ Provides early successional habitat by mowing in forested openings where existing vegetation needs to be maintained for early successional habitat. May also need 314 brush management, 666 forest stand improvement, 315 herbaceous weed control, 327 Conservation Cover, or 666 forest stand improvement, 315 herbaceous weed control, 327 Conservation Cover, or 666 forest stand improvement, 315 herbaceous weed control, 327 Conservation Cover, or 666 forest stand improvement, 315 herbaceous weed control, 327 Conservation Cover, or 666 forest stand improvement, 315 herbaceous weed control, 327 Conservation Cover, or 666 forest stand improvement, 315 herbaceous weed control, 327 Conservation Cover, or 666 forest stand improvement, 315 herbaceous weed control, 327 Conservation Cover, or 666 forest stand improvement.         3/ Applicable to Wildlife Landuse Only. Allowed when planned as a supporting practice to 643, 644,645,or 666. This practice will not disturb high quality, natural habitat.         374       Farmstead Energy Improvement         Ventilation - Paddle Stir Fan       Each       \$156.68       \$188.01         Plate Cooler 540 - 749 gal/hr       Each       \$4,165.27       \$4,998.33       1         Plate Cooler 500 - 749 gal/hr       Each       \$5,592.60       \$6,711.12       1         Plate Cooler 500 - 4,999 gal/hr       Each       \$9,279.78       \$11,135.73       1         Plate Cooler 1,000 - 4,999 ga	647	Early Successional Habitat Development/Management						
Import       Acre       \$27.89       \$33.47         Disking 2/ 3/       Acre       \$26.55       \$31.86       1 Year         1/ Provides early successional habitat by mowing in forested openings where existing vegetation needs to be maintained for early successional habitat. May also need 314 brush management, 666 forest stand improvement.       1/ Provides early successional habitat by disking vegetation and creating bare ground. May also need 314 brush management, 666 forest stand improvement.         2/ Provides early successional habitat by disking vegetation and creating bare ground. May also need 314 brush management, 666 forest stand improvement.       315 herbaceous weed control, 327 Conservation Cover, or 666 forest stand improvement.         3/ Applicable to Wildlife Landuse Only. Allowed when planned as a supporting practice to 643, 644,645,or 666. This practice will not disturb high quality, natural habitat.         374       Farmstead Energy Improvement         Ventilation - Paddle Stir Fan       Each       \$156.68       \$188.01         Plate Cooler 500 - 749 gal/hr       Each       \$4,165.27       \$4,998.33         Plate Cooler 750 - 999 gal/hr       Each       \$5,592.60       \$6,711.12         Plate Cooler 750 - 999 gal/hr       Each       \$9,279.78       \$11,135.73         Plate Cooler 7,000 - 4,999 gal/hr       Each       \$9,279.78       \$11,135.73         Plate Cooler 7,000 - 4,999 gal/hr       Each       \$9,279.78       \$11,135.73	047		A	<b>*</b>		A0- ···		
1/ Provides early successional habitat by mowing in forested openings where existing vegetation needs to be maintained for early successional habitat. May also need 314 brush management, 666 forest stand improvement, 315 herbaceous weed control, 327 Conservation Cover, or 666 forest stand improvement.         2/ Provides early successional habitat by disking vegetation and creating bare ground. May also need 314 brush management, 666 forest stand improvement, 315 herbaceous weed control, 327 Conservation Cover, or 666 forest stand improvement, 315 herbaceous weed control, 327 Conservation Cover, or 666 forest stand improvement, 315 herbaceous weed control, 327 Conservation Cover, or 666 forest stand improvement, 315 herbaceous weed control, 327 Conservation Cover, or 666 forest stand improvement, 315 herbaceous weed control, 327 Conservation Cover, or 666 forest stand improvement, 315 herbaceous weed control, 327 Conservation Cover, or 666 forest stand improvement, 315 herbaceous weed control, 327 Conservation Cover, or 666 forest stand improvement, 315 herbaceous weed control, 327 Conservation Cover, or 666 forest stand improvement, 315 herbaceous weed control, 327 Conservation Cover, or 666 forest stand improvement, 315 herbaceous weed control, 327 Conservation Cover, or 666 forest stand improvement, 315 herbaceous weed control, 327 Conservation Cover, or 666 forest stand improvement, 315 herbaceous weed control, 327 Conservation Cover, or 666 forest stand improvement, 315 herbaceous weed control, 327 Conservation Cover, or 666 forest stand improvement, 315 herbaceous weed control, 327 Conservation Cover, or 666 forest stand improvement, 315 herbaceous weed control, 327 Conservation Cover, or 666 forest stand improvement, 315 herbaceous weed control, 327 Conservation Cover, or 666 forest stand improvement, 315 herbaceous weed control, 327 Conservation Cover, or 666 forest stand improvement         374		Mowing 1/ 3/	Acre	\$27.89		\$33.47		1 Voor
3/ Applicable to Wildlife Landuse Only. Allowed when planned as a supporting practice to 643, 644,645,or 666. This practice will not disturb high quality, natural habitat.         3/ Applicable to Wildlife Landuse Only. Allowed when planned as a supporting practice to 643, 644,645,or 666. This practice will not disturb high quality, natural habitat.         3/ Applicable to Wildlife Landuse Only. Allowed when planned as a supporting practice to 643, 644,645,or 666. This practice will not disturb high quality, natural habitat.         Ventilation - Paddle Stir Fan       Each       \$156.68       \$188.01         Plate Cooler 5499 gal/hr       Each       \$4,165.27       \$4,998.33         Plate Cooler 750 - 999 gal/hr       Each       \$5,592.60       \$6,711.12         Plate Cooler 1,000 - 4,999 gal/hr       Each       \$9,279.78       \$11,135.73         HP       \$664.34       \$797.20       \$797.20	1/ Provide	s early successional habitat by mowing in forested openings where existing vegetations and sectors and	ion needs to be	maintained for	early successio	nal habitat. Ma	ı ay also need 314	brush
2/ Provides early successional nabitat by disking vegetation and creating bare ground. May also need 314 brush management, 666 forest stand improvement, 315 herbaceous weed control, 327 Conservation Cover, or 666 forest stand improvement.         3/ Applicable to Wildlife Landuse Only. Allowed when planned as a supporting practice to 643, 644,645,or 666. This practice will not disturb high quality, natural habitat.         374       Farmstead Energy Improvement         Ventilation - Paddle Stir Fan       Each       \$156.68       \$188.01         Plate Cooler ≤ 499 gal/hr       Each       \$4,165.27       \$4,998.33         Plate Cooler 500 - 749 gal/hr       Each       \$4,860.01       \$5,832.01         Plate Cooler 750 - 999 gal/hr       Each       \$5,592.60       \$6,711.12         Plate Cooler 1,000 - 4,999 gal/hr       Each       \$9,279.78       \$11,135.73         Scroll Compressor       HP       \$664.34       \$797.20	managem	enii, ooo torest stand improvement, 315 nerbaceous weed control, 327 Conservation	Lover, or 666	iorest stand in	iprovement.	tere el la		· · ·
3/ Applicable to Wildlife Landuse Only. Allowed when planned as a supporting practice to 643, 644,645,or 666. This practice will not disturb high quality, natural habitat.         374       Farmstead Energy Improvement         Ventilation - Paddle Stir Fan       Each         Plate Cooler 5499 gal/hr       Each         Plate Cooler 750 - 999 gal/hr       Each         Plate Cooler 1,000 - 4,999 gal/hr       Each         Scroll Compressor       HP	2/ Provide	s early successional habitat by disking vegetation and creating bare ground. May al 7 Conservation Cover, or 666 forest stand improvement	lso need 314 bi	ush managem	ent, 666 forest s	tand improvem	ent, 315 herbace	ous weed
3/ Applicable to Wildlife Landuse Only. Allowed when planned as a supporting practice to 643, 644,645,or 666. This practice will not disturb high quality, natural habitat.         374       Farmstead Energy Improvement       Image: Color State								
374       Farmstead Energy Improvement       Each       \$156.68       \$188.01         Ventilation - Paddle Stir Fan       Each       \$156.68       \$188.01         Plate Cooler ≤ 499 gal/hr       Each       \$4,165.27       \$4,998.33         Plate Cooler 500 - 749 gal/hr       Each       \$4,860.01       \$5,832.01         Plate Cooler 750 - 999 gal/hr       Each       \$5,592.60       \$6,711.12         Plate Cooler 1,000 - 4,999 gal/hr       Each       \$9,279.78       \$11,135.73         Scroll Compressor       HP       \$664.34       \$797.20	3/ Applica	ble to Wildlife Landuse Only. Allowed when planned as a supporting practice to 6	43, 644,645,or	666. This prac	tice will not distu	rb high quality,	natural habitat.	
Ventilation - Paddle Stir Fan         Each         \$156.68         \$188.01           Plate Cooler ≤ 499 gal/hr         Each         \$4,165.27         \$4,998.33           Plate Cooler 500 - 749 gal/hr         Each         \$4,860.01         \$5,832.01           Plate Cooler 750 - 999 gal/hr         Each         \$5,592.60         \$6,711.12           Plate Cooler 1,000 - 4,999 gal/hr         Each         \$9,279.78         \$11,135.73           Scroll Compressor         HP         \$664.34         \$797.20	374	Farmstead Energy Improvement						
Plate Cooler S 499 gai/hr       Each       \$4,165.27       \$4,998.33         Plate Cooler 500 - 749 gai/hr       Each       \$4,860.01       \$5,832.01         Plate Cooler 750 - 999 gai/hr       Each       \$5,592.60       \$6,711.12         Plate Cooler 1,000 - 4,999 gai/hr       Each       \$9,279.78       \$11,135.73         Scroll Compressor       HP       \$664.34       \$797.20		Ventilation - Paddle Stir Fan	Each	\$156.68		\$188.01		
Plate Cooler 300 - 149 gal/hr         Each         \$4,000.01         \$5,032.01           Plate Cooler 750 - 999 gal/hr         Each         \$5,592.60         \$6,711.12           Plate Cooler 1,000 - 4,999 gal/hr         Each         \$9,279.78         \$11,135.73           Scroll Compressor         HP         \$664.34         \$797.20		Plate Cooler 5 499 gal/hr	Each	\$4,165.27		\$4,998.33		
Plate Cooler 1,000 - 4,999 gal/hr         Each         \$9,279.78         \$11,135.73           Scroll Compressor         HP         \$664.34         \$797.20		Plate Cooler 750 - 999 gal/hr	Each	\$5.592 60		\$6.711 12		
Scroll Compressor         HP         \$664.34         \$797.20		Plate Cooler 1,000 - 4,999 gal/hr	Each	\$9,279.78		\$11,135.73		
		Scroll Compressor	HP	\$664.34		\$797.20		

Practice Code	Conservation Practice	Payment Unit	Payment Rate	Maximum Amount	HU Payment Rate	HU Maximum Amount	Lifespan
	Variable Speed Drive ≤ 50 HP	HP	\$282.21		\$338.66		
	Variable Speed Drive > 50 HP	HP	\$99.47	\$ 15,000.00	\$119.36	\$ 15,000.00	
	Automatic Controller System	Each	\$1,108.55	\$ 7,500.00	\$1,330.26	\$ 7,500.00	
	Motor Upgrade ≤ 2 HP	Each	\$570.48		\$684.58		
	Motor Upgrade > 2 and < 40 HP	Each	\$1,063.67		\$1,276.40		
	Motor Upgrade 40 and < 100 HP	Each	\$4,948.73		\$5,938.48		
	Motor Upgrade = or > 100 HP	Each	\$6,297.52		\$7,557.03		
	Vacuum Pump - Compatible w/Variable Speed	Each	\$3,467.79		\$4,161.34		
	Heating - Radiant Systems 1/	SqFt	\$0.47	\$ 40,000.00	\$0.56	\$ 40,000.00	
	Heating (Building) 2/	kBTU/Hr	\$9.59		\$11.51		
	Heating - Attic Heat Recovery vents	Each	\$115.39	\$ 10,000.00	\$138.47	\$ 10,000.00	
	Compressor Heat Recovery Unit	kBTU/Hr	\$2,887.29		\$3,464.75		
	Grain Dryer	BU/HR	\$73.52	\$ 50,000.00	\$88.22	\$ 50,000.00	10 Years

Practice must be a recommended practice in a Type 2 energy audit meeting the requirements of ANSI/ASABE S612, Completing An On Farm Energy Audit. The energy audit must have been completed within the last 4 years. Applicant must have certified audit completed before contract ranking to be eligible. Area Engineer will review all Farm Energy Improvement applications. Designs will be completed by third parties (Registered PE, TSP, etc) or Area Engineer; all designs must be submitted/approved by State Ag Eng or State Energy POC prior to implementation. All electrical practices requiring electrical wiring will be completed by licensed electrician. The licensed installer will provide certification that the work was completed in accordance with local and state codes. Landowner will provide material specifications which are used for these practices in order to certify that the material requirements in the energy audit are achieved. Energy Savings for each practice must be included in the energy audit and these energy savings must be entered into protracts during ranking.

1/ Replacement of pancake heaters or equivalent. Can use radiant tube heaters, radiant brooders heaters (aka round radiant heaters), or quad radiant heaters. Based upon square ft. of house.

2/ Natural gas, propane, or fuel oil unit heater or boiler; typic	ally for swine and greenhouse production.
---	---

382	Fence				
	Barbed/Smooth Wire	Ft	\$1.83	\$2.20	
	Woven Wire	Ft	\$2.44	\$2.93	
	Permanent Electric	Ft	\$0.97	\$1.16	
	Temporary Electric-Polywire	Ft	\$0.63	\$0.75	20 Years

515.81E(1)

Boundary fence (property line fence) or perimeter fence is eligible-

--- On expired or expiring Conservation Reserve Program (CRP) land to establish a grazing operation; however, practices may not be implemented until the CRP contract has expired. See section 515.52C regarding eligibility for EQIP on CRP.

--- On land to protect, restore, or enhance an environmentally sensitive area, such as a riparian area or wetland.

--- On land to facilitate a change in production systems per the requirements of section 515.81D(4). (see below).

### 515.81D(4)

(4) Changes in Production System

(i) Practices that facilitate a beneficial cost-effective change in production system (e.g., change in agricultural land use) provided that all of the following criteria are met:

• The change in production system results in a higher level of conservation benefit, such as a lower intensity land use

• The producer will implement a management practice that supports the change in production system

• The practices are necessary to address a natural resource concern that is associated with the new production system

Cost-effectiveness can be documented

(ii) Example 1.—Producer is transitioning highly erodible cropland to grazed pasture. The operation currently does not support or maintain livestock, but transitioning to grazed pasture will address erosion related resource concerns and result in a higher level of conservation benefit. Program support is allowed to implement fencing (CP 382), watering facility (CP 614), prescribed grazing (CP 528) and other facilitating practices that are necessary to establish the new production system and address the resource concern.

(iii) Example 2.—Producer is transitioning cropland to pastureland to address a resource concern resulting from overgrazing on part of the operating unit. At a minimum, the EQIP schedule of operations must include prescribed grazing (CP 528) to address resource concerns associated with livestock on the cropland being converted to grazing land. Other supporting or facilitating practices likely to be needed include forage and biomass planting (CP 512), watering facility (CP 614), fence (CP 382), or other practices identified that are necessary to address resource concerns associated with the conversion from cropland to grazing land. The conversion of cropland production system to a grazing production system reduces impact to the existing operating unit and also moderates erosion by lowering the intensity of use on the converted cropland field

Applicab	le to Wildlife Landuse Only. Allowed when planned as a supporting practice to Pr	escribed Grazi	ng (528) in conjunction v	vith Forest Stand Improvement (	(666), Restoration
			• • •		
386	Field Border				
	Field Boarder, Native Species 1/	Acre	\$90.79	\$108.95	
	Field Boarder, Pollinator 2/	Acre	\$133.83	\$160.60	
	Field boarder, Introduced Species 3/	Acre	\$65.21	\$78.25	10 Years
1/ Practic	e includes seedbed prep and planting of native species. The area of the field borde	er is taken out	of production.		
2/ Practic planting r	e includes seedbed prep and planting of pollinator friendly herbaceous species. Th ecommendations.	e area of the fi	eld border is taken out o	f production. See pollinator job	sheet for specific
3/ Practic	e includes seedbed prep and planting of introduced species. The area of the field b	oorder is taken	out of production.		
Applicab Biologist	le to Wildlife Landuse Only. Allowed when planted around active cropland and the variance to use non-native species if no suitable native species are available.	e area is taken	out of production . Nativ	ve species must be utilized . Mu	st request a State
393	Filter Strip				
	Filter Strip, Native species 1/	Acre	\$120.98	\$145.17	
	Filter Strip, Introduced species 2/	Acre	\$128.33	\$153.99	10 Years
Payment	made after establishment. Includes seedbed preparation. Limit one year.				
1/Native	herbaceous vegetation - Practice includes seedbed prep and planting.				
2/ Introdu	ced herbaceous vegetation. Practice includes seedbed prep and planting.				

Applicable to Wildlife Landuse Only. Only the Filter Strip payment scenaraio approvded for use under the wildlife fund pool. This practice will not disturb high quality, natural habitat.

Practice Code	Conservation Practice	Payment Unit	Payment Rate	Maximum Amount	HU Payment Rate	HU Maximum Amount	Lifespan
20.4	Firshrook						
394	Firebreak	<b>F</b> 4	¢0.00		¢0.00		
	Constructed - Dozer 1/	Ft	\$0.23		\$0.28 \$0.10		5 Years
la stall final	poonsi deled - Light Equipment 2/		ψ0.03		ψ0.10		0 10015
1/ track m	oreak as per required burn plan and according to the GFC GA Best Management Pr	actices for Fore	estry Manual.				
2/ rubber t	ired equipment						
512	Forage and Biomass Planting						
	Seedbed Prep. Seed & Seeding-Native Per. Warm Season Grass 1/	Acre	\$310.84		\$373.01		
	Seedbed Prep. Seed & Seeding-Intro. Perennial Grasses. 2/	Acre	\$216.17		\$259.40		
	Seedbed Prep. Seed & Seeding-Intro. Perennial Grasses Organic 3/	Acre	\$230.83		\$277.00		
		Acre	\$200.04		\$307.01 \$219.00		
	Overseeding Legumes 5/	Acre	\$182.41		\$218.90		
	Remediation-Seed and Seeding-Introduced Perennial Grasses 6/	Acre	\$86.34		\$103.61		5 Years
1/ Establis	h adapted perennial native warm season grasses. Used for either conventional or n	o-till seeding of	perennial nativ	/e warm season	grasses for pa	sture, hayland, a	nd wildlife
openings. 2/ Establis	This practice may be utilized for organic or regular production. This scenario assun	nes fertilizer, se scenario assur	ed, equipment	and labor for se eed, equipment	ed bed prep, til and labor for se	lage, seeding, ar eed bed prep, till	nd spreading. age, seeding
,and sprea	aling.	har annuantion		ling This prosti	an in for arrani	a production Th	
assumes f	ertilizer, seed, equipment and labor for seed bed prep, tillage, seeding ,and spreadi	ng.		ing. mis pracu			IS SCENARO
4/ Spriggir	ng new grasses with sprigging application. This scenario assumes fertilizer, sprigs,	equipment and	labor for seed	bed prep, tillage	, sprigging ,and	spreading.	f =
seeding a	and generating pasture. This practice may be utilized for organic or rend amendment spreading.	guiar production	n. This scenario	b assumes remin	zer, seed, equi	pment and labor	for no-tili
6/ Utilize v	when desirable perennial grass stands have thinned to less than 50% cover. Assess	s and documen	t baseline cond	lition using Pasti	ure Condition S	coring	
666	Forest Stand Improvement						
000							
	Pre-commercial Thinning - Hand tools 1/	Acre	\$85.33		\$102.39		
	Pre-Commercial Thinning-Mechanical 1/	Acre	\$44.18		\$53.01		
	Thinning for Wildlife and Forest Health at 50BA 2/3/	Acre	\$27.25		\$32.70		
	Thinning for Wildlife and Forest Health at 60BA 2/ 3/	Acre	\$20.92		\$25.11		
	Thinning for Wildlife Health at 70 BA 3/	Acre	\$13.88		\$16.66		10 Vears
1/ Adjusti	ng the stocking of a young, non-merchantable stand of trees. The operation is supe	rvised by a req	istered forester	. Mechancial eq	uipment can be	utilized to treat	ore-
commercia	al forest stand.	, ,			•		
2/Used to	open the canopy of a stand to improve the wildlife habitat and tree health by mecha	ancial equipmer	nt.				
3/4/5/6 Us	ed to open the canopy of a stand to improve the wildlife habitat and tree health.						
3/ <b>Applica</b> by the GA Restoratio Wetland V	ble to Wildlife Landuse Only. This practice scenario is approved for use under the Habitat Suitability Index model and comparisons with site appropriate Ecological Sin and Management of Rare or Declining Habitats (643), Stream Habitat Improveme Vildlife Habitat Management (644).	Wildlife fund p te Descriptions nt (395), Uplan	ool. This pract or other suitab d Wildlife Habit	tice will be imple le reference con at Management	mented accord ditions.Allowed (645), Wetland	ling to habitat nee as a supporting Restoration (65	eds identified practice to 7), or
655	Forost Trails and Landings						
655	Porest Trans and Landings	Each	¢00.04		¢109.05		
	Trail Frosion Control w/o Vegetation 2/	Foot	\$90.21		\$3.79		5 Years
Dual engi	neering/forestry practice, consult with NRCS Forestor and Engineer for design	n criteria; refei	ence PS560. /	Access Road fo	r design criter	ia.	
1/ Refer to	o Job Sheet				U		
2/ Grading	, shaping and installation of water deflectors to control sediment delivery to waterw	ays; not to be u	sed in conjunc	tion with waters	bar scenario.		
410	Grade Stabilization Structure		<b>.</b>		<b>A</b> 54.40		
	Check Dams 1/	Lon	\$45.08 \$4.25		\$54.10		
	Embankment, Pipe $< 12^{-24}$	Curd	\$4.25 \$4.56		\$5.10		
	Embankment Pine $> 36" 2/$	CuVd	.30 \$7 ΩF		φ0.40 \$0.40		
	Weir Drop Structures 3/	SaFt	\$64.22		\$77.06		
	Rock Drop Structures 3/	SqFt	\$49.25		\$59.10		15 Years
1/ Excavat	tion and riprap, does not include vegetation. Must add critical area planting and mul	lch.					
2/ Paymer 3/ Payme Biologist a	nt per cubic yard of embankment fill which includes fill, pipe system and outlet protect nt is based on weir length in feet times drop in "feet". The drop (feet) is defined as t and Assistant SCE for planning and design.	ction. Must add he structure inl	critical area pl et crest elevatio	anting and mulc on minus the cor	h. htrol outlet elev	ation. Consult w	ith State
Applicabl (666), Res Wetland V	e to Wildlife Landuse Only. Allowed when the planned purpose is wildlife habitat n storation and Management of Rare or Declining Habitats (643), Stream Habitat Impre Vildlife Habitat Management (644). This practice will not disturb high quality, pature	nanagement or ovement (395), I habitat	natural stream Upland Wildlife	restoration in co e Habitat Manag	onjunction with ement (645), W	Timber Stand Im /etland Restorati	provement on (657), or

Practice Code	Conservation Practice	Payment Unit	Payment Rate	Maximum Amount	HU Payment Rate	HU Maximum Amount	Lifespan
412	Grassed Waterway						
	Base Waterway 1/	Acre	\$2,661.84		\$3,194.20		10 1/2
1/ Gradino	Only. Must add critical area planting and mulch.	Acre	\$1,960.41		\$2,352.49	<u>.</u>	10 Years
2/ Includes	grading only and rock check dams. Must add critical area planting and mulch.						
561	Heavy Use Area Protection						
	Concrete with sand or gravel foundation 1/	Sq Ft	\$1.62		\$1.95		
	Rock/Gravel on Geotextile 2/	Sq Ft	\$1.15		\$1.38		10 Years
1/ 4" thick	fiber reinforced concrete pad						
2/ Includes	6" GAB, Geotextile, Grading and Shaping.						
Applicabl	e to Wildlife Landuse Only. Can be scheduled as a supporting practice in conjunct	tion with Prescr	ibed Grazing 5	28 when needeo	to protect wild	life or natural cor	nmunities.
422	Hedgerow Planting						
	Pollinator Habitat 1/	Ft	\$1.00		\$1.19		
	Wildlife Machine Plant 2/	Ft	\$0.41		\$0.49		15 Years
1/ A stand bloom peri establishm 2/ This sce species se	with a minimum of nine wildflower species and one native warm season grass shou ods (spring, summer, and fall). The stand should include a minimum of one legume tent jobsheet). Trees should be planted 12 foot apart and shrubs should be planted enario is for machine planting of woody species. A minimum of two species of nativ- lection and density goals) and a mix of 2 native grasses.	uld be establish especies and o <u>6 foot apart foll</u> e plants- 2 Tree	ed. This will in ne native buncl owing hedgero es and/or shrub	clude at least thi hgrass for a total w jobsheet spec os are typically pl	ree flowering sp l of ten or more ifications. ant at eight foo	becies from each species (see po t intervals (this w	of the three llinator vill vary with
Applicabl	e to Wildlife Landuse Only. Native species must be utilized . This practice will not	disturb high qu	ality, natural ha	bitat.			
315	Herbaceous Weed Control						
	Mechanical 1/	Acre	\$32.19		\$38.63		
	Chemical-Broad Band 2/	Acre	\$26.59		\$31.91		
	Chemical, Ground 3/	Acre	\$33.46		\$40.16		
	Invasive Chemical and Mechanical 4/	Acre	\$477.30		\$572.75	<u> </u>	5 Years
1/ Remova	al of herbaceous weeds by the use of mower brush hog disc, or light equipment in	order to reduce	fuel loading ar	nd improve ecolo	dical site condi	itions Weed has	exceeded
3/Eradicat improve eq 4/ Utilize a wildlife and	Jological conditions. Jological conditions. forestry mulcher, hydro axe, brush cutter, etc. mechancial equipment in combinatic d improve ecological condition.	y chemicals in c	Il/herbicides to	eliminate noxiou	s weeds, prom	ote forage produ	or wildlife and ctivity,
5/ Hand tre	eatment of sensitive habitats that could be damaged by broadcast treatment or heat	vy machinery us	se or where tre	atment areas are	e small.		
5/ Applica	ble to Wildlife Landuse Only. Only allowed when heavy invasion is present and ca	annot be adequ	ately treated by	y less expensive	alternatives.		
Applicabl	e to Wildlife Landuse Only. Method selected must have the least negative effect o	n desirable nat	ive vegetation				
325	High Tunnel System						
	High Tunnel	SqFt	\$2.89	\$ 7,000.00	\$3.47	\$ 7,000.00	4 Years
Costs are ONLY FO	based on purchase of manufactured kit and landowner installing the structure. Stru RORGANICAND HIGH TUNNEL INITIATIVES.	cture must be i	nstalled to mar	nufaturer's specif	ications. NOT	FOR GENERAL	EQIP,
420	Irrigation Pineline						
430		1.0	<b>.</b>		<b>AD</b> 10		00.V
Includes p	PVC (Iron Pipe Size) ipe, labor and equipment for placement. Add critical area planting and mulching wh	LB here needed.	\$1.80 Use spreadshe	et in section IV o	52.16 of EFOTG to co	nvert length of p	ipe to
pourius							
436	Irrigation Reservoir						
	Embankment Dam with On-Site Borrow 1/	CuYd	\$3.53	\$ 50,000.00	\$4.24	\$ 50,000.00	
	Embankment Reservoir ≤ 30 Acre-Feet 2/	CuYd	\$2.79	\$ 50,000.00	\$3.35	\$ 50,000.00	
1/ Earther	Plastic Tank 3/ n embankment built across a natural depression. Cost based upon volume of comp R IRRIGATION PILOT PROGRAM	Gal bacted earth fill.	\$1.14 Must add criti	cal area planting	\$1.37 and mulch. <b>N</b>	OT FOR GENEF	15 Years RAL EQIP,
2/ Excavat	ed reservoir, generally rectangular in shape. Must add critical area planting and mu	ulch. NOT FOR	GENERAL EG	IP, ONLY FOR	IRRIGATION F	PILOT PROGRA	<b>M</b> .
3/ Includes	s installation and a concrete pad. Pay per gallon of storage in tank. Use standard ta	ink closest in vo	plume to design	n volume.			
	Invitation System Misso						
441	Microiet 1/	Acre	\$2.077.46	\$ 30,000,00	\$2.402.00	\$ 30,000,00	
	Surface Micro with Screen Filter	Acre	\$1,109.00	\$ 30,000.00	\$1,330.80	\$ 30,000.00	
	Surface Micro with Sand Media Filter	Acre	\$1,220.36	\$ 30,000.00	\$1,464.43	\$ 30,000.00	

Practice Code	Conservation Practice	Payment Unit	Payment Rate	Maximum Amount	HU Payment Rate	HU Maximum Amount	Lifespan			
	Microirrigation High Tunnel	SqFt	\$0.16	\$ 30,000.00	\$0.19	\$ 30,000.00				
	SDI (Subsurface Drip Irrigation) 2/	Acre	\$1,466.91	\$ 30,000.00	\$1,760.30	\$ 30,000.00	15 Years			
vvater sup	by and conveyance from source to field is not addressed within this practice. An IW	VIM plan must r	be provided to	the landowner	when contrac	ting 441, but the	e IWM, PS Must have a			
engineers is not the Water qua	149, does not have to be included for payment in the EQIP contract. (High Tunnel is excluded). Producers may request an IWM Plan through the IWM CAP118. Must have a copy of system design completed and certified by a Certified Irrigation Designer (CID), Georgia PE, or Area Engineer. CID designs must be reviewed by NRCS engineers. Certification must be provided that system was installed in accordance with the certified design. Certification can be provided by the installer, provided the landowner is not the installer, the CID or field office staff. Irrigation conversion to micro irrigation system. Must be replacing existing non-microirrigation system. Does not include conveyance pipe from source to field under contract. Includes components for system including filters, control valves, flow meter (if required) and PVC pipe for laterals and sublaterals. Water quality testing (see PS and eFOTG) is required prior to design.									
1/ Orchard	ds/vineyards using above ground emitters or spray jets									
2/ Must ha	ave a GPS guidance system or markers placed for annual crops.									
119	Irrigation Water Management									
445	Basic IWM 1/	Acre	\$10.42		\$12.50		-			
	Intermediate IWM 2/	Acre	\$18.89		\$22.66					
	Advanced IWM 3/	Acre	\$24.56		\$29.47					
	Soil Moisture Sensors 4/	Each	\$69.51		\$83.42					
	Soil Moisture Sensors with Data Recorder 5/	Each	\$311.83		\$374.19					
	Variable Rate IWM	Acre	\$30.32		\$36.38		1 year			
Records	must be provided as outlined in the Irrigation Water Management Plan prior to	payment.								
1/ Low inte 1-year onl	ensity irrigation water management system. Soil moisture is determined by feel or o y).	ther similar met	thods; paymen	t after receipt of	1 growing seas	son of data (This	practice is for			
2/ Medium into a com (This prac	<ul> <li>intensity irrigation water management system. Soil moisture is determined by soil uputer program. Irrigation amounts determined by flow meters on system. Use in co tice is for 1-year only).</li> </ul>	moisture senso	rs with manual Soil Moisture S	data download. ensors; paymen	Records are k t after receipt c	ept by manual in f 1 growing seas	put of data on of data			
3/ High int system us	ensity irrigation water management system. Soil moisture determined by remote ming telemetry or mobile phone data system. Data is monitored daily and adjustment after receipt of 1 growing season of data (This practice is for 1-year only)	onitor soil moisi ts made accord	ture sensors. / ingly. Use in c	Automated loggir onjunction with S	ng of soil moist Soil Moisture So	ure data into con ensors with data	nputer logger;			
4/ Manual	ly read soil moisture sensors for use in the intermediate IWM scenario. Payment is f intract would be for 2 sensors.	or each individu	ual sensor; the	refore, if custome	er installs a sha	allow sensor and	a deep			
5/ Soil Mo	isture Sensors with automated data logging system for use in the advanced IWM so	enario. Use one	e set ner irriget	ion managemen	t unit					
			o oot por inigat	lon managemen						
460	Land Clearing									
	Heavy Equipment	Acre	\$1,326.01		\$1,591.21		10 Years			
For use w	ith Irrigation Reservoir only. NOT FOR GENERAL EQIP, ONLY FOR IRRIGATION	PILOT PROGR	RAM.							
670	Lighting System improvement	Fach	¢14.00	¢ 10.000.00	¢10.00	\$ 10.000.00				
	Lighting - CFL 1/	Each	\$14.06	\$ 10,000.00	\$10.89 \$21.67	\$ 10,000.00	-			
		Lach	\$10.00	\$ 10,000.00	φ21.07 Φ246.00	\$ 10,000.00				
	Lighting - Linear Fluorescent Lighting - Pulse-Start Metal Halide	Each	\$204.15	\$ 10,000.00	\$23.99	\$ 10,000.00	-			
	Automatic Controller System	Each	\$202.60	\$ 2,000.00	\$243.11	\$ 2,000.00				
	Poultry House Lighting 2/	SqFT	\$0.04	\$ 6,000.00	\$0.05	\$ 6,000.00	10 year			
Practice in	nust be a recommended practice in a Type 2 energy audit meeting the requirements	OF ANSI/ASAB	E S 612, Com	pleting An On Fa	Im Energy Auc	udit completed l	luait must			
contract ranking to be eligible. Area Engineer will review all Farm Energy Improvement applications. Designs will be completed by third parties (Registered PE, TSP, etc) or Area Engineer; all designs must be submitted/approved by State Ag Eng or State Energy POC prior to implementation. All electrical practices requiring electrical wiring will be completed by licensed electrician. The licensed installer will provide certification that the work was completed in accordance with local codes. Landowner will provide material specifications which are used for these practices in order to certify that the material requirements in the energy audit are achieved; and, self-certification that these measures were installed in the correct quantities. Energy Savings for each practice must be included in the energy audit and these energy savings must be entered into protracts during ranking. Lifespan should be considered when selecting item to cost share.										
1/ Lightin	g design requires additional lighting and wiring to implement.									
2/ Square	footage is based upon the size of the poultry house; based upon the scenario	of a one for o	ne exchange (	of bulbs in the h	nouse; no wiri	ng required.				
468	Lined Waterway or Outlet									
	Turf Reinforced Matting 1/	SaFt	\$0.64		\$0.76					
	Rock Lined - 12"or less 2/	SqFt	\$2.88		\$3.45		15 Years			
1/Pavmor	t is for SE of waterway. Includes grading and shaping of waterway and installation of	f a nermanent	erosion control	mat (TRM) Mu	st add critical c	area planting and	mulching			
2/ Pavmer	t is for SF of waterway. Includes grading and shaping of waterway and installation	of rock ripap wit	th geotextile he	eneath it. Must a	dd critical area	planting and mu	ilchina.			
			J. Hernie De				3.			
516	Livestock Pipeline									
		_					1			
H	PVC (Iron Pipe Size) Linear	IFt	\$1 29		\$1.55		20 Years			
This prop	PVC (Iron Pipe Size) Linear	Ft	\$1.29	et for any pipe th	\$1.55	equirements of C	20 Years			

Practice Code	Conservation Practice	Payment Unit	Payment Rate	Maximum Amount	HU Payment Rate	HU Maximum Amount	Lifespan
<b>Applicabl</b> and Mana Habitat Ma	e to Wildlife Landuse Only. Must be planned in conjunction with Prescribed Grazir gement of Rare or Declining Habitats (643), Stream Habitat Improvement (395), Up anagement (644). This practice will not disturb high quality, natural habitat.	ng (528) when p land Wildlife Ha	olanned in conj abitat Manager	unction with Tim nent (645), Wetla	ber Stand Impr and Restoration	ovement (666), F n (657), or Wetlar	Restoration nd Wildlife
576	Livestock Shelter Structure						
	Portable Shade Structure	SqFt	\$2.99	\$ 2,200.00	\$3.59	\$ 2,200.00	
	Prefabricated Portable Shade Structure	SqFt	\$3.58	\$ 2,600.00	\$4.29	\$ 2,600.00	10 Years
Applicabl	e to Grazing Landuse Only. Grassland Conservationist must be contacted for	design require	ments. This p	ractice must be u	used in conjund	ction with exclusion	on of animals
from sens	itive areas, when applicable.						
40.4	Malakima						
484	Mulching						
	Natural Material - Full Coverage 2/	Acre	\$332.41		\$398.89		
	Erosion Control Blanket 1/	SqFt	\$0.14		\$0.17		
	Synthetic Material 3/	Acre	\$675.97		\$811.17		1 Year
1/ Blanket cover.	is typically made of coconut coir, wood fiber, straw and is typically covered on both	sides with poly	propylene netti	ng. Used to help	control erosior	1 and establish ve	∋getative
2/ Mulch p	rovides full coverage using natural materials and is typically used with critical area p	planting. Assun	nes 125 bales/	acre (3 bales/10	00 sq ft). Paym	ent limit \$2,000 p	per contract.
3/ Installat	ion of geotextile, biodegradable plastic, polyethylene plastic, or other state approved	d synthetic mulo	ch to conserve	soil moisture, mo	oderate soil ter	nperature, suppre	ess weed
growth an	d provide erosion control. Payment based on actual area covered by mulching mate	rial. Payment II	mit \$2,000 per	contract.			·· · · (0.40)
Stream Ha	e to Wildlife Landuse Only. Allowed when planned in conjunction with Timber Star abitat Improvement (395), Upland Wildlife Habitat Management (645), Wetland Res incerns.	toration (657), c	or Wetland Wil	dlife Habitat Manag	agement of Rare	or Declining Hac to reduce short-	term soil
590	Nutrient Management				-		
	Basic NM System 1/	Acre	\$2.28		\$2.74		
	Basic NM system with manure injection or incorporated 2/	Acre	\$15.86	-	\$19.04		
	Basic NM system with manure and/or Compost 3/	Acre	\$4.05		\$4.85		4. V
	Small Farm NM 4/	Acre	\$115.91		\$139.10		1 Year
plant cove Payment r	ed nutrient management (NM) system will meet the current 590 standard. Records r crop, Code 340, for crop land, but not hay and pasture land. Use the Georgia Phe nade upon implementation of the NM system. Limit 2 years.	demonstrating osphorous Inde	mplementatio	n of the 4 R's of t inned rates of ph	osphorous exc	eeds UGA recom	Must also imendations.
1/ Basic s test and 5	ystem - Conventional or organic. There is no application of manure. Follow the resul 90 Nutrient Management Standard.	Its of a soil test	to develop a n	utrient managem	ient plan to app	oly fertilizer accor	ding to soil
2/ Basic s to conserv injection. ( Laboratory	ystem with the application of manure. All nutrient sources (except micronutrients) induction tillage systems. Applicable to other sytems where manure is applied to the soi Conventional or organic. Follow the results of a soil test to develop a nutrient manage analysis of organic nutrient sources required.	corporated with il surface. Also, jement plan to a	tillage at least applicable wh apply nutrients	3-4 in. deep or in ere manure is ind according to the	njected at least corporated with Nutrient Mana	t 4-6 in. deep. No ı tillage, but want gement 590 Stan	t applicable to adopt idard.
3/ Basic s	ystem with manure and/or compost. Also applies to systems relying totally on manu to the 590 Nutrient Management Standard. Laboratory analysis required for organic	re or compost. ( e fertilizer source	Conventional c es.	or organic. Follow	the results of	a soil test to appl	y nutrients
4/ Small fa	arm system (10 acres or less). Conventional or organic. Follow the results of a soil te	est and laborate	ory analysis of	organic fertilizer,	if applied. App	ly nutrients accor	rding to the
521C	Pond Sealing or Lining - Bentonite Sealant						
	Bentonite Treatment - Covered	CuYd	\$62.14		\$74.57		15 Years
Payment f waste stor	or installation of a liner treated with bentonite and a protective compacted fill cover.	Payment volur	me is the sum	of the volume of	the liner and th	e volume of the c	over. For
521D	Pond Sealing or Lining - Compacted Clay Treatment						
	Material Onsite 1/	CuYd	\$10.04		\$12.05		15 Years
	Material Hauled 2/	CuYd	\$16.47		\$19.77		
1/ Paymer	nt for installation of a compacted clay liner and protective cover using <b>on site</b> materi	als. Volume is	sum of liner ar	nd cover volumes	s. For waste st	orage ponds and	l lagoons
only. 2/ Paymer only.	nt for installation of a compacted clay liner and protective cover using imported mat	erials. Volume	is sum of liner	and cover volum	nes. For waste	storage ponds a	ind lagoons
521B	Pond Sealing or Lining - Soil Dispersant						
	Soil Dispersant - Covered	CuYd	\$3.67		\$4.41		20 Years
Payment f	or installation of a liner treated with soil dispersant and a protective compacted fill cluster and be added and be adde	over. Payment	volume is the	sum of the volum	he of the liner a	ing the volume of	the cover.
338	Prescribed Burning						
	Prescribed Burn 1/	Acre	\$20.66		\$24 79		1
	Prescribed Burn - High Risk 2/	Acre	\$30.04		\$36.05		1 Year

Practice Code	Conservation Practice	Payment Unit	Payment Rate	Maximum Amount	HU Payment Rate	HU Maximum Amount	Lifespan
1/ Burn ac cost of bu	cording to designed burn plan and NRCS Prescribed Burning (338) standard and sprn.	pecifications. S	Site prep burns	are included. Co	onstructed fireb	reak cost is not in	icluded in
2/ Prescrit burn paln	bed burns conducted when herbaceous vegetation (grasses and forbs) is actively gr and NRCS Prescribed Burning (338) standard and specifications. Constructed fireb	owing during su reaks cost is no	ummer months ot included in co	of June through ost of burn.	September. Bu	urn according to c	lesigned
<b>Applicabl</b> Stream Ha will be cor burn plan	e to Wildlife Landuse Only. Allowed when planned in conjunction with Timber Star abitat Improvement (395), Upland Wildlife Habitat Management (645), Wetland Res aducted within the natural variability of the ecological system being restored/manage and NRCS Prescribed Burning (338) standard and specifications and according to t	nd Improvemen toration (657), d d. Where nece he GFC GA Be	nt (666), Restor or Wetland Wild ssary, plan in c st Managemen	ation and Manag Ilife Habitat Mar onjunction with t Practices for F	gement of Rare nagement (644) Firebreak (394) orestry Manual	or Declining Hab and in a manner Burn according Site prep burns	itats (643), that burns to designed are included.
528	Prescribed Grazing		-				
	Standard 1/	Acre	\$11.88		\$14.25		1 Voor
1/ Design	and implementation of a grazing system using a 5 to 10 day rotation. Monitoring &	record keeping	az4.07	hoto points pre	and post grazin	a heights and o	
Pasture C	ondition Scoring).	record keeping	required (ex. p	noto pointo, pre		ig neights, and of	
2/ Design once annu	and implementation of a grazing system using a 4 day or less rotational cycle. Mon al Pasture Condition Scoring).	itoring and reco	ord keeping req	uired (ex: photo	points, pre and	d post grazing hei	ights, and
<b>Applicabl</b> Managem Habitat Ma	e to Wildlife Landuse Only. Allowed when planned for habitat restoration or manage ent of Rare or Declining Habitats (643), Stream Habitat Improvement (395), Upland anagement (644).	gement purpos Wildlife Habita	es in conjunctic t Management	n with Timber S (645), Wetland	tand Improvem Restoration (65	ent (666), Restor 57), or Wetland V	ation and Vildlife
533	Pumping Plant						
	Electric-Powered Pump ≤ 5 Hp 1/	внр	\$661.78		\$794.14		
	Electric-Powered Pump ≤ 5 HP with Pressure Tank 2/	BHP	\$1,404,56		\$1.685.47		
	Electric-Powered Pump >5 HP<=30 hp 3/	BHP	\$399.11		\$478.93		
	Electric-Powered Pump <30 hp <=75 4/	BHP	\$278.32		\$333.98		
	Electric-Roward Rump >75.5/	внр	\$157.95		\$189.54		
	Variable Frequency Drive 6/		\$107.90 \$192.60		\$109.04		
	Internal Combustion-Powered Pump < 50HP 7/	BHP	\$533.59		\$640.31		
	Internal Combustion-Powered Pump > 50 to 70 HP 7/	BHP	\$399.93		\$479.92		
	Internal Combustion-Powered Pump > 70 HP 7/	BHP	\$309.21		\$371.05		
	Photovoltaic-Powered Pump 8/	BHP	\$6.962.04		\$8.354.45		15 Years
Payment well pump will be the	will be made for the pump size required by the design for the pump rounded to next s the size for payment will be determined by the watering facility design spreadshee applicant's responsibility. All electrical work must meet local and state codes.	largest comments. If the application	rcially available ant wishes to us	pump (ie 1.67 h e a larger pump	np would be a 2 than the desig	.0 hp pump). In t n requires, the ac	he case of dditional cost
2/ Pump in	n well for livestock water or irrigation with pressure tank added.						
3/ Pump fo	or livestock water, waste transfer or irrigation. Centrifugal Pump.						
4/ Pump fe	or waste transfer or irrigation. Centrifugal Pump.						
5/ Pump fo	or livestock or irrigation. Centrifugal Pump.						
6/ Cost inc	cludes VFD modifications only. n and Ag Waste Transfer: Use only when not economically feasible to use elect	ric motor/num	n combination	15			
8/ Typical	installation of photvoltaic cells to run, solar pump (includes pump): Option only who	en there is no	available pow	er source and r	not economica	to run power to	o site.
Economic	cal threshold to run power must exceed \$10,000 to be feasible.						
Annlinghi	e te Wildlife Lenduce Only Can be askeduled as a supporting practice in estimat	tion with Draca	ibad Crazing E			life or notural cor	n muniti n n
Арріїсарі	e to wildlife Landuse Only. Can be scheduled as a supporting practice in conjunct	tion with Prescr	fibed Grazing 5	28 when heeded	a to protect wild	life of natural con	nmunities.
329	Residue & Tillage Mgmt - Notill/Striptill Direct Seed						
	No-Till/Strip-Till	Acre	\$14.31		\$17.17		1 Year
Limited to	2 years. Payment made when cash cron is seeded/planted with po-till drill or po-till/	strin-till planter	into cover crop	residue			
Svetom is	applicable in all cropland and land where crops are planted						
System is	applicable in all cropiand and land where crops are planted.						
643	Restoration and Mot. of Rare and Declining Habitats						
	Habitat Monitoring and Mgt. Low Intensity and Complexity	Acre	\$2.26		\$2.71		
	Rare or Dec. Habitat Monitoring and Mgt, Medium Intensity 1/	Acre	\$8.41		\$10.10		
	Habitat Monitoring and Mgt, High Intensity and Complexity 1/	Acre	\$15.68		\$18.81		
	Dev.of Shallow Micro-Topo Features with Normal Farm Equip 2/	Acre	\$28.70		\$34.44		
	Dev.of Deep Micro-TopoFeatures with Heavy Equipment 2/	Acre	\$78.19		\$93.82		1 Year
1/ Application will be publication	able to Wildlife Landuse Only. Requires a monitoring plan, an approved agreemen blicly available.	nt with the moni	toring organiza	tion, and a signe	ed landowner re	lease agreeing th	nat the data
2/ Applica Ecological	able to Wildlife Landuse Only. Restore and manage according to habitat needs ide Site Descriptions or other suitable reference conditions.	entified by the G	GA Habitat Suita	ability Index mod	del and compari	isons with site ap	propriate
391	Riparian Forest Buffer						
	Bare-root, hand planted 1/	Acre	\$191.22		\$229.46		
1	Bare-root, machine planted 2/	Acre	\$207.60		\$249.12		15 Years

Practice Code	Conservation Practice	Payment Unit	Payment Rate	Maximum Amount	HU Payment Rate	HU Maximum Amount	Lifespan			
1/ The buf hardwood	I/ The buffer will be located adjacent to and up-gradient from a watercourse or water body extending a minimum of 40 feet wide. The planting will consist of hand planted bare-root nardwood trees. One third of the area will be planted to each woody plant type. Tree spacing will be 12' x 12'.									
2/ The buf hardwood	fer will be located adjacent to and up-gradient from a watercourse or water body extrees. One third of the area will be planted to each woody plant type. Tree spacing	tending a minim g will be 12' x 12	um of 40 feet v	vide. The plantir	ng will consist c	of machine plante	ed bare-root			
558	Roof Runoff Structure	l nEt	¢4 32		\$5.19					
	Concrete Curb 2/	Lint	\$8.02		\$9.63		ĺ			
	Trench Drain 3/	LnFt	\$7.69		\$9.23					
	Roof Gutter with storage tank 4/	Gal	\$1.17		\$1.40		15 Years			
1/ Price of		00.	<u> </u>		<u> </u>					
2/ Price of	length of concrete curb.									
3/Price of	length of trench drain.									
4/ Pay per	gallon of storage in tank. Use standard tank closest in volume to design volume.	Cost includes le	ength of roof gu	tter.						
- 07										
367	Roots and Covers	CoEt.	¢6.42		¢7.70					
	Post Frame Building 1/	SaFt	\$5.27	\$ 50,000,00	\$6.32	\$ 50,000,00	10 Years			
1/ Posts a	of roof system with concrete footers at support posts. Square footage is measured	noet to post	ψυ.Ζι	φ 30,000.00	ψ0.02	φ 30,000.00				
2/ Posts a measured structure.	Ind roof system with concrete footers at support posts. Steel frame buildings must b post to post. Must provide additional information as to why a steel frame building is	be designed and needed (e.g m	t installation centering fire code	rtified by a regist ) rather than the	ered Georgia F less expensive	'E. Square foota e wooden post fra	ige is ame			
381	Silvopasture						<b>[</b>			
	Commercial thinning and establishment of introduced grasses. 1/	Acre	\$215.53		\$258.63					
	Tree Establishment 2/	Acre	\$80.33		\$95.06					
<u> </u>	Commercial Thinning and Establishment of Native Grass 3/	Acre	\$188.36		\$226.03		20 Years			
of 200 tree 3/ Comme establishm	es per acre. Arcial thinning of an existing stand of trees followed by establishment of native grasses nent. For the Sandhills, Coastal Plain, and Flatwoods Regions native grasses is the	ses. Thinning sl recommended	hould be to a ba forage species	asal area of 30 to . For the Ridge	50. Cost incluand Valley and	udes native grass Blue Ridge Reg	s ions native			
grasses ar	e the recommended forage species. See the native grass plant list for additional in	nformation for es	stablishment of	native grass for	age species thr	oughout the Piec	imont.			
574	Spring Development									
••••	Spring Development 1/ 2/	Each	\$2.571.88		\$3.086.26		20 Years			
1/ Includes	s collection system and spring box. Does not include livestock pipeline from spring	hox to watering	facility.		ψ0,000		20			
2/ <b>Applica</b> (395), Wet	<b>ible to Wildlife Landuse Only</b> . Allowed when planned in conjunction with Restorat tland Restoration (657), or Wetland Wildlife Habitat Management (644).This practic	ion and Manage ce will not distur	ement of Rare c b high quality, r	or Declining Hab atural habitat.	itats (643), Stre	am Habitat Impr	ovement			
442	Sprinkler System									
	Center Pivot System 1/	Ft	\$56.80	2 20 000 00	\$68.16	2 20 020 00				
	Solid Set System 2/	Acre	\$3,611.96	\$ 30,000.00	\$4,334.35	\$ 30,000.00				
	Traveling Gun System 1/	Each	\$34,762.34 ¢6.17		\$41,714.01 \$7.40					
			\$16.53		\$19.84		15 Years			
			ψισ.σσ		ψισ.στ		10 10010			
(FIRI) or of Ag Waste "Ag Waste acreage n hose reel I Freshwate Producers center pivo pivot syste the cost of	Vater supply and conveyance from source to field is not addressed within this practice. Efficiency of the system must be provided in the design package. The designer may use FIRI) or other similar programs to document the gain in efficiency; consult with Area Engineer. Ag Wastewater Notes: For Ag Wastewater the least cost system (center pivot, solid set system, or traveling gun system) will be selected based on acres figured in the Cost Estimator Ag Waste Calculator" tab. Actual wastewater and soil samples are required to calculate acreage needed to apply yearly wastewater prior to irrigation design or payment. Example, if acreage needed to apply yearly wastewater is 9.6 acres or less then a solid set system would be the least cost system for the practice instead of a hose reel. The producer can install a nose reel but payment will be based on the solid set system. Ag Wastewater applications will require a NMP. Freshwater Notes: An IWM plan must be provided to the landowner when contracting 442, but the IWM does not have to be included for payment in the EQIP contract. Producers can request an IWM plan through the IWM CAP 118. If a working center pivot system is determined to be past its usable life and landowner is willing to install a new enter pivot system. In addition, the old center pivot system being replaced will be destroyed. Conversion from a traveler system to a pivot will be acceptable; cost-share rate will be based on the costs of retrofit (high to low pressure) the old center pivot system to a pivot will be acceptable; cost-share rate will be based on the order pivot system being replaced will be destroyed. Conversion from a traveler system to a pivot will be acceptable; cost-share rate will be based on the cost of the new center pivot system to a pivot mill be acceptable; cost-share rate will be based on the cost of retrofitting the size pivot necessary for servicing the involved field. Must have a copy of system design completed and certified by a Certified Irrigation Designer(CID), Georgi									

1/ For Ag Wastewater Only. Use for wastewater application. Waste water application acres based on Cost Estimator "Ag Waste Calculator" tab for nitrogen.
Practice Code	Conservation Practice	Payment Unit	Payment Rate	Maximum Amount	HU Payment Rate	HU Maximum Amount	Lifespan				
2/ Includes all components of solid set system and installation costs. Use for wastewater application. Waste water application acres based on Cost Estimator "Ag Waste Calculator" tab for nitrogen. Use for freshwater for historically underserved clients.											
3/ Paymen	t rate covers all materials and labor for completing the retrofit in accordance with th	e system desig	n. Pressure re	egulators are rec	uired at each s	prinkler. Drop no	ozzles can be				
entrer woodlers, orbitors or rotator sprinklers. CID may approve the retrofit design and as-builts. 4/ Renovation of a previously retrofitted irrigation system with proper modular components and pressure regulating devices, along with all other needed components. VRI system											
requirement	is must be shown at signap.										
570	Stormwater Runoff Control		<b>\$507.45</b>		0.44.50						
	Combination, Most common Best Management Practices	Acre	\$537.15 \$5.02		\$6.03		20 Years				
For use wi			φ0.02		φ0.00		20 10010				
FOI USE WI		FILOT PROG									
578	Stream Crossing										
	Rock armored low water crossing 1/	SqFt	\$4.25		\$5.10						
	Concrete low water crossing Culvert installation 2/	SqFt In-Et	\$5.67 \$2.58		\$6.80						
	Low water crossing using prefabricated products 3/	SqFt	\$5.21		\$6.25		10 Years				
Must add contact St 1/ Includes	Must add critical area planting and mulch. May be used in WRP/ACEP-WRE and livestock systems (livestock must be fenced out of creeks). If needed in a forestry system, contact State Forester and State Engineer 1/ Includes stream crossing with any rock surface (GAB, surge stone, riprap). Price inlcudes all surfacing materials, geotextile and installation.										
2/ Paid by used on pe	inches of culvert diameter multiplied by culvert length. Must add HUA; Pipe must b erennial streams, need to submit a ACOE PCN under Nationwide Permit 40. Must	e designed to a receive prior	accommodate f approval from	ish passage (Mu Area Engineer	ıst use 396, Aq	uatic Organism F	assage). If				
3/ Geocell	filled with gravel, articulated concrete, pavers, or concrete block.										
Applicable to Wildlife Landuse Only. Allowed when planned for a wildlife habitat purpose and as a supporting practice to Forest Stand Improvement (666), Restoration and Management of Rare or Declining Habitats (643), Stream Habitat Improvement (395), Upland Wildlife Habitat Management (645), Wetland Restoration (657), or Wetland Wildlife Habitat Management (644) ONLY IF a stream crossing is required to carry out wildlife management activities. Use of this practice must be justified in the conservation plan. Plan in conjunction with Aquatic Organism Passage. This practice will not disturb high quality, natural habitat. Landowner must secure required permits. Must receive prior approval from the State Biologist and engineer to schedule these scenarios for wildlife land use.											
395	Stream Habitat Improvement and Management	A	¢0.470.00		<b>\$7.440.04</b>						
	Riparian Zone Improvement-Forested	Acre	\$6,176.93		\$7,412.31						
	Instream rock placement	Acre	\$9 645 84		\$11 575 01						
	Rock and wood structures	Acre	\$23.905.74		\$28.686.89						
	Fish Barrier	CuYd	\$4,348.10		\$5,217.72		5 Years				
Applicable	e to Wildlife Landuse Only. Must receive prior approval from the State Biologist ar am Visual Assessment Protocol 2 and comparisons with site appropriate Ecologic	nd/or engineer t al Site Descript	o schedule the	se scenarios. Ma uitable reference	anage accordin conditions.	g to habitat need	s identified				
Applicable	e to Wildlife Landuse Only. Landowner must secure required CWA and other nec	essary permits									
580	Streambank and Shoreline Protection										
300	Shaning 1/	l nFt	\$1/1 35		\$17.00						
	Bioengineered 2/	LnFt	\$49.00		\$58.80						
	Structural 3/	LnFt	\$128.34		\$154.01						
	Toe Protection 4/	LnFt	\$78.45		\$94.14		20 Years				
The Savannah District of the Corp of Engineers has put a regional restriction on Nationwide Permit 13. A preconstruction notification (PCN) must be filed with the Corp of Engineers prior to the construction of streambank stablization projects unless exempted under NWP 13. Landowner shall provide NRCS with a copy of the approved ACOE permit prior to contracting. Streambank and shoreline protection contracts must also include practices that are biologically beneficial to the system; this may include riparian forest buffer, fence, stream habitat improvement and management, etc. Consult with NRCS biologist and NRCS Assistant State Engineer prior to contracting.											
3/ Includes	shaping bank and installing riprap. Add critical area planting and mulch as needed										
4/ Type I o	r III rock rip rap used in conjunction with shaping or bioengineered streambank stab	ilization.									
Applicable to Wildlife Landuse Only. Allowed when planned in for a wildlife habitat purpose in conjunction with Timber Stand Improvement (666), Restoration and Management of Rare or Declining Habitats (643), Stream Habitat Improvement (395), Upland Wildlife Habitat Management (645), Wetland Restoration (657), or Wetland Wildlife Habitat Management (644).											
649	Structures for Wildlife				-						
	Nesting Box, Small no pole 1/	Each	\$30.68		\$36.81						
	Nesting Box, Small, with wood pole 2/	Number	\$45.80		\$54.96						
	Nesting Box, Large 3/	Each	\$61.76 \$181.20		\$/4.11 \$217 //						
	Escane Ramn 5/	Each	¢101.20		ψ217.44 \$21.2F						
I	Locape Manip J/	Laui	φ <b>20.1</b> 2		φ31.30						

Practice Code	Conservation Practice	Payment Unit	Payment Rate	Maximum Amount	HU Payment Rate	HU Maximum Amount	Lifespan			
	Fence Markers, Vinyl Undersill 6/	Ft	<u></u> \$0.11		<u></u> \$0.13					
	Brush Pile - Small 7/	Each	\$23.47		\$28.16					
	Brush Pile - Larg 8/	Each	\$95.63		\$114.76		5 Years			
1/ The inst 6" x 12-1/2	1/ The installation of nesting and rearing boxes that support the life-cycle needs of targeted speces, such as birds, bats and pollinators. Each nesting box is 1-1/2" x 6" x 12-1/2" w/ 1-1/2" diameter opening.									
2/ The installation nesting and rearing boxes support the life-cycle needs of targeted speces, such as blue birds and waterfowl. Each Bluebird nesting box is 1-1/2" x 6" x 12-1/2" w/ 1-1/2" diameter opening. Each Wood Post. End 6" X 8" CCA Treated										
3/ A struct to a tree, b	3/ A structure is provided to support the nesting and rearing of larger targeted species such as waterfowl, bats and barn owls, and is directly mounted to a tree, building or other structure. Habitat Box, waterfowl, typically 24" x 11" x 12" with 4" wide oval entrance. single.									
4/ Constru	4/ Constructing a nest box or rapture perch on a steel pole with a predator guard where needed. Pipe, steel, galvanized, threaded, 1 1/4", schedule 40. Habitat Box, Waterfowl Box, the minimum 24" x 13" with 4" wide outparts single Percent and the minimum single percent and the m									
5/ Retrofit	5/ Retrofit an existing watering trough/tank with an appropriately designed and installed wildlife escape ramp to reduce wildlife mortality and maintain water quality within									
6/ Existing	g facility. Pool Size 15 X 30, for small mammals less than one pound.	tality due to col	lision for wildlif	e species of con	ern Markers a	are installed				
approxima 7/ Small bi than 12 inc	tely every 3 feet along top wire using Vinyl Undersill Strips. ush piles are created to provide shrubby/woody escape cover for wildlife. Small bru shes in diameter.	sh piles are typ	ically 10' x 20'	area for structure	e covered by in	terlocking limbs of	of trees less			
8/ Downed at least 12	tree structures are created to provide shrubby/woody escape cover for wildlife. Larg	ge brush piles a	are typically 30	x 50' area for str	ructure covered	d by interlocking I	imbs of trees			
600	Torraga									
600	Broadbased	Ft	\$1.60		\$1.02					
	Narrow Base, less than 8% slope	Ft	¢1.00 \$1.63		φ1.92 \$1.95		10 Years			
Add critica	I area planting and mulching as needed	1.1	ψ1.05		ψ1.35		10 10013			
612	Tree/Shrub Establishment									
	Medium Density-hand plant Conifer B.R. 7/	Acre	\$03.06		\$112.76					
	Medium Density-Mach Plant Conifer 8/	Acre	\$93.50		\$113.57					
	High Density mech conifer planting 3/	Acre	\$144.55		\$173.46					
	High Doneity hand plant Conifer //	Acro	\$201.50		¢2/1 01					
	Hardwood Hand Planting-hare 1/		\$156.64		\$187.97					
	Hardwood Hand Planting-bare root-protected 2/	Acre	\$255.78		\$306.94					
	Shrub Planting 5/	Acre	\$105.32		\$126.38					
	Hardwoods Tree Planting and Shrubs Hand Planting 2-3 gallon plants	Acie	\$105.52		\$120.30					
	protected 6/	Acre	\$445.79		\$534.95		15 Years			
1/ Hardwo manageme	od seedlings will be planted at minimum of 12X12 spacing at 300 trees per acre. Al ent plan is required prior to payment.	LL forestry acre	s are eligible fo	or payment. Site	es will be hand	planted. A Fores	st			
2/ Hardwo will be han	od seedlings will be planted at minimum of 12X12 spacing by hand method at 300 to d planted. A Forest management plan is required prior to payment.	rees per acre w	ith protected tr	ee tubes. ALL fo	prestry acres ar	e eligible for pay	ment. Sites			
3/ Longleaf pines will be planted by mechancial method. ALL forestry acres are eligible for planting. A Forest Management plan is required prior to payment. A minimum of 605 trees per acre at a 6X12 spacing.										
4/ Longlea will be han	f Pines will be hand planted at 6X12 spacing at 605 trees per acre. ALL forestry ac d planted. Plant containerized longleaf pines seedling only.	cres are eligible	for planting.	A Forest Manage	ement plan is re	equired prior to pa	ayment.Sites			
5/ Applica tree shelte	<b>ble to Forestry Landuse Only</b> . Shrubs will be planted on a 20 X 30 spacing of 1-3 r or tree tube. A Forest Management plan is required prior to payment.	gallon shrubs p	plants for wildlif	e in forest openir	ngs. Each shru	b plant will be pro	otected with			
6/ Applicable to Wildlife Landuse Only. In one acre openings, hand plant 20 trees (hardwood, seedling or transplant, potted or B&B 2-3gal.) per acre and 20 shrubs (seedling or transplant, potted or B&B 2-3 gal.) per acre										
7 /Conifers ( loblolly or slash ) will be planted by hand method. ALL forestry acres are eligible for planting. A Forest Management plan is required prior to payment. A minimum of 545 trees per acre at a 8X10 spacing.										
8 /Conifers (loblolly or slash) will be planted by machine method. ALL forestry acres are eligible for planting. A Forest Management plan is required prior to payment. A minimum of 545 trees per acre at a 8X10 spacing.										
660	Tree/Shrub Pruning									
	Pruning-Low Height 1/ 2/	Acre	\$100.50		\$120.60		1 Year			
Applicable to Wildlife Landuse Only. 1/ Allowed when planned for a wildlife habitat purpose in conjunction with Timber Stand Improvement (666), Restoration and Management of Rare or Declining Habitats (643), Stream Habitat Improvement (395), Upland Wildlife Habitat Management (645), Wetland Restoration (657), or Wetland Wildlife Habitat Management (644) to restore a site-suited native plant community according to a Ecological Site Description or other appropriate reference condition										
2/ On Grazing and Forest Land, for misintenance of established silvopasture sites only. First lift should be done when trees reach 15-20 feet in height. Prune up to 9 feet (Do not remove>50% of canony). Second lift should be done when trees reach 30-40 feet in height is beint.										
490	Tree/Shrub Site Preparation									
	Mechanical - Medium 2/	Acre	\$177.88		\$213.46					

Practice Code	Conservation Practice	Payment Unit	Payment Rate	Maximum Amount	HU Payment Rate	HU Maximum Amount	Lifespan				
360	Waste Facility Closure										
	Liquid Waste Impoundment Closure with fill 1/	CuFt	\$0.30		\$0.36						
Contract f	Liquid Waste Impoundment Closure with no liquid/slurry 2/	CuYd	\$2.96		\$3.55		20 Years				
Producer must provide Notice of Termination to State Agency for state permitted sites along with certification that the closure was completed to NRCS Stds. Not for freshwater conversion. A Waste Facility Closure Plan is required; may be a component of a CNMP/NMP.											
1/ Covers the cost of pumping or hauling sludge and disposing of the wastes in accordance with a nutritent management plan and backfilling the holding pond with compacted earth fill. Need to add critical area planting and mulch (if needed).											
2/ Covers	/ Covers the cost of backfilling holding pond with compacted earth fill. Need to add critical area planting and mulch (if needed).										
632	Waste Separation Facility										
	Mechanical Separation Facility 1/	Each	\$25,825.31		\$30,990.37						
	Concrete Separator 2/	CuFt	\$4.05		\$4.86						
	Concrete Sand Settling Lane 3/	SqFt	\$4.82		\$5.78		15 Years				
Must hav	e an NRCS approved CNMP.										
1/ Include:	s equipment and concrete support pad. Must add critical area planting and mulch a	s needed.									
2/ Based of	on designed storage and includes grading and concrete placement. Must add critica	al area planting	and mulch as r	needed.							
3/ Include:	s grading and concrete placement. Must add critical area planting and mulch as new	eded.									
212	Wasto Storago Egoility										
313	Farthen Storage Facility 1/	CuEt	\$0.23		\$0.27						
	Dry Stack concrete floor wood wall 2/	SaEt	\$4.47		\$5.37						
	Conc Tank Buried 3/	CuEt	φτ.τ <i>ι</i> \$1.72		\$2.06						
	Dry Stack, concrete floor, concrete wall 4/	SaFt	\$5.59		\$6.70		15 Years				
NRCS Ap 1/ Paymer	NRCS Approved Comprehensive Nutrient Management Plan required. 1/ Payment based on designed storage volume to include manure, wastewater and rainfall on contributing areas and pond surface. Pay volume does not include freeboard or sludge										
2/ Must ac	2/ Must add critical area planting, mulch, roof and HUA for entrance pad. Size based on concrete pad area from post to post.										
3/ Must ac	ld critical area planting and mulch.	into and area fr		Concrete well		d for high maintu					
4/ Must ac	In chical area planting, mulch, roof and HOA for entrance pad. Size based on conci	ete paŭ area in	om post to post	. Concrete wan	s are to be use	a for high moistu	re manures				
634	Waste Transfer										
	Concrete Channel 1/	SqFt	\$8.75		\$10.50						
	Manure Flush System of transfer through a collection basin 2/	Gal	\$1.89		\$2.27						
	Waste Transfer Pipeline 3/	LB	\$2.43		\$2.91		15 Years				
NRCS Ap	proved Comprehensive Nutrient Management Plan required.										
1/ Cost of	concrete channel paid by sf of channel bottom. Must add critical area planting and	mulch as need	ed.								
2/ Flush T	anks; Includes cost of concrete pad for flush tank. Must add critical area planting an	d mulch as nee	eded.								
3/ For was	te transfer from a production area to a storage or treatment facility. Must add critica	al area planting	and mulch as r	eeded.							
250	Waste Treatment Lagoon										
339		0.5	<b>\$</b> 0.40		<b>0</b> 0.40		45 1/2				
	waste Treatment Lagoon	CuFt	\$0.16		\$0.19		15 Years				
NRCS Ap	proved Comprehensive Nutrient Management Plan required.										
Payment t include fre	pased on designed storage including manure, wastewater, minimum treatment volume board . Must add critical area planting and mulch as needed	me, and rainfall	on contributing	drainage areas	and pond surfa	ace. Pay volume	does not				
638	Water and Sediment Control Basin										
	WASCOB base	CuYd	\$2.12		\$2.55		10 Years				
Add critica	I area planting and mulch if needed. Use in conjunction with underground outlets a	s needed.									
642	Water Well										
	Typical Well 1/	Each	\$4,466.38		\$5,359.66		00.1/-				
	Deep well 2/	Each	\$6,687.83		\$8,025.40		∠U Years				
If existing well/water source is adequate for the resource need, a new well is not justified. Not to be used for providing water to confined feeding operations or in buildings. Must be part of a prescribed grazing system or where livestock exclusion has removed a water supply. Wells may be used for irrigation only for historically underserved applicants but only when existing well/water source is inadequate to supply irrigation water needs. Does not include the cost of the pump so include CPS 533, Pumping Plant, as a companion practice. All electrical work must meet local and state codes. Documentation must be provided to justify the need for a well, refer to water well drawing on eFOTG.											

1/Well depth 100 to 600 feet below ground surface. Complete well installation (casing, screen, seal, filter pack, concrete pad at well head).

Practice Code	Conservation Practice	Payment Unit	Payment Rate	Maximum Amount	HU Payment Rate	HU Maximum Amount	Lifespan		
2/ Well depth > 600 ft. below ground surface. Complete well installation (casing, screen, seal, filter pack, concrete pad at well head).									
	Wetering Facility								
614									
	Less than 100 gal 1/	Each	\$75.08		\$90.09				
	100-200 gal 2/	Each	\$196.70		\$236.05				
	201-400 gal 3/	Each	\$234.89		\$281.87				
	401-600 gal 4/	Each	\$377.70		\$453.24				
	Greater Than 600 gal 5/	Each	\$527.91		\$633.49				
	2 Ball Freeze proof 6/	Each	\$792.11		\$950.53				
	4 Ball Freeze proof 6/	Each	\$958.99		\$1,150.79				
	Storage Tank for Solar Systems //	Gal	\$0.79		\$0.95				
	High Velocity Watering ramp 9/	SaEt	\$4.63		\$5.55		10 Years		
For livest	ock grazing systems. Not to be used in confined feeding operations or in buildings	Must use Hea	wy Use Area P	rotection CPS 5	61 around wat	ering facility Us	e of used		
materials	is not allowed.					ching raciity. <b>US</b>	c or used		
1/ Very sm	nall trough for small animals; includes installation.								
2/ Small s	ize trough; includes installation								
3/ Medium	trough; includes installation.								
4/ Large tr	ough; includes installation.								
5/ Extra-La	arge trough; includes installation.								
6/ Includes	s concrete pad, trough and installation.								
7/ Includes	s tank concrete pad and installation								
8/ low velo	porter = still water such as ponds								
9/ high vel	ocity = moving water such as streams, creeks, etc.,.								
657	Wetland Restoration								
	Riverine Levee Removal and Floodplain Features	Acre	\$244.35		\$293.22				
	Ditch Plug	CuYd	\$10.40		\$12.48				
	Estuarine Fringe Levee Removal	Acre	\$12.04		\$14.45				
	Riverine Channel and Floodplain Restoration	Acre	\$331.91		\$398.29		15 Years		
Applicabl	e to Wildlife Landuse Only. Restoration will occur according to habitat needs iden	tified by the GA	Habitat Suitab	ility Index model	and compariso	ons with site appr	opriate		
Ecological		biologist and er	igineer approva	a phor to schedu					
644	Watland Wildlife Management								
644									
	Habitat Monitoring and Management, Very-Low Intensity and Complexity 1/	Acre	\$0.68		\$0.81				
	Wetland Widlife Habitat Mongtand Mgt, Low Intensity and Complexity 2/	Acre	\$2.26		\$2.71				
	Habitat Manitaring and Management, Medium Intensity and Complexity 2/	Aoro	¢0 /1		\$10.10				
	Habitat Monitoring and Management, Medium Intensity and Complexity S	Acie	φ <b>0.</b> 41		\$10.10				
ļ	Habitat Monitoring and Management, High Intensity and Complexity 4/	Acre	\$20.67		\$24.80				
<u> </u>	Dev of Shallow Micro-Topoc Features with Normal Equipment. 5/	Acre	\$28.70		\$34.44				
	Development of Deep Micro-Topo Features with Heavy Equipment. 6/	Acre	\$78.19		\$93.82		1 Year		
1/Wetland	wildlife habitat is improved by implementation of annual adaptive management ac	tions of very lo	w intensity and	complexity. The	adaptive mana	agement actions	such as		
cutting of I	imbs that are impeding access of birds into nest boxs, replacing damaged fence ma	arkers, cleaning	of nest structu	ires and debris a	around other str	uctures requires	only hand		
	d wildlife behitet is improved by implementation of enougl adaptive management as	lana ayah aa a	utting of limbot	hat are irreading	n access of hird	la inte naat have	roplasing		
2/ wetian	a wildlife habitat is improved by implementation of annual adaptive management ad fence markers, cleaning of nest structures and debris around other structures requi	res only hand la	bor and less th	nat are impeding an 8 hours labo	j access of bird r ber vear.	is into nest boxs,	replacing		
2/ Two or	three adaptive management efforts are required (such as cutting of limbs that are in	anoding accoss	of hirds into n	ost boxos, ropla	n domogod f	onco markors, cl	opping of		
or two or mee adaptive management errors are required (such as cutting or limbs that are impeding access or birds into nest boxes, replacing damaged tence markers, cleaning of nest structures and debris around other structures). The adaptive mant requires hand labor and the occasional use of light equipment. A crew of 2 is needed for the hand labor efforts									
and the cr	ew will require less than 16 total hours of labor per mgmt effort.		3.0						
4/ Two four monitoring efforts are needed and each requiring less than 2 people and less than 8 hours per effort. The adaptive management actions (2 5 efforts) such as cutting of									
limbs that	are impeding access of birds into nest boxes, replacing damaged fence markers, c t requiring a 2 person crew less than 1 day per effort	eaning of nest	structures and	debris around of	her structures r	equires hand lab	or and light		
equipment, requiring a 2 person one less than 1 day per enort. 5/ Soil is exceivated with normal farming equipment (e.g. tractor and how blade) to a depth of 2.6 inches and immediately deposited. This lowering and reising of a how blade restores the									
original mi	crotopographic features (6' X 6' depressions and mounds) common to most landsc	apes and landfo	orms prior to cle	earing, tilling, and	d annual mowir	ng. This scenario	it typically		
implemented for ecosystem restoration projects.									
b/ soil is excavated with track equipment (dozer) to a depth of 6.12 inches and immediately deposited. This lowering and raising of a dozer blade restores the original deep micro topographic features (10' X10' depressions and mounds) common to many landscapes and landforms prior to the lands conversion to particultural lands. This ecception is the incelled									
implement	ted for ecosystem restoration projects	and ianoionns	phor to the lane	us conversion to	agricultural lan	ius. This scenario	The typically		
1/ Applies	ble to Wildlife Landuse Only. Requires a monitoring plan, an approved agreement	nt with the moni	toring organiza	tion and a signe	d landowner re	lease agreeing th	nat the data		
will be put	licity available.		ioning organiza	aon, and a signe		adde agreenig ti			

Practice Code	Conservation Practice	Payment Unit	Payment Rate	Maximum Amount	HU Payment Rate	HU Maximum Amount	Lifespan			
2/ Applicable to Wildlife Landuse Only. Manage according to habitat needs identified by the GA Habitat Suitability Index model and comparisons with site appropriate Ecological Site Descriptions or other suitable reference conditions.										
380	Windbreak/Shelterbelt Establishment									
	2 Row windbreak, trees, Machine planted	Foot	\$0.44		\$0.52		15 Years			
Two offset be planted	Two offset rows of Hardwoods/Pines/Evergreens or Shrubs planted for wind protection, shelter for livestock, wildlife habitat, air quality or to provide a visual screen. Trees should be planted at the desired spacing to meet the resource need.									
FOOTNO	TES									
Maximum Amounts for the life of the contract are established on certain conservation practices or options, as noted in this Policy. EQIP funds provide financial assistance to eligible farmers and ranchers to help these producers enhance agricultural and forested lands in a cost-effective and environmentally beneficial manner. Establishing Maximum Amounts for the contract allows Georgia NRCS to make EQIP funding assistance available to a larger number of eligible farmers, ranchers and forest producers here in Georgia, and also as a method to make funding available to eligible producers regardless of size of operation (i.e., by not obligating large amounts of funds on operations with more acres, Georgia EQIP funds will be available to a larger number of separate operations). The specified "Maximum Amounts" for identified practices within this policy does not allow applicants to exceed the maximums through multiple offers/contracts on different acres when those acres are controlled by the same applicant(s), where 'control' means possession of the land by ownership, written lease, or other legal agreement (as generally indicated on FSA's EZ156 &/or Producer Farm Data Report forms). Historically Underserved Maximum Amounts refers to the maximum contract payment for Historically Underserved Farmers (Limited Resource Farmers, Beginning Farmers, and Socially Disadvantaged Farmers as defined in the 2014 EQIP Final Rule). NOTE: While there is no restriction on the number of applications (or contracts, if funded) that may be submitted by an applicant for EQIP applications (and contracted amounts) will count towards the Maximum Amount as listed in FY17 EQIP Policy for any and all FY17 EQIP applications (and FY17 EQIP contracts, if funded) where acres are controlled by the same applicant(s).										
FMP = Forest Management Plan. Approved FMP's are: (a) Forest Management Plan 106 Plan developed by a TSP OR (b) Forest Stewardship Plan (FSP) prepared by GFC OR (c) GFC Resource Management Plan OR (d) Conservation Plan on Forest Land OR (e) a site-specific plan prepared by a professional forester if this site-specific plan has been approved by either an NRCS forester or the Georgia State Forester at the time the EOIP applicant sions the CPA1200.										
Conservation practices that are either structural or vegetative, and have a multi-year lifespan. Structural practices involve the establishment, construction, or installation of site-specific measures. Vegetative practices involve the establishment or planting of site-specific vegetative measures. Payments are established as a one-time only payment, not multi-year payments. Georgia policy requires the owner be a construct which has EOIR funds used for any structural or vegetative practices in pagedonas with CDM/15, 74/03/03										
Technical S	Technical Service Provider (http://www.nrcs.usda.gov/wps/portal/nrcs/main/national/programs/technical/tsp)									
2/1/2017_										
	Georgia State Conservationist			Date						