

PERMIT NO. 5171-089-0100-V-05-0

ISSUANCE DATE:



GEORGIA

DEPARTMENT OF NATURAL RESOURCES

ENVIRONMENTAL PROTECTION DIVISION

Air Quality - Part 70 Operating Permit

Facility Name: Chevron Products Company – Doraville Terminal
Facility Address: 4026 Winters Chapel Road
Doraville, Georgia 30360, DeKalb County
Mailing Address: P. O. Box 1706
Atlanta, Georgia 30301
Parent/Holding Company: Chevron Products Company, a Division of Chevron U.S.A., Inc
Facility AIRS Number: 04-13-089-00100

In accordance with the provisions of the Georgia Air Quality Act, O.C.G.A. Section 12-9-1, et seq and the Georgia Rules for Air Quality Control, Chapter 391-3-1, adopted pursuant to and in effect under the Act, the Permittee described above is issued a Part 70 Permit for:

The operation of a bulk gasoline terminal, including a vapor recovery system and storage tanks.

This Permit is conditioned upon compliance with all provisions of The Georgia Air Quality Act, O.C.G.A. Section 12-9-1, et seq, the Rules, Chapter 391-3-1, adopted and in effect under that Act, or any other condition of this Permit. Unless modified or revoked, this Permit expires five years after the issuance date indicated above.

This Permit may be subject to revocation, suspension, modification or amendment by the Director for cause including evidence of noncompliance with any of the above, for any misrepresentation made in Title V Application No. TV-583852 signed on July 29, 2021, any other applications upon which this Permit is based, supporting data entered therein or attached thereto, or any subsequent submittal of supporting data, or for any alterations affecting the emissions from this source.

This Permit is further subject to and conditioned upon the terms, conditions, limitations, standards, or schedules contained in or specified on the attached **45** pages.



DRAFT

Richard E. Dunn, Director
Environmental Protection Division

Table of Contents

PART 1.0	FACILITY DESCRIPTION	1
1.1	Site Determination	1
1.2	Previous and/or Other Names	1
1.3	Overall Facility Process Description.....	1
PART 2.0	REQUIREMENTS PERTAINING TO THE ENTIRE FACILITY	2
2.1	Facility Wide Emission Caps and Operating Limits	2
2.2	Facility Wide Federal Rule Standards.....	2
2.3	Facility Wide SIP Rule Standards.....	2
2.4	Facility Wide Standards Not Covered by a Federal or SIP Rule and Not Instituted as an Emission Cap or Operating Limit	2
PART 3.0	REQUIREMENTS FOR EMISSION UNITS	3
3.1	Emission Units	3
3.2	Equipment Emission Caps and Operating Limits	3
3.3	Equipment Federal Rule Standards	4
3.4	Equipment SIP Rule Standards	8
3.5	Equipment Standards Not Covered by a Federal or SIP Rule and Not Instituted as an Emission Cap or Operating Limit	10
PART 4.0	REQUIREMENTS FOR TESTING.....	11
4.1	General Testing Requirements	11
4.2	Specific Testing Requirements	12
PART 5.0	REQUIREMENTS FOR MONITORING (Related to Data Collection)	13
5.1	General Monitoring Requirements.....	13
5.2	Specific Monitoring Requirements	13
PART 6.0	RECORD KEEPING AND REPORTING REQUIREMENTS	16
6.1	General Record Keeping and Reporting Requirements	16
6.2	Specific Record Keeping and Reporting Requirements.....	19
PART 7.0	OTHER SPECIFIC REQUIREMENTS.....	25
7.1	Operational Flexibility	25
7.2	Off-Permit Changes	25
7.3	Alternative Requirements.....	26
7.4	Insignificant Activities	26
7.5	Temporary Sources	26
7.6	Short-term Activities	26
7.7	Compliance Schedule/Progress Reports	26
7.8	Emissions Trading.....	26
7.9	Acid Rain Requirements	26
7.10	Prevention of Accidental Releases (Section 112(r) of the 1990 CAAA).....	26
7.11	Stratospheric Ozone Protection Requirements (Title VI of the CAAA of 1990)	28
7.12	Revocation of Existing Permits and Amendments.....	29
7.13	Pollution Prevention.....	29
7.14	Specific Conditions	29
PART 8.0	GENERAL PROVISIONS	30
8.1	Terms and References	30
8.2	EPA Authorities	30
8.3	Duty to Comply.....	30
8.4	Fee Assessment and Payment	31

Title V Permit

Chevron Products Company – Doraville Terminal

Permit No.: 5171-089-0100-V-05-0

8.5	Permit Renewal and Expiration	31
8.6	Transfer of Ownership or Operation	31
8.7	Property Rights.....	31
8.8	Submissions.....	32
8.9	Duty to Provide Information	32
8.10	Modifications	33
8.11	Permit Revision, Revocation, Reopening and Termination.....	33
8.12	Severability	34
8.13	Excess Emissions Due to an Emergency	34
8.14	Compliance Requirements	35
8.15	Circumvention.....	37
8.16	Permit Shield.....	37
8.17	Operational Practices	38
8.18	Visible Emissions.....	38
8.19	Fuel-burning Equipment	38
8.20	Sulfur Dioxide.....	39
8.21	Particulate Emissions	39
8.22	Fugitive Dust.....	39
8.23	Solvent Metal Cleaning.....	40
8.24	Incinerators.....	41
8.25	Volatile Organic Liquid Handling and Storage	41
8.26	Use of Any Credible Evidence or Information	42
8.27	Internal Combustion Engines.....	42
8.28	Boilers and Process Heaters	43
Attachments		45
A. List of Standard Abbreviations and List of Permit Specific Abbreviations		
B. Insignificant Activities Checklist, Insignificant Activities Based on Emission Levels and Generic Emission Groups		
C. List of References		

PART 1.0 FACILITY DESCRIPTION

1.1 Site Determination

This is the only facility at this Part 70 site.

1.2 Previous and/or Other Names

No previous or other names for this facility have been identified.

1.3 Overall Facility Process Description

This facility is a bulk gasoline terminal, which receives product by underground pipeline and dispenses it through a truck loading rack to tank trucks/cargo tanks where the product is delivered to gasoline dispensing facilities (gas stations). The facility's significant emission sources consist of eight storage tanks. In addition to these tanks, there are fourteen tanks included in the application as insignificant activities units, which are currently empty or store diesel fuel, water, or additives. The tanks, which are currently empty, may store diesel fuel in the future, retaining their insignificant emission unit status. The facility also has a truck loading rack with four product delivery bays, one vapor recovery unit (VRU) controlling emissions from the loading rack, and fugitive emission sources. The loading rack is equipped with safety features to prevent spills and is automatically shut down if the safety devices sense a spill or sense that a spill may occur.

Emissions of concern are volatile organic compound (VOC) and Hazardous Air Pollutant (HAP) emitted primarily from truck loading and storage tank losses (fugitive emissions). The facility's operating schedule is 24 hours per day, 7 days per week.

PART 2.0 REQUIREMENTS PERTAINING TO THE ENTIRE FACILITY

2.1 Facility Wide Emission Caps and Operating Limits

- 2.1.1 The Permittee shall not discharge or cause the discharge into the atmosphere from the entire facility any single hazardous air pollutant which is listed in Section 112 of the Clean Air Act, in an amount equal to or exceeding 10 tons during any twelve consecutive months, or any combination of such listed pollutants in an amount equal to or exceeding 25 tons during any twelve consecutive months.
[40 CFR 63 Area Source Classification and Avoidance of 40 CFR 63 Subpart R]

2.2 Facility Wide Federal Rule Standards

- 2.2.1 All equipment subject to 40 CFR 63 – “*National Emission Standards for Hazardous Air Pollutants for Source Category*,” shall comply with the applicable provisions of 40 CFR 63 Subpart A – “*General Provisions*.”
[40 CFR 63.1-16 and 63.11098]
- 2.2.2 For all equipment subject to 40 CFR 60 - “*Standards of Performance for New Stationary Sources*,” Subpart K, Subpart Kb, and Subpart XX, the Permittee shall comply with the applicable provisions of 40 CFR 60 Subpart A – “*General Provisions*.”
[40 CFR 60 Subpart A]

2.3 Facility Wide SIP Rule Standards

None applicable.

2.4 Facility Wide Standards Not Covered by a Federal or SIP Rule and Not Instituted as an Emission Cap or Operating Limit

None applicable.

PART 3.0 REQUIREMENTS FOR EMISSION UNITS

Note: Except where an applicable requirement specifically states otherwise, the averaging times of any of the Emissions Limitations or Standards included in this permit are tied to or based on the run time(s) specified for the applicable reference test method(s) or procedures required for demonstrating compliance.

3.1 Emission Units

Emission Units		Applicable Requirements/Standards	Air Pollution Control Devices	
ID No.	Description		ID No.	Description
T003	Tank No. 3 (Ethanol Tank)	391-3-1-.02(2)(bb) 391-3-1-.02(2)(a)(3)	N/A	Internal Floating Roof
T010	Tank No. 10 (Fixed Roof Tank Storing Transmix)	None	N/A	Fixed Roof
T012	Tank No. 12 (Internal Floating Roof Tank)	391-3-1-.02(2)(bb) 391-3-1-.02(2)(a)(3) 40 CFR 60 Subpart Kb 40 CFR 63 Subpart BBBBBB	N/A	Internal Floating Roof
T015	Tank No. 15 (Fixed Roof Tank storing Transmix)	None	N/A	Fixed Roof
T021	Tank No. 21 (Domed Internal Floating Roof Tank)	391-3-1-.02(2)(bb) 391-3-1-.02(2)(a)(3) 40 CFR 63 Subpart BBBBBB	N/A	Domed Internal Floating Roof
T027	Tank No. 27 (Fixed Roof Tank storing Transmix or PWC)	None	N/A	Fixed Roof
T028	Tank No. 28 (Internal Floating Roof Tank)	391-3-1-.02(2)(bb) 391-3-1-.02(2)(a)(3) 40 CFR 60 Subpart K 40 CFR 63 Subpart BBBBBB	N/A	Internal Floating Roof
T029	Tank No. 29 (Internal Floating Roof Tank)	391-3-1-.02(2)(bb) 391-3-1-.02(2)(a)(3) 40 CFR 60 Subpart K 40 CFR 63 Subpart BBBBBB	N/A	Internal Floating Roof
LR01	Product Loading Rack	391-3-1-.02(2)(cc) 40 CFR 60 Subpart XX 40 CFR 63 Subpart BBBBBB	C001	Vapor Recovery Unit (VRU)
	Gasoline Transport Vehicles/Cargo Tank/Tank Truck	391-3-1-.02(2)(ss)		

* Generally applicable requirements contained in this permit may also apply to emission units listed above. The lists of applicable requirements/standards are intended as a compliance tool and may not be definitive.

3.2 Equipment Emission Caps and Operating Limits

3.2.1 The Permittee shall have a vapor collection system designed and operated such that VOC emissions from truck loading do not exceed 35 milligrams of total organic compounds per liter of gasoline loaded (0.292 lb. of total organic compounds per 1,000 gallons).
[40 CFR 60.502 and 391-3-1-.02(2)(cc)]

3.3 Equipment Federal Rule Standards

- 3.3.1 Storage Tanks T028 and T029 shall comply with all applicable provisions of 40 CFR 60 Subpart K – “*Standards of Performance for Storage Vessels for Petroleum Liquids for Which Construction, Reconstruction, or Modification Commenced after June 11, 1973 and Prior to May 19, 1978.*” Tanks T028 and T029 shall be equipped with a floating roof, a vapor recovery system, or its equivalent.
[40 CFR 60.110 through 60.113]
- 3.3.2 Storage Tank T012 shall comply with all applicable provisions of 40 CFR 60 Subpart Kb - “*Standards of Performance for Volatile Organic Liquid Storage Vessels (Including Petroleum Liquid Storage Vessels) for Which Construction, Reconstruction, or Modification Commenced after July 23, 1984.*”
[40 CFR 60.110b and 40 CFR 60.112b]
- a. The internal floating roofs must be resting or floating on the stored liquid at all times except during the initial fill and during the times when the tank is completely emptied and the roof is resting on the leg supports. When the roofs are resting on the leg supports, the process of filling, emptying, or refilling shall be continuous and accomplished as rapidly as possible.
 - b. The internal floating roofs must have either a foam- or liquid mounted liquid-filled seal, a double seal, or a mechanical shoe seal.
 - c. Each opening in a noncontact internal floating roof except for automatic bleeder vents (vacuum breaker vents) and the rim space vents is to provide a projection below the liquid surface.
 - d. Each opening in the internal floating roofs except for leg sleeves, automatic bleeder vents, rim space vents, column wells, ladder wells, sample wells, and stub drains is to be equipped with a cover or lid which is to be maintained in a closed position at all times (i.e., no visible gap) except when the device is in actual use. The cover or lid shall be equipped with a gasket. Covers on each access hatch and automatic gauge float well shall be bolted except when they are in use.
 - e. Automatic bleeder vents shall be equipped with a gasket and are to be closed at all times when the roof is floating except when the roof is being floated off or is being landed on the roof leg supports.
 - f. Rim space vents shall be equipped with a gasket and are to be set to open only when the internal floating roof is not floating or at the manufacturer’s recommended setting.
 - g. Each penetration of an internal floating roof for the purpose of sampling shall be a sample well. The sample well shall have a slit fabric cover that covers at least 90 percent of the opening.

Title V Permit

- h. Each penetration of an internal floating roof that allows for passage of a column supporting the fixed roof shall have a flexible fabric sleeve seal or a gasketed sliding cover.
 - i. Each penetration of an internal floating roof that allows for passage of a ladder shall have a gasketed sliding cover.
- 3.3.3 The Permittee shall comply with all applicable requirements of 40 CFR 60 Subpart XX - *“Standards of Performance for Bulk Gasoline Terminals”*.
[40 CFR 60.502] [Vault NS-031-OT, 09/11]
 - a. Each vapor collection system shall be designed to prevent any organic compound vapors collected at one loading rack from passing to another loading rack.
 - b. Loadings of liquid product into gasoline tank trucks shall be limited to vapor-tight gasoline tank trucks using the following procedures:
 - i. The owner or operator shall obtain the vapor tightness documentation described in 40 CFR 60.505(b) for each gasoline tank truck which is to be loaded at the affected facility.
 - ii. The owner or operator shall require the tank identification number to be recorded as each gasoline tank truck is loaded at the affected facility.
 - iii. The owner or operator shall cross-check each tank identification number obtained in paragraph b.ii. of this Condition with the file of tank vapor tightness documentation within 2 weeks after the corresponding tank is loaded.
 - iv. The terminal owner or operator shall notify the owner or operator of each nonvapor-tight gasoline tank truck loaded at the affected facility within 3 weeks after the loading has occurred.
 - v. The terminal owner or operator shall take steps assuring that the nonvapor-tight gasoline tank truck will not be reloaded at the affected facility until vapor tightness documentation for that tank is obtained.
 - vi. Alternate procedures to those described in paragraphs b.i. through v. of this Condition for limiting gasoline tank truck loadings may be used upon application to, and approval by, the Division.
 - c. The owner or operator shall act to assure that loadings of gasoline tank trucks at the affected facility are made only into tanks equipped with vapor collection equipment that is compatible with the terminal’s vapor collection system.

Title V Permit

- d. The owner or operator shall act to assure that the terminal's and the tank truck's vapor collection systems are connected during each loading of a gasoline tank truck at the affected facility. Examples of actions to accomplish this include training drivers in the hookup procedures and posting visible reminder signs at the affected loading racks.
[40 CFR 60.502(g)]
- e. The vapor collection and liquid loading equipment shall be designed and operated to prevent gauge pressure in the delivery tank from exceeding 4,500 pascals (450 mm of water) during product loading. This level is not to be exceeded when measured by the procedures specified in 40 CFR 60.503(d).
[40 CFR 60.502(h)]
- f. No pressure-vacuum vent in the bulk gasoline terminal's vapor collection system shall begin to open at a system pressure less than 4,500 pascals (450 mm of water).
[40 CFR 60.502(i)]

3.3.4 The Permittee shall comply with the provisions of 40 CFR 63 Subpart BBBBBB - *“National Emission Standards for Hazardous Air Pollutants for Source Category: Gasoline Distribution Bulk Terminals, Bulk Plants, and Pipeline Facilities.”* In particular, [40 CFR 63.11080, 63.11081, 63.11082, 63.11083, and 63.11087]

- a. Comply with each emission limit and management practice listed in the following table (Table 1 to 40 CFR 63 Subpart BBBBBB) that applies to gasoline storage tanks.
[40 CFR 63.11087(a)]

Emission Unit	The Permittee shall
1. A gasoline storage tank meeting either of the following conditions: (i) a capacity of less than 75 cubic meters (m ³); or (ii) a capacity of less than 151 m ³ and a gasoline throughput of 480 gallons per day or less. Gallons per day are calculated by summing the current day's throughput plus the throughput for the previous 364 days, and then dividing that sum by 365.	Equip each gasoline storage tank with a fixed roof that is mounted to the storage tank in a stationary manner and maintain all openings in a closed position at all times when not in use.
2. A gasoline storage tank with a capacity of greater than or equal to 75 m ³ and not meeting any of the criteria specified in item 1 of this table.	2(a) Reduce emissions of total organic HAP or TOC by 95 weight-percent with a closed vent system and control device as specified in 40 CFR 60.112b(a)(3); or 2(b) Equip each internal floating roof gasoline storage tank according to the requirements in 40 CFR 60.112b(a)(1), except for the secondary seal requirements under 40 CFR 60.112b(a)(1)(ii)(B) and the requirements in 40 CFR 60.112b(a)(1)(iv) through (ix); and 2(c) Equip each external floating roof gasoline storage tank according to the requirements in 40 CFR 60.112b(a)(2), except that the requirements of 40 CFR 60.112b(a)(2)(ii) shall only be required if

Title V Permit

Chevron Products Company – Doraville Terminal

Permit No.: 5171-089-0100-V-05-0

Emission Unit	The Permittee shall
	such storage tank does not currently meet the requirements of 40 CFR 60.112b(a)(2)(i); or 2(d) Equip and operate each internal and external floating roof gasoline storage tank according to the applicable requirements in 40 CFR 63.1063(a)(1) and (b), except for the secondary seal requirements under 40 CFR 63.1063(a)(1)(i)(C) and (D), and equip each external floating roof gasoline storage tank according to the requirements of 40 CFR 63.1063(a)(2) if such storage tank does not currently meet the requirements of 40 CFR 63.1063(a)(1).
3. A surge control tank	Equip each tank with a fixed roof that is mounted to the tank in a stationary manner and with a pressure/vacuum vent with a positive cracking pressure of no less than 0.50 inches of water. Maintain all openings in a closed position at all times when not in use.

- b. Storage vessels equipped with floating roofs and not meeting the requirements of subparagraph a. of this condition shall be in compliance at the first degassing and cleaning activity after January 10, 2011, or by January 10, 2018, whichever is first.
[40 CFR 63.11087(b)]

3.3.5 The Permittee shall comply with applicable requirements for gasoline loading racks under 40 CFR 63 Subpart BBBBBB - “*National Emission Standards for Hazardous Air Pollutants for Source Category: Gasoline Distribution Bulk Terminals, Bulk Plants, and Pipeline Facilities.*” In particular:
[63.11088(a)]

- a. Comply with each emission limit and management practice listed in the following table (Table 2 to 40 CFR 63 Subpart BBBBBB) that applies to bulk gasoline terminals. In particular,

Emission Unit	The Permittee shall
A gasoline loading rack(s) at a bulk gasoline terminal with a gasoline throughput of 250,000 gallons per day, or greater.	(a) Equip the loading rack(s) with a vapor collection system designed to collect the TOC vapors displaced from cargo tanks during product loading; and (b) Reduce emissions of TOC to less than or equal to 80 mg/l of gasoline loaded into gasoline cargo tanks at the loading rack; and (c) Design and operate the vapor collection system to prevent any TOC vapors collected at one loading rack from passing to another loading rack or lane to the atmosphere; and (d) Limit the loading of gasoline into gasoline cargo tanks that are vapor tight using the procedures specified in 40 CFR 60.502(e) through (j). For the purposes of this condition, the term “tank truck” as used in 40 CFR 60.502(e) through (j) means “cargo tank” as defined in 40 CFR 63.11100.

3.4 Equipment SIP Rule Standards

3.4.1 State Only Enforceable Condition.

All above ground tanks with a capacity of 40,000 gallons or greater used to store a petroleum liquid with a true vapor pressure of 1.5 psia or greater, shall be painted with a paint of a heat-reflective nature when repainted.

[391-3-1-.02(2)(a)(3)]

3.4.2 The Permittee shall comply with 391-3-1-.02(2)(bb) - “*Petroleum Liquid Storage.*” Each tank with a capacity of 40,000 gallons or greater, storing a product with a true vapor pressure of greater than 1.52 psia, must have a floating roof or be fitted with a control device of equal or greater control efficiency.

[391-3-1-.02(2)(bb)(1)]

3.4.3 The Permittee shall not load gasoline into any tank trucks or trailers from any bulk gasoline terminal unless:

[391-3-1-.02(2)(cc)]

a. The bulk gasoline terminal is equipped with vapor control equipment properly installed, in good working order, in operation, and consisting of one of the following:

- i. An absorber or condensation equipment which processes and recovers at least 90 percent of all vapors and gases from the equipment being controlled; or
- ii. Vapor collection equipment which directs all vapors to a fuel gas system; or
- iii. Control equipment demonstrated to have control efficiency equivalent to or greater than required in i. or ii. of this paragraph, and approved by the Director; and

b. All displaced vapors and gases are vented only to the vapor control equipment; and

*c. Complete drainage of any loading arm will be accomplished before it is removed from the tank; and

d. All loading and vapor lines are equipped with fittings which make vapor-tight connections and which close automatically when disconnected, or a loading arm with vapor return line and a hatch seal designed to prevent the escape of gases and vapor while loading.

* The complete drainage requirement for loading arms in subparagraph c. of this condition only applies to top-loading arms.

3.4.4 The Permittee shall comply with 391-3-1-.02(2)(ss) - “*Gasoline Transport Vehicle and Vapor Collection Systems.*” In particular:

[391-3-1-.02(2)(ss)]

Title V Permit

- a. The facility shall not load or unload gasoline from a gasoline transport vehicle of any size capacity unless:
 - i. The tank sustains a pressure change of not more than 3 inches of water in 5 minutes when pressurized to 18 inches of water and evacuated to 6 inches of water as tested at least once per year in accordance with test procedures specified by the Division; and
 - ii. Displays a marking on the right front (passenger) side of the tank, in characters at least 2 inches high, which reads either P/V TEST DATE or EPA 27 and the date on which the gasoline transport tank was last tested; and
 - iii. The tank has no visible liquid leaks and no gasoline vapor leaks as measured by a combustible gas detector; and
 - iv. The owner or operator of the gasoline transport vehicle has submitted to the Division within 30 days of the test date a data sheet containing, at a minimum the following information: name of person(s) or company that conducted the test, date of test, test results including a list of any repairs made to the transport vehicle to bring it into compliance and the manufacturer's vehicle identification number (VIN) of the tank truck or frame number of a trailer-mounted tank; and
 - v. The transport vehicle has been equipped with fittings which are vapor tight and will automatically and immediately close upon disconnection so as to prevent release of gasoline or gasoline vapors, with a vapor return line and hatch seal designed to prevent the escape of gasoline or gasoline vapors while loading.
- b. The Permittee with a vapor collection and vapor control system shall:
 - i. Design and operate the vapor collection and control system and the gasoline loading equipment in a manner that prevents:
 - (A) Gauge pressure from exceeding 18 inches of water and vacuum from exceeding six inches of water in the gasoline tank truck;
 - (B) A reading equal to or greater than 100 percent of the lower explosive limit (LEL, measured as propane) at one inch from all points on the perimeter of a potential leak source when measured (in accordance with test procedures specified by the Division) during loading or unloading operations at gasoline dispensing facilities, bulk gasoline plants and bulk gasoline terminals; and
 - (C) Avoidable visible liquid leaks during loading and unloading operations at gasoline dispensing facilities, bulk gasoline plants and bulk gasoline terminals; and
 - ii. Within 15 days, repair and retest a vapor collection or control system that exceeds the limits in subparagraph b.i. above.

- c. The Division may require a pressure/vacuum retest or leak check for any transport vehicle, vapor collection or control system, and/or gasoline loading equipment subject to this subparagraph. A transport vehicle, vapor collection or control system, and/or gasoline loading equipment for which the Division has required a pressure/vacuum retest or leak check shall:
 - i. Cease loading and unloading operations within 14 days of the date of the initial retest or leak check request unless the retest or leak check has been completed to the satisfaction of the Division; and
 - ii. Provide written advance notification to the Division of the scheduled time and place of the test in order to provide the Division an opportunity to have an observer present; and
 - iii. Supply a copy of the results of all such tests to the Division within 30 days of the test date.

3.5 Equipment Standards Not Covered by a Federal or SIP Rule and Not Instituted as an Emission Cap or Operating Limit

- 3.5.1 Routine maintenance shall be performed on all air pollution control equipment. Maintenance records shall be recorded in a permanent form suitable and available for inspection by the Division. The records shall be retained for at least five years following the date of such maintenance.
[391-3-1-.03(2)(c)]
- 3.5.2 The Permittee shall maintain an inventory of spare parts for the vapor control system.
[391-3-1-.03(2)(c)]

PART 4.0 REQUIREMENTS FOR TESTING

4.1 General Testing Requirements

- 4.1.1 The Permittee shall cause to be conducted a performance test at any specified emission unit when so directed by the Environmental Protection Division (“Division”). The test results shall be submitted to the Division within 60 days of the completion of the testing. Any tests shall be performed and conducted using methods and procedures that have been previously specified or approved by the Division.
[391-3-1-.02(6)(b)1(i)]
- 4.1.2 The Permittee shall provide the Division thirty (30) days (or sixty (60) days for tests required by 40 CFR Part 63) prior written notice of the date of any performance test(s) to afford the Division the opportunity to witness and/or audit the test, and shall provide with the notification a test plan in accordance with Division guidelines.
[391-3-1-.02(3)(a) and 40 CFR 63.7(b)(1)]
- 4.1.3 Performance and compliance tests shall be conducted and data reduced in accordance with applicable procedures and methods specified in the Division’s Procedures for Testing and Monitoring Sources of Air Pollutants. The methods for the determination of compliance with emission limits listed under Sections 3.2, 3.3, 3.4 and 3.5 are as follows:
- a. Method 1 for selection of sampling site and number of traverse points.
 - b. Method 2 shall be used for stack gas flow rate.
 - c. Method 4 shall be used for moisture determination.
 - d. Method 18 and ASTM D2504 for the determination of concentration of sample component.
 - e. Method 21 for determination of tanker truck leaks, and leaks from any equipment in gasoline service.
 - f. Method 22 for the determination of visible emissions.
 - g. Method 25A and/or 25B for the measurement of inlet and outlet VOC concentrations.
 - h. ASTM D323, ASTM D2879 or method approved by the administrator for the measurement of Reid vapor pressure.
 - i. ASTM D2382 shall be used to determine the net heat of combustion of each component if published values are not available or cannot be calculated.
 - j. ASTM D2267 for determination of percent VHAP content in process fluid.
 - k. ASTM D2622 or ASTM D5453 for the measurement of sulfur content in gasoline.

- l. ASTM D1319 for the measure of olefin content in gasoline.
- m. ASTM D5580 for the measurement of aromatic hydrocarbon content in gasoline.
- n. Methods referenced in the applicable NSPS (found in 40 CFR 60) or NESHAP (found in 40 CFR 63) shall be used for determination of emissions specified in applicable requirements of such standards.

Minor changes in methodology may be specified or approved by the Director or his designee when necessitated by process variables, changes in facility design, or improvement or corrections that, in his opinion, render those methods or procedures, or portions thereof, more reliable.

[391-3-1-.02(3)(a)]

- 4.1.4 The Permittee shall submit performance test results to the US EPA's Central Data Exchange (CDX) using the Compliance and Emissions Data Reporting Interface (CEDRI) in accordance with any applicable NSPS or NESHAP standards (40 CFR 60 or 40 CFR 63) that contain Electronic Data Reporting Requirements. This Condition is only applicable if required by an applicable standard and for the pollutant(s) subject to said standard.

[391-3-1-.02(8)(a) and 391-3-1-.02(9)(a)]

4.2 Specific Testing Requirements

- 4.2.1 In accordance with the applicable provisions of 40 CFR 63.7, for any equipment which is subject to 40 CFR 63 - "National Emission Standards for Hazardous Air Pollutants for Source Categories," constructed or modified at the facility, the Permittee shall conduct a performance test within 60 days after achieving the maximum production rate at which the equipment will be operated, but no later than 180 days after initial startup, unless the equipment is specifically exempted from testing in the applicable Subpart of 40 CFR 63. The specific pollutants, sample volumes, run times, and other testing parameters shall be as specified in the applicable Subpart of 40 CFR 63.

[40 CFR 63.7]

PART 5.0 REQUIREMENTS FOR MONITORING (Related to Data Collection)**5.1 General Monitoring Requirements**

- 5.1.1 Any continuous monitoring system required by the Division and installed by the Permittee shall be in continuous operation and data recorded during all periods of operation of the affected facility except for continuous monitoring system breakdowns and repairs. Monitoring system response, relating only to calibration checks and zero and span adjustments, shall be measured and recorded during such periods. Maintenance or repair shall be conducted in the most expedient manner to minimize the period during which the system is out of service.
[391-3-1-.02(6)(b)1]

5.2 Specific Monitoring Requirements

- 5.2.1 The Permittee shall install, calibrate, operate, and maintain, according to manufacturer's instructions, a breakthrough detector and interlock system, acceptable to the Director, to continuously monitor and indicate the hydrocarbon concentration at the outlet of the vapor recovery unit (C001). The breakthrough monitor and interlock system shall prevent gasoline loading operations upon detecting breakthrough (defined as an hourly hydrocarbon concentration exceeding 1.75 percent by volume as propane) at the outlet of the VRU. The interlock system shall also prevent gasoline loading operations whenever the proper system operating conditions (such as carbon bed temperature, separator liquid level, vacuum pump seal fluid level, vacuum booster blower oil level, gas supply pump operation, seal fluid pump operation, seal fluid temperature, regenerative valve operation, knockout tank liquid level, or system power failure) are not met.
[391-3-1-.02(2)(cc), 40 CFR 70.6(a)(3)(i)(A), and 40 CFR 60.502]
- 5.2.2 The Permittee shall install, calibrate, maintain, and operate a pressure measurement device on each terminal's vapor collection system (liquid manometer, magnahelic, or equivalent instrument) capable of measuring up to 500 mm of water gauge pressure with a precision of ± 2.5 mm water column. Each system shall meet the applicable performance specification(s) of the Division's monitoring requirements.
[40 CFR 60.502, 391-3-1-.02(6)(b)1, 391-3-1-.03(10)(d)1(i), and 40 CFR 70.6(a)(3)(i)A]
- 5.2.3 The Permittee shall install, calibrate, operate, and maintain, according to manufacturer's instructions, a device, acceptable to the Director, to continuously indicate and record when the vapor staging valve (the valve that releases vapors into the adsorber) is open.
[391-3-1-.02(6)(b)1 and 40 CFR 70.6(a)(3)(i)A]
- 5.2.4 The Permittee shall install, calibrate, operate, and maintain, according to manufacturer's instructions, a device, acceptable to the Director, to indicate and record when the VRU's safety relief or by-pass valve is open.
[391-3-1-.02(6)(b)1 and 40 CFR 70.6(a)(3)(i)A]

Title V Permit

- 5.2.5 The Permittee shall perform a monthly leak inspection of all equipment in gasoline service including the vapor collection system, the vapor processing system, and each loading rack handling gasoline shall be inspected during the loading of gasoline tank trucks. For this inspection, detection methods incorporating sight, sound, and smell are acceptable. A logbook shall be used and shall be signed by the Permittee at the completion of each inspection. A section of the logbook shall contain a list, summary description, or diagram(s) showing the location of all equipment in gasoline service at the facility. Each detection of a liquid or vapor leak shall be recorded in the logbook. When a leak is detected, an initial attempt at repair shall be made as soon as practicable, but no later than 5 calendar days after the leak is detected. Repair or replacement of leaking equipment shall be completed within 15 calendar days after detection of each leak, except delay of repair of leaking equipment will be allowed if the repair is not feasible within 15 days. The Permittee shall provide in the semiannual report specified in condition 6.1.7, the reason(s) why the repair was not feasible and the date each repair was completed.

[40 CFR 63.11088(a), 40 CFR 63.11089, and 40 CFR 60.502(j)]

- 5.2.6 The following pollutant specific emission unit (PSEU) is subject to the Compliance Assurance Monitoring (CAM) Rule under 40 CFR 64.

Emission Unit	Pollutant
Tanker Truck Loading Rack	VOC

Permit conditions in this permit for the PSEU listed above with regulatory citation 40 CFR 70.6(a)(3)(i) are included for the purpose of complying with 40 CFR 64. In addition, the Permittee shall meet the requirements, as applicable, of 40 CFR 64.7, 64.8, and 64.9.

[40 CFR 64]

- 5.2.7 The Permittee shall comply with the performance criteria listed in the table below for the Volatile Organic Compounds (VOC) emissions from the Tanker Truck Loading Rack (Emission Unit ID No. LR01).

[40 CFR 64.6(c)(1)(iii)]

Performance Criteria [64.4(a)(3)]	Indicator No. 1 Continuous Emission Monitoring System
A. Data Representativeness [64.3(b)(1)]	Continuously monitor and Indicate Hydrocarbon Concentration in percent by volume propane, at the outlet of the VRU.
B. Verification of Operational Status (new/modified monitoring equipment only) [64.3(b)(2)]	N/A
C. QA/QC Practices and Criteria [64.3(b)(3)]	Automatic drift check verification every 24 hours, daily inspections, quarterly maintenance inspection, quarterly CGA, and RATA after installation of new CEM, as part of performance test, or as requested by the Director.

Title V Permit

Performance Criteria [64.4(a)(3)]	Indicator No. 1 Continuous Emission Monitoring System
D. Monitoring Frequency [64.3(b)(4)]	Sampling interval is every 5 seconds.
E. Data Collection Procedures [64.3(b)(4)]	Data collection is done through the RACS Computer system.
F. Averaging Period [64.3(b)(4)]	Data averaging period is 720 data points per hour.

- 5.2.8 The Permittee shall install, calibrate, certify, operate, and maintain, according to the manufacturer's specifications, a continuous emissions monitoring system (CEMS) capable of measuring organic compound concentration in the exhaust air stream.
[40 CFR 63.11092(b)(1)(i)]
- 5.2.9 The Permittee shall comply with the following requirements for each of the gasoline storage tanks subject to the emission standard in Condition 3.3.4:
[40 CFR 63.11092(e)]
- a. For any gasoline storage tank equipped with an internal floating roof, the Permittee shall perform inspections of the floating roof system according to the requirements of 40 CFR 60.113b(a).
- 5.2.10 In accordance with 40 CFR 63 Subpart BBBBBB, the Permittee shall operate the vapor processing systems/carbon adsorption systems at this facility in a manner for the hydrocarbon concentration not to exceed 1.75 percent as stated in Condition 5.2.1.
[40 CFR 63.11092(d) and 40 CFR 60.502]
- 5.2.11 In accordance with 40 CFR 60.116b(c), (d), and (e)(1) and (e)(2), the Permittee shall determine and maintain records of the maximum true vapor pressure of material contained in Tank T012 when storing a volatile organic liquid of known composition or variable composition.
- 5.2.12 In accordance with 40 CFR 60.113b (a)(2) the Permittee shall visually inspect Tank T012 to ensure the physical integrity of the internal floating roofs and the primary seals or the secondary seals through manholes and roof hatches on the fixed roof at least once every 12 months.
- 5.2.13 In accordance with 40 CFR 60.113b(a)(4) each time Tank T012 is emptied and degassed, but no less than once every 10 years, the Permittee shall visually inspect and repair (if necessary) the internal floating roof, the primary seal, the secondary seal, gaskets, slotted membranes and sleeve seals and any other parameter/condition that adversely affects VOL containment. Each time the tank is emptied, all repairs shall be completed before storage vessel is refilled with VOL.

PART 6.0 RECORD KEEPING AND REPORTING REQUIREMENTS**6.1 General Record Keeping and Reporting Requirements**

- 6.1.1 Unless otherwise specified, all records required to be maintained by this Permit shall be recorded in a permanent form suitable for inspection and submission to the Division and to the EPA. The records shall be retained for at least five (5) years following the date of entry.

[391-3-1-.02(6)(b)1(i) and 40 CFR 70.6(a)(3)]

- 6.1.2 In addition to any other reporting requirements of this Permit, the Permittee shall report to the Division in writing, within seven (7) days, any deviations from applicable requirements associated with any malfunction or breakdown of process, fuel burning, or emissions control equipment for a period of four hours or more which results in excessive emissions.

The Permittee shall submit a written report that shall contain the probable cause of the deviation(s), duration of the deviation(s), and any corrective actions or preventive measures taken.

[391-3-1-.02(6)(b)1(iv), 391-3-1-.03(10)(d)1(i) and 40 CFR 70.6(a)(3)(iii)(B)]

- 6.1.3 The Permittee shall submit written reports of any failure to meet an applicable emission limitation or standard contained in this permit and/or any failure to comply with or complete a work practice standard or requirement contained in this permit which are not otherwise reported in accordance with Conditions 6.1.4 or 6.1.2. Such failures shall be determined through observation, data from any monitoring protocol, or by any other monitoring which is required by this permit. The reports shall cover each semiannual period ending June 30 and December 31 of each year, shall be postmarked by August 29 and February 28, respectively following each reporting period, and shall contain the probable cause of the failure(s), duration of the failure(s), and any corrective actions or preventive measures taken.

[391-3-1-.03(10)(d)1.(i) and 40 CFR 70.6(a)(3)(iii)(B)]

- 6.1.4 The Permittee shall submit a written report containing any excess emissions, exceedances, and/or excursions as described in this permit and any monitor malfunctions for each semiannual period ending June 30 and December 31 of each year. All reports shall be postmarked by August 29 and February 28, respectively following each reporting period. In the event that there have not been any excess emissions, exceedances, excursions or malfunctions during a reporting period, the report should so state. Otherwise, the contents of each report shall be as specified by the Division's Procedures for Testing and Monitoring Sources of Air Pollutants and shall contain the following:

[391-3-1-.02(6)(b)1 and 40 CFR 70.6(a)(3)(iii)(A)]

- a. A summary report of excess emissions, exceedances and excursions, and monitor downtime, in accordance with Section 1.5(c) and (d) of the above referenced document, including any failure to follow required work practice procedures.
- b. Total process operating time during each reporting period.

Title V Permit

- c. The magnitude of all excess emissions, exceedances and excursions computed in accordance with the applicable definitions as determined by the Director, and any conversion factors used, and the date and time of the commencement and completion of each time period of occurrence.
- d. Specific identification of each period of such excess emissions, exceedances, and excursions that occur during startups, shutdowns, or malfunctions of the affected facility. Include the nature and cause of any malfunction (if known), the corrective action taken or preventive measures adopted.
- e. The date and time identifying each period during which any required monitoring system or device was inoperative (including periods of malfunction) except for zero and span checks, and the nature of the repairs, adjustments, or replacement. When the monitoring system or device has not been inoperative, repaired, or adjusted, such information shall be stated in the report.
- f. Certification by a Responsible Official that, based on information and belief formed after reasonable inquiry, the statements and information in the report are true, accurate, and complete.

6.1.5 Where applicable, the Permittee shall keep the following records:
[391-3-1-.03(10)(d)1(i) and 40 CFR 70.6(a)(3)(ii)(A)]

- a. The date, place, and time of sampling or measurement;
- b. The date(s) analyses were performed;
- c. The company or entity that performed the analyses;
- d. The analytical techniques or methods used;
- e. The results of such analyses; and
- f. The operating conditions as existing at the time of sampling or measurement.

6.1.6 The Permittee shall maintain files of all required measurements, including continuous monitoring systems, monitoring devices, and performance testing measurements; all continuous monitoring system or monitoring device calibration checks; and adjustments and maintenance performed on these systems or devices. These files shall be kept in a permanent form suitable for inspection and shall be maintained for a period of at least five (5) years following the date of such measurements, reports, maintenance and records.
[391-3-1-.03(10)(d)1(i) and 40 CFR 70.6 (a)(3)(ii)(B)]

6.1.7 For the purpose of reporting excess emissions, exceedances or excursions in the report required in Condition 6.1.4, the following excess emissions, exceedances, and excursions shall be reported:
[391-3-1-.02(6)(b)1, 40 CFR 70.6(a)(3)(i) and (iii), 40 CFR 60.502(e), 40 CFR 63.11095(a)(2) and (3) and 63.11095(b)(1), (2) and (5)]

Title V Permit

- a. Excess emissions: (means for the purpose of this Condition and Condition 6.1.4, any condition that is detected by monitoring or record keeping which is specifically defined, or stated to be, excess emissions by an applicable requirement)
 - i. Each instance of an excess emission caused by the opening of any pressure-vacuum vents on the terminal's vapor collection system or excess emissions from the delivery tank during product loading, as described in Condition 5.2.2.
 - ii. Each instance of a non-vapor tight gasoline cargo tank loading at the facility in which Permittee failed to take steps to assure that such cargo tank would not be reloaded at the facility before vapor tightness documentation for that cargo tank was obtained.
 - iii. Each reloading of a non-vapor tight gasoline cargo tank at the facility before vapor tightness documentation for that cargo tank is obtained by the facility in accordance with Condition 6.2.7b. (40 CFR 63.11094(b)).
 - iv. Each instance the hydrocarbon concentration exceeds 1.75 percent as required by Condition 5.2.1.
 - v. For each occurrence of an equipment leak for which no repair attempt was made within 5 days or for which repair was not completed within 15 days after detection:
 - (A) The date on which the leak was detected;
 - (B) The date of each attempt to repair the leak;
 - (C) The reasons for the delay of repair; and
 - (D) The date of successful repair.
- b. Exceedances: (means for the purpose of this Condition and Condition 6.1.4, any condition that is detected by monitoring or record keeping that provides data in terms of an emission limitation or standard and that indicates that emissions (or opacity) do not meet the applicable emission limitation or standard consistent with the averaging period specified for averaging the results of the monitoring)
 - i. Each instance of a non-vapor-tight gasoline cargo tank loading at the facility in which the owner or operator failed to take steps to assure that such cargo tank would not be reloaded at the facility before vapor tightness documentation for that cargo tank was obtained.
- c. Excursions: (means for the purpose of this Condition and Condition 6.1.4, any departure from an indicator range or value established for monitoring consistent with any averaging period specified for averaging the results of the monitoring)

None required to be reported in accordance with Condition 6.1.4.

- d. In addition to the excess emissions, exceedances and excursions specified above, the following should also be included with the report required in Condition 6.1.4:
 - i. For loading racks, each loading of a gasoline cargo tank for which vapor tightness documentation had not been previously obtained by the facility.
 - ii. For equipment leak inspections, the number of equipment leaks not repaired within 15 days after the detection.

- 6.1.8 The Permittee shall provide the Division with a statement, in such form as the Director may prescribe, showing the actual emissions of nitrogen oxides and volatile organic compounds from the entire facility. These statements shall be submitted every year by the date specified in 391-3-1-.02(6)(a)4 and shall show the actual emissions of the previous calendar year.
[391-3-1-.02(6)(b)1(i)]

6.2 Specific Record Keeping and Reporting Requirements

- 6.2.1 The Permittee shall maintain monthly records of HAP emissions from all affected sources at the facility. The Permittee shall use the monthly records to determine the total monthly emissions of combined hazardous air pollutants and the total monthly emissions of each listed hazardous air pollutant from the entire facility. All calculations used to determine the emissions should also be kept as part of the monthly record.
[391-3-1-.02(6)(b)1]
- 6.2.2 The Permittee shall use the records required by Condition 6.2.1 to determine the twelve-month rolling total emissions of each individual HAP for each month and the twelve-month rolling total combined HAP emissions for each month from the entire facility for each calendar month. The Permittee shall notify the Division in writing if the combined HAP emissions from the entire facility equal or exceed 25 tons and/or any individual HAP equals or exceeds 10 tons during any consecutive twelve-month period. This notification shall be postmarked by the fifteenth day of the following month and shall include an explanation of how the Permittee intends to attain compliance with the emission limit in Condition 2.1.1.
[391-3-1-.02(6)(b)1] [Vault OT-054-RR, 09/11]
- 6.2.3 The Permittee shall keep records at the terminal of the monthly leak inspections required by Condition 5.2.5. The documentation file shall be kept up-to-date and shall include, as a minimum, the following information:
[40 CFR 60.505(c), 391-3-1-.03(10)(d)1(i), and 40 CFR 70.6(a)(3)B]
- a. Date of inspection.
 - b. Findings (may indicate no leaks discovered; or location, nature and severity of each leak).
 - c. Leak determination method.

Title V Permit

- d. Corrective action (date each leak repaired; reasons for any repair interval in excess of 15 days).
 - e. Inspector name, signature, and affiliation.
- 6.2.4 Records shall be kept of each shutdown, malfunction and the subsequent maintenance performed on the vapor control system. Records shall be maintained on site for a period of at least five (5) years.
[391-3-1-.02(2)(cc)]
- 6.2.5 For purposes of the report required in Condition 6.1.4, the Permittee shall keep records of the following events:
[40 CFR 70.6(a)(3)(iii)(A) and 40 CFR 60.502(e)]
- a. Each instance of a leak detection found during the monthly inspections specified in Condition 5.2.5, or a pressure measurement in excess of 500 mm in accordance with Condition 5.2.2. The report shall include the monitoring data for the days on which the excursion occurred, and a description and timing of the steps taken to repair or perform maintenance on the vapor collection and processing systems and the monitoring systems.
 - b. Each instance of a gasoline cargo tank, which is not vapor-tight, loading at the facility in which the owner or operator failed to take steps to assure that such cargo tank would not be reloaded at the facility before vapor tightness documentation for that cargo tank was obtained.
 - c. For each occurrence of an equipment leak for which no repair attempt was made within 5 days or for which repair was not completed within 15 days after detection:
 - i. The date on which the leak was detected;
 - ii. The date of each attempt to repair the leak;
 - iii. The reasons for the delay of repair; and
 - iv. The date of successful repair.
 - d. Each instance of emissions from the opening of any pressure-vacuum vent on each terminal's vapor collection system or emissions from the delivery tank during product loading.
- 6.2.6 The Permittee shall keep an up-to-date, readily accessible record of the continuous monitoring data required under Condition 5.2.1 of this permit. This record shall indicate the time intervals during which loadings of gasoline cargo tanks have occurred or, alternatively, shall record the operating parameter data only during such loadings. The date and time of day shall also be indicated at reasonable intervals on this record.
[391-3-1-.02(2)(cc)]

Title V Permit

- 6.2.7 The Permittee shall keep records as specified in paragraphs a. through f. of this condition. In particular, the Permittee shall:
[40 CFR 63.9, 40 CFR 63.11094, 40 CFR 60.505(b), and 391-3-1-.02(2)(ss)]
- a. Keep records, as specified in 40 CFR 60.115b, for storage vessels subject to Subpart BBBBBB and complying with options 2(a), 2(b), or 2(c) in Condition 3.3.4a. (Table 1 to Subpart BBBBBB). The records shall be kept for at least 5 years.
 - b. Keep records of the test results for each gasoline cargo tank loading at the facility as specified below:
 - i. Annual certification testing performed under 40 CFR 63.11092(f)(1) and periodic railcar bubble leak testing performed under 40 CFR 63.11092(f)(2).
 - ii. The documentation file shall be kept up-to-date for each gasoline cargo tank loading at the facility. The documentation for each test shall include, as a minimum, the following information:
 - (A) Name of test: Annual Certification Test—Method 27 or Periodic Railcar Bubble Leak Test Procedure.
 - (B) Cargo tank owner's name and address.
 - (C) Cargo tank identification number.
 - (D) Test location and date.
 - (E) Tester name and signature.
 - (F) Witnessing inspector, if any: Name, signature, and affiliation.
 - (G) Vapor tightness repair: Nature of repair work and when performed in relation to vapor tightness testing.
 - (H) Test results: Test pressure; pressure or vacuum change, mm of water; time period of test; number of leaks found with instrument; and leak definition.
 - c. As an alternative to keeping records at the terminal of each gasoline cargo tank test result as required in subparagraph b., comply with one of the requirements below:
 - i. Keeping an instantly available electronic copy of each record at the terminal. The electric copy shall be an exact duplicate image of the original paper record with certifying signatures. The Division shall be notified in writing that each terminal using this alternative is in compliance with this requirement.

Title V Permit

- ii. For facilities that use a terminal automation system to prevent gasoline cargo tanks that do not have valid cargo tank vapor tightness documentation from loading (e.g., via a card lockout system), a copy of the documentation shall be made available (e.g., via facsimile) for inspection by the Division's representatives during the course of a site visit, or within a mutually agreeable time frame. The copy of each record/documentation shall be an exact duplicate image of the original paper record with certifying signatures. The Division shall be notified in writing that each terminal using this alternative is in compliance with this requirement.
- d. For equipment subject to the leak provisions of Condition 5.2.5 (40 CFR 63.11089), the Permittee shall prepare and maintain a record describing the types, identification numbers, and locations of all equipment in gasoline service. For facilities electing to implement an instrument program under Condition 5.2.5 (40 CFR 63.11089), the record shall contain a full description of the program.
- e. For equipment subject to leak inspections under Condition 5.2.5 (40 CFR 63.11089), the Permittee shall record in the log book the following information for each leak that is detected:
 - i. The equipment type and identification number.
 - ii. The nature of the leak (i.e., vapor or liquid) and the method of detection (i.e., sight, sound, or smell).
 - iii. The date the leak was detected and the date of each attempt to repair the leak.
 - iv. Repair methods applied in each attempt to repair the leak.
 - v. "Repair delayed" and the reason for the delay if the leak is not repaired within 15 calendar days after discovery of the leak.
 - vi. The expected date of successful repair of the leak if the leak is not repaired within 15 days.
 - vii. The date of successful repair of the leak.
- f. The Permittee shall keep an up-to-date, readily accessible record of the continuous monitoring data required under Condition 5.2.8 (40 CFR 63.11092(e)). This record shall indicate the time intervals during which loadings of gasoline cargo tanks have occurred or, alternatively, shall record the operating parameter data only during such loadings. The date and time of day shall also be indicated at reasonable intervals on this record.

Title V Permit

- 6.2.8 The Permittee shall keep records as specified in paragraphs a. and b. of this condition.
[40 CFR 63.11094(g)]
- a. Records of the occurrence and duration of each malfunction of operation (i.e., process equipment) or the air pollution control and monitoring equipment.
 - b. Records of actions taken during periods of malfunction to minimize emissions in accordance with Condition 8.17.1 including corrective actions to restore malfunctioning process and air pollution control and monitoring equipment to its normal or usual manner of operation.
- 6.2.9 The Permittee shall report the number, duration, and a brief description of each type of malfunction which occurred during the reporting period, and which caused or may have caused any applicable emission limitation to be exceeded. The report must also include a description of actions taken by the Permittee during a malfunction of an affected source to minimize emissions in accordance with Condition 8.17.1, including actions taken to correct a malfunction. The report may be submitted as a part of the semiannual compliance report.
[40 CFR 63.11095(d)]
- 6.2.10 For storage vessels/tanks complying with Condition 3.3.4b, the Notice of Compliance Status information can be included in the next semi-annual compliance report specified in Condition 6.1.4 in lieu of filing a separate Notice of Compliance Status report as required by 40 CFR 63.11093.
[40 CFR 63.11095(a)(4)]
- 6.2.11 In accordance with 40 CFR 60.116b, for Tank T012, the Permittee shall maintain a record of the following information at the facility. The information shall be available for inspection or submittal to the Division.
- a. A record of the dimensions of each storage tank and an analysis showing the capacity of the said tank shall be maintained for the life of the source.
 - b. A record on the volatile organic liquid (VOL) stored, the period of storage, and the maximum true vapor pressure of that VOL during the respective storage period.
- 6.2.12 The Permittee shall keep a record of each inspection performed as required by Conditions 5.2.9, 5.2.12, and 5.2.13. Each record shall identify the storage vessel on which the inspection was performed and shall contain the date the vessel was inspected and the observed condition of each component of the control equipment (seals, internal floating roof and fittings).
[40 CFR 60.113b]
- 6.2.13 If any failures are detected by the visual inspection required by Conditions 5.2.9, 5.2.12, and 5.2.13, a report shall be furnished to the Director within 30 days of the inspection. Each report shall identify the storage vessel, the nature of the defects, and the date the storage vessel was emptied, if applicable, or the nature of and date the repair was made. The report shall identify the storage vessel and the reason it did not meet the specifications.
[40 CFR 60.115b(a)(3)]

Title V Permit

- 6.2.14 In accordance with 40 CFR 60.113b the Permittee shall notify the Director in writing at least 30 days prior to the filling or refilling of each storage vessel for which an inspection is required by Condition 5.2.12. If an inspection, required by Conditions 5.2.9 and/or 5.2.12 and 5.2.13 of this permit, is not planned and the Permittee could not have known about the inspection 30 days in advance of refilling the tank, the Permittee shall notify the Director at least 7 days prior to the refilling of the storage vessel. Notification shall be made by telephone immediately followed by written documentation demonstrating why the inspection was unplanned. Alternatively, this notification including the written documentation may be made in writing and sent by express mail, if necessary, so that it is received by the Director at least 7 days prior to the refilling.
[40 CFR 60.113b(a)(5)]
- 6.2.15 If a failure that is detected during inspections required in Conditions 5.2.9, 5.2.12, and 5.2.13 cannot be repaired within 45 days and if the vessel cannot be emptied within 45 days, a 30-day extension may be requested from the Director in the inspection report required in accordance with 40 CFR Part 60.113b(a). Such a request for an extension must document that alternate storage capacity is unavailable and specify a schedule of actions the company will take that will assure that the control equipment will be repaired or the vessel will be emptied as soon as possible. The Director shall receive written notification at least 7 days prior to refilling any tank emptied as a result of required inspection.
[40 CFR 60.113b(a)(2)]

PART 7.0 OTHER SPECIFIC REQUIREMENTS**7.1 Operational Flexibility**

7.1.1 The Permittee may make Section 502(b)(10) changes as defined in 40 CFR 70.2 without requiring a Permit revision, if the changes are not modifications under any provisions of Title I of the Federal Act and the changes do not exceed the emissions allowable under the Permit (whether expressed therein as a rate of emissions or in terms of total emissions). For each such change, the Permittee shall provide the Division and the EPA with written notification as required below in advance of the proposed changes and shall obtain any Permits required under Rules 391-3-1-.03(1) and (2). The Permittee and the Division shall attach each such notice to their copy of this Permit.
[391-3-1-.03(10)(b)5 and 40 CFR 70.4(b)(12)(i)]

- a. For each such change, the Permittee's written notification and application for a construction Permit shall be submitted well in advance of any critical date (typically at least 3 months in advance of any commencement of construction, Permit issuance date, etc.) involved in the change, but no less than seven (7) days in advance of such change and shall include a brief description of the change within the Permitted facility, the date on which the change is proposed to occur, any change in emissions, and any Permit term or condition that is no longer applicable as a result of the change.
- b. The Permit shield described in Condition 8.16.1 shall not apply to any change made pursuant to this condition.

7.2 Off-Permit Changes

7.2.1 The Permittee may make changes that are not addressed or prohibited by this Permit, other than those described in Condition 7.2.2 below, without a Permit revision, provided the following requirements are met:
[391-3-1-.03(10)(b)6 and 40 CFR 70.4(b)(14)]

- a. Each such change shall meet all applicable requirements and shall not violate any existing Permit term or condition.
- b. The Permittee must provide contemporaneous written notice to the Division and to the EPA of each such change, except for changes that qualify as insignificant under Rule 391-3-1-.03(10)(g). Such written notice shall describe each such change, including the date, any change in emissions, pollutants emitted, and any applicable requirement that would apply as a result of the change.
- c. The change shall not qualify for the Permit shield in Condition 8.16.1.
- d. The Permittee shall keep a record describing changes made at the source that result in emissions of a regulated air pollutant subject to an applicable requirement, but not otherwise regulated under the Permit, and the emissions resulting from those changes.

- 7.2.2 The Permittee shall not make, without a Permit revision, any changes that are not addressed or prohibited by this Permit, if such changes are subject to any requirements under Title IV of the Federal Act or are modifications under any provision of Title I of the Federal Act.
[Rule 391-3-1-.03(10)(b)7 and 40 CFR 70.4(b)(15)]

7.3 Alternative Requirements

[White Paper #2]

Not Applicable

7.4 Insignificant Activities

(see Attachment B for the list of Insignificant Activities in existence at the facility at the time of permit issuance)

7.5 Temporary Sources

[391-3-1-.03(10)(d)5 and 40 CFR 70.6(e)]

Not Applicable

7.6 Short-term Activities

- Tank cleaning as needed (1-day duration)
- Tank painting as needed (1-week duration)
- Filter changeout as needed (1-day duration)

7.7 Compliance Schedule/Progress Reports

[391-3-1-.03(10)(d)3 and 40 CFR 70.6(c)(4)]

None Applicable

7.8 Emissions Trading

[391-3-1-.03(10)(d)1(ii) and 40 CFR 70.6(a)(10)]

Not Applicable

7.9 Acid Rain Requirements

Not Applicable

7.10 Prevention of Accidental Releases (Section 112(r) of the 1990 CAAA)

[391-3-1-.02(10)]

- 7.10.1 When and if the requirements of 40 CFR Part 68 become applicable, the Permittee shall comply with all applicable requirements of 40 CFR Part 68, including the following.
- a. The Permittee shall submit a Risk Management Plan (RMP) as provided in 40 CFR 68.150 through 68.185. The RMP shall include a registration that reflects all covered processes.

Title V Permit

- b. For processes eligible for Program 1, as provided in 40 CFR 68.10, the Permittee shall comply with 7.10.1.a. and the following additional requirements:
 - i. Analyze the worst-case release scenario for the process(es), as provided in 40 CFR 68.25; document that the nearest public receptor is beyond the distance to a toxic or flammable endpoint defined in 40 CFR 68.22(a); and submit in the RMP the worst-case release scenario as provided in 40 CFR 68.165.
 - ii. Complete the five-year accident history for the process as provided in 40 CFR 68.42 and submit in the RMP as provided in 40 CFR 68.168
 - iii. Ensure that response actions have been coordinated with local emergency planning and response agencies
 - iv. Include a certification in the RMP as specified in 40 CFR 68.12(b)(4)
- c. For processes subject to Program 2, as provided in 40 CFR 68.10, the Permittee shall comply with 7.10.1.a., 7.10.1.b. and the following additional requirements:
 - i. Develop and implement a management system as provided in 40 CFR 68.15
 - ii. Conduct a hazard assessment as provided in 40 CFR 68.20 through 68.42
 - iii. Implement the Program 2 prevention steps provided in 40 CFR 68.48 through 68.60 or implement the Program 3 prevention steps provided in 40 CFR 68.65 through 68.87
 - iv. Develop and implement an emergency response program as provided in 40 CFR 68.90 through 68.95
 - v. Submit as part of the RMP the data on prevention program elements for Program 2 processes as provided in 40 CFR 68.170
- d. For processes subject to Program 3, as provided in 40 CFR 68.10, the Permittee shall comply with 7.10.1.a., 7.10.1.b. and the following additional requirements:
 - i. Develop and implement a management system as provided in 40 CFR 68.15
 - ii. Conduct a hazard assessment as provided in 40 CFR 68.20 through 68.42
 - iii. Implement the prevention requirements of 40 CFR 68.65 through 68.87
 - iv. Develop and implement an emergency response program as provided in 40 CFR 68.90 through 68.95
 - v. Submit as part of the RMP the data on prevention program elements for Program 3 as provided in 40 CFR 68.175
- e. All reports and notification required by 40 CFR Part 68 must be submitted electronically using RMP*eSubmit (information for establishing an account can be found at www.epa.gov/rmp/rmpesubmit). Electronic Signature Agreements should be mailed to:

MAIL

**Risk Management Program (RMP) Reporting Center
P.O. Box 10162
Fairfax, VA 22038**

COURIER & FEDEX

**Risk Management Program (RMP) Reporting Center
CGI Federal
12601 Fair Lakes Circle
Fairfax, VA 22033**

Compliance with all requirements of this condition, including the registration and submission of the RMP, shall be included as part of the compliance certification submitted in accordance with Condition 8.14.1.

7.11 Stratospheric Ozone Protection Requirements (Title VI of the CAAA of 1990)

- 7.11.1 If the Permittee performs any of the activities described below or as otherwise defined in 40 CFR Part 82, the Permittee shall comply with the standards for recycling and emissions reduction pursuant to 40 CFR Part 82, Subpart F, except as provided for motor vehicle air conditioners (MVACs) in Subpart B:
- a. Persons opening appliances for maintenance, service, repair, or disposal must comply with the required practices pursuant to 40 CFR 82.156.
 - b. Equipment used during the maintenance, service, repair, or disposal of appliance must comply with the standards for recycling and recovery equipment pursuant to 40 CFR 82.158.
 - c. Persons performing maintenance, service, repair, or disposal of appliances must be certified by an approved technician certification program pursuant to 40 CFR 82.161.
 - d. Persons disposing of small appliances, MVACs, and MVAC-like appliances must comply with record keeping requirements pursuant to 40 CFR 82.166.
[Note: “MVAC-like appliance” is defined in 40 CFR 82.152.]
 - e. Persons owning commercial or industrial process refrigeration equipment must comply with the leak repair requirements pursuant to 40 CFR 82.156.
 - f. Owners/operators of appliances normally containing 50 or more pounds of refrigerant must keep records of refrigerant purchased and added to such appliances pursuant to 40 CFR 82.166.
- 7.11.2 If the Permittee performs a service on motor (fleet) vehicles and if this service involves an ozone-depleting substance (refrigerant) in the MVAC, the Permittee is subject to all the applicable requirements as specified in 40 CFR Part 82, Subpart B, Servicing of Motor Vehicle Air Conditioners.

The term “motor vehicle” as used in Subpart B does not include a vehicle in which final assembly of the vehicle has not been completed. The term “MVAC” as used in Subpart B does not include air-tight sealed refrigeration systems used for refrigerated cargo, or air conditioning systems on passenger buses using HCFC-22 refrigerant.

7.12 Revocation of Existing Permits and Amendments

The following Air Quality Permits, Amendments, and 502(b)10 are subsumed by this permit and are hereby revoked:

Air Quality Permit and Amendment Number(s)	Dates of Original Permit or Amendment Issuance
5171-089-0100-V-04-0	January 30, 2017

7.13 Pollution Prevention

Not Applicable

7.14 Specific Conditions

Not Applicable

PART 8.0 GENERAL PROVISIONS

8.1 Terms and References

- 8.1.1 Terms not otherwise defined in the Permit shall have the meaning assigned to such terms in the referenced regulation.
- 8.1.2 Where more than one condition in this Permit applies to an emission unit and/or the entire facility, each condition shall apply and the most stringent condition shall take precedence.
[391-3-1-.02(2)(a)2]

8.2 EPA Authorities

- 8.2.1 Except as identified as “State-only enforceable” requirements in this Permit, all terms and conditions contained herein shall be enforceable by the EPA and citizens under the Clean Air Act, as amended, 42 U.S.C. 7401, et seq.
[40 CFR 70.6(b)(1)]
- 8.2.2 Nothing in this Permit shall alter or affect the authority of the EPA to obtain information pursuant to 42 U.S.C. 7414, “Inspections, Monitoring, and Entry.”
[40 CFR 70.6(f)(3)(iv)]
- 8.2.3 Nothing in this Permit shall alter or affect the authority of the EPA to impose emergency orders pursuant to 42 U.S.C. 7603, “Emergency Powers.”
[40 CFR 70.6(f)(3)(i)]

8.3 Duty to Comply

- 8.3.1 The Permittee shall comply with all conditions of this operating Permit. Any Permit noncompliance constitutes a violation of the Federal Clean Air Act and the Georgia Air Quality Act and/or State rules and is grounds for enforcement action; for Permit termination, revocation and reissuance, or modification; or for denial of a Permit renewal application. Any noncompliance with a Permit condition specifically designated as enforceable only by the State constitutes a violation of the Georgia Air Quality Act and/or State rules only and is grounds for enforcement action; for Permit termination, revocation and reissuance, or modification; or for denial of a Permit renewal application.
[391-3-1-.03(10)(d)1(i) and 40 CFR 70.6(a)(6)(i)]
- 8.3.2 The Permittee shall not use as a defense in an enforcement action the contention that it would have been necessary to halt or reduce the Permitted activity in order to maintain compliance with the conditions of this Permit.
[391-3-1-.03(10)(d)1(i) and 40 CFR 70.6(a)(6)(ii)]
- 8.3.3 Nothing in this Permit shall alter or affect the liability of the Permittee for any violation of applicable requirements prior to or at the time of Permit issuance.
[391-3-1-.03(10)(d)1(i) and 40 CFR 70.6(f)(3)(ii)]

- 8.3.4 Issuance of this Permit does not relieve the Permittee from the responsibility of obtaining any other permits, licenses, or approvals required by the Director or any other federal, state, or local agency.
[391-3-1-.03(10)(e)1(iv) and 40 CFR 70.7(a)(6)]

8.4 Fee Assessment and Payment

- 8.4.1 The Permittee shall calculate and pay an annual Permit fee to the Division. The amount of fee shall be determined each year in accordance with the “Procedures for Calculating Air Permit Fees.”
[391-3-1-.03(9)]

8.5 Permit Renewal and Expiration

- 8.5.1 This Permit shall remain in effect for five (5) years from the issuance date. The Permit shall become null and void after the expiration date unless a timely and complete renewal application has been submitted to the Division at least six (6) months, but no more than eighteen (18) months prior to the expiration date of the Permit.
[391-3-1-.03(10)(d)1(i), (e)2, and (e)3(ii) and 40 CFR 70.5(a)(1)(iii)]
- 8.5.2 Permits being renewed are subject to the same procedural requirements, including those for public participation and affected State and EPA review, that apply to initial Permit issuance.
[391-3-1-.03(10)(e)3(i)]
- 8.5.3 Notwithstanding the provisions in 8.5.1 above, if the Division has received a timely and complete application for renewal, deemed it administratively complete, and failed to reissue the Permit for reasons other than cause, authorization to operate shall continue beyond the expiration date to the point of Permit modification, reissuance, or revocation.
[391-3-1-.03(10)(e)3(iii)]

8.6 Transfer of Ownership or Operation

- 8.6.1 This Permit is not transferable by the Permittee. Future owners and operators shall obtain a new Permit from the Director. The new Permit may be processed as an administrative amendment if no other change in this Permit is necessary, and provided that a written agreement containing a specific date for transfer of Permit responsibility coverage and liability between the current and new Permittee has been submitted to the Division at least thirty (30) days in advance of the transfer.
[391-3-1-.03(4)]

8.7 Property Rights

- 8.7.1 This Permit shall not convey property rights of any sort, or any exclusive privileges.
[391-3-1-.03(10)(d)1(i) and 40 CFR 70.6(a)(6)(iv)]

8.8 Submissions

- 8.8.1 Reports, test data, monitoring data, notifications, annual certifications, and requests for revision and renewal shall be submitted to:

**Georgia Department of Natural Resources
Environmental Protection Division
Air Protection Branch
Atlanta Tradeport, Suite 120
4244 International Parkway
Atlanta, Georgia 30354-3908**

- 8.8.2 Any records, compliance certifications, and monitoring data required by the provisions in this Permit to be submitted to the EPA shall be sent to:

**Air and Radiation Division
Air Planning and Implementation Branch
U. S. EPA Region 4
Sam Nunn Atlanta Federal Center
61 Forsyth Street, SW
Atlanta, Georgia 30303-3104**

- 8.8.3 Any application form, report, or compliance certification submitted pursuant to this Permit shall contain a certification by a responsible official of its truth, accuracy, and completeness. This certification shall state that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.

[391-3-1-.03(10)(c)2, 40 CFR 70.5(d) and 40 CFR 70.6(c)(1)]

- 8.8.4 Unless otherwise specified, all submissions under this permit shall be submitted to the Division only.

8.9 Duty to Provide Information

- 8.9.1 The Permittee, upon becoming aware that any relevant facts were omitted or incorrect information was submitted in the Permit application, shall promptly submit such supplementary facts or corrected information to the Division.

[391-3-1-.03(10)(c)5]

- 8.9.2 The Permittee shall furnish to the Division, in writing, information that the Division may request to determine whether cause exists for modifying, revoking and reissuing, or terminating the Permit, or to determine compliance with the Permit. Upon request, the Permittee shall also furnish to the Division copies of records that the Permittee is required to keep by this Permit or, for information claimed to be confidential, the Permittee may furnish such records directly to the EPA, if necessary, along with a claim of confidentiality.

[391-3-1-.03(10)(d)1(i) and 40 CFR 70.6(a)(6)(v)]

8.10 Modifications

- 8.10.1 Prior to any source commencing a modification as defined in 391-3-1-.01(pp) that may result in air pollution and not exempted by 391-3-1-.03(6), the Permittee shall submit a Permit application to the Division. The application shall be submitted sufficiently in advance of any critical date involved to allow adequate time for review, discussion, or revision of plans, if necessary. Such application shall include, but not be limited to, information describing the precise nature of the change, modifications to any emission control system, production capacity of the plant before and after the change, and the anticipated completion date of the change. The application shall be in the form of a Georgia air quality Permit application to construct or modify (otherwise known as a SIP application) and shall be submitted on forms supplied by the Division, unless otherwise notified by the Division.
[391-3-1-.03(1) through (8)]

8.11 Permit Revision, Revocation, Reopening and Termination

- 8.11.1 This Permit may be revised, revoked, reopened and reissued, or terminated for cause by the Director. The Permit will be reopened for cause and revised accordingly under the following circumstances:
[391-3-1-.03(10)(d)1(i)]
- a. If additional applicable requirements become applicable to the source and the remaining Permit term is three (3) or more years. In this case, the reopening shall be completed no later than eighteen (18) months after promulgation of the applicable requirement. A reopening shall not be required if the effective date of the requirement is later than the date on which the Permit is due to expire, unless the original permit or any of its terms and conditions has been extended under Condition 8.5.3;
[391-3-1-.03(10)(e)6(i)(I)]
 - b. If any additional applicable requirements of the Acid Rain Program become applicable to the source;
[391-3-1-.03(10)(e)6(i)(II)] (Acid Rain sources only)
 - c. The Director determines that the Permit contains a material mistake or inaccurate statements were made in establishing the emissions standards or other terms or conditions of the Permit; or
[391-3-1-.03(10)(e)6(i)(III) and 40 CFR 70.7(f)(1)(iii)]
 - d. The Director determines that the Permit must be revised or revoked to assure compliance with the applicable requirements.
[391-3-1-.03(10)(e)6(i)(IV) and 40 CFR 70.7(f)(1)(iv)]
- 8.11.2 Proceedings to reopen and reissue a Permit shall follow the same procedures as applicable to initial Permit issuance and shall affect only those parts of the Permit for which cause to reopen exists. Reopenings shall be made as expeditiously as practicable.
[391-3-1-.03(10)(e)6(ii)]

- 8.11.3 Reopenings shall not be initiated before a notice of intent to reopen is provided to the source by the Director at least thirty (30) days in advance of the date the Permit is to be reopened, except that the Director may provide a shorter time period in the case of an emergency.
[391-3-1-.03(10)(e)6(iii)]
- 8.11.4 All Permit conditions remain in effect until such time as the Director takes final action. The filing of a request by the Permittee for any Permit revision, revocation, reissuance, or termination, or of a notification of planned changes or anticipated noncompliance, shall not stay any Permit condition.
[391-3-1-.03(10)(d)1(i) and 40 CFR 70.6(a)(6)(iii)]
- 8.11.5 A Permit revision shall not be required for changes that are explicitly authorized by the conditions of this Permit.
- 8.11.6 A Permit revision shall not be required for changes that are part of an approved economic incentive, marketable Permit, emission trading, or other similar program or process for change which is specifically provided for in this Permit.
[391-3-1-.03(10)(d)1(i) and 40 CFR 70.6(a)(8)]

8.12 Severability

- 8.12.1 Any condition or portion of this Permit which is challenged, becomes suspended or is ruled invalid as a result of any legal or other action shall not invalidate any other portion or condition of this Permit.
[391-3-1-.03(10)(d)1(i) and 40 CFR 70.6(a)(5)]

8.13 Excess Emissions Due to an Emergency

- 8.13.1 An “emergency” means any situation arising from sudden and reasonably unforeseeable events beyond the control of the source, including acts of God, which situation requires immediate corrective action to restore normal operation, and that causes the source to exceed a technology-based emission limitation under the Permit, due to unavoidable increases in emissions attributable to the emergency. An emergency shall not include noncompliance to the extent caused by improperly designed equipment, lack of preventative maintenance, careless or improper operation, or operator error.
[391-3-1-.03(10)(d)7 and 40 CFR 70.6(g)(1)]
- 8.13.2 An emergency shall constitute an affirmative defense to an action brought for noncompliance with the technology-based emission limitations if the Permittee demonstrates, through properly signed contemporaneous operating logs or other relevant evidence, that:
- a. An emergency occurred and the Permittee can identify the cause(s) of the emergency;
- b. The Permitted facility was at the time of the emergency being properly operated;

- c. During the period of the emergency, the Permittee took all reasonable steps to minimize levels of emissions that exceeded the emissions standards, or other requirements in the Permit; and
 - d. The Permittee promptly notified the Division and submitted written notice of the emergency to the Division within two (2) working days of the time when emission limitations were exceeded due to the emergency. This notice must contain a description of the emergency, any steps taken to mitigate emissions, and corrective actions taken.
- 8.13.3 In an enforcement proceeding, the Permittee seeking to establish the occurrence of an emergency shall have the burden of proof.
[391-3-1-.03(10)(d)7 and 40 CFR 70.6(g)(4)]
- 8.13.4 The emergency conditions listed above are in addition to any emergency or upset provisions contained in any applicable requirement.
[391-3-1-.03(10)(d)7 and 40 CFR 70.6(g)(5)]

8.14 Compliance Requirements

8.14.1 Compliance Certification

The Permittee shall provide written certification to the Division and to the EPA, at least annually, of compliance with the conditions of this Permit. The annual written certification shall be postmarked no later than February 28 of each year and shall be submitted to the Division and to the EPA. The certification shall include, but not be limited to, the following elements:

[391-3-1-.03(10)(d)3 and 40 CFR 70.6(c)(5)]

- a. The identification of each term or condition of the Permit that is the basis of the certification;
- b. The status of compliance with the terms and conditions of the permit for the period covered by the certification, including whether compliance during the period was continuous or intermittent, based on the method or means designated in paragraph c below. The certification shall identify each deviation and take it into account in the compliance certification. The certification shall also identify as possible exceptions to compliance any periods during which compliance is required and in which an excursion or exceedance as defined under 40 CFR Part 64 occurred;
- c. The identification of the method(s) or other means used by the owner or operator for determining the compliance status with each term and condition during the certification period;
- d. Any other information that must be included to comply with section 113(c)(2) of the Act, which prohibits knowingly making a false certification or omitting material information; and

- e. Any additional requirements specified by the Division.

8.14.2 Inspection and Entry

- a. Upon presentation of credentials and other documents as may be required by law, the Permittee shall allow authorized representatives of the Division to perform the following:
[391-3-1-.03(10)(d)3 and 40 CFR 70.6(c)(2)]
 - i. Enter upon the Permittee's premises where a Part 70 source is located or an emissions-related activity is conducted, or where records must be kept under the conditions of this Permit;
 - ii. Have access to and copy, at reasonable times, any records that must be kept under the conditions of this Permit;
 - iii. Inspect at reasonable times any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under this Permit; and
 - iv. Sample or monitor any substances or parameters at any location during operating hours for the purpose of assuring Permit compliance or compliance with applicable requirements as authorized by the Georgia Air Quality Act.
- b. No person shall obstruct, hamper, or interfere with any such authorized representative while in the process of carrying out his official duties. Refusal of entry or access may constitute grounds for Permit revocation and assessment of civil penalties.
[391-3-1-.07 and 40 CFR 70.11(a)(3)(i)]

8.14.3 Schedule of Compliance

- a. For applicable requirements with which the Permittee is in compliance, the Permittee shall continue to comply with those requirements.
[391-3-1-.03(10)(c)2 and 40 CFR 70.5(c)(8)(iii)(A)]
- b. For applicable requirements that become effective during the Permit term, the Permittee shall meet such requirements on a timely basis unless a more detailed schedule is expressly required by the applicable requirement.
[391-3-1-.03(10)(c)2 and 40 CFR 70.5(c)(8)(iii)(B)]
- c. Any schedule of compliance for applicable requirements with which the source is not in compliance at the time of Permit issuance shall be supplemental to, and shall not sanction noncompliance with, the applicable requirements on which it is based.
[391-3-1-.03(10)(c)2 and 40 CFR 70.5(c)(8)(iii)(C)]

8.14.4 Excess Emissions

- a. Excess emissions resulting from startup, shutdown, or malfunction of any source which occur though ordinary diligence is employed shall be allowed provided that:
[391-3-1-.02(2)(a)7(i)]

- i. The best operational practices to minimize emissions are adhered to;
 - ii. All associated air pollution control equipment is operated in a manner consistent with good air pollution control practice for minimizing emissions; and
 - iii. The duration of excess emissions is minimized.
- b. Excess emissions which are caused entirely or in part by poor maintenance, poor operation, or any other equipment or process failure which may reasonably be prevented during startup, shutdown or malfunction are prohibited and are violations of Chapter 391-3-1 of the Georgia Rules for Air Quality Control.
[391-3-1-.02(2)(a)7(ii)]
- c. The provisions of this condition and Georgia Rule 391-3-1-.02(2)(a)7 shall apply only to those sources which are not subject to any requirement under Georgia Rule 391-3-1-.02(8) – New Source Performance Standards or any requirement of 40 CFR, Part 60, as amended concerning New Source Performance Standards.
[391-3-1-.02(2)(a)7(iii)]

8.15 Circumvention

State Only Enforceable Condition.

- 8.15.1 The Permittee shall not build, erect, install, or use any article, machine, equipment or process the use of which conceals an emission which would otherwise constitute a violation of an applicable emission standard. Such concealment includes, but is not limited to, the use of gaseous diluents to achieve compliance with an opacity standard or with a standard which is based on the concentration of the pollutants in the gases discharged into the atmosphere.
[391-3-1-.03(2)(c)]

8.16 Permit Shield

- 8.16.1 Compliance with the terms of this Permit shall be deemed compliance with all applicable requirements as of the date of Permit issuance provided that all applicable requirements are included and specifically identified in the Permit.
[391-3-1-.03(10)(d)6]
- 8.16.2 Any Permit condition identified as “State only enforceable” does not have a Permit shield.

8.17 Operational Practices

- 8.17.1 At all times, including periods of startup, shutdown, and malfunction, the Permittee shall maintain and operate the source, including associated air pollution control equipment, in a manner consistent with good air pollution control practice for minimizing emissions. Determination of whether acceptable operating and maintenance procedures are being used will be based on any information available to the Division that may include, but is not limited to, monitoring results, observations of the opacity or other characteristics of emissions, review of operating and maintenance procedures or records, and inspection or surveillance of the source.
[391-3-1-.02(2)(a)10]

State Only Enforceable Condition.

- 8.17.2 No person owning, leasing, or controlling, the operation of any air contaminant sources shall willfully, negligently or through failure to provide necessary equipment or facilities or to take necessary precautions, cause, permit, or allow the emission from said air contamination source or sources, of such quantities of air contaminants as will cause, or tend to cause, by themselves, or in conjunction with other air contaminants, a condition of air pollution in quantities or characteristics or of a duration which is injurious or which unreasonably interferes with the enjoyment of life or use of property in such area of the State as is affected thereby. Complying with Georgia's Rules for Air Quality Control Chapter 391-3-1 and Conditions in this Permit, shall in no way exempt a person from this provision.
[391-3-1-.02(2)(a)1]

8.18 Visible Emissions

- 8.18.1 Except as may be provided in other provisions of this Permit, the Permittee shall not cause, let, suffer, permit or allow emissions from any air contaminant source the opacity of which is equal to or greater than forty (40) percent.
[391-3-1-.02(2)(b)1]

8.19 Fuel-burning Equipment

- 8.19.1 The Permittee shall not cause, let, suffer, permit, or allow the emission of fly ash and/or other particulate matter from any fuel-burning equipment with rated heat input capacity of less than 10 million Btu per hour, in operation or under construction on or before January 1, 1972 in amounts equal to or exceeding 0.7 pounds per million BTU heat input.
[391-3-1-.02(2)(d)]
- 8.19.2 The Permittee shall not cause, let, suffer, permit, or allow the emission of fly ash and/or other particulate matter from any fuel-burning equipment with rated heat input capacity of less than 10 million Btu per hour, constructed after January 1, 1972 in amounts equal to or exceeding 0.5 pounds per million BTU heat input.
[391-3-1-.02(2)(d)]

- 8.19.3 The Permittee shall not cause, let, suffer, permit, or allow the emission from any fuel-burning equipment constructed or extensively modified after January 1, 1972, visible emissions the opacity of which is equal to or greater than twenty (20) percent except for one six minute period per hour of not more than twenty-seven (27) percent opacity.
[391-3-1-.02(2)(d)]

8.20 Sulfur Dioxide

- 8.20.1 Except as may be specified in other provisions of this Permit, the Permittee shall not burn fuel containing more than 2.5 percent sulfur, by weight, in any fuel burning source that has a heat input capacity below 100 million Btu's per hour.
[391-3-1-.02(2)(g)]

8.21 Particulate Emissions

- 8.21.1 Except as may be specified in other provisions of this Permit, the Permittee shall not cause, let, permit, suffer, or allow the rate of emission from any source, particulate matter in total quantities equal to or exceeding the allowable rates shown below. Equipment in operation, or under construction contract, on or before July 2, 1968, shall be considered existing equipment. All other equipment put in operation or extensively altered after said date is to be considered new equipment.
[391-3-1-.02(2)(e)]

- a. The following equations shall be used to calculate the allowable rates of emission from new equipment:

$$E = 4.1P^{0.67}; \text{ for process input weight rate up to and including 30 tons per hour.}$$

$$E = 55P^{0.11} - 40; \text{ for process input weight rate above 30 tons per hour.}$$

- b. The following equation shall be used to calculate the allowable rates of emission from existing equipment:

$$E = 4.1P^{0.67}$$

In the above equations, E = emission rate in pounds per hour, and
P = process input weight rate in tons per hour.

8.22 Fugitive Dust

[391-3-1-.02(2)(n)]

- 8.22.1 Except as may be specified in other provisions of this Permit, the Permittee shall take all reasonable precautions to prevent dust from any operation, process, handling, transportation or storage facility from becoming airborne. Reasonable precautions that could be taken to prevent dust from becoming airborne include, but are not limited to, the following:
- a. Use, where possible, of water or chemicals for control of dust in the demolition of existing buildings or structures, construction operations, the grading of roads or the clearing of land;

Title V Permit

- b. Application of asphalt, water, or suitable chemicals on dirt roads, materials, stockpiles, and other surfaces that can give rise to airborne dusts;
- c. Installation and use of hoods, fans, and fabric filters to enclose and vent the handling of dusty materials. Adequate containment methods can be employed during sandblasting or other similar operations;
- d. Covering, at all times when in motion, open bodied trucks transporting materials likely to give rise to airborne dusts; and
- e. The prompt removal of earth or other material from paved streets onto which earth or other material has been deposited.

8.22.2 The opacity from any fugitive dust source shall not equal or exceed 20 percent.

8.23 Solvent Metal Cleaning

8.23.1 Except as may be specified in other provisions of this Permit, the Permittee shall not cause, suffer, allow, or permit the operation of a cold cleaner degreaser subject to the requirements of Georgia Rule 391-3-1-.02(2)(ff) "Solvent Metal Cleaning" unless the following requirements for control of emissions of the volatile organic compounds are satisfied:
[391-3-1-.02(2)(ff)1]

- a. The degreaser shall be equipped with a cover to prevent escape of VOC during periods of non-use,
- b. The degreaser shall be equipped with a device to drain cleaned parts before removal from the unit,
- c. If the solvent volatility is 0.60 psi or greater measured at 100 °F, or if the solvent is heated above 120 °F, then one of the following control devices must be used:
 - i. The degreaser shall be equipped with a freeboard that gives a freeboard ratio of 0.7 or greater, or
 - ii. The degreaser shall be equipped with a water cover (solvent must be insoluble in and heavier than water), or
 - iii. The degreaser shall be equipped with a system of equivalent control, including but not limited to, a refrigerated chiller or carbon adsorption system.
- d. Any solvent spray utilized by the degreaser must be in the form of a solid, fluid stream (not a fine, atomized or shower type spray) and at a pressure which will not cause excessive splashing, and
- e. All waste solvent from the degreaser shall be stored in covered containers and shall not be disposed of by such a method as to allow excessive evaporation into the atmosphere.

8.24 Incinerators

- 8.24.1 Except as specified in the section dealing with conical burners, no person shall cause, let, suffer, permit, or allow the emissions of fly ash and/or other particulate matter from any incinerator subject to the requirements of Georgia Rule 391-3-1-.02(2)(c) “Incinerators”, in amounts equal to or exceeding the following:
[391-3-1-.02(2)(c)1-4]
- a. Units with charging rates of 500 pounds per hour or less of combustible waste, including water, shall not emit fly ash and/or particulate matter in quantities exceeding 1.0 pound per hour.
 - b. Units with charging rates in excess of 500 pounds per hour of combustible waste, including water, shall not emit fly ash and/or particulate matter in excess of 0.20 pounds per 100 pounds of charge.
- 8.24.2 No person shall cause, let, suffer, permit, or allow from any incinerator subject to the requirements of Georgia Rule 391-3-1-.02(2)(c) “Incinerators”, visible emissions the opacity of which is equal to or greater than twenty (20) percent except for one six minute period per hour of not more than twenty-seven (27) percent opacity.
- 8.24.3 No person shall cause or allow particles to be emitted from an incinerator subject to the requirements of Georgia Rule 391-3-1-.02(2)(c) “Incinerators” which are individually large enough to be visible to the unaided eye.
- 8.24.4 No person shall operate an existing incinerator subject to the requirements of Georgia Rule 391-3-1-.02(2)(c) “Incinerators” unless:
- a. It is a multiple chamber incinerator;
 - b. It is equipped with an auxiliary burner in the primary chamber for the purpose of creating a pre-ignition temperature of 800°F; and
 - c. It has a secondary burner to control smoke and/or odors and maintain a temperature of at least 1500°F in the secondary chamber.

8.25 Volatile Organic Liquid Handling and Storage

- 8.25.1 The Permittee shall ensure that each storage tank subject to the requirements of Georgia Rule 391-3-1-.02(2)(vv) “Volatile Organic Liquid Handling and Storage” is equipped with submerged fill pipes. For the purposes of this condition and the permit, a submerged fill pipe is defined as any fill pipe with a discharge opening which is within six inches of the tank bottom.
[391-3-1-.02(2)(vv)(1)]

8.26 Use of Any Credible Evidence or Information

- 8.26.1 Notwithstanding any other provisions of any applicable rule or regulation or requirement of this permit, for the purpose of submission of compliance certifications or establishing whether or not a person has violated or is in violation of any emissions limitation or standard, nothing in this permit or any Emission Limitation or Standard to which it pertains, shall preclude the use, including the exclusive use, of any credible evidence or information, relevant to whether a source would have been in compliance with applicable requirements if the appropriate performance or compliance test or procedure had been performed.
[391-3-1-.02(3)(a)]

8.27 Internal Combustion Engines

- 8.27.1 For diesel-fired internal combustion engine(s) manufactured after April 1, 2006 or modified/reconstructed after July 11, 2005, the Permittee shall comply with all applicable provisions of New Source Performance Standards (NSPS) as found in 40 CFR 60 Subpart A - “General Provisions” and 40 CFR 60 Subpart IIII – “Standards of Performance for Stationary Compression Ignition Internal Combustion Engines.” Such requirements include but are not limited to:
[40 CFR 60.4200]
- a. Equip all emergency generator engines with non-resettable hour meters in accordance with Subpart IIII.
 - b. Purchase only diesel fuel with a maximum sulfur content of 15 ppm unless otherwise specified by the Division in accordance with Subpart IIII.
 - c. Conduct engine maintenance prescribed by the engine manufacturer in accordance with Subpart IIII.
 - d. Limit non-emergency operation of each emergency generator to 100 hours per year in accordance with Subpart IIII. Non-emergency operation other than maintenance and readiness testing is prohibited for engines qualifying as “emergency generators” for the purposes of Ga Rule 391-3-1-.02(2)(mmm).
 - e. Maintain any records in accordance with Subpart IIII
 - f. Maintain a list of engines subject to 40 CFR 60 Subpart IIII, including the date of manufacture.[391-3-1-.02(6)(b)]
- 8.27.2 The Permittee shall comply with all applicable provisions of New Source Performance Standards (NSPS) as found in 40 CFR 60 Subpart A - “General Provisions” and 40 CFR 60 Subpart JJJJ - “Standards of Performance for Stationary Spark Ignition Internal Combustion Engines,” for spark ignition internal combustion engine(s) (gasoline, natural gas, liquefied petroleum gas or propane-fired) manufactured after July 1, 2007 or modified/reconstructed after June 12, 2006.
[40 CFR 60.4230]

- 8.27.3 The Permittee shall comply with all applicable provisions of National Emission Standards for Hazardous Air Pollutants (NESHAP) as found in 40 CFR 63 Subpart A - “General Provisions” and 40 CFR 63 Subpart ZZZZ - “National Emission Standards for Hazardous Air Pollutants for Stationary Reciprocating Internal Combustion Engines.”

For diesel-fired emergency generator engines defined as “existing” in 40 CFR 63 Subpart ZZZZ (constructed prior to June 12, 2006 for area sources of HAP, constructed prior to June 12, 2006 for ≤500hp engines at major sources, and constructed prior to December 19, 2002 for >500hp engines at major sources of HAP), such requirements (if applicable) include but are not limited to:

[40 CFR 63.6580]

- a. Equip all emergency generator engines with non-resettable hour meters in accordance with Subpart ZZZZ.
- b. Purchase only diesel fuel with a maximum sulfur content of 15 ppm unless otherwise specified by the Division in accordance with Subpart ZZZZ.
- c. Conduct the following in accordance with Subpart ZZZZ.
 - i. Change oil and filter every 500 hours of operation or annually, whichever comes first
 - ii. Inspect air cleaner every 1000 hours of operation or annually, whichever comes first and replace as necessary
 - iii. Inspect all hoses and belts every 500 hours of operation or annually, whichever comes first and replace as necessary.
- d. Limit non-emergency operation of each emergency generator to 100 hours per year in accordance with Subpart ZZZZ. Non-emergency operation other than maintenance and readiness testing is prohibited for engines qualifying as “emergency generators” for the purposes of Ga Rule 391-3-1-.02(2)(mmm).
- e. Maintain any records in accordance with Subpart ZZZZ
- f. Maintain a list of engines subject to 40 CFR 63 Subpart ZZZZ, including the date of manufacture.[391-3-1-.02(6)(b)]

8.28 Boilers and Process Heaters

- 8.28.1 If the facility/site is an area source of Hazardous Air Pollutants, the Permittee shall comply with all applicable provisions of National Emission Standards for Hazardous Air Pollutants (NESHAP) 40 CFR Part 63 Subpart A - “General Provisions” and 40 CFR 63 Subpart JJJJJ - “National Emission Standards for Hazardous Air Pollutants for Area Sources: Industrial, Commercial, and Institutional Boilers.”
- [40 CFR 63.11193]

Title V Permit

Chevron Products Company – Doraville Terminal

Permit No.: 5171-089-0100-V-05-0

- 8.28.2 If the facility/site is a major source of Hazardous Air Pollutants, the Permittee shall comply with all applicable provisions of National Emission Standards for Hazardous Air Pollutants (NESHAP) 40 CFR Part 63 Subpart A - “General Provisions” and 40 CFR 63 Subpart DDDDD - “National Emission Standards for Hazardous Air Pollutants for Major Sources: Industrial, Commercial, and Institutional Boilers and Process Heaters.”
[40 CFR 63.7480]

Attachments

- A. List of Standard Abbreviations and List of Permit Specific Abbreviations
- B. Insignificant Activities Checklist, Insignificant Activities Based on Emission Levels and Generic Emission Groups
- C. List of References

List Of Standard Abbreviations

[illegible]

Title V Permit

Chevron Products Company – Doraville Terminal

Permit No.: 5171-089-0100-V-05-0

ATTACHMENT B

NOTE: Attachment B contains information regarding insignificant emission units/activities and groups of generic emission units/activities in existence at the facility at the time of Permit issuance. Future modifications or additions of insignificant emission units/activities and equipment that are part of generic emissions groups may not necessarily cause this attachment to be updated.

INSIGNIFICANT ACTIVITIES CHECKLIST

Category	Description of Insignificant Activity/Unit	Quantity
Mobile Sources	1. Cleaning and sweeping of streets and paved surfaces	
Combustion Equipment	1. Fire fighting and similar safety equipment used to train fire fighters or other emergency personnel.	
	2. Small incinerators that are not subject to any standard, limitation or other requirement under Section 111 or 112 (excluding 112(r)) of the Federal Act and are not considered a “designated facility” as specified in 40 CFR 60.32e of the Federal emissions guidelines for Hospital/Medical/Infectious Waste Incinerators, that are operating as follows:	
	i) Less than 8 million BTU/hr heat input, firing types 0, 1, 2, and/or 3 waste.	
	ii) Less than 8 million BTU/hr heat input with no more than 10% pathological (type 4) waste by weight combined with types 0, 1, 2, and/or 3 waste.	
	iii) Less than 4 million BTU/hr heat input firing type 4 waste. (Refer to 391-3-1-.03(10)(g)2.(ii) for descriptions of waste types)	
	3. Open burning in compliance with Georgia Rule 391-3-1-.02 (5).	
	4. Stationary engines burning:	
	i) Natural gas, LPG, gasoline, dual fuel, or diesel fuel which are used exclusively as emergency generators shall not exceed 500 hours per year or 200 hours per year if subject to Georgia Rule 391-3-1-.02(2)(mmm).7	2
	ii) Natural gas, LPG, and/or diesel fueled generators used for emergency, peaking, and/or standby power generation, where the combined peaking and standby power generation do not exceed 200 hours per year.	
	iii) Natural gas, LPG, and/or diesel fuel used for other purposes, provided that the output of each engine does not exceed 400 horsepower and that no individual engine operates for more than 2,000 hours per year.	
	iv) Gasoline used for other purposes, provided that the output of each engine does not exceed 100 horsepower and that no individual engine operates for more than 500 hours per year.	
Trade Operations	1. Brazing, soldering, and welding equipment, and cutting torches related to manufacturing and construction activities whose emissions of hazardous air pollutants (HAPs) fall below 1,000 pounds per year.	
Maintenance, Cleaning, and Housekeeping	1. Blast-cleaning equipment using a suspension of abrasive in water and any exhaust system (or collector) serving them exclusively.	
	2. Portable blast-cleaning equipment.	
	3. Non-Perchloroethylene Dry-cleaning equipment with a capacity of 100 pounds per hour or less of clothes.	
	4. Cold cleaners having an air/vapor interface of not more than 10 square feet and that do not use a halogenated solvent.	
	5. Non-routine clean out of tanks and equipment for the purposes of worker entry or in preparation for maintenance or decommissioning.	
	6. Devices used exclusively for cleaning metal parts or surfaces by burning off residual amounts of paint, varnish, or other foreign material, provided that such devices are equipped with afterburners.	
	7. Cleaning operations: Alkaline phosphate cleaners and associated cleaners and burners.	

Title V Permit

Chevron Products Company – Doraville Terminal

Permit No.: 5171-089-0100-V-05-0

INSIGNIFICANT ACTIVITIES CHECKLIST

Category	Description of Insignificant Activity/Unit	Quantity
Laboratories and Testing	1. Laboratory fume hoods and vents associated with bench-scale laboratory equipment used for physical or chemical analysis.	1
	2. Research and development facilities, quality control testing facilities and/or small pilot projects, where combined daily emissions from all operations are not individually major or are support facilities not making significant contributions to the product of a collocated major manufacturing facility.	
Pollution Control	1. Sanitary waste water collection and treatment systems, except incineration equipment or equipment subject to any standard, limitation or other requirement under Section 111 or 112 (excluding 112(r)) of the Federal Act.	1
	2. On site soil or groundwater decontamination units that are not subject to any standard, limitation or other requirement under Section 111 or 112 (excluding 112(r)) of the Federal Act.	1
	3. Bioremediation operations units that are not subject to any standard, limitation or other requirement under Section 111 or 112 (excluding 112(r)) of the Federal Act.	
	4. Landfills that are not subject to any standard, limitation or other requirement under Section 111 or 112 (excluding 112(r)) of the Federal Act.	
Industrial Operations	1. Concrete block and brick plants, concrete products plants, and ready mix concrete plants producing less than 125,000 tons per year.	
	2. Any of the following processes or process equipment which are electrically heated or which fire natural gas, LPG or distillate fuel oil at a maximum total heat input rate of not more than 5 million BTU's per hour:	
	i) Furnaces for heat treating glass or metals, the use of which do not involve molten materials or oil-coated parts.	
	ii) Porcelain enameling furnaces or porcelain enameling drying ovens.	
	iii) Kilns for firing ceramic ware.	
	iv) Crucible furnaces, pot furnaces, or induction melting and holding furnaces with a capacity of 1,000 pounds or less each, in which sweating or distilling is not conducted and in which fluxing is not conducted utilizing free chlorine, chloride or fluoride derivatives, or ammonium compounds.	
	v) Bakery ovens and confection cookers.	
	vi) Feed mill ovens.	
	vii) Surface coating drying ovens	
	3. Carving, cutting, routing, turning, drilling, machining, sawing, surface grinding, sanding, planing, buffing, shot blasting, shot peening, or polishing; ceramics, glass, leather, metals, plastics, rubber, concrete, paper stock or wood, also including roll grinding and ground wood pulping stone sharpening, provided that:	
	i) Activity is performed indoors; &	
	ii) No significant fugitive particulate emissions enter the environment; &	
	iii) No visible emissions enter the outdoor atmosphere.	
	4. Photographic process equipment by which an image is reproduced upon material sensitized to radiant energy (e.g., blueprint activity, photographic developing and microfiche).	
	5. Grain, food, or mineral extrusion processes	
	6. Equipment used exclusively for sintering of glass or metals, but not including equipment used for sintering metal-bearing ores, metal scale, clay, fly ash, or metal compounds.	
	7. Equipment for the mining and screening of uncrushed native sand and gravel.	
	8. Ozonization process or process equipment.	
	9. Electrostatic powder coating booths with an appropriately designed and operated particulate control system.	
	10. Activities involving the application of hot melt adhesives where VOC emissions are less than 5 tons per year and HAP emissions are less than 1,000 pounds per year.	
	11. Equipment used exclusively for the mixing and blending water-based adhesives and coatings at ambient temperatures.	
	12. Equipment used for compression, molding and injection of plastics where VOC emissions are less than 5 tons per year and HAP emissions are less than 1,000 pounds per year.	
	13. Ultraviolet curing processes where VOC emissions are less than 5 tons per year and HAP emissions are less than 1,000 pounds per year.	

Title V Permit

Chevron Products Company – Doraville Terminal

Permit No.: 5171-089-0100-V-05-0

INSIGNIFICANT ACTIVITIES CHECKLIST

Category	Description of Insignificant Activity/Unit	Quantity
Storage Tanks and Equipment	1. All petroleum liquid storage tanks storing a liquid with a true vapor pressure of equal to or less than 0.50 psia as stored.	8
	2. All petroleum liquid storage tanks with a capacity of less than 40,000 gallons storing a liquid with a true vapor pressure of equal to or less than 2.0 psia as stored that are not subject to any standard, limitation or other requirement under Section 111 or 112 (excluding 112(r)) of the Federal Act.	
	3. All petroleum liquid storage tanks with a capacity of less than 10,000 gallons storing a petroleum liquid.	
	4. All pressurized vessels designed to operate in excess of 30 psig storing petroleum fuels that are not subject to any standard, limitation or other requirement under Section 111 or 112 (excluding 112(r)) of the Federal Act.	1
	5. Gasoline storage and handling equipment at loading facilities handling less than 20,000 gallons per day or at vehicle dispensing facilities that are not subject to any standard, limitation or other requirement under Section 111 or 112 (excluding 112(r)) of the Federal Act.	
	6. Portable drums, barrels, and totes provided that the volume of each container does not exceed 550 gallons.	3
	7. All chemical storage tanks used to store a chemical with a true vapor pressure of less than or equal to 10 millimeters of mercury (0.19 psia).	2

INSIGNIFICANT ACTIVITIES BASED ON EMISSION LEVELS

Description of Emission Units / Activities	Quantity
Butane blending system to mix butane with gasoline during the non-ozone season.	1
Lubricity Additive Tank (Tank No. 32, an 8,000-gallon tank Storing VOL with VP of approximately 0.7 psia.	1
PWC Tanks (petroleum contact water tank Nos. 8 and 9)	2

Title V Permit

Chevron Products Company – Doraville Terminal

Permit No.: 5171-089-0100-V-05-0

ATTACHMENT B (continued)

GENERIC EMISSION GROUPS

Emission units/activities appearing in the following table are subject only to one or more of Georgia Rules 391-3-1-.02 (2) (b), (e) &/or (n). Potential emissions of particulate matter, from these sources based on TSP, are less than 25 tons per year per process line or unit in each group. Any emissions unit subject to a NESHAP, NSPS, or any specific Air Quality Permit Condition(s) are not included in this table.

Description of Emissions Units / Activities	Number of Units (if appropriate)	Applicable Rules		
		Opacity Rule (b)	PM from Mfg Process Rule (e)	Fugitive Dust Rule (n)

The following table includes groups of fuel burning equipment subject only to Georgia Rules 391-3-1-.02 (2) (b) & (d). Any emissions unit subject to a NESHAP, NSPS, or any specific Air Quality Permit Condition(s) are not included in this table.

Description of Fuel Burning Equipment	Number of Units
Fuel burning equipment with a rated heat input capacity of less than 10 million BTU/hr burning only natural gas and/or LPG.	
Fuel burning equipment with a rated heat input capacity of less than 5 million BTU/hr, burning only distillate fuel oil, natural gas and/or LPG.	
Any fuel burning equipment with a rated heat input capacity of 1 million BTU/hr or less.	1

ATTACHMENT C

LIST OF REFERENCES

1. The Georgia Rules for Air Quality Control Chapter 391-3-1. All Rules cited herein which begin with 391-3-1 are State Air Quality Rules.
2. Title 40 of the Code of Federal Regulations; specifically 40 CFR Parts 50, 51, 52, 60, 61, 63, 64, 68, 70, 72, 73, 75, 76 and 82. All rules cited with these parts are Federal Air Quality Rules.
3. *Georgia Department of Natural Resources, Environmental Protection Division, Air Protection Branch, Procedures for Testing and Monitoring Sources of Air Pollutants.*
4. *Georgia Department of Natural Resources, Environmental Protection Division, Air Protection Branch, Procedures for Calculating Air Permit Fees.*
5. Compilation of Air Pollutant Emission Factors, AP-42, Fifth Edition, Volume I: Stationary Point and Area Sources. This information may be obtained from EPA's TTN web site at www.epa.gov/ttn/chief/ap42/index.html.
6. The latest properly functioning version of EPA's **TANKS** emission estimation software. The software may be obtained from EPA's TTN web site at www.epa.gov/ttn/chief/software/tanks/index.html.
7. The Clean Air Act (42 U.S.C. 7401 et seq).
8. White Paper for Streamlined Development of Part 70 Permit Applications, July 10, 1995 (White Paper #1).
9. White Paper Number 2 for Improved Implementation of the Part 70 Operating Permits Program, March 5, 1996 (White Paper #2).