(y) VOC Emissions from Metal Furniture Coating.

- 1. No person shall cause, let, permit, suffer, or allow the emissions of VOC from metal furniture coating operations to exceed:
- (i) 3.0 pounds per gallon of coating, excluding water, delivered to the coating applicator from prime and topcoat or single coat operations. If any coating delivered to the coating applicator contains more than 3.0 pounds VOC per gallon, the solids equivalent limit shall be 5.06 pounds VOC per gallon of coating solids delivered to the coating applicator.
- (ii) The emission limit in this subparagraph shall apply to the application area(s), flashoff area(s) and oven(s) of metal furniture coating lines involved in prime and topcoat or single coat operations.
- 2. The emission limits in subparagraph 1. shall be achieved by:
- (i) the application of low solvent coating technology where each and every coating meets the limit of 3.0 pounds VOC per gallon of coating, excluding water; or
- (ii) the application of low solvent coating technology where the 24-hour or monthly weighted average of all coatings on a single coating line or operation meets the solids equivalent limit of 5.06 pounds VOC-per-gallon of coating solids (averaging across lines is not allowed); or
- (iii) control equipment, including but not limited to incineration, carbon adsorption and condensation, with a capture system approved by the Director, provided that 90 percent of the nonmethane volatile organic compounds which enter the control equipment are recovered or destroyed, and that overall VOC emissions do not exceed the solids equivalent limit of 5.06 pounds VOC per gallon of coating solids.
- 3. No person shall cause, let, permit, suffer, or allow the emissions of VOC from metal furniture coating operations for baked coatings to exceed:
- (i) 2.3 pounds per gallon of coating, excluding water, delivered to the coating applicator from general one-component, and general multi-component coatings. If any coating delivered to the coating applicator contains more than 2.3 pounds VOC per gallon, the solids equivalent limit shall be 3.3 pounds VOC per gallon of coating solids as applied.
- (ii) 3.0 pounds per gallon of coating, excluding water, delivered to the coating applicator from extreme high gloss, extreme performance, heat resistant, metallic, solar absorbent and pretreatment coatings. If any coating delivered to the coating applicator contains more than 3.0 pounds VOC per gallon, the solids equivalent limit shall be 5.06 pounds VOC per gallon of coating solids as applied.
- 4. No person shall cause, let, permit, suffer, or allow the emissions of VOC from metal furniture coating operations for air-dried coatings to exceed:
- (i) 2.3 pounds per gallon of coating, excluding water, delivered to the coating applicator from general one-component coatings. If any coating contains more than 2.3 pounds VOC per gallon, the solids equivalent limit shall be 3.3 pounds VOC per gallon of coating solids as applied.

- (ii) 2.8 pounds per gallon of coating, excluding water, delivered to the coating applicator from general multi-component, and extreme high gloss coatings. If any coating delivered to the coating applicator contains more than 2.8 pounds VOC per gallon, the solids equivalent limit shall be 4.5 pounds VOC per gallon of coating solids as applied.
- (ii) 3.0 pounds per gallon of coating, excluding water, delivered to the coating applicator from extreme performance, heat resistant, metallic, solar absorbent and pretreatment coatings. If any coating delivered to the coating applicator contains more than 3.0 pounds VOC per gallon, the solids equivalent limit shall be 5.06 pounds VOC per gallon of coating solids as applied.
- 5. Each owner or operator of a facility that coats metal furniture shall ensure that all coating application systems utilize one or more of the application techniques stated below:
- (i) Electrostatic spray application;
- (ii) High volume low pressure (HVLP) spraying;
- (iii) Flow/curtain application;
- (iv) Roll coating;
- (v) Dip coat application including electrodeposition;
- (vi) Brush coat;
- (vii) Airless spray;
- (viii) Air-assisted airless spray; or
- (ix) Other coating application methods that achieve transfer efficiency equivalent to HVLP or electrostatic spray application methods, as determined by the Director.
- 6. Each owner or operator of a facility that coats metal furniture shall comply with the following work practice standards:
- (i) store all VOC-containing coatings, thinners, and coating-related waste materials in closed containers;
- (ii) ensure that mixing and storage containers used for VOC-containing coatings, thinners, and coating-related waste materials are kept closed at all times except when depositing or removing these materials;
- (iii) minimize spills of VOC-containing coatings, thinners, and coating-related waste materials; and
- (iv) convey VOC-containing coatings, thinners, and coating-related waste materials from one location to another in closed containers or pipes.
- 7. Each owner or operator of a facility that coats metal furniture shall comply with the following housekeeping requirements for any affected cleaning operation:

- (i) store all VOC-containing cleaning materials and used shop towels in closed containers;
- (ii) ensure that storage containers used for VOC-containing cleaning materials are kept closed at all times except when depositing or removing these materials;
- (iii) minimize spills of VOC-containing cleaning materials;
- (iv) convey VOC-containing cleaning materials from one location to another in closed containers or pipes; and
- (v) minimize VOC emissions from cleaning of application, storage, mixing, and conveying equipment by ensuring that equipment cleaning is performed without atomizing the cleaning solvent and all spent solvent is captured in closed containers.
- 8. The VOC limits specified in this subparagraphs 3. and 4. do not apply to the following types of metal furniture coatings and/or coating operations:
- (i) Touch-up and repair coatings;
- (ii) Stencil coatings;
- (iii) Safety-indicating coatings;
- (iv) Solid-film lubricants:
- (v) Electric-insulating and thermal-conducting coatings; and
- (vi) Coating application utilizing hand-held aerosol cans.
- 9. The emission limits in subparagraphs 3. and 4. shall be achieved by:
- (i) the application of low solvent coating technology where each and every coating meets the limit expressed in pounds VOC per gallon of coating, excluding water, stated in subparagraphs 3. and 4. of this subparagraph; or
- (ii) the application of low solvent coating technology where the 24-hour weighted average of all coatings on a single coating line or operation meets the solids equivalent limit expressed in pounds VOC per gallon of coating solids, stated in subparagraphs 3. and 4. of this subparagraph; averaging across lines is not allowed; or
- (iii) control equipment, including but not limited to incineration, carbon adsorption and condensation, with a capture system approved by the Director, provided that 90 percent of the nonmethane volatile organic compounds which enter the control equipment are recovered or destroyed, and that overall VOC emissions do not exceed the solids equivalent limit, expressed in pounds VOC per gallon of coating solids stated in subparagraphs 3. and 4. of this subparagraph.
- 10. For the purpose of this subparagraph, the following definitions apply:
- (i) "Application Area" means the area where the coating is applied by spraying, dipping or flow coating techniques.

- (ii) "Metal Furniture Coating" means the surface coating of any furniture made of metal or any metal part, which will be assembled with other metal wood, fabric, plastic or glass parts to form a furniture piece.
- 11. Applicability: Prior to January 1, 2015, the requirements of this subparagraph (y) shall apply to facilities at which the actual emissions of volatile organic compounds from the use of metal furniture coatings equal or exceed 15 pounds per day and are located in Cherokee, Clayton, Cobb, Coweta, DeKalb, Douglas, Fayette, Forsyth, Fulton, Gwinnett, Henry, Paulding, and Rockdale Counties as follows:
- (i) All applicable facilities shall comply with the provisions of subparagraphs 1., 2., and 10.
- 12. Applicability. Prior to January 1, 2015, the requirements of this subparagraph (y) shall apply to facilities at which the potential emissions of volatile organic compounds from the use of metal furniture coatings equal or exceed 100 tons per year and are located outside the counties of in Cherokee, Clayton, Cobb, Coweta, DeKalb, Douglas, Fayette, Forsyth, Fulton, Gwinnett, Henry, Paulding, and Rockdale Counties as follows:
- (i) All applicable facilities shall comply with the provisions of subparagraphs 1., 2., and 10.
- 13. Applicability. On and after January 1, 2015, the requirements of this subparagraph (y) shall apply to facilities at which the actual emissions of volatile organic compounds from the use of metal furniture coatings, before controls, equal or exceed 15 pounds per day (or 2.7 tons per 12-month rolling period) for facilities located in Barrow, Bartow, Carroll, Cherokee, Clayton, Cobb, Coweta, DeKalb, Douglas, Fayette, Forsyth, Fulton, Gwinnett, Hall, Henry, Newton, Paulding, Rockdale, Spalding, and Walton Counties as follows:
- (i) All applicable facilities shall comply with the provisions of subparagraphs 3., 4., 5., 6., 7., 8., 9., and 10.
- (ii) Any physical or operational changes that are necessary to comply with the provisions specified in subparagraphs 3., 4., 5., 6., 7., 8., or 9. are subject to the compliance schedule specified in subparagraph 16.
- 14. On and after January 1, 2015, the requirements of this subparagraph (y) shall apply to facilities at which the potential emissions of volatile organic compounds from the use of metal furniture coatings equal or exceed 100 tons per year and are located outside the counties of Barrow, Bartow, Carroll, Cherokee, Clayton, Cobb, Coweta, DeKalb, Douglas, Fayette, Forsyth, Fulton, Gwinnett, Hall, Henry, Newton, Paulding, Rockdale, Spalding, and Walton as follows:
- (i) All applicable facilities shall comply with the provisions of subparagraphs 1., 2., and 10.
- 15. Applicability. The requirements of subparagraphs 13. and 14. will no longer be applicable by the compliance deadlines if the counties specified in those subparagraphs are re-designated to attainment for the 1997 National Ambient Air Quality Standard for ozone prior to January 1, 2015 and such counties continue to maintain that Standard thereafter. Instead, the provisions of subparagraphs 11. and 12. will continue to apply on and after January 1, 2015. In the event the 1997 National Ambient Air Quality Standard for ozone is violated in the specified counties, the requirements of subparagraphs 13. and 14. will only be reinstated if the Director determines that the measure is necessary to meet the requirements of the contingency plan.

16. Compliance schedule:

- (i) An application for a permit to construct and operate volatile organic compound emission control systems and/or modifications of process and/or coatings used must be submitted to the Division no later than **July 1, 2014.**
- (ii) On-site of construction of emission control systems and/or modification of process or coatings must be completed by **November 1**, **2014**.
- (iii) Full compliance with the applicable requirements of subparagraphs 3., 4., 5., 6., 7., 8., and 9. must be completed before **January 1, 2015.**