

2.56 Industrial Cleaning Solvents

2.56.1 Applicability and Designation of Affected Facility

The provisions of this source category apply to each facility that uses organic solvents for cleaning operations.

2.56.2 Definitions and Symbols

All symbols used in this source category not defined below are given the meaning in the Clean Air Act of 1970 (as amended) or the Georgia Air Quality Act (as amended) or in published regulations pertaining thereto.

C_a	=	the VOC concentration in each gas stream leaving the control device and entering the atmosphere (parts per million by volume, as carbon)
C_b	=	the VOC concentration in each gas stream entering the control device (parts per million by volume, as carbon)
C_f	=	the VOC concentration in each gas stream emitted directly to the atmosphere (parts per million by volume, as carbon)
D_d	=	density of each diluent VOC-solvent (pounds per gallon)
D_r	=	density of VOC-solvent recovered by an emission control device (pounds per gallon)
E	=	VOC destruction efficiency of the control device (fraction)
F	=	the proportion of total VOCs emitted by an affected facility that enters the control device (fraction)
L_c	=	the volume of each solvent consumed, as received (gallons)
L_r	=	the volume of VOC-solvent recovered by an emission control device (liters)
M_d	=	the mass of diluent VOC-solvent consumed (pounds)
M_o	=	the mass of VOCs in a solvent consumed, as received (pounds)
M_r	=	the mass of VOCs recovered by an emission control device (pounds)
Q_a	=	the volumetric flow rate of each gas stream leaving the control device and entering the atmosphere (dry standard cubic feet per hour)
Q_b	=	the volumetric flow rate of each gas stream entering the control device (dry standard cubic feet per hour)
Q_f	=	the volumetric flow rate of each gas stream emitted directly to the atmosphere (dry standard cubic feet per hour)

2.56.3 Performance Tests and Compliance Provisions

- (a) The provisions of paragraph (f) of Section 1.2 of this text only apply to the required initial performance tests, and the provisions of paragraph (h) of Section 1.2 of this text apply only for the determination of the overall reduction efficiency, R.
- (b) The owner or operator of an affected facility shall conduct the initial performance test as required under Section 1.2 according to procedures in this section; and, thereafter, procedures in this section shall be used to conduct any required periodic performance tests to demonstrate compliance with the applicable Georgia Regulations for Air Quality Control.
- (c) The owner or operator shall use the following procedures for determining compliance with the applicable regulations.
 - (1) An owner or operator shall use the following procedures for any affected facility which does not use a capture system and control device to comply with the applicable emission limit. The owner or operator shall determine the composition of the solvents by formulation data supplied by the manufacturer of the solvent. The owner or operator shall determine the volume of the ink or coating and the mass of VOC-solvent used for thinning purposes from company records on the same basis as the averaging period.
 - (2) An owner or operator shall use the following procedures for any affected facility that uses a capture system and a control device that destroys VOCs (e.g., incinerator) to comply with the applicable emission limit.
 - (i) Determine the overall reduction efficiency (R) for the capture system and control device. For the initial performance test the overall reduction efficiency (R) shall be determined as prescribed in (c)(2)(i) (A), (B), and (C) of this section. In subsequent averaging periods, the owner or operator may use the most recently determined overall reduction efficiency (R) for the performance test providing control device and capture system operating conditions have not changed. The procedure in, (c)(2)(i) (A), (B), and (C), of this section, shall be repeated when directed by the Director or when the owner or operator elects to operate the control device or capture system at conditions different from the initial performance test.
 - (A) Determine the fraction (F) of total VOCs emitted by an affected facility that enters the control device using the following equation or as provided in Appendix G of this text:

$$F = \frac{\sum_{i=1}^n C_{bi} Q_{bi}}{\sum_{i=1}^n C_{bi} Q_{bi} + \sum_{j=1}^m C_{fj} Q_{fj}}$$

Where:

n is the number of gas streams entering the control device, and

m is the number of gas streams emitted directly to the atmosphere.

- (B) Determine the destruction efficiency of the control device (E) using values of the volumetric flow rate of each of the gas streams and the VOC content (as carbon) of each of the gas streams in and out of the device by the following equation:

$$E = \frac{\sum_{i=1}^n Q_{bi} C_{bi} - \sum_{j=1}^m Q_{aj} C_{aj}}{\sum_{i=1}^n Q_{bi} C_{bi}}$$

Where:

n is the number of gas streams entering the control device, and

m is the number of gas streams leaving the control device and entering the atmosphere.

- (3) An owner or operator shall use the following procedure for any affected facility which uses a control device that recovers the VOCs (e.g., carbon adsorption) to comply with the applicable emission limit. **Note:** If the owner or operator can demonstrate to the satisfaction of the Director that the procedure of paragraph (c)(3)(i), (ii), (iii) are impractical due to the length of the averaging period, then the procedure of paragraph (c)(2) may be used.

- (i) Calculate the mass of VOCs used ($M_o + M_d$) during each averaging period* for each affected facility by the following equation:

$$M_o + M_d = \sum_{i=1}^n L_{ci} D_{ci} + \sum_{j=1}^m L_{dj} D_{dj}$$

($L_{dj} D_{dj}$ will be 0 if no VOC solvent is added to the cleaning solvent, as received.)

Where:

n is the number of different solvents used during the averaging period, and

m is the number of different diluent VOC-solvents used during the averaging period.

- (ii) Calculate the total mass of VOCs recovered (M_r) during each averaging period using the following equation:

$$M_r = L_r D_r$$

- (iii) Calculate overall reduction efficiency of the control device (R) for each averaging period for each affected facility using the following equation:

$$R = \frac{M_r}{M_o + M_d}$$

2.56.4 Monitoring of Emissions and Operations

- (a) The owner or operator of an affected facility which uses a capture system and an incinerator to comply with the emission limits shall install, calibrate, maintain, and operate temperature measurement devices according to the following procedures:
- (1) Where thermal incineration is used, a temperature measurement device shall be installed in the firebox. Where catalytic incineration is used, a temperature measurement device shall be installed in the gas stream immediately before and after the catalyst bed.
 - (2) Each temperature measurement device shall be installed, calibrated, and maintained according to the manufacturer's specifications. The device shall have an accuracy of the greater of 0.75 percent of the temperature being measured expressed in degrees Celsius or $\pm 2.5^\circ\text{C}$.
 - (3) Each temperature measurement device shall be equipped with a recording device so that a permanent continuous record is produced.
- (b) The owner or operator of an affected facility which uses a capture system and a solvent recovery system to comply with the emission limits shall install the equipment necessary to determine the total volume of VOC-solvent recovered for each averaging period.

2.56.5 Test Methods and Procedures

- (a) The reference methods in Appendix A to this part, except as provided under Section 1.2, shall be used to determine compliance with the applicable standards as follows:
- (1) Method 25 for the measurement of VOC concentration.
 - (2) Method 1 for sample and velocity traverses.
 - (3) Method 2 for velocity and volumetric flow rate.
 - (4) Method 3 for gas analysis.

- (5) Method 4 for stack gas moisture.
- (b) For Method 25, the minimum sampling time for each of the 3 runs is 60 minutes and the minimum sample volume is 0.003 dry standard cubic meters, except that shorter sampling times or smaller volumes, when necessitated by process variables or other factors, may be approved by the Director.
- (c) The Director will approve testing of representative stacks on a case-by-case basis if the owner or operator can demonstrate to the satisfaction of the Director that testing of representative stacks yields results comparable to those that would be obtained by testing all stacks.
- (d) The protocols and methods of Appendix G shall be used to determine the capture efficiency.

* Each day or fraction of a day in which an affected facility is operated is considered the averaging period unless otherwise specified or approved by the Director.