

GEOLOGICAL SURVEY OF GEORGIA

S. W. McCALLIE, State Geologist

BULLETIN No. 16

SECOND REPORT

ON THE

WATER POWERS

OF

GEORGIA

BY

B. M. HALL AND M. R. HALL

CO-OPERATIVE WORK OF THE GEOLOGICAL SURVEY OF GEORGIA
AND THE UNITED STATES GEOLOGICAL SURVEY

The Franklin-Turner Company, Atlanta, Ga.

1908

ADDITIONAL REVISIONS

AND


REVISIONS

ATLANTA, GA.


THE FRANKLIN-TURNER COMPANY

PRINTERS, PUBLISHERS, BINDERS

1908



DAM, POWER-HOUSE AND TRANSMITTER-HOUSE OF THE NORTH GEORGIA ELECTRIC COMPANY AT DUNLAP SHOALS ON THE CHATTAHOOCHEE RIVER NEAR GAINESVILLE, HALL COUNTY, GEORGIA




THE ADVISORY BOARD
of the
Geological Survey of Georgia
in the Year 1908

(Ex-Officio)

HIS EXCELLENCY HOKE SMITH, Governor of Georgia
PRESIDENT OF THE BOARD

HON. PHILIP COOKSecretary of State
HON. R. E. PARK..... State Treasurer
HON. W. A. WRIGHT Comptroller-General
HON. JOHN C. HART..... Attorney-General
HON. T. G. HUDSON Commissioner of Agriculture
HON. J. M. POUND Commissioner of Public Schools



LETTER OF TRANSMITTAL

GEOLOGICAL SURVEY OF GEORGIA,

ATLANTA, July 7, 1908.

*To His Excellency, HOKE SMITH, Governor and President of the
Advisory Board of the Geological Survey of Georgia.*

SIR: I have the honor to transmit herewith a report on the Water Powers of Georgia to be published as Bulletin No. 16 of this Survey. This is the second bulletin which has been issued by the Survey on this very important subject; and, like the first report, Bulletin No. 3, is the result of co-operative work between the State Geological Survey and the United States Geological Survey. The report is, in a large measure, a reprint of Water-Supply and Irrigation Paper No. 197, entitled the Water Resources of Georgia, published by the United States Geological Survey in 1907, with the addition of considerable data subsequently collected. I would here add that the manuscript copy of this bulletin was submitted to this Survey by the Hall Brothers in 1905 at the same time a copy was furnished the United States Geological Survey; but, owing to the ill health of my predecessor, its publication has been delayed until the present.

Very respectfully yours,

S. W. McCALLIE,
State Geologist.



TABLE OF CONTENTS

	Page
The Advisory Board.....	7
Letter of Transmittal.....	9
List of illustrations.....	15
Topography and geology.....	17-21
General features.....	17-19
The Crystalline area.....	19
The Paleozoic area.....	20
The Coastal Plain.....	20-25
Uses of water.....	21-25
Irrigation.....	21-22
Domestic purposes and municipal supply.....	23
Industrial purposes.....	23-25
Water supply of streams.....	25-30
Measurements of flow.....	25-28
Definitions.....	28
Explanation of tables.....	28-29
Gaging stations in Georgia.....	29-30
Savannah River drainage basin.....	30-101
Description of basin.....	30-31
Stream flow.....	31-82
Tallulah River at Tallulah Falls.....	31-36
Tugaloo River near Madison, S. C.....	37-46
Savannah River near Calhoun Falls, S. C.....	46-54
Savannah River at Woodlawn, S. C.....	54-57
Savannah River at Augusta.....	57-59
Broad River (of Georgia) near Carlton.....	70-80
Broad River (South Fork) near Carlton.....	81
Miscellaneous measurements.....	81-82
River surveys.....	83-97
Tallulah River.....	83-85
Tugaloo and Savannah rivers.....	85-92
Chattooga River.....	93-94
Broad River.....	95-97
Water Power.....	97-101
General statement.....	97-98
Tallulah River.....	98-99

	Page
Savannah River drainage basin—Continued.	
Water power—Continued.	
Tugaloo River	99
Savannah River	99-100
Chattooga River	100
Broad River	101
Ogeechee River drainage basin.....	101-115
Description of basin.....	101-102
Stream flow	102-115
Ogeechee River near Millen.....	102-104
Williamsons Swamp Creek at Davisboro.....	104-107
Cannoochee River near Groveland.....	107-113
Miscellaneous measurements	113-115
Altamaha River drainage basin	116-223
Description of basin.....	116-117
Stream flow	117-207
South River near Lithonia.....	117-119
South River near Snapping Shoals.....	119-120
Ocmulgee River near Flovilla	120-124
Ocmulgee River at Macon.....	124-139
Yellow River near Stone Mountain.....	140
Yellow River at Almon.....	140-145
Alcovy River near Covington.....	146-151
Alcovy River near Stewart.....	151-153
Towaliga River near Juliette	154-156
Middle Oconee River near Athens.....	157-160
Oconee River at Barnett Shoals	160-162
Oconee River near Greensboro.....	162-167
Oconee River at Carey.....	168-170
Oconee River at Fraleys Ferry, near Milledgeville.....	170-173
Oconee River at Milledgeville.....	175-176
Oconee River at Dublin.....	176-189
Apalachee River near Buckhead.....	189-196
Ohoopce River near Reidsville.....	196-201
Miscellaneous measurements	202-204
River surveys	207-218
South River	207-209
Ocmulgee River	209-211
Yellow River	211-213
Alcovy River	213-214
Towaliga River	214-215
Oconee and Middle Oconee rivers.....	215-217
Apalachee River	218
Mulberry Fork of Oconee River.....	218

	Page
Altamaha River drainage basin—Continued.	
Water power—Continued.	
Water power	219-223
South River	219
Ocmulgee River	219-220
Yellow River	220-221
Alcovy River	221-222
Towaliga River	222
Oconee River and tributaries	222-223
Minor Atlantic drainage basins.....	223
Satilla River drainage basin.....	223
Miscellaneous measurements	223
Apalachicola River drainage basin.....	224-322
Description of basin.....	224
Stream flow	225-304
Chattahoochee River near Cornelia.....	225
Chattahoochee River near Gainesville.....	226-229
Apalachicola River drainage basin—Continued.	
Stream flow—Continued.	
Chattahoochee River near Buford.....	229-231
Chattahoochee River near Norcross.....	231-236
Chattahoochee River near Vinings.....	236-237
Chattahoochee River at Oakdale.....	237-248
Chattahoochee River at West Point.....	249-260
Soque River near Demorest.....	260-264
Sweetwater Creek near Austell.....	264-266
Mulberry Creek near Columbus.....	266-267
Flint River at Molina.....	267
Flint River near Woodbury.....	268-276
Flint River near Montezuma.....	276-278
Flint River at Albany	279-286
Big Potato Creek near Thomaston.....	286-287
Muckalee Creek near Leesburg.....	287
Muckalee Creek near Albany.....	287-289
Kinchafoonee Creek near Leesburg.....	289-292
Kinchafoonee Creek near Albany	292-294
Ichawaynochaway Creek at Milford.....	294-296
Miscellaneous measurements in Apalachicola River drainage basin	296-304
River surveys	304-317
Chattahoochee River	304-313
Soque River	313-314
Chestatee River	314-316
Flint River	316-317
Water power	318-322
Chattahoochee River	318-320
Soque River	320
Chestatee River	321
Flint River	321-322

	Page
Mobile River drainage basin.....	323-384
Description of basin.....	323
Stream flow	323-381
Etowah River near Ballground.....	323-324
Etowah River at Canton.....	324-335
Etowah River at Rome.....	335-336
Etowah River near Rome.....	337-341
Amicalola River near Ballground.....	341-342
Long Swamp Creek near Ballground.....	342
Coosa River at Rome.....	342-350
Oostanula River at Resaca.....	350-360
Coosawattee River at Carters.....	360-371
Cartecay River near Cartecay.....	372-373
Ellijay River near Ellijay.....	374
Mountaintown Creek near Ellijay.....	374-375
Talking Rock Creek near Carters.....	375
Big Cedar Creek near Cavespring.....	376
Tallapoosa River at Buchanan Bridge, near Tallapoosa.....	376-377
Tallapoosa River at Adderhold Bridge, near Tallapoosa.....	377
Miscellaneous measurements in Mobile River drainage basin in Georgia	378-381
River surveys	381-384
Etowah River	381-382
Coosawattee River	383-384
Water power	384
Etowah River	384
Hiwassee River drainage basin.....	385-410
Description of basin.....	385
Stream flow	385-410
Hiwassee River at Murphy, N. C.....	385-394
Nottely River at Ranger, N. C.....	394-400
Toccoa River near Blueridge, Ga.....	400-405
Ocoee River at McCays, Tenn.....	406-410
Fightingtown Creek at McCays, Tenn.....	410
Miscellaneous measurements in Hiwassee River drainage basin in	411
River surveys	411-418
Hiwassee River	411-414
Nottely River	414-416
Toccoa River	416-418
Index	419-422

LIST OF ILLUSTRATIONS

PLATES

	Opposite page
I. Dam, Power-House and Transmitter-House of the North Georgia Electric Company at Dunlap Shoals, on the Chattahoochee River near Gainesville, Hall county, Georgia -----	<i>Frontispiece</i>
II Indian Arrow Rapids, the head of Tallulah Falls, Georgia -----	32
III The Rapids on the Ocoee River near the Georgia-Tennessee State line -----	56
IV Natural Dam, Big Potato Creek, near Thomaston, Upson county, Georgia -----	80
V View of the Eagle and Phenix Mills, Columbus, Georgia -----	120
VI The Power Plant of the Atlanta Water and Electric Power Company near Roswell, Cobb county, Georgia	152
VII Interior View of the Atlanta Water and Electric Power Company's Power House near Roswell, Cobb county, Georgia -----	200
VIII View of the Ocoee River, near the Georgia-Tennessee State line -----	232
IX Forest Falls, near Whigham, Grady county, Georgia	264
X Toccoa Falls, Habersham county, Georgia -----	296
XI Flat Shoals, on the Flint River, between Pike and Meriwether counties, Georgia -----	328

LIST OF ILLUSTRATIONS

	Opposite page
XII A View of the Locks of the Augusta Canal, looking toward the city of Augusta -----	360
XIII Cotton Mill of the John King Manufacturing Com- pany, Augusta, Georgia -----	376
XIV Hurricane Falls, Tallulah Falls, Georgia -----	392

MAP

Drainage Map of Georgia, showing River Surveys and Stream Gaging Stations -----	17
------------------------------------------------------------------------------------	----

Water Powers of Georgia

TOPOGRAPHY AND GEOLOGY

GENERAL FEATURES

A systematic study of the water powers of the State requires a knowledge of the drainage systems, which are somewhat intricate.

The topography of the State is peculiar. Chattahoochee Ridge, which runs from the northeast corner of the State in a southwesterly and southerly direction through Gainesville, Atlanta, Griffin, Fort Valley, Fitzgerald, and through the Okefenoke Swamp to the Florida line, divides the waters of the Atlantic Ocean from the waters of the Gulf of Mexico and forms the backbone of the State. The great drainage basins on the Atlantic slope are the Savannah, the Ogeechee, the Altamaha, the Satilla, and the St. Marys. Those draining into the Gulf are the Suwanee basin, including Suwanee River and tributaries; the Ochlockonee basin, emptying into Ochlockonee Bay; the Apalachicola basin, including Chattahoochee and Flint Rivers, emptying at Apalachicola, Florida; the Mobile basin, or Coosa River system, draining to Mobile, Alabama; and the Tennessee basin, including Hiawasse, Nottely, and Toccoa (Ocoee) Rivers, which flow through Tennessee and Mississippi rivers, emptying into the Gulf at New Orleans. The last basin is cut off from all the others by the Blue Ridge Mountains, which run across the northern end of the State. Some idea of the diversity of drainage may be had from the statement that there are three springs in northeast Georgia within a stone's throw of each other that send out their waters to Savannah, Georgia, to Apalachicola, Florida, and to New Orleans, Louisiana.

The streams of the Savannah, Altamaha, Apalachicola, Mobile, and Tennessee basins begin in, and have a large part of their territory lying in, the crystalline or granitic region, which is all that part of the State lying north of the southern fall line, and east of the western fall line. The streams of these drainage basins rise at ele-

vations from 900 to 2,000 feet above sea-level and flow along the high Piedmont Plateau in a succession of cascades until they come to the fall line, where they take their last leap from the granitic bed rock to the navigable waters of the younger geologic formations.

The southern fall line passes through Augusta, Milledgeville, Macon, and Columbus, and marks the ancient Atlantic coast line and the present division between the crystalline and Cretaceous geologic formations. Along this line, which is practically parallel to the Blue Ridge Mountains, the Cretaceous lies unconformably upon gneiss, the surface of which slopes toward the sea at a steep angle, and gives unmistakable evidence of having formed at one time a barren rocky seacoast similar to that of Massachusetts.

The western fall line passes through Carters on Coosawattee River and Cartersville on Etowah River and marks the ancient coast line of the Gulf of Mexico or Paleozoic Sea and the present division between the Crystalline and Paleozoic geologic formations. The conditions along this fall line have no similarity to those along the southern fall line. The formations, both crystalline and Paleozoic, have been wrinkled, folded, and faulted by lateral pressure to such an extent that no contact slope exists between the two formations along which percolation could take place. Etowah River below Cartersville shows a hard blue limestone bed rock, out of which many bold springs flow into the river, and while the best shoal on the river is at Cartersville in the crystalline bed rock just above the fall line, the river is a series of shoals all the way down to Rome, where it unites with the navigable Oostanaula to form Coosa River.

The western fall line crosses the Coosawattee in Murray county at Carters, which is the head of navigation. The country along the Coosawattee below Carters is mainly a pervious shale that drinks up most of the smaller streams in driest weather. Although very large limestone springs having a good flow at all seasons abound, yet during long dry spells the streams from most of them become smaller and smaller as the distance from the fountain head increases, and finally soak into the ground and disappear.

From the foregoing discussion it will be seen that the largest and most important water powers of the State are in the crystalline area north of the southern fall line and east of the western fall line. It will be convenient, therefore, in this discussion to divide the State

hydrographically into three areas: (1) The crystalline area in Middle and Northeastern Georgia as above defined; (2) the Paleozoic area in Northwest Georgia, and (3) the coastal plain lying south of the southern fall line and embracing more than half the State.

THE CRYSTALLINE AREA

The crystalline area embraces the Blue Ridge Mountain region, with elevations from 1,000 to 4,800 feet above sea-level, and the Piedmont Plateau, with elevations from 600 to 1,600 feet above sea-level. The rivers of the Piedmont Plateau in this region rise at very high altitudes and flow over granite, gneiss, etc., with precipitous falls in successions of shoals and eddies, between high hills, affording excellent sites for dams and canals, and are peculiarly adapted to the development of high-head water powers, with a good and constant water supply. The following table shows the fall on the main rivers that cross the fall lines in the State:

Fall on Georgia rivers.

River	Distance	
	Miles	Feet
Savannah, above Augusta.....	64	257
Oconee, above Milledgeville.....	54	211
Ocmulgee, above Macon.....	50	219
Flint, above fall line.....	45	334
Chattahoochee, above Columbus.....	35	368
Etowah, above Cartersville.....	17	118
Coosawattee, above Carters.....	24	583

The above table gives an idea of the fall to the mile on the main rivers of the lower part of the Piedmont Plateau. The upper sections of these streams and of their tributaries are even more precipitous. Some shoals on tributaries are as follows:

Broad River, 63 feet in 2 miles.

Tallulah River, 525 feet in $2\frac{2}{3}$ miles.

Towaliga River, 96 feet in 1,200 feet.

Neither the rivers nor their tributaries have any regularity in fall; it is concentrated in shoals over hard ledges of granite or gneiss, with long stretches of gentle flow between. These streams will be considered in detail in the body of this report, and each shoal of importance will be mentioned.

THE PALEOZOIC AREA

The Paleozoic area lies from 400 to 1,000 feet above sea level. The only river in it with much fall is the Etowah, which at Cartersville crosses the fall line from crystalline bed rock to limestone. Between this point and Rome the shoals are caused by harder limestone ledges, the total fall being 109 feet in 46 miles. The tributaries of this river, together with those of the Conasauga, Oostanaula, Coosa, and Tennessee, furnish a large number of small water powers that are valuable for local enterprises, as they are mainly in rich agricultural districts. The entire area abounds also in large springs that can be relied on to furnish a pure and unfailing water supply for municipal and industrial purposes.

THE COASTAL PLAIN

The elevation of the Coastal Plain varies from tide water up to 500 feet above sea level. The large rivers from the crystalline belt cross the southern fall line into this area at the following elevations above sea level:

Elevation of rivers at southern fall line.

	Feet
Savannah, at Augusta.....	98
Oconee, at Milledgeville.....	215
Ocmulgee, at Macon.....	280
Flint, at fall line.....	327
Chattahoochee, at Columbus.....	190

Four of these rivers are rated as navigable streams below the points mentioned. The Savannah and Chattahoochee have regular steamboat lines to these points, but the Oconee and Ocmulgee will require considerable Government work before they can be navigated to Milledgeville and Macon, respectively. Flint River is shoaly all the way to Albany. It is the only one of these rivers that can be counted on for any water power in this area, but on smaller streams there are hundreds of good powers well distributed, many of which are already developed for local uses.

This part of Georgia is developing more rapidly as an agricultural and fruit-raising region than is any other part of the State. Its pine forests are still a great source of wealth, but land that has yielded its

full crop of turpentine and timber is proving more valuable for cotton, corn, watermelons, cantaloupes, pecans, pears, peaches, garden vegetables, and Georgia cane sirup. The climate is mild and healthful, the streams are bold and constant, and the supply of artesian water is abundant and of the best quality.

USES OF WATER

IRRIGATION

In the arid region of the Western States, where the rainfall is not sufficient or is not properly distributed through the year for making crops, the most important use of water is for irrigation. In Georgia and other Southern and Eastern States the rainfall is much greater and more evenly distributed through the year, but, nevertheless, the lack of rain at the proper time often cuts a crop to one-half or one-third what it would have been with one additional wetting at the time most needed. Thus a small amount of water in storage and ready for use will do more good in the East, where it has the help of frequent rains through a large part of the crop season, than will a much greater amount of water in the arid West, where artificial irrigation must be depended on exclusively.

Market gardening is one of the most attractive and most profitable agricultural pursuits in the South, but irrigation is almost a necessity for making the business a safe one. In any event, it can be relied on to double the yield of one crop and to enable the gardener to make from two to three crops on the same land in the same year. In Georgia the gardening season is ordinarily from February to July, but with irrigation it can be extended to November and even later. In Florida the gardening season is in winter, from November to April. This is the dry season, but the planters irrigate from flowing artesian wells and ship celery, lettuce, and other vegetables all winter. This system is being rapidly introduced in southern Georgia.

Artesian wells are the ideal source of water for individual irrigation plants where they can be had at small expense and where the supply is sufficient.

Gravity systems by means of storage dams and canals are more extensive in their application and are practicable on the lowlands of

river and creek valleys having adjacent hill country from which tributaries flow at a higher elevation. These tributaries can be impounded by large storage dams, and small canals can be cut along the hillsides near the foot of the hills to furnish water for irrigating the lowlands. A small stream, properly stored, can be made to irrigate a large area in this way, as one good wetting at the proper time is all that a crop is likely to need.

Hydraulic rams, which are now manufactured of large capacity, can be relied on for pumping water to any desired elevation for irrigating high lands. Some plants of this kind are now in use in Georgia and are giving good results. The water is pumped up by the ram into a large reservoir excavated on a clay hill or made by a dam in a high ravine. The water thus accumulated for months is held until needed and is run through open ditches onto the fields below the reservoir level. A small stream having a flow of 80 gallons a minute and a fall of 20 feet will operate a ram that will pump 15,000 gallons a day to a height of 100 feet above the ram. This amount of water, stored as suggested, will furnish all necessary irrigation to 10 or 12 acres in this State.

A ram of this size takes its water through a 4-inch drive pipe. Rams are made in all sizes, from a 1-inch ram using 3 gallons a minute to a duplex 12-inch ram using two 12-inch drive pipes and a water supply of 1,500 gallons a minute. One of the latter placed on a stream having a flow of 1,500 gallons a minute, which is a very small creek, will utilize a shoal of 20 feet and pump 288,000 gallons a day to a height of 100 feet above the ram. Such creeks are found in all parts of the crystalline region and are plentiful in the hilly parts of the Paleozoic area and of the Coastal Plain. Any amount of fall from 4 feet up to 40 feet can be utilized, the amount of water pumped being directly as the drive head and inversely as the lift. These improved rams open up great possibilities for cheap water supply. Their first cost is very moderate, and they pump by water power, requiring no attendant.

Near the coast, where the streams have very little fall, the agricultural lands are on a low level, from 5 to 15 feet above the streams, and the supply of pine wood for fuel is abundant. Under these conditions centrifugal steam pumps can be run very economically to give abundant water for irrigation.

USE OF WATER FOR DOMESTIC PURPOSES AND MUNICIPAL SUPPLY

Pure drinking water is abundant in all parts of the State. In north and middle Georgia it is obtained from wells, springs, and pure streams. Farther south the best supply is from artesian wells. Most of the large cities of north and middle Georgia get their supply from rivers. Atlanta uses filtered water from the Chattahoochee; Augusta from the Savannah; Macon from the Ocmulgee, and other cities of the region from rivers or local creeks. Savannah, Albany, Americus, Thomasville, Dublin, and other south Georgia municipalities get their supply from artesian wells. In country and suburban communities hydraulic rams are largely used for dairy farms and other domestic supplies. There are also many gravity systems in the mountains and artesian wells in the coastal plain.

USE OF WATER FOR INDUSTRIAL PURPOSES

The supply of water for mining, quarrying, manufacturing, steam making, etc., is very important.

Gold mining is a great industry in the State, and water is largely used for hydraulic work in placers and also in saprolite belts. In the latter class of mining, the water excavates and transports the material in long flumes, automatically depositing the loose gold in the sluice riffles, separating the slate, clay, and slimes from the quartz, and landing the concentrated ore in the mill, where it is crushed by stamps. The free gold is amalgamated on copper plates, and the auriferous iron sulphides are saved on a concentrator and reduced by chlorination and precipitation of the gold. All of these processes require large quantities of water. In the Dahlonega region water for hydraulic mining is brought long distances in open canals along the hillsides and hilltops. Some of these canals are 40 miles and more in length and have cost many thousands of dollars. One of the most famous is the Yahoola ditch from the upper waters of Yahoola Creek. It is 20 miles long from its head to the town of Dahlonega and has supplied mines through branch ditches 10 and 15 miles in length. It carries from 500 to 1,000 miners' inches of water, and water has been sold from it for many years at 12 cents per miner's inch per day. A miner's inch, Colorado standard, is

11¼ gallons, or 1½ cubic feet per minute, or one-fortieth of a cubic foot per second.

In a large part of the extensive gold regions of the State the mining is underground work in which water is not used for excavation, but a large amount of battery water is used in the mills, and an additional supply is needed for the concentrators.

Water is also used extensively in the washing and concentrating processes of iron, manganese, ocher, barytes, pyrites, corundum, asbestos, bauxite, and other minerals.

Quarrying industries require a good water supply, both for making steam and for operating rock drills. The marble quarries near Tate, Marble Hill, and Ball Ground, in Pickens County; the granite quarries at Stone Mountain, Lithonia, Conyers, Lexington, Elberton, and other points; the National Cement Quarries at Cement, Georgia, near Kingston; the slate and limestone quarries of the Southern States Portland Cement Company at Rockmart; and other quarries throughout the State are operated on a large scale.

Immediately allied with the quarrying industry are the great marble manufacturing mills at Tate, Marble Hill, Nelson, Ball Ground, Canton, and Marietta for sawing and finishing marble. The sawing and rubbing is done with sand and water, requiring a good water supply. Aside from the water required for power, there are many manufacturing industries, such as paper making and bleacheries, that can not be operated without pure water and a great deal of it.

There are many large springs in the Paleozoic region of northwest Georgia and also in the Coastal Plain of south Georgia that are clear and sparkling and excellent for drinking purposes, but that contain carbonates of lime and magnesia in solution, either of which is objectionable in a water to be used in chemical purposes such as bleaching; if present in large quantities they even render the water unfit for steam boilers, as they deposit incrustations of lime and magnesia on the inside of the boiler. The springs of the crystalline region of middle and northeast Georgia are generally pure, containing no carbonates and a very insignificant amount of the other mineral ingredients, but in the greater part of this area the springs are small, rarely having a flow of more than 10 or 15 gallons a minute. The exception to this rule is a belt of country within the crystalline

region, running nearly east and west along the pine mountain range in Pike, Upson, Meriwether, Talbot, and Harris Counties, in which there are large springs of pure freestone water, suitable both in quantity and quality for bleacheries, fish hatcheries, etc. One of the largest of these is the Cold Spring in Meriwether County, at Bullochville, about 1 mile below Warm Springs, Georgia, on the Georgia Midland division of the Southern Railway. It has a flow of 2,025 gallons per minute, and is utilized as a fish hatchery by the United States Fish Commission. It issues from a ledge of vitrified sandstone, which is continuous through the entire region, and forms the backbone of the pine mountain range, which is geologically the coast range of Georgia. Warm Spring, about 1 mile distant, has a flow of 1,890 gallons a minute, but is evidently of a much deeper origin, as its temperature is 87° Fahrenheit. There are many other springs of the same character as Cold Spring along the pine mountain belt, one of the most prominent of which is Big Blue Spring, in Harris County, which has been proposed as a water supply for the city of Columbus.

In other parts of the State probably one of the best sources of pure, clear water for chemical use is found in the gravel beds underlying the river bottom land. These gravel beds lie immediately on the bed rock and can generally be relied on to furnish a good supply of water that has been clarified by a natural filter.

WATER SUPPLY OF STREAMS ^a

MEASUREMENT OF FLOW

In order to obtain a knowledge of the water supply, or amount of water flowing in the streams at all seasons, certain convenient stations have been established on important rivers and tributaries.

A gage for observing the stage of the river is established at a bridge or other place where the record of flow is to be made. This gage is a vertical staff, or some other device by which the height of water may be observed, and is read each day by a person living near by. The average of the gage readings, if more than one, in any day is used as the mean gage height for that day.

^a The methods by which the records of stream discharge have been made by the United States Geological Survey are described in detail in *Water-Sup. and Irr. Papers Nos. 94 and 95.*

At various stages of the river one of the hydrographers of the Survey visits the station and measures with a current meter the amount of water flowing. This meter is primarily an instrument for measuring the velocity of moving water, and consists essentially of a wheel with vanes, which may be shaped like those of a windmill or of a screw, or with cups like those of an anemometer, the necessary qualification being that moving water shall readily cause the wheel of the meter to turn. Each meter is rated before use. The rating is done by moving the meter through still water at various observed speeds to determine the relation between the velocity with which the meter moves through the water and the revolutions of the wheel. This relation having been determined, the meter is used in running water, the revolutions per unit of time noted, and the velocity of the water computed.

Observations of depth of water are also made, and from them the area in cross section of each portion of the stream is computed; each partial area multiplied by the mean velocity of that area gives a partial discharge; the sum of the partial discharges is the total discharge of the stream.

Measurements of flow as outlined above are made covering a considerable range of gage height. They are then plotted on coordinate paper, with gage heights for ordinates and discharges for abscissas, and a smooth curve, called the rating curve, is drawn through the points. From this curve a rating table is made which shows the discharge of the stream for any gage height.

The data necessary for the construction of a rating table for a gaging station as just stated are (1) the results of the discharge measurements, which include the record of stage of the river at the time of measurement, the area of the cross section, the mean velocity of the current and the quantity of water flowing, and (2) a thorough knowledge of the conditions at and in the vicinity of the station.

The construction of the rating table depends on the following laws of flow for open permanent channels: (1) The discharge will remain constant so long as the conditions at and near the gaging station remain constant; (2) neglecting the change of slope due to the rise and fall of the stream, the discharge will be the same when-

ever the stream is at a given stage; (3) the discharge is a function of, and increases gradually with, the stage.

The plotting of results of the various discharge measurements, using gage heights as ordinates, and discharge, mean velocity, and area as abscissas, will define curves which show the discharge, mean velocity, and area corresponding to any gage height. For the development of these curves there should be, therefore, a sufficient number of discharge measurements to cover the range of the stage of the stream.^a

As the discharge is the product of two factors, the area and the mean velocity, any change in either factor alone will produce a corresponding change in the discharge. Their curves are therefore constructed in order to study each independently of the other.

The area curve can be definitely determined from accurate soundings extending to the limits of high water. It is always concave toward the horizontal axis or on a straight line, unless the banks of the stream are overhanging.

The form of the mean-velocity curve depends on the surface slope, the roughness of the bed, and the cross section of the stream. Of these the slope is the principal factor.

This curve may be a straight line, or a curve either convex or concave, or may be a combination of these three forms, owing to the relative degree to which any of the factors are present or to the change which they undergo during the change of gage height. A careful study of the conditions at a gaging station makes it possible to predict the form of this curve and to extend it beyond the limits of the actual measurements.

The discharge curve is defined primarily by the measured discharges, and when these do not cover the entire range of gage height for which it is desired to make a rating table, the curve is sometimes extended by the use of the area and mean-velocity curves, which have themselves been extended, as above shown. This curve, under normal conditions, is concave toward the horizontal axis and is generally parabolic in form.

In preparing the rating table the discharge for each tenth on the

^a A typical rating curve with corresponding area and mean velocity curves is given; in *Water Supply and Irrigation Paper No. 168, 1906, p. 17.*

gage is taken from the curve, and the differences between successive discharges are then adjusted according to the law that they shall be either increasing or constant. The finished rating table shows the discharge in cubic feet per second, corresponding to each tenth of a foot on the gage, and is used to supply the discharge values to the daily gage heights furnished by the observer in making up the daily or monthly estimate of flow.

DEFINITIONS

The volume of water flowing in a stream, the "run-off," is expressed in various terms, each of which is associated with a certain class of work. These terms may be divided into two classes: Those which represent a rate of flow, as second-foot, gallons per minute, and run-off in second-feet per square mile, and those which represent actual quantities of water, as run-off in depth in inches. They may be defined as follows:

"Second-foot" is an abbreviation for cubic foot per second and is the quantity of water flowing in a stream 1 foot wide, 1 foot deep, at the rate of 1 foot per second. It is generally used as a fundamental unit from which the others are computed.

"Gallons per minute" is generally used in connection with pumping and city water supply.

"Second-feet per square mile" is the average number of cubic feet of water flowing per second from each square mile of area drained, on the assumption that the run-off is distributed uniformly both as regards time and area.

"Run-off in inches" is the depth to which the drainage area would be covered if all the water flowing from it in a given period were conserved and uniformly distributed over the surface. It is used for comparing run-off with rainfall, which is usually expressed in depth in inches.

EXPLANATION OF TABLES

For each regular station are given, as far as available, the following data:

1. Description of station.
2. List of discharge measurements.
3. Gage-height tables.
4. Rating tables.

5. Tables of estimated monthly and yearly discharges and run-off, based upon all the facts available to date.

The descriptions of stations give such general information about the locality and equipment as would enable the reader to find and use the station. They also give, as far as possible, a complete history of all the changes that have occurred since the establishment of the station that would affect the use of the data collected.

The discharge-measurement table gives the results of the discharge measurements made during each year, and includes the date, the gage height, and the discharge in second-feet.

The table of daily gage heights gives for each day the mean height of the surface of the river, as found from the mean of the gage readings taken on that day.

The rating table gives discharges in second-feet corresponding to each stage of the river, as given by the gage-heights.

In the table of estimated run-off the column headed "Maximum" gives the mean flow for the day when the mean gage height was the highest, and it is the flow as given in the rating table for that mean gage height. As the gage height is the mean for the day, there might have been short periods when the water was higher and the corresponding discharge larger than given in this column. Likewise, in the column of "Minimum," the quantity given is the mean flow for the day when the mean gage height was lowest. The column headed "Mean" gives the average flow for each second during the month. Upon this mean the computations for the remaining columns are based.

GAGING STATIONS IN GEORGIA

The gaging stations maintained in Georgia are listed below :

Tallulah River at Tallulah Falls.	Chattahoochee River near Norcross.
Tugaloo River near Madison, S. C.	Chattahoochee River near Vinings.
Savannah River near Calhoun Falls, S. C.	Chattahoochee River at Oakdale.
Savannah River at Woodlawn, S. C.	Chattahoochee River at West Point.
Savannah River at Augusta.	Soque River near Demorest.
Broad River (of Georgia) near Carlton.	Sweetwater Creek near Austell.
Broad River (South Fork) near Carlton.	Mulberry Creek near Columbus.
Ogeechee River near Millen.	Flint River at Molina.
Williamsons Swamp Creek at Davisboro.	Flint River near Woodbury.
	Flint River near Montezuma.
	Flint River at Albany.
	Big Potato Creek near Thomaston.

Cannoochee River near Groveland.	Muckalee Creek near Leesburg.
South River near Lithonia.	Muckalee Creek near Albany.
South River near Snapping Shoals.	Kinchafoonee Creek near Leesburg.
Ocmulgee River near Flovilla.	Kinchafoonee Creek near Albany.
Ocmulgee River at Macon.	Ichawaynochaway Creek at Milford.
Yellow River near Stone Mountain.	Etowah River near Ballground.
Yellow River at Almon.	Etowah River at Canton.
Alcovy River near Covington.	Etowah River at Rome.
Alcovy River near Stewart.	Etowah River near Rome.
Towaliga River near Juliette.	Amicalola River near Ballground.
Middle Oconee River near Athens.	Long Swamp Creek near Ballground.
Oconee River at Barnett Shoals.	Coosa River at Rome.
Oconee River near Greensboro.	Oostanaula River at Resaca.
Oconee River at Carey.	Coosawattee River at Carters.
Oconee River at Fraleys Ferry, near Milledgeville.	Cartecay River near Cartecay.
Oconee River at Milledgeville.	Ellijay River near Ellijay.
Oconee River at Dublin.	Mountaintown Creek near Ellijay.
Apalachee River near Buckhead.	Talking Rock Creek near Carters.
Ohoopee River near Reidsville.	Big Cedar Creek near Cavespring.
Chattahoochee River near Cornelia.	Tallapoosa River at Buchanan Bridge, near Tallapoosa.
Chattahoochee River near Gainesville.	Tallapoosa River at Adderhold Bridge, near Tallapoosa.
Chattahoochee River near Buford.	

SAVANNAH RIVER DRAINAGE BASIN

DESCRIPTION OF BASIN

Savannah River is formed by the junction of Tugaloo and Seneca rivers, which unite about 100 miles above Augusta, Georgia. It flows in a southeasterly direction, forming the boundary between Georgia and South Carolina, and empties into the Atlantic Ocean near Savannah, Georgia. It is navigable up to Augusta, which is at the fall line.

Seneca River is formed by the junction of Little and Keowee rivers, about 5 miles northeast of Seneca, South Carolina. Both of these tributaries rise in the Blue Ridge in North Carolina and the northwestern part of South Carolina.

Tugaloo River is formed by the junction of Chattooga and Talulah rivers, which join at the western corner of Oconee County, South Carolina. It flows in a southeasterly direction and is a part of the boundary between Georgia and South Carolina. Chattooga River rises in Jackson County, North Carolina, and flows in a southwesterly direction along the boundary between Georgia and South

Carolina. Tallulah River rises in Macon County, North Carolina, and in the northwestern part of Rabun County, Georgia, and flows in a southeasterly direction. Parts of its course are cut through the solid rock for hundreds of feet, forming canyons and steep bluffs. Throughout its entire length the fall is very great, and at Tallulah Falls the stream drops more than 500 feet in a short distance.

Broad River joins the Savannah at the southeast corner of Elbert County, Georgia. It rises in Habersham and Banks counties and flows in a southeasterly direction to the southeast corner of Madison County, Georgia, where the South Fork joins it. From there it flows east to Savannah River. Its drainage is from a rolling country, and there is a considerable amount of fall at various points. At Anthony Shoals the fall is more than 50 feet in a short distance. Above Augusta, Georgia, there is much fall, which can be developed for water power. Except at the large plant at Augusta, very little of this is being used.

STREAM FLOW

TALLULAH RIVER AT TALLULAH FALLS

This station was originally established August 29, 1900, by M. R. Hall, and records of gage heights were obtained until October 19, 1900. The record was resumed January 18, 1901, and maintained until December 31, 1901. The station was reestablished July 10, 1904, when bench marks were determined and regular gage readings begun. The station is located at the wagon bridge about one-fourth mile above the falls and about the same distance from the village of Tallulah Falls, Georgia.

The channel is nearly straight for 300 feet above and 200 feet below the station. The current is swift. Both banks are high, wooded, rocky bluffs and are not subject to overflow. The bed of the stream is composed of rock and is rough and permanent. There is but one channel at all stages.

Discharge measurements are made from the iron wagon bridge, which has a single span of 100 feet and rests on timber piers. The initial point for soundings is the end of the bridge on the upstream side at the left bank.

The original gage is a vertical rod spiked to a small maple tree on

WATER POWERS OF GEORGIA


the left bank of the river about 50 feet above the bridge. June 21, 1905, a 5-foot rod gage was fastened vertically to the solid rock on the right bank 25 feet above the bridge. The datum is the same as that of the original gage. The gage is read once each day by J. T. McKay, who is paid by the Georgia Geological Survey. The bench mark consists of a copper plug set in the solid rock on the right bank, 27 feet upstream from the upper edge of the bridge; elevation, 7.05 feet above gage datum.

Discharge measurements of Tallulah River at Tallulah Falls

Date	Gage height	Dis-charge	Date	Gage height	Dis-charge
	<i>Feet</i>	<i>Sec.-ft.</i>		<i>Feet</i>	<i>Sec.-ft.</i>
1899			1904		
October 3.....	0.55	153	September 29.....	.50	145
November 25.....	.75	188	October 28.....	.40	125
1900			October 28.....	.41	127
August 29.....	1.00	252	November 23.....	.77	171
1901			November 23.....	.75	169
January 18.....	1.95	681	1905		
February 15.....	1.85	617	March 3.....	1.70	471
March 4.....	2.80	1,227	May 11.....	1.88	605
May 22.....	3.94	2,161	May 27.....	2.10	673
May 23.....	3.24	1,566	May 28.....	2.10	681
May 23.....	3.15	1,479	June 21.....	1.84	375
July 15.....	1.58	488	June 22.....	1.77	621
August 27.....	3.45	1,601	July 18.....	2.78	705
September 18.....	2.80	1,309	July 18.....	2.08	683
October 19.....	1.55	506	September 6.....	1.15	317
1903			October 24.....	.89	228
June 23.....	1.96	698	November 15.....	.82	198
1904			1906		
March 16.....	1.65	490	January 24.....	3.26	1,490
May 12.....	1.86	516	February 14.....	1.82	577
June 11.....	1.20	306	June 27.....	1.50	416
June 13.....	1.05	295	July 26.....	2.20	788
July 15.....	.70	181	September 28.....	3.81	2,060
August 22.....	.92	233	September 29.....	5.59	4,450
August 23.....	.80	218	September 29.....	5.56	4,340
			December 31.....	4.22	2,600
			December 31.....	4.12	2,440

Daily gage height, in feet, of Tallulah River at Tallulah Falls

Day	Aug.	Sept.	Oct.	Day	Aug.	Sept.	Oct.	Day	Aug.	Sept.	Oct.
1900				1900				1900			
1.....		1.5	1.03	12.....		0.85	1.01	23.....		1.25	
2.....		1.4	1.03	13.....		.8	1.01	24.....		1.2	
3.....		1.1	1.02	14.....		1.2	1.0	25.....		1.2	
4.....		1.0	1.01	15.....		1.95	1.0	26.....		1.19	
5.....		1.0	1.01	16.....		2.9	1.0	27.....		1.17	
6.....		1.0	1.03	17.....		1.95	1.0	28.....		1.1	
7.....		1.0	1.03	18.....		1.7	1.0	29.....	1.0	1.09	
8.....		1.0	1.02	19.....		1.4	1.0	30.....	.95	1.04	
9.....		.9	1.02	20.....		1.35		31.....	1.3		
10.....		.9	1.01	21.....		1.3					
11.....		.9	1.01	22.....		5.4					



INDIAN ARROW RAPIDS, THE HEAD OF TALLULAH FALLS, GEORGIA.



SAVANNAH DRAINAGE BASIN, STREAM FLOW

Daily gage height, in feet, of Tallulah River at Tallulah Falls.—Continued.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1901												
1		1.9	1.8	2.7	2.4	2.5	2.25	1.4	3.2	1.85	1.4	1.25
2		1.9	1.8	4.95	2.35	2.3	2.2	1.85	3.15	1.85	1.4	1.3
3		2.95	1.75	4.9	2.3	2.2	2.2	1.3	3.1	1.8	1.4	1.3
4		2.4	1.7	2.9	2.25	2.1	2.15	1.3	3.0	1.8	1.4	1.35
5		2.0	1.65	2.85	2.25	2.05	2.1	1.25	3.9	1.8	1.4	1.35
6		2.0	1.6	2.8	2.25	1.95	2.05	6.35	3.85	1.75	1.4	1.3
7		1.95	1.6	2.75	2.2	1.9	2.0	4.25	3.85	1.75	1.4	1.3
8		2.2	1.6	2.7	2.15	1.8	2.0	3.15	3.75	1.7	1.35	1.3
9		2.2	1.6	2.6	2.1	1.8	1.95	2.75	3.7	1.7	1.35	1.3
10		2.1	1.95	2.55	2.05	1.75	1.9	2.05	3.7	1.7	1.35	1.3
11		2.0	2.1	2.45	2.0	1.75	1.9	1.9	3.6	1.65	1.35	1.4
12		1.95	1.95	2.4	2.0	1.7	1.85	1.8	3.6	1.65	1.35	1.4
13		1.95	1.7	2.6	1.85	1.8	1.8	1.9	3.5	1.65	1.35	1.35
14		1.95	1.65	2.5	1.85	2.1	1.7	6.85	3.5	1.65	1.35	2.8
15		1.9	1.65	2.4	1.8	2.0	1.6	3.9	3.4	1.65	1.3	2.8
16		1.85	1.6	2.3	1.75	2.1	1.6	4.3	3.35	1.6	1.3	2.75
17		1.85	1.55	2.2	1.75	2.2	1.55	5.4	3.25	1.6	1.3	2.75
18	1.95	1.85	1.55	2.1	1.7	2.4	1.55	3.4	3.1	1.6	1.3	2.7
19	1.9	1.85	1.5	5.5	1.9	2.5	2.0	3.15	2.9	1.6	1.35	2.7
20	1.9	1.8	1.5	5.5	2.5	2.5	2.15	2.75	2.6	1.55	1.35	2.7
21	1.9	1.8	2.0	3.8	3.5	2.4	2.05	2.4	2.3	1.55	1.3	2.65
22	1.9	1.8	1.95	3.6	4.9	2.3	1.95	4.55	2.2	1.55	1.3	2.4
23	1.95	1.8	1.85	3.3	3.3	2.3	1.85	4.25	2.1	1.5	1.3	2.15
24	1.95	1.8	1.85	2.9	2.8	2.25	1.75	3.8	2.0	1.5	1.3	1.8
25	1.9	1.8	7.5	2.8	2.6	2.25	1.7	3.5	1.95	1.5	1.3	1.6
26	1.9	1.8	6.5	2.75	2.5	2.35	1.65	3.2	1.95	1.5	1.3	1.5
27	1.9	1.8	4.5	2.7	2.45	2.4	1.55	3.3	1.9	1.5	1.3	1.45
28	1.9	1.8	3.9	2.6	2.4	2.4	1.55	5.8	1.9	1.45	1.3	1.4
29	1.9		2.95	2.5	2.4	2.35	1.5	4.1	1.9	1.45	1.25	10.5
30	1.9		2.9	2.45	2.35	2.3	1.5	3.15	1.95	1.45	1.25	5.8
31	1.95		2.75		2.3		1.4	2.3		1.4		4.1

Day	July	Aug.	Sept.	Oct.	Nov.	Dec.	Day	July	Aug.	Sept.	Oct.	Nov.	Dec.
1904													
1		0.9	0.9	0.5	0.4	0.7	17	0.7	1.4	0.7	0.4	0.5	0.8
2		1.3	.8	.5	.4	.7	18	.7	1.3	.6	.4	.5	.8
3		1.0	.8	.5	.6	.8	19	.7	1.1	.6	.4	.5	.7
4		.9	1.3	.5	1.0	.8	20	.6	1.5	.7	.4	.5	.7
5		.9	1.5	.5	.9	1.9	21	.6	1.0	.6	.4	.5	.7
6		1.0	1.0	.5	.6	1.7	22	.6	.9	.6	.4	.6	.7
7		2.5	.8	.5	.6	1.1	23	.7	.8	.6	.4	.6	.7
8		2.5	.8	.5	.5	.9	24	.7	1.0	.6	.4	.6	.6
9		1.6	.8	.5	.5	.8	25	1.2	1.4	.6	.4	.6	1.0
10		1.7	.7	.5	.5	.8	26	.8	1.2	.6	.5	.5	.9
11		2.6	.8	.5	.5	.7	27	.7	1.7	.6	.5	.5	.9
12		2.0	.7	.5	.5	.7	28	.7	1.5	.7	.5	.5	2.4
13		2.9	.8	.4	.8	.7	29	.8	1.1	.6	.5	.5	1.5
14		1.7	.8	.4	.7	.7	30	.7	.9	.5	.4	.6	1.3
15		0.7	1.5	.7	.4	.6	31	.9	.8		.4		1.1
16		.7	1.4	.7	.4	.5							

WATER POWERS OF GEORGIA

Daily gage height, in feet, of Tallulah River at Tallulah Falls.—Continued.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1905												
1.....	1.1	1.2	1.8	1.6	1.7	1.2	3.5	1.4	1.1	0.8	0.9	0.9
2.....	1.0	1.1	1.7	1.6	1.6	1.2	1.9	1.4	1.1	.9	.9	1.0
3.....	1.0	1.1	1.7	1.5	1.8	1.1	1.4	1.3	1.0	.9	.9	4.5
4.....	.9	1.2	1.7	1.4	2.1	1.1	1.8	1.3	.9	1.1	.9	2.9
5.....	.9	1.2	1.6	1.8	2.0	1.1	2.0	1.4	.9	.9	1.0	2.5
6.....	1.0	1.5	1.7	1.6	2.9	1.2	4.2	1.4	1.1	.9	.9	1.3
7.....	1.8	1.8	1.7	1.7	2.9	1.2	1.3	1.3	1.0	.8	.9	1.2
8.....	1.3	1.8	1.8	1.7	2.2	1.4	1.7	2.3	1.1	.8	.9	1.4
9.....	1.1	2.7	3.5	1.5	2.1	1.8	1.6	2.1	1.1	1.1	.9	4.7
10.....	1.0	2.5	2.8	1.5	1.8	1.8	1.7	2.2	1.1	1.2	.8	2.8
11.....	1.1	2.3	2.3	1.5	1.7	1.4	3.5	2.5	1.0	3.1	.8	2.1
12.....	6.5	2.1	2.0	1.6	1.6	1.3	4.6	2.6	1.0	1.5	.8	1.8
13.....	3.2	3.2	1.8	1.6	1.6	1.2	3.4	2.5	1.0	1.3	.8	1.6
14.....	2.3	2.3	2.8	1.7	1.6	1.2	4.4	2.6	1.0	1.1	.8	1.6
15.....	1.9	2.1	1.7	1.7	1.7	1.3	3.0	2.0	.9	1.1	.8	1.7
16.....	1.6	1.8	1.7	1.8	3.1	1.4	2.4	1.8	1.0	1.1	.8	1.6
17.....	1.5	1.7	1.7	1.7	2.3	1.8	2.3	1.7	1.1	1.0	.9	1.7
18.....	1.4	1.5	1.6	1.7	2.0	1.4	2.1	1.7	1.0	1.0	.9	1.5
19.....	1.5	1.4	1.5	1.5	1.8	1.6	2.0	1.5	1.0	1.0	.9	1.5
20.....	1.4	2.5	1.7	1.5	1.6	1.7	2.1	1.6	.9	1.0	1.0	2.3
21.....	1.4	3.3	2.5	1.5	1.6	1.6	1.8	1.5	.9	1.0	1.0	2.1
22.....	1.4	3.0	2.0	1.5	1.8	1.8	1.7	1.4	1.0	1.0	.9	2.0
23.....	1.2	2.7	1.9	1.5	2.3	1.5	1.7	1.5	1.0	.9	.8	2.4
24.....	1.3	2.4	1.7	1.6	2.5	1.3	1.6	1.4	.9	.9	.8	2.4
25.....	1.3	2.2	1.7	1.6	1.8	1.3	1.6	1.5	.9	.9	1.0	2.5
26.....	1.1	2.0	1.8	1.7	1.9	1.2	1.7	1.5	.9	1.4	1.0	2.4
27.....	1.1	2.0	1.7	1.8	1.4	1.2	1.6	1.4	.8	1.3	.8	2.2
28.....	1.0	1.9	1.7	1.7	1.3	1.2	1.6	1.4	.8	1.2	.8	2.1
29.....	.9	1.7	1.6	1.4	1.3	1.6	1.2	.8	1.0	.8	1.9
30.....	1.1	1.6	1.9	1.2	1.4	1.4	1.2	.9	.9	.9	1.7
31.....	1.0	1.6	1.1	1.4	1.19	1.8
1906												
1.....	1.6	2.3	1.7	2.6	2.0	1.4	1.3	2.5	3.7	4.4	2.3	2.1
2.....	1.5	2.2	1.7	2.6	2.0	2.0	1.3	2.4	3.4	5.0	2.2	2.1
3.....	7.0	2.2	1.8	2.5	1.9	1.8	1.4	2.3	2.9	4.4	2.2	2.0
4.....	4.5	2.3	1.8	2.5	1.9	1.7	1.9	3.2	2.7	4.3	2.2	2.0
5.....	3.0	2.2	1.8	2.4	1.9	1.7	1.5	2.8	2.7	4.1	2.2	2.0
6.....	2.5	2.2	1.7	2.2	2.0	1.6	1.4	2.4	2.6	4.0	2.2	2.7
7.....	2.2	2.2	1.7	2.2	2.2	1.6	1.5	2.5	3.4	4.0	2.1	2.1
8.....	2.1	2.2	1.9	2.2	2.1	1.5	1.5	2.2	2.0	3.3	2.1	2.0
9.....	2.0	2.1	1.9	2.3	2.0	1.4	1.8	2.0	2.2	3.4	2.1	2.0
10.....	2.0	2.1	1.8	2.3	2.0	1.4	1.4	1.9	2.3	3.3	2.1	3.2
11.....	1.9	2.0	1.8	2.3	1.8	1.7	1.4	1.7	2.7	3.2	2.1	2.6
12.....	2.5	1.9	1.8	2.2	1.7	1.9	1.5	1.3	2.6	3.1	2.1	2.0
13.....	2.2	1.8	1.8	2.1	1.7	2.3	1.5	2.0	3.0	3.0	2.1	2.0
14.....	2.2	1.8	1.9	2.2	1.7	2.6	3.8	2.0	2.6	3.0	2.0	2.0
15.....	2.2	1.7	3.7	2.8	1.6	2.4	3.4	2.1	2.4	3.0	2.0	2.0
16.....	2.0	1.6	2.7	2.6	1.6	2.5	3.2	2.6	2.4	2.8	2.0	2.2
17.....	2.0	1.7	2.6	2.3	1.6	2.4	2.4	3.1	2.4	4.0	2.0	2.4
18.....	2.0	1.7	2.4	2.2	1.5	2.0	4.7	4.1	2.5	3.4	2.3	2.7
19.....	2.0	1.7	4.7	2.0	1.5	1.8	4.0	3.1	3.1	3.1	4.9	2.4
20.....	1.9	1.8	3.4	2.0	1.5	1.7	3.1	3.1	4.4	2.9	3.5	2.5
21.....	1.8	1.7	2.7	2.0	1.5	1.7	3.2	2.9	3.7	2.9	3.0	2.2
22.....	3.8	1.6	2.5	2.0	1.5	1.6	2.6	3.7	3.6	2.8	2.3	2.1
23.....	4.7	1.7	2.5	2.0	1.4	1.5	2.4	2.9	3.5	2.7	2.6	2.1
24.....	3.4	1.7	2.5	1.9	1.4	1.9	2.8	2.4	3.2	2.6	2.4	2.2
25.....	2.9	1.7	2.4	1.9	1.4	1.8	2.3	2.3	2.0	2.5	2.4	2.2
26.....	2.9	1.7	2.5	1.9	1.5	1.8	2.3	2.2	2.0	2.5	2.3	2.0
27.....	2.3	1.9	2.6	2.0	2.2	1.7	2.1	2.2	2.5	2.4	3.3	2.0
28.....	2.3	1.8	2.6	2.0	1.9	1.9	2.3	2.2	2.3	2.4	2.2	2.3
29.....	2.5	2.7	2.1	1.7	2.6	2.1	3.2	4.4	2.4	2.2	2.3
30.....	2.4	3.4	2.1	1.6	1.4	2.5	3.0	5.4	2.4	2.1	3.0
31.....	2.3	2.8	1.5	2.4	4.1	2.4	5.0

Rating table for Tallulah River at Tallulah Falls, from August 29, 1900, to December 31, 1905.^a

Gage height	Dis-charge						
<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>
0.40	125	1.30	355	2.20	800	3.50	1,805
0.50	145	1.40	395	2.30	860	4.00	2,230
0.60	165	1.50	435	2.40	920	5.00	3,080
0.70	185	1.60	480	2.50	1,000	6.00	3,980
0.80	210	1.70	525	2.60	1,070	7.00	4,780
0.90	235	1.80	575	2.70	1,145	8.00	5,630
1.00	260	1.90	630	2.80	1,220	9.00	6,480
1.10	290	2.00	685	2.90	1,300	10.00	7,330
1.20	320	2.10	740	3.00	1,380	11.00	8,180

^a Above gage height 3.0 feet the rating curve is a tangent, the difference being 85 per tenth.

Rating table for Tallulah River at Tallulah Falls, Ga., for 1906.

Gage height	Dis-charge						
<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>
1.30	355	2.30	860	3.30	1,600	4.60	3,000
1.40	395	2.40	920	3.40	1,690	4.80	3,260
1.50	435	2.50	1,000	3.50	1,780	5.00	3,520
1.60	480	2.60	1,070	3.60	1,880	5.20	3,810
1.70	525	2.70	1,140	3.70	1,980	5.40	4,110
1.80	575	2.80	1,210	3.80	2,080	5.60	4,410
1.90	630	2.90	1,280	3.90	2,180	5.80	4,730
2.00	685	3.00	1,360	4.00	2,290	6.00	5,060
2.10	740	3.10	1,440	4.20	2,510	7.00	6,980
2.20	800	3.20	1,520	4.40	2,750	8.00	9,000

NOTE.—The above table is based on discharge measurements made during 1904-1906 and is well defined below gage height 6 feet.

WATER POWERS OF GEORGIA

Estimated monthly discharge of Tallulah River at Tallulah Falls.

[Drainage area, 191 square miles.]

Month	Discharge in second-feet			Run-off	
	Maximum	Minimum	Mean	Sec.-ft. per sq. mile	Depth in inches
1900 ^a					
September.....	3,420	210	467	2.44	2.72
October (1-19).....	269	260	264	1.38	.975
1901 ^a					
January (18-31).....	658	630	638	3.34	1.74
February.....	1,340	575	670	3.51	3.66
March.....	5,200	435	1,007	5.27	6.08
April.....	3,500	740	1,442	7.55	8.42
May.....	6,060	525	1,070	5.60	6.46
June.....	1,000	525	782	4.09	4.56
July.....	830	395	603	3.16	3.64
August.....	4,650	338	1,690	8.85	10.20
September.....	2,145	630	1,379	7.22	8.06
October.....	602	395	491	2.57	2.96
November.....	395	338	369	1.93	2.15
December.....	7,760	338	1,029	5.39	6.21
1904					
July 15-31.....	320	165	195	1.02	0.645
August.....	1,300	210	447	2.34	2.70
September.....	575	145	209	1.09	1.22
October.....	145	125	135	.707	.815
November.....	260	125	160	.838	.985
December.....	980	165	266	1.39	1.60
1905					
January.....	4,360	235	526	2.75	3.17
February.....	1,635	290	744	3.90	4.06
March.....	1,805	435	649	3.40	3.92
April.....	630	395	490	2.57	2.87
May.....	1,465	290	650	3.40	3.92
June.....	575	290	369	1.93	2.15
July.....	2,740	355	900	4.71	5.43
August.....	1,070	290	537	2.81	3.24
September.....	290	210	254	1.33	1.43
October.....	1,465	210	312	1.63	1.83
November.....	260	210	230	1.20	1.34
December.....	2,825	235	793	4.15	4.73
The year.....	4,360	210	538	2.32	38.24
1906					
January.....	6,930	435	1,250	6.54	7.54
February.....	360	430	640	3.35	3.49
March.....	3,130	525	974	5.10	5.88
April.....	1,210	630	316	4.27	4.76
May.....	800	395	552	2.39	3.33
June.....	1,210	395	627	3.23	3.66
July.....	3,130	355	962	5.04	5.81
August.....	9,000	355	1,350	7.07	8.15
September.....	4,110	635	1,450	7.59	8.47
October.....	4,110	930	1,670	8.74	10.03
November.....	3,390	635	946	4.95	5.52
December.....	3,530	635	923	4.86	5.60
The year.....	9,000	355	1,010	5.31	72.29

^a These are revised estimates based on the 1904 rating curve, which more nearly represents the true flow for low stages than the curve previously used.

NOTE.—Values for 1906 are excellent.

TUGALOO RIVER NEAR MADISON, SOUTH CAROLINA

This station was originally established July 19, 1898, at Cooks Ferry and was discontinued December 31, 1901, when the ferry was moved. It was reestablished July 7, 1903, by M. R. Hall, at Holcombs Ferry, 1 mile west of Madison, South Carolina, and 900 feet below the Southern Railway bridge. This station is about 1½ miles above the point where the old station was located.

The bed of the river is sandy and the current is moderately swift. The channel is about 160 feet wide and is fairly uniform in width and general appearance for some distance, being straight for 1,000 feet or more both above and below the station. The banks are both moderately high, but will overflow for about 200 feet on the right bank and 250 feet on the left. Both are open and cultivated except for a few trees along the edge of the river. These conditions make it possible to obtain fairly good float measurements at the time of floods.

Discharge measurements are made from the ferry boat, or a small boat which is held in place by a cable stretched across the river. The initial point for soundings is the land side of the windlass used for stretching the cable; it is located on the right bank. Distances are measured along the hand line which is used to pull the boat across the river.

The gage consists of a vertical timber in three sections. The first section reads from 1 to 16 feet and is attached to a sycamore tree on the left bank, about 30 feet above the ferry landing; the second section reads from 16 to 22 feet and is attached to a sycamore tree on the left bank, about 18 feet above the ferry landing; the third section reads from 21 to 31 feet and is fastened to a locust tree on the left bank at the forks of the road, about 175 feet from the ferry landing. The gage is read once each day by T. A. Spencer. The bench mark is a U. S. Geological Survey standard bronze tablet marked "666 Atlanta" on the right-bank pier of the Southern Railway bridge; elevation, 35.30 feet above the datum of the gage. It is 665.47 feet above sea level.

WATER POWERS OF GEORGIA

Discharge measurements of Tugaloo River near Madison, S. C.

Date	Gage height	Dis-charge	Date	Gage height	Dis-charge
1898			1903		
May 25.....	<i>Feet</i> 1.50	<i>Sec.-ft.</i> 902	August 28.....	<i>Feet</i> 2.13	<i>Sec.-ft.</i> 798
June 9.....	.90	563	September 24.....	1.94	715
July 19.....	2.05	1,100	October 9.....	2.23	927
October 28.....	4.00	2,439	1904		
1899			January 13.....	1.81	680
April 21.....	4.50	2,604	March 11.....	3.86	1,679
May 22.....	3.20	1,687	June 10.....	2.30	809
June 20.....	2.10	1,325	July 23.....	1.80	622
September 12.....	1.00	734	September 6.....	2.52	896
1900			October 27.....	1.41	406
February 21.....	4.25	2,243	1905		
August 30.....	1.71	872	March 7.....	3.38	1,317
December 25.....	36.0	1,717	March 20.....	3.25	1,243
December 27.....	2.30	1,414	March 21.....	3.75	1,552
1901			March 21.....	4.00	1,795
February 14.....	3.40	1,669	May 1.....	3.31	1,264
May 24.....	5.65	3,120	June 29.....	2.56	874
1903			September 8.....	2.78	970
June 24.....	4.00	1,927	October 14.....	2.66	880
July 7.....	3.69	1,677	November 17.....	2.13	641
July 9.....	3.40	1,535	1906		
July 31.....	2.34	1,091	May 16.....	3.45	1,330
			June 26.....	3.68	1,410

Daily gage height, in feet, of Tugaloo River near Madison, S. C.

Day	July	Aug.	Sept.	Oct.	Nov.	Dec.	Day	July	Aug.	Sept.	Oct.	Nov.	Dec.
1898							1898						
1.....		2.3	6.4	3.0	3.6	5.0	17.....		4.1	3.7	4.3	3.6	2.7
2.....		2.1	20.0	2.8	3.5	3.4	18.....		6.4	3.6	9.35	3.6	2.7
3.....		6.2	17.0	3.1	3.4	3.4	19.....	2.1	5.7	3.4	6.2	4.7	2.7
4.....		9.75	13.0	18.0	3.3	3.5	20.....	1.9	5.7	3.3	5.0	4.0	4.5
5.....		9.2	8.2	22.0	3.4	4.3	21.....	1.8	4.3	3.2	5.5	3.6	3.5
6.....		6.7	7.3	14.0	4.1	3.6	22.....	1.7	3.8	3.4	6.3	3.4	3.2
7.....		5.4	6.3	8.7	3.4	3.5	23.....	4.1	3.4	3.1	5.2	6.3	7.3
8.....		6.1	5.4	7.8	3.3	3.4	24.....	4.4	3.4	4.3	4.7	4.7	4.7
9.....		4.7	4.9	6.8	3.2	3.3	25.....	4.5	3.8	3.7	4.5	4.1	4.0
10.....		4.8	4.9	6.2	3.3	3.2	26.....	4.0	3.9	3.4	4.3	3.9	3.7
11.....		8.9	4.8	5.8	4.1	3.6	27.....	2.9	3.6	3.3	4.2	3.6	3.5
12.....		7.95	4.5	5.5	3.4	3.0	28.....	4.1	3.1	3.2	4.1	3.4	3.4
13.....		6.7	4.2	5.1	3.3	2.9	29.....	3.0	2.9	3.2	3.9	3.5	3.3
14.....		7.9	4.1	4.8	4.0	2.9	30.....	2.8	3.4	3.1	3.9	3.8	3.2
15.....		4.8	3.9	4.6	3.5	2.8	31.....	4.3	3.2		3.7		3.3
16.....		4.5	3.8	4.4	3.4	2.8							

Daily gage height, in feet, of Tugaloo River near Madison, S. C.—Continued.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug	Sept.	Oct.	Nov.	Dec.
1899												
1.....	4.1	3.9	6.6	6.4	4.3	2.5	1.7	1.4	3.1	0.7	0.9	1.0
2.....	3.4	3.4	5.9	5.9	4.2	2.4	1.6	1.4	2.7	.7	.8	1.1
3.....	3.3	3.5	5.8	5.7	4.1	2.4	1.6	1.3	3.3	.7	.8	1.1
4.....	3.2	7.6	5.4	5.9	4.0	2.3	1.5	1.2	1.9	.7	.8	1.0
5.....	3.2	6.8	6.9	6.0	4.3	2.5	1.5	1.1	1.7	.8	.8	.9
6.....	6.45	11.35	6.0	5.6	4.1	3.3	1.6	1.1	1.4	.9	.7	.9
7.....	5.8	12.7	5.5	7.8	4.8	2.2	1.9	1.1	1.3	.8	.7	.9
8.....	4.6	8.8	5.2	3.7	4.0	2.2	1.6	1.0	1.2	3.3	.7	.8
9.....	4.2	6.8	5.1	6.8	3.8	2.1	1.6	1.0	1.2	2.5	.7	.8
10.....	3.9	5.8	4.9	6.2	3.7	2.0	1.6	1.4	1.1	1.5	.7	.8
11.....	4.2	5.5	4.8	5.8	3.7	2.2	1.5	1.3	1.1	1.0	.7	.9
12.....	4.1	5.3	4.7	5.5	3.6	3.9	1.4	1.0	1.0	.9	.7	12.3
13.....	3.9	8.4	4.2	5.3	3.6	5.3	1.3	.9	.9	.9	.7	8.45
14.....	4.0	4.4	8.05	5.2	3.4	3.5	1.3	1.0	.9	.8	.7	3.1
15.....	4.5	4.5	16.15	5.0	3.3	2.8	1.3	1.0	.8	.8	.7	2.5
16.....	4.0	5.6	13.8	5.1	3.2	2.4	1.2	1.0	.8	.8	.7	2.0
17.....	3.9	5.6	8.4	4.9	3.2	2.5	1.2	1.2	.8	.8	.7	1.8
18.....	3.7	5.0	6.9	4.8	3.1	2.4	1.2	1.0	.8	.9	.7	1.6
19.....	3.4	4.3	16.15	4.8	3.2	2.2	1.1	.9	.8	1.0	.7	1.6
20.....	3.4	4.6	11.6	4.6	3.0	2.1	1.2	.8	.9	1.0	.7	1.9
21.....	3.3	4.5	8.4	4.5	2.9	2.0	1.2	.8	.9	.9	.7	1.6
22.....	3.2	4.5	7.6	4.4	3.1	2.9	1.4	.8	.8	.9	.8	1.4
23.....	3.1	4.4	8.4	4.3	3.0	2.9	1.3	.9	.8	.9	.9	1.3
24.....	3.2	4.3	7.3	4.2	2.8	2.8	1.7	.8	.8	.8	1.1	5.0
25.....	3.4	4.1	6.8	6.8	2.7	2.0	1.4	.9	.8	.8	.9	3.0
26.....	3.2	6.5	6.4	6.0	2.7	1.8	4.1	.8	.9	.8	1.6	2.4
27.....	3.2	9.8	6.2	5.2	2.6	2.1	4.2	1.2	.9	.8	2.6	2.0
28.....	3.1	8.1	6.1	4.8	2.6	2.1	2.4	1.0	.8	.8	1.7	1.9
29.....	3.0	6.8	4.6	2.6	2.0	2.9	.9	.8	.9	1.3	1.8
30.....	2.9	6.0	4.4	2.5	1.8	1.9	1.4	.7	.9	1.1	1.6
31.....	3.1	6.9	2.5	1.6	6.58	1.4

WATER POWERS OF GEORGIA

Daily gage height, in feet, of Tugaloo River near Madison, S. C.—Continued.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1900												
1	1.4	1.6	9.4	3.5	4.2	2.3	5.1	3.1	2.5	1.7	2.1	2.5
2	1.3	1.6	5.5	3.4	4.1	2.6	5.6	2.8	2.8	1.6	2.1	2.4
3	1.3	1.8	3.9	3.4	4.3	2.8	5.1	2.7	2.1	1.7	2.2	2.3
4	1.3	1.7	3.9	3.6	4.0	2.7	4.6	2.5	1.9	1.7	2.9	5.6
5	1.2	2.5	3.7	3.7	3.8	2.9	4.2	2.5	1.8	1.9	2.3	4.8
6	1.2	2.3	3.5	3.4	3.7	2.9	3.9	2.4	1.7	3.2	2.1	3.4
7	1.2	2.1	3.8	3.3	3.6	5.5	3.8	2.3	1.6	1.8	2.0	3.1
8	1.2	2.2	4.3	3.2	3.4	6.7	3.6	2.3	1.6	1.8	2.0	3.0
9	1.2	3.0	6.6	3.1	3.4	4.5	3.8	2.2	1.5	1.5	1.9	2.9
10	1.4	3.5	5.1	3.1	3.3	3.6	3.6	2.1	1.5	1.8	1.9	2.6
11	1.6	4.6	4.5	3.3	3.2	3.3	3.7	2.1	1.5	1.7	1.8	2.5
12	5.5	7.0	4.2	4.1	3.1	3.0	3.6	2.1	1.4	1.6	1.8	2.4
13	3.3	19.95	3.9	3.8	3.1	3.3	3.9	2.2	1.4	2.6	1.8	2.3
14	2.5	9.0	3.7	3.4	3.0	3.3	3.9	2.0	1.6	1.8	1.7	2.3
15	2.1	6.2	3.6	3.2	2.9	3.1	3.7	2.3	3.1	1.6	1.7	2.2
16	2.0	5.2	5.1	3.0	2.9	3.0	3.6	2.1	7.3	1.6	1.7	2.2
17	1.9	4.5	4.0	5.9	2.8	6.9	3.2	2.3	4.0	1.5	1.7	2.1
18	1.8	4.0	3.6	5.1	2.8	5.3	3.1	2.1	2.9	1.5	1.8	2.1
19	4.5	3.8	3.7	7.6	3.3	4.5	3.0	2.0	2.6	1.4	1.9	2.0
20	6.9	3.5	6.2	7.5	2.8	3.9	2.9	1.9	2.3	1.4	2.0	2.3
21	3.4	3.5	5.0	13.4	2.7	3.5	2.8	1.8	2.2	1.4	2.0	4.2
22	3.1	5.0	4.4	3.3	2.6	4.2	2.8	1.8	2.1	1.6	2.0	3.3
23	2.9	4.0	4.2	6.3	2.5	5.8	3.1	2.1	2.0	7.4	1.9	3.0
24	2.4	3.8	4.1	6.2	3.3	13.0	2.9	2.3	2.0	6.8	1.9	4.2
25	2.4	4.0	4.2	5.3	2.9	9.4	2.7	2.1	2.9	4.9	2.2	3.6
26	2.2	3.5	5.8	4.9	2.9	11.4	3.6	2.2	1.8	3.9	9.4	3.1
27	2.1	3.3	4.8	4.6	2.7	6.5	3.2	1.9	2.1	2.9	5.2	2.8
28	1.9	3.1	4.3	4.9	2.5	6.9	3.8	1.8	1.9	2.9	4.1	2.7
29	1.9	4.1	4.7	2.5	6.4	3.1	1.7	1.8	2.5	3.0	2.6
30	1.8	3.9	4.4	2.4	5.7	4.2	1.7	1.7	2.3	3.4	2.6
31	1.8	3.7	2.3	3.3	2.8	2.2	4.0
1901												
1	3.3	2.9	2.4	4.4	4.7	4.6	4.1	2.4	7.3	3.7	2.5	1.9
2	3.1	2.8	2.6	6.6	4.6	4.1	3.8	2.4	6.7	3.9	2.5	1.9
3	2.8	3.0	2.5	10.3	4.5	3.0	3.4	2.3	6.1	4.0	2.5	3.1
4	2.7	6.9	2.5	6.7	4.4	3.9	3.3	2.3	5.6	3.6	2.4	2.7
5	2.6	4.3	2.5	5.8	4.3	3.8	3.2	2.1	5.4	3.5	2.5	2.6
6	2.5	3.9	2.4	5.5	4.4	3.7	3.4	4.1	5.2	3.4	2.4	2.4
7	2.5	3.5	2.3	4.0	4.3	4.1	4.2	9.8	5.1	3.3	2.3	2.2
8	2.4	3.4	2.3	4.7	4.0	5.3	3.4	4.5	4.9	3.2	2.3	2.0
9	2.4	4.8	2.3	4.4	4.0	3.5	3.2	3.6	4.8	3.2	2.3	4.1
10	2.4	4.4	2.3	4.4	4.9	3.4	3.0	3.2	4.7	3.2	2.2	3.1
11	10.35	3.9	4.0	4.3	4.9	3.4	2.9	3.6	5.4	3.2	2.2	3.0
12	12.4	3.8	3.3	4.2	3.8	3.1	2.3	3.9	4.5	3.1	2.2	2.9
13	6.7	3.6	3.0	4.1	3.7	3.4	2.7	4.0	4.9	3.6	2.4	2.6
14	5.5	3.5	2.9	6.7	3.6	5.5	2.8	12.1	3.9	3.2	2.3	3.2
15	4.6	3.8	2.6	5.6	3.6	9.1	2.7	10.5	4.1	3.1	2.1	9.9
16	4.2	3.1	2.6	4.7	3.5	3.0	4.1	11.3	9.7	3.1	2.1	6.9
17	4.2	3.1	2.5	4.3	3.0	5.6	3.3	12.3	3.6	3.0	2.0	5.1
18	3.9	3.0	2.5	4.2	3.0	6.6	2.7	11.5	7.9	3.0	2.0	4.3
19	3.5	3.0	2.5	7.3	3.8	4.2	4.3	8.3	6.5	3.9	2.1	4.1
20	3.3	2.9	2.4	22.0	5.2	4.4	4.1	7.5	4.9	2.9	2.1	3.9
21	3.3	2.8	6.1	9.6	9.9	4.3	3.1	7.3	4.6	2.8	2.0	3.7
22	3.2	2.7	3.7	7.4	17.1	4.1	3.4	10.95	4.3	2.8	2.0	3.2
23	3.1	2.6	3.2	6.7	8.6	3.9	2.3	18.5	4.2	2.3	2.0	3.1
24	3.2	2.7	3.6	6.1	5.9	4.0	2.6	10.1	4.1	2.7	2.5	3.4
25	3.3	2.6	7.9	5.7	5.7	3.9	2.5	7.6	4.0	2.7	2.2	3.6
26	3.3	2.5	19.6	5.6	5.2	5.2	2.5	7.8	3.9	2.7	2.1	3.7
27	3.0	2.4	10.1	5.2	4.8	4.9	3.1	6.9	3.7	2.6	2.0	4.0
28	3.1	2.4	6.7	5.2	4.6	4.9	2.5	9.7	3.8	2.6	1.9	4.0
29	3.9	5.7	4.9	4.4	4.6	2.4	11.9	4.2	2.6	1.9	20.0
30	3.3	4.5	4.3	4.2	4.2	2.5	9.0	3.9	2.5	1.9	10.0
31	2.8	4.4	4.3	2.5	8.6	2.5	7.1

SAVANNAH DRAINAGE BASIN, STREAM FLOW

Daily gage height, in feet, of Tugaloo River near Madison, S. C.—Continued.

Day	July	Aug.	Sept.	Oct.	Nov.	Dec.	Day	July	Aug.	Sept.	Oct.	Nov.	Dec.
1903							1903						
1		2.8	2.0	1.7	1.8	1.6	17	3.3	4.9	3.9	1.7	1.8	1.7
2		5.4	1.9	1.7	1.9	1.6	18	3.2	3.8	3.5	2.4	2.8	1.7
3		4.6	1.9	1.9	2.3	1.6	19	3.1	2.9	2.3	2.0	2.2	1.5
4		4.2	1.9	1.8	2.2	1.6	20	3.0	2.7	2.1	1.8	1.9	1.7
5		3.4	1.9	1.7	3.0	1.6	21	2.9	3.0	2.0	1.8	1.8	2.5
6		2.9	1.9	1.7	2.5	1.7	22	2.9	2.6	2.0	1.7	1.8	2.0
7	3.7	2.8	1.8	1.8	2.1	1.6	23	2.9	2.5	1.9	1.7	1.8	1.9
8	3.7	2.7	1.8	2.4	1.9	1.6	24	2.8	2.4	1.9	1.7	1.8	1.8
9	3.4	2.5	1.8	2.4	1.9	1.6	25	2.7	2.3	1.9	1.6	1.7	1.9
10	3.6	2.4	1.9	1.9	1.8	1.6	26	2.7	2.3	1.8	1.6	1.7	2.0
11	3.9	3.0	1.8	1.8	1.8	1.6	27	2.7	2.2	1.9	1.6	1.7	1.9
12	4.4	2.8	1.7	1.8	1.8	1.6	28	2.6	2.1	1.9	1.6	1.6	1.8
13	4.5	2.7	1.7	1.7	1.9	1.8	29	3.1	2.1	1.8	1.6	1.6	1.8
14	4.1	2.6	1.7	1.7	1.9	2.0	30	2.7	2.1	1.7	1.6	1.6	1.8
15	3.6	2.7	4.1	1.6	1.8	1.8	31	2.9	2.0		1.6		1.8
16	3.2	4.3	5.6	1.6	1.9	1.8							

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1904												
1	1.7	2.0	2.7	3.35	2.7	3.3	2.4	3.7	2.85	1.6	1.4	1.5
2	1.7	1.9	2.3	3.2	2.7	3.4	2.0	3.95	2.2	1.55	1.4	1.6
3	1.8	1.9	2.3	3.1	2.85	2.8	2.0	2.5	2.4	1.6	1.5	1.6
4	1.7	1.9	2.5	2.95	3.1	2.6	1.9	2.4	3.2	1.55	2.2	1.7
5	1.6	1.9	2.5	2.9	2.9	2.4	1.8	2.4	3.2	1.5	2.2	2.0
6	1.6	1.8	2.3	2.85	2.8	2.35	1.8	2.45	2.65	1.5	2.0	4.9
7	1.9	2.0	3.2	4.1	2.7	2.3	1.8	7.0	2.3	1.5	1.6	2.6
8	1.7	4.8	6.9	3.9	4.95	3.3	1.8	6.9	2.2	1.5	1.5	2.1
9	1.6	3.0	5.0	6.1	6.5	2.5	2.1	4.1	2.2	1.5	1.5	1.9
10	1.6	2.5	4.2	4.5	4.5	2.3	2.3	5.5	2.2	1.55	1.5	1.8
11	1.7	2.6	3.9	4.0	3.6	2.3	2.0	6.6	2.05	1.5	1.5	1.8
12	1.7	2.9	3.6	3.7	3.3	2.3	1.9	5.4	2.1	1.45	1.5	1.8
13	1.8	2.3	3.4	3.5	3.1	2.2	2.1	3.8	2.05	1.45	1.8	1.8
14	1.7	2.1	3.5	3.4	3.05	2.1	1.8	3.3	2.0	1.4	2.0	1.7
15	1.7	2.1	3.6	3.3	3.0	2.1	1.75	2.3	1.9	1.4	1.8	1.7
16	1.6	2.1	3.3	3.2	2.9	2.1	1.7	3.0	1.85	1.4	1.6	1.65
17	1.9	2.1	3.1	3.1	2.8	2.1	1.8	2.5	1.9	1.4	1.5	1.7
18	2.0	2.0	3.05	3.1	2.75	2.1	1.8	2.3	1.8	1.4	1.5	1.75
19	1.8	2.2	2.95	3.0	2.7	2.1	1.7	2.2	1.75	1.35	1.5	1.7
20	1.8	4.4	2.85	2.9	2.6	2.5	1.6	3.3	1.75	1.35	1.5	1.65
21	1.7	3.2	2.3	2.95	2.55	2.5	1.55	2.5	1.75	1.4	1.55	1.6
22	5.1	9.5	5.3	2.9	2.5	2.2	2.2	2.2	1.9	1.35	1.6	1.65
23	6.5	5.4	5.3	2.8	2.5	2.1	1.85	2.05	1.8	1.35	1.3	1.6
24	3.4	4.2	5.3	2.8	2.45	2.0	1.75	2.2	1.7	1.35	1.7	1.6
25	2.8	3.5	2.9	2.8	2.45	1.95	1.9	2.2	1.7	1.4	1.55	1.9
26	2.4	3.2	4.7	2.9	2.4	1.95	2.0	2.35	1.7	1.4	1.5	2.0
27	2.3	3.0	4.3	3.3	2.4	1.9	1.9	4.5	1.7	1.4	1.5	1.95
28	2.2	3.0	4.0	2.9	2.3	1.9	1.7	3.6	1.65	1.4	1.5	7.0
29	2.2	2.8	3.7	2.85	2.25	2.7	2.0	2.3	1.7	1.45	1.5	3.5
30	2.1		3.5	2.8	2.4	3.6	1.9	2.5	1.6	1.4	1.5	2.7
31	2.0		3.4		5.2		3.95	2.3		1.4		2.3
1905												
1	2.1	2.4	3.8	2.9	3.4	3.6	21.5	3.4	3.0	2.35	2.35	2.2
2	2.1	2.4	3.6	2.9	3.1	3.5	7.1	3.3	3.8	2.35	2.3	2.1
3	2.1	2.35	3.5	2.9	3.5	3.4	4.9	3.2	3.7	2.3	2.3	12.3
4	2.0	2.25	3.4	2.9	4.5	3.3	4.1	3.2	3.2	3.2	2.3	5.2
5	1.8	2.2	3.3	3.1	4.1	3.2	4.8	3.3	3.1	2.6	2.3	3.7
6	1.9	3.2	3.2	3.3	5.8	3.1	4.7	3.5	2.9	2.4	2.3	3.1
7	4.4	4.0	3.4	3.1	6.2	3.0	4.8	3.3	2.8	2.35	2.35	2.86
8	2.8	3.4	3.4	2.9	5.0	3.0	4.1	4.5	2.8	2.3	2.3	2.8
9	2.4	7.3	3.3	2.9	4.6	2.9	4.0	4.6	2.85	2.3	2.3	12.6
10	2.4	6.6	4.6	3.1	4.0	2.9	4.0	6.2	2.75	2.4	2.3	7.0
11	2.3	4.9	5.1	2.9	3.8	2.8	7.7	6.7	2.7	7.4	2.25	5.0
12	11.8	4.5	4.3	2.95	3.6	2.8	14.0	6.4	2.75	4.0	2.25	4.2
13	3.7	7.9	4.0	3.5	3.5	2.8	10.3	6.8	2.9	3.5	2.25	3.8
14	5.3	5.8	4.0	3.2	3.3	2.7	14.5	6.0	2.7	2.6	2.2	3.5
15	4.0	4.8	3.7	3.0	3.2	2.9	8.0	5.3	2.6	2.6	2.2	3.9

WATER POWERS OF GEORGIA

Daily gage height, in feet, of Tugaloo River near Madison, S. C.—Continued.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1905												
16.....	3.6	4.0	3.6	3.2	5.9	3.4	6.7	4.7	2.6	2.65	2.15	3.9
17.....	3.3	3.9	3.4	3.0	4.6	3.6	6.0	4.3	2.6	2.5	2.15	3.6
18.....	3.0	3.5	3.4	2.9	3.9	3.1	5.3	4.2	2.55	2.4	2.1	3.4
19.....	2.9	3.3	3.3	2.8	3.6	2.9	5.3	4.1	2.6	2.45	2.1	3.2
20.....	2.9	7.1	3.3	2.8	3.4	3.2	5.3	3.9	2.6	2.45	2.55	3.4
21.....	2.8	3.5	3.5	2.75	3.3	3.4	4.7	3.8	2.6	2.45	2.35	7.0
22.....	2.6	6.9	4.1	2.8	3.5	3.8	4.5	3.7	2.5	2.3	2.2	5.2
23.....	2.5	5.9	3.7	2.7	6.2	3.3	4.2	3.5	2.45	2.35	2.15	4.4
24.....	2.5	5.1	3.5	2.7	6.6	3.0	4.1	3.9	2.4	2.3	2.1	4.6
25.....	2.4	4.7	3.4	2.65	4.5	2.8	4.0	3.8	2.35	2.35	2.3	4.1
26.....	2.0	4.4	3.3	2.7	4.3	2.7	3.9	4.0	2.35	2.9	2.4	3.8
27.....	2.1	4.1	3.2	3.5	4.9	2.6	3.3	3.4	2.3	2.7	2.25	3.6
28.....	2.4	4.0	3.1	3.3	5.4	2.65	3.7	3.3	2.3	2.5	2.15	3.5
29.....	2.3	3.1	3.0	4.6	2.6	3.3	3.2	2.3	2.45	2.15	4.5
30.....	2.4	3.0	4.0	4.1	15.0	3.6	3.1	2.3	2.45	2.2	3.9
31.....	2.4	3.0	3.9	3.5	3.0	2.4	3.6
1906												
1.....	3.45	5.2	3.6	6.6	4.45	3.25	3.2	7.3	8.0	14.4	5.2	4.6
2.....	3.35	5.0	3.5	6.0	4.15	3.5	3.0	6.0	6.8	11.2	5.1	4.55
3.....	13.4	4.85	4.25	5.6	4.05	3.65	3.1	5.2	6.3	15.4	5.0	4.5
4.....	18.0	4.75	6.6	5.4	4.35	4.5	4.9	6.0	6.0	14.0	4.95	4.45
5.....	9.0	4.65	5.6	5.2	4.05	3.7	3.7	5.3	6.4	11.1	4.9	4.35
6.....	6.2	4.55	4.55	5.2	3.95	3.7	3.3	5.4	5.8	11.2	4.85	4.3
7.....	5.4	4.55	4.25	5.0	4.35	3.35	3.75	5.4	9.4	10.6	5.2	4.3
8.....	5.0	4.4	4.85	4.85	4.05	3.25	3.6	5.0	7.3	9.6	4.7	4.3
9.....	5.2	4.35	4.65	4.8	3.9	3.15	4.6	4.7	5.7	8.8	4.65	4.3
10.....	4.75	4.25	4.35	5.6	3.75	3.3	3.6	4.5	5.5	8.4	4.6	4.2
11.....	4.35	4.15	4.15	4.85	3.75	4.2	3.3	4.4	5.2	8.0	4.6	7.1
12.....	5.2	4.25	4.05	4.7	3.7	3.4	3.3	4.2	8.0	7.7	4.55	5.1
13.....	4.85	4.3	3.95	4.6	3.65	5.8	3.35	4.2	9.2	7.4	4.5	4.7
14.....	4.85	4.15	3.95	4.55	3.6	6.9	3.2	4.3	5.6	9.2	4.4	4.6
15.....	4.65	4.05	12.2	7.2	3.55	5.2	17.5	7.2	5.3	7.0	4.6	4.45
16.....	4.85	3.95	7.2	5.8	3.45	6.2	9.3	7.2	5.1	6.9	4.5	4.3
17.....	4.55	3.85	5.6	5.2	3.4	5.4	8.3	5.4	4.95	6.7	4.5	5.9
18.....	4.35	3.8	5.0	4.95	3.35	4.7	12.9	12.7	9.2	6.6	9.7	7.4
19.....	4.35	3.75	11.2	4.75	3.25	4.15	7.9	7.1	16.2	3.7	11.5	5.4
20.....	4.15	3.75	9.0	4.65	3.3	4.0	7.4	7.6	14.0	7.1	8.4	5.6
21.....	4.05	3.85	6.8	4.55	3.2	3.75	7.6	6.1	9.5	6.7	6.9	5.3
22.....	10.2	4.35	6.0	4.45	3.3	3.55	6.5	6.1	8.8	6.4	6.3	5.2
23.....	18.0	3.95	5.6	4.4	3.25	3.4	5.9	6.6	8.1	6.3	5.8	4.8
24.....	9.0	3.85	5.2	4.25	3.15	3.7	6.8	6.6	7.7	6.1	5.5	4.6
25.....	7.2	3.8	5.0	4.25	3.1	3.6	5.4	5.8	7.4	6.0	5.2	4.4
26.....	6.8	3.7	4.95	4.15	3.45	3.75	5.1	5.6	7.3	5.8	5.1	4.35
27.....	6.8	3.7	4.95	4.15	5.5	3.4	4.8	6.1	6.9	5.7	5.0	4.3
28.....	6.6	3.65	5.2	4.45	3.9	3.3	5.4	5.2	7.3	5.6	5.5	4.5
29.....	6.2	5.3	4.25	3.3	3.35	4.9	5.2	11.5	5.5	4.8	4.8
30.....	5.8	8.9	4.85	3.5	3.2	5.9	16.8	19.6	5.4	4.7	4.6
31.....	5.6	3.4	3.35	7.3	11.4	5.3	15.5

SAVANNAH DRAINAGE BASIN, STREAM FLOW

Rating tables for Tugaloo River near Madison, S. C.

JULY 19 TO DECEMBER 31, 1898.^a

Gage height		Discharge		Gage height		Discharge		Gage height		Discharge	
Feet	Sec.-ft	Feet	Sec.-ft	Feet	Sec.-ft	Feet	Sec.-ft	Feet	Sec.-ft	Feet	Sec.-ft
1.70	975	3.10	1,807	4.50	2,835	5.90	3,941				
1.80	1,030	3.20	1,874	4.60	2,914	6.00	4,020				
1.90	1,085	3.30	1,941	4.70	2,998	6.20	4,178				
2.00	1,140	3.40	2,008	4.80	3,072	6.40	4,336				
2.10	1,200	3.50	2,075	4.90	3,151	6.60	4,494				
2.20	1,260	3.60	2,148	5.00	3,230	6.80	4,652				
2.30	1,320	3.70	2,221	5.10	3,309	7.00	4,810				
2.40	1,380	3.80	2,294	5.20	3,388	7.20	4,968				
2.50	1,440	3.90	2,367	5.30	3,467	7.40	5,126				
2.60	1,500	4.00	2,440	5.40	3,546	7.60	5,284				
2.70	1,560	4.10	2,519	5.50	3,625	7.80	5,442				
2.80	1,620	4.20	2,598	5.60	3,704	8.00	5,600				
2.90	1,680	4.30	2,677	5.70	3,783						
3.00	1,740	4.40	2,756	5.80	3,862						

JANUARY 1 TO DECEMBER 31, 1899.^b

0.70	512	3.00	1,685	5.30	3,100	9.20	6,220
.80	563	3.10	1,736	5.40	3,180	9.40	6,380
.90	614	3.20	1,787	5.50	3,260	9.60	6,540
1.00	665	3.30	1,838	5.60	3,340	9.80	6,700
1.10	716	3.40	1,889	5.70	3,420	10.00	6,860
1.20	767	3.50	1,940	5.80	3,500	10.50	7,260
1.30	818	3.60	1,991	5.90	3,580	11.00	7,660
1.40	869	3.70	2,042	6.00	3,660	11.50	8,060
1.50	920	3.80	2,093	6.20	3,820	12.00	8,460
1.60	971	3.90	2,144	6.40	3,980	12.50	8,860
1.70	1,022	4.00	2,195	6.60	4,140	13.00	9,260
1.80	1,073	4.10	2,250	6.80	4,300	13.50	9,660
1.90	1,124	4.20	2,310	7.00	4,460	14.00	10,060
2.00	1,175	4.30	2,370	7.20	4,620	14.50	10,460
2.10	1,226	4.40	2,434	7.40	4,780	15.00	10,860
2.20	1,277	4.50	2,500	7.60	4,940	15.50	11,260
2.30	1,328	4.60	2,570	7.80	5,100	16.00	11,660
2.40	1,379	4.70	2,640	8.00	5,260	17.00	12,460
2.50	1,430	4.80	2,710	8.20	5,420	18.00	13,260
2.60	1,481	4.90	2,780	8.40	5,580	19.00	14,000
2.70	1,533	5.00	2,860	8.60	5,740	20.00	14,860
2.80	1,583	5.10	2,940	8.80	5,900		
2.90	1,634	5.20	3,020	9.00	6,060		

^a Discharge estimated above gage height 8.00 feet.

^b Above gage height 4.00 feet the rating curve is a tangent, the difference being 80 per tenth.

WATER POWERS OF GEORGIA

Rating tables for Tugaloo River near Madison, S. C.—Continued.

JANUARY 1, 1900, TO DECEMBER 31, 1901.^a

Gage height	Dis-charge						
<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>
1.20	705	2.20	1,090	3.20	1,580	4.20	2,220
1.30	740	2.30	1,135	3.30	1,635	4.30	2,300
1.40	775	2.40	1,180	3.40	1,690	4.40	2,380
1.50	810	2.50	1,225	3.50	1,745	4.50	2,460
1.60	845	2.60	1,275	3.60	1,800	4.60	2,540
1.70	880	2.70	1,325	3.70	1,860	4.70	2,620
1.80	920	2.80	1,375	3.80	1,920	4.80	2,700
1.90	960	2.90	1,425	3.90	1,990		
2.00	1,000	3.00	1,475	4.00	2,060		
2.10	1,045	3.10	1,525	4.10	2,140		

JULY 7 TO DECEMBER 31, 1903.

1.50	510	2.50	980	3.50	1,560	4.50	2,320
1.60	552	2.60	1,032	3.60	1,630	4.60	2,400
1.70	596	2.70	1,086	3.70	1,700	4.70	2,480
1.80	640	2.80	1,140	3.80	1,775	4.80	2,560
1.90	686	2.90	1,195	3.90	1,850	4.90	2,640
2.00	732	3.00	1,250	4.00	1,925	5.00	2,720
2.10	780	3.10	1,310	4.10	2,000	5.40	3,040
2.20	828	3.20	1,370	4.20	2,080	5.60	3,200
2.30	878	3.30	1,430	4.30	2,160		
2.40	928	3.40	1,495	4.40	2,240		

JANUARY 1 TO DECEMBER 31, 1904.

1.35	435	2.50	915	3.70	1,582	5.80	3,180
1.40	452	2.60	963	3.80	1,646	6.00	3,365
1.50	490	2.70	1,012	3.90	1,710	6.20	3,555
1.60	528	2.80	1,062	4.00	1,775	6.40	3,745
1.70	567	2.90	1,114	4.20	1,905	6.60	3,940
1.80	607	3.00	1,168	4.40	2,045	6.80	4,140
1.90	645	3.10	1,224	4.60	2,195	7.00	4,340
2.00	690	3.20	1,281	4.80	2,345	9.50	7,325
2.10	733	3.30	1,339	5.00	2,505	13.20	14,450
2.20	777	3.40	1,398	5.20	2,665		
2.30	822	3.50	1,458	5.40	2,830		
2.40	868	3.60	1,519	5.60	3,000		

JANUARY 1 TO DECEMBER 31, 1905.^b

1.80	520	3.30	1,275	4.80	2,410	7.60	5,220
1.90	560	3.40	1,340	4.90	2,500	7.80	5,440
2.00	600	3.50	1,405	5.00	2,590	8.00	5,660
2.10	640	3.60	1,470	5.20	2,770	9.00	6,860
2.20	680	3.70	1,540	5.40	2,960	10.00	8,060
2.30	725	3.80	1,610	5.60	3,160	11.00	9,260
2.40	770	3.90	1,680	5.80	3,360	12.00	10,460
2.50	820	4.00	1,755	6.00	3,560	13.00	11,660
2.60	870	4.10	1,830	6.20	3,760	14.00	12,860
2.70	925	4.20	1,910	6.40	3,960	15.00	14,060
2.80	980	4.30	1,990	6.60	4,160	16.00	15,260
2.90	1,035	4.40	2,070	6.80	4,360	18.00	17,660
3.00	1,095	4.50	2,155	7.00	4,560	20.00	20,060
3.10	1,155	4.60	2,240	7.20	4,780	22.00	22,460
3.20	1,215	4.70	2,325	7.40	5,000		

^a Above gage height 4.80 this table is the same as the 1899 table.^b Above gage height 3.00 feet the rating curve is a tangent, the difference being 120 per tenth.

SAVANNAH DRAINAGE BASIN, STREAM FLOW

Estimated monthly discharge of Tugaloo River near Madison, S. C.

[Drainage area, 593 square miles.]

Month	Discharge in second-feet			Run-off	
	Maximum	Minimum	Mean	Sec.-ft. per sq. mile	Depth in inches
1898					
July 19-31.....	2,835	975	1,824	3.08	1.49
August.....	6,982	1,200	3,354	5.66	6.52
September.....	13,658	1,807	3,771	6.96	7.10
October.....	13,516	1,620	4,238	7.15	8.24
November.....	4,257	1,874	2,267	3.82	4.26
December.....	5,442	1,560	2,159	3.64	4.20
1899					
January.....	4,020	1,634	2,099	3.54	4.08
February.....	9,020	1,889	3,790	6.37	6.63
March.....	11,780	2,310	4,771	8.05	9.28
April.....	5,820	2,310	3,276	5.52	6.16
May.....	2,710	1,430	1,881	3.17	3.66
June.....	3,100	1,073	1,448	2.44	2.72
July.....	2,310	716	1,027	1.78	1.99
August.....	4,060	563	801	1.85	1.56
September.....	1,838	512	765	1.29	1.44
October.....	1,838	512	662	1.12	1.29
November.....	1,481	512	619	1.04	1.16
December.....	8,700	563	1,411	2.88	2.74
The year.....	11,780	512	1,879	3.17	42.71
1900					
January.....	4,380	705	1,223	2.06	2.38
February.....	14,820	845	2,508	4.23	4.40
March.....	6,380	1,745	2,505	4.22	4.86
April.....	9,580	1,475	2,751	4.64	5.17
May.....	2,300	1,135	1,562	2.63	3.04
June.....	9,260	1,135	2,931	4.94	5.51
July.....	3,340	1,325	1,834	3.18	3.66
August.....	1,525	880	1,095	1.85	2.13
September.....	5,340	775	1,305	2.20	2.45
October.....	4,780	775	1,290	2.18	2.52
November.....	6,880	880	1,322	2.23	2.49
December.....	3,340	1,000	1,491	2.51	2.90
The year.....	14,820	705	1,822	3.07	41.51
1901					
January.....	8,780	1,180	2,153	3.63	4.19
February.....	4,380	1,180	1,719	2.90	3.02
March.....	15,540	1,135	2,444	4.12	4.75
April.....	16,460	2,060	3,804	6.42	7.16
May.....	12,540	1,475	2,932	4.95	5.71
June.....	6,140	1,475	2,549	4.30	4.80
July.....	2,300	1,180	1,570	2.65	3.06
August.....	13,660	1,045	4,876	8.22	9.48
September.....	6,620	1,360	3,047	5.14	5.74
October.....	2,060	1,225	1,542	2.60	3.00
November.....	1,225	960	1,091	1.84	2.05
December.....	14,360	960	2,577	4.35	5.01
The year.....	16,460	960	2,525	4.26	57.97
1903					
July 7-31.....	2,320	1,032	1,441	2.43	2.26
August.....	3,040	732	1,233	2.16	2.49
September.....	3,200	596	874	1.47	1.64
October.....	923	552	634	1.07	1.23
November.....	1,250	552	720	1.21	1.35
December.....	980	510	623	1.05	1.21
1904					
January.....	3,340	528	829	1.40	1.61
February.....	7,325	607	1,304	2.20	2.37
March.....	14,450	822	2,100	3.54	4.08
April.....	3,460	1,062	1,369	2.31	2.58
May.....	3,840	800	1,259	2.12	2.44
June.....	1,519	648	880	1.48	1.65
July.....	1,742	509	682	1.15	1.33
August.....	4,340	712	1,543	2.60	3.00
September.....	1,231	528	717	1.21	1.35
October.....	528	435	469	.791	.912
November.....	777	452	539	.909	1.01
December.....	4,340	490	830	1.40	1.61
The year.....	14,450	435	1,043	1.76	23.94

WATER POWERS OF GEORGIA

Estimated monthly discharge of Tugaloo River near Malison, S. C.—Continued.

Month	Discharge in second-feet			Run-off	
	Maximum	Minimum	Mean	Sec.-ft. per sq. mile	Depth in inches
1905					
January.....	10,220	520	1,442	2.43	2.80
February.....	7,460	630	2,494	4.21	4.38
March.....	2,680	1,095	1,466	2.47	2.85
April.....	1,755	898	1,107	1.87	2.09
May.....	4,160	1,155	2,087	3.52	4.06
June.....	14,060	870	1,572	2.65	2.96
July.....	21,860	1,405	4,025	6.79	7.86
August.....	4,860	1,095	1,986	3.35	3.86
September.....	1,610	725	942	1.59	1.77
October.....	5,000	725	996	1.68	1.94
November.....	845	640	704	1.19	1.33
December.....	11,180	640	2,414	4.07	4.69
The year.....	21,860	520	1,770	2.98	40.56
1906					
January.....	72,000	9,140	23,400	3.55	4.09
February.....	13,800	7,540	10,300	1.56	1.62
March.....	59,500	7,230	18,900	2.86	3.30
April.....	13,900	7,080	10,500	1.59	1.77
May.....	16,500	5,760	8,210	1.24	1.43
June.....	38,200	5,220	12,600	1.91	2.13
July.....	33,000	5,760	16,100	2.44	2.81
August.....	26,100	8,170	14,400	2.18	2.51
September.....	39,200	8,170	16,500	2.50	2.79
October.....	43,100	8,490	16,000	2.42	2.79
November.....	20,100	7,540	9,030	1.37	1.53
December.....	13,100	7,230	9,780	1.48	1.71
The year.....	72,000	5,220	13,800	2.09	2.848

NOTE.—Values for 1905 and 1906 are excellent.

SAVANNAH RIVER NEAR CALHOUN FALLS, SOUTH CAROLINA.

Systematic measurements were begun at this point August 4, 1896. The station is located at the Seaboard Air Line Railroad bridge, 3 miles west of Calhoun Falls, South Carolina, above the mouth of Beaver Dam Creek, at the head of Trotters Shoal, and about one-fourth mile below the mouth of Rocky River. The observer is Peter J. Pfeiffer, who reads the gage once daily. The station is also used by the United States Weather Bureau, which pays the gage reader.

The river is divided into two channels by a large island containing several hundred acres. Both channels are slightly curved for about 2,000 feet above the bridge and are straight for about 500 feet below. The west channel, which is the main river, is sluggish only at low water. It has a rough and rocky bed and in places the current is irregular.

The east channel is a good section, but has a low velocity. The right bank of the west channel and the left bank of the east channel are high and wooded and are not liable to overflow. The island between the channels is nearly covered at extreme high water. At low water the east channel is 150 feet wide and from 3 to 4 feet deep. The main channel is about 400 feet wide and from 2 to 8 feet deep.

Discharge measurements are made from the upstream side of the railroad bridge, to which the gage is attached. This bridge consists of one short span 175 feet in length across the east channel and three spans of 155 feet each across the west, or main channel. These two sections are connected by 875 feet of a wooden trestle, from 35 to 45 feet high, which crosses the island between the two channels. The base of the rail is about 54 feet above low water. The initial point for soundings is the left-bank end of the iron bridge on the up-stream side. A separate initial point has been used for each channel, the description being the same in both cases.

The chain gage is bolted to the downstream guard rail, 185 feet from the initial point for soundings. The length of the chain from the index to the end of weight is 57.10 feet.

Bench mark No. 1 is the top of the iron girder under the cross-ties of the downstream side of the bridge at a point 40 feet west of the second pier from the east end of the bridge; elevation, 54 feet above the gage datum. Bench mark No. 3 is a copper plug set in solid rock on the east bank of the east channel, 15 feet from the edge of the water and 110 feet upstream from the center of the railroad track; elevation, 14.38 feet above gage datum. The station was discontinued December 31, 1903.

Gage heights and monthly estimates of flow for 1901 and 1902, previously published for this station, are considered unreliable and hence are not republished in this paper.

WATER POWERS OF GEORGIA

Discharge measurements of Savannah River near Calhoun Falls, S. C.

Date	Gage height	Dis-charge	Date	Gage height	Dis-charge
1896			1900		
August 4.....	<i>Feet</i> 2.40	<i>Sec.-ft.</i> 2,668	March 1.....	<i>Feet</i> 5.47	<i>Sec.-ft.</i> 13,800
September 22.....	1.77	1,531	1901		
October 31.....	2.10	2,054	January 21.....	3.15	5,331
1897			April 25.....	4.60	10,430
January 20.....	2.90	4,204	August 13.....	4.55	10,840
April 28.....	3.21	6,446	1902		
June 12.....	2.80	4,469	July 19.....	2.50	2,517
September 29.....	1.90	1,693	October 1.....	3.45	6,844
November 3.....	2.92	3,812	1903		
1898			March 20.....	4.15	9,769
April 16.....	2.75	4,081	May 7.....	3.60	7,103
1899			June 10.....	4.75	10,900
March 4.....	4.77	12,080	August 13.....	2.80	3,823
May 16.....	3.45	5,258	September 15.....	2.52	3,209
September 28.....	2.30	2,057	October 28.....	2.33	2,534
November 10.....	2.25	2,039	December 8.....	2.12	2,098

Daily gage height, in feet, of Savannah River near Calhoun Falls, S. C.

Day	Aug.	Sept.	Oct.	Nov.	Dec.	Day	Aug.	Sept.	Oct.	Nov.	Dec.
1896						1896					
1.....		2.0	2.0	2.2	5.6	17.....	2.1	2.0	1.95	3.0	3.4
2.....		1.9	1.95	2.15	5.0	18.....	2.05	1.95	1.9	2.9	3.1
3.....		1.85	1.9	2.05	4.95	19.....	2.05	1.9	1.85	2.65	3.0
4.....	2.4	1.8	1.95	3.0	5.15	20.....	2.0	1.85	1.8	2.4	2.85
5.....	2.3	1.95	1.9	5.65	5.0	21.....	1.9	1.8	1.8	2.25	2.8
6.....	2.15	3.85	1.85	7.15	4.05	22.....	1.85	1.7	1.75	2.35	2.75
7.....	2.1	3.0	1.9	4.75	3.5	23.....	1.8	2.5	1.75	2.3	2.65
8.....	2.0	2.4	1.75	3.0	3.75	24.....	1.75	2.4	2.15	2.3	2.6
9.....	2.05	2.4	1.7	2.6	3.05	25.....	1.75	2.35	2.05	2.3	2.55
10.....	2.1	2.25	1.7	2.45	3.2	26.....	2.0	2.25	2.0	2.25	2.5
11.....	2.05	2.2	2.0	2.3	2.35	27.....	2.45	2.0	1.95	2.25	2.45
12.....	2.0	2.3	2.25	2.2	2.6	28.....	2.0	1.9	1.9	2.2	2.4
13.....	1.95	2.15	2.5	5.6	2.45	29.....	1.95	1.95	1.85	2.3	2.4
14.....	2.8	2.1	2.4	4.1	2.55	30.....	1.0	2.0	1.95	2.95	2.4
15.....	3.1	2.05	2.15	3.6	3.85	31.....	1.85		2.1		2.35
16.....	2.3	2.0	2.0	3.25	3.2						

SAVANNAH DRAINAGE BASIN, STREAM FLOW

Daily gage height, in feet, of Savannah River near Calhoun Falls, S. C.—Contin'd.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1897												
1.....	2.5	2.8	3.0	5.4	3.8	2.2	2.8	2.5	2.2	1.8	2.55	2.8
2.....	2.4	5.2	2.95	6.9	5.65	2.15	2.65	2.4	2.4	1.8	3.4	2.7
3.....	2.4	4.0	2.8	5.2	4.3	3.05	2.55	2.35	2.3	1.85	3.05	2.85
4.....	2.4	3.6	2.8	4.75	3.95	4.4	2.4	2.25	2.25	1.85	2.7	3.0
5.....	2.35	3.25	2.75	11.65	3.85	4.1	2.3	2.1	2.05	1.8	2.5	2.9
6.....	2.35	6.0	2.65	13.35	3.8	3.1	3.05	2.65	2.0	1.75	2.45	2.75
7.....	2.3	8.55	6.8	8.15	3.7	2.95	2.5	2.95	1.95	1.75	2.35	2.7
8.....	2.25	7.2	4.65	4.95	3.65	3.05	2.4	2.9	1.95	1.7	2.25	2.6
9.....	2.25	5.05	4.2	4.05	3.4	3.25	2.65	2.7	1.9	1.65	2.2	2.55
10.....	2.25	4.1	4.0	4.0	3.25	3.05	2.45	2.6	1.85	1.75	2.2	2.55
11.....	2.2	3.85	4.4	4.15	3.15	2.95	2.5	2.4	1.8	2.25	2.15	2.5
12.....	2.2	5.15	5.5	4.1	3.05	2.3	2.55	2.3	1.8	2.65	2.1	2.4
13.....	2.3	4.4	7.75	4.0	3.0	3.0	3.25	2.25	1.85	2.4	2.1	2.35
14.....	3.05	4.1	7.25	3.95	3.05	2.85	2.65	2.2	1.8	2.25	2.05	2.95
15.....	2.75	4.0	6.0	3.95	3.1	2.3	2.55	2.15	1.8	2.2	2.0	2.8
16.....	2.6	4.05	5.2	3.85	3.15	3.0	2.45	2.2	1.75	2.15	2.0	2.7
17.....	2.55	3.95	4.15	3.8	3.1	3.05	2.5	2.25	1.75	2.1	2.05	2.65
18.....	3.35	3.8	3.85	3.75	3.05	2.95	3.9	2.2	1.7	2.15	2.0	2.55
19.....	3.1	3.65	3.5	3.65	3.0	2.85	3.3	2.3	1.7	2.4	2.0	2.5
20.....	2.9	3.7	4.0	3.5	2.95	2.3	3.1	2.25	1.75	3.05	1.95	2.45
21.....	5.4	3.5	5.35	3.4	2.9	2.7	4.05	2.2	1.75	2.6	1.95	2.5
22.....	3.95	3.35	4.4	3.35	2.9	2.65	3.45	2.7	1.85	2.4	1.9	2.65
23.....	3.6	4.05	4.1	3.3	2.85	2.55	3.0	2.6	2.75	2.35	1.9	2.6
24.....	3.2	3.8	4.0	3.25	2.75	2.55	2.75	2.4	2.25	2.3	1.85	2.55
25.....	3.1	4.0	3.9	3.25	2.7	2.45	2.65	2.3	2.05	2.25	1.85	2.5
26.....	3.0	3.9	3.65	3.3	2.6	2.5	2.95	2.25	2.0	2.3	2.0	2.9
27.....	2.95	3.45	3.05	3.25	2.55	2.4	3.5	2.2	2.0	2.25	3.25	2.4
28.....	2.95	3.2	3.4	3.2	2.4	2.3	3.0	2.15	1.95	2.2	3.05	2.4
29.....	2.9	3.25	3.25	2.35	3.5	2.9	2.1	1.9	2.2	2.95	2.35
30.....	2.9	3.25	3.4	2.25	2.95	2.7	2.0	1.85	2.15	2.85	2.35
31.....	2.75	3.3	2.2	2.55	2.05	2.1	2.3
1898												
1.....	2.3	3.25	2.3	4.6	2.65	1.8	1.75	3.2
2.....	2.3	3.1	2.35	3.4	2.75	1.8	1.7	3.0
3.....	2.25	3.0	2.45	3.25	2.8	1.8	1.65	3.6
4.....	2.25	2.9	2.8	3.0	2.8	1.75	1.6	3.0
5.....	2.2	2.85	3.0	4.45	2.75	1.95	1.9	2.75
6.....	2.4	2.8	2.8	4.0	2.7	2.05	2.45	2.5
7.....	2.35	2.75	2.65	3.8	2.6	2.0	2.75	5.05
8.....	2.3	2.65	2.6	3.55	2.55	1.95	3.95	4.4
9.....	2.25	2.6	2.5	3.2	2.5	1.85	3.05	3.25
10.....	2.25	2.6	2.45	3.0	2.5	1.8	2.6
11.....	2.2	2.55	2.35	3.15	2.4	1.75	2.45
12.....	2.2	2.6	2.25	3.05	2.25	1.75	2.3
13.....	2.15	2.5	2.2	3.0	2.15	1.95	2.5
14.....	2.15	2.5	2.25	3.0	2.0	1.9	4.9
15.....	2.2	2.45	2.5	2.9	2.2	1.9	5.05
16.....	2.4	2.4	2.4	2.7	2.1	1.95	3.95
17.....	2.35	2.35	2.45	2.65	2.05	2.0	3.6
18.....	2.35	2.3	2.35	2.55	2.0	2.05	3.4
19.....	2.45	2.3	2.3	2.5	2.05	2.25	3.25
20.....	2.35	2.3	2.3	2.65	2.0	2.35	3.0
21.....	2.7	2.35	2.3	2.5	1.9	2.05	2.85
22.....	2.65	2.3	2.25	2.45	2.0	2.0	2.5
23.....	2.9	2.3	2.2	2.35	1.95	1.95	2.75
24.....	2.35	2.25	2.25	2.75	1.95	1.9	4.0
25.....	3.65	2.25	2.25	3.0	1.9	1.85	4.5
26.....	5.5	2.25	2.2	2.85	1.85	1.9	4.05
27.....	4.65	2.35	2.2	3.05	1.85	1.85	3.85
28.....	4.05	2.4	2.25	2.9	1.8	1.8	4.0
29.....	3.85	2.3	2.8	1.8	1.8	3.75
30.....	3.6	3.9	2.7	1.85	1.8	3.9
31.....	3.45	6.75	1.8	3.65

a Discontinued August 9, 1898, and reestablished March 4, 1899.

Daily gage height, in feet, of Savannah River near Calhoun Falls, S. C.—Contin'd.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1899												
1				6.6	4.0	3.3	3.2	3.3	3.0	2.2	2.6	2.7
2				5.0	3.9	3.2	3.0	3.1	2.9	2.1	2.5	2.8
3				4.85	3.8	3.2	2.9	3.0	2.9	2.1	2.5	2.9
4			4.75	4.9	3.8	3.2	2.7	2.9	2.8	2.2	2.4	2.7
5			4.95	4.75	3.7	3.1	2.7	2.8	2.7	2.4	2.4	2.6
6			4.65	4.7	3.9	3.0	2.6	2.7	2.9	3.0	2.4	2.6
7			4.4	4.75	3.9	2.9	2.7	2.6	2.9	2.8	2.5	2.6
8			4.35	4.65	3.8	3.0	2.7	2.6	3.0	3.9	2.4	2.5
9			4.25	5.6	3.8	3.3	3.0	3.0	3.0	3.5	2.3	2.5
10			4.2	5.1	3.7	3.2	2.9	2.9	2.9	3.2	2.2	2.4
11			4.05	4.95	3.7	3.4	2.8	2.8	3.2	3.0	2.2	2.5
12			3.9	4.8	3.7	3.5	2.8	2.8	3.0	2.7	2.1	4.9
13			4.0	4.7	3.6	5.0	2.7	2.7	3.0	2.5	2.1	5.0
14			4.0	4.5	3.6	3.9	2.6	2.7	2.9	2.4	2.0	3.8
15			5.25	4.3	3.5	3.7	2.5	2.6	2.9	2.3	2.1	3.5
16			13.6	4.0	3.4	3.6	2.4	2.6	2.8	2.4	2.1	3.3
17			9.0	3.9	3.4	3.6	2.4	2.6	2.7	2.4	2.1	3.1
18			6.9	3.7	3.4	3.5	2.3	2.6	2.6	2.3	2.0	3.0
19			7.0	3.7	3.5	3.3	2.4	2.5	2.6	2.3	2.0	3.0
20			9.9	3.5	3.5	3.2	2.3	2.5	2.9	2.4	2.0	2.9
21			7.05	3.4	3.4	3.1	2.2	2.6	2.9	2.3	2.1	2.9
22			5.0	3.2	3.5	3.0	2.3	2.8	2.8	2.3	2.1	2.8
23			5.0	3.0	3.7	3.0	2.3	3.0	2.6	2.3	2.3	2.7
24			4.9	2.9	3.55	2.9	2.3	2.9	2.5	2.2	2.3	3.9
25			5.0	4.0	3.5	2.9	2.4	2.7	2.4	2.2	2.4	3.8
26			5.1	4.6	3.4	3.0	2.7	2.7	2.6	2.2	4.0	3.5
27			4.95	5.1	3.25	3.9	2.7	2.8	2.4	2.1	3.4	3.5
28			4.85	5.0	3.2	4.0	5.0	3.0	2.3	2.1	3.2	3.6
29			6.95	4.7	3.2	3.6	3.5	2.9	2.3	2.2	2.9	3.7
30			5.1	4.1	3.1	3.3	3.6	3.5	2.2	2.3	2.8	3.6
31			7.0		3.3		3.4	3.2		2.5		2.9
1900												
1	3.3	2.9	5.3	3.6	4.0	2.8	3.6	3.2	3.2	2.1	2.9	3.0
2	3.2	2.8	6.5	3.5	3.9	2.7	3.2	3.0	3.7	2.0	3.0	2.9
3	3.2	2.8	4.6	3.5	4.2	3.1	3.0	3.0	3.3	2.0	3.9	2.8
4	3.1	2.7	4.2	3.7	4.0	2.9	3.0	2.9	3.0	2.1	4.3	3.9
5	3.0	2.8	3.9	3.6	3.9	3.5	2.9	2.9	3.0	2.1	4.0	3.8
6	3.0	2.8	3.8	3.4	3.7	3.4	2.9	2.8	2.9	3.0	3.8	3.8
7	2.9	2.9	3.6	3.3	3.6	3.9	2.8	2.8	2.8	2.7	3.7	3.7
8	2.9	2.9	4.0	3.4	3.4	11.0	2.7	2.7	2.6	2.6	3.4	3.6
9	2.9	3.0	4.9	3.4	3.3	5.0	2.7	2.6	2.5	2.5	3.3	3.4
10	3.0	3.2	4.3	3.3	3.1	3.5	2.6	2.4	2.3	2.4	3.2	3.4
11	3.2	5.2	3.9	3.6	3.1	3.0	2.5	2.3	2.2	2.4	3.2	3.3
12	4.0	9.3	3.8	4.0	3.0	3.0	2.4	2.2	2.1	2.6	3.0	3.3
13	3.9	15.5	3.6	3.8	3.0	3.1	2.4	2.7	2.0	3.9	2.9	3.4
14	3.7	19.4	3.4	3.6	3.0	3.0	2.5	2.6	2.0	3.0	2.7	3.7
15	3.6	8.0	3.3	3.6	2.9	3.0	2.4	2.5	4.7	2.9	2.7	3.6
16	3.5	5.5	4.6	3.5	2.9	3.3	2.3	2.5	6.9	2.8	2.6	3.4
17	3.3	4.9	4.5	3.5	2.9	5.6	2.2	2.6	5.0	2.6	2.6	3.4
18	3.3	4.7	4.0	3.9	2.8	6.1	2.2	2.6	3.2	2.5	2.6	3.3
19	3.4	4.4	3.8	5.0	3.0	4.9	2.1	2.4	3.0	2.5	2.6	3.3
20	3.9	4.3	4.2	5.1	3.0	4.0	2.1	2.3	2.9	2.4	3.0	3.6
21	3.8	4.2	4.0	8.0	2.9	3.7	2.1	2.2	2.9	2.4	2.9	3.7
22	3.6	5.4	3.9	10.4	2.9	3.6	2.0	2.0	2.7	2.4	2.8	3.5
23	3.5	4.7	3.8	5.5	3.0	4.0	2.2	2.0	2.7	2.5	2.8	3.4
24	3.4	4.4	4.0	6.9	4.9	12.7	2.3	1.9	2.6	5.0	2.6	3.4
25	3.2	4.2	5.6	6.0	4.2	12.0	2.2	2.5	2.4	4.0	2.6	3.3
26	3.2	4.0	5.7	4.9	3.2	7.8	2.2	2.9	2.4	3.9	3.6	3.3
27	3.1	3.9	5.0	4.2	3.0	5.0	2.3	2.7	2.2	3.7	3.4	3.3
28	3.0	3.9	4.8	4.0	3.0	4.5	3.4	2.9	2.0	3.5	3.2	3.2
29	3.0		4.2	4.2	2.9	3.9	3.2	2.3	2.0	3.3	3.1	3.2
30	3.0		3.9	4.0	2.9	3.8	3.4	2.2	2.1	3.1	3.0	3.3
31	2.9		3.7		2.8		3.1	2.1		2.9		3.3
1903												
1	4.0	4.2	10.4	5.2	3.8	3.6	3.5	3.1	2.9	2.6	2.3	2.0
2	4.0	3.8	7.1	4.5	3.7	5.5	3.5	3.0	2.8	2.5	2.2	2.1
3	4.4	3.9	4.9	4.0	3.7	4.4	3.6	3.0	2.8	2.5	2.2	2.1
4	4.4	6.3	4.4	3.9	4.0	4.6	3.9	3.1	2.8	2.4	2.3	2.2
5	4.2	3.1	4.2	4.0	3.9	4.8	3.7	3.2	2.7	2.4	2.6	2.2

Daily gage height, in feet, of Savannah River near Calhoun Falls, S. C.—Contin'd.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1908												
6.....	4.1	6.4	4.1	3.9	3.7	7.0	3.8	3.4	2.7	2.4	2.5	2.3
7.....	4.1	5.9	4.1	3.9	3.6	15.3	4.8	3.2	2.6	2.5	2.3	2.2
8.....	4.0	12.7	4.0	4.0	3.5	8.0	4.0	3.1	2.6	2.5	2.2	2.2
9.....	3.9	9.4	4.3	5.9	3.5	4.9	4.1	3.0	2.5	2.7	2.2	2.2
10.....	3.9	5.3	4.2	4.5	3.5	4.0	3.9	3.0	3.0	2.6	2.2	2.3
11.....	4.1	7.3	4.0	4.1	3.4	3.5	4.0	3.1	2.9	2.6	2.1	2.2
12.....	4.4	11.2	6.3	4.0	3.4	4.0	4.1	3.2	2.8	2.5	2.1	2.2
13.....	4.3	6.4	5.9	5.1	3.3	3.8	4.0	3.3	2.6	2.5	2.2	2.3
14.....	4.1	4.6	4.6	12.9	3.3	3.7	4.2	3.4	2.7	2.4	2.2	2.2
15.....	3.9	4.4	4.4	9.5	3.4	3.6	4.0	3.2	3.4	2.4	2.1	2.2
16.....	3.8	5.3	4.4	5.0	3.5	3.5	3.8	3.1	4.2	2.5	2.1	2.1
17.....	3.7	9.5	4.3	5.4	3.4	3.5	3.7	3.5	4.0	2.6	2.1	2.1
18.....	3.6	8.4	4.2	5.0	3.3	3.4	3.5	5.5	3.5	3.0	2.2	2.2
19.....	3.6	6.6	4.2	5.0	3.4	3.2	3.3	6.9	3.2	2.3	2.2	2.2
20.....	3.6	5.4	4.3	4.9	3.4	3.0	3.2	4.5	3.0	2.6	2.7	2.3
21.....	3.6	4.9	4.5	4.9	3.3	3.2	3.1	4.0	3.0	2.5	2.4	2.4
22.....	3.7	4.5	5.9	4.3	3.3	3.1	3.0	3.7	2.9	2.4	2.3	2.3
23.....	3.6	4.3	11.1	4.7	3.2	3.0	3.0	3.3	2.9	2.4	2.2	2.2
24.....	3.5	4.1	14.5	4.5	3.2	3.1	3.1	3.1	2.8	2.3	2.2	2.2
25.....	3.3	4.0	8.7	4.3	3.1	3.0	2.9	3.1	2.8	2.2	2.1	2.2
26.....	3.2	3.7	6.9	4.0	3.0	3.0	2.9	3.0	2.3	2.2	2.1	2.1
27.....	3.1	3.8	4.7	3.9	3.0	3.2	2.9	3.0	2.7	2.1	2.0	2.2
28.....	3.3	7.0	4.4	3.9	3.1	3.5	2.3	2.9	2.7	2.2	2.0	2.2
29.....	3.4	4.9	3.8	3.1	4.0	2.3	2.9	2.7	2.1	2.0	2.2
30.....	4.3	9.1	3.8	3.4	3.6	2.9	3.0	2.6	2.1	2.0	2.1
31.....	3.3	7.5	3.5	3.0	2.9	2.3	2.1

Rating tables for Savannah River, near Calhoun Falls, S. C.

AUGUST 4 TO NOVEMBER 28, 1896.^a

Gage height	Dis-charge						
<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>
1.75	1,460	2.00	1,850	2.30	2,450	2.60	3,060
1.80	1,575	2.10	2,050	2.40	2,670	2.70	3,280
1.90	1,700	2.20	2,250	2.50	2,870	2.80	3,500

NOVEMBER 29, 1896, TO DECEMBER 31, 1898.^b

1.60	1,350	2.60	3,240	3.50	7,500	4.40	12,000
1.70	1,450	2.70	3,590	3.60	8,000	4.50	12,500
1.80	1,580	2.80	4,000	3.70	8,500	4.60	13,000
1.90	1,720	2.90	4,500	3.80	9,000	4.70	13,500
2.00	1,875	3.00	5,000	3.90	9,500	4.80	14,000
2.10	2,045	3.10	5,500	4.00	10,000	4.90	14,500
2.20	2,235	3.20	6,000	4.10	10,500	5.00	15,000
2.30	2,445	3.30	6,500	4.20	11,000	6.00	20,000
2.40	2,680	3.40	7,000	4.30	11,500	7.00	25,000
2.50	2,940						

^a Above gage height 2.30 feet the following rating table (Nov. 29, 1896, to Dec. 31, 1898) should be used.
^b Above gage height 2.80 feet the rating curve is a tangent, the difference being 500 per tenth.

WATER POWERS OF GEORGIA

Rating table for Savannah River, near Calhoun Falls, S. C.—Continued.

JANUARY 1 TO DECEMBER 31, 1899.^a

Gage height	Dis-charge						
<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>
2.00	1,830	3.10	3,790	4.40	9,476	7.50	23,240
2.10	1,910	3.20	4,160	4.60	10,364	8.00	25,460
2.20	1,990	3.30	4,598	4.80	11,552	8.50	27,680
2.30	2,090	3.40	5,086	5.00	12,140	9.00	29,900
2.40	2,190	3.50	5,480	5.20	13,028	9.50	32,120
2.50	2,340	3.60	5,924	5.40	13,916	10.00	34,340
2.60	2,490	3.70	6,768	5.60	14,840	10.50	36,560
2.70	2,680	3.80	6,812	5.80	15,692	11.00	38,780
2.80	2,870	3.90	7,256	6.00	16,580	12.00	43,220
2.90	3,145	4.00	7,700	6.50	18,800	13.00	47,660
3.00	3,420	4.20	8,588	7.00	21,020	14.00	52,100

^a Above gage height 3.40 feet the rating curve is a tangent, the difference being 444 per tenth.JANUARY 1 TO DECEMBER 31, 1900.^a

1.40	1,175	2.90	3,500	4.40	9,990	8.00	25,650
1.50	1,260	3.00	3,900	4.50	10,425	8.50	27,825
1.60	1,350	3.10	4,335	4.60	10,860	9.00	30,000
1.70	1,445	3.20	4,770	4.70	11,295	9.50	32,175
1.80	1,545	3.30	5,205	4.80	11,735	10.00	34,350
1.90	1,650	3.40	5,640	4.90	12,165	11.00	38,700
2.00	1,760	3.50	6,075	5.00	12,600	12.00	43,050
2.10	1,870	3.60	6,510	5.20	13,470	13.00	47,400
2.20	1,990	3.70	6,945	5.40	14,340	14.00	51,750
2.30	2,120	3.80	7,380	5.60	15,210	15.00	56,100
2.40	2,280	3.90	7,815	5.80	16,080	16.00	60,450
2.50	2,470	4.00	8,250	6.00	16,950	17.00	64,800
2.60	2,690	4.10	8,685	6.50	19,125	18.00	69,150
2.70	2,910	4.20	9,120	7.00	21,300	20.00	77,850
2.80	3,150	4.30	9,555	7.50	23,475		

^a Above gage height 3.00 feet the rating curve is a tangent, the difference being 435 per tenth.JANUARY 1 TO DECEMBER 31, 1903.^a

2.00	1,870	2.80	3,930	3.60	6,910	4.40	10,060
2.10	2,050	2.90	4,230	3.70	7,300	4.50	10,470
2.20	2,250	3.00	4,640	3.80	7,690	4.60	10,880
2.30	2,470	3.10	5,000	3.90	8,080	4.70	11,310
2.40	2,710	3.20	5,390	4.00	8,470	4.80	11,740
2.50	2,980	3.30	5,770	4.10	8,860	4.90	12,170
2.60	3,280	3.40	6,150	4.20	9,260	5.00	12,600
2.70	3,600	3.50	6,530	4.30	9,660		

^a Above gage height 5.00 feet this table is the same as the 1900 table.

Estimated monthly discharge of Savannah River near Calhoun Falls, S. C.

[Drainage area, 2,712 square miles.]

Month	Discharge in second-feet			Run-off	
	Maximum	Minimum	Mean	Sec.-ft. per sq. mile	Depth in inches
1896					
August 4 to 31.....	5,500	1,525	2,126	0.78	0.81
September.....	9,250	1,460	2,360	.87	.97
October.....	2,870	1,460	1,821	.67	.77
November.....	26,000	1,950	5,644	2.08	2.32
December.....	18,000	2,560	6,468	2.38	2.75
1897					
January.....	17,000	2,235	4,456	1.64	1.89
February.....	32,750	4,000	11,366	4.19	4.86
March.....	28,750	3,420	10,950	4.04	4.66
April.....	56,750	6,000	13,342	4.92	5.49
May.....	18,000	2,235	6,010	2.22	2.56
June.....	12,000	2,140	4,698	1.73	1.93
July.....	10,250	2,445	4,307	1.59	1.83
August.....	4,750	1,875	2,654	.98	1.13
September.....	3,800	1,460	1,873	.69	.77
October.....	5,250	1,405	2,220	.82	.94
November.....	7,000	1,650	2,320	1.04	1.16
December.....	5,000	2,445	3,355	1.24	1.43
The year.....	56,750	1,405	5,671	2.09	28.15
1898					
January.....	17,500	2,140	4,500	1.66	1.91
February.....	6,250	2,340	3,231	1.19	1.24
March.....	23,750	2,235	3,638	1.34	1.54
April.....	13,000	2,560	5,396	1.99	2.22
May.....	4,000	1,580	2,399	.88	1.01
June.....	2,560	1,520	1,761	.65	.72
July.....	15,250	1,350	6,314	2.33	2.69
August 1 to 9.....	15,250	2,940	7,137	2.68	.88

WATER POWERS OF GEORGIA

Estimated monthly discharge of Savannah River, near Calhoun Falls, S. C.—Con.

Month	Discharge in second-feet			Run-off	
	Maximum	Minimum	Mean	Sec.-ft. per sq. mile	Depth in inches
1899					
March 4 to 31.....	50,324	7,256	15,185	5.60	5.83
April.....	19,244	3,120	9,632	3.55	3.96
May.....	7,700	3,770	5,798	2.14	2.47
June.....	12,140	3,120	4,922	1.81	2.02
July.....	12,140	1,990	3,184	1.17	1.35
August.....	5,480	2,330	3,031	1.12	1.29
September.....	4,160	1,990	2,870	1.06	1.18
October.....	7,256	1,910	2,549	.94	1.08
November.....	7,700	1,830	2,474	.91	1.01
December.....	12,140	2,190	4,484	1.63	1.88
1900					
January.....	8,250	3,500	3,961	1.46	1.68
February.....	75,240	2,910	13,362	4.93	5.14
March.....	19,125	5,205	9,485	3.50	4.04
April.....	36,090	5,205	10,043	3.70	4.13
May.....	12,165	3,150	5,235	1.93	2.23
June.....	46,095	2,910	11,427	4.21	4.69
July.....	6,510	1,760	3,019	1.11	1.23
August.....	4,770	1,660	2,700	1.00	1.15
September.....	20,865	1,760	4,230	1.56	1.74
October.....	12,600	1,760	3,819	1.41	1.63
November.....	9,555	2,690	4,531	1.87	1.86
December.....	7,815	3,150	5,659	2.09	2.41
The year.....	75,240	1,660	6,456	2.33	31.98
1903					
January.....	10,060	5,010	7,777	2.87	3.31
February.....	46,095	7,300	17,551	6.47	6.74
March.....	53,925	8,470	16,244	5.99	6.90
April.....	46,965	7,600	12,325	4.54	5.07
May.....	8,470	4,640	6,216	2.29	2.61
June.....	57,405	4,640	10,071	3.71	4.14
July.....	11,740	3,930	6,623	2.44	2.81
August.....	20,865	4,280	6,265	2.31	2.66
September.....	9,260	2,980	4,402	1.62	1.81
October.....	4,640	2,050	2,878	1.06	1.22
November.....	3,600	1,870	2,301	.85	.95
December.....	2,710	1,870	2,170	.80	.92
The year.....	57,405	1,870	7,902	2.91	39.17

SAVANNAH RIVER AT WOODLAWN, SOUTH CAROLINA

This station was established November 9, 1905, by M. R. Hall. It is located at the Charleston and Western Carolina Railway bridge, 1,000 feet from the depot at Woodlawn, South Carolina, 17 miles above Augusta, Georgia, and 10 miles above the Augusta water-power dam.

The flow is almost natural at this point, being affected very slightly by stored water, mostly from Seneca River. The river is divided by a low island into two channels. The east channel is the main part of the river, as there is very little water flowing in the west channel at ordinary stages and probably none at the lowest stage. The channel is practically straight at the station. The left

bank is high and will not overflow except under the short trestle approach. The island and the bank for a short distance west of the west channel will overflow. The current is swift and is good in the greater part of the section at low water, but at places it is broken and irregular or is sloping with the direction of the section. The bed of the stream is mostly rock, the considerable roughness of which causes the irregularities in the current above mentioned. Careful measurements should give good results at this station.

Discharge measurements are made from the upstream side of the railroad bridge, which is in four spans over the east channel and a single span over the west channel. Across the island between the two channels there is about 900 feet of wooden trestle.

The gage is a boxed chain gage, attached to the upstream end of the second floor beam from the left end of the bridge. The length of the chain is 39 feet. It is read twice each day by M. A. Palmore. The bench mark is the top of the upstream end of the second floor beam from the left end of the bridge; elevation, 37.00 feet above the datum of the gage.

Discharge measurements of Savannah River at Woodlawn, S. C., in 1905-6.

Date	Gage height	Dis-charge
1905	<i>Feet</i>	<i>Sec.-ft.</i>
November 9.....	3.49	3,220
November 21.....	3.31	3,060
1906		
March 6.....	5.52	8,940
March 7.....	5.30	8,400
April 26.....	5.04	7,680
June 29.....	4.52	6,150
August 21.....	3.65	21,200
October 30.....	5.30	8,540

Daily gage height, in feet, of Savannah River at Woodlawn, S. C.

Day	Nov.	Dec.	Day	Nov.	Dec.	Day	Nov.	Dec.
1905			1905			1905		
1.....		3.65	12.....	4.1	6.9	22.....	4.0	14.0
2.....		3.6	13.....	3.8	5.6	23.....	3.75	9.8
3.....		5.9	14.....	3.45	5.4	24.....	3.55	7.3
4.....		12.1	15.....	3.55	5.8	25.....	3.	6.3
5.....		9.2	16.....	3.5	6.2	26.....	3.6	5.8
6.....		6.2	17.....	3.45	5.9	27.....	3.6	5.4
7.....		5.0	18.....	3.45	5.3	28.....	3.7	5.4
8.....		4.6	19.....	3.5	5.0	29.....	3.75	7.3
9.....	3.55	5.4	20.....	3.3	7.2	30.....	3.7	7.3
10.....	3.55	11.6	21.....	3.4	15.5	31.....		6.2
11.....	4.1	9.4						

WATER POWERS OF GEORGIA


Daily gage height, in feet, of Savannah River at Woodlawn, S. C., for 1906.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1	6.0	6.8	5.0	8.1	5.25	4.6	4.4	9.7	9.2	10.8	5.8	5.1
2	5.6	6.4	4.9	7.0	5.2	4.2	6.2	8.4	7.2	9.4	5.2	5.0
3	5.8	6.2	4.95	6.6	5.05	4.5	5.6	8.1	6.4	10.6	5.2	5.05
4	16.5	6.1	5.1	6.2	5.2	5.65	6.4	7.4	6.0	13.4	5.2	5.05
5	18.6	5.9	6.5	6.0	5.5	6.7	7.6	7.4	6.3	12.1	5.2	4.9
6	12.6	5.7	5.6	5.95	5.4	5.6	5.8	6.8	7.0	9.8	5.15	4.9
7	8.0	5.8	5.3	5.8	6.3	5.05	5.0	6.1	6.3	9.2	5.1	5.1
8	6.8	6.0	5.8	5.7	7.0	4.7	5.2	5.7	6.0	8.2	5.1	5.2
9	6.3	6.8	8.8	5.7	6.2	4.5	9.4	5.4	5.5	7.3	5.05	5.0
10	6.2	6.4	7.6	6.2	5.3	4.55	8.8	5.35	5.35	7.0	5.0	5.0
11	5.8	6.0	6.4	6.2	5.0	4.9	6.6	5.35	5.2	6.8	5.0	6.2
12	8.1	6.0	5.8	5.8	4.9	5.1	5.75	5.3	6.8	6.4	5.0	7.9
13	8.4	5.95	5.35	5.5	4.8	9.7	5.5	5.5	9.2	6.3	5.05	6.3
14	7.1	6.1	6.4	5.5	4.85	11.3	5.1	6.6	7.7	6.2	5.05	5.7
15	6.4	5.8	11.4	6.4	4.65	10.0	5.15	6.4	6.0	6.1	5.1	5.4
16	6.1	5.65	14.6	7.2	4.65	12.0	11.2	6.3	5.55	6.0	5.3	5.2
17	6.1	5.45	12.2	6.3	4.6	12.4	10.0	6.2	5.2	6.0	5.3	5.2
18	6.0	5.3	8.3	5.75	4.5	9.9	10.1	6.1	7.5	6.0	5.3	5.35
19	5.7	5.3	8.2	5.7	4.5	7.7	11.3	6.9	10.1	6.8	6.3	7.0
20	5.6	5.2	16.7	5.4	4.5	6.2	9.6	7.8	12.6	7.5	8.4	7.2
21	5.7	5.5	15.6	5.4	4.45	5.5	8.4	8.8	12.1	6.4	6.9	7.2
22	5.5	6.2	10.3	5.3	4.4	5.2	7.3	7.6	8.6	6.0	6.1	6.5
23	14.0	6.1	7.6	5.2	4.4	4.95	7.6	6.4	7.3	5.85	5.75	5.9
24	19.2	5.5	6.8	4.85	4.5	4.75	6.8	6.0	7.6	5.8	5.6	5.6
25	13.2	5.3	6.5	5.1	4.5	4.8	7.6	5.8	7.7	5.65	5.4	5.4
26	11.6	5.2	6.2	5.0	4.4	4.7	7.7	5.2	7.7	5.6	5.3	5.3
27	12.4	5.1	6.1	5.0	7.0	4.7	6.2	6.8	7.4	5.55	5.3	5.3
28	11.4	5.0	7.1	5.45	7.5	4.7	5.9	7.4	6.7	5.45	5.25	5.25
29	9.4	7.3	6.0	5.9	4.5	6.4	8.8	7.2	5.3	5.2	5.35
30	7.9	7.6	5.6	5.1	4.5	7.1	8.3	8.6	5.3	5.15	5.65
31	8.4	4.8	10.5	5.3	6.2

Rating table for Savannah River at Woodlawn, S. C., for 1905-6.

Gage height	Dis-charge						
<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>
3.00	2,440	4.40	5,760	5.80	10,160	8.40	20,120
3.10	2,640	4.50	6,040	5.90	10,510	8.60	20,940
3.20	2,850	4.60	6,330	6.00	10,860	8.80	21,760
3.30	3,060	4.70	6,630	6.20	11,560	9.00	22,600
3.40	3,280	4.80	6,930	6.40	12,280	10.00	27,000
3.50	3,500	4.90	7,230	6.60	13,010	11.00	31,600
3.60	3,730	5.00	7,540	6.80	13,760	12.00	36,300
3.70	3,960	5.10	7,850	7.00	14,520	13.00	41,100
3.80	4,200	5.20	8,170	7.20	15,300	14.00	46,000
3.90	4,450	5.30	8,490	7.40	16,080	15.00	51,000
4.00	4,700	5.40	8,810	7.60	16,880	16.00	56,000
4.10	4,960	5.50	9,140	7.80	17,680	17.00	61,000
4.20	5,220	5.60	9,480	8.00	18,480	18.00	66,000
4.30	5,490	5.70	9,820	8.20	19,300	19.00	71,000

NOTE.—The above table is based on seven discharge measurements made during 1905-6, and is well defined below gage height 8 feet. Above gage height 14 feet the rating curve is a tangent, the difference being 500 per tenth.



THE RAPIDS ON THE OCOEE RIVER NEAR THE GEORGIA-TENNESSEE STATE LINE. THE HAZINESS IN THE DISTANCE IS DUE TO SULPHUR FUMES FROM THE DUCKTOWN SMELTERS,



Monthly discharge for Savannah River at Woodlawn, S. C., for 1905-6.

[Drainage area, 6,600 square miles.]

Month	Discharge in second-feet			Run-off	
	Maximum	Minimum	Mean	Sec.-ft. per sq. mile	Depth in inches
1905					
November 9-30	4,930	3,060	3,820	0.579	0.47
December	53,500	3,730	15,900	2.41	2.73
1906					
January	72,000	9,140	23,400	3.55	4.09
February	13,800	7,540	10,300	1.56	1.62
March	59,500	7,230	18,900	2.86	3.30
April	18,900	7,080	10,500	1.59	1.77
May	16,500	5,760	8,210	1.24	1.43
June	38,200	5,220	12,600	1.91	2.13
July	33,000	5,760	16,100	2.44	2.81
August	26,100	8,170	14,400	2.18	2.51
September	39,200	8,170	16,500	2.50	2.79
October	43,100	8,490	16,000	2.42	2.79
November	20,100	7,540	9,030	1.37	1.53
December	18,100	7,230	9,730	1.48	1.71
The year	72,000	5,220	13,800	2.09	23.43

NOTE.—Values for 1905 and 1906 are excellent.

SAVANNAH RIVER AT AUGUSTA

Since 1875 observations of river heights have been maintained at this station by the city of Augusta at the city highway bridge. The United States Weather Bureau has published the results of observations from 1875 to 1905 in a volume entitled "Stages of Water at River Stations."

The channel is straight for a long distance above and below the bridge and is about 560 feet wide at low water. The banks are high, but will overflow at times under a part of the length of the approaches and, at very high stages, for a long distance on either side of the river beyond the ends of the bridge. The bed of the stream is sandy and undergoes considerable change. The current is swift.

Discharge measurements are made from the downstream side of the North Augusta bridge at Thirteenth street in the city of Augusta. This bridge consists of three spans, each 208 feet long, with 319 feet of wooden approach on the right bank and 259 feet on the left. The initial point for soundings is the end of the bridge at the right bank on the downstream side.

The gage, located at the Fifth Street Bridge, 1 mile below the

measuring station, is a vertical timber fastened to the first bridge pier which is in the water on the side of the pier near the upstream corner, facing the right bank. Readings are made four times each day by J. M. Youngblood, keeper of the city bridge, usually 6 a. m., 12 m., 6 p. m., and 9 p. m. The 6 a. m. readings are those used by the Weather Bureau, but are liable to be very misleading, owing to the great diurnal fluctuation of the water surface, and should not be used for important work. In the publications of the United States Geological Survey since 1900 the average of all four of the daily readings is used and is reduced to feet and tenths of a foot. The zero of the gage is the datum of all the city levels, and any city benchmark can therefore be used. A point is established on the North Augusta bridge from which to measure down with a steel tape. This is the top of the plate through which the top pipe of the bridge-fencing passes, which is riveted to the right side of the intermediate post at the down-stream end of the third floor beam from the right-bank end of the bridge, and at ordinary stages it is 55.00 feet above water, less the reading of the gage.

This station is located below all the wheels of the large developed water power belonging to the city of Augusta.

Water is diverted from the river above the city by a canal following along the right bank, described in Volume XVI of the Tenth Census, 1880, page 789. A measurement of the canal by B. M. Hall on September 29, 1897, above all the water wheels, showed a flow of 2,640 second-feet, presumably all of which was passing through the water wheels under varying heads. The full head is 50 feet, but the canal has three levels. Some of the wheels discharge from the upper level or main canal directly into the river, while others discharge from one level to another.

The highest water recorded was on September 11, 1888, at 38.7 feet. At that time the entire city was submerged, 10 persons were drowned, and property was damaged to the amount of \$2,000,000.

The floods of this river have been investigated under the direction of the Corps of Engineers, United States Army, and reports prepared by George W. Brown, assistant engineer. The first of these, dated February 11, 1889, was printed, with maps, as House Ex.

Doc. No. 213, Fifty-first Congress, first session; it was also given, with few maps, in the Report of the Chief of Engineers, United States Army, 1890, page 1340. A later report, dated June 10, 1890, also prepared by Mr. George W. Brown, was printed as Ex. Doc. No. 255, Fifty-first Congress, second session. In this report is given a rating table, showing the probable discharge of the river at heights on the gage of from 5 to 40 feet. On page 17 of this latter document is shown the run-off in cubic feet per second per square mile for various portions of the drainage basin. A table of distances and elevations and slope of river, as well as a description of the character of the drainage basin, is also given.

From the figures in the above-named reports a computation was made by Cyrus C. Babb of the fluctuations of flow of Savannah River, the results being published in the Fourteenth Annual Report, Part II, of the United States Geological Survey, page 147, relating to the years 1884 to 1891, inclusive. A discussion of the results is also given in Transactions American Society of Civil Engineers, Volume XXIII, page 332.

By the use of a rating table Mr. Hall has computed the minimum flow, by months, from 1892 to 1898, inclusive. In each case he has taken the average of all the readings for the day of lowest water in the given month, and not the lowest single reading. The lowest average daily reading for the seven years is that on July 3, 1898, of 3.88.

WATER POWERS OF GEORGIA

Minimum monthly gage height and discharge of Savannah River at Augusta, for
1892 to 1898, inclusive.

Date	Gage height	Dis-charge	Date	Gage height	Dis-charge
1892			1895		
January 2.....	<i>Feet</i> 7.80	<i>Sec.-Ft.</i> 6,820	July 21.....	<i>Feet</i> 6.66	<i>Sec.-Ft.</i> 5,905
February 7.....	8.55	8,328	August 3.....	5.90	3,910
March 6.....	8.25	7,698	September 30.....	5.40	3,436
April 30.....	8.63	8,502	October 26.....	5.03	3,125
May 2.....	7.80	5,922	November 2.....	5.20	3,268
June 30.....	7.53	6,368	December 8.....	5.40	3,436
July 17.....	6.76	5,033	1896		
August 10.....	6.06	4,091	January 15.....	6.50	4,660
September 21.....	6.40	4,522	February 23.....	8.10	7,396
October 2.....	6.30	4,589	March 31.....	7.50	6,274
November 2.....	6.80	5,092	April 24.....	6.03	4,040
December 15.....	6.63	4,843	May 23.....	5.30	3,352
1893			June 18.....	4.93	3,045
January 18.....	6.45	4,591	July 4.....	4.73	2,875
February 10.....	8.06	7,318	August 25.....	5.16	3,200
March 31.....	8.00	7,200	September 23.....	4.10	2,405
April 20.....	6.30	4,589	October 11.....	3.94	2,323
May 29.....	6.35	4,455	November 1.....	4.30	2,980
June 30.....	6.70	4,944	December 27.....	6.16	4,153
July 15.....	5.53	3,550	1897		
August 26.....	5.23	3,296	January 12.....	6.00	4,020
September 26.....	6.86	5,200	February 1.....	7.40	6,093
October 31.....	6.06	4,091	March 6.....	9.20	9,804
November 21.....	5.73	3,735	April 29.....	3.60	4,836
December 15.....	6.30	4,589	May 29.....	6.60	4,800
1894			June 27.....	6.00	4,020
January 6.....	7.10	5,572	July 4.....	5.65	3,655
February 4.....	7.76	6,760	August 31.....	5.40	3,436
March 31.....	8.13	7,456	September 15.....	4.55	2,738
April 28.....	7.23	5,810	October 10.....	3.93	2,330
May 31.....	6.36	4,484	November 14.....	5.00	3,100
June 18.....	5.33	3,380	December 12.....	5.85	3,860
July 16.....	5.23	3,296	1898		
August 24.....	5.90	3,910	January 11.....	5.97	3,930
September 13.....	5.30	3,352	February 26.....	5.67	3,885
October 31.....	5.83	3,840	March 27.....	5.67	3,670
November 12.....	5.76	3,765	April 23.....	6.97	5,350
December 3.....	5.53	3,550	May 29.....	4.92	3,032
1895			June 11.....	4.20	2,475
January 8.....	7.75	6,728	July 3.....	3.88	2,294
February 10.....	8.66	8,506	August 4.....	6.55	4,730
March 1.....	8.95	9,220	September 30.....	7.47	6,220
April 7.....	8.76	8,300	October 2.....	7.02	5,435
May 18.....	8.70	8,656	November 6.....	7.55	6,364
June 27.....	6.73	5,040	December 18.....	7.85	6,916

SAVANNAH DRAINAGE BASIN, STREAM FLOW

Discharge measurements of Savannah River at Augusta.

Date	Gage height	Dis-charge	Date	Gage height	Dis-charge
1896	<i>Feet</i>	<i>Sec.-ft.</i>	1901	<i>Feet</i>	<i>Sec.-ft.</i>
October 3.....	5.41	3,154	April 4.....	32.10	127,100
1897			August 10.....	10.00	9,720
July 15.....	6.67	4,198	1902		
September 9.....	5.17	3,130	June 20.....	8.85	7,497
November 6.....	6.20	4,311	July 25.....	7.85	5,246
1898			September 5.....	7.90	5,239
April 28.....	11.55	14,490	1903		
June 16.....	5.25	3,333	June 10.....	15.10	17,740
July 27.....	9.85	11,350	September 29.....	7.13	3,331
July 28.....	10.37	14,250	December 3.....	7.20	3,898
August 2.....	7.17	6,302	1904		
August 3.....	6.72	5,511	February 5.....	7.50	4,714
September 3.....	28.27	37,470	February 15.....	8.70	6,714
September 16.....	8.10	7,432	April 7.....	7.96	5,647
September 17.....	8.00	7,108	July 14.....	6.45	3,326
November 14.....	11.68	13,240	August 10.....	24.57	55,680
1899			October 9.....	5.77	3,068
March 17.....	25.20	60,720	October 18.....	5.07	2,057
March 18.....	20.60	35,970	1905		
May 3.....	9.70	10,860	March 29.....	7.72	5,333
May 9.....	9.50	9,908	April 12.....	8.04	5,867
May 29.....	7.60	6,271	June 7.....	7.35	5,092
July 1.....	7.22	5,391	October 13.....	10.10	9,822
August 3.....	6.68	4,226	October 14.....	7.78	5,204
October 10.....	12.48	14,610	November 22.....	6.70	4,365
1900			1906		
August 28.....	7.30	5,968	March 8.....	9.42	8,640
1901			April 27.....	8.89	7,200
January 19.....	11.65	13,040	August 20.....	13.92	20,000
February 21.....	8.55	7,664	October 29.....	9.44	8,400

WATER POWERS OF GEORGIA

Daily gage height, in feet, of Savannah River at Augusta.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1899 α												
1.....	8.5	12.7	28.8	19.5	9.6	7.9	7.2	7.4	13.9	5.0	6.2	7.3
2.....	10.3	13.0	21.0	13.9	9.5	8.4	6.7	6.7	10.9	5.0	6.4	6.9
3.....	10.3	14.3	16.2	15.3	9.3	7.6	6.2	6.3	9.1	5.5	6.3	5.8
4.....	9.0	15.8	14.2	13.2	9.3	7.5	6.0	6.3	8.0	5.6	5.8	7.0
5.....	8.5	14.5	13.7	12.9	9.2	7.2	6.0	6.0	7.5	5.8	5.6	8.7
6.....	8.5	20.7	16.2	13.0	9.8	7.3	6.0	5.9	6.9	11.8	5.8	6.7
7.....	12.3	28.0	15.2	12.2	10.3	7.3	5.3	5.7	6.6	9.6	5.9	6.3
8.....	22.9	31.0	13.3	12.4	10.4	7.0	6.7	5.5	7.4	10.5	5.8	6.3
9.....	19.2	29.9	12.2	15.5	9.7	7.0	7.0	5.7	7.0	14.1	5.9	6.1
10.....	14.3	22.9	11.8	14.2	9.1	6.9	8.3	6.0	7.0	12.1	5.8	6.0
11.....	12.3	18.3	11.5	12.8	8.8	7.3	7.8	5.7	8.7	8.5	5.5	5.9
12.....	17.3	14.7	11.2	12.0	8.5	6.9	6.5	8.0	9.3	7.3	5.6	5.9
13.....	17.4	13.7	11.2	11.5	8.5	7.5	6.0	3.3	8.6	6.9	5.6	6.3
14.....	15.3	12.9	11.1	11.2	8.5	9.7	6.0	6.4	6.9	6.4	5.7	10.7
15.....	15.4	12.3	11.0	11.0	8.3	9.7	6.0	6.0	6.3	6.0	6.1	14.5
16.....	14.5	14.4	13.8	10.8	8.2	8.2	6.0	5.5	5.8	6.3	5.3	10.5
17.....	17.3	25.0	25.5	10.5	8.2	8.0	5.7	5.4	5.6	6.0	5.3	8.5
18.....	16.8	24.3	21.5	10.5	8.0	8.7	5.6	5.0	5.2	6.0	5.3	7.5
19.....	13.9	19.1	17.1	10.2	8.0	7.9	5.8	5.0	5.4	6.3	5.4	7.3
20.....	11.7	15.3	20.0	10.5	7.9	7.3	5.7	5.3	5.7	6.1	5.7	7.0
21.....	10.7	13.5	22.5	10.4	7.9	7.3	5.5	4.0	6.0	6.5	5.7	6.8
22.....	10.0	14.7	17.1	10.0	7.3	7.0	5.3	4.7	6.6	6.7	5.3	6.9
23.....	9.9	14.3	15.8	9.9	7.7	6.7	5.3	5.3	6.0	6.0	5.3	7.4
24.....	11.4	13.0	15.5	9.6	8.2	6.7	5.8	4.8	5.4	6.0	7.0	9.3
25.....	11.9	11.7	15.5	10.0	8.0	6.5	5.7	5.7	5.9	5.3	8.3	13.3
26.....	10.8	11.5	13.3	11.5	7.8	6.8	6.0	5.6	5.6	5.3	9.2	12.3
27.....	10.3	17.7	14.5	13.0	7.6	6.7	7.0	7.0	5.3	5.6	11.3	9.3
28.....	10.0	29.6	13.0	11.2	7.4	7.5	11.7	13.3	5.8	5.7	9.3	8.3
29.....	11.0	14.0	10.3	7.4	7.7	11.6	11.3	5.8	5.6	8.4	5.0
30.....	11.2	15.5	10.0	7.4	7.5	9.3	9.2	5.6	5.3	7.5	8.3
31.....	10.5	13.0	7.3	8.5	11.4	5.9	7.7

α For the months of September, October, and November, 1899, the figures given are an average of four readings daily—6 a. m., 12 m., 6 p. m., and 8 p. m. For the other months the readings are those taken at 6 a. m.

Daily gage height, in feet, of Savannah River at Augusta.—Continued.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1900. α												
1.....	7.12	6.87	17.37	9.98	11.5	7.7	14.46	11.29	7.37	6.18	7.2	7.95
2.....	6.94	6.81	23.12	9.89	11.2	7.5	12.9	9.46	7.79	6.38	7.3	7.5
3.....	6.67	6.44	13.87	9.54	10.7	7.5	12.25	8.3	8.35	6.38	7.7	7.75
4.....	6.42	6.52	14.06	9.54	12.3	8.3	11.66	7.76	7.33	6.16	13.8	9.18
5.....	6.5	8.33	11.44	9.65	10.6	10.2	10.6	7.73	7.0	6.4	12.0	15.81
6.....	6.67	9.1	10.6	9.63	9.6	9.5	9.62	7.33	6.85	6.65	9.8	14.44
7.....	6.39	8.89	10.37	9.2	9.3	11.7	9.27	7.27	6.44	7.65	8.0	11.22
8.....	6.65	8.08	10.64	9.0	9.0	19.7	8.96	7.19	6.2	7.41	7.7	9.32
9.....	6.71	8.12	17.35	8.75	9.0	19.9	8.79	7.13	6.27	7.35	7.5	8.5
10.....	6.71	10.04	17.6	8.9	8.8	19.9	8.39	7.09	5.89	7.5	7.4	8.4
11.....	7.12	20.58	14.85	9.15	8.7	10.8	8.52	7.06	6.16	6.3	6.9	8.06
12.....	10.4	27.19	12.21	11.1	8.6	9.5	8.22	6.57	6.06	6.75	7.0	7.9
13.....	15.0	29.6	10.96	11.35	8.4	9.2	8.68	6.62	6.08	6.85	7.1	7.8
14.....	12.79	32.31	10.39	10.77	8.3	9.3	8.94	7.31	5.99	7.48	7.0	8.8
15.....	9.37	30.08	10.08	9.47	8.3	9.9	9.6	7.17	7.4	7.14	7.0	11.66
16.....	8.65	22.08	15.25	9.16	8.2	9.7	9.37	6.77	14.49	6.62	6.8	9.81
17.....	8.12	16.29	17.27	8.88	7.8	15.0	8.64	7.67	14.24	6.56	6.8	8.6
18.....	7.67	12.75	14.21	12.15	8.4	19.8	8.37	7.27	10.6	6.47	6.5	7.97
19.....	7.94	11.39	11.42	23.89	9.7	18.4	8.19	6.78	8.35	6.45	6.8	7.44
20.....	8.94	10.46	13.68	24.7	11.0	13.5	8.04	6.82	7.7	6.27	7.2	8.15
21.....	10.26	10.35	15.25	24.25	10.6	10.7	7.89	6.62	7.27	5.95	7.5	12.1
22.....	10.44	14.79	13.7	26.73	8.9	9.6	7.39	6.48	7.12	6.3	7.4	12.7
23.....	9.11	15.44	11.85	24.73	8.4	11.7	8.0	6.5	6.92	6.32	7.3	11.12
24.....	8.44	12.89	11.73	18.27	10.4	21.8	8.2	6.56	6.35	12.66	7.4	9.35
25.....	8.12	12.96	14.10	14.75	13.0	29.2	8.92	6.77	6.75	16.72	7.0	9.4
26.....	7.96	12.37	19.65	17.08	11.0	26.8	8.32	7.77	6.5	12.3	10.0	9.2
27.....	7.73	10.98	18.37	13.73	9.1	23.0	9.23	7.12	6.67	10.6	14.9	8.72
28.....	7.19	10.31	14.79	12.5	8.5	19.6	11.12	7.2	6.46	9.72	11.8	8.4
29.....	7.22	12.67	11.81	8.1	16.7	10.2	6.69	6.5	8.52	9.1	8.25
30.....	7.2	11.46	11.2	7.9	14.6	11.88	6.62	6.19	7.95	8.3	8.4
31.....	7.08	10.69	7.8	13.35	7.08	7.6	15.22
1901. α												
1.....	15.2	10.4	8.3	14.0	10.1	14.1	12.2	8.3	18.4	10.8	8.4	8.2
2.....	15.23	9.5	8.2	14.7	10.0	13.3	11.6	7.3	18.2	11.9	8.4	8.4
3.....	17.3	10.0	8.0	30.3	9.8	11.4	9.9	7.4	15.0	12.2	8.3	8.2
4.....	15.12	25.6	8.2	30.9	9.5	10.1	8.9	7.2	12.8	12.1	8.5	8.9
5.....	12.4	26.7	8.1	23.8	9.4	9.8	8.8	7.3	11.4	10.1	8.4	9.9
6.....	10.28	20.4	8.0	18.5	9.3	9.8	8.5	7.7	10.8	9.4	8.7	9.1
7.....	9.37	16.1	8.0	14.3	9.3	15.0	8.3	12.9	10.4	9.3	8.5	8.6
8.....	8.95	12.7	7.8	12.7	9.3	15.7	8.6	18.9	10.0	9.1	8.4	8.6
9.....	8.62	14.0	7.8	11.6	9.2	12.1	9.0	13.2	9.9	9.2	8.5	8.6
10.....	8.55	17.3	8.1	11.0	9.0	9.6	8.9	10.0	9.8	8.9	8.3	8.4
11.....	8.55	15.3	10.1	10.6	8.8	9.0	8.7	9.2	9.7	8.7	8.4	8.5
12.....	17.12	12.7	14.9	10.3	8.5	9.1	8.2	12.0	10.0	8.8	8.5	9.1
13.....	23.45	11.6	11.8	10.5	8.6	10.4	7.7	10.6	9.8	11.2	8.7	8.9
14.....	19.13	10.7	9.8	17.6	8.7	21.7	8.1	11.3	9.6	12.0	8.4	8.9
15.....	14.65	10.2	8.9	18.6	8.6	26.9	8.4	13.1	9.3	10.8	8.5	14.8
16.....	11.8	9.3	8.6	14.9	8.5	26.2	9.2	19.8	9.2	9.1	8.5	23.1
17.....	11.9	9.3	8.2	12.4	8.5	23.0	8.7	22.4	10.7	9.0	8.2	17.2
18.....	13.3	9.2	8.2	11.3	8.3	17.3	9.3	21.8	28.5	8.9	8.5	12.4
19.....	11.55	9.1	8.0	11.7	8.9	14.8	9.7	19.7	30.9	8.6	8.4	10.7
20.....	9.87	8.9	8.0	19.6	15.1	12.1	13.3	17.9	25.5	8.4	8.4	9.9
21.....	9.48	8.6	8.0	23.6	20.8	11.0	12.4	15.3	17.1	8.2	8.5	9.3
22.....	9.05	8.6	8.7	18.2	25.6	11.2	9.8	17.0	13.1	8.4	8.6	9.2
23.....	9.0	8.6	9.4	14.8	27.0	11.7	9.0	20.2	11.5	8.4	8.6	9.1
24.....	9.07	8.6	8.6	13.3	10.6	12.2	8.2	24.0	10.7	8.6	8.4	9.6
25.....	10.28	8.7	8.9	12.4	15.0	11.7	8.0	21.6	10.2	8.7	8.3	10.2
26.....	10.32	8.7	15.1	11.7	13.5	11.8	8.0	16.3	10.0	8.5	8.6	9.9
27.....	9.47	8.7	27.7	11.2	14.0	11.0	10.0	13.9	9.7	8.5	8.5	9.7
28.....	9.12	8.4	28.0	10.8	11.9	10.2	9.8	22.0	9.3	8.6	8.4	13.3
29.....	9.05	20.3	10.5	11.1	10.8	9.3	28.7	9.8	8.3	8.4	23.1
30.....	8.95	14.8	10.2	10.4	10.9	9.1	26.1	10.7	8.4	8.3	29.6
31.....	8.85	14.4	10.8	8.4	21.4	8.6	30.4

α Mean of four daily readings.

WATER POWERS OF GEORGIA

Daily gage height, in feet, of Savannah River at Augusta.—Continued.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1902 <i>a</i>												
1.....	23.9	19.3	33.8	18.6	9.8	8.3	7.3	7.8	7.7	8.7	7.5	11.8
2.....	16.6	29.5	32.3	14.5	10.6	8.5	7.2	8.1	7.4	9.9	7.2	13.2
3.....	13.6	32.4	28.6	13.1	10.8	8.9	7.1	9.0	7.3	9.2	7.1	17.4
4.....	12.4	28.5	21.5	12.3	10.2	8.5	7.0	8.5	7.2	8.5	7.3	21.1
5.....	11.5	21.1	17.4	12.5	9.9	8.4	6.9	7.8	7.8	9.2	7.1	17.4
6.....	11.0	15.6	15.1	12.0	9.8	8.3	6.8	7.7	7.7	10.9	7.4	14.3
7.....	10.5	13.2	13.9	12.0	9.7	8.3	6.9	7.7	7.1	10.3	7.5	11.8
8.....	10.5	12.2	13.2	13.4	9.4	8.5	7.0	7.6	7.1	8.7	9.2	10.5
9.....	10.4	11.6	12.7	13.6	9.6	8.8	7.4	7.2	7.1	8.3	8.3	9.5
10.....	10.2	11.0	13.1	12.3	10.1	8.6	8.0	7.1	12.3	8.1	8.0	9.1
11.....	9.9	10.7	12.5	11.6	10.6	8.1	8.0	7.4	13.1	8.0	7.5	9.0
12.....	9.8	10.4	12.3	11.1	9.6	8.1	8.3	8.6	9.9	8.0	7.4	8.9
13.....	9.6	10.2	12.3	10.6	9.1	8.1	9.6	8.8	8.3	8.8	7.5	10.7
14.....	9.4	10.2	13.7	11.1	9.1	8.1	9.4	8.0	7.7	9.4	7.4	10.6
15.....	9.3	10.3	13.5	10.6	9.7	8.4	8.7	9.5	8.9	8.9	7.3	9.7
16.....	9.4	10.7	13.5	10.8	9.4	13.0	10.0	10.4	8.0	9.2	7.2	8.9
17.....	9.2	11.4	27.9	11.2	9.3	15.0	9.2	9.4	7.7	8.4	7.4	9.2
18.....	9.2	11.1	25.6	13.1	9.2	11.4	8.7	9.2	7.4	8.0	8.0	14.0
19.....	9.2	10.9	19.5	13.4	9.2	10.4	7.6	8.3	7.4	7.3	8.7	11.5
20.....	9.2	10.6	16.0	12.7	9.2	9.4	7.1	8.9	8.0	7.5	8.8	10.2
21.....	9.5	11.8	13.8	12.1	9.2	9.3	6.9	8.1	9.2	7.9	8.0	9.4
22.....	10.2	14.5	13.1	11.1	9.4	8.9	6.9	7.3	8.4	7.4	7.9	12.2
23.....	10.2	13.7	12.5	10.7	9.5	8.6	6.9	7.4	8.1	7.2	7.4	14.6
24.....	9.7	12.6	12.4	10.5	9.2	8.5	7.0	7.4	7.8	7.2	7.5	12.2
25.....	9.5	16.7	11.9	10.2	8.9	8.4	7.5	7.3	7.9	7.2	7.7	10.4
26.....	9.3	18.1	12.0	10.2	8.8	8.3	7.6	7.4	13.6	7.0	10.1	9.9
27.....	9.3	16.2	11.6	10.0	8.6	7.9	7.6	7.4	13.8	7.4	12.4	9.4
28.....	9.2	25.5	11.9	10.1	8.5	7.8	7.0	7.4	12.3	8.9	10.8	8.9
29.....	9.9	19.6	9.3	8.4	7.5	7.0	8.7	10.9	8.9	9.1	8.6
30.....	11.6	28.2	9.9	8.3	7.6	7.3	8.4	9.3	8.2	8.4	8.9
31.....	11.4	24.6	8.2	8.0	7.5	7.3	8.7
1903 <i>a</i>												
1.....	9.7	10.2	26.7	23.4	10.6	11.0	9.7	9.0	7.4	7.1	6.8	7.0
2.....	9.4	9.6	24.0	18.7	10.5	16.3	9.4	8.9	7.2	7.0	7.2	7.2
3.....	11.2	9.7	13.4	16.1	10.5	20.0	9.0	12.0	7.3	7.0	8.3	7.2
4.....	13.8	10.8	14.9	15.2	10.6	15.3	9.5	13.6	7.3	6.9	9.1	7.1
5.....	13.9	18.5	13.9	14.6	12.4	13.2	9.6	11.7	7.4	7.1	9.1	7.0
6.....	12.2	18.2	13.7	13.9	11.3	19.9	10.6	10.6	7.2	6.9	9.4	7.0
7.....	10.7	14.6	13.7	13.0	10.7	24.7	10.0	9.5	7.1	7.1	8.8	7.1
8.....	9.9	30.7	13.3	13.3	10.5	25.5	10.1	8.6	7.2	7.1	8.0	7.2
9.....	9.5	33.0	15.0	16.8	10.5	17.7	9.5	8.1	7.3	7.2	7.8	7.3
10.....	9.2	28.7	15.1	17.5	10.4	15.6	9.2	8.1	7.2	7.5	7.6	7.4
11.....	9.2	24.1	14.9	14.9	10.4	16.1	9.2	8.1	8.3	7.4	7.6	7.4
12.....	11.7	28.4	13.2	13.3	10.0	16.1	9.9	10.0	7.8	7.3	7.5	7.4
13.....	14.1	26.5	19.0	13.1	10.0	15.0	10.0	9.1	7.2	7.0	7.5	7.1
14.....	12.2	20.4	15.3	20.4	10.4	12.1	13.2	8.3	7.4	7.0	7.5	7.2
15.....	10.6	16.0	13.8	23.6	11.2	11.1	13.4	9.5	8.2	6.9	7.3	7.4
16.....	9.9	14.4	13.2	17.3	12.9	10.6	11.0	9.8	9.4	6.9	7.3	7.6
17.....	9.6	25.9	12.7	14.6	11.7	10.1	9.5	10.3	11.9	7.3	7.3	7.5
18.....	9.3	29.1	12.2	13.6	10.5	9.8	8.9	9.9	10.8	9.2	7.5	7.3
19.....	9.2	23.4	11.9	12.7	9.9	9.7	8.7	17.7	9.0	8.4	7.6	7.2
20.....	9.1	18.6	11.3	12.5	9.6	9.6	8.4	14.8	8.1	8.2	7.8	7.0
21.....	9.1	14.6	12.0	12.3	9.5	9.8	8.2	11.3	8.2	7.6	7.7	7.1
22.....	9.2	13.1	13.2	12.3	9.4	10.4	8.2	9.9	7.6	7.4	7.3	7.4
23.....	9.0	12.6	25.5	11.9	9.5	9.8	8.1	8.7	7.5	7.0	7.3	7.9
24.....	9.0	12.1	29.4	11.5	9.2	9.4	8.1	8.4	7.4	7.1	7.3	7.6
25.....	9.1	11.7	28.6	11.1	9.2	9.4	8.0	8.3	7.4	6.8	7.4	7.4
26.....	9.9	11.5	22.5	11.4	9.0	9.3	7.6	8.0	7.4	7.0	7.3	7.7
27.....	10.2	11.6	17.1	11.7	8.7	9.7	7.9	7.8	7.2	7.0	7.3	8.0
28.....	10.9	16.9	15.2	11.5	8.8	10.7	8.0	7.6	7.2	6.9	7.1	8.0
29.....	10.9	14.8	11.0	9.4	12.9	7.7	7.6	7.1	6.9	7.0	7.6
30.....	11.8	25.3	10.7	9.6	11.0	8.0	7.5	7.1	7.0	7.1	7.5
31.....	11.2	27.3	9.7	8.7	7.5	7.0	7.5

a Mean of four daily readings.

SAVANNAH DRAINAGE BASIN, STREAM FLOW

Daily gage height, in feet, of Savannah River at Augusta.—Continued.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1904 <i>a</i>												
1.....	7.3	8.0	8.8	8.6	7.4	9.2	6.8	7.7	7.3	5.3	5.1	5.7
2.....	7.2	7.9	8.6	8.3	7.5	11.2	7.5	7.1	7.0	4.8	4.8	6.0
3.....	7.1	7.9	8.6	8.3	7.3	9.1	6.8	8.9	7.0	5.3	5.4	6.3
4.....	7.2	7.7	8.7	8.2	7.3	7.9	5.8	8.6	6.2	5.2	5.4	6.9
5.....	7.3	7.6	8.4	8.1	7.6	7.0	6.4	10.4	9.3	4.9	5.6	7.3
6.....	7.2	7.7	8.1	8.0	7.5	6.9	6.0	8.6	11.1	5.0	6.3	8.4
7.....	7.1	7.4	10.4	7.9	7.3	7.0	5.5	8.4	10.4	5.3	6.7	11.5
8.....	6.8	9.0	16.3	8.2	7.0	7.5	5.6	16.3	8.1	4.7	6.5	9.8
9.....	7.0	11.9	16.2	9.1	8.8	8.0	5.1	24.5	7.3	3.8	6.4	8.1
10.....	7.0	11.2	12.6	10.1	8.9	7.1	6.2	24.5	7.0	5.5	6.0	7.7
11.....	7.3	14.4	10.5	9.3	8.9	6.0	7.0	19.1	6.5	5.2	5.6	7.2
12.....	7.4	12.7	9.7	8.7	8.0	6.0	6.9	14.3	6.7	4.1	5.5	7.2
13.....	7.6	10.7	9.3	8.4	7.6	6.7	6.7	11.8	6.4	5.2	5.4	7.0
14.....	7.4	9.2	9.1	8.2	7.5	6.6	6.3	9.6	6.3	4.6	6.6	7.1
15.....	7.5	8.7	9.1	8.0	7.0	6.5	5.7	9.3	6.1	4.5	6.8	7.0
16.....	7.5	8.6	9.4	8.0	7.1	6.4	5.4	10.3	6.1	3.8	7.0	7.0
17.....	7.2	8.4	9.0	7.8	7.2	6.2	4.8	10.7	5.8	5.5	6.7	6.9
18.....	7.5	8.2	8.4	8.0	7.0	6.0	5.6	9.1	5.5	4.3	6.3	7.4
19.....	7.7	8.1	8.4	8.0	7.0	5.2	5.4	8.3	5.7	4.5	5.9	7.6
20.....	7.6	8.9	8.2	7.9	6.8	6.5	5.5	7.6	5.5	4.3	5.4	7.1
21.....	7.4	11.6	8.3	7.8	6.8	6.6	5.3	10.1	5.5	5.1	6.3	7.1
22.....	7.6	14.6	8.5	7.7	6.5	7.1	5.2	9.0	5.6	4.2	5.8	6.8
23.....	13.1	18.5	9.6	7.7	6.7	7.2	5.0	7.4	5.7	3.3	5.4	6.8
24.....	13.4	15.7	11.1	7.5	6.6	6.7	10.1	7.1	5.6	5.5	5.9	6.3
25.....	11.5	12.5	13.4	7.5	6.4	6.1	7.7	6.9	5.5	4.3	6.2	6.1
26.....	9.4	10.6	11.9	7.6	6.4	5.4	8.7	6.8	5.7	4.3	5.9	6.4
27.....	8.5	9.5	10.5	7.6	6.4	6.2	7.8	9.2	5.4	4.2	5.6	6.8
28.....	8.2	9.1	10.4	7.9	6.4	5.7	7.6	12.5	5.5	5.4	6.2	7.8
29.....	8.2	9.0	9.6	7.8	5.6	5.7	9.5	12.4	5.6	5.3	5.7	9.7
30.....	8.0	9.1	7.6	5.6	6.6	8.5	9.9	5.3	3.8	5.4	9.9
31.....	7.9	8.8	6.8	6.8	8.0	5.6	8.3
1905 <i>a</i>												
1.....	7.5	7.2	9.6	7.6	6.6	8.1	11.3	6.8	7.1	5.0	6.2	6.3
2.....	7.6	7.1	9.4	7.6	8.6	7.9	22.6	6.9	7.0	5.3	6.1	6.1
3.....	7.5	7.2	9.1	7.5	8.3	7.7	20.2	7.0	9.2	5.3	6.1	8.1
4.....	7.3	7.0	8.8	7.5	10.9	7.1	12.3	6.9	9.5	5.6	5.9	20.6
5.....	7.2	7.2	8.6	7.5	12.3	7.2	9.6	6.7	8.2	6.4	6.0	20.3
6.....	7.2	7.1	9.0	7.8	11.0	7.2	9.5	6.4	7.6	7.5	6.3	12.6
7.....	7.5	7.3	8.1	8.1	11.5	7.0	13.1	6.7	7.1	6.6	6.1	9.3
8.....	8.6	9.0	8.2	8.2	18.1	7.1	12.1	7.3	6.9	5.4	5.6	8.4
9.....	8.8	13.4	8.5	7.4	15.0	6.8	10.4	9.1	6.8	6.0	6.2	9.4
10.....	8.0	16.9	8.5	7.7	12.1	6.6	9.3	11.1	6.5	5.3	6.1	19.0
11.....	7.7	17.2	8.7	8.3	10.0	6.2	8.1	9.3	6.3	6.3	6.4	18.2
12.....	7.7	16.4	10.6	7.9	9.0	6.7	11.5	12.6	6.6	6.6	7.6	14.0
13.....	12.0	23.5	12.3	8.5	8.3	6.4	18.4	13.8	6.3	9.3	7.2	10.6
14.....	17.9	25.3	9.8	8.8	7.9	6.6	20.7	13.3	6.6	7.9	6.5	9.4
15.....	14.2	20.9	9.9	8.4	7.9	7.4	16.5	10.6	7.0	6.7	6.3	9.9
16.....	10.8	16.3	9.3	8.2	7.8	7.6	13.1	9.5	6.7	6.3	6.4	11.2
17.....	9.2	12.5	8.9	8.2	7.9	7.4	11.1	9.6	5.9	6.5	6.3	10.4
18.....	8.7	10.8	8.6	7.3	9.4	7.7	9.3	9.4	6.5	6.5	6.2	9.6
19.....	8.4	10.2	8.5	7.4	8.2	7.8	9.5	8.8	6.3	6.4	5.6	9.1
20.....	8.2	10.1	8.4	7.4	7.6	7.5	9.3	8.5	5.6	6.5	6.2	10.2
21.....	8.3	13.0	8.4	7.4	7.4	7.1	9.1	8.5	6.2	6.0	6.1	27.6
22.....	8.2	23.5	8.7	7.1	7.8	7.1	8.4	7.3	6.1	5.3	6.5	27.5
23.....	8.2	20.2	9.0	6.9	8.4	7.8	7.6	7.9	6.1	6.5	7.0	21.5
24.....	8.0	15.6	8.6	6.9	14.6	7.8	7.9	8.7	5.4	5.3	6.4	16.2
25.....	7.7	12.4	8.2	6.9	14.2	6.9	7.6	9.2	5.8	6.1	6.4	12.4
26.....	7.5	11.4	8.4	7.0	11.4	6.9	7.6	10.9	5.7	5.9	5.4	10.8
27.....	7.2	10.7	8.4	7.0	9.7	6.3	7.5	10.5	5.9	5.9	6.5	9.8
28.....	7.0	9.7	7.6	7.3	9.5	6.6	7.3	9.0	5.7	6.1	6.3	9.7
29.....	6.8	7.6	7.7	9.6	6.3	7.6	8.1	5.6	6.5	6.4	14.3
30.....	7.2	7.3	9.2	9.4	6.5	7.7	7.7	5.2	6.4	6.3	14.0
31.....	7.2	7.5	8.7	7.9	7.2	6.1	12.9

a Mean of four daily readings.

WATER POWERS OF GEORGIA

Daily gage height, in feet, of Savannah River at Augusta.—Continued.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1906												
1.....	11.2	12.4	8.9	15.6	9.4	8.2	7.8	19.5	17.8	18.4	9.5	9.0
2.....	10.4	11.9	8.8	13.6	9.4	7.8	12.7	18.4	14.6	18.1	9.4	8.8
3.....	9.9	11.2	8.7	11.9	8.9	7.6	10.7	16.4	12.1	18.6	9.4	8.9
4.....	26.1	10.8	8.8	11.2	9.0	9.5	11.0	13.8	10.7	23.2	9.0	8.8
5.....	23.3	10.8	10.9	11.0	9.7	12.1	13.7	12.6	10.5	22.5	9.1	8.7
6.....	23.9	9.9	10.1	10.5	9.4	10.5	11.5	11.6	12.3	19.2	9.1	8.7
7.....	17.6	10.5	9.5	10.3	10.9	9.5	10.5	11.8	11.7	17.8	9.1	9.0
8.....	13.1	10.4	9.9	10.0	12.8	8.6	9.7	10.6	10.7	16.1	9.0	9.2
9.....	11.6	12.3	16.4	10.0	11.4	8.1	14.6	9.9	9.8	13.8	9.0	9.0
10.....	11.1	12.1	15.2	10.7	9.6	8.0	17.7	9.3	9.8	12.7	9.0	8.8
11.....	10.6	11.0	11.6	11.1	9.0	8.0	13.7	8.9	9.2	12.0	8.8	9.0
12.....	12.6	11.0	10.9	10.6	8.8	9.3	11.5	8.8	9.4	11.7	9.1	13.4
13.....	15.8	11.2	9.8	10.0	8.6	15.4	9.7	9.2	16.9	11.0	9.0	11.3
14.....	14.0	11.1	9.7	9.8	8.5	21.0	9.9	10.8	14.5	10.6	9.0	10.5
15.....	11.8	10.6	11.0	10.7	8.4	19.4	9.1	11.6	12.5	10.6	9.1	9.8
16.....	11.0	10.2	24.3	12.0	8.2	23.7	17.8	11.2	10.6	10.6	9.2	9.2
17.....	10.8	9.6	22.8	11.5	8.0	24.3	19.5	11.4	9.4	10.5	9.3	9.2
18.....	10.8	9.5	18.8	10.5	8.0	20.4	18.0	10.6	11.6	10.5	9.2	9.5
19.....	10.1	9.4	13.4	9.8	8.0	16.0	20.9	11.0	17.9	11.2	10.0	11.1
20.....	9.9	9.3	26.9	9.6	7.8	12.6	17.9	13.8	21.9	13.5	14.5	12.5
21.....	9.7	9.2	27.2	9.5	7.8	10.5	16.5	15.2	22.4	11.7	12.7	13.5
22.....	10.0	10.8	21.5	9.4	7.8	9.4	14.0	14.5	17.5	11.0	11.0	12.1
23.....	20.0	10.9	15.6	9.5	7.7	9.1	13.9	12.7	14.1	10.5	10.2	10.5
24.....	23.8	10.1	13.1	8.9	7.8	8.5	12.9	12.3	13.4	10.0	9.9	10.0
25.....	25.1	9.4	11.8	8.8	8.2	8.6	13.3	10.9	15.9	9.9	9.5	9.5
26.....	22.6	9.3	11.4	8.8	8.0	9.0	14.2	10.5	14.2	9.9	9.5	9.5
27.....	24.2	9.2	11.1	8.8	10.5	8.6	12.4	11.3	14.0	9.6	9.3	9.3
28.....	22.3	9.0	13.2	9.1	13.3	8.7	10.6	12.2	12.7	9.5	9.2	9.3
29.....	18.8	14.4	10.6	11.2	8.0	11.1	14.8	12.7	9.5	9.2	9.6
30.....	15.6	13.7	10.2	9.2	7.9	11.9	14.8	15.0	9.4	9.1	10.0
31.....	13.6	15.2	8.6	19.8	16.6	9.4	10.2

NOTE.—These gage heights are the mean of four readings per day.

Rating tables for Savannah River at Augusta.

JANUARY 1, 1899, TO DECEMBER 31, 1901.

Gage height	Discharge						
<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>
3.30	1,930	6.20	4,240	9.10	8,570	14.00	17,900
3.40	1,990	6.30	4,360	9.20	8,740	14.20	18,340
3.50	2,050	6.40	4,490	9.30	8,910	14.40	18,780
3.60	2,110	6.50	4,620	9.40	9,080	14.60	19,220
3.70	2,170	6.60	4,750	9.50	9,250	14.80	19,660
3.80	2,230	6.70	4,880	9.60	9,420	15.00	20,100
3.90	2,290	6.80	5,020	9.70	9,590	15.50	21,250
4.00	2,350	6.90	5,160	9.80	9,760	16.00	22,400
4.10	2,410	7.00	5,300	9.90	9,930	16.50	23,600
4.20	2,470	7.10	5,450	10.00	10,100	17.00	24,800
4.30	2,530	7.20	5,600	10.20	10,460	17.50	26,050
4.40	2,595	7.30	5,750	10.40	10,820	18.00	27,300
4.50	2,660	7.40	5,900	10.60	11,180	18.50	28,700
4.60	2,725	7.50	6,050	10.80	11,540	19.00	30,100
4.70	2,790	7.60	6,200	11.00	11,900	19.50	31,700
4.80	2,860	7.70	6,350	11.20	12,280	20.00	33,300
4.90	2,930	7.80	6,500	11.40	12,660	21.00	36,900
5.00	3,000	7.90	6,650	11.60	13,040	22.00	41,000
5.10	3,080	8.00	6,800	11.80	13,420	23.00	45,800
5.20	3,160	8.10	6,960	12.00	13,800	24.00	52,000
5.30	3,250	8.20	7,120	12.20	14,200	25.00	60,000
5.40	3,340	8.30	7,280	12.40	14,600	26.00	68,800
5.50	3,440	8.40	7,440	12.60	15,000	27.00	77,600
5.60	3,540	8.50	7,600	12.80	15,400	28.00	86,400
5.70	3,650	8.60	7,760	13.00	15,800	29.00	95,200
5.80	3,760	8.70	7,920	13.20	16,220	30.00	104,000
5.90	3,880	8.80	8,080	13.40	16,640	31.00	112,800
6.00	4,000	8.90	8,240	13.60	17,060	32.00	121,600
6.10	4,120	9.00	8,400	13.80	17,480		

SAVANNAH DRAINAGE BASIN, STREAM FLOW

JANUARY I, 1902, TO DECEMBER 31, 1903.^a

6.80	3,400	8.40	6,400	10.00	9,600	11.60	12,860
7.00	3,740	8.60	6,800	10.20	10,000	11.80	13,280
7.20	4,100	8.80	7,200	10.40	10,400	12.00	13,700
7.40	4,460	9.00	7,600	10.60	10,800	12.20	14,120
7.60	4,840	9.20	8,000	10.80	11,200	12.40	14,540
7.80	5,220	9.40	8,400	11.00	11,600	12.60	14,960
8.00	5,600	9.60	8,800	11.20	12,020	12.80	15,380
8.20	6,000	9.80	9,200	11.40	12,440	13.00	15,800

JANUARY I TO DECEMBER 31, 1904.

3.80	1,450	5.20	2,360	10.50	9,150	17.00	23,700
3.90	1,500	5.40	2,520	11.00	10,050	17.50	25,120
4.00	1,550	5.60	2,690	11.50	10,980	18.00	26,600
4.10	1,610	5.80	2,870	12.00	11,950	18.50	28,170
4.20	1,670	6.00	3,050	12.50	12,950	19.00	29,800
4.30	1,730	6.50	3,550	13.00	14,000	19.50	31,470
4.40	1,790	7.00	4,100	13.50	15,080	20.00	33,200
4.50	1,850	7.50	4,680	14.00	16,200	21.00	36,900
4.60	1,920	8.00	5,300	14.50	17,350	22.00	41,000
4.70	1,990	8.50	5,980	15.00	18,550	23.00	45,800
4.80	2,060	9.00	6,700	15.50	19,780	24.00	52,000
4.90	2,130	9.50	7,480	16.00	21,050	25.00	60,000
5.00	2,200	10.00	8,300	16.50	22,350		

JANUARY I TO DECEMBER 31, 1905.^b

5.00	2,650	5.90	3,400	6.80	4,300	7.70	5,340
5.10	2,725	6.00	3,495	6.90	4,410	7.80	5,470
5.20	2,800	6.10	3,590	7.00	4,520	7.90	5,600
5.30	2,880	6.20	3,690	7.10	4,630	8.00	5,740
5.40	2,960	6.30	3,790	7.20	4,740	8.10	5,890
5.50	3,045	6.40	3,890	7.30	4,860	8.20	6,050
5.60	3,130	6.50	3,990	7.40	4,980	8.30	6,220
5.70	3,220	6.60	4,090	7.50	5,100		
5.80	3,310	6.70	4,190	7.60	5,220		

^a Above gage height 13.0 feet this table is the same as the table for 1899 to 1901.

^b Above gage height 8.3 feet this table is the same as that for 1903.

Rating table for Savannah River at Augusta, Ga., for 1906.

Gage height	Dis-charge						
<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>
7.60	5,100	9.30	8,040	11.00	11,800	16.00	25,900
7.70	5,250	9.40	8,250	11.20	12,260	17.00	29,400
7.80	5,400	9.50	8,460	11.40	12,740	18.00	33,200
7.90	5,560	9.60	8,670	11.60	13,220	19.00	37,300
8.00	5,720	9.70	8,890	11.80	13,700	20.00	41,700
8.10	5,880	9.80	9,110	12.00	14,200	21.00	46,400
8.20	6,040	9.90	9,330	12.20	14,700	22.00	51,500
8.30	6,210	10.00	9,550	12.40	15,220	23.00	57,000
8.40	6,380	10.10	9,770	12.60	15,740	24.00	62,900
8.50	6,550	10.20	9,990	12.80	16,260	25.00	69,000
8.60	6,720	10.30	10,210	13.00	16,800	26.00	75,500
8.70	6,900	10.40	10,430	13.20	17,340	27.00	82,300
8.80	7,080	10.50	10,650	13.40	17,900	28.00	89,500
8.90	7,260	10.60	10,880	13.60	18,460	29.00	97,000
9.00	7,450	10.70	11,110	13.80	19,020	30.00	105,000
9.10	7,640	10.80	11,340	14.00	19,600		
9.20	7,840	10.90	11,570	15.00	22,650		

NOTE.—The above table is based on discharge measurements made during 1904-1906 and earlier high-water measurements, and is well defined.

WATER POWERS OF GEORGIA

Estimated monthly discharge of Savannah River at Augusta.

[Drainage area, 7,294 square miles.]

Month	Discharge in second-feet			Run-off	
	Maximum	Minimum	Mean	Sec.-ft. per sq. mile	Depth in inches
1899 ^a					
January.....	45,320	7,600	16,034	2.20	2.54
February.....	112,800	12,850	34,891	4.78	4.93
March.....	93,440	11,900	24,804	3.41	3.93
April.....	31,700	9,420	14,386	1.97	2.20
May.....	10,820	5,750	7,640	1.05	1.21
June.....	9,590	4,360	6,090	0.83	0.92
July.....	13,230	3,250	5,148	0.71	0.82
August.....	16,430	2,350	5,126	0.70	0.81
September.....	17,690	3,160	5,554	0.76	0.85
October.....	13,120	3,000	5,611	0.77	0.89
November.....	12,470	3,340	4,807	0.66	0.73
December.....	19,000	3,000	7,043	0.97	1.12
The year.....	112,800	2,350	11,423	1.57	21.00
1900					
January.....	20,100	4,490	7,267	1.00	1.15
February.....	124,240	4,555	26,261	3.60	3.74
March.....	46,420	10,280	18,322	2.51	2.90
April.....	75,400	8,000	9,695	1.33	1.48
May.....	15,800	6,500	9,264	1.27	1.46
June.....	96,960	6,050	22,702	3.11	3.47
July.....	18,390	5,900	9,590	1.31	1.51
August.....	12,470	4,620	5,776	0.79	0.91
September.....	19,000	3,880	6,199	0.85	0.95
October.....	24,080	3,940	6,681	0.92	1.06
November.....	19,880	4,620	7,431	1.02	1.14
December.....	20,790	5,975	9,704	1.33	1.53
The year.....	124,240	3,880	11,574	1.59	21.30
1901					
January.....	43,590	7,680	14,295	1.96	2.26
February.....	75,060	7,440	16,566	2.27	2.36
March.....	86,400	6,500	15,133	2.07	2.39
April.....	111,920	10,460	25,365	3.48	3.33
May.....	77,600	7,230	15,344	2.10	2.42
June.....	76,720	8,400	19,574	2.63	2.99
July.....	16,430	6,350	8,981	1.23	1.42
August.....	92,560	5,600	26,256	3.60	4.15
September.....	111,920	8,740	20,563	2.82	3.15
October.....	14,200	7,120	9,172	1.26	1.45
November.....	7,920	7,120	7,547	1.03	1.15
December.....	107,520	7,120	13,565	2.54	2.93
The year.....	111,920	5,600	16,447	2.25	30.55
1902					
January.....	51,380	8,000	11,689	1.60	1.84
February.....	125,120	10,000	27,595	3.78	3.94
March.....	137,440	12,860	36,025	4.94	5.69
April.....	23,980	9,200	13,466	1.85	2.06
May.....	11,200	6,000	8,394	1.15	1.33
June.....	20,100	4,650	7,439	1.03	1.15
July.....	9,600	3,400	5,059	.69	.80
August.....	10,400	3,920	5,843	.80	.92
September.....	17,480	3,920	7,453	1.02	1.14
October.....	11,400	3,740	6,423	.88	1.01
November.....	14,540	3,920	5,851	.80	.89
December.....	37,310	6,800	12,700	1.74	2.01
The year.....	137,440	3,400	12,333	1.69	22.78

^a Low-water daily estimates of flow are liable to considerable error from January to August and for December, 1899. See description, p. 39.

Estimated monthly discharge of Savannah River at Augusta—Continued.

Month	Discharge in second-feet			Run-off	
	Maximum	Minimum	Mean	Sec. ft. per sq. mile	Depth in inches
1903					
January.....	18,120	7,600	10,591	1.45	1.67
February.....	130,400	8,800	39,580	5.42	5.64
March.....	98,720	13,280	32,924	4.51	5.20
April.....	49,520	11,000	19,907	2.73	3.05
May.....	15,590	7,000	10,040	1.33	1.59
June.....	64,400	8,200	18,265	2.50	2.79
July.....	16,640	4,840	8,153	1.12	1.29
August.....	26,550	4,650	9,054	1.24	1.43
September.....	13,490	3,920	5,315	.73	.81
October.....	8,000	3,400	4,179	.57	.66
November.....	8,400	3,400	4,979	.68	.76
December.....	5,600	3,740	4,405	.60	.69
The year.....	130,400	3,400	13,949	1.91	25.58
1904					
January.....	14,860	3,380	5,583	.765	.882
February.....	28,170	4,560	9,206	1.26	1.46
March.....	21,830	5,430	8,579	1.18	1.36
April.....	8,470	4,680	5,512	.756	.844
May.....	6,550	2,690	4,292	.583	.678
June.....	10,410	2,360	4,088	.560	.625
July.....	8,470	2,060	3,769	.517	.596
August.....	55,750	3,380	11,710	1.61	1.86
September.....	10,230	2,440	3,796	.620	.580
October.....	2,690	^a 1,450	2,079	.285	.329
November.....	4,100	2,060	3,015	.413	.461
December.....	10,930	2,730	4,772	.654	.754
The year.....	55,750	1,450	5,533	.759	10.33
1905					
January.....	25,800	4,300	7,075	.970	1.12
February.....	62,640	4,520	18,780	2.57	2.68
March.....	14,330	5,100	7,275	.997	1.15
April.....	8,000	4,410	5,416	.743	.829
May.....	27,530	4,090	9,764	1.34	1.54
June.....	5,890	3,690	4,704	.645	.720
July.....	43,880	4,860	12,620	1.73	1.99
August.....	17,480	3,890	7,745	1.06	1.22
September.....	8,600	2,800	4,218	.578	.645
October.....	9,200	2,650	3,916	.537	.619
November.....	5,220	2,960	3,789	.519	.579
December.....	82,880	3,590	19,270	2.64	3.04
The year.....	82,880	2,650	8,714	1.19	16.13

^a The low days in October, 1904, occurred on Sundays, when the mills were not running, and water was being held back by the dam.

Month	Discharge in second feet			Run-off	
	Maximum	Minimum	Mean	Sec. ft. per sq. mile	Depth in inches
January.....	99,400	8,890	30,900	4.23	4.83
February.....	15,200	7,450	10,600	1.45	1.51
March.....	33,700	6,900	23,300	3.19	3.63
April.....	24,600	7,080	10,800	1.48	1.65
May.....	17,600	5,250	8,020	1.10	1.27
June.....	64,700	5,100	16,100	2.21	2.47
July.....	45,900	5,400	19,500	2.67	3.03
August.....	39,500	7,080	16,200	2.22	2.56
September.....	53,700	8,040	19,600	2.68	2.99
October.....	58,200	8,250	18,700	2.56	2.95
November.....	21,100	7,080	8,820	1.21	1.35
December.....	13,200	6,900	9,580	1.31	1.51
The year.....	99,400	5,100	16,000	2.19	29.90

NOTE.—Values for 1906 are good; the records at Woodlawn are better than at Augusta.

BROAD RIVER (OF GEORGIA) NEAR CARLTON

This station was established May 27, 1897, by M. R. Hall. The gage is now maintained and the observer paid by the United States Weather Bureau. The station is located at the Seaboard Air Line bridge 3 miles east of Carlton and 2 miles above the mouth of the South Fork.

The channel above and below the station is straight for 500 feet. The right bank is high and is not liable to overflow. The left bank is low for about 400 feet, beyond which it is high and rocky. It overflows at a gage height of about 16 feet. The bed of the stream is sand and gravel and is somewhat changeable.

Discharge measurements are made from the upstream side of the deck bridge, which has two spans of 125 feet each, with trestle approaches 340 feet long on the left bank and 50 feet long on the right bank. The initial point for soundings is the end of the iron bridge on the right bank, upstream side.

A standard chain gage is fastened to the guard rail, with its bottom resting on the upstream end of the cross-ties. The center of the pulley is 39.5 feet from the initial point for soundings. The length of the chain is 54.00 feet. The gage is read once each day by S. P. Powers, jr. During the low water of October 1 to December 31, 1905, the gage was read twice each day. Bench marks were established as follows: (1) The top of the upstream iron girder under the cross-ties at a point about 40 feet from the initial point for soundings; elevation, 51 feet. (2) The top of the capstone of the right bank pier at a point under the upstream side of the end of the bridge; elevation, 30.78 feet above the datum of the gage, which is 384 feet above sea level.

SAVANNAH DRAINAGE BASIN, STREAM FLOW

Discharge measurements of Broad River (of Georgia) near Carlton.

Date	Gage height	Dis-charge	Date	Gage height	Dis-charge
1897	<i>Feet</i>	<i>Sec.-ft.</i>	1901	<i>Feet</i>	<i>Sec.-ft.</i>
May 27.....	2.10	595	January 1.....	3.55	1,497
June 22.....	1.92	580	January 22.....	2.85	991
July 28.....	2.24	920	April 23.....	3.50	1,807
August 17.....	2.25	865	August 14.....	5.25	3,173
September 27.....	1.60	353			
October 29.....	1.67	407	1902		
November 10.....	1.70	395	July 18.....	2.40	633
December 10.....	2.00	615	September 30.....	2.83	960
1898			1903		
January 29.....	2.63	995	March 21.....	4.55	2,592
February 21.....	2.00	577	May 8.....	3.10	1,242
April 20.....	2.10	667	June 11.....	3.65	1,766
June 14.....	1.56	366	August 14.....	2.70	953
July 25.....	3.75	2,165	September 16.....	4.52	2,435
September 13.....	2.50	930	October 29.....	2.16	606
October 8.....	2.50	960	December 8.....	2.20	628
	3.05	1,446	1904		
1899			March 17.....	2.62	809
February 28.....	9.05	3,281	May 5.....	2.20	581
March 1.....	5.28	3,205	July 21.....	1.48	299
April 25.....	3.65	1,341	September 6.....	2.37	737
May 15.....	2.60	919	November 15.....	1.83	460
June 28.....	2.50	1,063	1905		
September 27.....	2.00	514	January 18.....	2.50	745
November 11.....	2.05	485	Do.....	2.50	762
December 21.....	2.25	591	March 18.....	2.25	642
1900			1906		
February 16.....	4.25	2,088	March 31.....	4.71	2,560
March 30.....	3.30	1,480	July 18.....	5.95	3,993
May 3.....	4.49	2,562	October 19.....	4.10	1,970
October 17.....	2.22	661			

Daily gage height, in feet, of Broad River (of Georgia) near Carlton.

Day	July	Aug.	Sept.	Oct.	Nov.	Dec.	Day	July	Aug.	Sept.	Oct.	Nov.	Dec.
1897							1897						
1.....	1.85	1.85	1.7	1.5	1.65	2.2	17.....	1.85	3.3	1.5	1.6	1.7	2.0
2.....	1.85	1.85	2.0	1.5	2.4	2.1	18.....	3.6	2.0	1.5	1.8	1.7	2.0
3.....	1.8	1.8	2.3	1.5	2.25	2.2	19.....	4.9	1.9	1.5	2.0	1.65	2.05
4.....	1.8	1.8	1.85	1.5	1.95	2.7	20.....	6.3	2.0	1.5	2.4	1.65	2.1
5.....	2.0	1.8	1.8	1.5	1.8	2.55	21.....	5.3	1.95	1.5	2.2	1.7	2.1
6.....	2.0	1.75	1.7	1.5	1.8	2.5	22.....	3.85	2.15	1.5	2.1	1.7	2.15
7.....	1.9	2.6	1.6	1.5	1.8	2.3	23.....	2.9	2.0	1.7	1.8	1.7	2.4
8.....	2.1	2.2	1.55	1.5	1.75	2.1	24.....	2.3	1.95	1.7	1.8	1.7	2.2
9.....	2.35	2.0	1.55	1.5	1.75	2.05	25.....	2.15	1.85	1.65	1.7	1.7	2.1
10.....	2.05	2.0	1.55	1.5	1.7	2.0	26.....	2.25	1.8	1.65	1.65	1.7	2.3
11.....	2.55	1.95	1.55	1.6	1.7	1.95	27.....	2.15	1.75	1.6	1.7	3.15	2.65
12.....	2.35	1.9	1.55	2.45	1.7	1.95	28.....	2.3	1.75	1.6	1.65	2.75	2.35
13.....	1.93	1.85	1.5	2.5	1.7	1.9	29.....	2.1	1.7	1.55	1.65	2.3	2.1
14.....	1.85	1.8	1.5	2.05	1.7	2.1	30.....	1.95	1.7	1.5	1.65	2.7	2.1
15.....	1.8	1.8	1.5	1.85	1.7	2.3	31.....	1.9	1.65	1.65	2.1
16.....	1.75	4.55	1.5	1.7	1.7	2.1							

WATER POWERS OF GEORGIA

Daily gage height, in feet, of Broad River (of Georgia) near Carlton—Continued.

Day	Jan.	Feb.	Mar.	Apr.	May.	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1898												
1.....	2.05	2.25	1.9	3.6	2.2	1.6	1.4	2.1	9.1	2.15	2.35	2.75
2.....	2.0	2.15	1.9	2.75	2.15	1.6	1.35	1.95	18.35	2.1	2.35	2.55
3.....	1.95	2.1	1.95	2.45	2.05	1.6	1.35	1.8	18.53	3.2	2.3	2.8
4.....	1.95	2.05	2.1	2.3	2.05	1.6	1.4	3.0	13.38	4.85	2.3	3.9
5.....	1.95	2.0	2.15	5.25	2.0	1.55	1.8	3.85	7.88	11.2	2.3	3.5
6.....	1.95	2.05	2.05	4.45	2.0	1.5	2.85	4.0	5.0	10.1	3.2	3.1
7.....	1.95	2.05	2.0	3.0	2.0	1.45	3.5	4.2	4.6	4.85	2.4	2.85
8.....	1.95	2.0	1.95	2.6	1.85	1.45	2.6	3.4	4.5	3.25	2.35	2.7
9.....	1.95	2.0	1.9	2.45	1.95	1.4	2.3	2.5	3.5	2.9	2.35	2.6
10.....	1.9	2.0	1.9	2.4	1.9	1.35	1.95	2.2	2.9	2.7	2.65	2.55
11.....	1.9	2.0	1.85	2.45	1.9	1.3	1.7	3.05	2.85	2.6	2.45	2.55
12.....	1.9	2.0	1.85	2.35	1.9	1.45	1.6	6.2	2.7	2.5	2.4	2.5
13.....	1.9	1.95	1.85	2.25	1.85	2.0	4.9	4.05	2.55	2.45	2.45	2.5
14.....	1.9	1.95	2.35	2.3	1.85	1.6	3.2	3.5	2.45	2.4	2.95	2.45
15.....	1.9	1.95	2.8	2.3	1.85	1.5	1.85	3.0	2.4	2.3	2.9	2.4
16.....	1.9	1.9	2.4	2.25	1.8	1.5	3.55	2.7	2.35	2.25	2.75	2.4
17.....	1.85	1.9	2.45	2.15	1.8	1.5	2.55	2.35	2.35	2.25	3.0	2.45
18.....	1.85	1.95	2.35	2.1	1.8	2.4	2.0	3.25	2.25	2.7	3.0	2.45
19.....	1.85	2.05	2.25	2.05	1.85	2.35	1.8	6.95	2.25	3.35	3.55	2.45
20.....	2.15	2.0	2.1	2.1	2.1	2.15	1.8	3.6	2.2	2.65	3.4	2.7
21.....	2.55	2.0	2.05	2.05	1.85	1.8	1.7	3.0	2.2	3.6	2.9	3.0
22.....	2.35	1.95	2.0	2.0	1.8	1.6	1.65	2.85	2.25	4.45	2.7	3.65
23.....	2.2	1.95	1.95	2.0	1.8	1.55	9.0	2.55	2.4	3.65	2.7	4.05
24.....	2.9	1.9	1.95	2.95	1.95	1.55	6.0	2.25	3.45	3.0	2.6	4.85
25.....	4.9	1.9	1.95	2.75	2.1	1.5	4.2	2.1	2.55	2.65	2.55	3.65
26.....	5.1	1.85	1.9	2.3	1.8	1.5	3.1	2.45	2.35	2.55	2.5	3.1
27.....	3.3	1.9	1.9	2.6	1.75	2.3	2.6	2.6	2.25	2.45	2.45	2.8
28.....	3.05	1.95	1.85	3.3	1.65	1.55	6.4	3.0	2.2	2.4	2.4	2.7
29.....	2.7	1.95	2.6	1.6	1.5	4.6	2.7	2.2	2.4	2.75	2.65
30.....	2.5	3.35	2.35	1.6	1.45	2.7	2.5	2.15	2.45	3.0	2.6
31.....	2.35	4.4	1.6	2.35	2.35	2.4	2.65
1899												
1.....	3.1	3.45	5.2	5.8	3.0	2.6	2.3	2.4	3.3	1.9	2.15	2.35
2.....	2.95	3.0	4.1	4.45	3.0	2.55	2.25	2.35	3.0	1.9	2.1	2.4
3.....	2.75	3.75	3.8	3.6	2.95	2.5	2.2	2.25	2.5	1.9	2.1	2.3
4.....	2.7	3.7	3.6	3.65	2.95	2.5	2.2	2.2	2.3	1.9	2.05	2.3
5.....	2.65	4.3	3.95	3.7	3.0	2.45	2.2	2.2	2.2	2.0	2.05	2.25
6.....	4.45	7.2	4.2	3.45	3.2	2.4	2.2	2.15	2.15	2.2	2.05	2.2
7.....	6.45	13.18	3.65	3.6	3.15	2.4	2.25	2.1	2.1	2.15	2.05	2.2
8.....	6.4	10.6	3.45	4.4	3.0	2.5	2.4	2.1	2.1	4.3	2.05	2.2
9.....	3.9	5.45	3.4	4.2	2.95	2.6	2.3	2.1	2.1	3.4	2.05	2.2
10.....	3.3	4.3	3.35	3.6	2.95	2.45	2.4	2.1	2.1	2.5	2.05	2.2
11.....	3.8	3.75	3.3	3.5	2.9	2.4	2.3	2.15	2.5	2.35	2.05	2.2
12.....	4.05	3.6	3.3	3.4	2.85	2.6	2.25	2.1	2.1	2.25	2.05	3.4
13.....	3.7	3.45	3.25	3.3	2.8	3.7	2.2	2.15	2.5	2.2	2.05	3.6
14.....	3.45	3.35	3.5	3.3	2.8	3.0	2.2	2.05	2.0	2.15	2.05	2.95
15.....	3.75	3.3	4.4	3.25	2.75	2.4	2.15	2.0	2.0	2.1	2.1	2.5
16.....	3.5	4.4	13.88	3.25	2.75	2.5	2.1	1.95	1.95	2.1	2.1	2.45
17.....	3.5	5.05	11.3	3.2	2.7	2.65	2.1	1.9	1.95	2.1	2.05	2.35
18.....	3.25	4.45	4.7	3.15	2.7	2.65	2.25	1.9	1.95	2.1	2.05	2.3
19.....	3.1	3.3	4.5	3.25	2.65	2.55	2.15	1.9	1.95	2.1	2.05	2.3
20.....	3.0	3.5	8.1	3.2	2.65	2.45	2.1	1.9	2.05	2.1	2.05	2.3
21.....	2.9	3.55	5.2	3.15	2.6	2.4	2.1	2.0	2.0	2.1	2.05	2.25
22.....	2.85	3.6	4.0	3.1	2.65	2.35	2.05	1.95	2.0	2.05	2.05	2.25
23.....	2.95	3.5	4.15	3.05	2.7	2.3	2.2	2.0	2.0	2.05	3.65	2.2
24.....	3.05	3.3	4.55	3.1	2.65	2.3	2.25	1.95	1.95	2.05	3.45	4.4
25.....	3.0	3.2	3.75	3.2	2.6	2.3	2.15	2.0	1.95	2.05	2.45	4.3
26.....	2.95	3.15	3.6	3.5	2.6	3.7	2.45	2.05	1.95	2.05	3.6	3.0
27.....	2.85	15.78	3.5	3.2	2.6	3.0	6.5	3.95	2.0	2.05	3.7	2.6
28.....	2.8	11.15	3.45	3.15	2.55	2.8	5.3	2.45	1.95	2.05	2.9	2.6
29.....	2.8	4.2	3.1	2.55	2.3	3.5	2.1	1.95	2.05	2.55	2.6
30.....	2.75	3.7	3.1	2.5	2.5	2.8	3.5	1.9	2.1	2.4	2.5
31.....	3.1	5.0	2.7	2.5	4.1	2.15	2.45
1900												
1.....	2.4	2.3	5.5	3.1	3.4	2.6	3.5	3.7	2.3	2.1	2.4	2.4
2.....	2.4	2.3	4.9	3.1	3.2	2.5	3.3	3.3	2.5	2.1	2.4	2.4
3.....	2.4	2.3	3.85	3.0	4.7	2.8	3.4	3.6	2.5	2.1	6.5	4.2
4.....	2.35	2.3	3.3	3.1	3.9	2.9	3.2	3.6	2.3	2.2	3.5	5.0
5.....	2.35	3.3	3.15	3.0	3.2	2.9	3.0	2.5	2.2	2.3	2.8

SAVANNAH DRAINAGE BASIN, STREAM FLOW

Daily gage height, in feet, of Broad River (of Georgia) near Carlton—Continued.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1900												
6	2.3	2.95	3.0	3.0	3.1	3.0	2.9	2.5	2.2	2.5	2.6	3.8
7	2.3	2.7	3.0	2.9	3.0	4.3	2.8	2.5	2.1	3.0	2.5	3.2
8	2.3	2.65	6.5	2.8	3.0	7.7	2.8	2.4	2.1	2.6	2.4	2.8
9	2.3	2.8	6.8	2.8	2.9	7.6	2.8	2.4	2.1	2.5	2.4	2.7
10	2.4	4.0	5.1	2.7	2.9	3.8	2.7	2.3	2.1	2.4	2.4	2.6
11	2.9	6.0	3.8	3.5	2.9	3.2	2.6	2.3	2.1	2.3	2.4	2.6
12	5.85	10.5	3.3	3.9	2.8	3.1	2.9	2.3	2.0	2.3	2.4	2.5
13	4.9	22.2	3.2	3.9	2.8	3.1	3.05	4.0	2.0	2.7	2.3	2.5
14	3.3	16.9	3.1	3.3	2.8	3.8	3.55	2.5	2.1	2.6	2.3	2.8
15	2.95	8.0	3.0	3.1	2.7	3.1	3.0	2.4	5.5	2.4	2.3	2.6
16	2.75	4.3	4.2	3.0	2.7	3.5	2.9	2.4	5.0	2.3	2.3	2.5
17	2.65	3.7	3.8	2.9	2.7	4.3	2.8	2.5	4.0	2.2	2.3	2.4
18	3.15	3.3	3.3	3.9	2.7	5.6	2.7	2.5	2.8	2.2	2.3	2.4
19	3.6	3.2	3.1	7.5	3.0	4.9	2.6	2.6	2.5	2.2	2.4	2.4
20	3.75	3.1	4.6	6.7	2.9	3.5	2.6	2.4	2.4	2.2	2.4	2.8
21	3.7	3.1	4.1	3.0	2.7	3.1	2.5	2.3	2.3	2.2	2.4	3.8
22	2.85	3.8	3.7	12.2	2.7	3.0	2.5	2.2	2.3	2.1	2.5	3.3
23	2.7	3.65	3.4	5.8	2.7	4.2	2.5	2.3	2.3	4.2	2.4	3.0
24	2.6	3.2	3.6	6.5	4.0	13.0	3.0	2.2	2.3	5.0	2.4	2.9
25	2.5	3.65	4.7	7.3	3.2	12.6	2.7	2.2	2.2	3.1	3.6	2.8
26	2.45	3.6	6.5	5.1	2.9	7.0	2.9	2.6	2.2	4.0	3.6	2.6
27	2.45	3.2	5.3	3.9	2.8	5.6	3.4	2.5	2.2	3.8	2.8	2.5
28	2.4	3.0	4.0	3.7	2.7	4.6	3.7	2.2	2.2	3.1	2.6	2.5
29	2.4	3.5	3.5	2.7	4.0	3.4	2.2	2.2	2.7	2.5	2.5
30	2.35	3.3	3.5	2.6	4.5	3.3	2.9	2.1	2.5	2.5	2.5
31	2.3	3.25	2.6	3.9	2.2	2.5	3.8
1901												
1	3.6	3.2	2.6	3.6	2.7	4.3	3.9	2.4	5.0	2.9	2.5	2.5
2	3.2	2.9	2.6	6.9	2.6	3.9	3.1	2.3	3.9	2.9	2.5	2.5
3	3.6	3.8	2.6	11.95	2.6	3.3	3.0	2.3	3.5	4.3	2.5	3.0
4	3.5	7.9	2.6	9.3	2.6	3.0	2.9	2.3	3.1	2.9	2.5	3.4
5	3.3	6.8	2.6	4.5	2.5	2.9	2.8	2.3	3.0	2.8	2.6	3.4
6	2.3	4.1	2.6	3.9	2.9	2.8	2.7	2.5	2.9	2.7	2.5	2.7
7	2.7	3.5	2.6	3.6	2.9	3.7	2.7	4.4	2.9	2.7	2.5	2.7
8	2.7	3.3	2.5	3.4	2.8	3.0	2.7	4.0	2.8	2.6	2.5	2.6
9	2.6	4.2	2.5	3.3	2.8	2.8	2.6	3.0	2.8	2.6	2.5	2.6
10	2.6	4.8	2.5	3.2	2.7	2.7	2.6	2.6	2.7	2.6	2.5	2.9
11	5.9	3.8	4.4	3.1	2.7	2.7	2.5	4.3	2.7	2.5	2.5	2.8
12	11.4	3.5	4.1	3.1	2.7	3.1	2.5	3.2	3.0	2.5	2.5	2.7
13	11.5	3.2	3.2	3.1	2.7	2.9	2.4	2.8	2.8	3.0	2.6	2.6
14	5.0	3.1	3.0	5.5	2.6	4.6	2.4	5.5	2.7	3.0	2.6	2.7
15	4.1	3.0	2.9	4.9	2.6	11.1	2.6	6.0	2.7	2.8	2.5	5.3
16	3.4	2.9	2.8	3.9	2.6	11.2	2.6	10.0	2.75	2.7	2.5	4.2
17	3.4	2.9	2.7	3.5	2.6	5.0	4.6	8.4	6.6	2.7	2.5	3.1
18	3.0	2.9	2.7	3.4	3.0	3.9	3.2	5.4	14.8	2.6	2.5	2.9
19	3.0	2.8	2.6	3.6	3.5	3.6	4.6	3.9	3.6	2.6	2.6	2.8
20	2.9	2.8	2.6	4.4	5.7	3.3	6.3	4.3	4.6	2.6	2.6	2.7
21	2.3	2.7	3.0	4.3	5.7	3.2	3.5	6.7	3.6	2.6	2.7	2.7
22	2.3	2.7	2.9	4.0	7.9	3.2	2.8	5.4	3.3	2.6	2.6	2.6
23	2.3	2.7	2.8	3.5	7.7	3.8	2.7	7.3	3.1	2.5	2.6	2.6
24	2.9	2.8	2.8	3.3	4.0	3.6	2.6	9.0	3.0	2.5	2.6	3.1
25	3.6	2.8	2.8	3.2	3.4	4.8	2.5	5.1	2.9	2.5	2.6	3.0
26	3.1	2.7	14.25	3.2	3.5	4.0	2.5	4.3	2.9	2.5	2.6	3.0
27	2.9	2.7	13.35	3.2	3.3	3.8	3.2	5.5	2.8	2.5	2.5	3.0
28	2.9	2.7	3.4	3.2	3.1	3.7	2.8	3.4	2.9	2.5	2.5	4.0
29	2.3	4.2	3.0	3.0	3.6	2.6	6.3	3.0	2.5	2.5	14.2
30	2.3	3.6	2.3	2.9	5.9	2.6	6.5	2.9	2.5	2.5	19.9
31	3.5	3.6	2.9	2.5	4.9	2.5	12.4
1902												
1	4.7	7.5	23.2	4.3	3.3	2.9	2.2	2.3	2.3	3.9	2.3	4.3
2	4.0	23.2	9.5	4.0	3.4	2.8	2.2	2.2	2.2	3.6	2.2	3.6
3	3.7	17.1	5.8	3.8	3.3	2.7	2.3	3.1	2.2	2.7	2.2	6.6
4	3.5	6.3	4.8	3.8	3.3	2.7	2.8	3.0	2.2	2.6	2.1	6.4
5	3.4	5.7	4.4	3.7	3.2	2.6	2.6	2.7	2.2	3.6	2.2	4.5
6	3.3	4.1	4.2	3.7	3.7	2.6	2.3	2.5	2.2	3.0	2.5	4.0
7	3.2	3.8	3.9	3.7	3.3	2.6	2.2	2.3	2.1	2.65	2.5	3.3
8	3.1	3.5	3.8	3.6	3.2	2.8	2.4	2.2	2.1	2.45	2.3	3.0
9	3.1	3.4	4.0	3.5	3.2	2.6	2.8	2.1	3.3	2.4	2.3	2.9
10	3.0	3.4	3.9	3.4	3.1	2.5	2.4	2.1	4.7	2.3	2.3	2.7

WATER POWERS OF GEORGIA

Daily gage height, in feet, of Broad River (of Georgia) near Carlton—Continued.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1902												
11.....	3.0	3.3	3.8	3.4	3.1	2.5	2.4	2.1	3.6	2.5	2.3	2.7
12.....	2.9	3.3	3.8	3.3	3.1	2.5	2.7	2.6	2.6	3.5	2.3	2.6
13.....	2.9	3.3	4.6	3.3	3.0	2.5	2.6	2.3	2.8	2.9	2.2	2.8
14.....	2.9	3.2	4.3	3.3	3.4	2.5	2.4	5.0	2.8	2.7	2.2	2.8
15.....	2.9	3.3	4.4	3.3	3.1	2.7	4.8	4.8	2.6	2.8	2.2	2.8
16.....	2.9	3.5	5.1	3.8	3.0	3.3	3.4	3.0	2.5	2.5	2.2	2.9
17.....	2.8	3.6	8.5	4.0	3.0	2.3	2.6	3.5	2.3	2.5	2.2	4.3
18.....	2.8	3.5	6.0	4.6	3.0	2.6	2.4	3.0	2.3	2.4	2.9	3.6
19.....	2.9	3.4	4.2	3.6	3.0	2.6	2.3	2.4	2.8	2.3	2.9	3.1
20.....	3.0	3.5	3.9	3.6	3.0	3.0	2.3	2.9	2.4	2.3	2.5	2.9
21.....	3.0	3.6	3.7	3.5	3.1	2.7	2.3	2.9	2.5	2.3	2.4	2.8
22.....	3.1	4.0	3.7	3.4	3.0	2.6	2.3	2.3	2.3	2.3	2.4	3.8
23.....	2.9	3.6	3.6	3.3	3.0	2.5	2.2	2.5	2.2	2.3	2.4	3.4
24.....	2.3	3.5	3.6	3.3	2.9	2.4	2.2	2.4	2.2	2.3	2.3	3.1
25.....	2.9	4.4	3.5	3.3	2.9	2.4	2.3	2.3	5.9	2.2	2.3	3.0
26.....	2.8	4.6	3.5	3.2	2.8	2.4	2.3	2.3	8.2	2.2	4.6	2.8
27.....	2.8	3.9	3.5	3.2	2.8	2.4	2.2	2.2	4.6	2.3	4.0	2.8
28.....	3.0	24.5	3.9	8.1	2.7	2.4	3.1	2.4	3.4	2.5	3.9	2.6
29.....	4.4	15.0	3.1	2.7	2.3	3.3	3.6	3.6	2.3	3.0	2.6
30.....	3.9	12.0	3.2	2.6	2.3	2.3	3.1	3.3	2.3	2.6	3.3
31.....	4.1	6.5	2.6	2.3	2.5	2.3	3.3
1903												
1.....	3.0	3.1	7.9	5.8	3.2	4.3	3.0	3.1	2.2	2.2	2.3	2.2
2.....	3.1	3.0	5.2	4.4	3.1	4.6	2.9	2.7	2.2	2.2	2.3	2.2
3.....	3.9	3.6	4.0	4.2	3.1	6.0	3.0	3.1	2.2	2.2	2.9	2.2
4.....	3.7	7.0	3.7	4.4	3.7	4.5	3.4	3.5	2.1	2.2	3.1	2.2
5.....	3.4	7.8	3.6	4.0	3.5	4.6	2.9	3.7	2.1	2.2	3.0	2.2
6.....	3.1	5.2	3.7	3.8	3.2	6.1	2.8	3.2	2.1	2.2	3.1	2.3
7.....	3.0	3.8	3.7	3.7	3.1	3.0	3.3	3.6	2.2	2.2	2.5	2.3
8.....	2.8	17.6	3.8	4.1	3.1	6.0	2.9	2.5	2.2	2.3	2.4	2.2
9.....	2.3	11.2	3.6	4.8	3.1	4.8	2.8	2.4	2.2	2.4	2.3	2.2
10.....	2.3	5.6	4.3	4.1	3.0	4.4	2.7	2.4	2.2	2.3	2.3	2.3
11.....	2.9	6.5	5.7	3.8	3.0	3.6	2.7	5.3	2.1	2.2	2.3	2.2
12.....	4.9	10.4	5.8	3.6	2.9	4.3	3.2	3.3	2.1	2.2	2.3	2.2
13.....	4.7	7.5	4.6	3.6	3.0	3.9	5.5	2.7	2.1	2.2	2.3	2.3
14.....	3.5	4.4	3.9	6.8	3.2	3.3	4.9	2.7	2.1	2.2	2.3	2.5
15.....	3.2	4.0	3.7	5.5	3.6	3.2	3.3	4.7	3.2	2.2	2.3	2.3
16.....	3.1	3.8	3.6	4.0	3.3	3.1	2.9	4.0	4.4	2.2	2.3	2.3
17.....	2.9	13.1	3.4	3.7	3.1	3.1	2.8	2.9	4.3	2.3	2.3	2.2
18.....	2.9	12.7	3.4	3.6	3.1	3.0	2.7	7.3	3.2	2.6	2.4	2.2
19.....	2.3	4.9	3.3	3.5	3.0	3.0	2.7	4.0	2.6	2.4	2.3	2.1
20.....	2.3	4.1	3.2	3.5	3.0	2.9	2.6	3.6	2.5	2.3	2.3	2.2
21.....	2.9	3.8	4.1	3.5	3.2	3.1	2.6	2.8	2.5	2.3	2.3	2.5
22.....	2.8	3.7	5.5	3.4	3.0	2.9	2.5	2.7	2.4	2.2	2.3	2.4
23.....	2.7	3.5	13.2	3.4	3.0	2.3	2.5	2.6	2.4	2.2	2.2	2.3
24.....	2.9	3.4	21.0	3.3	2.9	2.3	2.5	2.5	2.4	2.2	2.2	2.2
25.....	3.1	3.3	10.7	3.3	2.9	2.7	2.4	2.5	2.3	2.2	2.2	2.3
26.....	3.0	3.3	5.0	3.4	2.8	2.7	2.4	2.5	2.3	2.2	2.2	2.7
27.....	2.9	3.2	4.4	3.4	2.8	3.1	2.4	2.4	2.3	2.2	2.2	2.5
28.....	3.1	6.0	4.2	3.3	2.9	5.6	2.3	2.4	2.3	2.1	2.2	2.4
29.....	3.7	5.4	3.3	2.8	3.6	2.4	2.4	2.2	2.1	2.2	2.3
30.....	4.3	9.0	3.2	2.9	3.3	2.7	2.3	2.2	2.1	2.2	2.2
31.....	3.4	9.0	4.0	2.8	2.3	2.2	2.2
1904												
1.....	2.2	2.6	2.6	2.5	2.2	2.4	2.1	1.6	1.9	1.5	1.6	1.9
2.....	2.2	2.5	2.6	2.5	2.2	2.5	2.0	2.6	1.9	1.5	1.6	2.0
3.....	2.3	2.4	2.8	2.5	2.1	2.1	1.9	2.4	1.8	1.5	1.7	2.5
4.....	2.3	2.4	2.3	2.4	2.1	2.0	1.8	2.0	2.4	1.5	1.9	2.1
5.....	2.2	2.3	2.6	2.4	2.1	1.9	1.7	1.9	3.2	1.5	2.1	2.4
6.....	2.2	2.3	2.6	2.4	2.1	1.9	1.7	2.3	2.8	1.5	2.0	4.2
7.....	2.2	2.5	3.7	2.6	2.2	2.1	1.6	2.5	2.7	1.5	1.8	3.2
8.....	2.2	3.4	5.7	2.6	2.2	2.2	1.6	6.5	2.1	1.5	1.7	2.6
9.....	2.2	3.1	4.8	2.7	3.5	1.9	4.2	10.4	2.0	1.5	1.7	2.4
10.....	2.2	3.0	3.4	2.5	3.0	1.9	2.7	6.3	1.9	1.5	1.6	2.2
11.....	2.3	3.3	3.0	2.5	2.4	1.8	2.0	4.2	1.8	1.5	1.6	2.3
12.....	2.3	3.0	2.3	2.4	2.2	1.8	2.0	3.3	1.8	1.5	1.6	2.1
13.....	2.4	2.7	2.7	2.4	2.2	1.8	2.0	3.0	1.8	1.5	2.0	2.0
14.....	2.4	2.6	2.9	2.3	2.1	1.8	1.8	2.7	1.7	1.5	2.2	2.0
15.....	2.3	2.6	3.0	2.3	2.1	1.7	1.7	2.5	1.7	1.5	2.0	2.0

SAVANNAH DRAINAGE BASIN, STREAM FLOW

Daily gage height, in feet, of Broad River (of Georgia) near Carlton—Continued.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1904												
16.....	2.2	2.5	2.8	2.3	2.1	1.7	1.6	2.6	1.7	1.5	1.9	2.0
17.....	2.3	2.5	2.7	2.4	2.0	1.7	2.1	2.4	1.6	1.5	1.9	2.0
18.....	2.5	2.4	2.6	2.4	2.0	1.6	1.8	2.2	1.6	1.5	1.8	2.0
19.....	2.4	2.4	2.6	2.3	2.0	1.8	1.6	2.1	1.6	1.5	1.8	2.0
20.....	2.2	3.6	2.5	2.3	2.0	1.7	1.5	4.2	1.6	1.5	1.7	1.9
21.....	2.2	3.3	2.5	2.4	1.9	2.5	1.5	2.9	1.6	1.5	1.7	1.9
22.....	2.2	4.8	4.0	2.3	1.9	2.1	1.6	2.1	2.1	1.5	1.7	1.9
23.....	3.8	4.6	3.4	2.3	1.9	2.0	1.9	2.0	1.6	1.5	1.9	1.9
24.....	3.2	3.7	4.3	2.2	1.9	1.7	1.3	1.9	1.6	1.5	2.3	1.9
25.....	2.7	3.4	3.5	2.2	1.8	1.7	1.6	1.9	1.6	1.5	2.0	2.0
26.....	2.5	2.9	3.3	2.3	1.8	1.6	2.6	1.9	1.6	1.6	1.9	2.1
27.....	2.4	2.8	3.0	2.4	1.8	1.6	1.9	3.1	1.6	1.7	1.8	2.1
28.....	2.4	2.7	2.9	2.3	1.8	1.6	1.7	3.3	1.6	1.7	1.8	3.3
29.....	2.5	2.6	2.7	2.2	1.8	1.9	3.0	2.9	1.6	1.6	1.7	3.0
30.....	2.6	2.6	2.2	3.0	2.3	1.8	2.2	1.5	1.6	1.7	2.5
31.....	2.5	2.6	3.4	1.6	2.0	1.6	2.3
1905												
1.....	2.2	2.0	2.5	2.1	2.2	2.3	6.3	1.7	1.6	1.4	1.65	1.7
2.....	2.2	2.0	2.5	2.1	2.1	2.1	4.3	1.6	3.0	1.5	1.65	1.7
3.....	2.2	2.0	2.5	2.1	2.2	2.1	3.0	1.6	2.4	1.6	1.65	9.4
4.....	2.1	2.0	2.4	2.1	5.3	2.0	2.2	1.6	2.0	2.0	1.6	8.4
5.....	2.0	2.0	2.4	2.2	3.4	2.0	2.4	1.6	1.7	2.2	1.6	4.2
6.....	2.0	2.2	2.4	2.3	4.9	1.9	8.2	1.6	1.7	1.7	1.6	3.5
7.....	2.6	2.6	2.3	2.2	6.8	1.9	3.6	1.6	1.7	1.6	1.7	3.0
8.....	2.7	3.0	2.3	2.1	6.9	1.9	2.3	1.6	1.6	1.5	1.65	2.5
9.....	2.4	4.0	2.3	2.2	4.4	1.8	2.0	3.1	1.6	1.5	1.65	7.0
10.....	2.2	5.7	2.5	2.2	3.4	1.8	2.0	2.2	1.6	1.6	1.8	7.9
11.....	2.2	5.4	2.4	2.1	2.8	1.8	3.9	2.7	1.6	2.0	2.0	5.4
12.....	2.3	4.4	2.5	2.1	2.5	1.7	3.6	3.2	1.6	2.6	1.8	4.3
13.....	6.1	6.6	2.6	2.2	2.4	2.1	5.0	4.0	2.3	2.2	1.7	3.3
14.....	6.0	6.4	2.5	2.2	2.3	1.9	4.4	2.6	1.9	1.8	1.7	2.9
15.....	3.5	4.7	2.4	2.1	2.2	3.0	3.8	2.6	1.7	1.7	1.7	3.0
16.....	3.0	3.3	2.4	2.1	2.3	2.0	3.0	2.4	1.6	1.7	1.6	3.0
17.....	2.7	3.0	2.3	2.1	2.7	2.0	2.5	2.0	1.6	1.7	1.6	2.7
18.....	2.6	2.9	2.2	2.1	2.5	2.0	2.3	2.0	1.5	1.65	1.6	2.6
19.....	2.4	2.8	2.2	2.0	2.4	2.0	2.1	2.2	1.5	1.7	1.6	2.6
20.....	2.6	3.0	2.2	2.0	2.2	2.7	2.6	2.0	1.5	1.7	1.65	4.3
21.....	2.5	7.8	2.3	2.0	2.2	1.9	2.0	1.9	1.5	1.7	1.95	7.3
22.....	2.4	8.5	2.3	2.0	2.2	2.2	2.5	1.9	1.5	1.6	1.9	5.7
23.....	2.2	5.0	2.3	2.0	2.4	2.0	2.3	1.8	1.5	1.6	1.7	3.0
24.....	2.2	3.7	2.3	2.0	4.5	2.0	2.0	2.2	1.4	1.6	1.7	2.5
25.....	2.1	3.3	2.3	2.0	4.4	1.9	1.8	2.2	1.4	1.6	1.7	2.4
26.....	2.1	3.0	2.2	2.0	2.9	1.9	1.8	2.8	1.4	1.8	2.1	2.3
27.....	2.1	2.8	2.2	2.0	2.8	1.7	1.3	2.6	1.4	2.0	2.1	2.2
28.....	2.1	2.7	2.1	2.0	2.7	1.7	1.7	2.2	1.4	1.8	1.95	2.2
29.....	2.0	2.1	2.0	2.8	1.7	1.7	1.9	1.4	1.75	1.8	3.3
30.....	2.0	2.1	2.1	2.6	1.6	1.7	1.7	1.4	1.7	1.75	2.9
31.....	2.0	2.1	2.3	1.7	1.7	1.7	2.6
1906												
1.....	2.6	3.5	2.4	4.2	2.8	2.4	2.4	3.8	3.7	3.6	2.6	2.5
2.....	2.5	3.3	2.4	3.5	2.7	2.4	2.4	3.3	3.0	3.9	2.6	2.5
3.....	4.6	3.0	2.5	3.5	2.7	2.6	2.6	3.2	2.9	5.5	2.6	2.5
4.....	14.3	2.9	3.0	3.2	3.7	3.4	3.1	3.2	2.7	6.0	2.5	2.5
5.....	12.9	2.9	2.9	3.2	3.0	2.7	2.3	4.2	2.7	4.7	2.5	2.5
6.....	7.0	3.0	2.5	3.1	2.8	2.6	2.6	4.4	2.6	4.0	2.5	2.5
7.....	3.5	3.0	2.5	3.0	3.3	2.5	3.0	3.0	2.3	3.8	2.5	2.6
8.....	3.3	2.8	3.3	3.0	4.0	2.5	4.3	2.8	2.6	3.6	2.5	2.6
9.....	3.1	2.7	5.5	3.0	3.5	2.4	6.3	2.6	2.6	3.4	2.5	2.5
10.....	3.0	2.6	3.9	3.1	3.0	2.4	6.0	2.5	2.6	3.0	2.5	2.5

Daily gage height, in feet, of Broad River (of Georgia) near Carlton—Continued.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1906												
11.....	3.0	2.6	3.2	3.0	2.8	3.1	5.0	2.5	2.6	3.0	2.5	4.6
12.....	3.4	2.6	3.0	3.0	2.7	2.9	3.5	2.4	3.9	3.0	2.5	4.4
13.....	4.0	2.6	3.0	2.9	2.7	4.4	3.3	2.5	3.2	2.9	2.5	3.4
14.....	3.0	2.5	2.8	2.9	2.6	5.3	3.6	4.1	3.0	2.8	2.5	3.0
15.....	2.9	2.5	11.0	3.7	2.5	4.5	4.2	3.4	2.3	2.8	2.6	3.0
16.....	2.8	2.5	14.0	3.5	2.5	3.8	5.5	3.1	2.5	2.6	2.6	2.8
17.....	2.8	2.5	8.3	3.1	2.5	5.6	7.9	2.8	2.5	2.6	2.6	2.8
18.....	2.7	2.5	4.2	3.0	2.5	4.0	6.4	2.6	4.0	2.6	3.0	3.0
19.....	2.7	2.5	8.8	2.9	2.5	3.6	6.2	3.2	4.5	4.0	3.1	3.0
20.....	2.6	2.5	15.7	2.8	2.5	2.8	5.2	7.9	3.2	3.6	3.1	4.0
21.....	2.6	2.6	11.2	2.8	2.4	2.7	4.6	6.4	5.0	2.9	3.0	3.8
22.....	2.8	2.7	6.0	2.8	2.4	2.6	4.1	5.8	4.0	2.9	3.0	3.6
23.....	19.0	2.5	3.8	2.7	2.4	2.6	5.0	3.5	3.3	2.8	2.8	3.1
24.....	9.8	2.5	3.6	2.7	2.4	2.5	4.2	3.1	3.0	2.8	2.7	3.0
25.....	6.0	2.5	3.5	2.7	2.3	2.5	3.6	2.8	3.9	2.7	2.6	3.0
26.....	4.4	2.5	3.3	2.7	2.8	2.5	3.2	3.2	4.7	2.6	2.6	2.8
27.....	6.9	2.5	3.3	2.8	4.1	2.9	2.9	3.1	3.8	2.6	2.6	2.8
28.....	5.3	2.5	3.3	3.9	3.7	2.7	3.0	3.6	3.2	2.6	2.5	2.9
29.....	4.0	4.0	3.0	3.2	2.6	3.8	4.6	3.6	2.6	2.5	3.0
30.....	3.8	4.6	3.0	2.6	2.6	7.6	4.6	4.0	2.6	2.5	3.0
31.....	3.5	4.8	2.5	4.6	4.0	2.6	3.6

SAVANNAH DRAINAGE BASIN, STREAM FLOW

Rating tables for Broad River (of Georgia) near Carlton.

JULY 1 TO DECEMBER 31, 1897.^a

Gage height	Dis-charge						
<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>
1.50	315	2.50	973	3.50	1,633	4.50	2,333
1.60	360	2.60	1,044	3.60	1,754	4.60	2,464
1.70	410	2.70	1,115	3.70	1,825	4.70	2,535
1.80	476	2.80	1,186	3.80	1,896	4.80	2,606
1.90	547	2.90	1,257	3.90	1,967	4.90	2,677
2.00	618	3.00	1,328	4.00	2,038	5.00	2,748
2.10	689	3.10	1,399	4.10	2,109	5.50	3,100
2.20	760	3.20	1,470	4.20	2,180	6.00	3,460
2.30	831	3.30	1,541	4.30	2,251		
2.40	902	3.40	1,612	4.40	2,322		

JANUARY 1 TO DECEMBER 31, 1898.^b

1.40	320	3.20	1,600	5.00	3,364	8.40	6,696
1.50	352	3.30	1,698	5.20	3,560	8.60	6,892
1.60	385	3.40	1,796	5.40	3,756	8.80	7,088
1.70	422	3.50	1,894	5.60	3,952	9.00	7,284
1.80	480	3.60	1,992	5.80	4,148	9.20	7,480
1.90	527	3.70	2,090	6.00	4,344	9.40	7,676
2.00	577	3.80	2,188	6.20	4,540	9.60	7,872
2.10	635	3.90	2,286	6.40	4,736	9.80	8,068
2.20	700	4.00	2,384	6.60	4,932	10.00	8,264
2.30	775	4.10	2,482	6.80	5,128	11.00	9,244
2.40	850	4.20	2,580	7.00	5,324	12.00	10,224
2.50	940	4.30	2,678	7.20	5,520	13.00	11,204
2.60	1,080	4.40	2,776	7.40	5,716	14.00	12,184
2.70	1,122	4.50	2,874	7.60	5,912	15.00	13,164
2.80	1,215	4.60	2,972	7.80	6,108	16.00	14,144
2.90	1,310	4.70	3,070	8.00	6,304	17.00	15,124
3.00	1,405	4.80	3,168	8.20	6,500	18.00	16,104
3.10	1,502	4.90	3,266				

JANUARY 1, 1899, TO DECEMBER 31, 1901.^c

1.90	490	3.70	1,760	6.00	4,160	10.00	9,550
2.00	540	3.80	1,840	6.20	4,420	10.50	10,225
2.10	600	3.90	1,920	6.40	4,690	11.00	10,900
2.20	660	4.00	2,000	6.60	4,960	11.50	11,575
2.30	730	4.10	2,090	6.80	5,230	12.00	12,250
2.40	800	4.20	2,180	7.00	5,500	12.50	12,925
2.50	870	4.30	2,270	7.20	5,770	13.00	13,600
2.60	940	4.40	2,360	7.40	6,040	13.50	14,275
2.70	1,010	4.50	2,450	7.60	6,310	14.00	14,950
2.80	1,080	4.60	2,550	7.80	6,580	15.00	16,300
2.90	1,150	4.70	2,650	8.00	6,850	16.00	17,650
3.00	1,220	4.80	2,750	8.20	7,120	17.00	19,000
3.10	1,295	4.90	2,850	8.40	7,390	18.00	20,350
3.20	1,370	5.00	2,950	8.60	7,660	19.00	21,700
3.30	1,445	5.20	3,160	8.80	7,930	20.00	23,050
3.40	1,520	5.40	3,390	9.00	8,200	21.00	24,400
3.50	1,600	5.60	3,640	9.50	8,875	22.00	25,750
3.60	1,680	5.80	3,900				

a Above gage height 1.80 feet the rating curve is a tangent, the difference being 71 per tenth.

b Above gage height 3.10 feet the rating curve is a tangent, the difference being 98 per tenth.

c Above gage height 6.20 feet the rating curve is a tangent, the difference being 135 per tenth.

WATER POWERS OF GEORGIA

Rating tables for Broad River (of Georgia) near Carlton—Continued.

JANUARY 1 TO DECEMBER 31, 1902.^a

Gage height	Discharge						
<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>
2.10	420	2.70	870	3.30	1,365	3.90	1,890
2.20	490	2.80	950	3.40	1,450	4.00	1,980
2.30	565	2.90	1,030	3.50	1,535	4.10	2,070
2.40	640	3.00	1,110	3.60	1,620	4.20	2,165
2.50	715	3.10	1,195	3.70	1,710	4.30	2,260
2.60	790	3.20	1,280	3.80	1,800	4.40	2,355

JANUARY 1 TO DECEMBER 31, 1903.^b

2.10	575	2.80	1,030	3.50	1,570	4.20	2,180
2.20	630	2.90	1,105	3.60	1,655	4.30	2,270
2.30	690	3.00	1,180	3.70	1,740	4.40	2,365
2.40	755	3.10	1,255	3.80	1,825	4.50	2,460
2.50	820	3.20	1,330	3.90	1,910	4.60	2,555
2.60	890	3.30	1,410	4.00	2,000	4.70	2,650
2.70	960	3.40	1,490	4.10	2,090	4.80	2,750

JANUARY 1, 1904, TO DECEMBER 31, 1905.

1.40	270	2.60	850	3.80	1,770	5.80	3,340
1.50	305	2.70	920	3.90	1,860	6.00	4,100
1.60	340	2.80	990	4.00	1,950	6.50	4,750
1.70	380	2.90	1,060	4.20	2,130	7.00	5,400
1.80	420	3.00	1,130	4.40	2,320	7.50	6,100
1.90	460	3.10	1,200	4.60	2,520	8.00	6,800
2.00	510	3.20	1,280	4.80	2,720	8.50	7,500
2.10	560	3.30	1,360	5.00	2,920	9.00	8,200
2.20	610	3.40	1,440	5.20	3,140	9.50	8,950
2.30	670	3.50	1,520	5.40	3,360	10.00	9,700
2.40	730	3.60	1,600	5.60	3,600	10.50	10,450
2.50	790	3.70	1,680				

^a Above gage height 4.40 feet the above table is the same as the 1899 to 1901 table.^b Above gage height 4.80 feet this rating table is the same as the 1899 to 1901 table.

JANUARY 1, 1906, TO DECEMBER 31, 1906.

<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>
2.30	645	3.60	1,535	4.90	2,770	9.00	3,220
2.40	695	3.70	1,620	5.00	2,880	10.00	3,760
2.50	750	3.80	1,705	5.20	3,100	11.00	4,360
2.60	805	3.90	1,790	5.40	3,325	12.00	5,000
2.70	865	4.00	1,880	5.60	3,560	13.00	5,700
2.80	930	4.10	1,970	5.80	3,800	14.00	6,400
2.90	1,000	4.20	2,065	6.00	4,050	15.00	7,100
3.00	1,070	4.30	2,160	6.20	4,300	16.00	7,800
3.10	1,140	4.40	2,255	6.40	4,560	17.00	8,500
3.20	1,215	4.50	2,350	6.60	4,820	18.00	9,200
3.30	1,290	4.60	2,450	6.80	5,090	19.00	9,900
3.40	1,370	4.70	2,555	7.00	5,360		
3.50	1,450	4.80	2,660	8.00	6,760		

NOTE.—The above table is based on discharge measurements made during 1904-1906 and is well defined below gage height 6 feet. Above gage height 6 feet it is based on one high-water measurement in 1899.

SAVANNAH DRAINAGE BASIN, STREAM FLOW

Estimated monthly discharge of Broad River (of Georgia) near Carlton.

[Drainage area, 762 square miles.]


Month	Discharge in second-feet			Run-off	
	Maximum	Minimum	Mean	Sec.-ft.-per sq. mile	Depth in inches
1897					
July.....	3,671	443	979	1.28	1.48
August.....	2,423	385	641	0.84	0.97
September.....	831	315	380	0.50	0.56
October.....	973	315	468	0.61	0.70
November.....	1,434	385	547	0.72	0.80
December.....	1,115	547	748	0.98	1.13
1898					
January.....	3,462	505	887	1.16	1.34
February.....	738	505	575	0.75	0.78
March.....	2,776	505	730	1.00	1.15
April.....	3,609	577	1,073	1.41	1.57
May.....	700	385	524	0.69	0.79
June.....	850	300	422	0.55	0.61
July.....	7,284	300	1,455	1.91	2.20
August.....	5,275	480	1,533	2.01	2.32
September.....	16,937	666	2,961	3.89	4.34
October.....	9,440	632	1,786	2.34	2.70
November.....	1,943	775	1,099	1.44	1.61
December.....	3,217	850	1,319	1.73	1.99
The year.....	16,937	300	1,197	1.57	21.40
1899					
January.....	4,757	875	1,599	2.10	2.42
February.....	17,380	1,220	3,602	4.73	4.98
March.....	14,815	1,407	2,870	3.77	4.35
April.....	3,900	1,257	1,622	2.13	2.38
May.....	1,870	870	1,072	1.41	1.63
June.....	1,760	730	957	1.26	1.41
July.....	4,825	570	943	1.24	1.43
August.....	2,090	490	721	0.95	1.09
September.....	1,840	490	654	0.86	0.95
October.....	2,270	490	684	0.90	1.04
November.....	1,760	570	771	1.01	1.13
December.....	2,360	660	940	1.23	1.42
The year.....	17,380	490	1,370	1.80	24.18
1900					
January.....	3,965	730	1,146	1.50	1.73
February.....	26,020	730	3,468	4.55	4.74
March.....	5,230	1,220	2,171	2.85	3.29
April.....	12,520	1,010	2,651	3.43	3.88
May.....	2,650	940	1,168	1.53	1.76
June.....	13,600	870	2,994	3.93	4.38
July.....	1,920	870	1,227	1.61	1.86
August.....	2,000	660	958	1.26	1.45
September.....	3,510	540	908	1.19	1.33
October.....	2,950	600	1,001	1.31	1.51
November.....	4,825	730	1,043	1.37	1.53
December.....	2,950	800	1,155	1.52	1.75
The year.....	26,020	540	1,658	2.18	29.21
1901					
January.....	11,575	940	2,093	2.75	3.17
February.....	6,715	1,010	1,697	2.23	2.32
March.....	15,288	870	2,266	2.97	3.42
April.....	12,182	1,080	2,421	3.13	3.55
May.....	6,715	870	1,673	2.20	2.54
June.....	11,170	1,010	2,354	3.09	3.44
July.....	4,550	800	1,270	1.67	1.93
August.....	9,550	730	3,196	4.19	4.83
September.....	16,030	1,010	2,153	2.82	3.14
October.....	2,750	870	1,033	1.42	1.64
November.....	1,010	870	898	1.18	1.32
December.....	22,915	870	2,769	3.63	4.18
The year.....	22,915	730	1,989	2.61	35.48

Estimated monthly discharge of Broad River (of Georgia) near Carlton—Cont'd.

Month.	Discharge in second-feet			Run-off	
	Maximum	Minimum	Mean	Sec.-ft. per sq. mile	Depth in inches
1902.					
January	2,650	950	1,304	1.71	1.97
February	29,125	1,280	4,514	5.92	6.16
March	27,370	1,535	4,225	5.54	6.39
April	2,550	1,195	1,579	2.07	2.31
May	1,710	790	1,163	1.53	1.76
June	1,365	565	800	1.05	1.17
July	2,750	490	764	1.00	1.15
August	2,950	420	919	1.21	1.39
September	7,120	420	1,227	1.61	1.80
October	1,890	490	837	1.10	1.27
November	2,550	420	777	1.02	1.14
December	4,960	790	1,479	1.94	2.24
The year	29,125	420	1,632	2.14	28.75
1903.					
January	2,850	960	1,375	1.81	2.09
February	19,810	1,180	4,638	6.09	6.34
March	24,400	1,330	4,110	5.39	6.21
April	5,230	1,330	2,007	2.63	2.93
May	2,000	1,030	1,270	1.67	1.93
June	6,850	960	2,125	2.79	3.11
July	3,510	690	1,150	1.51	1.74
August	5,905	690	1,387	1.82	2.10
September	2,365	575	818	1.07	1.19
October	890	575	651	.85	.98
November	1,255	630	750	.98	1.09
December	960	575	683	.90	1.04
The year	24,400	575	1,747	2.29	30.75
1904.					
January	1,770	610	741	.972	1.12
February	2,720	670	1,113	1.46	1.58
March	3,720	790	1,247	1.64	1.89
April	920	610	720	.945	1.05
May	1,520	420	629	.825	.951
June	790	340	478	.627	.700
July	2,130	305	522	.685	.790
August	10,300	340	1,409	1.85	2.13
September	1,280	305	471	.613	.690
October	380	305	314	.412	.475
November	670	340	434	.570	.636
December	2,130	460	683	.903	1.04
The year	10,300	305	730	.959	13.05
1905.					
January	4,230	510	984	1.23	1.42
February	7,500	510	2,046	2.69	2.80
March	850	560	687	.902	1.04
April	670	510	555	.728	.812
May	5,270	560	1,392	1.83	2.11
June	1,130	340	514	.675	.753
July	7,080	380	1,277	1.68	1.94
August	1,950	340	630	.827	.953
September	1,130	270	382	.501	.559
October	850	270	407	.534	.616
November	560	340	397	.521	.581
December	3,800	380	2,184	2.87	3.31
The year	3,800	270	950	1.25	16.89
1906.					
January	24,900	750	3,620	4.75	5.48
February	1,450	750	871	1.14	1.19
March	19,300	695	3,630	4.76	5.49
April	2,060	365	1,150	1.51	1.63
May	1,970	645	989	1.30	1.50
June	3,560	695	1,200	1.57	1.75
July	6,620	695	2,340	3.07	3.54
August	7,050	695	1,870	2.45	2.82
September	7,050	750	1,530	2.01	2.24
October	4,050	305	1,330	1.75	2.02
November	1,140	750	834	1.09	1.22
December	2,450	750	1,120	1.47	1.70
The year	24,900	645	1,710	2.24	30.63



NATURAL DAM, BIG POTATO CREEK, NEAR THOMASTON, UPSON COUNTY, GEORGIA.



BROAD RIVER (SOUTH FORK) NEAR CARLTON

This station was established as a bench-mark station. It is located at Bull Bat Rock, about 1 mile south of Carlton, Ga. Discharge measurements are made at a shoal about 100 yards above the rock by means of a boat. The initial point for soundings is a small sweet-gum tree on the left bank. The channel is curved for 200 feet above and 500 feet below the station. The current is sluggish. The right bank is cultivated and the left is wooded. Both banks are subject to overflow at rare intervals. The bed of the stream is composed of rock and is very rough. The bench mark is composed of three copper nails driven into the gum tree, which forms the initial point for sounding. Its elevation is 5.00 feet above datum.

Discharge measurements of Broad River (South Fork) near Carlton.

Date	Gage height	Dis-charge
1904	<i>Feet</i>	<i>Sec.-ft.</i>
July 20.....	1.00	64
September 7.....	1.20	115

MISCELLANEOUS MEASUREMENTS IN SAVANNAH RIVER DRAINAGE
BASIN

Broad River (South Fork).—A measurement was made May 4, 1904, at the foot of the shoals below Watson's mill near Carlton, as follows:

Width, 50 feet; area, 81 square feet; mean velocity, 1.28 feet per second; discharge, 104 second-feet. The gage at Carlton read 2.20 feet.

The following measurement was made March 16, 1904, at the Seaboard Air Line railroad bridge, 1½ miles west of Comer. The bench mark is the top of the girder at sounding point 30. Its elevation is 49.00 feet above the datum of the gage.

Width, 74 feet; area, 68 square feet; mean velocity, 1.56 feet per second; gage height, 1.18 feet; discharge, 106 second-feet.

Chattooga River.—This river joins the Tallulah River and forms Tugaloo River. The following measurement was made November 16, 1905, from a small boat at a point about 5 miles northeast of Tallulah Falls, at a narrow channel about 1,000 feet below Atkins Ferry and opposite B. H. Atkin's residence. There is a small shoal

about 150 feet below and one 300 feet above the point of measurement. At the time of flood in 1876 the water is said to have been 36 to 40 feet higher than the present stage and did much damage to property. The bench mark is the center of the head of a wire nail driven horizontally into a sycamore stump, which stands on the right bank about 200 feet above the point of measurement; elevation, 6.13 feet above the datum of the assumed gage. The gage height at the same time at the regular station on Tallulah River at Tallulah Falls was 0.82 foot.

Width, 107 feet; area, 442 square feet; mean velocity, 0.77 foot per second; gage height, 2.00 feet; discharge, 339 second-feet.

Little River.—Two measurements were made June 6, 1905, near Washington. The bench mark is the top of the downstream wooden stringer under the cross-ties at the center of the first span of the railroad bridge at the right bank; elevation, 29.00 feet above the datum of the assumed gage.

Measurement at bridge of Washington Branch of Georgia Railroad: Width, 37 feet; area, 59 square feet; mean velocity, 0.58 foot per second; gage height, 1.40 feet; discharge, 34 second-feet.

Measurement at wagon bridge, 400 feet above railroad bridge; Width, 47 feet; area, 185 square feet; mean velocity, 0.19 foot per second; gage height, 1.40 feet; discharge, 35 second-feet.

Panther Creek.—The following measurement was made June 22, 1905, a short distance below where the Tallulah Falls Railroad crosses Panther Creek, near Tallulah Falls. The stage of the creek was probably somewhat high at the time of gaging, owing to showers the day before.

Width, 9 feet; area, 5.85 square feet; mean velocity, 1.17 feet per second; discharge, 6.82 second-feet.

Tiger Creek.—This stream is tributary to Tallulah River from the north, entering near Tallulah Falls. The following measurement was made June 13 from the railroad trestle, one-fourth mile northwest of Wiley.

Width, 14 feet; area, 11 square feet; mean velocity, 1.12 feet per second; discharge, 12.3 second-feet.

RIVER SURVEYS IN SAVANNAH RIVER DRAINAGE
BASIN

TALLULAH RIVER

The elevations in the following list are based on a bronze tablet in rock 70 feet east of public road and 20 feet south of Tallulah Falls station, marked "1569 ATLANTA," the elevation of which is accepted as 1,568.302 feet above mean sea level in accord with the 1903 adjustment of the precise level net. The line is corrected to accord with primary work at mouth and at Burton.

The leveling was done in the summer of 1903 by Thomas B. O'Hagan, levelman, under the direction of Carroll Caldwell, field assistant.

Elevations on Tallulah River in Georgia from mouth near Tallulah Falls up to Blalock.

Dis- tance	Description of points	Elevation above sea level
<i>Miles</i>		<i>Feet</i>
0.0	Junction of Chattooga and Tallulah rivers, water surface	754'
0.0	100 feet north of junction of rivers, edge of river, point on rock	761.29
0.0	200 feet north of junction of rivers, west side of Tugaloo River, gum tree, nail in root of	762.65
0.2	Chattooga River, 500 feet north of, west side of Tallulah River, nail in root of oak stump	769.46
0.3	Water surface	767
0.4	Mouth of small stream, water surface	782
0.9	Water surface	818
1.3	Water surface	848
1.6	Water surface	878
1.7	Water surface	898
1.8	Water surface	911
2.0	Foot of rapids, water surface	935
2.1	Middle of rapids, water surface	944
2.2	Head of rapids, water surface	947
2.2	Foot of rapids, water surface	954
2.25	Water surface	964
2.3	Foot of small falls, water surface	981
2.35	Foot of rapids, water surface	987
2.38	300 feet below bend, head of rapids, water surface	980
2.4	Water surface	997
2.5	Water surface	1,008
2.6	Bridal Veil Falls, foot of, water surface	1,022
2.6	Head of falls, water surface	1,039
2.65	Water surface	1,057
2.8	Oceana Falls, foot of, water surface	1,074
2.85	Head of fall's, water surface	1,115
3.1	Hurricane Falls, foot of, water surface	1,140
3.1	Hurricane Falls, head of, water surface	1,229

Elevations on Tallulah River in Georgia from mouth near Tallulah Falls up to Blalock—Continued.

Dis- tance	Description of points	Elevation above sea level
<i>Miles</i>		<i>Feet</i>
3.1	Tempesta Falls, foot of, water surface.....	1,246
3.1	Tempesta Falls, head of, water surface.....	1,322
3.2	Ladore Falls, foot of, water surface.....	1,322
3.2	Ladore Falls, head of, water surface.....	1,350
3.3	Water surface.....	1,379
3.4	Water surface.....	1,396
3.6	Clayton road iron highway bridge, water surface.....	1,414
3.6	Tallulah Falls station, 70 feet east of public road, 20 feet south of station, in rock, bronze tablet marked "1569 ATLANTA".....	1,568.302
3.6	Tallulah Falls, 0.5 mile northeast of, at fork of road, 50 feet south of bridge over river.....	1,457.92
3.6	Clayton road iron highway bridge, floor of.....	1,441.87
3.6	Clayton road iron highway bridge, water surface.....	1,419
3.6	Opposite stone pier railroad bridge, water surface.....	1,439
4.9	Foot of falls, water surface.....	1,486
4.9	Top of falls, water surface.....	1,492
5.1	Water surface.....	1,509
5.5	Head of island, water surface.....	1,530
5.6	Tallulah Falls Railroad, 20 feet west of, point on top of rock.....	1,538.21
5.6	Water surface.....	1,529
6.0	Water surface.....	1,538
6.5	Water surface.....	1,553
6.6	Water surface.....	1,559
7.3	150 feet east of river, in cornfield, dead apple tree, nail in root of.....	1,579.23
8.4	Water surface.....	1,573
8.6	Water surface.....	1,578
8.7	65 feet north of river, in cornfield, walnut tree, nail in root of.....	1,589.25
8.7	Water surface.....	1,578
9.6	Tiger Creek, on point of land between river and creek, burned poplar tree, nail in side of.....	1,590.30
9.6	Water surface.....	1,584
9.9	Water surface.....	1,589
10.0	5 feet west of river, on footpath, point on sharp rock.....	1,595.59
10.2	Water surface.....	1,592
10.4	Water surface.....	1,596
10.5	10 feet west of river, nail in root of beech tree.....	1,601.32
10.6	Water surface.....	1,600
10.9	Water surface.....	1,603
11.8	Crane Ford, 150 feet west of apple tree, nail in root of.....	1,620.33
11.8	Crane Ford, water surface.....	1,607
12.1	Water surface.....	1,610
13.3	Dockens Ford, 12 feet west of river, nail in side of dead tree.....	1,623.06
13.3	Dockens Ford, water surface.....	1,615
13.8	Ellerd Ford, 150 feet east of, poplar tree, nail in side of.....	1,634.36
13.8	Ellerd Ford, water surface.....	1,621
14.4	Water surface.....	1,626
14.5	Water surface.....	1,628
14.6	Eden Church, 150 feet west of, 150 feet east of river, nail in foot of large red- oak tree.....	1,649.41
15.6	Taylor Shoals, 10 feet west of river, middle of, point on large flat rock.....	1,644.90
15.6	Taylor Shoals, water surface.....	1,641
16.2	Water surface.....	1,648
16.5	Water surface.....	1,657
16.6	Water surface.....	1,657
17.7	James Smith boat landing, 2 feet west of river, nail in stump.....	1,670.53
18.4	Fall Creek, mouth of, water surface.....	1,669
18.6	Jones Ford, 6 feet south of river, slanting persimmon tree, nail in side of.....	1,677.33
18.6	Jones Ford, water surface.....	1,674.6
19.2	Flat Creek, mouth of, water surface.....	1,681
20.6	Water surface.....	1,687
20.9	Cliff Creek, mouth of, water surface.....	1,690
21.4	Water surface.....	1,697
21.5	Denton Ford, 10 feet west of river, nail in root of pine tree.....	1,703.61
21.5	Denton Ford, water surface.....	1,701
21.8	Mouth of small stream.....	1,703
21.9	Seal Creek, mouth of, foot of double shoals, water surface.....	1,704
22.0	Water surface.....	1,707
22.3	Middle of shoals, water surface.....	1,714

Elevations on Tallulah River in Georgia from mouth near Tallulah Falls up to Blalock—Continued.

Distance	Description of points	Elevation above sea level
<i>Miles</i>		<i>Feet</i>
22.6	Crow Ford, 100 feet south of, 10 feet south of river, twin hemlock tree, nail in root of.....	1,725.93
22.6	Crow Ford, water surface.....	1,724
22.7	Scarecrow Creek, mouth of, water surface.....	1,727
24.0	George Creek, mouth of, water surface.....	1,737
24.5	Bridge Creek, mouth of, water surface.....	1,738
25.0	In shoals, water surface.....	1,747
25.1	Ford, water surface.....	1,749
25.1	Above ford, south edge of river, point on rock.....	1,750.29
25.6	Rocky Ford, 10 feet south of, dead hemlock tree, nail in root of.....	1,758.47
25.6	Rocky Ford, water surface.....	1,756
25.9	Water surface.....	1,757
26.2	Kenny Creek, mouth of, water surface.....	1,760
26.3	Fuller Ford, water surface.....	1,760
26.4	Fuller Ford, 500 feet northwest of, point on rock.....	1,762.62
27.0	Water surface.....	1,767
27.3	Cannon Ford, 75 feet southwest of, nail in foot of white oak.....	1,781.97
27.3	Cannon Ford, water surface.....	1,769
28.2	Ford, west side of, nail in root of red-gum tree.....	1,777.87
28.2	Ford, water surface.....	1,774
28.5	Wildcat Creek, 50 feet southwest of, west side of road, point on rock.....	1,783.19
28.5	Wildcat Creek, water surface.....	1,776
29.3	Water surface.....	1,785
29.5	Water surface.....	1,787
29.6	Mouth of Dicks Creek, water surface.....	1,789
30.1	Burton, 12 feet southwest of bridge, nail in root of maple tree.....	1,794.96
30.1	Burton, floor of bridge.....	1,806.4
30.1	Burton, water surface.....	1,790
30.1	Burton, high water.....	1,804
30.2	Burton, 1,000 feet above bridge, 15 feet east of river, 10 feet west of road, bronze tablet.....	1,795.140
32.1	12 feet west of ford, nail in side of ash tree.....	1,819.04
32.1	Water surface.....	1,813
32.4	Water surface.....	1,819
32.7	Mur Ford, 100 feet southwest of, nail in west side of white-oak tree.....	1,838.05
32.7	Mur Ford, water surface.....	1,824
33.0	Rocky Ford, water surface.....	1,829
33.1	Shallow Ford, 500 feet southeast of, in road, point on rock.....	1,841.43
33.2	Water surface.....	1,835
33.6	Deep Ford, 30 feet south of, nail in side of sycamore tree.....	1,842.39
33.6	Deep Ford, water surface.....	1,839
34.3	Popcorn Creek, mouth of.....	1,849
35.8	Persimmon Creek, 75 feet east of river, 30 feet south of creek, nail in side of hickory tree.....	1,881.67

SURVEY OF TUGALOO AND SAVANNAH RIVERS.

The elevations in the following list are based on an aluminum tablet marked "1050 M. C.," at the Washington street entrance to the State capitol at Atlanta, the elevation of which is accepted as 1,049.546 feet above mean sea level. The initial point on which these levels depend is a bronze tablet at the north side of east entrance at court-house at Clarkesville, Ga., marked "1373 ATLANTA," the elevation of which is accepted as 1,371.991 feet above mean sea level, in accordance with the 1903 adjustment of the precise level net.

The leveling on Tugaloo, and on Savannah River from Tugaloo River to Broad River, was done in the summer of 1903, under the direction of Carroll Caldwell, field assistant, by Thomas B. O'Hagan, levelman.

The survey of Savannah River from Broad River to Augusta, Ga., was made by C. M. Pritchett, in January, 1903, for the United States Geological Survey.

Elevations on Tugaloo and Savannah rivers from head of Tugaloo River to Augusta.

Dis- tance	Description of points	Elevation above sea- level
<i>Miles</i>		<i>Feet</i>
0.0	Nail in root of gum tree, west side of Tallulah River, 200 feet northwest of junction of Tallulah and Chattooga rivers.....	762.65
0.0	Point on rock, edge of river, 100 feet northwest of junction of Tallulah and Chattooga rivers.....	761.29
0.0	Point on rock, edge of river, 100 feet northwest of junction of Tallulah and Chattooga rivers, water surface.....	754

TUGALOO RIVER TO JUNCTION WITH SENECA RIVER.

0.7	Nail in root of pine tree, below head of Tugaloo river.....	728.86
0.7	Head of island, water surface.....	723
0.8	Water surface.....	711
2.0	Water surface.....	698
2.0	Point on rock, west side of river.....	698.79
2.1	Water surface.....	690
2.4	Water surface.....	686
2.8	Nail in root of hickory tree.....	690.51
2.8	Water surface.....	684
2.9	Water surface.....	681
3.1	Mouth of small stream, water surface.....	674
4.4	Mouth of Panther Creek, water surface.....	669
4.4	Bronze tablet marked "715 ATLANTA," in large rock, west edge of public road, 600 feet south of mouth of Panther Creek, 50 feet west of river.....	718.793
5.3	Water surface.....	667
5.4	Dieton Ford, water surface.....	666
5.0	Water surface at small bridge.....	664
5.4	Nail in root of walnut tree.....	676.45
6.3	Water surface.....	659
6.4	Mouth of small creek, South Carolina side, water surface.....	655
7.4	Nail in root of walnut tree, 100 feet west of river.....	664.87
7.5	Water surface at small boat landing.....	652
8.0	Mouth of Big John Creek, water surface.....	650
8.9	Nail in side of cottonwood tree, Prather's Bridge, 100 feet northwest of river and old bridge.....	659.02
8.9	Water surface.....	648
9.9	Bronze tablet marked "728 ATLANTA," middle step, front entrance, James Prather homestead.....	726.873
10.5	Mouth of stream.....	646
11.5	Nail in root of apple tree, 600 feet west of river.....	657.40
11.5	Water surface.....	644
13.0	Mouth of stream.....	642
13.0	Nail in root of gum tree, 10 feet west of river.....	658.51
13.8	Nail in root of gum tree, west edge of river.....	651.33
13.8	Mouth of Toccoa Creek, water surface.....	641
13.9	Jarrett Bridge, water surface.....	641

Elevations on Tugaloo and Savannah rivers from head of Tugaloo River to Augusta—Continued.

TUGALOO RIVER TO JUNCTION WITH SENECA RIVER—Continued.

Dis- tance	Description of points	Elevation above sea level.
<i>Miles</i>		<i>Feet.</i>
15.4	Nail in root of water-oak tree 4 feet east of river	642.50
15.4	Nail in root of walnut tree, 50 feet west of railroad bridge	660.52
15.4	Bronze tablet marked "666 ATLANTA," west abutment of railroad bridge cross- ing river	665.467
16.0	Mouth of stream, water surface	639
16.4	Mouth of stream, water surface	639
16.5	Nail in root of sycamore tree, 50 feet south of river	641.09
16.5	Mouth of stream	637
17.5	Nail in root of birch tree, 50 feet east of river	646.91
18.0	Water surface	636
18.0	Nail in root of walnut tree, 100 feet west of river, 200 feet east of county road ..	648.60
19.0	Mouth of stream opposite sawmill, water surface	632
19.1	Nail in root of walnut tree	647.65
20.1	Mouth of stream, water surface	630
21.3	Nail in top of swamp-bush, 3 feet northwest of river	634.60
21.7	Nail in root of walnut tree, 10 feet south of Rock Creek	640.35
21.7	Water surface	624
22.0	Nail in root of walnut tree, 400 feet northwest of Jenkins Ferry, 200 feet west of river	638.10
22.0	Bronze tablet marked "732 ATLANTA," in chimney 2 feet above ground, north side of house, W. J. Perkins's homestead (the above is on a single spur line) ...	730.754
22.0	Water surface	624
22.0	High water	638.00
22.3	Mouth of stream, water surface	622
22.4	Nail in stump, walnut tree	635.56
22.6	Nail in root of walnut tree, 40 feet west of river	634.32
23.2	Nail in root of birch tree on edge of small stream	629.55
24.5	Nail in root of small tree, 4 feet west of river	619.47
24.5	Water surface	618
25.1	Water surface	616
25.5	Nail in root of pine tree, 50 feet west of river	625.12
25.7	Water surface	614
26.1	Nail in old stump, 41 feet west of river	615.42
26.3	Head of Shelors Shoals, water surface	610
27.6	Nail in root of walnut tree, 10 feet north of river	614.54
27.6	Water surface	607
27.9	Water surface	605
28.1	Mouth of large creek, water surface	604
29.1	Nail in top of pine tree, 5 feet northeast of river	623.27
29.3	Nail in root of water-oak tree, Shelors Ferry, 10 feet northeast of river	606.46
29.3	Water surface	600
29.3	Bronze tablet marked "630 ATLANTA," in large rock, 100 feet northwest of I. E. Martin's house, 10 feet north of road, 0.3 mile southwest of Shelors Ferry	628.875
30.1	Mouth of stream, water surface	599
30.3	Nail in root of sycamore tree, 10 feet north of river	601.17
30.3	Mouth of stream, near bend in river, water surface	597
30.4	Nail in root of water-oak stump, 10 feet north of river	598.10
30.4	Water surface	595
31.8	Mouth of Gumlog Creek, water surface	592
32.3	Nail in root of apple tree, near middle branch	597.79
32.4	Water surface	590
33.1	Water surface	588
33.6	Nail in root of maple tree in fork of road, 100 feet west of Knox Bridge	602.78
33.6	Water surface	588
33.6	Bronze tablet marked "613 ATLANTA," in chimney, S. A. Glenn's house, 200 feet west of Knox Bridge	612.241
34.3	Water surface	587
34.3	Nail in top of dead stump, 25 feet northwest of Shoal Creek	598.34
35.3	Mouth of Shoal Creek, water surface	586
35.3	Nail in top of pine stump, 200 feet north of river	601.72
35.4	Mouth of Knox Branch, water surface	586
36.1	Nail in root of oak tree, 900 feet north of river	591.83
36.5	Mouth of Burton Branch, water surface	582
37.5	South side of river, point on bottom of cliff	588.07
37.8	Nail in root of red-oak tree, 10 feet north of road, 250 feet south of Pullins Ferry ..	596.59
37.8	Pullins Ferry, water surface	581

WATER POWERS OF GEORGIA

Elevations on Tugaloo and Savannah rivers from head of Tugaloo River to Augusta—Continued.

TUGALOO RIVER TO JUNCTION WITH SENECA RIVER—Continued.

Distance	Description of points	Elevation above sea level
<i>Miles</i>		<i>Feet</i>
38.4	Head of Cleveland Shoals, water surface	578
39.6	Nail in root of sycamore tree, 10 feet north of river, Avery's Ferry.....	584.96
39.6	Foot of shoals, water surface	578
39.8	Point on rock, bottom of cliff, 2 feet south of river	581.95
39.8	Bronze tablet marked "588 ATLANTA" in rock, top of cliff, Avery's Ferry, 20 feet south of river	587.448
40.3	Nail in root of walnut tree, 100 feet south of river, Bradberrys Ferry	581.95
40.3	Head of Chandlers Shoals, water surface	575
40.7	Point on rock, bottom of cliff, 1 foot south of river.....	577.26
40.8	Nail in root of beech tree, 1 foot south of river	572.24
40.8	Water surface	570
40.9	Mouth of Reed Creek, water surface	564
41.1	Foot of Chandlers Shoals, water surface	562
41.4	Nail in stump, 900 feet east of Reed Creek, 10 feet south of river.....	566.95
41.7	Nail in root of birch tree at boat landing	563.72
42.3	Head of Hatten Shoals, water surface	565
42.8	Nail in root of maple tree, 1,000 feet south of F. Clark's house, north edge of river.	556.79
42.8	Water surface	555
43.3	Nail in root of beech tree, 25 feet east of Beaverdam Creek	554.01
43.3	Water surface	546
43.7	Nail in root of large pine tree, 5 feet north of river, 25 feet east of small stream .	537.07
43.7	Water surface	535
44.2	Point on rock, bottom of cliff, Hatten Ford.....	526.91
44.2	Water surface	525
44.5	Mouth of branch, water surface	522
44.7	do	519
45.3	Nail in root of water-oak tree, 30 feet northeast of river,	529.96
46.3	Nail in root of beech tree, 15 feet east of river	525.17
46.3	Water surface	519
46.6	Nail in top of burnt stump, 40 feet east of river.	524.70
46.6	Water surface	518
47.7	Nail in root of twin beech tree, 15 feet north of river, ½ mile north of Andersonville, S. C	522.27
47.8	Mouth of Branch, water surface	516
48.2	Foot of rapids, water surface	511
48.2	Bronze tablet marked "588 ATLANTA," in rock, east side of road, 200 feet east of river, northwest of Little Beaverdam Creek, Andersonville, S. C	537.519
48.2	"Brouris" Ferry, water surface	510
48.2	Point on rock, 20 feet west of river.....	514.45

SAVANNAH RIVER FROM JUNCTION OF SENECA AND TUGALOO RIVERS TO BROAD RIVER.

48.7	Mouth of Seneca River, water surface.....	505
48.7	Nail in root of small pine tree.....	512.60
49.3	Mouth of branch, water surface	501
49.3	Nail in root of sycamore tree, on edge of bank branch and river	502.78
50.5	Mouth of creek, water surface	497
50.7	Nail in top of willow stump, 50 feet west of river, opposite island	503.38
50.7	Mouth of branch	493
51.4	Nail in root of large red-oak tree in footpath, 10 feet west of river.....	499.76
51.4	Triple water-oak tree, at Lightwood Creek, 400 feet west of river	507.28
52.3	Carters Ferry, water surface.....	492
52.3	High water	516
52.3	Mouth of Lightwood Creek, water surface.....	491
52.8	Nail in root of large walnut tree, 60 feet west of river	501.09
53.3	Nail in root of double water-oak tree, 40 feet west of Browns Ferry.	497.79
53.3	Water surface.....	488
53.3	High water	499
53.3	Bronze tablet marked "518 ATLANTA," in brick and stone abutment at rear of O. C. Brown's house, northwest corner, 1,200 feet northeast of Browns Ferry	516.891
54.6	Mouth of Powderbag Creek, water surface.....	487
54.5	Nail in root of box-elder tree, 520 feet south of creek, 30 feet west of river.....	491.38
55.0	Dooleys Ferry, nail in root of poplar tree, 114 feet west of river.....	492.64

Elevations on Tugaloo and Savannah rivers from head of Tugaloo River to Augusta—Continued.

SAVANNAH RIVER FROM JUNCTION OF SENECA AND TUGALOO RIVERS TO BROAD RIVER.
Continued.

Distance	Description of points	Elevation above sea level
<i>Miles</i>		<i>Feet</i>
55.0	Dooleys Ferry, water surface.....	486
55.7	Nail in root of maple tree hanging over edge of river, opposite Crafts island.....	485.18
55.7	Water surface.....	485
55.7	Mouth of Long Branch, head of McDaniel Shoals, water surface.....	484
56.1	Nail in root of large poplar tree, 30 feet south of river.....	487.61
56.1	Water surface.....	482
56.1	High-water mark.....	487
56.8	Nail in root of pine tree, 70 feet southwest of river.....	483.26
56.8	Water surface.....	474
57.3	Nail in root of birch tree, mouth of Turner Creek, southwest of river.....	473.43
57.3	Water surface.....	471
57.5	Nail in root of birch tree, 20 feet southwest of river.....	476.13
57.5	Water surface.....	470
58.0	Nail in root of red-oak tree bending over edge of river 0.1 mile west of Harpers Island.....	472.57
58.7	Foot of McDaniel shoals, water surface.....	466
59.1	Bronze tablet marked "495 ATLANTA," in cliff foot of steep hill, west side of ferry road, opposite colored house, 0.2 mile above Parks Ferry.....	494.435
59.3	Parks Ferry, nail in root of large red-oak tree, 15 feet west of river.....	488.53
59.3	Parks Ferry, water surface.....	461
59.5	Water surface.....	460
60.5	Nail in root of mulberry tree stump, west side of river.....	462.42
60.5	Water surface.....	453
60.8	Saddlers Old Ferry, point on rock, rock cliff, 40 feet west of river.....	466.598
60.8	Saddlers Old Ferry, water surface.....	453
60.9	Nail in root of hickory tree, 60 feet south of river.....	471.27
60.9	Water surface.....	457
61.5	Nail in root of large black-oak tree, 500 feet north of river at Cedar Creek.....	480.66
61.5	Mouth of Cedar Creek.....	455
62.3	Nail in root of white-ash tree, 10 feet west of river, 0.1 mile southwest of Kinleys Ferry.....	457.68
62.3	Water surface.....	454
62.4	Head of Turner's Shoals, water surface.....	453
62.5	Mouth of McMullins Branch, water surface.....	450
64.2	Nail in root of small hickory tree, 50 feet south of river.....	456.55
64.3	Shoals, water surface.....	450
65.8	Nail in root of black oak tree, 200 feet west of river.....	459.62
65.9	Water surface.....	443
66.2	Nail in root of black-oak tree, 25 feet west of river.....	445.80
66.2	Water surface.....	440
66.9	Nail in root of red-oak tree, Crafts Ferry, 10 feet west of river.....	443.67
66.9	Mouth of creek, water surface.....	437
66.9	Aluminum tablet marked "450 ATLANTA," in rock, 60 feet west of river, 125 feet west of boat landing, Crafts Ferry.....	449.306
66.9	Foot of Turners Shoals, water surface.....	437
68.1	Head of Middleton Shoals, water surface.....	435
68.5	Nail in root of small black-oak tree, 125 feet west of river, opposite Barnes Island.....	443.11
68.5	Water surface.....	431
68.7	Nail in root of dogwood tree on top of cliff, 300 feet west of river.....	457.46
69.5	Nail in root of willow stump, west edge of river.....	428.03
69.8	Foot of Middleton Shoals, water surface.....	424
69.8	Nail in root of post-oak tree, 20 feet west of river.....	432.50
70.2	Nail in root of water-oak tree, 20 feet west of river, Powells Ferry.....	435.23
70.2	Powells Ferry, water surface.....	422
70.9	Water surface.....	419
71.0	Nail in top of white ash stub, 150 feet west of river, 0.8 mile south of Powells Ferry.....	459.30
71.3	Head of Greggs Shoals, water surface.....	418.7
72.4	Black Ferry, nail in root of birch tree, 25 feet west of river.....	421.677
72.4	Black Ferry, water surface.....	410.3
72.5	Nail in root of octagon burnt tree stump, 350 feet east of river.....	431.08
73.2	Mouth of creek, water surface.....	409
73.4	Nail in root of persimmon-tree stump, 350 feet east of river.....	419.39
73.7	Mouth of branch, water surface.....	407
73.7	Opposite mill, water surface.....	406
73.8	Mouth of Clearwater Creek, water surface.....	406

WATER POWERS OF GEORGIA

Elevations on Tugaloo and Savannah rivers from head of Tugaloo River to Augusta—Continued.

SAVANNAH RIVER FROM JUNCTION OF SENECA AND TUGALOO RIVERS TO BROAD RIVER.
Continued.

Dis- tance	Description of points.	Elevation above sea level.
<i>Miles</i>		<i>Feet.</i>
74.3	Nail in root of persimmon tree, 140 feet southwest of small branch, 350 feet east of Mof river.....	414.39
75.8	Head of Allens Creek, water surface.....	404
76.2	Harpers Ferry, nail in root of water-oak tree, south side of road, 20 ft. east of river.....	412.26
76.2	Harpers Ferry, water surface.....	408
76.2	High-water mark.....	416
76.4	Bronze tablet marked "420 ATLANTA," in limestone rock side of brook, 250 feet southwest of W. J. Taylor house.....	419.146
77.0	Mouth of branch, water surface.....	402
77.3	Ruckers and Tuckers Ferry, nail in side of willow tree, 40 feet southeast of and 5 feet west of river.....	405.49
77.3	Ruckers and Tuckers Ferry, water surface.....	401
77.3	High-water mark.....	418
77.6	Water surface.....	400
78.1	Water surface.....	399
78.4	Nail in root of white-hickory stump, 50 feet north of river, 60 feet west of English Creek.....	417.13
78.4	Mouth of English Creek, water surface.....	398
78.9	Water surface 900 feet south of head of McCauleys Island.....	397
79.2	McCauleys Ferry, nail in root of ash stump, 40 feet west of river.....	407.19
79.2	McCauleys Ferry, water surface.....	397
79.6	Nail in root of beech tree, 150 feet north of river.....	407.39
79.6	Water surface.....	396
80.5	Mouth of branch.....	395
80.8	Nail in root of walnut tree, 50 feet east of river.....	398.77
81.0	Moseleys Ferry, nail in root of walnut tree, 50 feet east of river.....	400
81.0	Moseleys Ferry, water surface.....	392
81.3	Water surface.....	392
81.6	Water surface.....	391
81.7	Head of large falls, water surface.....	390
81.8	Nail in root of twin pine tree, 50 feet east of river.....	399.23
81.9	Cherokee Shoals, water surface.....	388
82.6	Water surface.....	379
82.6	Nail in root of oak tree, 125 feet east of river.....	385.75
83.2	Water surface.....	374
83.3	Nail in root of white-oak tree, 40 feet west of river, Carters Island, ferry.....	382.52
83.5	Water surface.....	373
83.7	Mouth of Rocky River, water surface.....	372
84.2	Water surface.....	371
84.2	Bronze tablet marked "383 ATLANTA," abutment, Seaboard Air Line bridge, east side of bridge.....	382.161
85.1	Nail in root of oak tree, 15 feet north of river, lower end of Watkins Island.....	375.70
85.2	Nail in side of dead stump, on mainland, 150 feet southwest of Watkins Island.....	374.59
85.2	Head of Trotters Shoals, water surface.....	367
85.5	Shoals, water surface.....	364
85.7	Head of island, water surface.....	362
85.9	Water surface.....	358
86.0	Nail in stub 75 feet west of river.....	367.40
86.2	End of Calhoun's Island, water surface.....	356
86.3	Nail in root of black-ash tree, 60 feet southwest of river.....	365.01
86.3	Trotter Shoals, water surface.....	353
86.6	Water surface.....	351
86.6	Point on rock, bottom of cliff.....	354.27
87.1	Nail in root of triple cedar tree, 75 feet west of river, Calhoun's Ferry.....	348.39
87.1	Water surface.....	340
87.5	Water surface.....	336
87.6	Nail in root of pine tree in path, 50 feet southwest of river.....	341.32
88.1	Mouth of creek, water surface.....	329.7
88.3	Water surface.....	328
88.6	Nail in root of Spanish oak, 400 feet west of river, 10 feet southeast of road.....	338.61
88.9	Water surface.....	325
89.2	Nail in root of hickory tree in footpath, on top of steep hill, 200 feet west of river.....	360.67
89.2	Water surface.....	322
89.4	Water surface.....	318

SAVANNAH DRAINAGE BASIN, RIVER SURVEYS

Elevations on Tugaloo and Savannah rivers from head of Tugaloo River to Augusta—Continued.

SAVANNAH RIVER FROM JUNCTION OF SENECA AND TUGALOO RIVERS TO BROAD RIVER.
Continued.

Distance	Description of points	Elevation above sea level
Miles		Feet
89.7	Bronze tablet marked "320 ATLANTA," in large rock, 50 feet west of river, 2.5 miles southeast of Calhoun's Ferry.....	319.252
89.7	Water surface.....	313
90.1	Water surface.....	308
90.2	Water surface.....	304
90.3	Nail in root of water-oak, 300 feet north of old mill, 10 feet west of river.....	305.90
90.3	Water surface.....	301
90.4	Water surface.....	299
91.3	Mouth of branch, water surface.....	292
91.3	Nail in root of dead birch tree, 10 feet west of river.....	300.21
91.3	Water surface.....	251
91.3	Creek.....	289
92.8	Clarks Ferry, copper tack in root of water oak, 200 feet west of river.....	309.13
92.8	Clarks Ferry.....	287
92.8	High-water mark.....	307
93.7	1,500 feet below creek, water surface.....	285
93.9	Copper tack in side of gum tree, 50 feet west of river.....	299.66
94.2	Water surface.....	284
96.1	Nail in root of dead black gum, east side of road, Petersburg Ferry.....	293.41
96.1	Mouth of Broad River.....	281
96.2	Nail in root of water oak, south side of ferry road.....	295.77
96.4	Bronze tablet marked "328 ATLANTA," in brick wall of R. L. Cade's store, Lisbon.....	327.850

SAVANNAH RIVER (FROM BROAD RIVER TO AUGUSTA).

96.8	Water surface.....	279
97.6	Hesters Ferry, 6-inch willow.....	295.20
97.6	Hesters Ferry, water surface.....	277
98.4	Water surface.....	276
98.5	Twelve-inch pine opposite Goat Island.....	308
98.5	Water surface.....	276
99.3	Water surface.....	275
101.1	Water surface.....	274
102.1	Mouth of branch, water surface.....	278
102.8	Water surface.....	271
103.6	Water surface.....	270
103.6	Six-inch willow at Rimsons Ferry.....	280.59
104.3	Opposite Murray Island, water surface.....	270
105.4	Water surface.....	269
105.8	Water surface.....	267
106.4	Water surface.....	267
106.4	Twelve-inch birch, at Barksdales Ferry.....	281.07
107.1	Water surface.....	266
108.1	Ter-inch willow, near branch.....	276.51
108.1	Water surface.....	264
108.6	Water surface.....	264
109.1	Water surface.....	263
109.6	Mouth of small branch.....	263
110.3	Mouth of small branch.....	261
112.1	Water surface.....	258
112.1	Eight-inch cotton tree at Dog Ferry, mouth of Little River (of South Carolina).....	269
113.1	Mouth of Hawes Creek.....	255
114.3	Thirty-inch cotton tree at Ferguson Ferry.....	262.16
114.3	Water surface.....	252
115.1	Head of Point Lookout Shoals.....	250
115.3	Foot of Point Lookout Shoals.....	248
115.8	Water surface.....	247
116.6	Mouth of Landram Creek.....	245
117.3	Water surface.....	245
117.6	Twenty-four-inch pine, 50 feet from river, near a rocky hill.....	252.12
117.6	Water surface.....	239
118.4	Water surface.....	235
118.8	Water surface.....	234
119.3	Mouth of Jordan Creek.....	231

WATER POWERS OF GEORGIA

Elevations on Tugaloo and Savannah rivers from head of Tugaloo River to Augusta—Continued.

SAVANNAH RIVER (FROM BROAD RIVER TO AUGUSTA)—Continued.

Distance	Description of points	Elevation above sea level
<i>Miles</i>		<i>Feet</i>
120.1	Mouth of small branch.....	220
121.1	Prices Ferry, 30-inch cotton tree.....	221.12
121.1	Prices Ferry, water surface.....	212
122.1	Water surface.....	210
122.8	Water surface.....	206
123.4	Kilcrease Ferry, foot of Long Shoals, 24-inch cotton tree.....	209.76
123.4	Kilcrease Ferry, water surface.....	203
123.8	Water surface.....	199
124.1	Eighteen-inch cotton tree above old channel way.....	205.06
124.8	Mouth of Owl Branch, water surface.....	197
125.8	Head of Little River Shoals, water surface.....	193
126.3	Foot of Little River Shoals, water surface.....	189
126.3	Six-inch willow, mouth of Little River of Georgia.....	191.87
126.4	Mouth of Keg Creek, water surface.....	188
127.1	Bench mark on 8-inch gum below ditch.....	201.84
127.6	Head of Scotts Shoals, water surface.....	186
128.6	Foot of Scotts Shoals, water surface.....	180
129.6	Lukes Ferry, water surface.....	178
131.1	Bench mark on 8-inch crooked willow.....	189.72
131.1	Water surface.....	178
131.8	Water surface.....	178
132.4	Mouth of Big Kiokee Creek, water surface.....	177
133.4	Mouth of Little Kiokee Creek, water surface.....	175
134.4	Harveys Falls water surface.....	174
135.0	Water surface.....	173
135.6	Woodlawn, bench mark on beam over last pier of bridge.....	199.15
135.6	Woodlawn, water surface.....	171
136.6	Furys Ferry, on 6-inch pine.....	188.80
137.6	Head of Pine Log Shoals, water surface.....	168
137.8	Foot of Pine Log Shoals, water surface.....	165
138.6	Water surface.....	164
139.4	Water surface.....	162
140.4	Above branch, 10-inch sycamore.....	171.08
140.4	Water surface.....	158
141.6	Ten-inch willow, mouth of Stevens Creek.....	162.78
141.6	Water surface.....	155
142.8	Above dam, water surface.....	152
142.8	Below dam, water surface.....	142
142.8	Headwater in canal below locks.....	151
142.8	Bench mark at locks, top of masonry.....	164.04
143.4	Water surface at waste gate.....	137
143.8	Water surface.....	135
144.4	Water surface.....	135
144.6	Headwater in canal.....	150
144.8	Bench mark on 10-inch pine near canal bank.....	155.52
145.1	Headwater in canal.....	150
145.4	Water surface at waste gate.....	127
146.1	Water surface.....	122
146.4	Headwater in canal at city pumping station.....	150
147.1	Water surface.....	118
147.6	Warwick Manufacturing Co. tailrace and wastewier, water surface.....	112
148.4	J. P. King, tailrace, water surface.....	111
149.1	Hawks Gully, water surface.....	109
149.1	Bench mark marble slab, corner Fifteenth and Broad streets.....	185.84
149.1	Zero of gage at Center street, Augusta, Ga.....	98.17

SURVEY OF CHATTOOGA RIVER.

The elevations in the following list are based on an aluminum tablet, marked "1050 M. C.," at the Washington street entrance to the State capitol at Atlanta, the elevation of which is accepted as 1,049.546 feet above mean sea level. The initial point upon which these levels depend is a bench mark of primary levels of the Tugaloo and Savannah River survey at the mouth of Chattooga River. The elevations accord with the 1903 adjustment.

The leveling was done for the U. S. Geological Survey in 1903 by Thomas B. O'Hagan, levelman, under the direction of Carroll Caldwell, field assistant.

Elevations on Chattooga River from mouth of Chattooga River to Russell Bridge, Georgia. ^a

Dis- tance	Description of points	Elevation above sea level
<i>Miles</i>		<i>Feet</i>
0.0	Tallulah and Chattooga rivers, 100 feet north of junction, point on rock.....	761.29
0.0	Tallulah and Chattooga rivers, white-oak tree 75 feet west of junction of, 25 feet north of Tallulah River, nail in root of oak tree.....	762.21
0.0	Tallulah and Chattooga rivers, water surface.....	754
0.2	Water surface.....	759
0.7	Mouth of stream, water surface.....	763
1.0	Worse Creek, mouth of, water surface.....	765
1.2	Water surface.....	766
1.9	Small stream on north edge of river, Spanish oak, nail in root of.....	776.27
1.9	Water surface.....	772
2.1	Water surface.....	775
2.6	North side of river, point on rock.....	788.68
3.0	Water surface.....	779
4.0	East side of river, point on rock.....	851.51
4.0	Water surface.....	849
4.1	Water surface.....	869
4.5	Mouth of creek, water surface.....	892
4.7	Water surface.....	899
4.9	East side of river, point on rock.....	918.27
4.9	Water surface.....	919
5.0	Water surface.....	929
5.1	Water surface.....	939
5.2	Water surface.....	949
5.3	Mouth of stream, head of shoals, water surface.....	954
5.6	Camp Creek, mouth of, water surface.....	961
5.6	Trail Ford, point on rock 20 feet east of river.....	967.50
5.6	Trail Ford, water surface.....	962
5.8	Water surface.....	969
6.1	Water surface.....	979
6.3	Water surface.....	989
6.7	Water surface.....	999
7.0	Water surface.....	1,000
7.2	Water surface.....	1,029
7.4	Cliff Creek, mouth of, water surface.....	1,035
7.4	Cliff Creek, 300 feet above, east side river, point on rock.....	1,045.26
7.5	Water surface.....	1,039
7.6	Chechero Creek, mouth of, water surface.....	1,049
7.8	Water surface.....	1,059
8.0	Water surface.....	1,069
8.2	Water surface.....	1,079
8.4	Water surface.....	1,089
8.5	Water surface.....	1,099
8.6	Water surface.....	1,109
9.0	Water surface.....	1,119
9.5	Water surface.....	1,129
9.8	Water surface.....	1,149
10.0	East side of river on edge of bank, point on rock.....	1,152.43
10.0	Water surface.....	1,159
10.0	Iron bridge, South Carolina side, iron bar under bridge, point on.....	1,168.95
10.0	Iron bridge, water surface.....	1,166.3
10.0	High water.....	1,177
10.5	Water surface.....	1,169
10.6	Mouth of creek, water surface.....	1,173

^a Seven miles north of Russell, S. C.

Elevations on Chattooga River from mouth of Chattooga River to Russell Bridge,
Georgia—Continued.

Dis- tance	Description of points	Elevation above sea level
<i>Miles</i>		<i>Feet.</i>
10.6	Head of falls, water surface	1,179
10.8	Mouth of stream, water surface	1,188
11.0	Water surface	1,189
11.4	Water surface	1,199
11.7	Mouth of stream, water surface	1,204
12.0	Water surface	1,209
12.5	50 feet south of island, east side of river, 10 feet from bank, point on rock.....	1,217.86
12.7	Water surface.....	1,219
12.9	Water surface.....	1,223
13.0	Water surface.....	1,229
13.2	Mouth of stream, water surface.....	1,232
13.6	Water surface.....	1,239
13.8	South Carolina side of river, at large cliff, point on rock	1,245.53
14.0	Water surface.....	1,249
14.0	Mouth of Fall Creek, water surface.....	1,262
14.5	Water surface.....	1,268
14.7	Water surface.....	1,279
15.0	Water surface.....	1,289
15.7	Water surface.....	1,296
16.0	Water surface.....	1,299
16.6	Rich Creek, mouth of, water surface.....	1,308
16.8	Water surface.....	1,309
16.9	South Carolina side of river, point on rock	1,310.4
17.0	Water surface.....	1,319
17.4	Water surface.....	1,329
17.8	Sandy bottom, 1,000 feet below, east side of river, point on rock.....	1,332
18.0	Water surface.....	1,340
18.7	Water surface.....	1,359
18.7	East side of river, point on rock	1,366.45
18.9	Water surface.....	1,360
19.1	300 feet below falls, at bend in river, point on rock	1,376.19
19.2	Foot of falls, surface of water.....	1,375
19.0	Head of falls, water surface	1,381
19.7	Water surface.....	1,399
19.8	Rock Creek, mouth of, water surface.....	1,406
20.0	Sand ford, water surface.....	1,411
20.0	Sand ford, 75 feet north of, 15 feet east of river, nail in root of white oak tree.....	1,416.55
20.2	Water surface.....	1,419
20.6	Water surface.....	1,429
20.7	Dick Creek, mouth of, water surface.....	1,439
20.8	Water surface.....	1,449
21.0	East side of river, point on rock.....	1,452.91
21.2	Water surface.....	1,459
22.0	Water surface.....	1,469
22.1	Water surface.....	1,473
22.3	4 feet east of river, nail in root of pine tree.....	1,481.86
22.7	Water surface.....	1,479
23.0	Earl Ford, 100 feet below ford, east side of river, point on rock	1,486.74
23.0	Earl Ford, water surface.....	1,486
23.0	Warwoman Creek, mouth of, water surface	1,486
23.8	South side of river point on rock	1,494.13
23.8	Water surface.....	1,492
24.8	Water surface.....	1,499
25.2	West side of river, point on rock.....	1,510.51
25.2	Water surface.....	1,505
26.0	Horseback Ford, water surface.....	1,518
26.3	Water surface.....	1,519
26.4	Ford, 65 feet above, north side of river, nail in live stob (white-oak tree).....	1,522.66
26.4	Water surface.....	1,521
26.8	Water surface.....	1,529
27.1	Water surface.....	1,339
27.9	Barlow stream, center of river, point on rock.....	1,547.26
28.0	Water surface.....	1,549
28.7	Long Bottom Ford, east side, nail in fork of sugar-maple tree.....	1,557.68
29.7	Small stream, mouth of river at, water surface.....	1,554
30.6	West fork, mouth of, water surface.....	1,563
30.6	Wooden bridge above Russell, S. C., southwest side of bridge, point on bolt.....	1,584.84
30.6	Bridge, water surface.....	1,564

SURVEY OF BROAD RIVER.

The elevations in the following list are based on a bronze tablet in a brick wall of R. L. Cade's store at Lisbon, Ga., marked "ATLANTA 328," the elevation of which is accepted as 327.850 feet above mean sea level in accord with the 1903 adjustment of the precise level net.

The leveling was done in 1903 for the United States Geological Survey by Thomas B. O'Hagan, levelman, under the direction of Carroll Caldwell, field assistant.

Elevations on Broad River from mouth to Harrison Bridge, near Carnesville.

Distance	Description of points	Elevation above sea level
<i>Miles</i>		<i>Feet</i>
0.0	Lisbon, mouth of Broad River, 870 feet northwest of, south side of ferry road, nail in twin water oak.....	295.77
0.0	Broad River, mouth, water surface.....	280
0.0	Broad River, 870 feet northwest of mouth, high-water bench mark.....	300
0.6	Small stream near, water surface.....	281
1.4	Mill Ford Shoals, foot of, water surface.....	281
2.1	Mill Ford Shoals, middle of, water surface.....	288
2.4	Mill Ford Shoals, head of, water surface.....	289
2.4	Mill Ford Shoals, 200 feet east of river near 5-inch elm tree, nail in line stob.....	304.9
2.7	Center of bend, water surface.....	391
3.4	J. De Bose Ferry, 300 feet above, water surface.....	392
4.7	Anthony Shoals, foot of, water surface.....	298
5.0	Anthony Shoals, water surface.....	295
5.2	Anthony Shoals, at large bend in river, surface of water.....	307
5.2	Anthony Shoals, at rock cliff, water surface.....	310
5.2	Anthony Shoals, at rock cliff, point on rock 1 foot west of river.....	311.57
5.4	Anthony Shoals, water surface.....	319
5.6	Anthony Shoals, water surface.....	329
5.8	Anthony Shoals, in front of factory, water surface.....	339
6.0	Anthony Shoals, at dam, east edge of river, nail in root of birch tree.....	347.77
6.0	Anthony Shoals, at dam, water surface.....	351
6.4	Anthony Shoals, head of, water surface.....	355
6.5	Burton Ferry, 6 feet south of river, nail in root of Spanish-oak tree.....	361.44
6.5	Burton Ferry, water surface.....	355
6.5	Burton Ferry, high water.....	364
7.1	Water surface.....	355
8.7	Mouth of creek, water surface.....	356
8.7	60 feet south of river, 25 feet east of creek, nail in sweet-gum tree.....	367.59
10.0	Water surface.....	356
10.9	Bakers Ferry, small shoals, water surface.....	356
11.0	Bakers Ferry, 20 feet southwest of river, nail in root of large birch tree.....	364
11.0	Bakers Ferry, water surface.....	357
11.8	Wahache Creek, mouth of, water surface.....	360
13.8	Bells Bridge, north side, nail in joist.....	375.69
13.8	Bells Bridge, water surface.....	360
13.8	Bells Bridge, high water.....	386
13.8	Bells Bridge, floor of.....	393.2
15.0	Bells Bridge, 250 feet north of river, large pine tree near path to river, nail in tree.....	375.34
15.4	Mouth of small stream, water surface.....	361
15.6	Falling creek, mouth of, water surface.....	362
16.0	Foot of shoals, water surface.....	363
16.4	Fish dam, foot of, water surface.....	365
16.4	Fish dam, head of, water surface.....	363
16.4	Fish Dam Ferry, north side of river, nail in root of large water-oak tree.....	374.35
16.4	Fish Dam Ferry, south side of, nail in root of gum tree.....	374.87
16.4	Fish Dam Ferry, water surface.....	363
17.7	Water surface.....	363
18.9	North of river, point on rock.....	386.66
18.9	Water surface.....	370
20.0	Grimes Old Ferry, edge of river, nail in root of white-oak tree.....	375.51
20.0	Grimes Old Ferry, water surface.....	371
21.3	500 feet south of river, 25 feet south of river road, nail in root of Spanish oak.....	323.89
22.1	Mouth of large creek, water surface.....	372.8
22.5	Pine grove, 400 feet north of river, 900 feet west of large creek, nail in root of pine tree.....	393.51
23.1	Mattox Bridge, north side, nail in plank.....	401.35
23.1	Mattox Bridge, floor.....	404
23.1	Mattox Bridge, water surface.....	374
23.1	Mattox Bridge, high water.....	400
24.8	Rock cliff, near, 40 feet south of river, nail in root of gum tree.....	397.88
24.8	Water surface.....	377

Elevations on Broad River from mouth to Harrison Bridge, near Carnesville—
Continued.

Dis- tance	Description of points	Elevation above sea level
<i>Miles</i>		<i>Feet</i>
25.2	Jones Ferry, east side, nail in root of water-oak tree.....	398.43
25.2	Jones Ferry, water surface.....	377
25.2	Jones Ferry, high-water mark.....	401
25.5	Jones Ferry, 0.3 mile above, 40 feet west of river, nail in white oak tree.....	394.38
26.0	Surface of water.....	380
26.7	Millstone Creek, mouth of, 60 ft. east of, 25 ft. south of river, nail in side of elder	392.64
26.7	Millstone Creek, water surface.....	381
28.0	Gold Mine Cliff, water surface.....	384
28.5	Horseshoe bend, head of, 150 feet south of river, in cornfield, nail in Spanish oak	405.67
28.5	Dove Creek, mouth of, water surface.....	386
28.6	Bend in river, water surface.....	396.4
28.6	Water surface.....	386
30.0	260 feet north of river, nail in root of pine tree.....	411.3
30.9	Water surface.....	391
31.0	Martin Old Ferry, near spring, point on rock.....	420.14
31.3	Junction South Fork and Broad River, southwest point of rivers, nail inside of birch tree.....	395.86
31.3	Water surface.....	391
32.4	Detweiler Ferry, foot of shoals, water surface.....	395
32.9	Detweiler Ferry, east side, edge of water, slanting Spanish oak, nail in.....	406.07
32.9	Detweiler Ferry, head of shoals, water surface.....	402.1
32.9	Detweiler Ferry, high water.....	428.6
33.4	Seaboard Air Line bridge, abutment, east side of river, 350 feet from.....	420.28
33.4	Seaboard Air Line bridge, water surface.....	402
34.0	Moores Shoals, water surface.....	404
34.4	Old Mill, 25 feet east of river, point on rock.....	416.23
34.4	Old Mill, mouth of stream, water surface.....	409
34.4	Moores Shoals, head of, water surface.....	411
34.7	Bells Ferry, edge of river, 2 feet from road overhanging Spanish oak.....	418.87
34.7	Bells Ferry, water surface.....	412.3
34.7	Bells Ferry, high water.....	430
35.9	Harpers Ferry, north side of river, east side ferry, nail in root of black-gum tree	422.54
35.9	Harpers Ferry, water surface.....	414
35.9	Harpers Ferry, high water.....	432
36.3	Holly Branch, mouth of, water surface.....	416
37.5	Moons Ferry, east of ferry, nail in side of white-oak tree.....	423.19
37.5	Moons Ferry, water surface.....	418
37.8	Water surface.....	419
37.9	Mouth of creek, water surface.....	420
38.6	Payton Shoals, foot of, water surface.....	422
39.0	Payton Shoals, east side of river, nail in sycamore tree.....	428.57
39.0	Payton Shoals, head of, water surface.....	425
39.0	South Payton Ferry, 25 feet from river, east side of ferry, nail in side of dead willow tree.....	431.35
39.1	Payton Ferry, water surface.....	427
39.1	Payton Ferry, high-water.....	449
39.4	Payton Ferry, No. 2, head of shoals, water surface.....	429
39.8	Victory Ferry, overhanging birch tree, nail in side of.....	432.17
39.8	Victory Ferry, water surface.....	430
39.8	Victory Ferry, high-water.....	450
40.4	Moons Ferry, nail in root of white-oak tree.....	442.62
40.4	Moons Ferry, foot of shoals, water surface.....	431
40.5	Moons Shoals, head of, water surface.....	433
41.1	Bend in river, 1,500 feet east of Mill Creek, east side of river, point on rock.....	443.14
41.1	Water surface.....	438
41.4	Mill Shoal Creek, mouth of, water surface.....	439
41.4	Water surface.....	441
42.2	Head of shoals, water surface.....	450
42.7	Moores Ferry, west side of, large spruce tree, nail.....	455.77
42.7	Moores Ferry, water surface.....	450
42.7	Moores Ferry, high-water mark.....	460
43.0	Moores Shoals, at spring, foot of shoal, surface of water.....	454
43.3	Shoals, water surface.....	462
43.3	Moores Shoals, point on rock.....	470
43.8	Browns Ferry, burnt stump northeast of river, nail in.....	482.09
43.8	Browns Ferry, near head of Moores Shoals, water surface.....	471
44.2	Moores Shoals, head of, water surface.....	482
44.6	Dudleys Shoal, east bank of river, point on rock.....	489.28
44.6	Dudleys Shoal, water surface.....	482
45.5	Dudley Ferry, black-gum tree, north side of ferry, nail in root.....	502
45.5	Dudley Ferry, water surface.....	487
45.5	Dudley Ferry, high-water mark.....	504
45.6	Bryant Shoals, foot of, water surface.....	489
46.2	Bryant Shoals, head of, water surface.....	496
46.5	Sawmill, Spanish-oak tree, 50 feet from river, nail in root of.....	506.65
46.5	Water surface.....	502
46.5	Head of shoals, water surface.....	506
47.7	North side of river, 1.2 miles below Blue Creek, point on rock.....	518.33
47.7	Water surface.....	512
48.9	Mouth of Blue Creek, water surface.....	517

SAVANNAH DRAINAGE BASIN, RIVER SURVEYS

Elevations on Broad River from mouth to Harrison Bridge, near Carnesville—
Continued.

Dis- tance	Description of points	Elevation above sea level
<i>Miles.</i>		<i>Feet</i>
49.6	Water surface	521
50.4	New bridge, east side of river, nail in floor of	546.44
50.4	Bridge floor	548.8
50.4	Water surface	523
50.4	High-water mark	548.1
51.2	Mouth of stream, foot of shoals, water surface	523.7
51.6	Head of shoals, water surface	526
52.3	Winters Creek, just below bend in river, water surface	545
52.4	Winters Creek, mouth of, head of shoals, water surface	529
53.2	Water surface	532
53.9	Mouth of stream, water surface	535
54.7	Braggs Ferry, 2 feet from river, nail in root of large red-oak tree	541.75
54.7	Braggs Ferry, mouth of Hudson River, water surface	537
55.2	Water surface	541
55.7	Dove Bridge, southeast corner of, nail in side of white-oak tree	561.78
55.7	Dove Bridge, water surface	542
55.7	Dove Bridge, high water mark	569
57.2	Foot of shoals, water surface	548
57.3	Head of shoals, water surface	552
57.6	Water surface	554
57.7	Creek, 60 feet southeast of mouth of, nail in white-oak tree	568.30
57.7	Mouth of creek, water surface	556
58.1	Mouth of stream, water surface	556
58.8	Middle Broad and Broad Rivers, fork of, walnut tree, 75 ft. west of fork, nail in side	575.16
58.8	Water surface	557
59.1	Double bridge, northwest side of, nail in plank	581.11
59.0	Water surface	563
59.1	High-water mark	576
59.1	Bridge floor	584
59.7	Head of shoals, water surface	570
59.9	Water surface	573
60.6	Corey Creek, 6 miles below, large rock projecting out from bank, point on	581.02
60.9	Small shoal in river	560
60.9	Corey Creek, mouth of	581
61.5	Bend on east side of river, point on rock	591.15
61.5	Water surface	584
62.1	Fish dam, water surface	586
62.2	Water surface	588
62.3	Bend in river, east side, point on rock cliff.	598.59
62.8	Philip Shoal, head of	591
63.2	Stevens Creek, mouth of	592
63.4	Ford, oak tree, 75 feet north of, nail in north side of	608.49
63.4	Water surface	598
63.4	Water surface	594
64.6	Harrisons Bridge, east of, north of river, nail in root of Spanish oak	607.07
64.6	Bridge floor	613.7
64.6	Water surface	596
64.6	High-water mark	612

WATER POWER IN SAVANNAH RIVER DRAINAGE
BASIN.

GENERAL STATEMENT.

It is intended that the foregoing lists of water surface elevations along the main river and tributaries above Augusta shall give full and complete data in regard to the total fall and its distribution on these streams:

The record of the hydrographic stations at Augusta, Ga., Calhoun Falls, S. C., and Fort Madison, S. C., on Savannah and Tugaloo Rivers, Carlton on Broad River, and Tallulah Falls on Tallulah River will form a basis for estimating the amount of water flowing at all points.

In the following, attention is called to certain important shoals and proposed grouping of shoals into proposed powers, and mention is made of some of the conditions relative to developing these powers, as well as to powers already utilized.

TALLULAH RIVER.

From the mouth of Popcorn Creek, near the headwaters, down to mouth of Tiger Creek, a distance of 25 miles, the fall is 265 feet, and as can be seen from the list of elevations is almost uniformly distributed, being slightly more than 10 feet to the mile. At a few points in the section the drop is from 5 to 10 feet in a short distance, and good small-power sites are available. In the next 4 miles below Tiger Creek the fall is 55 feet. This reaches the head of the rapids above Tallulah Falls, at which point there is an excellent location for a large storage dam. The fall from here down to the head of Tallulah Falls proper is 110 feet. Somewhere in this section the water should be diverted to a canal if the falls proper should ever be developed into a water power, as by beginning the canal at high enough elevation it can be put on comparatively good ground outside the gorge. A large water power can be developed in this section entirely above the falls proper at a comparatively small expense. Along Tallulah River, beginning at Tallulah Falls, is some of the most picturesque and rugged scenery in the Southern States. In $3\frac{1}{2}$ miles the river drops from 1,414 to 754 feet above sea level, or a distance of 660 feet. The principal falls, in the order they occur, are L'eau D'or 28 feet, Tempesta 76 feet, Hurricane 89 feet, Oceana 41 feet, Bridal Veil 17 feet, all occurring within a distance of less than three-fourths of a mile. The gorge is very difficult and dangerous to climb. On both banks are precipitous cliffs, rising in some places 500 feet sheer. The gorge continues to the Tugaloo, except for one stretch about one-half mile long, where it opens up and forms what is known as the Old Valley farm. In the $2\frac{1}{2}$ miles above the

mouth of the river there is a fall of 254 feet, all below the falls proper, which could be used for power without interfering with Tallulah Falls.

WATER POWER ON TUGALOO RIVER.

From the head of Tugaloo River down to the mouth of Panther Creek, a distance of $4\frac{1}{2}$ miles, there are some good shoals, the total fall being 85 feet. The banks are favorable for power development along the entire stretch. From Panther Creek to Averys Ferry, a distance of 35 miles, the slope is too gentle and the valley too wide to utilize the river without flooding considerable farming land. Chandler Shoals, $1\frac{1}{4}$ miles below Averys Ferry, begin near Bradberry Ferry and have a fall of 10 feet in three-fourths mile. Three-fourths of a mile below are Hatten Shoals, with a fall of 35 feet in 2 miles. These shoals are considered the finest on the river; a 45-foot dam at them would back the water about 4 miles, with very little damage to cultivated land. From this point down to the mouth of Seneca River, which is the head of Savannah River, the fall is 14 feet in a distance of 4 miles.

WATER POWER ON SAVANNAH RIVER.

The fall in Savannah River for the first 7 miles, down to the head of McDaniels Shoals, is 20 feet. At McDaniels Shoals there is a fall of 19 feet in 3 miles. Half a mile above the foot of the shoals, at the head of Harpers Island, is an excellent site for a dam about 700 feet long.

In the 4 miles between this power and the next at Turners Shoals the fall is 12 feet. At Turners Shoals there is a fall of 17 feet in about $4\frac{1}{2}$ miles. These shoals begin at Kenly Ferry and extend to Crafts Ferry. The river widens considerably about a mile below Kenly Ferry. There are several good sites for dams, one being on Crafts Island. The river is wide, however, requiring a dam about 1,000 feet long.

Half a mile below, at Middleton Shoals, there is a fall of 11 feet in $1\frac{3}{4}$ miles, with an excellent site for a dam at the foot of the shoals. In $1\frac{1}{2}$ miles below, the fall is 5 feet. This reaches the head of Gregg Shoals, where the fall is 8 feet in about a mile. Here the

river runs between steep hills, and a dam would be about 900 feet long.

Half a mile below Moseleys Ferry are the Cherokee Shoals, having 19 feet fall in $2\frac{1}{2}$ miles. This is a very fine power site, as the river runs between steep hills. A dam would have to be 1,000 feet long, and would be placed about a quarter of a mile above the Seaboard Air Line railroad bridge.

One and a quarter miles below the bridge are Trotters Shoals, with a fall of 75 feet in 6 miles. These are considered the finest shoals on the river. They commence at the foot of Watkins Island and extend below Tate's mill to Coffey Creek. In this distance there are numerous rocky bluffs where there are excellent dam sites.

In the next 5 miles, extending to the mouth of Broad River, the fall is 11 feet. From the mouth of Broad River down to Little River, from the South Carolina side, the fall is slight, being 23 feet in the distance of 16 miles. From this point down to the upper end of Long Shoals the fall is 42 feet in 6 miles.

The fall is 23 feet in the next 5 miles, extending to the foot of Scotts Shoals. From here to the Augusta dam the fall is 28 feet in 15 miles.

At Augusta the power is fully developed by a dam about 10 feet high and a canal 7 miles long. The head is about 50 feet. This power belongs to the city of Augusta. It was developed in 1845-1847 and the canal was enlarged in 1872-1875.

WATER POWER ON CHATTOOGA RIVER.

Tallulah River unites with Chattooga River to form the Tugaloo. Chattooga River contains many available undeveloped power sites. From its mouth to Warwoman Creek, a distance of 23 miles, the river flows through a wild, rugged country, being in a gorge almost the entire distance, which results in a very narrow and swift stream. There are numerous dam sites along this distance, the river being almost one continuous shoal, averaging a fall of 32 feet to the mile, and having a fine rock bottom, with rock cliffs on either side. From Warwoman Creek up to Russells Bridge the valley is wide and the fall is much less, being 78 feet in 7 miles.

WATER POWER ON BROAD RIVER.

In the $4\frac{3}{4}$ miles from the mouth of the river to foot of Anthony Shoals the fall is 13 feet, 8 feet of which occurs in a distance of 1 mile at Millford Shoals.

Anthony Shoals is the finest power site on the river and is one of the best in the State, the fall being 62 feet in a distance of $1\frac{3}{4}$ miles. Several plans have been proposed for developing the power. Probably the best plan is to build a dam near the upper end of the shoal high enough to raise the water at least 10 feet, and to construct a canal to a point near the foot of the shoals. The proposed raise of 10 feet would back the water 10 miles up the river to the foot of Fish dam, where there is a 3-foot dam, 250 feet long, furnishing power for a gristmill and a sawmill. From Fish dam to the mouth of South Broad River, 15 miles, there is a fall of 23 feet, with no shoal of any consequence. The bottoms are wide in most places and are in a high state of cultivation.

One mile above the mouth of South Broad River are the Detweiler Shoals, with a fall of 7 feet in one-half mile. A mile and a half farther are the Lower Moore Shoals, with a fall of 7 feet in one-third mile, with good outcrops of hard rock on both sides. A dam here would be about 350 feet long.

Five miles farther up the river are Payton Shoals with a fall of 3 feet in one-third mile. In the 4 miles from Payton Shoals to the foot of Moores Shoals the fall is 29 feet. At Moores Shoals there is a fall of 28 feet in $1\frac{1}{4}$ miles. Above this point there are several shoals with good sites for dams. The fall is 35 feet for the first 5 miles up to the mouth of Blue Creek, and about 5 feet to the mile above this to the end of the survey at Harrison Bridge.

OGEECHEE RIVER DRAINAGE BASIN.

DESCRIPTION OF BASIN.

Ogeechee River is formed by the junction of Williamsons Swamp Creek and Rocky Comfort Creek in Jefferson County, Ga., and drains a small basin in southeastern Georgia lying between the Savannah and Altamaha basins. Ogeechee River runs in a southeasterly direction and empties into the Atlantic Ocean. Its main

tributary is Cannoochee River, which rises in Emanuel County, Ga., and flows southeast, joining the Ogeechee about 20 miles from the Atlantic Ocean. The streams in this basin run through a country that is mostly low. The current is generally good, but the fall available for power is probably small. The bank on one side or the other of the stream is generally low and swampy.

STREAM FLOW.

OGEECHEE RIVER NEAR MILLEN.

This station was established by F. A. Murray at Daniel's toll bridge, 1 mile west of Millen, on June 20, 1903, but was discontinued December 31, 1903, on account of poor conditions for accurate measurement of the flow.

The channel is straight for about 300 feet above and about 500 feet below the bridge. The current is swift in the main channel and sluggish near the banks. The right bank is low and overflows. There is a trestle approach for about 300 feet over low, swampy land on this side of the river. The left bank is lower than the right bank, the swamp extending back from the river about one-fourth mile. The bed of the stream is sandy and shifting. There is but one channel at ordinary stages, but several channels at high water.

Discharge measurements were made from the upstream side of the wooden highway bridge to which the gage is attached. The bridge is at an angle of about 45° to the current. The initial point for soundings is the end of the hand rail at the tollhouse on the left bank, upstream side of the bridge.

The gage is a vertical rod reading from 0 to 12 feet. It is nailed to the upstream post of the third bent from the tollhouse. The gage was read once daily during 1903 by T. J. Lane, the toll keeper.

Bench mark No. 1 is the top of the upstream end of the cap of the first bent from the tollhouse; elevation, 12.00 feet above the zero of the gage. Bench mark No. 2 consists of a notch and nails in the corner of the tollhouse next the river; elevation, 18.00 feet above the zero of the gage.

OGEECHEE DRAINAGE BASIN, STREAM FLOW

Discharge measurements of Ogeechee River near Millen in 1903.

Date	Gage height	Dis-charge	Date	Gage height	Dis-charge
June 20..... 1903	<i>Feet</i> 5.06	<i>Sec.-Ft.</i> 1,548	October 10..... 1903	<i>Feet</i> 2.09	<i>Sec.-Ft.</i> 519
July 30.....	2.35	515	November 20.....	4.00	889
October 10.....	2.08	470			

Daily gage height, in feet, of Ogeechee River near Millen.

Day	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1903							
1.....		6.0	2.3	2.4	2.5	2.6	4.0
2.....		5.7	2.4	2.3	2.4	2.6	3.9
3.....		5.5	2.7	2.3	2.3	2.7	3.8
4.....		5.3	3.0	2.3	2.2	2.9	3.8
5.....		5.3	3.1	2.2	2.1	3.0	3.8
6.....		5.3	3.4	2.2	2.0	3.2	3.7
7.....		5.2	3.8	2.1	2.0	3.5	3.7
8.....		5.0	4.2	2.0	2.0	3.8	3.7
9.....		5.4	4.1	1.9	2.0	4.0	3.7
10.....		5.8	3.9	1.9	2.1	4.2	3.7
11.....	6.5	5.5	3.6	1.8	2.1	4.5	3.7
12.....	7.1	5.7	3.3	1.7	2.1	4.6	3.8
13.....	6.9	6.2	3.1	1.5	2.1	4.7	3.8
14.....	6.7	6.4	3.0	1.6	2.1	4.8	3.8
15.....	6.6	6.4	3.3	1.9	2.2	4.7	3.9
16.....	6.5	6.3	3.5	4.1	2.2	4.5	3.9
17.....	6.2	6.4	3.9	4.9	2.2	4.3	4.0
18.....	5.9	6.3	4.0	5.5	2.3	4.1	4.0
19.....	5.5	6.0	4.2	5.6	2.8	4.0	4.0
20.....	5.2	5.7	4.3	5.4	3.4	4.0	4.0
21.....	5.0	5.4	5.7	5.1	3.8	4.0	4.0
22.....	4.8	5.0	6.0	4.9	4.0	4.0	4.1
23.....	4.8	4.6	5.9	4.8	4.0	4.0	4.2
24.....	4.9	4.0	5.7	4.7	4.0	4.0	4.3
25.....	4.8	3.6	5.5	4.5	4.0	4.0	4.4
26.....	4.6	3.3	5.3	4.1	4.0	4.0	4.5
27.....	4.7	3.0	5.1	3.5	3.8	4.0	4.7
28.....	5.1	2.8	4.8	3.0	3.4	4.0	4.9
29.....	5.5	2.6	4.0	2.7	3.0	4.1	5.1
30.....	5.8	2.5	3.3	2.6	2.8	4.1	5.3
31.....		2.3	2.6		2.6		5.5

Rating table for Ogeechee River near Millen from June 11 to December 31, 1903.

Gage height	Dis-charge						
<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>
1.50	418	2.30	595	4.10	933	5.40	1,860
1.60	428	2.90	611	4.20	980	5.50	1,960
1.70	440	3.00	628	4.30	1,030	5.60	2,065
1.80	452	3.10	646	4.40	1,085	5.70	2,170
1.90	465	3.20	665	4.50	1,145	5.80	2,275
2.00	478	3.30	685	4.60	1,210	6.00	2,490
2.10	492	3.40	707	4.70	1,275	6.20	2,710
2.20	506	3.50	731	4.80	1,345	6.40	2,930
2.30	520	3.60	757	4.90	1,420	6.60	3,150
2.40	534	3.70	785	5.00	1,500	6.80	3,370
2.50	549	3.80	816	5.10	1,585	7.00	3,590
2.60	564	3.90	850	5.20	1,675		
2.70	579	4.00	889	5.30	1,765		

WATER POWERS OF GEORGIA

Estimated monthly discharge of Ogeechee River near Millen.

Month	Discharge in second-feet		
	Maximum	Minimum	Mean
1903			
June 11-30.....	3,700	1,210	2,183
July.....	2,930	520	1,771
August.....	2,490	520	1,077
September.....	2,065	418	855
October.....	889	478	609
November.....	1,345	564	905
December.....	1,960	785	989

WILLIAMSON'S SWAMP CREEK AT DAVISBORO.

This station was established June 19, 1903, by F. A. Murray, at the Davisboro Bridge, about 200 yards south of the Central of Georgia Railroad station, which is in the middle of the town. It was discontinued on December 31, 1904.

The channel is straight for about 200 feet above and below the station. The right bank is low and overflows at a gage reading of 4 to 4½ feet. The left bank will overflow at a gage height of 3 feet. The bed of the stream is sandy and is slightly shifting. There is but one channel at all stages. The current is somewhat obstructed by the bents which support the bridge at low water and by trees and brush on the banks at high water. Discharge measurements were made from the upstream side of the wooden highway bridge, which is supported by wooden bents about 18 feet apart. The initial point for soundings is the outer edge of the post which supports the end of the hand rail on the left bank upstream side of the bridge. The gage is a vertical rod 10 feet long. It is nailed to the left side of the upstream post of the bent which supports the bridge at a point 302 feet from the initial point for soundings. It was read once each day by A. Baker, a hotel proprietor, who was paid by the Georgia Geological Survey.

Bench mark No. 1 is the top of the bridge floor at the bent 302 feet from the initial point for soundings on the upstream side of the bridge. The point is marked with a cross and the letters "B. M." cut into the top of the bridge-floor plank; elevation, 11.00 feet above the zero of the gage, which is attached to the same bent. Bench

mark No. 2 is the center of a large wire nail driven horizontally into the brideward side of an ash tree which stands in the creek near the right bank about 40 feet below the bridge; elevation, 5.50 feet above the zero of the gage.

Discharge measurements of Williamsons Swamp Creek at Davisboro.

Date	Gage height	Dis-charge	Date	Gage height	Dis-charge
1908			1908		
	<i>Feet.</i>	<i>Sec.-ft.</i>		<i>Feet</i>	<i>Sec.-ft.</i>
June 19.....	2.41	83	October 13.....	1.72	47
July 18.....	2.58	100	October 18.....	1.64	41
July 29.....	1.64	46	November 21.....	2.58	94
July 29 ^a	1.64	45	December 28.....	2.69	97

^a Wading 50 feet below bridge.

WATER POWERS OF GEORGIA

Daily gage height, in feet, of Williamsons Swamp Creek at Davisboro.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1903.												
1							2.5	2.1	1.8	1.7	2.1	2.4
2							2.3	4.0	1.9	1.8	2.2	2.5
3							3.3	2.4	1.7	1.8	2.1	2.7
4							3.7	3.5	1.7	1.7	2.4	2.8
5							2.3	3.0	1.7	1.5	4.4	2.4
6							2.8	2.4	1.8	1.6	3.2	2.4
7							5.8	2.1	1.7	1.6	2.9	2.2
8							5.0	2.0	1.7	2.0	2.5	2.3
9							3.5	1.8	1.7	2.0	2.4	2.4
10							3.9	1.9	1.7	2.0	2.4	2.5
11							3.2	2.1	1.7	1.9	2.5	2.6
12							4.3	2.3	1.7	1.8	2.4	2.5
13							3.6	2.3	1.8	1.7	2.6	2.5
14							5.1	2.2	1.9	1.7	2.6	2.4
15							4.7	2.1	3.0	1.7	2.5	2.5
16							3.4	2.1	4.0	1.8	2.5	2.5
17							2.8	2.3	3.0	2.9	2.5	2.5
18							2.6	2.1	2.8	4.0	2.5	2.5
19						2.4	2.5	3.0	2.5	2.4	2.7	2.4
20						2.5	2.5	3.8	1.9	2.1	2.5	2.6
21						2.5	2.3	3.6	1.8	2.2	2.6	3.0
22						2.6	2.1	3.2	2.0	2.2	2.6	2.8
23						2.4	2.1	2.1	1.9	2.1	2.5	2.5
24						2.3	2.1	2.0	2.0	2.0	2.5	2.5
25						2.2	2.3	2.1	1.9	2.1	2.4	2.8
26						2.2	2.3	1.9	1.9	2.0	2.4	3.3
27						2.2	1.9	1.8	2.0	2.0	2.5	3.8
28						4.4	1.8	1.8	1.9	2.0	2.5	2.6
29						4.0	1.7	1.7	1.8	2.1	2.5	2.7
30						2.9	1.8	1.7	1.8	2.1	2.4	2.7
31							1.8	1.8	2.1	2.2		2.7
1904.												
1	2.7	2.8	2.8	2.5	1.8	3.1	2.2	4.6	2.2	1.65	1.4	2.1
2	2.6	2.9	2.7	2.7	1.8	3.1	1.3	4.6	2.1	1.5	1.4	2.1
3	2.5	2.6	2.6	2.4	1.85	2.3	1.4	2.3	2.0	1.5	2.0	4.0
4	2.4	2.5	3.4	2.25	1.9	1.9	1.3	1.8	2.0	1.3	2.9	3.1
5	2.5	2.6	3.2	2.3	1.55	1.45	1.3	3.8	2.05	1.7	2.9	3.7
6	2.5	2.6	3.1	2.4	1.3	1.4	1.3	3.6	2.05	1.6	2.4	3.6
7	2.5	3.2	4.1	2.45	1.8	1.3	1.3	3.8	2.1	1.6	2.2	3.2
8	2.5	3.1	3.6	2.2	1.9	3.4	1.85	3.85	2.0	1.7	2.1	3.0
9	2.5	3.3	3.4	2.9	1.8	2.0	1.35	5.35	2.0	1.6	2.0	2.1
10	2.5	4.2	3.2	2.7	1.8	1.6	2.7	5.5	2.0	1.45	1.9	2.9
11	2.7	5.1	3.1	2.6	1.8	1.6	2.0	4.0	2.0	1.5	1.8	2.6
12	2.8	3.8	3.1	2.3	1.65	1.6	1.7	2.8	2.0	1.5	1.8	2.6
13	2.6	3.5	2.8	2.25	1.55	1.5	1.5	2.6	2.0	1.4	3.2	2.6
14	2.6	3.7	2.7	2.3	1.45	1.5	1.4	2.4	1.95	1.5	3.6	2.5
15	2.9	3.5	3.2	2.25	1.65	1.5	1.5	2.4	1.9	1.5	3.0	2.7
16	2.7	3.5	2.8	2.2	1.6	1.4	1.35	2.2	1.85	1.5	2.1	3.3
17	2.6	3.3	2.5	2.1	1.5	1.4	1.3	2.05	1.8	1.4	2.2	3.0
18	2.5	3.1	2.4	2.0	1.5	1.4	1.8	2.0	1.8	1.5	2.0	2.1
19	2.6	3.1	2.7	2.1	1.45	1.35	1.6	1.9	1.8	1.5	2.0	2.1
20	2.7	3.1	2.6	2.1	1.4	1.3	1.5	1.8	1.8	1.4	2.0	2.1
21	2.8	3.7	2.9	2.05	1.4	1.3	1.2	1.8	1.7	1.6	2.0	2.6
22	2.9	4.0	2.6	2.0	1.4	1.4	1.4	1.8	1.7	1.5	2.0	2.6
23	4.2	3.7	2.6	2.0	1.25	1.25	1.5	1.9	1.75	1.4	2.6	2.6
24	3.9	3.3	2.6	2.0	1.6	1.2	1.85	1.8	1.8	1.4	2.8	2.6
25	3.0	3.0	3.0	1.9	1.3	1.2	1.45	1.8	1.8	1.4	2.8	2.6
26	2.8	3.1	2.9	2.0	1.25	1.2	2.5	1.7	1.8	1.7	2.6	2.5
27	2.8	3.1	3.4	2.0	1.25	1.2	1.8	5.1	1.7	1.5	2.3	2.5
28	3.0	3.0	3.3	2.0	1.25	1.1	1.6	5.0	1.8	1.4	2.2	2.6
29	3.0	2.9	2.5	1.95	1.3	1.5	2.5	3.6	1.6	1.4	2.2	2.6
30	2.9		2.5	1.9	1.6	1.55	2.25	2.5	1.6	1.4	2.4	3.0
31	2.9		2.6		3.0		2.1	2.3		1.4		2.8

Rating table for Williamsons Swamp Creek at Davisboro, from June 19 to December 31, 1903.^a

Gage height	Dis-charge						
<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>
1.50	40	2.60	95	3.70	175	4.80	270
1.60	44	2.70	101	3.80	183	4.90	279
1.70	48	2.80	108	3.90	191	5.00	288
1.80	52	2.90	115	4.00	199	5.10	297
1.90	57	3.00	122	4.10	207	5.20	306
2.00	62	3.10	129	4.20	216	5.30	315
2.10	67	3.20	136	4.30	225	5.40	324
2.20	72	3.30	143	4.40	234	5.50	334
2.30	77	3.40	151	4.50	243	5.60	344
2.40	83	3.50	159	4.60	252	5.70	354
2.50	89	3.60	167	4.70	261	5.80	364

^a This rating table can not be applied to the 1904 gage heights, owing to the shifting character of the stream bed.

Estimated monthly discharge of Williamsons Swamp Creek at Davisboro.

Month	Discharge in second-feet		
	Maximum	Minimum	Mean
1903			
June 19-30.....	234	72	107
July.....	364	48	127
August.....	199	48	85
September.....	199	48	66
October.....	199	40	65
November.....	234	67	94
December.....	183	72	97

CANNOOCHEE RIVER NEAR GROVELAND

This station was established June 12, 1903, by F. A. Murray, at Moody's bridge, 3 miles south of Groveland, Bryan County.

The channel is straight for about 300 feet above and 400 feet below the station. The current is swift in the main channel, but sluggish near the banks. Both banks are of clay and sand, and overflow at from 15 to 16 feet gage height. The bed of the stream is of silt, and is shifting. There is but one channel at all stages, broken by the piers of the bridge, up to the height at which the river overflows its banks.

Discharge measurements are made from the downstream side of the nine-span wooden highway bridge. The initial point for soundings is the outer edge of the post which supports the end of the hand rail on the downstream side of the bridge on the left bank.

The original gage, reading from 0 to 17 feet, is nailed to the right

side of the upstream post of the fourth bent from the left bank. From 17 to 20 feet the post is graduated to feet and half feet. A new gage, reading from 0 to 10 feet, is fastened to the left-bank side of the upstream post of the third bent from the left bank, this being the first bent in the water at ordinary stages. Another section of the gage, reading from 5 to 10 feet, is fastened to a gum tree on the left bank 25 feet above the bridge. This gage faces the bridge, and is used for the stages which it covers. The gage is read once each day by J. M. Edwards. Bench marks were established as follows: (1) The top of the bridge floor at the fourth bent from the left end of the bridge on the upstream side opposite a point 61 feet from the initial point for soundings, marked by a cross and the letters "B. M." cut in the floor; elevation, 20.00 feet. (2) Two large wire nails driven into the tree to which the third section of the gage is fastened; elevation, 5.30 feet. Two more nails are also driven at the 8-foot mark.

Discharge measurements of Cannoochee River near Groveland.

Date	Gage height	Dis-charge	Date	Gage height	Dis-charge
1903.			1904.		
June 12.....	<i>Feet</i> 12.90	<i>Sec.-ft.</i> 3,467	November 29.....	<i>Feet.</i> 2.27	<i>Sec.-ft.</i> 91
June 23.....	5.20	734	November 30.....	2.30	93
July 17.....	9.97	2,224	1905.		
July 17.....	9.92	2,562	April 26.....	6.17	1,051
August 21.....	15.11	4,125	April 26.....	6.14	1,050
October 9.....	4.45	462	June 12.....	1.60	30
November 18.....	5.05	734	July 27.....	2.51	140
December 29.....	6.20	1,014	July 27 <i>b</i>	2.50	133
1904.			November 7 <i>b</i>	1.25	23
February 20.....	9.45	2,075	November 7 <i>b</i>	1.26	27
July 22.....	1.53	27	1906.		
July 22 <i>a</i>	1.61	30	April 14.....	4.92	1,630
September 12.....	4.16	438	May 18.....	4.43	920
September 12.....	4.16	435	October 9.....	5.19	2,170
October 29 <i>a</i>	1.54	29	October 10.....	5.02	1,810
October 29 <i>a</i>	1.54	31			

a Wading 1,000 feet below bridge.

b Made at different section.

OGEECHEE DRAINAGE BASIN, STREAM FLOW

Daily gage height, in feet, of Cannoochee River near Groveland.

Day.	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug	Sept.	Oct.	Nov.	Dec.
1908.												
1.....							9.8	2.6	5.5	5.7	3.8	4.4
2.....							8.0	2.6	5.1	5.4	3.9	4.3
3.....							6.9	2.6	5.0	5.3	5.4	4.3
4.....							6.4	2.7	4.5	5.1	6.2	4.2
5.....							6.1	3.2	4.8	4.8	6.7	4.1
6.....							6.3	4.3	4.9	4.7	6.9	4.1
7.....							5.9	6.0	4.6	4.6	6.6	3.9
8.....							5.4	6.7	4.2	4.6	6.2	3.8
9.....							5.9	6.7	4.0	4.5	5.9	3.8
10.....							6.8	5.5	3.8	4.3	5.6	4.5
11.....							8.7	4.9	3.7	4.2	5.2	4.6
12.....							10.6	4.5	3.6	4.0	5.0	4.5
13.....							9.7	4.9	3.7	3.9	4.8	4.3
14.....							9.5	7.2	3.8	3.8	4.7	4.3
15.....							9.2	8.1	7.0	3.8	4.7	4.3
16.....							9.5	10.1	13.8	3.7	4.5	4.3
17.....							10.0	11.1	17.8	3.7	4.5	4.1
18.....							9.5	17.2	18.0	5.7	5.0	3.8
19.....							8.9	16.7	17.3	7.9	5.0	3.9
20.....							8.2	16.0	16.5	8.8	4.6	3.8
21.....							5.5	15.2	15.7	9.4	4.5	3.9
22.....							5.2	15.0	14.7	8.9	4.4	4.0
23.....						5.2	4.9	16.0	13.2	7.9	4.2	4.1
24.....						5.7	3.7	15.8	11.3	6.6	4.0	4.0
25.....						5.6	3.5	15.1	9.6	6.0	4.0	4.0
26.....						5.7	3.3	13.8	8.2	5.4	4.1	4.4
27.....						5.2	3.3	12.0	7.3	4.7	4.5	5.2
28.....						6.5	3.2	10.4	6.6	4.4	4.6	5.5
29.....						8.1	3.0	8.5	6.3	4.2	4.5	6.2
30.....						9.0	2.9	7.0	6.1	4.0	4.3	6.9
31.....							2.7	6.0		3.9		7.7

WATER POWERS OF GEORGIA

Daily gage height, in feet, of Cannoochee River near Groveland—Continued.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1904												
1.....	7.2	9.3	9.6	5.9	2.4	2.0	1.7	4.5	6.2	2.1	1.5	2.2
2.....	7.6	8.5	9.1	5.7	2.4	2.0	1.7	4.6	6.4	2.0	1.5	2.2
3.....	7.6	8.2	8.2	5.2	2.3	2.0	1.7	5.9	6.2	1.9	1.6	2.1
4.....	6.9	7.6	8.0	4.7	2.2	2.0	1.7	4.9	4.8	1.9	1.8	2.2
5.....	6.5	7.0	7.6	4.3	2.2	2.0	1.6	5.9	4.1	1.9	2.1	2.4
6.....	6.1	6.8	7.6	4.2	2.1	2.0	1.6	8.0	3.8	1.8	2.1	2.4
7.....	5.7	6.6	7.6	4.0	2.1	1.9	1.6	10.8	5.0	1.8	2.0	2.7
8.....	5.3	6.2	8.0	4.0	2.1	1.9	1.6	13.2	6.8	1.7	2.0	2.8
9.....	5.2	6.3	8.0	4.0	2.0	1.9	1.6	14.2	6.0	1.7	2.0	2.9
10.....	5.1	7.6	8.1	4.4	2.0	1.9	1.6	14.2	4.7	1.7	2.0	2.8
11.....	4.9	12.5	7.6	4.8	2.0	1.9	1.9	13.7	4.1	1.7	1.9	2.8
12.....	5.2	14.5	7.7	5.0	2.0	1.8	1.9	11.0	4.1	1.7	1.9	2.8
13.....	5.2	15.4	7.4	5.2	2.0	1.8	1.9	9.9	3.9	1.6	2.0	2.8
14.....	5.2	15.3	7.1	5.3	2.0	1.7	2.1	8.9	3.5	1.6	2.5	2.7
15.....	5.0	14.5	7.1	5.1	2.0	1.7	2.0	7.9	3.2	1.6	2.7	2.6
16.....	5.0	13.7	6.9	4.8	2.0	1.7	1.8	6.9	3.0	1.6	2.6	2.4
17.....	5.0	13.7	6.7	4.3	1.9	1.6	1.7	6.0	2.9	1.7	2.5	2.4
18.....	4.7	11.5	6.4	3.8	1.8	1.6	1.6	5.3	2.8	1.7	2.5	2.5
19.....	4.5	10.2	6.2	3.5	1.8	1.6	1.6	4.8	2.9	1.7	2.5	2.6
20.....	4.4	9.5	6.0	3.0	1.7	1.6	1.6	4.6	2.5	1.7	2.5	2.6
21.....	4.4	9.2	5.8	3.2	1.7	1.7	1.6	4.4	2.4	1.7	2.3	2.4
22.....	4.0	10.0	5.5	3.4	1.7	1.3	1.5	4.2	2.4	1.6	2.2	2.4
23.....	5.5	11.5	5.3	3.6	1.7	1.9	1.8	4.0	2.7	1.6	2.2	2.7
24.....	9.7	12.3	5.2	3.0	1.6	1.9	2.0	3.8	3.0	1.6	2.2	2.4
25.....	11.6	13.7	5.9	2.8	1.6	1.9	2.2	3.9	2.7	1.6	2.3	2.3
26.....	12.7	12.5	6.8	2.6	1.6	1.9	2.4	4.2	2.6	1.6	2.4	2.2
27.....	13.4	11.7	7.2	2.5	1.6	1.9	2.2	4.5	2.5	1.5	2.4	2.2
28.....	12.2	10.2	8.0	2.5	1.6	1.8	2.0	4.9	2.4	1.5	2.2	2.2
29.....	11.0	9.8	7.6	2.5	1.9	1.8	2.0	5.2	2.3	1.5	2.2	2.4
30.....	10.5	6.9	2.3	1.8	1.8	1.9	5.6	2.2	1.5	2.2	2.5
31.....	9.8	6.3	1.9	2.3	5.9	1.5	2.7
1905												
1.....	2.6	3.3	9.8	6.2	4.9	2.5	2.0	3.0	3.2	1.5	1.4	1.3
2.....	2.6	3.3	8.7	6.2	4.9	2.6	2.2	3.9	3.0	1.5	1.3	1.3
3.....	2.6	3.3	7.7	5.5	4.9	2.4	2.5	3.6	2.8	1.5	1.3	1.8
4.....	2.6	3.3	7.5	5.3	4.7	2.3	2.4	3.5	2.4	1.4	1.3	2.2
5.....	2.6	3.2	7.0	5.1	4.5	2.1	2.3	3.5	2.0	1.4	1.3	2.5
6.....	2.6	3.4	6.3	5.4	4.5	1.9	3.7	3.4	2.4	1.4	1.3	2.4
7.....	2.7	3.6	6.4	5.7	4.5	1.8	4.5	3.0	2.6	1.4	1.3	2.2
8.....	2.9	4.0	6.2	5.7	4.5	1.8	7.4	2.8	2.4	1.5	1.3	2.3
9.....	2.9	4.7	6.2	5.6	4.4	1.7	7.5	2.6	2.2	1.6	1.3	2.5
10.....	2.8	5.3	6.2	5.6	4.3	1.7	7.7	2.5	2.2	1.5	1.3	2.8
11.....	2.8	5.6	6.7	6.0	4.0	1.6	7.7	2.2	2.0	1.4	1.5	2.8
12.....	2.8	6.6	8.0	6.0	3.4	1.6	7.9	2.0	2.0	1.4	1.5	2.7
13.....	3.0	8.1	10.4	6.4	3.0	1.6	8.0	2.3	1.9	1.4	1.5	2.5
14.....	3.5	10.1	13.4	7.2	3.0	1.6	7.2	2.6	1.8	1.4	1.5	2.8
15.....	4.0	11.2	14.2	7.4	3.0	1.6	6.5	3.1	1.8	1.4	1.4	3.0
16.....	4.5	11.9	14.1	9.2	2.9	1.8	6.5	3.1	1.9	1.4	1.3	3.4
17.....	4.4	13.1	13.9	6.8	2.5	2.0	6.5	3.1	1.8	1.4	1.3	3.3
18.....	4.3	14.8	13.8	6.5	2.4	2.6	6.0	3.2	1.7	1.4	1.3	3.2
19.....	4.2	14.5	13.7	6.5	2.4	2.8	6.2	3.3	1.9	1.3	1.3	3.0
20.....	4.1	13.1	13.0	6.4	2.4	3.1	6.3	4.0	1.9	1.3	1.3	3.1
21.....	4.1	11.0	12.1	6.2	2.4	3.3	5.3	5.0	2.0	1.3	1.3	3.6
22.....	4.0	10.5	11.2	6.0	2.6	3.0	3.8	5.6	2.0	1.3	1.3	4.3
23.....	3.9	11.6	10.2	5.9	2.7	2.5	3.2	6.0	1.8	1.3	1.3	4.2
24.....	3.6	11.7	9.2	5.8	2.8	2.6	3.1	4.2	1.7	1.3	1.4	4.8
25.....	3.6	11.5	8.0	5.9	2.9	2.6	2.6	3.3	1.7	1.3	1.4	5.1
26.....	3.5	13.0	8.9	6.1	2.8	2.5	2.1	3.0	1.6	1.4	1.4	5.0
27.....	3.5	12.0	7.6	6.1	2.8	2.3	2.0	3.2	1.6	1.4	1.4	4.8
28.....	3.4	10.7	6.9	5.8	2.8	2.0	2.2	3.5	1.6	1.4	1.3	4.7
29.....	3.2	6.7	5.4	2.7	1.9	2.3	3.6	1.5	1.4	1.3	4.7
30.....	3.1	6.5	5.0	2.6	1.8	2.3	3.7	1.5	1.4	1.3	4.8
31.....	3.3	6.2	2.5	2.9	3.4	1.4	4.7

OGEECHEE DRAINAGE BASIN, STREAM FLOW

111

Daily gage height, in feet, of Cannochee River near Groveland, Ga., for 1906.

Day.	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1.....	4.8	10.1	7.7	7.3	2.4	3.4	4.7	9.0	5.8	3.8	2.4	2.1
2.....	5.0	9.6	7.0	6.9	2.3	3.1	5.7	10.5	6.0	3.8	2.4	2.1
3.....	5.4	8.6	6.8	6.6	2.2	2.9	5.2	13.0	6.2	3.9	2.3	2.1
4.....	5.7	7.0	8.9	6.4	2.2	3.9	5.8	11.9	6.1	5.3	2.2	2.2
5.....	6.0	6.6	11.7	5.8	2.2	4.5	6.4	10.5	6.0	7.4	2.3	2.5
6.....	6.6	6.1	12.5	5.2	2.1	5.7	7.1	10.0	5.9	8.4	2.3	2.5
7.....	7.1	6.1	11.4	4.8	2.5	7.6	7.6	9.7	5.8	7.4	2.3	2.7
8.....	7.0	7.0	10.0	4.8	5.0	8.4	7.7	9.0	5.0	6.8	2.2	2.9
9.....	6.6	7.8	10.4	4.6	5.5	7.5	7.8	8.0	4.6	5.2	2.1	2.7
10.....	6.2	9.1	11.1	4.1	4.6	4.7	9.1	7.0	4.0	4.5	2.1	2.5
11.....	6.1	10.0	11.3	4.0	4.3	4.2	10.4	6.5	3.6	4.3	2.1	2.3
12.....	5.8	11.1	10.9	3.9	3.7	7.0	12.7	5.0	3.3	4.0	2.0	2.3
13.....	5.6	11.7	10.5	3.8	3.3	9.6	10.8	5.5	3.3	3.5	2.0	2.3
14.....	5.4	12.0	9.9	3.7	3.0	11.9	9.6	4.9	3.3	3.5	2.0	2.3
15.....	5.3	11.6	9.2	4.0	2.8	14.0	8.0	4.9	3.0	3.0	2.1	2.3
16.....	5.2	11.2	8.3	4.8	2.6	17.0	7.2	5.0	3.3	3.0	2.2	2.2
17.....	5.2	11.0	7.4	4.8	2.6	17.2	9.2	4.6	3.3	2.8	2.3	2.1
18.....	5.1	10.5	6.8	4.9	2.5	16.4	10.9	4.5	3.4	2.7	2.4	2.0
19.....	5.0	9.8	6.4	5.0	2.3	15.2	12.2	4.4	3.4	2.7	2.4	2.0
20.....	4.9	8.9	7.0	4.9	2.3	13.2	12.5	4.3	3.5	2.9	2.4	2.0
21.....	4.8	7.8	8.6	4.5	2.2	11.4	13.2	3.3	3.4	3.0	2.4	2.0
22.....	5.0	8.5	9.7	4.3	2.1	10.2	11.9	4.0	3.2	3.2	2.4	2.1
23.....	5.1	9.3	9.5	3.9	2.0	8.2	10.9	4.5	3.1	3.2	2.4	2.3
24.....	6.4	10.3	9.4	3.3	2.1	7.2	10.7	6.0	3.0	3.1	2.4	2.5
25.....	6.7	9.2	9.3	3.1	3.3	6.6	10.9	6.3	3.4	3.0	2.4	2.6
26.....	7.5	9.42	8.9	3.0	4.8	5.5	11.9	6.4	3.6	2.9	2.3	2.6
27.....	9.0	8.5	8.0	2.8	5.1	4.4	12.4	6.2	3.8	2.9	2.2	2.6
28.....	10.3	8.2	7.3	2.6	4.4	4.3	12.2	6.5	4.3	2.8	2.2	2.6
29.....	11.1	7.0	2.5	4.2	4.1	10.5	5.8	4.3	2.7	2.1	2.6
30.....	10.5	7.2	2.4	3.8	4.4	9.4	5.8	3.9	2.7	2.1	2.7
31.....	10.7	7.4	3.5	8.3	5.8	2.7	2.9

WATER POWERS OF GEORGIA

Rating tables for Camoochee River near Groveland.

JUNE 23 TO DECEMBER 31, 1903.^a

Gage height	Dis-charge						
<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>
2.80	142	3.90	316	6.40	1,150	9.00	2,060
2.70	151	4.00	338	6.60	1,220	9.50	2,235
2.80	160	4.20	359	6.80	1,290	10.00	2,410
2.90	170	4.40	451	7.00	1,360	10.50	2,585
3.00	180	4.60	520	7.20	1,430	11.00	2,760
3.10	191	4.80	590	7.40	1,500	11.50	2,935
3.20	203	5.00	660	7.60	1,570	12.00	3,110
3.30	216	5.20	730	7.80	1,640	13.00	3,460
3.40	230	5.40	800	8.00	1,710	14.00	3,810
3.50	245	5.60	870	8.20	1,780	15.00	4,160
3.60	261	5.80	940	8.40	1,850	16.00	4,510
3.70	278	6.00	1,010	8.60	1,920	17.00	4,860
3.80	296	6.20	1,080	8.80	1,990	18.00	5,210

JANUARY 1 TO DECEMBER 31, 1904.^b

1.50	30	2.70	149	4.60	554	8.50	1,740
1.60	36	2.80	165	4.80	608	9.00	1,915
1.70	42	2.90	182	5.00	660	9.50	2,090
1.80	49	3.00	200	5.20	714	10.00	2,275
1.90	57	3.10	218	5.40	769	11.00	2,650
2.00	65	3.20	237	5.60	825	12.00	3,025
2.10	74	3.40	276	5.80	882	13.00	3,400
2.20	84	3.60	317	6.00	940	14.00	3,775
2.30	95	3.80	360	6.50	1,090	15.00	4,150
2.40	107	4.00	405	7.00	1,245		
2.50	120	4.20	453	7.50	1,405		
2.60	134	4.40	503	8.00	1,570		

JANUARY 1 TO DECEMBER 31, 1905.^c

1.30	27	1.90	66	2.50	131	3.10	220
1.40	32	2.00	75	2.60	144	3.20	238
1.50	38	2.10	85	2.70	158	3.30	257
1.60	44	2.20	96	2.80	172		
1.70	51	2.30	107	2.90	187		
1.80	58	2.40	119	3.00	203		

JANUARY 1 TO DECEMBER 31, 1906.

2.00	75	3.30	257	4.60	554	6.80	1,133
2.10	85	3.40	276	4.70	580	7.00	1,245
2.20	96	3.50	296	4.80	606	7.20	1,309
2.30	107	3.60	317	4.90	633	7.40	1,373
2.40	119	3.70	338	5.00	660	7.60	1,438
2.50	131	3.80	360	5.20	714	7.80	1,504
2.60	144	3.90	382	5.40	769	8.00	1,570
2.70	158	4.00	405	5.60	825	9.00	1,915
2.80	172	4.10	429	5.80	882	10.00	2,275
2.90	187	4.20	453	6.00	940	11.00	2,650
3.00	203	4.30	478	6.20	1,000	12.00	3,025
3.10	220	4.40	503	6.40	1,060		
3.20	238	4.50	528	6.60	1,121		

NOTE.—The above table is based on discharge measurements made during 1903-1906 and is well defined below gage height 6.2 feet. Above gage height 10 feet the rating curve is a tangent, the difference being 375 per foot.

^a Above gage height 4.50 feet the rating curve is a tangent, the difference being 35 per tenth.

^b Above 10 feet the rating curve is a tangent, the difference being 75 per 0.2 foot rise in gage.

^c Above 3.3 feet this table is the same as the one for 1904.

OGEECHEE DRAINAGE BASIN, STREAM FLOW

Estimated monthly discharge of Cannoochee River near Groveland.

[Drainage area, 960 square miles.]

Month.	Discharge in second-feet.			Run-off.	
	Maximum.	Minimum.	Mean.	Sec. ft. per sq. mile.	Depth in inches.
1903.					
June 23-30.....	2,060	730	1,141	1.19	0.354
July.....	2,620	151	1,242	1.29	1.49
August.....	4,930	142	2,100	2.19	2.52
September.....	5,210	261	1,855	1.93	2.15
October.....	2,200	278	774	.806	.929
November.....	1,325	296	646	.673	.751
December.....	1,605	296	499	.520	.600
1904.					
January.....	3,550	405	1,317	1.37	1.58
February.....	4,900	1,000	2,508	2.61	2.32
March.....	2,131	714	1,301	1.36	1.57
April.....	911	95	423	.446	.498
May.....	107	36	60.8	.063	.073
June.....	65	36	52.2	.054	.060
July.....	107	30	52.6	.055	.063
August.....	3,850	360	1,324	1.33	1.59
September.....	1,133	84	390	.406	.453
October.....	74	30	42.0	.044	.051
November.....	149	30	84.1	.088	.098
December.....	182	74	122	.127	.146
The year.....	4,300	30	640	.667	9.00
1905.					
January.....	523	144	279	.291	.336
February.....	4,075	238	1,835	1.96	2.04
March.....	3,350	1,000	2,050	2.14	2.47
April.....	1,987	660	976	1.02	1.14
May.....	633	119	299	.311	.353
June.....	257	44	102	.106	.118
July.....	1,570	75	649	.676	.779
August.....	940	75	297	.309	.356
September.....	233	38	84.6	.083	.093
October.....	44	27	32.2	.034	.039
November.....	33	27	29.5	.031	.035
December.....	687	27	295	.307	.354
The year.....	4,075	27	532	.606	8.12
1906.					
January.....	2,690	606	1,120	1.17	1.35
February.....	3,020	970	2,010	2.09	2.13
March.....	3,210	1,060	1,920	2.00	2.31
April.....	1,340	119	539	.561	.63
May.....	797	75	272	.283	.33
June.....	4,980	187	1,750	1.82	2.03
July.....	3,430	530	2,120	2.21	2.55
August.....	3,400	257	1,230	1.28	1.43
September.....	1,000	203	468	.483	.54
October.....	1,710	158	432	.450	.52
November.....	119	75	102	.106	.12
December.....	137	75	118	.123	.14
The year.....	4,980	75	1,010	1.05	14.13

MISCELLANEOUS MEASUREMENTS IN OGEECHEE RIVER DRAINAGE BASIN.

Buckhead Creek.—This stream was measured at Daniels Bridge, 1 mile northwest of Millen. The bench mark is the top of first bent from a large cypress stump near the right bank, downstream side of bridge.

Discharge measurements of Buckhead Creek at Daniels Bridge, 1 mile northwest of Millen.

Date	Height of bench mark above water	Discharge
1903		
	<i>Feet</i>	<i>Sec.-ft.</i>
June 10.....	4.68	617
June 11.....	3.33	1,163
June 20.....	6.71	251
July 18.....	5.02	500
October 10.....	9.34	107

Bull Creek.—At the new bridge 2 miles southeast of Claxton this stream was discharging 18 second-feet on June 22, 1903, when the water surface was 5.40 feet below the top of the upstream end of the cap of the first bent from right bank.

Cannoochee River.—At Moores Bridge, 2½ miles northwest of Groveland, this stream was discharging 1,958 second-feet on June 9, 1903, when the water surface was 6.87 feet below the top of the first bent from the right bank, upstream side of bridge.

At Hendrix Bridge, 1½ miles from Claxton, this stream was discharging 469 second-feet on June 22, 1903, when the water surface was 13.40 feet below the bridge floor at 50 feet from the outer edge of the post at the end of the hand rail, right bank, upstream side.

Cedar Creek.—At 1¾ miles northwest of Claxton this stream was discharging 11 second-feet on June 22, 1903, when the water surface was 10.13 feet below the bridge floor at midstream.

Little Ogeechee River.—Near Agricola this stream was discharging 4.2 second-feet on October 14, 1903, when the water surface was 13.83 feet below the top of the floor at the hand-rail brace.

Lotts Creek.—This stream was measured at a foot log 100 yards above its mouth, about 2 miles northwest of Groveland. The bench mark is a large spike in a 9 by 9 post near right bank.

Discharge measurements of Lotts Creek, about 2 miles northwest of Groveland.

Date	Height of bench mark above water	Discharge
1903	<i>Feet</i>	<i>Sec.-ft.</i>
June 23.....	8.00	253
October 9.....	9.47	119
October 9.....	9.47	112

A measurement made June 12, 1905, gave the following results:

Width, 16 feet; area, 11.4 square feet; mean velocity, 1.18 feet per second; discharge, 13 second-feet.

Ogeechee River.—At Harrisons Bridge, 2 miles west of Agricola, this stream was discharging 24 second-feet on October 14, 1903, when the water surface was 19.56 feet below the top of the bent at the right end of the bridge, downstream side.

At the wagon bridge 5 miles northeast of Davisboro this stream was discharging 197 second-feet on November 20, 1903, when the water surface was 12.20 feet below the top of the second bent from the left bank.

Williamsons Swamp Creek (west prong).—At Buffalo Ford, near Sandersville, this stream was discharging 16 second-feet on July 2, 1903, when the water was at ordinary stage.

Williamsons Swamp Creek (north prong).—At Jones Bridge, near Sandersville, this stream was discharging 19 second-feet on July 2, 1903, when the water was at ordinary stage.

Williamsons Swamp Creek.—At Jordans Mill Bridge, near Sandersville, this stream was discharging 95 second-feet on July 2, 1903, when the water was at ordinary stage.

ALTAMAHA RIVER DRAINAGE BASIN.

DESCRIPTION OF BASIN.

Altamaha River is formed by the junction of Oconee and Ocmulgee rivers, which unite at the southern boundary of Montgomery County, Ga. Ochoopee River is also a tributary, entering from the north side about 50 miles below the junction of the Oconee and Ocmulgee. The Altamaha River drainage is entirely within the State of Georgia. The river rises in the north-central part and flows in a southeasterly direction, emptying into the Atlantic Ocean near Darien. Below the junction of the Oconee and Ocmulgee and for a long distance above, on both rivers, there is no great amount of fall. Steamboat navigation is carried on from Darien to Macon on the Ocmulgee, and to Dublin, and at times to Milledgeville, on the Oconee.

Ochoopee River rises in Washington County and flows in a southeasterly direction to the Altamaha. It flows from the low hills of southeastern Georgia into the flat pine lands. Though it has not so much fall as the more northern streams, it has considerable fall that can be developed into power.

Oconee River rises on the southern slope of the Chattahoochee Ridge, in Hill County, and joins the middle Oconee on the southwest boundary of Clarke County. From there it flows in a southeasterly direction to the Altamaha. Apalachee River is a large tributary which rises in Gwinnett and Walton counties and enters the Oconee near the southeastern corner of Morgan County. Little River enters the main stream at the corner of Putnam, Hancock, and Baldwin counties, about 15 miles above Milledgeville, Ga. These tributaries have much fall, and a small part of it is developed. The Oconee has a fall of 250 feet in 45 miles. It has some very large water powers available from its source down to Milledgeville, where it crosses the fall line.

Ocmulgee River, the most westerly of the main tributaries, rises in the north-central part of Georgia on the southern slope of the Chattahoochee Ridge in Fulton, DeKalb, and Gwinnett counties. It is formed by the junction of Yellow and South rivers just south of the southern corner of Newton County. Yellow River rises in Gwinnett County and flows in a southerly direction into the Ocmulgee. South River rises in Fulton and DeKalb counties and flows

in a southeasterly direction. Alcovy River joins the Ocmulgee about 5 miles below the junction of the South and Yellow rivers. Towaliga River enters the Ocmulgee at about the southwest corner of Jasper County.

All these tributaries rise in and flow through a very hilly country and have a great deal of fall. Ocmulgee River has a fall of over 210 feet in 35 miles. The last fall of much size is only a few miles above Macon, Ga.

STREAM FLOW.

SOUTH RIVER NEAR LITHONIA.

This station was established by F. A. Murray on August 17, 1903, a short distance above Albert Shoals, 6 miles south of Lithonia, and was discontinued on December 31, 1904.

The channel above the station is nearly straight for about 300 feet, and the current is sluggish, being held back by rock ledges below the station. Below the station the channel curves slightly and the current is sluggish for about 400 feet, at which point the shoals begin. The right bank is low and overflows at a gage height of 9 or 10 feet into a second channel, which has a width at high water of about 200 feet. The left bank is high and rocky, and does not overflow. The bottom is solid rock.

Discharge measurements were made from the 3-span wooden highway bridge. The initial point for soundings is the end of the bridge on the right bank, upstream side.

The gage is a vertical 10-foot rod fastened to a tree on the right bank just below the bridge. It was read once each day by W. N. New, who was paid by the Georgia Geological Survey.

Bench mark No. 1 is the top of the upstream end of the first wooden floor beam from the right bank; elevation, 15.00 feet above the zero of the gage. Bench mark No. 2 is the center of a wire nail driven horizontally in the upstream side of the base of a willow tree on the left bank about 40 feet upstream from the bridge; elevation, 4.00 feet above the zero of the gage.

WATER POWERS OF GEORGIA

Discharge measurements of South River near Lithonia.

Date	Gage height	Dis-charge	Date	Gage height	Dis-charge
1903			1904		
	<i>Feet</i>	<i>Sec.-ft.</i>		<i>Feet</i>	<i>Sec.-ft.</i>
August 17.....	3.55	179	March 11.....	3.67	185
September 10.....	3.43	104	July 16.....	3.22	56
September 10a.....	3.46	120	August 9.....	4.90	1,172
October 5.....	3.40	104	August 9.....	4.60	934
			August 10.....	4.53	812
1904			September 23.....	3.16	55
January 13.....	3.58	138	December 5.....	4.28	588
March 7.....	4.20	549			

a Parkers Bridge, 1 mile above station.

Daily gage height, in feet, of South River, near Lithonia.

Day.	Aug.	Sept.	Oct.	Nov.	Dec.	Day.	Aug.	Sept.	Oct.	Nov.	Dec.
1903.						1903.					
1.....		3.5	3.5	3.5	3.5	17.....	3.5	3.9	3.5	3.5	3.5
2.....		3.4	3.5	3.5	3.5	18.....	4.1	3.6	3.6	3.6	3.5
3.....		3.5	3.5	3.5	3.5	19.....	3.8	3.5	3.5	3.6	3.5
4.....		3.4	3.5	4.6	3.5	20.....	3.6	3.4	3.5	3.5	3.6
5.....		3.4	3.5	4.0	3.5	21.....	3.5	3.5	3.5	3.5	3.5
6.....		3.4	3.5	3.6	3.5	22.....	3.6	3.5	3.5	3.5	3.5
7.....		3.5	3.5	3.6	3.5	23.....	3.4	3.5	3.5	3.5	3.5
8.....		3.4	3.5	3.6	3.5	24.....	3.5	3.5	3.5	3.5	3.5
9.....		3.4	3.5	3.6	3.5	25.....	3.5	3.5	3.5	3.5	3.5
10.....		3.4	3.5	3.6	3.5	26.....	3.5	3.5	3.5	3.5	3.6
11.....		3.5	3.5	3.6	3.5	27.....	3.6	3.5	3.5	3.6	3.5
12.....		3.4	3.5	3.5	3.5	28.....	3.5	3.5	3.5	3.5	3.5
13.....		3.5	3.5	3.6	3.5	29.....	3.6	3.5	3.5	3.5	3.5
14.....		3.4	3.5	3.6	3.5	30.....	3.6	3.5	3.5	3.5	3.5
15.....		4.5	3.5	3.5	3.5	31.....	3.4	3.5	3.5
16.....		4.4	3.5	3.5	3.5						

Day.	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1904.												
1.....	3.5	3.6	3.6	3.6	3.6	4.1	3.7	3.6	3.5	3.4	3.3	3.5
2.....	3.5	3.6	3.6	3.6	3.6	3.6	3.6	3.6	3.5	3.4	3.3	3.5
3.....	3.5	3.6	3.6	3.6	3.6	3.6	3.6	4.3	3.5	3.4	3.3	3.5
4.....	3.5	3.5	3.7	3.6	3.6	3.5	3.5	3.6	4.2	3.4	3.3	3.5
5.....	3.5	3.5	3.6	3.6	3.6	3.6	3.5	3.5	3.8	3.4	3.3	4.3
6.....	3.5	3.6	3.5	3.6	3.5	3.8	3.5	3.7	3.6	3.4	3.3	3.7
7.....	3.5	3.6	4.2	3.7	3.5	4.4	3.5	5.7	3.6	3.4	3.3	3.6
8.....	3.5	4.1	4.1	3.7	4.1	3.8	3.5	6.3	3.6	3.4	3.3	3.6
9.....	3.5	3.7	3.65	3.6	3.7	3.7	3.5	6.5	3.6	3.3	3.3	3.5
10.....	3.5	4.5	3.6	3.7	3.6	3.6	3.6	4.6	3.6	3.2	3.3	3.6
11.....	3.5	4.3	3.7	3.6	3.6	3.6	3.5	3.8	3.6	3.3	3.3	3.6
12.....	3.5	3.7	3.7	3.7	3.6	3.6	3.6	3.7	3.6	3.3	3.3	3.6
13.....	3.5	3.6	3.6	3.7	3.6	3.6	3.6	3.6	3.5	3.3	3.4	3.6
14.....	3.5	3.7	4.1	3.6	3.6	3.5	3.6	3.6	3.5	3.3	3.3	3.6
15.....	3.6	3.7	3.7	3.6	3.6	3.5	3.5	3.7	3.5	3.3	3.3	3.6
16.....	3.5	3.6	3.7	3.6	3.6	3.5	3.5	4.2	3.5	3.2	3.3	3.6
17.....	3.7	3.6	3.65	3.6	3.6	3.5	3.5	3.3	3.6	3.2	3.3	3.6
18.....	3.6	3.7	3.6	3.6	3.6	3.5	3.6	3.6	3.5	3.2	3.3	3.6
19.....	3.6	3.7	3.6	3.6	3.5	3.5	3.5	4.1	3.5	3.3	3.3	3.6
20.....	3.6	4.5	3.6	3.6	3.5	3.6	3.5	3.6	3.5	3.3	3.3	3.6
21.....	3.6	4.1	3.6	3.6	3.5	3.6	3.5	3.6	3.5	3.3	3.3	3.6
22.....	4.6	4.6	3.7	3.6	3.6	3.8	3.5	3.6	3.5	3.3	3.4	3.6
23.....	4.2	4.5	3.7	3.6	3.5	3.7	3.7	3.5	3.5	3.3	3.4	3.6
24.....	4.1	4.3	3.7	3.6	3.5	3.6	3.6	3.5	3.5	3.2	3.4	3.6
25.....	4.1	3.8	3.7	3.6	3.5	3.6	3.5	3.6	3.5	3.2	3.4	3.6
26.....	3.6	3.7	3.7	3.7	3.5	3.5	3.5	3.5	3.5	3.2	3.4	3.6
27.....	3.6	3.7	3.6	3.7	3.5	3.5	3.5	3.6	3.5	3.2	3.4	3.3
28.....	3.5	3.7	3.6	3.6	3.5	3.8	3.5	3.7	3.4	3.2	3.4	3.9
29.....	3.5	3.6	3.6	3.6	3.5	3.8	4.5	3.6	3.4	3.2	3.4	3.6
30.....	3.5	3.6	3.6	3.8	3.8	3.7	3.6	3.4	3.2	3.4	3.6
31.....	3.5	3.6	4.6	3.5	3.5	3.2	3.6

Rating table for South River, near Lithonia, from August 17, 1903, to December 31, 1904.

Gage height.	Dis-charge.						
<i>Feet.</i>	<i>Sec.-ft.</i>	<i>Feet.</i>	<i>Sec.-ft.</i>	<i>Feet.</i>	<i>Sec.-ft.</i>	<i>Feet.</i>	<i>Sec.-ft.</i>
3.20	55	4.10	454	5.00	1,220	5.80	2,050
3.30	77	4.20	580	5.10	1,320	5.90	2,190
3.40	100	4.30	606	5.20	1,420	6.00	2,340
3.50	130	4.40	684	5.30	1,520	6.20	2,660
3.60	168	4.50	764	5.40	1,620	6.40	3,020
3.70	214	4.60	848	5.50	1,720	6.60	3,400
3.80	266	4.70	986	5.60	1,820	6.80	3,800
3.90	322	4.80	1,025	5.70	1,980		
4.00	384	4.90	1,120				

Estimated monthly discharge of South River near Lithonia.

Month.	Discharge in second-feet.		
	Maximum.	Minimum.	Mean.
1903.			
August 17-31.....	454	100	169
September.....	764	100	167
October.....	168	130	131
November.....	848	130	178
December.....	168	130	135
1904.			
January.....	848	130	198
February.....	848	130	318
March.....	530	130	213
April.....	214	168	179
May.....	848	130	189
June.....	684	130	206
July.....	764	130	168
August.....	3,800	130	502
September.....	530	100	155
October.....	100	55	74.4
November.....	100	77	84.7
December.....	606	130	186
The year.....	3,800	55	206

SOUTH RIVER NEAR SNAPPING SHOALS.

This station was established in 1905 for the purpose of making a series of miscellaneous discharge measurements. It is located at a four-span wooden bridge, known as Butlers Bridge, about 15 miles south from Conyers, and 4 miles above Snapping Shoals, where there is a large amount of fall.

The current is smooth and is fairly swift at lowest water. It is broken by one pier at low water. The right bank may overflow beyond the bridge approach at high floods. The left bank will not overflow. The bed is sandy and will probably change.

Gage heights are determined directly from the bench mark, which is the top of the downstream end, at the edge of the floor, of the first wooden floor beam from the left end of the third span from the left bank; elevation, 25.00 feet above the datum of the assumed gage.

Discharge measurements of South River, near Snapping Shoals.

Date.	Gage height.	Dis-charge.
1905.	<i>Feet.</i>	<i>Sec.-ft.</i>
October 23	8.46	120
October 24	8.56	135


OCMULGEE RIVER NEAR FLOVILLA.

A station was established July 26, 1901, on Ocmulgee River at Lamars Ferry, one-half mile below Lamar's mill and 5 miles east of Flovilla. The object of this station was to compare the discharge of the river at this point with its discharge below, at Macon, through the low-water season. The gage and bench marks were washed away by a flood February 27, 1902. The station was reestablished June 18, 1903, at Lamars Ferry, by M. R. Hall.


The channel is straight for 1,000 feet above and 5,000 feet below the station. The current is swift and regular. The right bank is high, but overflows at extreme high water. The left bank is somewhat lower. The bed of the stream is sandy and shifting, and there is but one channel.

Discharge measurements are made from the ferryboat. The initial point for soundings is the windlass on the right bank.

The vertical gage is in three sections: The first section, reading from 0 to 5 feet, is fastened to a willow tree at the mouth of a small branch about 20 feet above the ferry landing on the right bank; the second section, reading from 5 to 15 feet, is nailed to an ash tree about 60 feet from the river up the same branch; the third section, reading from 15 to 25 feet, is attached to a cottonwood tree on the bank of the same branch, about 200 feet from the river. No attempt was made to place this gage on the same datum as the old one. The gage is read once each day by B. S. White, who is paid by the Georgia Geological Survey. During the low-water period from October 1 to December 31, 1905, the gage was read twice each day. Bench marks were established as follows: (1) A nail driven into a large cottonwood tree about 200 feet from the river, on the branch on which the gage is located; elevation, 14.00 feet. (2) A cross in the solid rock, 100 feet uphill from the first bench mark and



VIEW OF THE EAGLE AND PHENIX MILLS, COLUMBUS, GEORGIA.



ALTAMAHA DRAINAGE BASIN, STREAM FLOW

140 feet north from the wagon road, at a point 250 feet west of the ferry; elevation, 34.24 feet. Elevations refer to the datum of the gage.

Discharge measurements of Ocmulgee River near Flowilla.

Date.	Gage height.	Dis-charge.	Date.	Gage height.	Dis-charge.
1901.			1904:		
July 26.....	Feet. a2.93	Sec.-ft. 1,035	January 22.....	Feet. 5.50	Sec.-ft. 3,459 ^a
September 12.....	a3.10	1,087	February 16.....	2.93	1,745
November 5.....	a2.90	948	April 15.....	1.67	970
1902.			May 28.....	.50	511
February 10.....	a5.60	2,376	June 17.....	.47	463
1903.			July 12.....	1.39	891
June 18.....	2.00	1,383	August 26.....	2.36	1,450
August 25.....	1.61	893	September 20.....	.03	332
September 29.....	1.35	771	October 6.....	.21	302
October 13.....	1.30	701	November 2.....	.08	406
November 12.....	1.78	1,070	December 21.....	.98	740
December 19.....	1.61	879	1905.		
1904.			March 25.....	1.88	1,155
January 13.....	1.97	1,130	June 15.....	1.16	1,074
January 21.....	1.85	1,003	July 24.....	.34	496
			September 29.....	.32	293
			November 3.....	.27	474

^aOld gage for 1901 and 1902 measurements.

Daily gage height, in feet, of Ocmulgee River near Flowilla.

Date.	July	Aug.	Sept.	Oct.	Nov.	Dec.	Date.	July	Aug.	Sept.	Oct.	Nov.	Dec.	
1901.							1901.							
1.....		3.0	7.9	3.5	2.7	2.8	17.....		10.0	7.5	3.0	2.7	5.3 ^a	
2.....		2.7	6.7	5.9	2.8	2.7	18.....		2.7	17.4	3.0	2.7	4.5 ^a	
3.....		2.6	4.5	6.5	2.8	3.3	19.....		6.9	18.3	2.9	2.7	4.0 ^a	
4.....		2.5	4.1	5.1	2.8	4.2	20.....		5.0	9.0	2.9	3.2	3.7	
5.....		2.7	3.7	4.0	2.8	3.7	21.....		5.4	6.8	2.9	3.2	3.5 ^a	
6.....		6.0	3.6	3.6	2.8	3.4	22.....		9.0	6.0	2.9	3.1	3.2 ^a	
7.....		6.5	3.4	3.4	2.8	3.6	23.....		16.0	5.7	2.9	3.0	3.6 ^a	
8.....		5.0	3.3	3.3	2.8	3.2	24.....		16.5	5.3	2.9	3.0	4.2 ^a	
9.....		3.9	3.2	3.2	2.8	3.1	25.....		7.0	4.9	2.8	3.0	4.2 ^a	
10.....		2.2	3.1	3.2	2.8	3.4	26.....		2.9	6.1	4.2	2.7	3.9	
11.....		10.5	3.1	3.2	2.8	3.3	27.....		2.8	8.7	3.5	2.8	2.9	
12.....		5.2	3.1	3.1	2.8	3.6	28.....		3.5	9.7	3.5	2.8	2.8	
13.....		5.3	3.0	3.5	2.8	3.4	29.....		3.1	8.9	4.0	2.8	2.8	
14.....		4.0	4.0	3.4	2.8	3.3	30.....		3.6	7.1	4.0	2.8	2.8	
15.....		4.5	3.5	3.2	2.8	10.2	31.....		3.4	5.3	2.8	
16.....		12.4	3.2	3.0	2.7	6.8							18.0 ^a	
1902.							1902.							
1.....	Jan.	Feb.	Day.	Jan.	Feb.	Day.	Jan.	Feb.	Day.	Jan.	Feb.	Day.	Jan.	Feb.
1.....	14.0	14.6	9.....	4.4	5.7	17.....	3.8	5.5	25.....	4.0	6.2 ^a			
2.....	9.0	19.0	10.....	4.3	5.6	18.....	3.7	5.3	26.....	4.3	7.6			
3.....	6.5	20.2	11.....	4.1	5.3	19.....	3.9	5.0	27.....	4.4	7.6 ^a			
4.....	5.7	19.5	12.....	4.1	5.7	20.....	4.1	5.5	28.....	4.1	(a)			
5.....	5.2	10.0	13.....	4.0	5.0	21.....	4.2	5.8	29.....	4.7			
6.....	5.0	8.1	14.....	3.7	4.3	22.....	4.7	5.6	30.....	5.4			
7.....	4.3	7.2	15.....	3.7	5.2	23.....	4.5	5.4	31.....	5.3			
8.....	4.5	6.5	16.....	4.0	5.7	24.....	4.2	5.1					

^aGage washed out February 23, 1902.

WATER POWERS OF GEORGIA

Daily gage height, in feet, of Ocmulgee River near Flowilla—Continued.

Day.	July	Aug.	Sept.	Oct.	Nov.	Dec.	Day.	July.	Aug.	Sept.	Oct.	Nov.	Dec.
1903.							1903.						
1.....	2.2	1.6	1.2	1.3	1.2	1.5	17.....	2.9	3.3	6.5	1.8	1.5	1.7
2.....	1.9	1.4	1.1	1.3	1.2	1.5	18.....	2.4	7.5	3.9	1.8	1.7	1.7
3.....	2.3	2.1	1.1	1.3	1.3	1.4	19.....	2.3	6.1	2.8	1.7	1.7	1.6
4.....	2.9	4.0	1.3	1.2	1.4	1.7	20.....	2.1	3.4	2.4	1.5	1.8	1.7
5.....	2.7	3.4	1.1	1.2	3.2	1.6	21.....	1.9	2.7	1.9	1.4	1.5	2.0
6.....	2.1	2.7	0.9	1.2	2.2	1.6	22.....	1.7	2.4	1.8	1.3	1.5	2.0
7.....	2.6	2.1	0.9	1.2	2.1	1.6	23.....	1.6	2.1	1.7	1.2	1.6	1.9
8.....	3.2	1.7	0.9	1.3	2.3	1.7	24.....	1.5	1.9	1.6	1.2	1.6	1.7
9.....	3.3	1.5	0.8	1.3	1.5	1.6	25.....	1.5	1.6	1.5	1.1	1.7	1.7
10.....	3.3	1.4	0.7	1.3	1.6	2.1	26.....	1.4	1.5	1.5	1.1	1.6	2.0
11.....	3.2	1.3	0.9	1.2	1.4	2.0	27.....	1.3	1.4	1.4	1.1	1.6	2.5
12.....	5.3	1.7	0.8	1.1	1.8	1.8	28.....	1.2	1.3	1.4	1.2	1.5	1.9
13.....	4.5	1.3	0.8	1.1	1.7	1.7	29.....	1.3	1.2	1.4	1.2	1.5	1.8
14.....	9.5	3.8	1.1	1.0	1.6	1.9	30.....	1.5	1.1	1.3	1.2	1.5	1.7
15.....	6.6	5.2	6.2	0.9	1.5	1.8	31.....	2.0	1.2	1.2	1.7
16.....	4.0	9.2	9.9	1.2	1.5	1.7

Day.	Aug.	Sept.	Oct.	Nov.	Dec.	Day.	Aug.	Sept.	Oct.	Nov.	Dec.
1904.						1904.					
1.....	2.7	0.7	0.8	0.8	0.6	17.....	4.0	0.0	0.6	0.6	1.0
2.....	2.7	.7	.3	.2	.6	18.....	2.7	.0	.6	.5	1.0
3.....	2.2	.3	.3	.2	.8	19.....	1.7	.0	.4	.4	1.0
4.....	3.2	.4	.5	.7	1.2	20.....	1.5	.1	.4	.4	.9
5.....	1.5	3.7	.3	.9	1.8	21.....	1.1	.1	.3	.2	1.0
6.....	1.0	2.3	.3	.7	4.0	22.....	1.2	.1	.3	.5	.9
7.....	4.25	1.4	.3	.6	3.8	23.....	.9	.4	.3	.9	.9
8.....	7.4	1.0	.3	.4	3.0	24.....	1.3	.0	.4	.5	.8
9.....	10.5	.5	.3	.3	2.0	25.....	2.9	.2	.6	.4	.8
10.....	11.0	.3	.4	.1	2.8	26.....	2.4	.3	.6	.8	.7
11.....	7.6	.4	.5	.1	1.4	27.....	1.5	.3	.2	.7	1.0
12.....	5.0	.3	.3	.1	1.5	28.....	1.4	.2	.2	.4	3.5
13.....	4.0	.4	.3	.6	1.3	29.....	2.2	.1	.2	.6	3.5
14.....	3.9	.3	.3	1.1	1.0	30.....	1.1	.2	.1	.5	3.0
15.....	2.0	.2	.4	1.0	1.0	31.....	.93	1.9
16.....	4.1	.2	.4	.8	.9

Day.	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1905.												
1.....	1.6	1.4	2.6	1.5	1.4	1.0	6.0	0.5	0.3	0.2	0.35	0.65
2.....	1.5	1.5	2.5	1.5	1.3	.8	6.0	.4	.7	.4	.25	.65
3.....	1.4	1.4	2.4	1.4	2.1	.7	4.2	.3	1.6	1.15	.20	11.2
4.....	1.2	1.5	2.3	1.6	3.0	.8	2.4	.0	.5	.65	.15	14.4
5.....	1.1	1.4	2.1	1.7	3.2	.7	2.5	.1	.6	.6	.1	10.4
6.....	1.3	1.5	2.0	2.2	2.5	.7	2.1	.2	.5	.45	.1	4.8
7.....	1.7	1.4	2.0	2.0	2.0	.6	3.7	.3	.3	.25	.5	4.0
8.....	1.8	5.0	2.0	1.8	1.8	.5	2.6	.5	.1	.1	.4	3.4
9.....	1.8	6.9	2.0	2.2	1.9	.4	2.4	2.1	.2	.15	.3	6.6
10.....	1.4	7.1	2.4	4.3	1.5	.2	1.7	2.5	.0	.05	.9	8.6
11.....	1.5	6.2	2.1	3.0	1.3	.0	4.3	2.9	.1	.3	3.5	6.1
12.....	2.0	5.5	2.4	2.4	1.2	.0	3.4	9.2	.1	1.05	2.55	4.2
13.....	6.2	12.6	3.0	2.1	1.0	1.7	7.0	6.3	.1	.75	1.75	4.0
14.....	6.9	10.5	2.7	1.9	.9	1.0	4.0	4.3	.1	.5	1.25	3.6
15.....	6.0	7.2	2.5	1.5	.8	.7	2.9	5.3	.2	.35	1.0	4.0
16.....	2.1	5.0	2.2	2.0	1.5	1.2	2.1	3.7	.0	.3	.65	3.8
17.....	2.8	4.2	1.9	1.8	1.4	1.1	1.7	2.2	.1	.4	.25	3.4
18.....	2.6	4.0	1.9	1.6	1.3	.9	1.5	2.0	.0	.3	.4	3.0
19.....	2.1	3.5	1.8	1.4	1.0	.7	1.2	1.4	.2	.42	.5	1.9
20.....	2.1	3.3	1.7	1.5	.8	.4	1.0	1.1	.2	.72	.45	7.2
21.....	2.0	5.5	2.1	1.4	.6	.3	.9	.9	.2	.0	.55	14.6
22.....	1.8	6.6	2.5	1.3	.8	.2	.6	.3	.3	.0	.6	9.3
23.....	1.7	5.3	2.2	1.3	1.3	1.8	.4	.7	.3	.0	.58	5.0
24.....	1.6	4.3	2.0	1.3	3.9	2.3	.3	2.5	.4	.2	.5	6.0
25.....	1.4	3.9	1.9	1.3	4.0	1.3	.6	2.4	.5	.2	.5	5.2
26.....	1.3	3.6	1.7	1.2	3.6	1.1	1.9	1.2	.6	.7	.5	3.6
27.....	1.4	3.2	1.6	1.2	2.2	1.5	1.5	.7	.4	.7	.75	3.5
28.....	1.3	2.8	1.5	1.1	2.0	1.9	.8	.5	.5	.6	.35	3.4
29.....	1.5	1.4	1.0	1.9	2.2	.5	.4	.4	.4	.30	3.8
30.....	1.4	1.5	2.0	1.7	1.4	.3	.4	.2	.35	.75	3.6
31.....	1.5	1.4	1.52	.33	3.5

ALTAMAHA DRAINAGE BASIN, STREAM FLOW

Rating tables for Ocmulgee River near Flowilla.

JULY 26, 1901, TO FEBRUARY 27, 1902.^a

Gage height.	Dis-charge.						
<i>Feet.</i>	<i>Sec.-ft.</i>	<i>Feet.</i>	<i>Sec.-ft.</i>	<i>Feet.</i>	<i>Sec.-ft.</i>	<i>Feet.</i>	<i>Sec.-ft.</i>
2.50	885	3.60	1,344	5.40	2,271	13.00	6,185
2.60	870	3.70	1,395	5.60	2,374	14.00	6,700
2.70	907	3.80	1,447	5.80	2,477	15.00	7,215
2.80	947	3.90	1,498	6.00	2,580	16.00	7,730
2.90	990	4.00	1,550	6.50	2,837	17.00	8,245
3.00	1,037	4.20	1,653	7.00	3,095	18.00	8,760
3.10	1,087	4.40	1,756	8.00	3,610	19.00	9,275
3.20	1,138	4.60	1,859	9.00	4,125	20.00	9,790
3.30	1,189	4.80	1,962	10.00	4,640	21.00	10,305
3.40	1,241	5.00	2,065	11.00	5,155	22.00	10,820
3.50	1,292	5.20	2,168	12.00	5,670	23.00	11,335

JULY 1 TO DECEMBER 31, 1903.^b

0.70	635	2.00	1,120	3.30	2,010	5.00	3,200
.80	648	2.10	1,185	3.40	2,080	5.50	3,550
.90	663	2.20	1,250	3.50	2,150	6.00	3,900
1.00	680	2.30	1,315	3.60	2,220	6.50	4,250
1.10	700	2.40	1,380	3.70	2,290	7.00	4,600
1.20	725	2.50	1,450	3.80	2,360	7.50	4,950
1.30	755	2.60	1,520	3.90	2,430	8.00	5,300
1.40	790	2.70	1,590	4.00	2,500	8.50	5,650
1.50	832	2.80	1,660	4.10	2,570	9.00	6,000
1.60	880	2.90	1,730	4.20	2,640	9.50	6,350
1.70	935	3.00	1,800	4.30	2,710	10.00	6,700
1.80	995	3.10	1,870	4.40	2,780		
1.90	1,055	3.20	1,940	4.50	2,850		

AUGUST 1 TO DECEMBER 31, 1904.

-0.60	200	0.60	525	1.80	1,020	4.00	2,350
-.50	225	.70	560	1.90	1,070	4.20	2,490
-.40	250	.80	595	2.00	1,120	4.40	2,640
-.30	275	.90	630	2.20	1,225	4.60	2,790
-.20	300	1.00	670	2.40	1,335	4.80	2,940
-.10	325	1.10	710	2.60	1,450	5.00	3,090
.00	350	1.20	750	2.80	1,570	5.50	3,475
.10	375	1.30	790	3.00	1,690	6.00	3,875
.20	400	1.40	835	3.20	1,820	6.50	4,275
.30	430	1.50	880	3.40	1,950	7.00	4,675
.40	460	1.60	925	3.60	2,080	7.50	5,085
.50	490	1.70	970	3.80	2,210		

JANUARY 1 TO DECEMBER 31, 1905.^c

-0.60	220	0.40	510	1.40	895	2.40	1,370
-.50	245	.50	545	1.50	940	2.50	1,420
-.40	270	.60	580	1.60	985	2.60	1,470
-.30	295	.70	615	1.70	1,030	2.70	1,525
-.20	325	.80	650	1.80	1,075	2.80	1,580
-.10	355	.90	690	1.90	1,120	2.90	1,635
.00	385	1.00	730	2.00	1,170	3.00	1,690
.10	415	1.10	770	2.10	1,220		
.20	445	1.20	810	2.20	1,270		
.30	475	1.30	850	2.30	1,320		

^a Above gage height 4.00 feet the rating curve is a tangent, the difference being 51.5 per tenth

^b Above gage height 2.40 feet the curve is a tangent, the difference being 70 per tenth.

^c Above gage height 3.0 feet the table is the same as that for 1904.

WATER POWERS OF GEORGIA

Estimated monthly discharge of Ocmulgee River near Flovilla.

[Drainage area, 1,500 square miles.]

Month	Discharge in second-feet			Run-off	
	Maximum	Minimum	Mean	Sec-ft. per sq. mile	Depth in inches
1901					
August.....	7,987	895	2,916	1.94	2.24
September.....	8,451	1,087	2,219	1.48	1.65
October.....	2,837	907	1,223	.82	.94
November.....	1,138	907	1,593	1.06	1.18
December.....	11,850	907	2,581	1.69	1.95
1902					
January.....	6,700	1,395	2,020	1.35	1.56
February 1-27.....	9,808	1,962	3,538	2.36	2.37
1903					
July.....	6,350	725	1,681	1.12	1.29
August.....	6,140	700	1,635	1.09	1.26
September.....	6,630	635	1,235	.86	.96
October.....	995	663	754	.50	.58
November.....	1,940	725	932	.62	.69
December.....	1,450	790	981	.65	.75
1904					
August.....	8,100	630	2,005	1.34	1.54
September.....	2,145	275	507	.338	.377
October.....	325	200	261	.174	.201
November.....	710	275	493	.329	.367
December.....	2,350	525	987	.658	.759
1905					
January.....	4,595	770	1,328	.885	1.02
February.....	9,540	895	2,917	1.94	2.02
March.....	1,690	895	1,212	.808	.932
April.....	2,565	730	1,071	.714	.797
May.....	2,350	530	1,107	.738	.851
June.....	1,320	385	722	.481	.537
July.....	4,675	445	1,457	.971	1.12
August.....	6,530	385	1,273	.849	.979
September.....	985	220	402	.268	.299
October.....	790	325	512	.341	.393
November.....	2,015	415	651	.434	.484
December.....	11,340	598	3,592	2.39	2.76
The year.....	11,340	220	1,354	.902	12.19

OCMULGEE RIVER AT MACON.

A station was established at Macon January 21, 1893, by the United States Weather Bureau. Discharge measurements were begun by the United States Geological Survey in 1895, and a wire gage was established on the bridge of the Macon, Dublin and Savannah Railroad and was set on the same datum as the Weather Bureau gage. For a time gage-height records were maintained by the Geological Survey, as the Weather Bureau records were for a part of the year only and were discontinued altogether from June 30, 1897, to June 1, 1899. Since June 1, 1899, the Weather Bureau gage-height records have been taken continuously and have been furnished to the Geological Survey.

The channel is straight and without obstructions, except for one bridge pier. The banks are high and not subject to overflow. The bed of the river is soft and changeable. The station was a fairly good one until the spring of 1902, when the bed of the stream below the station, which is of shifting sand, changed to such an extent as to make the current very sluggish at low stages.

Discharge measurements are made from the downstream side of the Fifth Street Bridge, an iron bridge of two 190-foot spans, located about 500 feet above the railroad bridge. The initial point for soundings is the end of the iron hand rail of the footway at the right bank on the downstream side.

The Weather Bureau gage is a heavy timber bolted to the downstream portion of the right-bank stone pier of the Central of Georgia Railway bridge. October 9, 1905, a standard chain gage was installed on the Fifth Street Bridge, on the outside of the latticed railing of the downstream footway at a point 85 feet from the right-bank end; length of chain, 40.83 feet. Bench marks were established as follows: (1) The top of the iron rim of the sidewalk 80 feet from the initial point for soundings; elevation, 34.42 feet. (2) An aluminum tablet on the wall at the west side of the door of the United States Government building at the Mulberry street front. This bench mark is marked 334 feet and has an elevation of 64.37 feet above zero of the gage.

WATER POWERS OF GEORGIA

Discharge measurements of Ocmulgee River at Macon.

Date	Gage height	Dis-charge	Date	Gage height	Dis-charge
1895			1901		
October 18.....	<i>F</i> 0.39	<i>Sec.-ft.</i> 813	January 2.....	<i>F</i> 12.32	8,662
October 23.....	.20	767	February 21.....	4.35	2,495
December 13.....	1.59	1,530	April 19.....	6.50	3,724
1896			May 8.....	3.75	1,958
January 28.....	5.52	3,436	November 6.....	2.15	1,107
June 12.....	— .10	791	November 8.....	2.15	1,141
June 30.....	— .82	<i>a</i> 442	1902		
August 6.....	2.97	2,045	June 26.....	3.53	1,074
August 31.....	— .13	651	June 25.....	3.50	689
October 16.....	— .61	459	July 31.....	4.20	1,126
1897			September 15.....	3.61	885
March 15.....	16.75	25,530	September 18.....	3.30	705
May 4.....	4.30	2,750	October 23.....	3.10	829
May 5.....	3.50	2,275	November 13.....	3.10	779
May 18.....	2.10	1,592	November 26.....	9.29	6,483
June 11.....	2.35	2,111	November 26.....	9.59	5,900
June 12.....	1.85	1,479	December 5.....	9.00	4,612
June 29.....	.90	1,005	1903		
September 23.....	— .35	504	January 26.....	4.00	1,794
September 23.....	— .35	497	April 2.....	11.30	7,244
November 7.....	.06	735	April 4.....	9.00	5,118
December 6.....	1.20	1,356	April 21.....	7.88	4,985
1898			July 14.....	11.00	7,676
January 7.....	.42	899	July 14.....	11.00	7,314
February 10.....	.60	1,010	August 24.....	3.61	1,382
March 28.....	.36	976	September 30.....	2.55	1,022
March 30.....	.50	1,023	September 30.....	2.56	1,057
May 19.....	— .20	687	October 15.....	2.22	926
June 23.....	— .34	620	October 15.....	2.28	915
July 26.....	4.92	3,218	November 13.....	2.84	1,236
July 27.....	5.65	3,799	December 21.....	2.88	1,264
August 29.....	9.25	6,125	December 21.....	2.95	1,329
August 30.....	7.20	4,477	1904		
October 19.....	4.50	3,111	February 17.....	4.35	2,232
November 5.....	1.90	1,474	April 11.....	3.52	1,759
1899			May 24.....	1.38	703
February 1.....	9.72	6,302	May 27.....	1.29	625
February 3.....	13.75	14,950	July 20.....	1.87	1,011
February 3.....	13.75	14,780	August 19.....	3.31	1,584
February 3.....	12.81	12,690	September 20 <i>b</i>30	431
April 14.....	4.50	2,587	October 6 <i>c</i>	— .20	232
April 29.....	5.00	3,094	November 1 <i>c</i>	— .14	302
June 7.....	1.60	1,015	1905		
June 9.....	1.48	983	March 14.....	4.88	2,554
June 21.....	1.22	1,009	June 14.....	1.22	789
August 2.....	1.98	1,345	September 13.....	.71	772
September 14.....	1.70	1,314	September 28.....	— .39	321
September 16.....	.30	793	November 4 <i>d</i>46	565
October 21.....	2.30	1,314	1906		
December 13.....	4.50	3,009	April 14.....	4.92	1,680
December 15.....	2.50	1,540	May 18.....	4.43	920
1900			October 9.....	5.19	2,170
April 13.....	7.38	4,855	October 10.....	5.02	1,810
November 20.....	2.40	1,369			
December 6.....	8.70	5,698			
December 21.....	12.82	9,621			

a Lowest estimated discharge for 1906 was 380 second-feet.*b* At shoals above bridge.*c* Boat at Second street.*d* Made at different section.

ALTAMAHA DRAINAGE BASIN, STREAM FLOW

Daily gage height, in feet, of Ocmulgee River at Macon.

Day.	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.	
1893 a													
1.....		5.3	12.7	2.4	1.6	2.6	1.0	1.4	9.3	1.3	1.7	2.5	
2.....		4.8	10.0	2.3	1.4	2.4	1.1	1.8	8.7	1.3	1.6	3.0	
3.....		8.9	7.8	2.2	1.8	5.4	1.1	2.2	5.5	1.5	1.6	2.8	
4.....		3.1	12.7	2.1	6.7	6.8	1.8	1.8	3.0	8.0	1.6	2.7	
5.....		2.8	12.2	2.1	3.4	6.7	1.0	2.0	2.8	5.0	1.6	2.5	
6.....			3.4	9.5	2.3	3.1	5.1	1.0	6.2	2.4	3.5	1.6	3.2
7.....			2.3	7.1	2.5	7.2	5.5	1.0	13.4	2.4	3.0	1.5	2.0
8.....			1.8	6.5	2.2	4.9	9.7	1.0	9.5	2.3	2.8	1.5	1.8
9.....			1.6	4.7	2.0	4.9	7.0	1.8	5.0	3.0	2.7	1.5	1.7
10.....			1.8	8.9	1.8	3.4	3.4	1.2	3.2	4.0	2.6	1.5	1.6
11.....			2.8	7.8	1.7	2.9	2.5	1.2	2.0	4.1	2.6	1.5	1.5
12.....			4.6	5.8	1.7	2.2	2.2	1.2	1.8	5.4	2.5	1.5	1.5
13.....			14.6	5.0	1.6	1.8	2.0	1.1	1.7	9.4	2.5	1.5	1.5
14.....			13.0	4.1	1.6	1.6	3.0	1.1	1.7	10.9	2.3	1.5	1.5
15.....			11.2	3.5	1.6	1.3	3.0	1.1	4.2	6.8	2.7	1.5	1.5
16.....			11.0	2.6	1.7	1.2	3.0	.9	4.0	4.0	2.5	1.5	1.5
17.....			13.4	3.0	1.6	1.5	2.0	.9	2.0	3.5	2.5	1.5	3.0
18.....			12.0	2.4	1.4	1.2	1.8	1.0	1.9	2.0	2.5	1.5	2.8
19.....			11.3	2.2	1.2	1.2	3.0	1.4	1.7	2.0	2.4	1.5	3.5
20.....			10.6	2.1	2.5	1.0	2.6	1.6	1.6	2.2	1.5	3.2	3.2
21.....		2.7			9.0	.8	2.3	1.7	1.6	1.6	2.1	2.0	3.1
22.....		2.8	6.8		7.4	.7	2.4	5.4	1.4	1.5	2.1	2.8	3.0
23.....		2.8	3.3		4.3	.6	2.2	2.4	1.3	1.5	2.0	3.0	2.8
24.....		2.6	5.4	2.9	2.9	.7	2.2	2.2	1.3	1.5	2.0	2.8	2.6
25.....		4.6	4.0	3.7	2.2	.6	2.2	2.0	1.2	1.4	2.0	2.6	2.4
26.....		5.0	3.6	5.3	1.3	.6	1.0	1.8	1.2	1.4	2.0	2.4	3.2
27.....		4.7	3.5	4.0	1.3	.7	1.0	1.8	1.1	1.6	2.0	2.3	2.0
28.....		5.3	11.9	3.1	1.7	.4	1.0	2.0	1.2	1.5	1.8	2.1	1.9
29.....		5.3		2.3	1.6	.2	1.1	1.4	1.4	1.4	1.7	2.0	1.3
30.....		6.3		2.6	1.6	.1	1.0	1.3	1.4	1.4	1.7	2.0	2.5
31.....		6.6		2.5		5.6		1.2	2.0		1.7		3.4
1894 b													
1.....	3.2	2.3	10.4	3.0	1.3	1.2	1.8	7.0	3.4	.9	5.0	1.0	
2.....	3.0	2.0	9.1	3.0	1.7	1.2	1.6	6.0	3.2	.9	5.6	1.0	
3.....	2.8	2.0	8.6	2.5	1.5	1.2	1.4	5.8	3.0	.9	7.0	.9	
4.....	2.6	3.0	8.0	2.5	1.5	1.2	1.3	4.8	2.3	.8	6.5	1.0	
5.....	2.3	2.8	4.9	3.0	1.5	1.2	1.2	9.0	2.6	.8	6.0	1.5	
6.....	2.0	2.6	4.2	2.3	1.5	1.1	2.5	14.2	3.0	.8	5.0	1.5	
7.....	1.8	2.4	3.9	2.3	1.5	1.1	3.0	12.2	4.0	.8	4.0	1.4	
8.....	1.6	2.3	3.3	2.5	1.5	1.0	2.3	9.6	6.0	.9	3.0	1.3	
9.....	3.7	2.2	3.7	2.5	1.5	1.0	2.6	6.9	5.5	11.0	2.8	1.3	
10.....	3.3	2.1	3.5	2.5	1.3	1.0	3.0	5.4	5.0	15.1	2.4	2.0	
11.....	4.5	3.0	3.2	5.6	1.3	.9	4.0	4.0	4.8	8.0	2.3	4.0	
12.....	6.0	7.2	7.1	5.2	1.3	.9	3.8	4.0	4.6	6.0	2.1	9.8	
13.....	6.3	10.0	7.9	5.0	1.2	.9	3.4	3.8	5.0	4.5	2.0	13.2	
14.....	5.5	11.0	6.0	4.6	1.5	1.0	3.2	3.6	5.8	4.3	2.0	10.3	
15.....	3.2	13.7	4.0	4.0	3.0	.9	3.0	3.4	4.6	4.1	1.9	8.4	
16.....	3.8	9.8	3.5	3.3	2.5	.9	2.8	3.1	4.3	3.9	1.8	7.2	
17.....	4.2	7.5	4.0	3.5	2.0	.9	3.0	3.0	4.2	3.6	1.7	3.0	
18.....	3.3	6.2	6.0	3.0	1.7	1.0	3.0	3.0	5.0	3.4	1.7	2.5	
19.....	3.0	5.7	5.0	2.3	2.5	.9	7.6	4.0	5.3	3.2	1.5	2.4	
20.....	2.8	5.2	4.6	6.5	2.3	.9	6.3	3.0	11.3	3.1	1.5	2.2	
21.....	3.0	4.9	4.3	6.0	2.0	.8	7.9	4.5	5.5	3.0	1.5	2.1	
22.....	3.2	5.1	4.0	5.8	1.7	2.0	4.0	4.0	3.0	2.3	1.5	2.0	
23.....	3.0	5.2	3.8	5.5	1.5	2.5	3.0	3.8	2.8	2.6	1.5	2.0	
24.....	3.6	5.6	3.5	4.0	1.3	2.6	3.0	3.6	2.6	2.4	1.4	1.9	
25.....	3.2	6.0	3.2	3.7	1.3	3.0	2.6	5.0	2.7	2.3	1.3	1.8	
26.....	3.3	8.9	6.0	3.5	1.3	2.5	2.3	4.8	2.3	2.1	1.3	1.7	
27.....	3.2	10.4	5.6	3.2	1.3	2.0	3.0	4.6	2.2	2.0	1.2	3.0	
28.....	3.0	9.5	4.0	2.0	1.3	1.8	4.0	4.2	2.1	1.3	1.2	4.0	
29.....	2.8		3.5	2.0	1.3	1.6	3.7	4.0	1.0	1.7	1.1	3.9	
30.....	2.7		3.2	2.0	1.3	2.0	4.0	3.8	1.0	1.6	1.0	3.7	
31.....	2.5		3.0		1.2		7.2	3.6		4.0		3.5	

a 1893 record from United-States Weather Bureau.

b 1894 and 1895 records from United States Weather Bureau.

WATER POWERS OF GEORGIA

Daily gage height, in feet, of Ocmulgee River at Macon—Continued.

Day.	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1895. ^a												
1.....	3.5	6.0	3.0	4.6	6.0	3.3	10.9	2.3	4.4	52.0	0.5	0.5
2.....	3.4	6.0	4.0	4.5	5.5	3.7	10.0	2.3	4.2	1.8	.77	.5
3.....	3.2	5.3	10.3	4.3	4.0	3.6	7.3	2.3	4.0	1.6	.35	.65
4.....	3.0	5.3	10.0	4.2	3.3	3.5	11.3	4.0	5.0	1.4	.67	.62
5.....	3.0	5.1	6.0	4.0	3.7	3.5	10.0	6.0	4.8	1.4	.55	.54
6.....	2.3	4.0	4.0	4.0	3.6	3.4	9.5	5.3	4.6	1.2	.45	.51
7.....	2.7	4.0	5.7	3.9	3.6	3.3	9.0	5.6	4.3	1.0	.36	.44
8.....	2.6	3.9	10.9	11.2	3.6	3.2	13.4	5.4	4.2	1.0	.47	.4
9.....	3.0	3.7	8.5	11.0	3.6	3.2	10.0	5.3	4.0	1.0	.55	.46
10.....	15.0	3.6	6.0	8.0	5.0	3.0	7.0	5.0	3.9	.3	.63	.45
11.....	14.5	3.5	4.0	7.0	5.0	3.0	5.0	4.9	5.0	.6	.65	2.5
12.....	11.5	3.5	4.0	6.5	5.5	2.9	4.0	4.7	4.3	.7	.6	2.29
13.....	7.0	4.0	6.0	6.0	5.3	2.9	3.9	4.5	4.5	.65	.77	1.51
14.....	6.0	4.2	14.8	5.3	5.0	3.0	3.7	4.6	4.3	.4	.94	1.11
15.....	5.0	4.7	15.3	5.3	4.3	4.0	3.5	7.0	4.1	.3	.72	1.01
16.....	3.0	4.5	16.4	5.0	4.6	4.0	3.4	9.7	4.0	.2	.65	1.72
17.....	2.9	4.2	18.4	4.3	4.2	4.5	3.3	12.2	3.9	.2	.57	.53
18.....	2.7	4.1	16.3	12.5	5.0	4.3	3.2	12.0	3.7	.17	.55	.64
19.....	2.6	4.0	12.0	10.0	4.2	4.0	3.3	12.0	3.6	.2	.5	.61
20.....	2.5	3.9	9.0	8.0	4.0	3.9	3.6	9.0	3.5	.18	.5	.59
21.....	3.2	3.6	11.0	7.0	3.3	3.3	3.5	6.0	3.5	.25	.5	2.02
22.....	2.1	3.5	9.0	6.0	4.0	3.7	3.4	10.0	3.5	.22	.5	3.1
23.....	2.0	3.5	8.0	6.5	4.5	4.0	3.3	9.0	3.4	.21	.5	2.63
24.....	2.0	3.4	7.0	6.0	5.0	3.9	3.2	6.0	3.4	.21	.5	1.7
25.....	2.0	3.3	6.0	4.3	5.0	3.3	3.2	4.5	3.3	.17	.49	1.43
26.....	12.5	3.2	5.3	4.7	7.0	3.7	3.1	4.0	3.2	.19	.49	1.01
27.....	3.0	3.2	5.5	3.1	12.5	3.5	3.0	4.0	3.2	.13	.47	1.0
28.....	7.0	3.1	5.4	10.9	7.0	3.4	3.0	5.0	3.2	.13	.45	1.2
29.....	11.0		5.3	10.0	5.0	3.2	2.9	4.0	3.1	.17	.55	1.3
30.....	11.0		3.0	7.0	4.0		2.9	4.0	3.0	.22	.54	1.35
31.....	7.0		4.3		3.9		2.9	4.5		.5		4.46
1896.												
1.....	4.31	3.0	c2.5	c3.1	.39	.08	-.9	1.02	.11	-.32	.14	9.5
2.....	3.5	2.9	3.2	3.0	.75	.11	-1.0	1.5	.12	-.86	.08	11.03
3.....	2.2	3.2	2.1	4.6	.63	.56	+1.1	1.32	.11	-.88	.02	12.6
4.....	1.7	3.0	2.0	3.4	.9	.85	+1.15	2.22	.22	-.31	10.0	10.2
5.....	1.42	2.9	2.0	2.9	2.12	1.32	2.0	2.52	.19	-.75	14.2	3.0
6.....	1.03	13.5	1.9	1.3	2.73	1.52	4.0	3.0	.19	-.79	14.4	6.15
7.....	1.96	10.7	4.0	1.6	1.37	.36	5.3	3.05	.19	-.72	3.3	4.52
8.....	1.72	7.5	6.0	1.1	1.62	.73	11.0	2.78	.12	-.82	5.4	3.62
9.....	2.33	13.1	5.0	1.1	.36	.25	20.0	2.41	.08	-.32	3.22	3.0
10.....	2.77	11.3	4.0	1.4	.61	.01	13.4	1.33	.04	-.32	2.25	2.42
11.....	2.1	8.7	5.0	1.3	.33	.05	15.0	1.43	.01	-.73	1.5	1.33
12.....	1.6	7.0	7.2	1.1	.3	.1	10.2	.4	.01	-.65	1.13	1.53
13.....	1.5	6.3	6.5	1.2	.19	.17	3.2	.2	.31	-.73	10.0	1.23
14.....	1.2	6.5	6.2	1.2	.11	.29	7.1	.13	.45	-.73	3.1	1.12
15.....	2.0	5.0	5.0	1.13	.09	.32	7.0	.25	.3	-.65	5.32	11.7
16.....	2.5	4.3	6.0	1.12	.07	.2	6.2	1.03	-.63	-.77	1.53	6.0
17.....	7.2	4.2	3.5	1.09	.05	.25	16.0	.5	-.78	-.3	1.14	4.62
18.....	5.0	3.4	5.3	1.05	.03	.25	13.2	.6	.3	-.33	.97	3.34
19.....	4.5	3.2	5.0	.38	.05	.3	13.0	.38	.32	-.35	.35	2.35
20.....	4.0	3.0	4.3	.34	.1	.4	7.05	.2	.91	-.33	.63	2.33
21.....	3.9	2.9	4.7	.36	-.1	.47	3.3	.11	-.9	-.39	.7	2.0
22.....	3.7	2.7	4.5	.76	.15	.56	3.2	.08	-.32	-.9	.62	1.9
23.....	3.4	2.6	4.2	.71	.05	.7	3.0	.06	-.41	-.77	.53	1.73
24.....	13.3	2.5	5.0	.63	.56	.6	2.9	.05	-.43	-.4	.53	1.33
25.....	12.0	2.43	5.0	.33	.5	.3	2.35	.0	-.91	-.52	.51	1.13
26.....	9.3	2.4	4.3	1.02	.73	.2	2.7	-.03	-.72	-.25	.51	1.11
27.....	7.0	2.3	4.7	2.9	.32	.35	2.4	-.04	-.73	-.03	.5	.96
28.....	5.3	3.3	4.6	2.32	.34	.63	2.1	.07	-.33	-.2	.47	.3
29.....	5.3	2.3	4.4	1.36	.17	.73	1.92	.07	-.31	-.32	.43	.33
30.....	4.3		4.2	1.02	.12	.35	1.06	.09	-.9	-.23	.32	.73
31.....	3.2		4.1		.12		1.41	.12		-.13		.7

^a 1894 and 1895 records from United States Weather Bureau.^b From October 1 to 23, 1895, estimated by B. M. Hall.^c Gage heights from March 1 to April 14, 1896, supplied from Weather Bureau records.

ALTAMAHA DRAINAGE BASIN, STREAM FLOW

Daily gage height, in feet, of Ocmulgee River at Macon—Continued.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1897												
1	0.68	2.0	4.0	5.57	1.95	1.22	1.08	1.08	1.1	-0.5	-0.12	1.22
2	.63	5.0	3.7	9.75	1.9	1.18	.75	.84	1.25	-.45	+.35	.7
3	.6	8.0	3.2	10.05	1.87	3.15	.65	.72	.68	-.5	.48	.6
4	.58	6.0	2.0	10.0	2.15	3.2	2.15	.4	.62	-.54	.35	.62
5	.56	6.0	4.0	15.12	2.23	3.12	2.3	.38	.35	-.61	.25	1.43
6	.54	8.0	3.0	15.15	2.47	3.1	3.8	.42	.28	-.68	.12	1.3
7	.52	6.5	11.6	12.6	3.0	3.0	3.12	1.4	.22	-.32	.1	1.12
8	.5	5.0	12.7	10.48	3.0	2.54	1.62	3.22	.12	-.55	.5	1.48
9	.49	4.75	7.5	10.0	2.91	2.32	1.28	1.1	.07	-.55	.2	.6
10	.49	4.55	5.0	10.8	2.72	2.26	.9	.8	.03	-.58	.2	.52
11	.51	5.0	4.8	7.8	2.57	2.18	3.1	1.6	-.1	+.12	.3	.48
12	.49	13.5	6.0	6.4	2.45	2.08	3.33	2.0	.5	.1	.6	.43
13	.48	12.75	17.3	5.0	3.05	2.04	1.5	1.02	-.2	.12	.3	.41
14	.53	7.0	18.0	4.7	3.15	2.01	.9	.7	-.12	.3	-.2	.9
15	.46	5.0	17.7	4.0	3.28	1.89	.3	.4	-.2	.3	-.1	1.46
16	.44	5.0	13.0	4.0	3.0	1.73	.5	.32	-.18	.1	-.18	1.22
17	.44	5.12	9.45	3.7	2.5	1.52	.22	.2	-.22	-.2	.1	.4
18	1.15	3.0	8.25	3.5	2.22	1.45	.4	2.6	-.33	-.18	-.2	.58
19	1.5	2.75	8.2	3.2	2.09	1.37	1.48	2.28	.6	-.2	-.2	.52
20	2.1	2.62	9.57	3.0	1.84	3.25	4.5	8.18	.2	-.02	-.1	.47
21	1.25	2.65	10.0	2.9	1.81	3.12	9.82	8.8	-.12	.0	-.08	.47
22	7.0	2.71	9.0	2.8	1.78	2.8	8.4	8.1	-.14	.2	-.13	.51
23	5.5	2.0	15.5	2.7	1.71	2.62	5.52	6.48	-.35	.18	-.1	.7
24	3.0	1.9	14.0	2.6	1.68	2.7	3.05	4.7	-.28	.1	-.5	1.08
25	2.25	6.0	10.6	2.4	1.6	3.0	1.7	2.1	.3	.05	-.2	1.02
26	2.0	10.5	8.35	2.3	1.56	3.11	1.11	1.4	-.28	.02	-.1	.89
27	3.0	7.02	7.1	2.22	1.53	2.5	1.32	1.08	-.25	.12	+.1	.89
28	3.12	5.0	6.4	2.16	1.5	1.0	3.22	.8	-.32	.16	.25	1.42
29	1.5		5.57	2.08	1.47	.9	2.1	.58	-.35	.2	3.1	1.08
30	1.25		5.21	2.0	1.36	1.5	1.76	.52	-.42	.2	1.4	.75
31	1.2		5.2		1.28		1.12	.4		.2		.65
1898												
1	.5	1.1	.25	1.75	1.87	-.53	-.82	5.11	4.96	.75	2.54	4.15
2	.45	1.01	.3	.5	1.1	-.48	-.87	3.70	14.48	.72	2.19	3.51
3	.38	1.0	.3	.48	.92	-.52	-.35	2.11	16.6	7.72	2.08	9.4
4	.32	.7	1.08	.6	.78	-.58	-.5	1.85	18.22	16.85	2.0	13.6
5	.32	.69	3.35	4.33	.6	-.7	-.78	10.5	15.76	17.32	1.85	9.72
6	.38	.71	3.3	12.1	.5	-.78	-.9	10.76	14.72	15.15	1.92	8.1
7	.45	.77	1.45	10.13	.58	-.82	+.212	10.79	11.0	13.35	2.03	6.61
8	.43	.75	1.35	7.9	.58	-.87	1.35	8.72	9.4	11.75	2.03	6.03
9	.41	.67	1.1	4.37	.47	-.8	.93	4.91	6.9	9.21	1.9	5.21
10	.43	.6	.8	3.92	.3	-.83	3.48	2.7	6.11	7.35	1.83	5.8
11	.58	.6	.75	2.9	.21	-.94	3.62	6.31	4.0	5.02	2.91	4.21
12	.75	.52	.6	2.74	.18	-.95	1.22	12.7	3.65	4.1	3.37	3.64
13	1.63	.5	.6	2.1	.2	-.96	.9	13.0	3.8	3.5	4.22	3.6
14	1.3	.48	.6	1.75	.18	+.1	1.2	12.97	2.3	3.07	6.41	3.42
15	.9	.36	2.0	1.6	.1	-.53	3.2	9.12	2.5	2.85	6.23	3.21
16	.94	.32	3.92	1.5	.04	-.1	3.8	6.52	1.93	2.56	14.1	2.91
17	.83	.25	3.0	1.2	-.08	-.1	2.67	4.92	1.89	2.3	10.21	2.8
18	.76	.4	2.02	.98	-.15	-.38	1.6	5.41	1.72	4.12	9.27	2.77
19	.6	.63	1.49	.85	-.2	+.11	.7	2.7	1.56	4.38	12.31	3.11
20	.66	.72	1.22	1.02	-.1	-.83	.2	4.1	1.3	4.18	9.02	3.0
21	1.45	.64	.95	1.6	-.15	.6	-.11	2.1	1.22	5.21	6.95	4.1
22	1.85	.5	.85	1.32	+.05	2.21	-.28	1.94	1.48	6.9	5.5	5.67
23	1.56	.4	.75	1.3	.11	.2	-.32	1.9	1.42	5.23	5.15	5.6
24	1.1	.33	.5	7.95	.91	-.41	+.332	1.42	1.35	4.17	4.31	5.52
25	1.22	.29	.5	8.9	1.52	-.5	2.51	.9	1.81	3.94	4.0	4.91
26	2.7	.25	.45	6.12	1.46	-.53	5.35	.5	1.28	3.2	4.5	4.6
27	5.37	.23	.39	3.15	1.1	+.3	3.3	4.25	1.12	2.91	3.18	4.07
28	4.31	.22	.36	2.9	.32	.51	3.1	7.21	.98	2.43	2.92	3.8
29	2.5		.39	2.55	-.11	-.42	3.14	9.45	.33	2.32	3.5	3.3
30	2.08		.5	2.05	-.3	-.65	4.3	7.53	.77	2.9	3.31	3.21
31	1.62		1.5		-.36		9.02	5.08		2.71		3.1
1899												
1	4.42	9.6	14.72	11.3	4.05	4.4	1.5	2.5	2.6	.3	.8	1.7
2	6.6	8.41	11.14	8.71	3.8	2.8	1.5	2.1	1.8	.3	.6	1.5
3	5.96	13.7	9.11	7.97	3.6	2.6	1.2	1.4	2.0	.3	.6	1.2
4	5.21	11.93	8.32	7.86	3.5	2.6	.9	1.4	1.8	.4	.5	2.1
5	3.7	9.94	8.11	8.11	3.45	1.9	.9	1.2	1.8	.5	.5	1.9

Daily gage height, in feet, of Ocmulgee River at Macon—Continued.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1899												
6.....	4.12	10.8	7.62	7.85	8.1	1.8	1.0	1.0	1.1	2.3	0.5	1.5
7.....	15.2	15.83	6.81	6.89	6.72	1.6	1.1	.8	.7	2.0	.4	1.3
8.....	12.65	13.42	6.72	6.5	5.8	1.6	1.5	.7	.7	10.0	.4	1.1
9.....	10.21	12.13	6.4	5.97	3.8	1.6	2.0	.6	.5	6.4	.4	1.1
10.....	9.23	10.8	6.11	5.63	3.55	1.4	1.3	.5	.4	3.2	.4	1.0
11.....	12.14	9.78	5.81	5.42	3.23	1.6	1.1	2.1	2.2	2.2	.4	1.1
12.....	11.87	8.21	5.74	5.01	3.1	1.5	.9	1.0	2.5	1.8	.5	3.7
13.....	9.38	7.6	5.69	4.71	2.96	2.3	.8	1.2	2.2	1.3	.5	4.7
14.....	8.96	7.13	5.58	4.58	2.9	2.9	.8	.8	1.7	1.0	.5	3.9
15.....	8.21	6.1	5.51	4.4	2.82	2.2	.7	.7	.9	1.0	.8	2.6
16.....	9.67	12.3	8.51	5.01	2.69	1.7	.6	.7	.6	.9	.7	2.0
17.....	12.91	11.98	7.21	4.42	2.52	1.5	.6	.6	.6	.8	.7	1.8
18.....	10.87	11.12	9.38	4.33	2.45	2.3	.5	.6	.5	.8	.7	1.5
19.....	9.34	9.76	12.94	10.33	2.33	1.4	.7	.5	.5	.8	.6	1.4
20.....	5.91	8.32	10.72	7.82	2.2	1.3	.9	.4	.4	2.0	.6	1.4
21.....	5.11	8.27	9.42	5.52	2.13	1.3	1.0	.4	.3	2.8	.6	1.3
22.....	5.42	8.16	8.11	4.72	2.43	1.2	.3	2.0	.3	3.2	.5	1.3
23.....	5.1	8.1	6.42	4.61	3.67	1.0	1.3	3.3	.3	2.4	.6	1.4
24.....	5.37	7.13	8.65	5.43	3.35	.9	3.2	3.1	.2	1.6	1.0	6.4
25.....	5.31	6.23	8.85	11.87	3.01	.9	2.0	2.1	.2	1.2	1.4	5.9
26.....	5.01	6.13	6.93	12.41	2.4	1.2	2.0	1.2	.4	1.0	4.4	5.2
27.....	4.71	12.13	6.01	8.22	2.18	3.2	2.3	.8	.4	.8	5.3	3.5
28.....	4.69	14.91	7.37	5.34	2.12	3.2	4.3	3.0	.4	.7	4.2	2.6
29.....	5.03		7.3	6.16	2.06	1.6	5.1	2.3	.3	1.4	3.1	2.3
30.....	4.9		6.91	4.71	2.03	1.7	4.2	1.8	.3	1.0	2.0	2.1
31.....	5.07		6.23		2.15		3.2	2.4		1.1		1.6
1900												
1.....	1.6	1.6	9.2	5.2	6.1	2.9	9.6	6.1	10.5	1.8	2.0	2.7
2.....	1.5	1.5	9.4	4.9	7.3	2.9	8.3	4.4	5.8	1.8	3.2	2.6
3.....	1.2	1.5	7.7	4.8	8.6	3.2	13.3	4.2	5.0	1.7	2.8	2.5
4.....	1.2	1.5	6.2	4.6	8.0	3.8	11.2	3.7	3.5	2.2	12.3	8.4
5.....	1.2	2.3	5.3	4.5	7.3	4.6	8.3	3.4	2.7	4.1	8.2	11.5
6.....	1.5	2.9	5.5	4.5	6.4	6.4	6.4	3.1	2.5	3.6	4.9	9.3
7.....	1.4	2.5	5.3	4.3	5.6	8.0	5.5	3.0	2.4	5.0	3.6	6.4
8.....	1.4	2.3	7.0	4.3	4.4	8.9	4.9	2.8	2.1	4.6	3.2	4.3
9.....	1.3	3.2	7.8	4.1	4.1	7.7	5.0	2.6	2.2	2.7	2.8	4.2
10.....	1.3	3.3	9.7	4.1	4.1	6.6	4.5	2.5	2.1	3.2	2.6	3.7
11.....	1.9	16.1	8.1	4.3	4.1	5.5	4.3	2.4	2.0	2.6	2.5	3.3
12.....	2.9	18.7	6.4	7.0	4.0	5.2	4.3	2.3	2.0	2.5	2.4	3.2
13.....	4.2	19.0	5.8	7.6	3.9	3.8	5.3	2.4	1.8	2.4	2.3	3.0
14.....	3.7	21.7	5.3	6.1	3.8	3.7	4.9	2.6	1.7	2.7	2.2	3.5
15.....	2.6	19.5	5.3	5.3	3.7	3.2	4.5	2.4	4.7	2.6	2.2	12.5
16.....	2.2	15.5	10.4	4.8	3.4	8.6	4.0	2.4	13.3	2.4	2.2	8.5
17.....	2.0	11.4	7.3	4.3	3.4	3.8	3.9	2.6	10.5	2.2	2.1	4.6
18.....	2.0	8.5	5.8	5.0	3.3	10.9	3.7	2.7	6.0	2.1	2.1	4.4
19.....	2.9	7.4	5.2	13.0	4.1	11.2	3.5	2.7	4.0	2.0	2.1	3.9
20.....	3.3	6.8	8.0	15.6	4.0	8.0	3.5	2.6	3.3	1.9	2.0	4.0
21.....	4.6	8.2	7.7	13.9	3.7	5.3	3.4	2.4	2.7	1.9	2.4	12.8
22.....	3.9	3.9	6.6	16.0	3.5	4.0	3.3	2.3	2.5	1.9	2.4	12.1
23.....	3.1	7.7	5.6	13.9	3.3	4.0	3.4	2.2	2.4	2.1	2.5	8.6
24.....	2.7	6.4	7.3	13.2	4.6	16.0	3.9	3.6	2.3	3.3	2.7	6.5
25.....	2.5	7.3	7.9	13.0	4.8	20.2	3.4	4.1	2.3	4.2	2.5	5.5
26.....	2.2	6.5	10.5	12.4	4.2	20.0	3.3	4.3	2.2	3.7	7.1	4.3
27.....	2.0	5.9	10.9	9.3	3.3	16.4	4.2	3.8	2.0	2.9	5.5	4.1
28.....	2.0	5.5	7.8	7.6	3.3	14.0	4.5	2.7	2.0	2.5	4.3	3.9
29.....	1.9		7.4	7.0	3.1	12.7	5.6	2.4	2.0	2.4	3.2	3.7
30.....	1.7		6.6	6.3	3.0	10.4	6.3	2.3	1.9	2.3	2.9	3.8
31.....	1.6		5.8		2.9		8.0	3.8		2.1		7.5
1901												
1.....	11.7	4.7	4.1	14.5	4.2	9.9	5.3	3.8	5.4	3.4	1.7	1.9
2.....	12.3	5.0	4.0	9.5	4.1	8.5	5.5	3.0	7.5	3.3	1.7	1.9
3.....	13.7	4.5	3.9	13.3	4.0	6.2	5.7	2.5	4.8	5.3	1.7	2.0
4.....	11.9	14.9	3.8	17.3	3.9	5.4	3.8	2.2	4.4	5.6	1.7	1.9
5.....	9.5	15.9	3.8	13.1	3.9	5.1	3.2	2.2	3.4	3.9	2.0	3.2

a Mud around gage, August 22, 1899.

ALTAMAHA DRAINAGE BASIN, STREAM FLOW

Daily gage height, in feet, of Ocmulgee River at Macon—Continued.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1901												
6	7.7	13.7	3.7	10.5	4.0	4.3	3.0	3.8	3.1	3.8	2.0	2.7
7	6.5	10.1	3.5	9.0	3.9	4.7	2.9	9.4	3.0	3.0	2.1	2.4
8	5.7	8.7	3.4	7.7	3.8	6.8	3.2	7.4	2.8	2.8	2.0	2.4
9	5.1	12.1	3.4	6.7	3.7	5.3	3.1	4.4	2.6	2.7	1.9	2.3
10	4.8	11.3	3.5	6.1	3.6	4.0	3.0	3.0	2.5	2.6	2.0	2.4
11	4.6	9.5	5.8	5.7	3.5	3.5	3.8	3.8	2.4	2.6	2.0	3.1
12	5.8	7.9	6.9	5.4	3.4	3.3	2.9	3.2	2.4	2.5	1.9	2.9
13	12.6	7.4	5.4	5.6	3.4	3.8	2.7	5.0	2.3	3.0	1.9	2.5
14	12.0	6.5	5.0	8.5	3.5	6.0	2.6	4.4	2.6	2.9	2.0	2.3
15	8.6	5.8	4.2	10.4	3.5	6.9	2.5	3.4	3.2	2.8	2.1	13.7
16	7.2	5.4	3.8	10.2	3.3	9.6	3.7	5.9	2.9	2.6	2.0	11.9
17	11.4	5.1	3.6	8.3	3.2	3.8	4.0	14.6	5.0	2.5	1.9	7.5
18	11.2	4.9	3.4	6.8	3.1	7.5	3.5	11.6	17.7	2.3	1.9	4.7
19	7.8	4.7	3.4	6.5	3.0	9.2	4.0	7.4	16.2	2.2	2.0	3.7
20	6.1	4.6	3.3	7.7	3.3	6.6	15.4	7.0	12.0	2.0	2.2	3.2
21	4.3	4.4	3.7	7.8	5.5	5.2	8.5	7.8	7.8	1.9	2.4	2.7
22	5.0	4.2	3.9	6.5	12.0	4.6	5.5	5.2	6.0	2.1	2.5	2.1
23	4.5	4.2	3.6	5.8	13.9	5.1	4.0	10.0	4.7	2.0	2.3	2.3
24	4.4	4.4	3.8	5.5	9.2	5.3	3.5	14.4	3.9	2.0	2.2	3.1
25	4.3	4.5	4.4	5.2	5.7	4.7	2.8	12.0	3.5	1.9	2.2	3.4
26	5.1	4.6	16.1	5.0	5.0	3.3	2.6	7.2	3.3	1.9	2.1	3.4
27	4.5	4.6	16.1	4.8	5.3	5.3	2.5	4.8	3.1	1.9	2.0	3.7
28	5.0	4.4	13.2	4.6	4.7	5.1	2.9	10.0	3.1	1.8	2.0	4.9
29	5.1	9.4	4.5	4.1	4.3	3.1	10.4	3.7	1.8	1.9	13.6
30	4.5	7.2	4.3	3.8	5.4	3.1	9.6	3.9	1.7	1.9	17.1
31	5.3	15.8	4.7	3.0	7.4	1.7	17.9
1902												
1	15.7	11.5	22.8	12.8	5.8	4.2	3.3	3.9	4.0	5.0	3.5	8.5
2	11.0	18.0	20.9	10.4	5.7	4.1	3.2	3.8	3.6	5.6	3.3	7.3
3	19.2	17.3	8.8	5.7	4.5	3.3	3.7	3.5	4.5	3.3	13.3
4	6.3	18.5	13.0	8.5	5.8	4.3	3.1	5.5	3.3	3.9	3.2	11.9
5	5.2	15.0	11.1	8.2	5.5	4.1	3.3	5.9	3.4	4.3	3.2	9.5
6	4.7	10.6	10.1	7.9	5.4	4.0	3.3	9.5	3.4	5.2	3.3	7.0
7	4.4	8.4	9.4	7.6	5.3	4.0	3.3	5.5	3.4	4.8	3.4	5.9
8	4.2	7.2	8.7	10.5	5.2	6.2	3.2	4.6	3.3	4.2	3.7	5.2
9	4.0	6.4	8.4	10.2	5.2	6.1	3.3	4.0	3.4	3.8	3.5	4.7
10	3.9	5.8	8.2	9.8	5.5	5.0	3.2	3.8	3.4	3.7	3.4	4.2
11	3.7	5.5	7.9	7.7	5.5	4.6	3.2	3.7	3.3	3.5	3.3	3.8
12	3.6	5.3	7.7	7.3	5.3	4.2	3.3	3.4	3.6	3.9	3.3	4.0
13	3.5	5.0	7.5	7.1	5.2	4.1	3.2	4.6	3.5	4.6	3.2	5.2
14	3.3	4.9	8.4	6.9	5.1	4.0	3.2	4.0	3.3	4.6	3.1	4.0
15	3.1	5.1	9.4	6.9	5.0	4.0	5.2	3.8	4.2	4.3	3.2	4.3
16	3.1	5.5	10.7	6.9	5.4	5.8	4.1	4.1	3.3	3.9	3.1	4.1
17	3.2	5.7	13.6	6.8	6.4	5.0	4.0	5.9	3.5	3.6	3.2	3.6
18	3.1	5.4	16.8	11.1	5.7	4.5	3.8	4.1	3.3	3.5	3.5	6.8
19	3.1	5.3	13.4	9.0	5.7	4.8	3.6	3.4	3.3	3.4	4.3	5.8
20	3.2	5.2	11.0	7.6	5.7	4.4	3.4	3.7	3.2	3.4	4.6	4.8
21	3.4	5.9	9.4	7.1	5.2	4.2	3.4	3.4	4.2	3.3	3.9	6.8
22	3.9	6.3	3.9	7.0	5.0	4.0	3.4	3.3	4.1	3.5	3.6	6.6
23	4.2	5.9	3.6	6.6	4.8	3.8	3.8	3.7	3.7	3.2	3.5	6.0
24	3.7	5.3	3.2	6.4	4.7	3.7	3.5	3.6	3.6	3.2	3.3	5.3
25	3.4	7.2	9.1	6.3	4.6	3.7	3.6	3.3	3.4	3.1	3.2	4.8
26	3.4	8.1	3.9	6.2	4.6	3.6	3.5	3.2	6.3	3.1	3.8	4.3
27	3.4	8.4	3.3	6.2	4.5	3.6	4.8	3.2	5.8	3.8	3.5	4.2
28	3.4	19.9	10.0	6.1	4.4	3.5	3.7	3.3	5.3	5.4	5.7	4.0
29	3.3	16.2	5.9	4.3	3.4	4.9	4.3	5.4	4.7	4.4	3.8
30	3.9	17.3	5.8	4.2	3.4	4.7	4.6	5.2	3.9	4.1	4.0
31	4.4	14.6	4.2	4.2	4.7	3.6	4.8
1903												
1	4.8	4.2	14.3	14.3	5.3	7.2	4.4	4.1	2.9	2.3	2.2	2.5
2	4.5	4.0	12.3	11.4	5.1	13.5	4.3	3.5	2.7	2.3	2.3	2.4
3	4.7	4.0	9.3	9.9	5.2	11.5	4.4	3.7	2.6	2.4	2.5	2.3
4	4.7	4.3	3.3	9.0	6.1	9.4	4.6	5.6	2.4	2.4	2.3	2.3
5	5.2	5.7	9.5	8.9	6.6	12.9	4.9	6.3	2.0	2.4	3.5	2.4
6	4.9	7.8	10.0	8.1	6.4	17.4	4.4	7.4	2.5	2.5	4.1	2.7
7	4.6	6.7	3.3	8.3	5.8	12.9	4.4	5.5	2.3	2.5	3.2	2.8
8	4.4	20.0	7.3	7.7	7.0	12.3	4.9	3.9	2.2	2.5	3.0	2.8
9	4.2	20.7	7.7	12.2	6.5	3.8	6.0	3.5	2.2	2.6	2.9	2.9
10	4.0	13.4	19.3	13.0	6.0	3.2	5.6	3.4	2.1	2.6	2.6	3.3

WATER POWERS OF GEORGIA

Daily gage height, in feet, of Ocmulgee River at Macon—Continued.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1903.												
11	3.9	15.75	11.2	10.0	5.5	6.9	4.5	3.2	2.1	2.5	2.6	3.3
12	4.9	17.6	11.4	8.9	5.3	6.4	7.3	3.1	2.1	2.4	2.5	3.2
13	5.4	16.3	11.2	7.7	5.1	5.8	6.6	3.5	2.2	2.3	2.9	2.9
14	4.9	12.9	9.3	8.9	5.3	5.3	10.2	3.6	2.2	2.4	2.8	2.9
15	4.4	10.6	8.1	8.8	7.2	5.1	11.0	5.9	9.9	2.4	2.7	3.2
16	4.2	10.2	9.2	7.7	11.0	4.7	7.4	7.3	14.7	2.3	2.8	2.9
17	4.2	16.3	8.7	6.9	8.2	4.5	5.3	7.3	13.0	2.9	2.7	2.7
18	4.1	16.5	7.5	6.6	6.3	4.4	4.6	5.7	8.3	4.9	2.9	2.7
19	3.9	14.1	6.9	6.3	5.7	4.4	4.3	9.8	5.5	3.5	2.9	2.6
20	3.8	11.1	6.5	6.2	5.2	4.2	4.2	11.2	4.4	3.1	3.1	2.4
21	3.8	9.4	6.4	8.2	5.1	4.1	3.9	5.7	3.8	2.9	3.0	2.9
22	3.8	7.9	11.5	7.3	4.9	4.4	3.9	5.1	3.6	2.7	2.9	3.2
23	3.8	7.3	15.2	6.2	4.7	4.5	3.6	4.1	3.3	2.4	2.7	3.1
24	3.8	6.9	18.3	5.8	4.9	4.4	3.5	4.3	3.2	2.4	2.8	2.9
25	4.0	6.3	18.3	5.7	4.5	4.2	3.4	4.0	3.2	2.4	2.8	2.6
26	4.1	6.2	15.6	6.6	4.3	4.0	3.4	3.2	3.1	2.3	2.7	3.7
27	4.8	6.1	11.3	6.5	4.2	4.2	3.3	3.1	3.0	2.3	2.6	3.4
28	5.1	8.0	9.2	5.9	4.7	5.3	3.2	2.9	3.0	2.3	2.6	3.4
29	5.1		8.3	5.6	5.3	6.7	3.4	2.8	2.7	2.3	2.6	3.2
30	5.3		14.5	5.4	4.7	5.4	3.2	2.7	2.5	2.3	2.5	2.8
31	4.7		16.1		4.6		5.3	2.7		2.3		2.7
1904.												
1	2.5	3.5	4.2	3.1	2.8	3.9	1.9	3.5	1.8	.0	.0	1.0
2	2.5	3.5	4.1	3.0	2.8	4.8	1.9	2.3	1.7	-.3	.1	1.1
3	2.1	3.6	4.2	3.1	2.8	3.4	2.0	2.9	1.4	α-.5	.2	2.4
4	2.8	3.3	4.4	3.0	2.7	3.3	1.2	4.4	1.0	α-.8	.7	1.8
5	2.7	3.2	4.2	2.9	2.7	1.9	.9	5.3	1.0	α-1.0	1.6	2.0
6	2.6	3.1	3.8	2.8	2.6	1.7	1.7	3.4	4.7	-.2	1.5	5.1
7	2.4	3.2	6.1	3.0	2.5	1.5	1.2	2.4	3.0	.2	1.4	6.0
8	2.4	3.3	7.3	3.2	2.6	2.0	1.2	10.0	2.0	.1	.9	4.4
9	2.6	7.5	7.1	5.7	3.6	4.3	1.0	11.1	1.6	.0	.9	3.3
10	2.7	6.5	5.7	5.1	3.3	3.3	.7	15.4	1.5	-.1	.8	2.5
11	3.1	10.3	5.1	3.9	3.7	2.0	1.0	13.0	1.4	.0	.8	2.3
12	3.3	9.7	4.6	3.1	3.0	1.5	1.0	9.7	1.3	-.1	.5	2.0
13	3.2	7.9	4.2	3.2	2.8	1.3	1.9	6.7	1.3	-.1	.9	2.0
14	3.2	6.1	4.1	3.1	2.7	1.1	1.7	3.7	1.1	.1	1.3	1.9
15	3.3	5.2	4.2	3.0	2.6	1.0	1.7	6.7	1.0	-.1	1.8	1.9
16	3.2	4.8	5.0	2.9	2.5	1.0	1.2	5.4	1.0	-.2	1.8	2.0
17	3.5	4.5	4.3	3.0	2.4	.9	1.0	5.3	.9	-.3	1.3	1.9
18	4.5	4.2	3.9	2.8	2.3	.9	1.1	4.9	.8	-.1	1.0	2.0
19	4.2	3.8	3.7	2.8	2.2	1.1	1.4	3.5	.8	-.3	.9	1.8
20	3.5	4.1	3.7	3.0	2.1	.9	1.9	2.5	.7	-.3	1.0	1.8
21	3.2	5.8	3.6	3.0	2.0	.8	1.3	2.0	.5	.0	.9	1.7
22	3.1	7.0	3.4	2.9	1.9	4.3	1.3	1.8	1.7	-.3	.9	1.5
23	12.9	10.3	3.6	2.9	1.8	3.4	1.1	1.7	.6	-.2	1.0	1.4
24	10.2	9.3	3.9	2.9	1.7	2.0	1.4	1.7	.9	.4	1.5	1.4
25	6.9	7.2	4.0	2.9	1.6	1.4	2.7	7.0	.6	.2	2.1	1.5
26	5.0	5.4	3.7	2.8	1.6	1.0	2.2	5.3	.4	.3	1.8	1.7
27	4.3	5.2	3.6	2.8	1.5	.8	1.2	6.3	.3	.3	1.3	2.0
28	3.8	4.7	3.8	3.0	1.4	.8	1.1	4.8	.3	.2	1.2	6.4
29	3.7	4.3	4.3	3.0	1.3	1.3	.8	3.3	.2	.0	1.0	5.5
30	3.6		3.2	2.9	1.3	3.0	1.7	2.9	.1	.1	1.0	4.7
31	3.5		3.0		1.3		4.6	2.0		-.1		3.3
1905.												
1	2.7	2.1	4.2	2.2	2.9	2.1	3.0	.8	.7	.6	.7	.8
2	2.3	2.1	3.9	2.2	2.4	1.8	6.7	.7	1.7	1.0	.6	.8
3	2.4	2.0	3.6	2.3	2.7	1.6	7.9	.8	2.4	1.2	.4	1.7
4	2.4	1.9	3.4	2.2	4.4	2.3	7.5	.6	2.2	2.9	.43	13.0
5	2.1	2.0	3.3	2.4	4.6	2.0	5.0	.4	2.2	2.0	.44	15.0
6	2.0	2.3	3.2	3.3	4.4	1.6	3.5	.0	1.5	1.5	.37	10.4
7	2.2	3.2	3.0	3.3	3.6	1.4	3.9	-.1	1.3	1.15	.32	6.7
8	2.7	6.2	3.0	3.0	3.8	1.3	4.5	-.1	.8	.75	.65	5.1
9	3.0	13.3	3.0	2.7	3.4	1.1	3.9	2.2	.4	.3	.62	6.9
10	2.4	11.4	3.7	3.3	3.0	1.0	3.2	4.4	.2	.27	.85	11.6

α See footnote to estimated monthly discharge, 1904.

ALTAMAHA DRAINAGE BASIN, STREAM FLOW

Daily gage height, in feet, of Ocmulgee River at Macon—Continued.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1905												
11.....	2.1	10.3	3.4	5.3	2.7	0.8	3.7	3.5	-.1	0.24	3.3	11.2
12.....	1.9	10.7	4.6	4.3	2.3	.7	6.7	3.4	-.2	.8	4.2	8.3
13.....	5.3	16.4	5.7	6.3	2.0	.9	6.6	10.6	-.3	1.3	3.4	6.7
14.....	9.0	15.4	5.0	4.6	1.8	1.7	3.2	7.4	-.6	1.5	2.3	4.9
15.....	7.9	12.7	4.4	3.0	1.7	1.1	6.7	6.2	.2	1.2	1.85	6.6
16.....	5.0	10.2	3.9	4.1	2.4	1.8	3.3	6.3	.2	.7	1.7	5.9
17.....	4.1	7.7	3.5	3.3	4.0	3.8	2.7	4.2	.0	.45	1.35	5.4
18.....	3.8	6.4	3.3	3.1	2.5	2.2	2.3	3.5	-.2	.51	1.2	4.6
19.....	3.1	5.8	3.0	2.7	2.2	1.7	1.7	3.2	-.3	.43	1.12	4.1
20.....	3.0	5.3	3.0	2.4	1.8	1.4	1.6	1.9	-.4	.36	1.1	4.9
21.....	2.9	8.0	5.6	2.2	1.7	1.1	1.8	1.5	-.5	.34	.6	16.7
22.....	2.9	9.6	4.3	2.2	1.6	1.1	1.8	1.3	-.5	.26	.6	15.1
23.....	2.8	9.1	4.2	2.1	4.0	4.8	1.3	1.2	-.5	.16	.8	12.4
24.....	2.5	7.3	3.5	2.1	3.8	3.9	1.2	2.3	-.3	.18	.7	10.5
25.....	2.4	6.1	3.4	2.1	4.9	3.2	.9	2.9	-.3	.12	.6	9.4
26.....	2.2	5.6	3.3	2.0	4.4	2.3	1.2	2.3	-.2	.9	.6	7.9
27.....	1.9	5.0	3.2	2.0	3.5	1.8	2.1	1.5	-.3	1.3	.7	5.8
28.....	1.7	4.5	2.9	2.0	3.0	1.4	1.7	1.2	-.4	1.1	.9	4.7
29.....	2.0	2.7	2.0	2.9	2.5	1.2	1.1	-.3	1.25	1.1	6.4
30.....	2.0	2.5	2.2	2.9	2.5	1.1	.9	-.2	1.1	.9	5.8
31.....	2.0	2.4	2.5	1.0	1.474	4.8
1906												
1.....	5.2	6.2	3.5	9.2	3.2	2.2	3.3	3.2	4.7	4.8	2.9	2.8
2.....	4.8	6.0	3.4	3.0	3.1	2.1	2.4	6.5	6.7	16.6	2.9	2.7
3.....	5.0	5.4	4.2	6.9	3.0	2.0	2.5	5.6	8.5	17.6	2.9	2.8
4.....	16.1	5.3	4.2	6.1	3.3	3.4	2.8	4.9	6.9	13.2	2.8	2.9
5.....	15.3	4.9	4.5	5.7	3.4	5.2	2.9	3.1	4.5	17.6	2.9	2.9
6.....	14.2	4.8	4.1	5.4	3.4	3.0	2.6	7.1	3.7	12.9	2.9	2.8
7.....	10.5	4.5	3.8	5.2	3.5	2.4	2.4	6.6	3.5	13.3	2.9	2.9
8.....	9.9	4.9	4.1	5.0	4.8	2.1	2.3	9.2	3.0	9.3	2.8	3.0
9.....	7.3	6.5	9.7	4.9	4.8	2.0	3.5	5.0	2.5	7.2	2.8	3.1
10.....	6.4	5.6	11.0	5.5	4.0	2.1	6.6	3.8	2.4	6.0	2.8	2.9
11.....	6.4	5.3	3.5	6.3	3.4	2.1	4.9	3.5	2.7	5.1	2.7	2.9
12.....	5.9	5.0	6.9	5.7	3.2	2.0	3.6	3.0	2.6	4.5	2.8	4.0
13.....	7.0	5.0	6.2	5.1	3.2	13.5	3.3	3.2	3.2	4.2	2.9	4.2
14.....	6.6	4.8	5.2	4.8	3.1	18.0	2.9	4.4	5.0	4.1	2.9	3.6
15.....	6.3	4.5	8.7	5.0	2.9	17.2	4.3	11.2	3.2	3.8	3.2	3.4
16.....	5.4	4.2	14.1	4.8	2.8	17.0	4.5	9.5	2.6	3.8	3.6	3.2
17.....	5.1	4.1	14.5	4.5	2.7	13.4	4.5	5.3	2.3	3.6	3.5	3.0
18.....	5.0	4.1	11.8	4.2	2.6	12.9	4.8	4.2	2.2	3.6	3.5	3.4
19.....	4.8	4.0	9.5	4.1	2.5	10.4	7.7	4.1	6.2	3.8	3.5	4.1
20.....	4.7	3.9	16.3	4.0	2.5	8.0	10.5	3.3	7.2	4.6	5.4	6.1
21.....	4.7	4.1	17.0	3.9	2.3	5.9	9.2	3.2	3.1	4.5	4.8	5.6
22.....	5.2	4.9	15.9	3.9	2.3	5.1	6.3	4.4	9.8	3.3	4.1	5.2
23.....	19.9	4.0	12.5	3.8	2.4	5.1	7.9	7.3	7.6	3.7	3.9	4.5
24.....	14.3	3.9	9.9	3.5	2.4	4.0	10.0	7.8	7.4	3.5	3.6	3.9
25.....	11.3	3.9	8.2	3.3	2.2	3.5	9.0	5.1	8.5	3.5	3.4	3.6
26.....	11.9	3.9	7.0	3.3	2.4	3.2	6.4	3.8	3.2	3.4	3.1	3.3
27.....	12.0	3.8	6.3	3.3	2.2	3.2	5.9	4.6	5.5	3.2	3.1	3.2
28.....	11.0	3.6	11.0	3.2	3.2	3.1	4.2	5.6	6.7	3.1	3.0	3.1
29.....	9.6	11.9	3.3	3.2	2.8	3.7	9.8	5.9	3.0	2.9	3.6
30.....	8.5	10.3	3.3	2.9	2.6	3.3	8.5	5.4	2.9	2.8	5.1
31.....	7.2	10.7	2.5	9.2	7.7	2.9	6.8

WATER POWERS OF GEORGIA

Rating tables for Ocmulgee River at Macon.

JANUARY 1, 1893, TO DECEMBER 31, 1896.

Gage height	Discharge						
<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>
—0.90	380	1.20	1,285	3.40	2,240	7.40	5,060
— .80	426	1.30	1,328	3.60	2,330	7.60	5,290
— .70	469	1.40	1,371	3.80	2,420	7.80	5,520
— .60	512	1.50	1,414	4.00	2,525	8.00	5,750
— .50	555	1.60	1,457	4.20	2,630	8.50	6,500
— .40	598	1.70	1,500	4.40	2,740	9.00	7,250
— .30	641	1.80	1,543	4.60	2,850	9.50	7,925
— .20	684	1.90	1,586	4.80	2,970	10.00	8,625
— .10	727	2.00	1,629	5.00	3,090	10.50	9,450
— .00	770	2.10	1,672	5.20	3,210	11.00	10,300
+ .10	813	2.20	1,715	5.40	3,340	11.50	11,125
— .20	855	2.30	1,758	5.60	3,460	12.00	11,975
— .30	898	2.40	1,801	5.80	3,600	13.00	14,000
— .40	941	2.50	1,844	6.00	3,750	14.00	16,750
— .50	984	2.60	1,887	6.20	3,900	15.00	19,750
— .60	1,027	2.70	1,920	6.40	4,070	16.00	23,000
— .70	1,070	2.80	1,963	6.60	4,240	17.00	26,200
— .80	1,113	2.90	2,006	6.80	4,430	18.00	29,375
— .90	1,156	3.00	2,050	7.00	4,600	19.00	32,750
1.00	1,200	3.20	2,150	7.20	4,880	20.00	36,200
1.10	1,242						

JANUARY 1 TO DECEMBER 31, 1897.^a

— .60	450	2.00	1,604	5.40	3,351	8.80	6,120
— .50	481	2.20	1,698	5.60	3,474	9.00	6,430
— .40	516	2.40	1,793	5.80	3,598	9.50	7,450
— .30	554	2.60	1,888	6.00	3,722	10.00	8,700
— .20	594	2.80	1,985	6.20	3,846	10.50	9,950
— .10	636	3.00	2,083	6.40	3,975	11.00	11,200
— .00	680	3.20	2,182	6.60	4,109	11.50	12,450
— .10	726	3.40	2,280	6.80	4,251	12.00	13,700
— .20	772	3.60	2,379	7.00	4,400	12.50	14,950
— .40	864	3.80	2,478	7.20	4,554	13.00	16,200
— .60	956	4.00	2,577	7.40	4,716	13.50	17,450
— .80	1,048	4.20	2,676	7.60	4,884	14.00	18,700
1.00	1,140	4.40	2,779	7.80	5,058	15.00	21,200
1.20	1,232	4.60	2,886	8.00	5,225	16.00	23,700
1.40	1,324	4.80	2,997	8.20	5,408	17.00	26,200
1.60	1,416	5.00	3,112	8.40	5,616	18.00	28,700
1.80	1,510	5.20	3,230	8.60	5,850		

^a Above gage height 10.0 feet the rating curve is a tangent, the difference being 250 per tenth.

JANUARY 1 TO DECEMBER 31, 1898.^a

—1.00	370	0.80	1,060	2.60	1,960	5.80	3,720
— .90	388	.90	1,105	2.70	2,015	6.00	3,880
— .80	440	1.00	1,150	2.80	2,070	6.50	4,110
— .70	475	1.10	1,195	2.90	2,125	7.00	4,410
— .60	510	1.20	1,240	3.00	2,180	7.50	4,715
— .50	550	1.30	1,285	3.20	2,290	8.00	5,060
— .40	590	1.40	1,330	3.40	2,400	8.50	5,440
— .30	620	1.50	1,380	3.60	2,510	9.00	5,880
— .20	660	1.60	1,430	3.80	2,620	9.50	6,340
— .10	700	1.70	1,480	4.00	2,730	10.00	6,900
— .00	740	1.80	1,530	4.20	2,840	11.00	8,800
— .10	780	1.90	1,580	4.40	2,950	12.00	11,800
— .20	820	2.00	1,630	4.60	3,060	13.00	15,000
— .30	860	2.10	1,685	4.80	3,170	14.00	18,200
— .40	900	2.20	1,740	5.00	3,280	15.00	21,400
— .50	940	2.30	1,795	5.20	3,390	16.00	24,600
— .60	980	2.40	1,850	5.40	3,500	17.00	27,800
— .70	1,020	2.50	1,905	5.60	3,610	18.00	31,000

^a Above gage height 12.0 feet the rating curve is a tangent, the difference being 320 per tenth.

Rating tables for Ocmulgee River at Macon—Continued.

JANUARY 1 TO DECEMBER 31, 1899.

Gage height	Dis-charge	Gage height	Dis-charge	Gage height	Dis-charge	Gage height	Dis-charge
<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft</i>	<i>Feet</i>	<i>Sec.-ft.</i>
0.20	580	2.00	1,860	3.80	2,440	7.20	4,480
.30	600	2.10	1,420	3.90	2,500	7.40	4,600
.40	620	2.20	1,480	4.00	2,560	7.60	4,720
.50	650	2.30	1,540	4.20	2,680	7.80	4,860
.60	690	2.40	1,600	4.40	2,800	8.00	5,010
.70	730	2.50	1,660	4.60	2,920	8.50	5,410
.80	770	2.60	1,720	4.80	3,040	9.00	5,810
.90	810	2.70	1,780	5.00	3,160	9.50	6,250
1.00	850	2.80	1,840	5.20	3,280	10.00	6,820
1.10	895	2.90	1,900	5.40	3,400	10.50	7,450
1.20	940	3.00	1,960	5.60	3,520	11.00	8,120
1.30	990	3.10	2,020	5.80	3,640	11.50	8,985
1.40	1,040	3.20	2,080	6.00	3,760	12.00	10,010
1.50	1,090	3.30	2,140	6.20	3,880	13.00	12,900
1.60	1,140	3.40	2,200	6.40	4,000	14.00	16,000
1.70	1,195	3.50	2,260	6.60	4,120	15.00	19,200
1.80	1,250	3.60	2,320	6.80	4,240	16.00	22,400
1.90	1,305	3.70	2,380	7.00	4,360		

JANUARY 1 TO DECEMBER 31, 1900.^b

10.00	6,820	12.50	10,300	15.00	18,100	20.00	39,100
10.50	7,420	13.00	11,240	16.00	22,300	21.00	43,300
11.00	8,020	13.50	12,470	17.00	26,500	22.00	47,500
11.50	8,645	14.00	13,900	18.00	30,700	23.00	51,700
12.00	9,400	14.50	16,000	19.00	34,900		

^b Below gage height 10.0 feet this table is the same as the 1899 table.

JANUARY 1 TO DECEMBER 31, 1901.^c

1.70	978	3.10	1,594	4.50	2,365	6.80	3,940
1.80	1,019	3.20	1,643	4.60	2,426	7.00	4,090
1.90	1,059	3.30	1,693	4.70	2,488	7.20	4,243
2.00	1,100	3.40	1,744	4.80	2,551	7.40	4,398
2.10	1,142	3.50	1,795	4.90	2,615	7.60	4,556
2.20	1,184	3.60	1,849	5.00	2,680	7.80	4,717
2.30	1,227	3.70	1,903	5.20	2,811	8.00	4,880
2.40	1,270	3.80	1,958	5.40	2,945	8.20	5,047
2.50	1,314	3.90	2,014	5.60	3,081	8.40	5,218
2.60	1,359	4.00	2,070	5.80	3,219	8.60	5,395
2.70	1,405	4.10	2,127	6.00	3,360	8.80	5,579
2.80	1,451	4.20	2,185	6.20	3,502	9.00	5,770
2.90	1,498	4.30	2,244	6.40	3,646	9.50	6,265
3.00	1,546	4.40	2,304	6.60	3,792	10.00	6,820

^c Above gage height 10.0 feet this table is the same as the 1900 table.

JANUARY 1 TO DECEMBER 31, 1902.^a

3.10	800	4.40	1,685	5.70	2,700	7.80	4,565
3.20	865	4.50	1,760	5.80	2,780	8.00	4,755
3.30	930	4.60	1,835	5.90	2,865	8.20	4,945
3.40	995	4.70	1,910	6.00	2,950	8.40	5,140
3.50	1,060	4.80	1,985	6.20	3,120	8.60	5,340
3.60	1,125	4.90	2,060	6.40	3,290	8.80	5,540
3.70	1,190	5.00	2,140	6.60	3,460	9.00	5,740
3.80	1,260	5.10	2,220	6.80	3,640	9.20	5,945
3.90	1,330	5.20	2,300	7.00	3,820	9.40	6,155
4.00	1,400	5.30	2,380	7.20	4,000	9.60	6,370
4.10	1,470	5.40	2,460	7.40	4,185	9.80	6,590
4.20	1,540	5.50	2,540	7.60	4,375	10.00	6,820
4.30	1,610	5.60	2,620				

^a Above gage height 10.0 feet this table is the same as the 1900 table.

WATER POWERS OF GEORGIA

Rating tables for Ocmulgee River at Macon—Continued.

JANUARY 1 TO DECEMBER 31, 1903.^b

Gage height	Dis-charge						
<i>Feet</i>	<i>Sec.-feet</i>	<i>Feet</i>	<i>Sec.-feet</i>	<i>Feet</i>	<i>Sec.-feet</i>	<i>Feet</i>	<i>Sec.-feet</i>
2.00	810	3.30	1,505	5.20	2,640	7.80	4,290
2.10	860	3.40	1,560	5.40	2,760	8.00	4,420
2.20	910	3.50	1,620	5.60	2,880	8.50	4,770
2.30	960	3.60	1,680	5.80	3,000	9.00	5,170
2.40	1,010	3.70	1,740	6.00	3,120	9.50	5,570
2.50	1,065	3.80	1,800	6.20	3,250	10.00	6,060
2.60	1,120	3.90	1,860	6.40	3,380	11.00	7,380
2.70	1,175	4.00	1,920	6.60	3,510	12.00	9,020
2.80	1,230	4.20	2,040	6.80	3,640	13.00	11,140
2.90	1,285	4.40	2,160	7.00	3,770	14.00	13,900
3.00	1,340	4.60	2,280	7.20	3,900		
3.10	1,395	4.80	2,400	7.40	4,030		
3.20	1,450	5.00	2,520	7.60	4,160		

JANUARY 1 TO DECEMBER 31, 1904.^c

-0.30	250	0.70	480	1.70	810	3.40	1,660
-.20	270	.80	510	1.80	850	3.60	1,770
-.10	290	.90	540	1.90	895	3.80	1,890
.00	310	1.00	570	2.00	940	4.00	2,010
.10	330	1.10	600	2.20	1,030	4.20	2,130
.20	350	1.20	630	2.40	1,130	4.40	2,250
.30	375	1.30	665	2.60	1,230	4.60	2,370
.40	400	1.40	700	2.80	1,330	4.80	2,490
.50	425	1.50	735	3.00	1,440	5.00	2,610
.60	450	1.60	770	3.20	1,550		

^b Above gage height 14.0 feet this table is the same as the 1900 table.^c For gage heights above 5.0 feet the discharge has been estimated from 1903 measurements.JANUARY 1 TO DECEMBER 31, 1905.^c

-0.60	270	0.70	640	2.00	1,075	3.60	1,800
-.50	295	.80	670	2.10	1,110	3.80	1,910
-.40	320	.90	700	2.20	1,150	4.00	2,020
-.30	345	1.00	730	2.30	1,190	4.20	2,130
-.20	370	1.10	760	2.40	1,230	4.40	2,250
-.10	400	1.20	795	2.50	1,270	4.60	2,370
.00	430	1.30	830	2.60	1,315	4.80	2,490
.10	460	1.40	865	2.70	1,360	5.00	2,610
.20	490	1.50	900	2.80	1,405		
.30	520	1.60	935	2.90	1,450		
.40	550	1.70	970	3.00	1,500		
.50	580	1.80	1,005	3.20	1,600		
.60	610	1.90	1,040	3.40	1,700		

^c For gage heights above 5.0 feet the discharge has been estimated from 1903 measurements.

JANUARY 1 TO DECEMBER 31, 1906.

2.00	1,075	3.50	1,750	5.00	2,610	8.00	4,580
2.10	1,110	3.60	1,800	5.20	2,730	9.00	5,340
2.20	1,150	3.70	1,855	5.40	2,850	10.00	6,240
2.30	1,190	3.80	1,910	5.60	2,980	11.00	7,270
2.40	1,230	3.90	1,965	5.80	3,110	12.00	8,400
2.50	1,270	4.00	2,020	6.00	3,240	13.00	9,600
2.60	1,315	4.10	2,075	6.20	3,372	14.00	10,900
2.70	1,360	4.20	2,130	6.40	3,504	15.00	12,300
2.80	1,405	4.30	2,190	6.60	3,636	16.00	13,800
2.90	1,450	4.40	2,250	6.80	3,768	17.00	15,400
3.00	1,500	4.50	2,310	7.00	3,900	18.00	17,100
3.10	1,550	4.60	2,370	7.20	4,032	19.00	18,900
3.20	1,600	4.70	2,430	7.40	4,164	20.00	20,800
3.30	1,650	4.80	2,490	7.60	4,300		
3.40	1,700	4.90	2,550	7.80	4,440		

NOTE.—The above table is based on discharge measurements made during 1903-1906 and is fairly well defined.

ALTAMAHA DRAINAGE BASIN, STREAM FLOW

Estimated monthly discharge of Ocmulgee River at Macon.

[Drainage area, 2,425 square miles.]

Month.	Discharge in second-feet			Run-off	
	Maximum	Minimum	Mean	Sec.-ft. per sq. mile	Depth in inches
1893.					
January 21 to 31	4,240	1,887 ^a	2,881 ^d	1.19	0.48
February	18,550	1,828	5,667	2.34	2.44
March 1 to 20, 24 to 31	13,385	1,672	4,498 ^b	1.83	1.90
April	7,250	1,285	1,988	0.80	0.89
May	4,830	855	1,844 ^c	0.76	0.87
June	8,205	1,290	2,352	0.97	1.08
July	3,830	1,113 ^e	1,411	0.58	0.67
August	15,100	1,242	2,836 ^f	1.15	1.28
September	10,130	1,371	2,787	0.96	1.10
October	5,750	1,328	1,905	0.79	0.91
November	20,50	1,414 ^g	1,552	0.64	0.71
December	2,285	1,414 ^h	1,794 ⁱ	0.74	0.85
1894.					
January	4,430	1,457 ^j	2,246	0.93	1.07
February	15,925	1,629 ^k	4,488	1.85	1.92
March	9,285	2,050 ^l	3,415	1.41	1.63
April	4,155 ^m	1,629 ⁿ	2,409	0.99	1.10
May	2,050	1,285 ^o	1,464 ^p	0.60	0.69
June	2,050	1,113 ^q	1,859	0.76	0.82
July	5,635	1,285	2,391	0.98	1.13
August	17,350	2,050	3,854	1.59	1.33
September	10,795	1,200 ^r	2,723	1.12	1.25
October	20,075	1,113 ^s	2,841	1.17	1.35
November	4,600	1,200	1,980	0.82	0.91
December	14,550	1,156	2,827	1.17	1.35
The year	20,075	1,113 ^t	2,666	1.10	14.85
1895.					
January	19,750	1,629 ^u	4,698	1.94	2.24
February	3,750	2,100	2,510	1.08	1.13
March	30,715	2,050	8,187 ^v	3.38	3.40
April	12,975	2,470	5,040	2.08	2.32
May	12,975	2,820	3,244 ^w	1.34	1.54
June	2,800	2,006	2,522	0.96	1.07
July	15,100	2,006	4,360	1.80	2.16
August	14,000	1,963 ^x	4,529	1.87	2.18
September	3,090	2,050	2,502	1.03	1.15
October	1,629	842	1,036	0.43	0.49
November	1,174	971	1,016	0.42	0.47
December	2,775	941	1,284	0.53	0.61
The year	30,715	842 ^y	3,402 ^z	1.40 ^{aa}	19.16
1896.					
January	13,600	1,178	3,353	1.38	1.59
February	14,270	1,801	3,889	1.60	1.73
March	4,800	1,586	2,884	1.19	1.37
April	2,860	1,043 ^{bb}	1,449 ^{cc}	0.60	0.67
May	1,942 ^{dd}	727 ^{ee}	1,001	0.41	0.47
June	4,586	405	888	0.37	0.41
July	36,200	340	7,436	3.07	3.54
August	2,075	727 ^{ff}	1,150	0.47	0.54
September	813	380	608	0.25	0.28
October	727 ^{gg}	380	487	0.20	0.23
November	17,950	706 ^{hh}	3,227	1.33	1.48
December	13,200	1,070	3,261	1.35	1.56
The year	36,200	340 ⁱⁱ	2,469	1.02	13.87
1897.					
January	4,400	382 ^{jj}	1,369 ^{kk}	0.56	0.64
February	17,450	1,584	4,275	1.76	1.83
March	28,700	1,604	8,377	3.66	4.22
April	21,575 ^{ll}	1,604	5,463	2.25	2.51
May	2,221	1,269	1,692 ^{mm}	0.70	0.81
June	2,206	1,094 ⁿⁿ	1,732	0.71	0.79 ^{oo}
July	8,250	781	1,913	0.79	0.91
August	6,120	772 ^{pp}	1,759	0.73	0.84
September	1,416	481	715	0.29 ^{qq}	0.32 ^{rr}
October	1,048	442 ^{ss}	622 ^{tt}	0.26	0.30 ^{uu}
November	2,132	481 ^{vv}	730	0.32	0.36
December	1,361	364 ^{ww}	1,059 ^{xx}	0.44 ^{yy}	0.51
The year	28,700	442 ^{zz}	2,521	1.04	14.04 ^{aa}

Estimated monthly discharge of Ocmulgee River at Macon—Continued.

Month	Discharge in second-feet			Run-off	
	Maximum	Minimum	Mean	Sec.-ft. per sq. mile	Depth in inches
1898					
January.....	3,472	860	1,300	0.54	0.62
February.....	1,195	820	964	0.40	0.42
March.....	2,675	840	1,263	0.52	0.60
April.....	12,120	940	2,619	1.08	1.20
May.....	1,555	600	909	0.38	0.44
June.....	1,740	388	653	0.27	0.30
July.....	5,880	405	1,645	0.68	0.78
August.....	15,000	940	4,630	1.91	2.20
September.....	31,640	1,040	6,008	2.48	2.77
October.....	23,760	1,020	5,784	2.36	2.72
November.....	18,520	1,555	3,698	1.52	1.70
December.....	16,920	2,042	3,567	1.47	1.99
The year.....	31,640	388	2,749	1.13	15.44
1899					
January.....	19,840	2,380	5,570	2.30	2.66
February.....	21,920	3,820	8,140	3.36	3.50
March.....	18,292	3,460	5,495	2.27	2.62
April.....	11,060	2,770	4,481	1.85	2.06
May.....	5,090	1,390	2,112	0.87	1.00
June.....	2,800	810	1,331	0.55	0.61
July.....	3,220	650	1,196	0.49	0.56
August.....	2,140	620	1,071	0.44	0.51
September.....	1,720	580	880	0.36	0.40
October.....	6,820	600	1,339	0.55	0.63
November.....	3,340	620	987	0.41	0.46
December.....	4,000	850	1,531	0.65	0.75
The year.....	21,920	580	2,849	1.17	15.76
1900					
January.....	2,920	940	1,530	0.63	0.73
February.....	46,240	1,090	9,700	4.00	4.16
March.....	7,900	3,280	4,644	1.92	2.21
April.....	30,700	2,620	7,005	2.89	3.22
May.....	5,490	1,900	2,871	1.18	1.36
June.....	39,940	1,900	8,216	3.39	3.78
July.....	11,950	2,140	3,615	1.49	1.72
August.....	3,820	1,480	1,995	0.82	0.95
September.....	11,950	1,195	2,560	1.06	1.18
October.....	5,250	1,195	1,876	0.77	0.89
November.....	9,940	1,360	2,307	0.95	1.06
December.....	10,840	1,660	4,079	1.63	1.94
The year.....	46,240	940	4,200	1.73	23.20
1901					
January.....	13,010	2,244	4,903	2.02	2.33
February.....	21,880	2,185	5,165	2.13	2.22
March.....	22,720	1,693	4,536	1.89	2.18
April.....	34,060	2,244	6,556	2.70	3.01
May.....	13,590	1,546	2,806	1.16	1.34
June.....	6,704	1,693	3,323	1.37	1.53
July.....	19,780	1,314	2,521	1.04	1.20
August.....	16,420	1,184	4,686	1.93	2.23
September.....	29,440	1,227	3,913	1.61	1.80
October.....	3,081	978	1,412	.58	.67
November.....	1,314	978	1,104	.46	.51
December.....	30,230	1,059	4,324	1.78	2.05
The year.....	34,060	973	3,775	1.56	21.07
1902					
January.....	21,040	800	2,242	.92	1.06
February.....	38,680	2,060	8,444	3.48	3.62
March.....	50,860	4,280	12,700	5.24	6.04
April.....	10,840	2,780	4,738	1.95	2.18
May.....	3,290	1,540	2,292	.95	1.10
June.....	3,120	995	1,631	.67	.75
July.....	2,300	800	1,169	.48	.55
August.....	6,260	865	1,624	.67	.77
September.....	3,680	865	1,377	.57	.64
October.....	2,620	800	1,430	.59	.68
November.....	5,540	800	1,423	.59	.66
December.....	11,950	1,125	2,961	1.22	1.41
The year.....	50,860	800	3,502	1.44	19.46

Estimated monthly discharge of Ocmulgee River at Macon—Continued.

Month	Discharge in second-feet			Run-off	
	Maximum	Minimum	Mean	Sec.-ft. per sq. mile	Depth in inches
1903					
January.....	2,760	1,800	2,191	0.90	1.04
February.....	42,040	1,920	11,345	4.89	5.09
March.....	31,960	3,380	9,561	3.94	4.54
April.....	15,160	2,760	5,003	2.06	2.30
May.....	7,380	2,040	2,991	1.23	1.42
June.....	28,180	1,920	4,962	2.05	2.29
July.....	7,380	1,450	2,558	1.05	1.21
August.....	7,660	1,175	2,460	1.01	1.16
September.....	16,840	810	2,380	.98	1.09
October.....	2,460	960	1,110	.46	.58
November.....	1,980	910	1,235	.51	.57
December.....	1,740	960	1,272	.52	.60
The year.....	42,040	810	3,964	1.63	21.84
1904					
January.....	9,480	985	2,064	.851	.981
February.....	6,540	1,495	3,149	1.30	1.40
March.....	4,100	1,440	2,214	.913	1.05
April.....	3,050	1,330	1,535	.633	.706
May.....	1,830	665	1,120	.462	.533
June.....	2,490	510	1,029	.424	.473
July.....	2,370	480	772	.318	.367
August.....	12,600	810	2,967	1.22	1.41
September.....	2,430	330	671	.277	.309
October.....	400	250	300	.124	.143
November.....	985	290	602	.248	.277
December.....	3,505	570	1,295	.534	.616
The year.....	12,600	250	1,476	.609	8.26
1905					
January.....	5,170	970	1,599	.659	.760
February.....	23,980	1,040	5,307	2.19	2.23
March.....	2,940	1,230	1,816	.749	.864
April.....	3,315	1,075	1,484	.612	.683
May.....	2,460	985	1,530	.635	.732
June.....	2,400	640	1,072	.442	.493
July.....	4,560	700	1,878	.774	.892
August.....	6,830	400	1,466	.605	.698
September.....	1,230	270	533	.220	.246
October.....	1,450	466	696	.287	.331
November.....	2,130	526	810	.334	.373
December.....	25,240	670	5,580	2.30	2.65
The year.....	25,240	270	1,982	.817	11.00
1906					
January.....	20,600	2,430	5,820	2.40	2.77
February.....	3,570	1,800	2,430	1.00	1.04
March.....	15,400	1,700	5,980	2.47	2.85
April.....	5,520	1,600	2,560	1.06	1.13
May.....	2,430	1,150	1,520	.628	.72
June.....	17,100	1,080	4,170	1.72	1.92
July.....	6,740	1,190	2,590	1.19	1.37
August.....	7,490	1,500	3,300	1.36	1.57
September.....	6,060	1,150	2,860	1.18	1.32
October.....	17,500	1,450	4,510	1.86	2.14
November.....	2,920	1,360	1,670	.690	.77
December.....	3,770	1,360	1,890	.781	.90
The year.....	20,600	1,080	3,300	1.36	18.55

a Gage heights from October 3 to 5 are considered too low to represent the true mean. The minimum discharge for the month has been assumed to apply for those days.

ALTAMAHA DRAINAGE BASIN, STREAM FLOW

Discharge measurements of Yellow River at Almon.

Date.	Gage height	Dis-charge	Date.	Gage height	Dis-charge
1896.	<i>Feet</i>	<i>Sec.-ft.</i>	1899.	<i>Feet</i>	<i>Sec.-ft.</i>
September 19.....	0.75	62	August 7.....	1.40	218
1897.			October 19.....	1.70	200
March 27.....	3.90	876	1900.		
June 21.....	2.50	287	April 19.....	9.00	3,295
September 7.....	1.53	123	November 30.....	2.40	341
December 8.....	2.10	227	December 22.....	4.50	966
1899.			1901.		
May 3.....	2.97	481	January 29.....	3.40	541
May 9.....	3.16	561	April 3.....	13.80	4,536
May 16.....	2.30	364	June 14.....	3.80	610
June 6.....	1.80	235	August 8.....	2.58	283
June 27.....	2.42	427	October 26.....	2.33	253

Daily gage height, in feet, of Yellow River at Almon.

Day	Sept.	Oct.	Nov.	Dec.	Day	Sept.	Oct.	Nov.	Dec.
1897					1897				
1.....		1.2	1.6	2.2	17.....	1.25	1.5	1.33	2.0
2.....		1.1	1.65	2.8	18.....	1.3	1.6	1.69	2.08
3.....		1.15	1.98	2.7	19.....	1.3	1.7	1.65	1.98
4.....		1.2	1.9	2.2	20.....	1.22	1.8	1.64	2.0
5.....		1.1	1.88	2.8	21.....	1.2	1.7	1.63	2.08
6.....		1.15	1.7	2.9	22.....	1.2	1.68	1.67	2.09
7.....		1.1	1.5	2.1	23.....	1.28	1.66	1.66	2.2
8.....		1.1	1.6	2.08	24.....	1.35	1.6	1.7	2.18
9.....		1.15	1.75	2.06	25.....	1.25	1.58	1.68	2.1
10.....		1.2	1.7	2.0	26.....	1.3	1.5	1.7	2.18
11.....		1.35	1.68	1.98	27.....	1.35	1.4	1.7	2.1
12.....	1.4	1.9	1.66	1.98	28.....	1.3	1.4	1.76	2.0
13.....	1.3	1.98	1.64	1.95	29.....	1.28	1.45	1.8	1.98
14.....	1.42	1.9	1.64	1.89	30.....	1.24	1.5	2.0	2.0
15.....	1.4	1.8	1.64	1.86	31.....		1.5		2.04
16.....	1.3	1.52	1.64	1.90					

WATER POWERS OF GEORGIA

Daily gage height, in feet, of Yellow River at Almon—Continued.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1899.												
1.....						2.4	1.6	1.9	2.1	1.2	1.6	2.0
2.....						2.1	1.5	1.8	2.0	1.2	1.6	2.7
3.....						2.0	1.4	1.7	1.8	1.2	1.5	2.5
4.....						1.9	1.3	1.6	1.6	1.2	1.5	2.3
5.....						1.8	1.4	1.6	1.5	1.7	1.5	2.0
6.....						1.8	1.5	1.4	1.5	2.0	1.5	1.9
7.....						1.7	1.3	1.4	1.5	2.5	1.5	1.9
8.....						1.7	1.6	1.4	1.5	4.0	1.5	1.9
9.....					3.2	1.7	1.3	1.3	1.4	2.3	1.5	1.9
10.....					2.8	1.7	1.6	1.3	1.4	2.2	1.5	1.9
11.....					2.3	1.7	1.4	1.3	2.5	1.3	1.5	1.9
12.....					2.7	2.0	1.4	1.3	2.0	1.3	1.5	4.0
13.....					2.7	2.5	1.3	1.2	1.7	1.3	1.5	3.0
14.....					2.5	2.1	1.3	1.2	1.5	1.3	1.5	2.5
15.....					2.5	1.9	1.2	1.2	1.5	1.7	1.5	2.3
16.....					2.5	1.8	1.2	1.1	1.4	1.7	1.6	2.0
17.....					2.3	1.8	1.2	1.1	1.4	1.7	1.5	2.0
18.....					2.1	1.8	1.3	1.0	1.4	1.7	1.5	2.0
19.....					2.3	1.7	1.4	1.0	1.3	1.7	1.5	2.0
20.....					2.1	1.6	1.4	1.0	1.3	2.0	1.5	2.0
21.....					2.0	1.5	1.6	1.0	1.3	1.9	1.5	2.0
22.....					2.3	1.5	1.3	1.0	1.3	1.7	1.5	2.0
23.....					2.3	1.5	2.0	1.0	1.3	1.5	2.2	2.0
24.....					2.5	1.4	1.4	1.0	1.2	1.5	2.2	5.5
25.....					2.2	1.4	1.6	1.0	1.2	1.5	1.9	4.6
26.....					2.0	3.2	2.4	3.6	1.2	1.5	4.5	3.4
27.....					2.0	2.6	5.3	3.0	1.2	1.5	4.0	2.5
28.....					2.0	2.0	5.0	2.8	1.2	1.5	3.2	2.5
29.....					1.9	2.0	3.7	2.7	1.2	1.6	2.5	2.5
30.....					1.8	1.8	2.3	2.5	1.2	1.7	2.0	2.5
31.....					3.3		2.0	2.3		1.7		2.3
1900.												
1.....	2.1	2.0	4.5	3.1	3.7	2.4	4.0	3.4	3.0	2.0	2.0	2.4
2.....	1.9	2.0	4.5	3.0	3.3	2.4	5.0	2.7	3.0	2.0	2.0	2.3
3.....	1.9	2.0	3.5	3.0	7.2	2.4	5.0	2.5	2.5	2.0	2.0	2.3
4.....	1.9	2.0	3.4	3.0	6.9	2.4	4.7	2.3	2.3	2.5	4.3	7.5
5.....	2.0	2.5	3.2	3.0	4.0	3.4	4.0	2.3	2.1	2.5	4.0	7.0
6.....	2.0	2.7	3.0	3.0	3.6	4.0	3.5	2.2	2.1	2.3	3.0	5.0
7.....	2.0	2.5	3.0	2.9	3.4	3.4	3.0	2.1	2.0	3.5	2.5	3.5
8.....	2.0	2.5	4.7	2.9	3.2	6.7	3.0	2.0	2.0	4.0	2.0	3.0
9.....	2.0	3.5	10.0	2.9	3.1	4.4	3.0	2.0	2.0	3.0	2.0	2.9
10.....	2.3	5.7	6.0	2.9	3.0	3.3	3.0	2.0	2.0	2.7	2.0	2.3
11.....	2.9	5.9	4.0	3.9	3.0	3.1	3.0	1.9	2.0	2.4	2.0	2.3
12.....	4.4	15.0	3.8	4.7	3.0	2.9	3.0	1.9	2.0	2.4	2.0	2.9
13.....	3.5	20.0	3.6	4.0	2.9	2.8	3.0	1.9	2.0	2.4	2.0	2.7
14.....	3.0	15.0	3.4	3.4	2.3	3.2	3.0	1.9	3.0	2.3	2.0	4.0
15.....	2.5	7.0	3.3	3.0	2.3	3.0	3.0	2.5	3.0	2.3	2.0	3.5
16.....	2.5	5.0	3.3	2.0	2.3	4.0	2.3	2.3	7.0	2.2	2.0	3.2
17.....	2.4	4.9	3.4	3.0	2.3	6.0	2.7	2.2	4.0	2.1	2.0	3.0
18.....	3.4	4.7	3.0	3.0	2.7	5.0	2.6	2.0	3.0	2.0	2.0	2.3
19.....	4.0	3.6	3.4	9.0	3.5	4.0	2.5	2.0	2.5	2.0	2.0	2.3
20.....	4.3	4.7	5.0	6.3	2.3	3.5	2.0	2.0	2.0	2.0	2.0	5.0
21.....	3.6	3.9	4.3	12.0	2.3	3.2	2.0	2.0	2.0	2.0	2.0	6.5
22.....	3.0	3.3	3.7	10.0	2.6	3.0	2.0	2.5	2.0	2.0	2.0	4.5
23.....	2.3	3.7	3.4	6.0	2.6	7.5	2.0	2.5	2.0	3.0	2.0	3.5
24.....	2.6	3.7	3.7	7.2	4.0	11.0	2.0	2.4	2.0	3.0	2.0	3.5
25.....	2.5	3.7	5.5	12.0	3.0	11.0	2.5	2.3	2.0	2.5	2.0	3.5
26.....	2.4	3.3	3.0	6.3	2.3	12.0	2.0	2.0	2.0	2.3	4.5	3.0
27.....	2.3	3.3	6.0	6.0	2.6	9.0	3.0	2.0	2.0	2.0	3.5	3.0
28.....	2.2	3.3	4.4	5.3	2.4	9.5	3.5	2.0	2.0	2.0	2.5	2.9
29.....	2.1		4.0	5.4	2.4	6.3	3.5	2.0	2.0	2.0	2.4	2.9
30.....	2.0		3.5	4.3	2.4	5.0	5.0	2.0	2.0	2.0	2.4	4.0
31.....	2.0		3.2		2.4		4.0	5.0		2.0		7.5
1901.												
1.....	6.0	3.4	3.2	6.0	3.2	5.0	3.2	2.4	5.5	3.0	2.2	2.4
2.....	5.5	3.4	3.2	11.0	3.1	4.1	3.0	2.3	4.2	4.5	2.2	2.4
3.....	6.0	10.0	3.1	13.9	3.0	3.5	2.9	2.2	3.1	4.3	2.4	3.0
4.....	5.0	15.0	3.1	8.3	3.0	3.4	2.3	2.2	3.4	4.0	2.4	2.9
5.....	4.3	12.0	3.1	5.5	3.0	3.3	2.7	2.1	3.4	3.2	2.4	2.3

ALTAMAHA DRAINAGE BASIN, STREAM FLOW

Daily gage height, in feet, of Yellow River at Almon—Continued.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1901												
6.....	4.0	5.5	3.0	5.0	3.0	3.2	2.6	2.8	3.1	3.0	2.4	2.7
7.....	3.8	5.5	3.0	4.5	3.0	4.4	2.5	3.0	3.0	3.0	2.4	2.7
8.....	3.7	5.8	3.0	4.0	2.9	3.5	2.4	2.8	2.9	3.0	2.4	2.8
9.....	3.5	6.3	3.0	3.9	2.9	3.4	2.3	2.5	2.9	3.0	2.4	2.8
10.....	3.4	5.4	3.0	3.8	2.8	3.3	2.2	2.4	2.8	3.0	2.4	2.8
11.....	5.0	4.6	4.5	3.7	2.8	3.2	2.4	2.8	2.8	3.0	2.4	2.8
12.....	10.0	4.4	4.0	3.7	2.8	3.0	2.3	4.2	3.5	3.0	2.4	2.8
13.....	10.0	4.0	3.5	4.0	2.7	3.4	2.2	3.4	2.8	2.8	2.4	2.8
14.....	5.5	3.9	3.0	9.5	2.7	3.6	2.2	2.8	2.8	2.8	2.4	2.8
15.....	4.5	3.7	2.9	8.4	2.7	6.7	2.8	3.8	2.8	2.7	2.4	6.0
16.....	4.2	3.5	2.8	5.2	2.6	7.0	3.0	7.0	2.8	2.7	2.4	4.8
17.....	4.0	3.4	2.8	5.0	2.6	4.8	3.8	7.5	3.5	2.7	3.0	3.2
18.....	4.0	3.4	2.8	4.0	2.8	7.0	3.4	4.8	9.0	2.7	3.0	3.0
19.....	3.8	3.4	2.8	5.1	2.8	6.1	10.0	3.5	10.0	2.7	3.0	2.8
20.....	3.8	3.4	2.8	5.4	2.8	4.1	7.0	6.0	4.8	2.7	3.0	2.8
21.....	3.5	3.3	2.8	4.5	5.0	3.2	3.4	3.9	3.0	2.7	3.0	2.8
22.....	3.5	3.2	2.8	4.0	7.5	3.2	3.2	6.0	3.6	2.6	3.0	2.8
23.....	3.4	3.2	2.8	3.9	6.1	3.1	2.9	10.0	3.6	2.6	3.0	3.0
24.....	3.8	3.2	5.4	3.8	4.2	3.0	2.8	8.0	3.4	2.6	3.0	3.0
25.....	4.0	3.4	6.0	3.7	3.6	3.0	2.7	4.7	3.2	2.5	2.8	3.0
26.....	3.5	3.2	7.0	3.6	3.4	4.0	2.6	3.8	3.2	2.5	2.7	3.0
27.....	3.4	3.2	10.0	3.5	3.3	4.2	2.4	5.0	3.0	2.5	2.6	3.0
28.....	3.4	3.2	7.0	3.5	3.2	3.3	2.3	9.0	3.0	2.5	2.5	3.0
29.....	3.4	5.0	3.4	3.0	3.1	2.2	10.0	3.0	2.5	2.4	10.0
30.....	4.0	4.0	3.3	2.9	3.1	2.7	4.8	3.0	2.4	2.4	20.0
31.....	3.5	3.0	5.2	2.5	4.0	2.3	15.0

Rating tables for Yellow River at Almon.^a

SEPTEMBER 12 TO DECEMBER 31, 1897.

Gage height	Dis-charge						
Feet	Sec.-ft.	Feet	Sec.-ft.	Feet	Sec.-ft.	Feet	Sec.-ft.
1.10	85	1.60	130	2.10	194	2.60	326
1.20	98	1.70	140	2.20	211	2.70	366
1.30	101	1.80	152	2.30	231	2.80	408
1.40	110	1.90	165	2.40	256	2.90	450
1.50	120	2.00	179	2.50	290		

MAY 9 TO DECEMBER 31, 1899.

1.00	120	2.20	345	3.40	615	4.60	835
1.10	133	2.30	367	3.50	637	4.70	907
1.20	147	2.40	390	3.60	660	4.80	930
1.30	160	2.50	412	3.70	682	4.90	952
1.40	175	2.60	435	3.80	705	5.00	975
1.50	193	2.70	457	3.90	727	5.20	1,020
1.60	212	2.80	480	4.00	750	5.40	1,065
1.70	233	2.90	502	4.10	772	5.60	1,110
1.80	255	3.00	525	4.20	795	5.80	1,155
1.90	277	3.10	547	4.30	817		
2.00	300	3.20	570	4.40	840		
2.10	322	3.30	592	4.50	862		

^aAbove gage height 3.8 feet the rating curve is a tangent, the difference being 39 per tenth

WATER POWERS OF GEORGIA

Rating tables for Yellow River at Almon—Continued.

JANUARY 1 TO DECEMBER 31, 1900.

Gage height	Discharge						
<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>
1.90	275	3.60	660	5.60	1,480	9.00	3,200
2.00	290	3.70	690	5.80	1,585	9.50	3,568
2.10	310	3.80	720	6.00	1,690	10.00	3,887
2.20	330	3.90	750	6.20	1,797	10.50	4,106
2.30	350	4.00	780	6.40	1,904	11.00	4,375
2.40	370	4.10	815	6.60	2,012	11.50	4,643
2.50	390	4.20	850	6.80	2,119	12.00	4,912
2.60	410	4.30	885	7.00	2,227	12.50	5,181
2.70	430	4.40	920	7.20	2,334	13.00	5,450
2.80	455	4.50	955	7.40	2,441	13.50	5,718
2.90	480	4.60	990	7.60	2,549	14.00	5,987
3.00	505	4.70	1,035	7.80	2,656	15.00	6,525
3.10	530	4.80	1,080	8.00	2,763	16.00	7,062
3.20	555	4.90	1,125	8.20	2,870	17.00	7,600
3.30	580	5.00	1,175	8.40	2,977	18.00	8,137
3.40	605	5.20	1,275	8.60	3,085	19.00	8,675
3.50	630	5.40	1,375	8.80	3,192	20.00	9,212

JANUARY 1 TO DECEMBER 31, 1901.

2.10	295	3.80	652	6.00	1,510	9.40	2,836
2.20	250	3.90	691	6.20	1,588	9.60	2,914
2.30	266	4.00	730	6.40	1,666	9.80	2,992
2.40	283	4.10	769	6.60	1,744	10.00	3,070
2.50	301	4.20	808	6.80	1,822	11.00	3,460
2.60	320	4.30	847	7.00	1,900	12.00	3,850
2.70	340	4.40	886	7.20	1,978	13.00	4,240
2.80	361	4.50	925	7.40	2,056	14.00	4,630
2.90	383	4.60	964	7.60	2,134	15.00	5,020
3.00	406	4.70	1,003	7.80	2,212	16.00	5,410
3.10	430	4.80	1,042	8.00	2,290	17.00	5,800
3.20	455	4.90	1,081	8.20	2,368	18.00	6,190
3.30	482	5.00	1,120	8.40	2,446	19.00	6,580
3.40	511	5.20	1,198	8.60	2,524	20.00	6,970
3.50	543	5.40	1,276	8.80	2,602		
3.60	577	5.60	1,354	9.00	2,680		
3.70	614	5.80	1,432	9.20	2,758		

ALTAMAHA DRAINAGE BASIN, STREAM FLOW

Estimated monthly discharge of Yellow River at Almon.

[Drainage area, 379 square miles.]

Month	Discharge in second-feet			Run-off	
	Maximum	Minimum	Mean	Sec.-ft.-per sq. mile	Depth in inches
1897					
September 12-30.....	112	93	101	0.27	0.18
October.....	174	85	119	.31	.36
November.....	179	120	141	.37	.41
December.....	450	160	215	.57	.66
1899					
May 9-31.....	570	255	391	1.03	.88
June.....	570	175	276	.73	.81
July.....	1,155	147	284	.75	.86
August.....	660	120	223	.59	.68
September.....	412	147	197	.52	.58
October.....	750	147	256	.68	.78
November.....	862	193	272	.72	.80
December.....	1,087	277	405	1.07	1.23
1900					
January.....	920	275	427	1.13	1.30
February.....	9,225	290	1,493	3.94	4.10
March.....	3,837	505	963	2.54	2.93
April.....	4,912	290	1,432	3.78	4.21
May.....	2,333	370	622	1.64	1.89
June.....	4,912	370	1,390	3.67	4.09
July.....	1,175	290	570	1.50	1.73
August.....	1,175	275	358	.94	1.08
September.....	2,763	290	492	1.30	1.45
October.....	780	290	373	.98	1.13
November.....	955	290	379	1.00	1.12
December.....	2,492	350	806	2.43	2.46
The year.....	9,225	275	775	2.05	27.49
1901					
January.....	3,070	511	984	2.46	2.84
February.....	5,020	455	1,076	2.84	2.96
March.....	3,070	361	710	1.87	2.16
April.....	4,591	482	1,221	3.22	2.59
May.....	2,095	320	551	1.45	1.67
June.....	1,900	406	741	1.96	2.19
July.....	3,070	250	488	1.29	1.49
August.....	3,070	235	988	2.61	3.01
September.....	3,070	361	655	1.73	1.93
October.....	925	266	397	1.05	1.21
November.....	406	250	320	.84	.94
December.....	6,970	283	880	2.32	2.68
The year.....	6,970	235	947	1.97	25.67

ALCOVY RIVER NEAR COVINGTON

This station was established on April 30, 1901, about 3 miles east of Covington, at a low wooden bridge which is often under water. It was discontinued on December 31, 1904.

The banks are low and liable to overflow. The ground on the right bank is low and swampy for several hundred yards and is flooded by a moderate rise. The bed of the stream is sandy and shifting, and the water is sluggish at low stages. Discharge measurements were made from the upstream side of a low, two-span, wooden bridge about 100 feet long. The initial point for soundings is the end of the bridge floor on the left bank, upstream side. The gage is a vertical rod 10 feet long, spiked to a birch tree on the left bank of the river 2 feet from the upstream side of the bridge. The observer was Stephen Belcher, a farmer living near, who was paid by the Georgia Geological Survey. Bench mark No. 2 is a copper plug set in the solid rock on the north edge of the side ditch on the upstream side of the road, 100 feet from the end of the bridge, on the left bank of the river; elevation, 7.82 feet above the zero of the gage.

Discharge measurements of Alcovy River near Covington.

Date	Gage height	Dis-charge	Date	Gage height	Dis-charge
1901			1903		
	<i>Feet</i>	<i>Sec.-ft.</i>		<i>Feet</i>	<i>Sec.-ft.</i>
April 30.....	3.00	307	August 27.....	1.60	127
June 14.....	3.12	353	October 8.....	1.50	120
August 8.....	3.64	376	November 14.....	1.90	157
October 26.....	2.00	162	December 19.....	1.85	155
1902			1904		
February 27.....	4.87	661	February 20.....	3.67	415
June 14.....	1.70	156	April 13.....	2.11	202
July 18.....	1.32	127	June 16.....	.63	65
September 12.....	1.20	128	July 12.....	1.00	94
1903			September 22.....	.45	53
March 11.....	4.41	575	September 22 <i>a</i>45	53
May 28.....	3.43	385	September 22 <i>b</i>45	42
July 24.....	1.92	174	December 6.....	3.35	328
			December 6.....	3.38	358

a 20) feet below bridge.

b 300 feet above bridge.

Daily gage height, in feet, of Alcovy River near Covington.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1901												
1.....					2.9	4.2	4.0	1.6	5.0	3.0	2.0	2.1
2.....					2.8	4.3	3.4	1.5	4.5	4.3	2.0	2.0
3.....					2.8	4.0	2.8	1.4	3.7	4.3	2.0	2.8
4.....					2.7	3.3	2.6	1.6	3.0	4.2	2.0	3.2
5.....					2.7	3.0	2.4	1.6	2.8	3.2	2.3	3.0
6.....					2.7	2.7	2.2	4.3	2.5	2.9	2.1	2.7
7.....					2.8	4.5	2.0	5.1	2.4	2.5	2.1	2.5
8.....					2.6	4.0	1.9	4.0	2.2	2.3	2.1	2.5
9.....					2.5	3.2	1.9	2.5	2.0	2.3	2.0	2.4
10.....					2.4	2.6	1.8	2.1	2.0	2.3	2.1	2.9
11.....					2.4	2.4	2.0	5.2	2.0	2.3	2.1	3.0
12.....					2.3	2.3	2.5	5.0	2.0	2.3	2.1	2.7
13.....					2.3	2.5	3.1	4.0	1.9	2.5	2.1	2.5
14.....					2.4	3.1	3.9	3.5	2.0	2.4	2.1	2.5
15.....					2.3	3.3	4.6	4.8	2.1	2.4	2.0	5.2
16.....					2.2	3.8	4.3	6.1	2.0	2.3	2.0	5.3
17.....					2.1	4.3	4.0	5.9	5.0	2.1	2.0	4.5
18.....					2.0	4.8	3.8	5.5	6.3	2.0	2.1	4.2
19.....					2.0	5.7	3.3	5.3	5.9	2.0	2.1	3.0
20.....					2.5	5.3	4.0	4.6	6.0	2.0	2.5	2.8
21.....					3.4	5.0	4.8	5.6	5.3	1.9	2.8	2.4
22.....					4.5	3.6	5.3	5.6	3.9	1.9	2.6	2.8
23.....					4.2	2.9	5.8	6.8	3.2	1.9	2.4	2.8
24.....					3.7	2.6	5.0	6.2	2.9	2.0	2.4	3.0
25.....					3.2	2.4	4.2	5.0	2.3	2.0	2.3	3.2
26.....					2.9	2.8	3.7	4.5	2.6	2.0	2.3	3.3
27.....					2.8	4.5	3.2	4.0	2.5	2.0	2.2	3.1
28.....					2.7	5.1	2.7	4.7	2.4	2.0	2.1	3.8
29.....					2.5	4.9	2.5	6.2	2.4	2.0	2.1	5.4
30.....				3.0	2.4	3.6	2.0	6.0	2.5	2.0	2.1	6.9
31.....					3.3		2.4	4.9		2.0		7.4
1902												
1.....	6.5	5.2	9.5	5.6	3.0	1.9	1.0	1.8	1.4	2.7	1.6	3.5
2.....	5.4	7.3	7.2	5.0	3.5	1.4	1.0	1.4	1.3	2.5	1.7	5.0
3.....	4.8	8.8	6.2	4.8	3.2	2.2	1.0	4.2	1.2	2.0	1.6	5.3
4.....	4.3	7.0	5.3	4.5	3.0	2.0	2.2	3.7	1.0	1.7	1.9	5.1
5.....	4.0	6.7	5.3	4.3	2.9	1.9	1.7	5.0	1.0	2.0	2.2	4.9

Daily gage height, in feet, of Alcovy River near Covington—Continued.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1902												
6	3.7	6.3	5.0	4.2	2.8	1.7	1.7	3.8	1.0	1.9	2.1	4.7
7	3.5	4.9	4.8	4.5	2.7	1.7	1.5	2.5	1.2	1.8	2.0	2.5
8	3.4	4.4	4.6	4.9	2.6	2.5	1.3	2.4	1.1	1.7	2.0	3.2
9	3.3	4.3	4.5	4.7	2.7	3.8	1.2	1.9	1.0	1.6	1.6	3.0
10	3.2	4.0	4.4	4.5	2.6	2.7	1.1	1.5	1.0	1.6	1.6	2.9
11	3.1	3.8	4.3	4.0	2.6	2.2	1.0	1.4	1.0	1.6	1.5	2.7
12	3.0	3.7	4.2	3.8	2.6	2.0	2.5	1.3	1.8	2.2	1.5	2.4
13	2.9	3.6	4.0	3.8	2.5	1.9	2.0	1.0	2.9	2.5	1.5	2.2
14	2.8	3.6	4.4	3.7	2.5	1.8	1.9	1.0	3.3	2.6	1.4	2.2
15	2.7	3.6	4.8	3.7	2.5	2.2	1.8	2.0	2.9	2.1	1.4	2.1
16	2.8	3.8	5.8	3.6	2.6	2.7	1.7	1.9	2.4	1.9	1.6	2.7
17	2.8	3.8	6.8	3.6	2.5	2.5	1.6	1.2	2.0	1.7	1.6	3.0
18	2.7	3.8	6.7	4.3	2.8	2.3	1.4	1.1	1.7	1.5	2.7	3.5
19	2.8	3.7	6.0	4.2	2.7	2.2	1.4	1.3	2.2	1.7	3.2	2.9
20	2.8	3.7	5.7	4.0	2.6	2.1	1.1	1.2	2.8	1.8	2.9	2.4
21	3.0	3.8	5.1	3.9	2.4	2.9	1.1	1.1	2.9	1.6	2.2	3.0
22	3.4	3.8	4.8	3.8	2.6	2.9	1.1	1.0	2.4	1.6	2.0	2.9
23	3.5	3.8	4.5	3.7	2.4	2.8	1.1	1.0	2.1	1.6	1.7	2.8
24	3.0	4.2	4.5	3.7	2.4	2.8	1.1	1.0	1.6	1.6	1.7	2.7
25	3.0	4.3	4.5	3.5	2.3	2.8	1.0	1.0	3.0	1.6	3.3	2.6
26	3.0	4.4	4.3	3.4	2.2	2.8	1.0	1.0	3.0	1.7	4.1	2.4
27	3.0	5.0	3.9	3.0	2.0	2.8	1.0	1.0	3.4	2.1	3.3	2.4
28	3.0	12.8	4.3	3.0	2.0	2.8	2.3	1.2	2.8	2.0	3.0	2.9
29	3.2	5.5	3.0	2.0	1.2	3.5	1.9	2.6	1.9	2.4	2.9
30	3.6	7.4	3.0	2.0	1.2	3.7	2.4	2.8	1.8	2.4	3.0
31	4.0	6.9	2.0	2.8	1.5	1.7	3.0
1903												
1	3.2	2.5	4.9	6.3	3.0	7.0	2.8	1.9	1.2	1.5	1.7	1.9
2	3.0	2.5	5.5	5.7	3.0	6.7	2.6	2.5	1.2	1.4	1.7	1.9
3	2.9	2.7	5.2	5.0	3.0	5.7	2.7	4.5	1.2	1.4	1.8	1.8
4	3.0	3.0	4.7	4.8	5.7	5.2	2.8	3.8	1.2	1.6	2.3	1.8
5	2.9	3.6	4.5	4.7	5.0	5.4	2.7	3.0	1.4	1.6	2.7	1.8
6	2.8	4.0	4.2	4.5	4.5	6.1	2.6	2.7	1.8	1.5	3.0	2.2
7	2.7	4.4	4.2	4.3	4.0	6.0	4.5	2.0	1.2	1.5	2.5	2.1
8	2.6	3.0	4.1	4.8	3.4	5.5	5.5	2.4	1.2	1.5	2.0	2.0
9	2.5	7.5	4.0	6.1	3.5	4.5	4.4	1.8	1.2	1.5	1.9	2.1
10	2.3	7.0	4.5	5.9	3.3	4.0	3.7	1.7	1.2	1.5	1.9	2.5
11	2.8	6.5	4.4	5.6	3.1	3.8	4.8	1.6	1.1	1.4	1.9	2.2
12	3.0	6.5	4.3	4.5	3.0	3.5	4.0	1.6	1.1	1.4	1.9	2.0
13	3.3	6.6	4.7	4.4	2.9	3.3	6.5	1.6	1.0	1.4	1.9	2.1
14	2.9	6.2	5.1	4.7	3.3	3.0	6.3	2.2	1.2	1.4	1.9	2.0
15	2.8	5.3	4.7	4.5	4.0	2.9	5.1	3.0	3.3	1.4	1.9	2.5
16	2.7	4.9	4.6	4.3	4.2	2.8	4.2	4.0	4.4	1.4	1.9	2.3
17	2.6	6.5	4.5	4.0	4.0	2.7	3.2	4.5	4.7	1.4	2.5	2.2
18	2.5	6.7	4.0	3.8	3.5	2.6	2.9	3.5	4.0	2.0	2.2	2.0
19	2.4	6.6	3.8	3.8	3.1	2.4	2.7	2.4	3.7	1.9	2.2	1.8
20	2.3	5.4	3.7	3.7	2.9	2.4	2.5	2.0	2.4	1.3	2.0	2.0
21	2.2	4.8	3.8	3.6	2.8	3.0	2.3	2.4	2.2	1.7	2.0	2.2
22	2.2	4.6	5.5	3.4	2.7	2.8	2.1	3.6	2.0	1.6	2.0	2.5
23	2.2	4.3	7.5	3.1	2.6	2.6	2.0	3.0	1.9	1.6	2.0	2.2
24	2.4	4.0	8.6	2.0	2.5	2.4	1.9	2.5	1.8	1.6	2.0	2.1
25	2.5	3.8	7.4	2.0	2.5	2.3	1.9	2.0	1.7	1.5	2.0	2.0
26	2.5	3.7	6.1	2.9	2.5	2.2	2.9	1.7	1.7	1.5	2.0	2.0
27	2.3	3.6	5.3	3.3	3.3	3.6	2.7	1.6	1.8	1.5	1.9	2.5
28	3.1	4.3	4.9	3.5	3.5	3.6	2.6	1.5	1.7	1.6	1.9	2.4
29	3.0	4.2	3.3	3.1	3.2	2.4	1.4	1.6	1.6	1.9	2.8
30	2.9	5.7	3.1	2.8	3.0	2.0	1.3	1.5	1.5	1.9	2.2
31	2.6	6.2	2.7	2.0	1.3	1.5	2.1
1904												
1	2.0	2.6	2.9	2.4	2.1	2.9	1.25	.8	1.15	.25	.55	1.1
2	2.9	2.5	2.8	2.4	1.9	2.4	1.15	1.2	1.0	.45	.65	1.4
3	2.0	2.4	2.9	2.5	1.8	2.3	.8	3.65	.8	.3	.8	1.5
4	2.2	2.3	3.0	2.4	1.7	1.5	.6	1.85	1.3	.2	1.3	1.7
5	2.4	2.2	2.9	2.0	1.7	1.3	.6	1.45	2.5	.2	1.45	2.5
6	2.3	2.2	2.6	2.0	1.7	1.5	.5	1.3	1.7	.2	1.55	3.4
7	2.2	2.5	4.0	2.5	1.5	1.4	.4	2.8	1.15	.35	1.35	3.45
8	2.1	2.7	4.5	3.0	2.5	1.5	.75	3.1	1.0	.3	.95	3.4
9	2.2	2.4	4.9	3.7	2.2	1.5	1.75	4.4	1.1	.35	.95	2.4
10	2.1	3.5	4.6	2.9	2.6	1.5	1.7	4.3	1.0	.3	.9	2.3

ALTAMAHA DRAINAGE BASIN, STREAM FLOW

Daily gage height, in feet, of Alcovy River near Covington—Continued.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1904												
11.....	2.3	5.5	4.0	2.5	2.9	1.3	1.65	5.7	1.0	0.3	0.85	2.2
12.....	2.5	5.0	3.3	2.3	2.0	1.2	1.6	5.9	.75	.3	.85	2.25
13.....	2.4	4.5	3.0	2.1	1.9	1.1	1.0	4.75	.3	.25	1.5	2.0
14.....	2.6	4.1	3.0	2.0	1.4	1.0	1.2	3.3	.75	.25	1.45	1.95
15.....	2.3	3.8	3.5	2.0	1.4	.9	.9	3.1	.75	.25	1.3	1.7
16.....	2.1	3.6	3.6	2.0	1.5	.8	.75	4.9	.7	.25	1.35	1.7
17.....	2.5	3.2	3.2	2.0	1.4	.6	.7	4.75	.5	.25	1.2	1.8
18.....	2.7	3.0	3.0	2.0	1.5	.6	.5	2.3	.65	.25	1.1	1.7
19.....	2.6	3.4	2.8	2.0	1.3	.5	.6	2.0	.6	.25	1.05	1.7
20.....	2.4	3.7	2.5	2.0	1.3	.4	.7	1.8	.5	.3	1.1	1.6
21.....	3.4	4.2	2.5	2.1	1.3	.4	.9	1.7	.45	.25	1.15	1.6
22.....	3.5	4.7	2.9	2.1	1.3	.7	.5	1.4	.4	.25	1.1	1.5
23.....	4.5	5.0	3.1	2.0	1.2	.6	.7	1.2	.3	.25	1.6	1.5
24.....	4.1	4.7	3.1	2.1	1.2	.5	.8	1.2	.3	.25	1.8	1.5
25.....	3.5	4.4	2.9	2.0	1.1	.5	.7	1.2	.5	.9	2.15	1.75
26.....	3.0	3.9	2.8	2.2	1.1	.5	.6	1.1	.45	.85	2.0	1.85
27.....	2.9	3.4	2.8	2.2	1.1	.45	.5	1.15	.4	.75	1.5	1.8
28.....	2.7	3.2	2.7	2.2	1.1	.4	.4	1.7	.35	.65	1.3	2.1
29.....	2.6	3.0	2.5	2.0	1.0	.75	.6	1.4	.3	.65	1.2	2.6
30.....	2.5		2.3	1.9	1.0	1.3	.5	1.25	.3	.65	1.2	2.9
31.....	2.9		2.3	2.0	2.0		.7	1.1		.65		2.75

Rating tables for Alcovy River near Covington.

APRIL 30 TO DECEMBER 31, 1901 ^a

Gage height	Dis-charge						
<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>
1.40	111	3.00	308	4.60	612	7.40	1,144
1.50	118	3.10	327	4.70	631	7.60	1,152
1.60	126	3.20	346	4.80	650	7.80	1,220
1.70	134	3.30	365	4.90	669	8.00	1,258
1.80	143	3.40	384	5.00	688	8.20	1,296
1.90	152	3.50	403	5.20	726	8.40	1,324
2.00	162	3.60	422	5.40	764	8.60	1,372
2.10	173	3.70	441	5.60	802	8.80	1,410
2.20	185	3.80	460	5.80	840	9.00	1,448
2.30	198	3.90	479	6.00	878	10.00	1,638
2.40	212	4.00	498	6.20	916	11.00	1,828
2.50	226	4.10	517	6.40	954	12.00	2,018
2.60	241	4.20	536	6.60	992	13.00	2,208
2.70	257	4.30	555	6.80	1,030		
2.80	273	4.40	574	7.00	1,068		
2.90	290	4.50	593	7.20	1,106		

JANUARY 1 TO DECEMBER 31, 1902 ^b

1.00	108	1.60	152	2.10	197	2.60	252
1.10	114	1.70	160	2.20	207	2.70	265
1.20	121	1.80	169	2.30	218	2.80	278
1.30	128	1.90	178	2.40	229	2.90	292
1.40	136	2.00	187	2.50	240	3.00	305
1.50	144						

^a Above gage height 3.0 feet the rating curve is a tangent, the difference being 19 per tenth.

^b Above gage height 3.0 feet the above table is the same as the 1901 table.

Rating tables for Alcovy River near Covington—Continued.

JANUARY 1 TO DECEMBER 31, 1903^a

Gage height	Dis-charge						
<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>
1.00	83	2.30	206	3.50	392	4.70	630
1.10	94	2.40	218	3.60	410	4.80	650
1.20	100	2.50	232	3.70	430	4.90	670
1.30	107	2.60	246	3.80	450	5.00	690
1.40	114	2.70	260	3.90	470	5.20	730
1.50	122	2.80	274	4.00	490	5.40	770
1.60	130	2.90	290	4.10	510	5.60	810
1.70	140	3.00	306	4.20	530	5.80	850
1.80	150	3.10	322	4.30	550	6.00	890
1.90	160	3.20	338	4.40	570	7.00	1,090
2.00	170	3.30	356	4.50	590	8.00	1,290
2.10	182	3.40	374	4.60	610	9.00	1,490
2.20	194						

JANUARY 1 TO DECEMBER 31, 1904

0.20	88	1.50	135	2.70	259	3.90	460
.30	45	1.60	144	2.80	272	4.00	480
.40	52	1.70	153	2.90	286	4.20	522
.50	59	1.80	162	3.00	300	4.40	564
.60	66	1.90	171	3.10	315	4.60	606
.70	73	2.00	180	3.20	331	4.80	648
.80	83	2.10	190	3.30	347	5.00	690
.90	87	2.20	201	3.40	364	5.20	734
1.00	95	2.30	212	3.50	382	5.4	778
1.10	103	2.40	223	3.60	401	5.60	822
1.20	111	2.50	234	3.70	420	5.80	866
1.30	119	2.60	246	3.80	440	6.00	910
1.40	127						

^a At about 6 feet gage height the right bank overflows for a width of about 1,000 feet. Bank is covered by a thick swamp growth, so the velocity is probably small. Above gage height 3.6 feet the rating curve is a tangent, the difference being 20 per tenth.

Estimated monthly discharge of Alcovy River near Covington.

[Drainage area, 228 square miles.]

Month	Discharge in second-feet			Run-off	
	Maximum	Minimum	Mean	Sec.-ft. per sq. mile	Depth in inches
1901					
May.....	593	162	271	1.19	1.37
June.....	821	198	442	1.94	2.16
July.....	840	143	377	1.65	1.90
August.....	1,030	111	582	2.55	2.94
September.....	935	152	361	1.58	1.76
October.....	555	152	228	1.00	1.15
November.....	273	162	183	.80	.89
December.....	1,144	162	393	1.72	1.98
1902					
January.....	973	265	391	1.72	1.93
February.....	2,170	422	675	2.96	3.03
March.....	1,543	479	754	3.31	3.82
April.....	302	308	496	2.18	2.43
May.....	403	137	251	1.10	1.27
June.....	460	121	195	.86	.96
July.....	441	103	163	.71	.82
August.....	688	103	193	.85	.98
September.....	334	103	204	.89	.99
October.....	265	144	131	.79	.91
November.....	517	136	212	.93	1.04
December.....	745	197	344	1.51	1.74
The year.....	2,170	103	383	1.48	20.02

Estimated monthly discharge of Alcovy River near Covington—Continued.

Month	Discharge in second feet			Run-off	
	Maximum	Minimum	Mean	Sec. ft. per sq. mile	Depth in inches
1903					
January	356	194	262	1.15	1.33
February	1,290	232	691	3.03	3.16
March	1,410	430	689	3.02	3.48
April	350	170	535	2.35	2.62
May	830	232	371	1.63	1.33
June	1,090	194	468	2.05	2.29
July	990	160	375	1.64	1.59
August	590	107	244	1.07	1.23
September	630	88	186	.82	.91
October	170	114	126	.55	.63
November	306	140	178	.79	.88
December	232	150	185	.81	.93
The year	1,410	88	359	1.58	21.23
1904					
January	585	130	264	1.16	1.34
February	300	201	406	1.78	1.92
March	669	212	331	1.45	1.67
April	420	171	209	.917	1.02
May	286	95	147	.645	.744
June	286	52	105	.460	.513
July	157	52	84.2	.369	.425
August	883	30	230	1.27	1.46
September	234	45	80.8	.354	.395
October	87	38	50.6	.222	.256
November	195	63	115	.504	.562
December	373	103	193	.846	.975
The year	888	38	190	.831	11.28

ALCOVY RIVER NEAR STEWART

This station was established September 16, 1905, by M. R. Hall. It is located at a wooden wagon bridge known as "Waters Bridge," about 15 miles south of Covington, Ga., and 5 miles from Stewart, below the mouth of Bear Creek and about 4 miles from the mouth of the river. The station is important because it is a short distance below a large amount of fall at the old Newton factory site.

The channel curves to the left bank about 45° in 300 feet above the station, and is straight for 1,000 feet below the station. The right bank is high and will not overflow. The left bank may overflow about 200 feet at high floods. The channel above and below appears to contain much sand, which is shifting, though the bed is mostly rock in the part under the right span of the bridge, to which nearly all of the flow is confined at lowest stage of water.

Discharge measurements are made from the bridge of three spans of about 50 feet each.

A vertical staff gage is attached to a birch tree at the right edge of the water, 12 feet upstream from the bridge. It is read once each day by A. J. White. The bench mark is a cross and circles cut on a solid rock outcrop at the right edge of the water, just under the

WATER POWERS OF GEORGIA

downstream side of the bridge; elevation, 2.36 feet above the datum of the gage.

Discharge measurement of Alcovy River near Stewart.

Date	Gage height	Discharge	Date	Gage height	Discharge
1905			1906		
	<i>Feet</i>	<i>Sec.-ft.</i>		<i>Feet</i>	<i>Sec.-ft.</i>
September 16.....	1.54	48	January 13.....	4.82	600
September 16.....	1.55	48	January 13.....	4.22	483
November 24.....	2.03	106	April 13.....	2.39	242
November 24.....	2.05	105	June 28.....	5.64	810
November 24.....	4.80	580	August 16.....	3.02	242
			October 31.....		


Daily gage height, in feet, of Alcovy River near Stewart.

Day	Sept.	Oct.	Nov.	Dec.	Day	Sept.	Oct.	Nov.	Dec.
1905					1905				
1.....		1.65	1.95	2.05	17.....	1.75	1.65	2.1	4.2
2.....		1.6	1.8	2.05	18.....	1.7	1.7	2.1	4.0
3.....		1.6	1.8	6.25	19.....	1.7	1.7	2.1	3.8
4.....		1.7	1.6	6.2	20.....	1.65	1.7	2.1	5.8
5.....		1.75	1.65	7.5	21.....	1.6	1.7	2.0	7.5
6.....		2.0	1.7	7.0	22.....	1.6	1.7	2.05	7.0
7.....		2.05	2.05	6.0	23.....	1.6	1.7	2.0	7.8
8.....		1.75	1.75	5.3	24.....	1.55	1.6	2.0	7.0
9.....		1.75	1.8	6.3	25.....	1.55	1.65	2.0	6.0
10.....		1.65	2.1	5.2	26.....	1.5	1.8	2.1	5.5
11.....		2.0	3.3	5.2	27.....	1.5	1.85	2.2	4.8
12.....		1.8	2.3	5.8	28.....	1.5	1.85	2.2	4.4
13.....		1.95	2.3	6.0	29.....	1.45	1.95	2.05	4.4
14.....		2.05	2.7	5.2	30.....	1.5	1.9	2.15	4.2
15.....		2.0	2.45	4.8	31.....		1.9		4.2
16.....	1.55	1.95	2.25	4.2					


Daily gage height, in feet, of Alcovy River near Stewart.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1906												
1.....	4.05	4.5	3.2	5.5	2.95	2.6	2.75	6.0	6.5	4.3	2.9	3.0
2.....	3.9	4.8	3.2	5.1	3.1	2.5	2.65	6.0	4.5	10.4	2.9	3.0
3.....	7.0	4.4	3.2	4.0	3.05	2.75	2.3	5.3	4.0	8.5	2.85	3.0
4.....	8.0	4.2	3.5	4.2	3.0	4.0	2.75	4.5	3.1	9.0	3.0	3.0
5.....	7.0	4.1	3.6	4.1	3.0	3.1	2.85	4.0	2.8	8.5	3.0	3.0
6.....	8.0	4.0	3.5	4.0	3.1	2.75	2.9	4.2	2.75	9.0	3.0	3.0
7.....	7.5	4.0	3.5	4.0	3.3	2.7	2.7	4.0	2.7	6.5	3.0	3.0
8.....	7.0	3.9	4.4	3.9	3.6	2.6	2.9	3.8	2.7	5.8	3.0	3.25
9.....	5.8	4.0	4.9	3.9	3.8	2.6	6.6	3.5	2.6	5.3	3.0	3.25
10.....	4.7	4.0	5.0	3.85	3.65	2.5	7.2	3.1	2.5	4.8	3.0	3.25
11.....	4.6	3.9	5.5	4.3	3.35	2.5	5.0	3.0	2.6	4.0	3.0	3.5
12.....	4.5	3.9	5.5	4.5	3.1	2.6	4.1	2.9	2.5	3.8	3.15	3.75
13.....	4.5	3.85	4.8	4.3	3.0	10.5	3.4	8.0	3.3	3.6	3.2	3.7
14.....	4.4	3.8	4.0	3.9	2.9	10.5	3.5	5.0	3.25	3.5	3.2	3.7
15.....	4.4	3.8	6.5	3.75	2.8	10.0	3.5	6.2	3.0	3.4	3.3	3.7
16.....	4.6	3.7	6.2	3.7	2.75	11.0	3.7	6.0	3.1	3.3	3.35	3.4
17.....	4.5	3.7	6.8	3.6	2.65	11.5	4.4	5.0	2.9	3.3	3.4	3.4
18.....	4.2	3.5	7.0	3.55	2.6	11.0	6.8	4.0	6.5	3.4	4.8	3.6
19.....	4.1	3.45	8.0	3.5	2.6	8.5	7.0	3.5	6.0	3.5	4.4	3.6
20.....	3.9	3.4	8.0	3.4	2.55	6.5	6.5	3.0	5.5	3.6	4.0	4.0
21.....	4.0	3.85	9.5	3.3	2.5	5.0	5.8	2.9	4.5	3.5	4.0	4.0
22.....	4.9	3.6	9.0	3.3	2.65	4.0	5.0	2.9	6.0	3.55	3.9	4.3
23.....	7.5	3.5	8.0	3.2	2.9	3.75	7.0	3.4	8.0	3.4	3.65	4.3
24.....	7.0	3.45	6.5	3.1	2.8	3.45	5.0	3.25	6.8	3.35	3.4	4.1
25.....	6.5	3.45	5.5	3.1	2.6	3.1	4.8	3.1	4.5	3.3	3.3	a
26.....	6.5	3.4	5.0	3.0	2.8	2.9	5.5	3.7	4.6	3.2	3.2
27.....	6.2	3.35	4.9	3.0	3.0	2.9	4.5	4.0	6.0	3.1	3.2
28.....	6.1	3.25	5.5	3.0	3.25	2.9	3.5	3.0	4.5	3.1	3.15
29.....	6.0	4.9	3.0	3.9	2.8	5.5	3.0	4.4	3.1	3.1
30.....	5.5	5.4	2.95	3.25	2.8	5.0	3.0	4.4	3.0	3.05
31.....	5.0	6.0	2.8	4.8	3.6	3.0

a No records after December 24,



THE POWER PLANT OF THE ATLANTA WATER AND ELECTRIC POWER COMPANY, LOCATED AT MORGAN FALLS NEAR ROSWELL 16 MILES FROM ATLANTA. THE POWER WHICH VARIES FROM 2,250 TO 4,500 HORSE POWER, IS TRANSMITTED TO ATLANTA WHERE IT IS USED FOR OPERATING ELECTRIC CARS, ELECTRIC LIGHTING, ETC.



Rating table for Alcovy River near Stewart from September 16 to December 31, 1905.

Gage height	Dis-charge						
<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>
1.40	34	2.70	192	4.00	412	5.60	796
1.50	44	2.80	206	4.10	432	5.80	852
1.6	55	2.90	220	4.20	452	6.00	910
1.70	66	3.00	236	4.30	474	6.20	970
1.80	77	3.10	252	4.40	496	6.40	1,030
1.90	88	3.20	268	4.50	518	6.60	1,090
2.00	100	3.30	284	4.60	540	6.80	1,150
2.10	112	3.40	300	4.70	564	7.00	1,210
2.20	124	3.50	318	4.80	588	7.20	1,274
2.30	136	3.60	336	4.90	612	7.40	1,338
2.40	150	3.70	354	5.0	636	7.60	1,402
2.50	164	3.80	372	5.20	688	7.80	1,466
2.60	178	3.90	392	5.40	740		

Rating table for Alcovy River near Stewart, for 1906.

Gage height	Dis-charge						
<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>
2.50	170	3.50	334	4.50	530	6.00	910
2.60	185	3.60	352	4.60	552	6.20	970
2.70	200	3.70	370	4.70	585	6.40	1,030
2.80	216	3.80	388	4.80	608	6.60	1,090
2.90	232	3.90	406	4.90	631	6.80	1,150
3.00	243	4.00	425	5.00	645	7.00	1,210
3.10	255	4.10	445	5.20	698	7.20	1,274
3.20	282	4.20	465	5.40	743	7.40	1,338
3.30	299	4.30	487	5.60	796	7.60	1,402
3.40	316	4.40	508	5.80	852	7.80	1,466

NOTE.—The above table is based on ten discharge measurements made during 1905-6 and is fairly well defined below gage height 5.7 feet. Above gage height 7.0 feet the rating curve is a tangent, the difference being 32 per tenth.

Estimated monthly discharge of Alcovy River near Stewart.

[Drainage area, 395 square miles.]

Month	Discharge in second-feet			Run-off	
	Maximum	Minimum	Mean	Sec.-ft. per sq. mile	Depth in inches
1905					
September 16-30.....	72	38	52.9	0.134	0.075
October.....	106	55	76.5	.194	.224
November.....	284	55	117	.296	.330
December.....	1,466	106	766	1.94	2.24
1906					
January.....	1,530	406	818	2.07	2.39
February.....	608	290	393	.995	1.04
March.....	2,010	282	824	2.09	2.41
April.....	768	240	333	.970	1.08
May.....	406	170	252	.638	.74
June.....	2,650	170	764	1.93	2.15
July.....	1,270	192	532	1.47	1.70
August.....	1,530	232	481	1.22	1.41
September.....	1,530	170	518	1.31	1.46
October.....	2,300	248	635	1.71	1.86
November.....	608	224	305	.772	.86
December 1-24.....	487	248	335	.848	.76
The period.....	2,650	170	524	1.32	17.86

WATER POWERS OF GEORGIA

TOWALIGA RIVER NEAR JULIETTE.

The drainage basin of this stream occupies a small area in central Georgia, its headwater tributary adjoining those of Flint River on the west, and small creeks draining into the Ocmulgee on the east. The river is a tributary of Ocmulgee River, entering it 25 miles above Macon. The area drained is a rolling country and extensively cultivated. A gaging station was established by B. M. Hall near its mouth, at the Southern Railway bridge, $2\frac{1}{2}$ miles north of Juliette on May 5, 1899, but observations of gage heights were not started until November 2. The station was discontinued December 31, 1901.

At low stages measurements were made at the wagon bridge a half mile above the railroad bridge. W. L. Jackson, a farmer living a half mile from the bridge, was the observer. His address is Berner, Ga. The rod is nailed to the timber crib at the base of the left-bank pier of the iron single-span bridge. Bench mark No. 1 is at the top of the downstream iron girder under the cross-ties 40 feet from the left end of the bridge; elevation, 37.30 feet above gage datum. Bench mark No. 2 is at the top of the rail at the same point; elevation, 38.80 feet above gage datum.

Discharge measurements of Towaliga River near Juliette

Date	Gage height	Dis-charge	Date	Gage height	Dis-charge
1899			1901		
	<i>Feet</i>	<i>Sec.-ft.</i>		<i>Feet</i>	<i>Sec.-ft.</i>
May 5.....	3.45	581	January 14.....	3.75	563.
May 17.....	2.10	255	February 22.....	2.70	362'
November 2.....	1.50	167	May 8.....	2.22	301
November 2.....	1.50	163	July 27.....	1.48	172'
December 16.....	1.90	184	September 13.....	1.55	163
			September 22.....	2.63	312'
			November 5.....	1.65	185'
1900					
February 17.....	6.35	1,025			
April 3.....	2.60	348			
December 8.....	2.75	468			

Daily gage height, in feet, of Towaliga River near Juliette

Day	Nov.	Dec.	Day	Nov.	Dec.	Day	Nov.	Dec.	Day	Nov.	Dec.
1899			1899			1899			1899		
1.....		1.7	9.....	1.2	1.6	17.....	1.6	1.8	25.....	1.2	3.8
2.....	1.2	1.65	10.....	1.1	1.55	18.....	1.3	1.7	26.....	3.35	2.5
3.....	1.2	1.65	11.....	1.2	1.5	19.....	1.3	1.7	27.....	3.2	2.1
4.....	1.1	1.75	12.....	1.1	3.7	20.....	1.2	1.7	28.....	2.2	1.1
5.....	1.1	1.75	13.....	1.1	3.6	21.....	1.3	1.7	29.....	1.95	2.0
6.....	1.1	1.65	14.....	1.1	2.5	22.....	1.2	1.5	30.....	1.8	1.9
7.....	1.1	1.55	15.....	1.1	2.0	23.....	1.3	1.6	31.....		1.9
8.....	1.1	1.5	16.....	1.7	1.9	24.....	1.2	4.0			

ALTAMAHA DRAINAGE BASIN, STREAM FLOW

Daily gage height, in feet, of Towaliga River near Juliette—Continued.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1900												
1.....	2.2	2.0	2.9	1.8	3.1	2.0	4.0	2.2	4.5	0.9	1.8	1.9
2.....	2.2	1.9	4.3	1.6	3.6	2.1	4.0	2.2	1.5	1.0	2.0	1.9
3.....	2.0	1.9	3.1	2.6	4.9	2.1	3.5	1.7	1.9	1.4	8.2	4.7
4.....	2.0	2.1	2.8	2.8	3.3	3.7	3.5	1.7	1.6	2.1	7.0	4.0
5.....	1.9	2.7	2.4	2.6	3.1	2.9	4.1	2.3	1.5	3.4	6.4	3.4
6.....	1.9	2.6	2.4	2.5	2.6	2.5	3.5	1.7	1.3	3.6	5.5	3.0
7.....	1.9	2.3	1.4	2.7	2.6	3.2	3.3	1.5	1.2	3.9	2.2	3.0
8.....	1.9	1.4	2.9	2.6	2.5	5.2	4.2	1.3	1.0	3.8	2.1	2.4
9.....	1.9	2.4	3.4	2.5	2.5	2.4	4.0	1.2	1.0	1.7	2.1	2.4
10.....	1.9	7.3	2.8	2.5	2.5	2.6	4.0	1.2	1.0	1.5	2.0	2.3
11.....	1.9	11.8	2.3	3.4	2.4	2.9	3.8	1.2	1.0	1.5	2.0	2.0
12.....	2.7	14.1	1.3	5.7	2.4	2.3	3.7	1.1	1.0	1.6	1.9	2.0
13.....	2.3	14.8	2.0	4.0	2.4	2.3	4.4	1.3	1.0	1.7	1.9	2.3
14.....	2.3	16.5	1.1	2.9	2.3	2.4	3.7	1.0	2.4	1.7	1.9	9.0
15.....	2.2	16.3	1.0	2.3	2.3	2.3	2.2	1.7	8.0	1.5	1.9	7.4
16.....	2.1	8.3	4.0	2.7	2.2	2.9	2.0	1.5	6.4	1.4	1.8	4.0
17.....	2.0	4.8	3.1	2.7	2.2	3.3	1.8	1.3	4.2	1.3	1.8	3.6
18.....	2.1	3.8	2.3	12.8	2.2	3.8	1.0	1.9	3.1	1.1	1.8	3.0
19.....	2.8	3.3	1.1	17.8	2.2	4.1	1.0	1.3	2.9	1.1	2.0	2.6
20.....	3.2	3.2	3.3	14.8	2.2	5.2	1.0	1.2	2.0	1.1	1.9	6.4
21.....	2.9	2.4	3.1	7.8	2.2	2.2	1.0	1.1	1.4	1.1	1.8	7.5
22.....	2.5	4.0	2.3	12.8	2.1	1.9	1.5	0.8	1.3	1.1	1.8	5.5
23.....	2.3	3.3	2.2	5.5	2.1	2.2	1.5	0.9	1.2	2.4	1.9	3.5
24.....	2.2	2.9	2.7	4.8	2.8	9.8	2.2	2.1	1.3	3.6	1.9	3.5
25.....	2.2	2.4	3.4	4.1	2.9	10.8	1.9	3.0	1.3	3.5	2.5	2.8
26.....	2.1	3.0	4.0	3.6	2.5	8.8	1.6	4.3	1.2	2.9	4.4	2.7
27.....	2.0	2.9	3.6	3.4	2.4	6.8	2.4	2.6	1.2	2.1	3.1	2.5
28.....	2.1	2.4	2.8	3.2	2.4	6.6	2.5	1.5	1.1	1.5	2.4	2.5
29.....	2.0	2.4	3.3	2.2	6.2	4.0	1.2	1.1	1.3	2.3	2.3
30.....	2.0	2.4	3.2	2.1	4.2	5.1	1.6	0.8	1.2	1.9	3.4
31.....	2.1	2.1	2.1	3.4	5.3	1.2	4.3
1901												
1.....	5.1	2.8	2.7	8.8	2.5	5.6	2.0	2.0	3.4	2.6	1.5	1.7
2.....	5.9	3.0	2.7	11.7	2.4	3.7	3.0	3.0	2.5	2.6	1.5	1.7
3.....	7.2	3.4	2.6	13.9	2.4	2.8	2.2	1.7	2.1	3.0	1.6	1.7
4.....	5.4	8.3	2.5	12.0	2.3	2.5	2.0	1.6	2.0	2.2	1.6	2.0
5.....	4.8	8.8	2.5	5.6	2.3	2.3	2.0	1.5	1.8	2.0	1.5	2.5
6.....	4.3	4.6	2.5	4.7	2.3	2.3	1.8	1.4	1.5	2.0	1.5	2.4
7.....	4.1	3.5	2.4	4.2	2.2	5.0	2.2	2.6	1.5	2.0	1.5	2.0
8.....	4.3	5.2	2.4	3.9	2.1	3.8	1.8	2.4	1.5	1.9	1.5	1.8
9.....	3.9	5.9	2.4	3.5	2.1	2.4	9.2	1.9	1.4	1.8	1.5	1.8
10.....	3.9	6.0	4.1	3.4	2.1	2.2	2.8	1.8	1.4	1.8	1.5	2.0
11.....	3.5	5.8	4.1	3.3	2.1	2.2	2.4	4.6	1.5	1.8	1.5	2.0
12.....	5.1	4.6	2.9	3.2	2.1	2.1	2.2	3.4	1.5	2.0	1.4	2.0
13.....	5.8	3.6	3.4	4.3	2.1	3.6	2.0	3.1	1.5	1.7	1.4	2.0
14.....	4.3	3.3	3.1	4.6	2.1	4.0	2.0	2.4	1.8	1.7	1.4	2.0
15.....	2.9	3.0	3.1	4.0	2.1	5.0	2.0	4.3	1.6	1.7	1.4	7.0
16.....	2.5	3.0	2.6	3.6	2.1	5.6	2.1	6.1	1.5	1.7	1.4	6.4
17.....	7.1	2.9	2.9	3.2	2.1	4.5	2.1	11.2	12.2	1.7	1.5	5.3
18.....	5.8	2.8	2.8	3.1	2.1	3.3	2.0	4.2	7.6	1.7	1.4	2.8
19.....	3.6	2.7	2.7	4.6	2.1	2.5	9.1	3.1	3.6	1.7	2.0	2.5
20.....	3.3	2.7	2.5	4.0	2.6	2.3	3.5	4.2	3.0	1.6	2.4	2.3
21.....	3.1	2.7	2.9	3.4	3.5	2.2	1.8	3.1	3.0	1.5	2.3	2.1
22.....	3.0	2.6	2.6	3.1	7.6	2.2	1.6	2.6	2.7	1.5	2.1	2.3
23.....	2.8	2.8	2.4	2.9	7.1	3.0	1.5	5.9	2.4	1.5	1.7	2.2
24.....	2.8	3.0	2.9	2.9	3.5	4.5	2.6	9.0	2.3	1.5	1.7	2.6
25.....	3.0	3.0	3.1	2.8	3.4	3.4	2.2	4.6	2.1	1.5	1.7	2.3
26.....	2.8	3.0	6.3	2.8	2.8	2.2	1.5	4.5	1.8	1.5	1.7	2.1
27.....	3.0	3.0	11.6	2.8	2.5	2.3	1.4	3.4	1.8	1.5	1.7	3.1
28.....	2.8	2.7	5.3	2.7	2.5	2.3	1.3	2.4	2.0	1.5	1.7	6.4
29.....	3.0	4.0	2.7	2.4	2.1	1.8	4.5	3.4	1.5	1.7	11.0
30.....	3.0	3.6	2.7	2.3	2.0	2.4	3.1	3.0	1.5	1.7	8.5
31.....	2.8	9.2	4.8	2.0	2.6	1.5	6.4

WATER POWERS OF GEORGIA

Rating table for Towaliga River near Juliette from November 2, 1899, to December 31, 1901.^a

Gage height	Dis-charge						
<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>
1.00	120	2.20	273	4.40	669	10.00	1,677
1.10	127	2.40	309	4.60	705	11.00	1,857
1.20	135	2.60	345	4.80	741	12.00	2,037
1.30	144	2.80	381	5.00	777	13.00	2,217
1.40	154	3.00	417	5.50	867	14.00	2,397
1.50	165	3.20	453	6.00	957	15.00	2,577
1.60	177	3.40	489	6.50	1,047	16.00	2,757
1.70	190	3.60	525	7.00	1,137	17.00	2,937
1.80	204	3.80	561	7.50	1,227	18.00	3,117
1.90	220	4.00	597	8.00	1,317		
2.00	237	4.20	633	9.00	1,497		

^a Above gage height 2.0 feet the rating curve is a tangent, the difference being 18 per tenth.

Estimated monthly discharge of Towaliga River near Juliette.

[Drainage area, 350 square miles.]

Month	Discharge in second-feet			Run-off	
	Maximum	Minimum	Mean	Sec.-ft. per sq. mile	Depth in inches
1899					
November.....	480	127	170	0.49	0.53
December.....	597	127	248	.71	.82
1900					
January.....	453	220	274	.78	.90
February.....	2,847	154	1,449	4.14	4.31
March.....	597	120	354	1.01	1.16
April.....	3,081	177	751	2.15	2.40
May.....	759	255	422	1.21	1.40
June.....	1,821	220	595	1.70	1.90
July.....	795	120	408	1.17	1.35
August.....	867	109	222	.63	.73
September.....	1,317	109	271	.77	.86
October.....	579	114	243	.69	.80
November.....	1,353	144	357	1.02	1.14
December.....	1,497	220	526	1.50	1.73
The year.....	3,081	109	489	1.40	18.68
1901					
January.....	1,173	327	602	1.72	1.98
February.....	1,461	345	576	1.65	1.72
March.....	1,965	309	520	1.49	1.72
April.....	2,379	363	707	2.02	2.25
May.....	1,245	255	380	1.09	1.26
June.....	885	237	440	1.26	1.41
July.....	1,533	144	337	.96	1.11
August.....	1,393	154	531	1.52	1.75
September.....	1,245	154	360	1.03	1.15
October.....	417	165	209	.60	.69
November.....	309	154	185	.53	.59
December.....	1,357	190	475	1.36	1.57
The year.....	2,379	144	444	1.27	17.20

MIDDLE OCONEE RIVER NEAR ATHENS

Middle Oconee River rises in Hall County and flows southeastward through Jackson and Clarke counties to its junction with the East Fork, 6 miles below Athens. It drains a rolling area of 300 square miles.

Measurements were begun at Athens on October 11, 1901, the station having been established by Prof. C. M. Strahan, of the University of Georgia. It is located on a wagon bridge, known as Mitchells Bridge, on the Athens and Lawrenceville road, $3\frac{1}{2}$ miles from Athens and about $7\frac{1}{2}$ miles above the junction of Middle Oconee with its eastern fork. It is 4 miles above the dam of the Princeton factory, an 8-foot shoal intervening, and one-third of a mile below the dam of the Athens Electric Railway Company. The station was discontinued on October 25, 1902.

The channel is straight and unobstructed except by remains of old piers just inside the present piers, the old piers being covered at a gage height of 3 feet. The banks are high and the approaches short. The water rises rapidly in time of flood, the maximum gage height being 22.9 feet and the average gage height 2.5 to 3 feet.

Discharge measurements were made from the bridge, which is of the covered wooden lattice type. The initial point for soundings is a spike at the west end of the north bridge truss. The gage is of wire, mounted on the north truss, near the east end of the bridge. It is protected by a plank cover and locked. The bench mark is the top of the lower chord at the gage pulley, 26.85 feet above the river bottom, which is the zero point of the gage, the latter being set to read zero when the weight touches the bottom. The graduations are laid off on the lower chord 20 feet and can be extended to 26 feet.

WATER POWERS OF GEORGIA

Discharge measurements of Middle Oconee River at Athens.

Date	Gage height	Dis-charge	Date	Gage height	Dis-charge
1901			1902		
	<i>Feet</i>	<i>Sec.-ft.</i>		<i>Feet</i>	<i>Sec.-ft.</i>
October 11.....	2.80	498	February 28.....	22.50	16,970
October 26.....	2.80	491	May 2.....	(a)	886
December 31.....	11.38	6,779	June 30.....	1.70	275
1902			July 17.....	2.10	400
January 3.....	3.65	855	July 19.....	1.95	350
			July 22.....	1.85	318

a Gaging made 7 miles above Athens.

Daily gage height, in feet, of Middle Oconee River near Athens.

Day	Oct.	Nov.	Dec.	Day	Oct.	Nov.	Dec.
1901				1901			
1.....		2.8	2.7	17.....	2.8	2.7	3.2
2.....		2.7	2.7	18.....	2.8	2.7	3.0
3.....		2.7	3.1	19.....	2.8	2.8	2.9
4.....		2.8	3.1	20.....	2.8	3.0	2.8
5.....		2.9	2.9	21.....	2.8	2.9	2.8
6.....		2.8	2.9	22.....	2.8	2.8	2.8
7.....		2.8	2.8	23.....	2.8	2.8	3.1
8.....		2.8	2.8	24.....	2.8	2.8	3.4
9.....		2.7	2.8	25.....	2.8	2.7	3.3
10.....		2.7	3.0	26.....	2.8	2.7	3.2
11.....	2.8	2.7	3.0	27.....	2.7	2.7	3.2
12.....	2.9	2.8	2.8	28.....	2.8	2.6	4.2
13.....	2.9	2.8	2.8	29.....	2.8	2.7	11.2
14.....	3.0	2.8	2.9	30.....	2.8	2.7	18.0
15.....	2.9	2.8	4.3	31.....	2.8		10.2
16.....	2.9	2.7	3.5				

Daily gage height, in feet, of Middle Oconee River, near Athens.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.
1902										
1.....	4.2	6.2	19.0	3.0	2.5	2.1	1.7	1.8	1.7	2.2
2.....	3.9	14.0	7.3	3.2	2.5	2.1	1.7	1.8	1.7	2.3
3.....	3.7	17.0	5.7	3.0	2.5	2.1	2.1	2.9	1.7	2.4
4.....	3.5	5.5	5.2	2.9	2.4	2.0	2.0	2.0	1.7	1.9
5.....	3.5	4.2	4.8	2.9	2.4	2.0	1.9	2.7	1.7	2.3
6.....	3.5	3.9	4.6	2.9	2.4	2.0	1.8	2.0	1.7	2.3
7.....	3.4	3.8	4.4	2.9	2.4	2.4	1.8	2.0	1.6	2.1
8.....	3.4	3.8	3.8	3.0	2.4	2.3	1.8	1.9	1.6	1.9
9.....	3.3	3.6	3.6	3.0	2.3	2.2	1.8	1.8	2.1	1.8
10.....	3.3	3.5	3.6	2.9	2.3	2.1	1.8	1.8	2.1	1.8
11.....	3.3	3.5	3.3	2.9	2.3	2.1	1.9	1.7	1.9	1.8
12.....	3.2	3.4	3.3	2.8	2.3	2.0	2.0	2.1	1.8	2.3
13.....	3.2	3.4	4.0	2.8	2.3	2.0	2.5	2.0	2.5	2.3
14.....	3.2	3.4	3.5	2.8	2.3	2.0	3.8	1.9	2.3	2.1
15.....	3.2	3.6	3.4	2.8	2.3	2.2	2.3	1.8	1.9	2.0
16.....	3.2	3.7	5.3	2.8	2.2	2.4	2.2	1.7	1.6	1.9
17.....	3.2	3.6	8.4	3.2	2.2	2.2	2.1	1.7	1.6	1.9
18.....	3.1	3.5	4.7	3.7	2.2	2.1	2.0	1.7	1.6	1.8
19.....	3.2	3.5	3.6	3.0	2.2	2.1	1.9	1.7	1.8	1.8
20.....	3.3	3.6	3.3	2.8	2.2	2.0	1.8	1.7	2.1	1.8
21.....	3.3	3.7	3.1	2.8	2.2	2.0	1.8	1.7	1.9	1.8
22.....	3.2	3.7	3.0	2.8	2.2	2.0	1.9	1.7	1.7	1.8
23.....	3.2	3.5	2.9	2.7	2.2	2.0	1.9	1.6	1.7	1.8
24.....	3.2	3.5	2.9	2.7	2.2	1.9	1.9	1.6	1.6	1.8
25.....	2.2	4.0	2.9	2.6	2.2	1.9	2.2	1.6	3.6	1.8
26.....	3.2	4.3	2.9	2.6	2.2	1.8	1.8	1.6	5.6	
27.....	3.2	3.8	2.9	2.6	2.2	1.8	2.0	1.6	3.9	
28.....	3.4	25.5	3.4	2.5	2.1	1.8	2.3	1.6	3.0	
29.....	4.4		11.3	2.5	2.1	1.8	2.0	1.7	2.1	
30.....	3.9		18.6	2.6	2.1	1.7	1.8	1.7	2.0	
31.....	4.3		4.6		2.1		1.8	1.7		

Rating tables for Middle Oconee River, near Athens.

OCTOBER 11 TO DECEMBER 31, 1901.^a

Gage height	Dis-charge						
<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>
2.60	430	4.50	1,261	6.80	2,822	11.50	7,050
2.70	464	4.60	1,315	7.00	3,000	12.00	7,500
2.80	499	4.70	1,370	7.20	3,180	12.50	7,950
2.90	535	4.80	1,426	7.40	3,360	13.00	8,400
3.00	572	4.90	1,483	7.60	3,540	13.50	8,850
3.10	610	5.00	1,541	7.80	3,720	14.00	9,300
3.20	650	5.10	1,600	8.00	3,900	15.00	10,200
3.30	691	5.20	1,661	8.20	4,080	16.00	11,100
3.40	733	5.30	1,723	8.40	4,260	17.00	12,000
3.50	776	5.40	1,786	8.60	4,440	18.00	12,900
3.60	820	5.50	1,850	8.80	4,620	19.00	13,800
3.70	865	5.60	1,915	9.00	4,800	20.00	14,700
3.80	911	5.70	1,982	9.20	4,980	21.00	15,600
3.90	958	5.80	2,050	9.40	5,160	22.00	16,500
4.00	1,006	5.90	2,119	9.60	5,340	23.00	17,400
4.10	1,055	6.00	2,190	9.80	5,520	24.00	18,300
4.20	1,105	6.20	2,336	10.00	5,700	25.00	19,200
4.30	1,156	6.40	2,490	10.50	6,150		
4.40	1,208	6.60	2,652	11.00	6,600		

JANUARY 1 TO OCTOBER 25, 1902.^b

1.60	243	2.40	499	3.20	755	4.00	1,046
1.70	275	2.50	531	3.30	777	4.10	1,088
1.80	307	2.60	563	3.40	819	4.20	1,131
1.90	339	2.70	595	3.50	851	4.30	1,174
2.00	371	2.80	627	3.60	884	4.40	1,217
2.10	403	2.90	659	3.70	929	4.50	1,261
2.20	435	3.00	691	3.80	966		
2.30	467	3.10	723	3.90	1,005		

^a Above gage height 7.0 feet the rating curve is a tangent, the difference being 90 per tenth.

^b Above gage height 4.5 feet, this table is the same as the 1901 table.

Estimated monthly discharge of Middle Oconee River, near Athens.

[Drainage area, 395 square miles.]

Month	Discharge in second-feet			Run-off	
	Maximum	Minimum	Mean	Sec.-ft. per sq. mile	Depth in inches
1901					
October 11-31.....	572	464	508	1.29	0.80
November.....	572	430	486	1.23	1.37
December.....	12,900	464	1,373	3.48	4.01
1902					
January.....	1,217	723	837	2.12	2.44
February.....	19,560	819	2,362	5.98	6.23
March.....	13,800	659	2,189	5.54	6.39
April.....	884	531	652	1.65	1.84
May.....	531	403	458	1.16	1.34
June.....	499	275	383	.97	1.08
July.....	966	275	375	.95	1.10
August.....	659	243	317	.80	.92
September.....	1,915	243	426	1.08	1.20
October 1-25.....	499	307	367	.93	.87

OCONEE RIVER AT BARNETT SHOALS.

This station was established by Prof. C. M. Strahan, of the University of Georgia, on August 6, 1901, and was discontinued on August 23, 1902, for want of an observer. It was located at Barnetts Bridge, 1 mile above Barnett Shoals and 4 miles east of Watkinsville. Discharge measurements were made from the downstream side of the bridge, which is a covered lattice single-span bridge, with a total length of 109 feet between abutments. The observer was R. L. McRee, a storekeeper at Barnett Shoals, who read the gage once daily at ordinary stages and twice daily during low stages, when the regularity of the flow is affected by the small dam of the Georgia factory, 6½ miles upstream. The gage is a 10-foot rod nailed to a tree on the left bank just above the bridge, and extended to a length of 16 feet by means of a plank marked in feet fastened above. The bench mark is a large nail driven into the tree; elevation, 6.00 feet above the datum of the gage.

Discharge measurements of Oconee River at Barnett Shoals.

Date	Gage height	Dis-charge	Date	Gage height	Dis-charge
1901			1902		
	<i>Feet</i>	<i>Sec.-ft.</i>		<i>Feet</i>	<i>Sec.-ft.</i>
May 2.....	1.40	1,025	January 1.....	6.35	5,061
August 6.....	2.70	1,461	March 22.....	3.20	1,412
August 13.....	4.53	1,882	May 31.....	2.10	800
September 6.....	2.22	825	June 28.....	1.77	619
September 20.....	4.77	2,832			
October 19.....	2.05	808			
December 30.....	12.10	16,670			

Daily gage height, in feet, of Oconee River at Barnett Shoals.

Day	Aug.	Sept.	Oct.	Nov.	Dec.	Day	Aug.	Sept.	Oct.	Nov.	Dec.
1901						1901					
1.....		3.3	2.3	2.0	2.1	17.....	6.0	6.4	2.1	2.0	3.0
2.....		3.0	3.5	2.0	2.1	18.....	3.8	3.3	2.1	2.0	2.6
3.....		2.7	3.9	2.0	2.0	19.....	4.8	3.6	2.05	2.1	2.3
4.....		2.5	3.0	2.0	2.3	20.....	5.9	4.7	2.1	2.2	2.2
5.....		2.4	2.5	2.0	2.2	21.....	4.8	3.2	2.1	2.2	2.1
6.....		2.3	2.3	2.0	2.1	22.....	3.3	2.3	2.1	2.1	2.0
7.....		2.3	2.2	2.0	2.0	23.....	9.7	2.6	2.05	2.1	2.3
8.....		2.2	2.1	2.0	2.0	24.....	7.0	2.5	2.1	2.0	2.2
9.....		2.2	2.1	2.0	2.0	25.....	4.0	2.4	2.0	2.0	2.1
10.....		2.2	2.2	2.0	2.4	26.....	3.4	2.4	2.0	2.0	2.0
11.....		2.5	2.2	2.0	2.3	27.....	6.5	2.3	2.0	2.0	3.0
12.....		2.3	2.1	2.0	2.2	28.....	6.3	2.5	2.0	2.3	5.0
13.....	4.6	2.3	2.2	2.0	2.2	29.....	6.3	2.7	2.0	2.2	10.0
14.....	4.1	2.2	2.2	2.0	3.0	30.....	4.5	2.5	2.0	2.2	12.0
15.....	4.1	2.1	2.3	2.0	5.0	31.....	3.4		2.0		9.5
16.....	6.1	2.2	2.2	2.0	4.0						

ALTAMAHA DRAINAGE BASIN, STREAM FLOW

Daily gage height, in feet, of Oconee River at Barnett's Shoals.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.
1902								
1.....	5.8	8.0	14.0			2.2	1.5	1.6
2.....	4.0	14.0	8.0			2.1	1.5	1.6
3.....	3.0	10.0	6.0			2.1	1.5	2.4
4.....	2.9	8.9	5.0			2.1	2.6	2.4
5.....	2.8	7.6	4.5			2.0	2.7	3.9
6.....	2.7	6.0	4.0			2.0	1.8	2.5
7.....	2.6	4.8	3.6			2.2	1.8	1.9
8.....	2.5	3.9	3.0			3.0	1.9	1.7
9.....	2.4	3.3				2.3	1.7	1.6
10.....	2.4	3.0				2.2	1.9	1.6
11.....	2.4	2.8				2.1	2.5	1.8
12.....	2.4	2.7				2.1	2.4	2.4
13.....	2.4	2.7				1.9	3.2	1.8
14.....	2.3	2.7				1.8	2.2	1.6
15.....	2.3	3.0				1.9	4.3	1.8
16.....	2.3	3.3				2.5	4.3	1.6
17.....	2.3	3.3				2.2	2.5	1.7
18.....	2.3	3.2				2.1	2.0	1.7
19.....	2.4	3.0				2.0	1.9	1.5
20.....	2.3	2.8			2.2	2.7	1.8	1.7
21.....	2.5	2.6			2.2	2.0	1.7	1.8
22.....	2.4	2.6			2.2	1.8	1.7	1.9
23.....	2.3	2.5			2.2	1.8	1.6	1.6
24.....	2.6	2.5			2.3	1.7	1.6	
25.....	2.5	2.5			2.3	1.7	1.6	
26.....	2.4	2.5			2.3	1.7	1.8	
27.....	2.5	8.0			2.2	1.7	1.7	
28.....	2.6	17.0			2.1	1.6	1.7	
29.....	2.9				2.1	1.7	2.0	
30.....	3.6				2.0	1.7	1.8	
31.....	4.0				2.0		1.7	

Rating tables for Oconee River at Barnett Shoals.

AUGUST 13 TO DECEMBER 31, 1901.^a

Gage height	Dis-charge	Gage height	Dis-charge	Gage height	Dis-charge	Gage height	Dis-charge
<i>Feet.</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>
2.00	780	3.80	1,878	5.60	3,835	8.80	9,946
2.10	824	3.90	1,958	5.70	3,980	9.00	10,350
2.20	870	4.00	2,060	5.80	4,130	9.50	11,360
2.30	918	4.10	2,145	5.90	4,285	10.00	12,370
2.40	968	4.20	2,233	6.00	4,445	10.50	13,380
2.50	1,020	4.30	2,324	6.20	4,780	11.00	14,390
2.60	1,074	4.40	2,418	6.40	5,135	11.50	15,400
2.70	1,130	4.50	2,515	6.60	5,510	12.00	16,410
2.80	1,188	4.60	2,615	6.80	5,906	12.50	17,420
2.90	1,248	4.70	2,719	7.00	6,310	13.00	18,430
3.00	1,310	4.80	2,827	7.20	6,714	13.50	19,440
3.10	1,374	4.90	2,939	7.40	7,118	14.00	20,450
3.20	1,440	5.00	3,055	7.60	7,522	15.00	22,470
3.30	1,508	5.10	3,175	7.80	7,926	16.00	24,490
3.40	1,578	5.20	3,299	8.00	8,330	17.00	26,510
3.50	1,650	5.30	3,427	8.20	8,734		
3.60	1,724	5.40	3,559	8.40	9,138		
3.70	1,800	5.50	3,695	8.60	9,542		

JANUARY 1 TO AUGUST 23, 1902.^b

1.50	520	1.80	665	2.10	813	2.40	967
1.60	568	1.90	713	2.20	864	2.50	1,020
1.70	616	2.00	763	2.30	915		

^a Above gage height 6.8 feet the rating curve is a tangent, the difference being 202 per tenth.

^b Above gage height 2.50 feet this table is the same as the 1901 table.

Estimated monthly discharge of Oconee River at Barnett Shoals.

[Drainage area, 835 square miles.]

Month	Discharge in second-feet			Run-off	
	Maximum	Minimum	Mean	Sec.-ft. per sq. mile	Depth in inches
1901					
August 13-31.....	11,760	1,578	4,092	4.90	3.46
September.....	9,542	824	1,763	2.11	2.35
October.....	1,958	780	916	1.10	1.27
November.....	918	780	801	.96	1.07
December.....	16,410	780	2,294	2.75	3.17
1902					
January.....	4,130	915	1,211	1.45	1.67
February.....	26,510	1,020	4,456	5.34	5.56
March 1-8.....	20,450	1,310	5,486	6.57	1.95
May 20-31.....	915	768	851	1.02	.46
June.....	1,310	568	743	.90	1.00
July.....	2,324	520	842	1.01	1.16
August 1-23.....	1,958	520	736	.88	.75

OCONEE RIVER NEAR GREENSBORO.

This station was established July 25, 1903, by M. R. Hall. It is located at the new wagon bridge, about 5 miles west of Greensboro, on the road to Madison.

Ordinarily the river is about 120 feet wide, with sandy and shifting bed. The channel is nearly straight, and the current is regular. The right bank is high and rocky, with the exception of a low bench under the bridge and approach. The left bank is low and will overflow at a gage height of about 12 to 15 feet to the end of the approach for a distance of about 600 feet and at extreme high water may pass beyond the end of the approach.

Discharge measurements are made from the downstream side of the bridge, the initial point for soundings being the end of the iron trestle on the right bank, downstream side. The bridge is of two spans: The first span from the right bank is 80 feet long, and is not over the water except at time of floods; the main span over the river is 144 feet long. There are also 52 feet of iron trestle and about 40 feet of wooden trestle on the right bank, and 253 feet of iron trestle and about 325 feet of wooden trestle on the left bank.

A standard chain gage is fastened to the lower chord of the downstream side of the bridge 163 to 165 feet from the initial point for soundings; length of chain, 38.73 feet. The gage is read once each day by M. A. Stevens, except during three months of the low-water period, when it is read twice each day. Bench marks were established as follows: (1) The top of the downstream end of the second

floor beam from the right-bank pier; elevation, 36.00 feet; (2) a copper plug set in the rock under the upstream side of the bridge opposite a point 84 feet from the initial point for soundings; elevation, 13.55 feet.

Discharge measurements of Oconee River near Greensboro.

Date	Gage height	Dis-charge	Date	Gage height	Dis-charge
1903			1905		
June 12	Feet 4.00	Sec.-ft. 1,521	March 23	Feet 2.32	Sec.-ft. 826
July 25	1.75	783	May 11	2.43	886
August 28	1.70	666	June 8	1.36	519
October 9	1.70	690	June 8	1.80	514
December 2	1.66	725	September 7	.77	338
1904			September 7	.74	331
February 19	2.75	1,066	October 30	.74	323
March 19	2.75	1,023	October 30	.73	325
May 12	1.90	753	November 25	1.03	407
June 9	1.57	617	1906		
July 13	.99	455	February 10	3.62	1,310
August 9	9.82	5,017	April 28	4.35	1,710
August 9	10.49	5,435	June 28	2.13	835
September 21	.45	297	August 17	5.75	2,500
September 21	.45	301	October 17	2.70	961
October 13	0.51	302			
October 13	.50	291			
November 26	1.35	523			
November 26	1.28	494			

Daily gage height, in feet, of Oconee River near Greensboro.

Day	July	Aug.	Sept.	Oct.	Nov.	Dec.	Day	July	Aug.	Sept.	Oct.	Nov.	Dec.
1903							1903						
1		1.9	1.6	1.6	1.6	1.8	17		4.1	8.9	1.8	1.9	1.8
2		4.5	1.4	1.5	1.6	1.7	18		9.6	6.8	1.7	1.7	1.7
3		6.9	1.4	1.5	1.8	1.6	19		13.2	5.2	1.7	1.9	1.7
4		5.6	1.4	1.5	3.7	1.5	20		5.8	2.6	1.6	2.0	1.6
5		4.0	1.4	1.5	2.8	1.5	21		3.5	2.1	1.6	2.1	1.6
6		2.9	1.3	1.5	3.7	1.6	22		2.9	2.2	1.5	1.8	1.8
7		2.2	1.3	1.6	2.6	1.6	23		2.6	2.0	1.5	1.6	1.8
8		2.1	1.2	1.8	2.4	1.8	24		2.1	1.9	1.5	1.6	2.4
9		1.9	1.2	1.7	2.1	2.0	25		1.9	1.8	1.5	1.9	2.2
10		2.5	1.7	1.7	2.1	1.9	26		1.6	1.9	1.8	1.5	1.9
11		2.1	1.8	1.4	1.9	1.9	27		1.6	1.8	1.7	1.5	1.8
12		1.5	1.4	1.4	1.9	1.8	28		1.7	1.8	1.6	1.4	1.7
13		1.5	.9	1.3	1.8	1.7	29		1.6	1.6	1.6	1.3	1.6
14		4.1	1.2	1.2	1.8	1.7	30		2.0	1.5	1.6	1.3	1.6
15		2.5	1.8	1.3	1.9	1.9	31		2.4	1.5		1.5	1.8
16		5.0	10.2	1.5	1.7	2.0							

WATER POWERS OF GEORGIA

Daily gage height, in feet, of Oconee River near Greensboro—Continued.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1904												
1.....	1.8	2.0	3.1	2.6	1.8	3.1	2.5	2.6	1.5	0.4	0.7	1.4
2.....	1.8	2.2	2.8	2.6	1.8	2.6	1.7	2.7	1.5	.3	.8	1.4
3.....	2.0	2.3	3.0	2.4	1.7	2.0	1.5	2.4	1.7	.3	.8	1.8
4.....	1.8	2.4	3.4	2.3	1.5	1.4	1.0	2.0	2.0	.4	1.2	1.7
5.....	1.8	2.5	3.4	2.3	1.5	1.2	.9	1.4	3.8	.6	1.3	1.9
6.....	1.6	2.5	3.4	2.2	1.6	1.0	.9	3.4	2.8	.5	1.0	4.4
7.....	1.7	2.3	6.0	2.7	1.6	1.0	.8	2.2	1.9	.4	.9	4.7
8.....	1.8	5.1	7.9	2.8	1.6	1.8	.8	3.7	1.8	.4	.9	2.8
9.....	1.8	5.5	7.6	3.8	1.7	1.3	1.1	9.3	1.2	.3	.7	2.2
10.....	1.9	4.0	4.3	3.0	1.8	1.2	1.0	11.9	1.0	.2	.6	1.9
11.....	2.0	8.5	3.8	2.5	4.5	1.1	1.7	10.0	1.0	.6	.6	2.0
12.....	2.0	6.2	3.6	2.4	2.0	2.3	1.5	5.3	.9	.6	.6	2.0
13.....	2.1	4.2	3.4	2.2	2.0	1.3	1.1	3.8	.9	.5	1.6	1.8
14.....	2.0	3.9	3.1	2.1	1.8	1.2	.9	2.8	.9	.5	1.4	1.7
15.....	2.0	3.3	4.8	2.2	1.8	1.1	.8	2.4	.8	.2	1.2	1.7
16.....	1.9	3.2	3.5	2.1	1.7	.9	.7	8.9	.7	.1	1.2	1.5
17.....	2.5	2.8	3.2	2.2	1.8	.9	.7	2.7	.7	.2	1.2	1.8
18.....	2.0	2.7	2.8	2.2	1.6	1.0	.7	2.1	.6	.2	1.1	1.8
19.....	2.0	3.0	2.7	2.3	1.5	.9	.7	1.7	.6	.4	1.1	1.7
20.....	1.8	4.7	2.5	2.0	1.3	.7	.7	1.6	.6	.4	1.0	1.7
21.....	2.2	4.9	2.7	2.0	1.2	1.2	.8	1.5	.5	.5	.8	1.5
22.....	2.0	6.7	3.7	2.0	1.2	2.1	1.7	1.6	.5	.5	.8	1.5
23.....	2.2	5.2	4.3	2.4	1.1	1.5	1.2	1.5	.5	.6	1.0	1.5
24.....	4.7	4.8	3.7	2.0	1.1	1.4	1.0	1.5	.5	.1	1.5	1.4
25.....	4.8	4.5	3.4	2.0	1.0	1.0	1.1	1.4	.4	.1	1.8	1.2
26.....	3.0	4.0	3.3	2.0	1.0	1.0	1.1	1.3	.4	.2	1.4	1.2
27.....	2.5	3.4	3.6	3.5	.9	.9	1.0	1.8	.5	.1	1.2	1.4
28.....	2.4	3.4	3.1	3.0	1.0	.7	1.0	1.8	.6	.8	1.0	3.3
29.....	2.3	3.0	2.8	2.8	1.1	1.0	.9	1.8	.5	.6	1.0	3.8
30.....	2.3	2.7	2.6	1.2	2.7	.8	1.6	.4	.5	1.3	2.8
31.....	2.1	2.6	2.8	3.7	1.64	2.2
1905 a												
1.....	2.2	1.9	3.2	2.1	2.0	2.3	2.2	1.4	1.25	.4	.7	1.3
2.....	2.1	2.0	3.1	2.1	2.0	2.0	2.0	1.3	1.85	.15	.65	1.1
3.....	2.0	2.0	2.9	1.9	2.6	2.0	6.8	1.3	1.3	.85	.7	8.1
4.....	1.9	2.1	2.8	2.0	4.1	1.8	2.8	1.0	1.1	1.55	.65	11.6
5.....	1.7	2.2	2.8	2.1	5.4	1.7	2.1	.7	1.4	1.3	.55	13.3
6.....	1.5	2.4	2.7	2.1	4.5	1.7	3.0	.4	1.15	1.15	.6	11.2
7.....	2.0	2.0	2.7	2.4	5.6	1.6	6.0	.3	.9	.35	.7	4.0
8.....	2.7	4.0	2.6	2.2	4.0	1.4	11.2	.6	.85	.8	.7	3.8
9.....	2.4	4.8	2.6	2.2	3.6	1.3	5.0	1.4	.8	.9	.95	8.1
10.....	2.0	6.9	2.7	2.0	3.0	1.1	3.1	4.3	.65	1.05	1.2	11.8
11.....	1.9	7.2	2.6	2.0	2.5	1.1	2.8	3.4	.40	1.25	2.55	12.4
12.....	1.5	8.0	2.6	2.1	2.2	1.2	5.1	4.4	.9	.95	2.0	8.2
13.....	3.0	11.4	2.7	2.0	2.0	1.2	4.4	4.6	1.1	1.25	1.85	5.4
14.....	8.5	12.5	3.2	2.0	1.9	1.5	4.3	4.3	.95	1.2	1.7	3.4
15.....	6.2	10.7	3.0	1.9	1.6	1.5	3.6	5.4	.95	.9	1.35	4.2
16.....	4.3	6.2	2.6	2.0	2.0	1.6	2.9	5.6	.8	.85	1.25	4.5
17.....	3.7	4.9	2.6	2.0	2.0	2.2	2.1	5.6	.65	1.1	1.2	3.9
18.....	2.7	4.0	2.4	1.9	2.0	2.0	2.0	4.6	.35	1.05	1.05	3.4
19.....	2.5	3.7	2.4	1.8	1.7	1.3	1.7	2.2	.8	1.05	1.0	3.2
20.....	2.5	4.2	2.4	1.8	1.5	1.8	1.3	2.4	.8	1.05	1.05	4.0
21.....	2.5	8.1	2.8	1.7	1.6	1.7	1.3	1.7	.6	.95	1.15	12.7
22.....	2.3	9.6	2.7	1.7	1.6	1.6	1.7	1.7	.6	.50	1.25	14.0
23.....	2.3	10.3	2.4	1.8	2.0	2.7	1.4	1.5	.55	.45	1.3	10.5
24.....	2.1	7.0	2.4	1.8	7.5	2.8	1.6	1.7	.35	.7	1.3	6.6
25.....	1.9	5.2	2.3	1.7	6.5	2.4	1.9	3.4	.20	.75	1.3	5.8

ALTAMAHA DRAINAGE BASIN, STREAM FLOW

Daily gage height, in feet, of Oconee River near Greensboro—Continued.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1905 <i>a</i>												
26	1.7	4.2	2.3	1.7	4.1	2.0	1.9	4.4	.50	.8	1.85	4.6
27	1.7	3.5	2.1	1.7	3.2	1.5	1.8	2.2	.45	.8	1.4	3.6
28	1.5	3.2	2.3	1.7	2.8	1.5	1.5	1.75	.4	.75	1.8	3.4
29	1.8		2.3	1.6	2.6	1.8	1.4	1.6	.45	.7	1.4	4.0
30	1.7		2.2	1.7	2.5	2.0	1.2	1.15	.5	.55	1.8	4.0
31	1.9		2.1		2.3		1.0	1.1		.6		3.8
1906												
1	3.5	5.1	3.6	5.6	3.4	2.0	1.8	8.4	5.6	3.5	2.5	2.3
2	3.5	5.0	3.6	5.4	3.0	1.8	4.9	8.4	3.6	5.7	2.5	2.3
3	3.8	4.9	3.8	5.4	2.7	4.8	2.6	3.7	2.8	6.1	2.4	2.3
4	13.9	4.5	3.5	5.2	2.9	5.6	3.3	9.5	2.6	8.7	2.4	2.3
5	16.3	3.8	3.4	5.0	2.9	3.3	2.1	7.7	2.3	10.2	2.3	2.2
6	16.8	3.6	3.2	4.0	2.9	2.3	2.0	6.2	2.4	9.3	2.4	2.3
7	12.5	3.8	2.0	4.1	5.2	2.1	2.1	5.2	3.6	5.8	2.5	2.4
8	3.3	4.0	2.8	3.6	4.6	2.0	6.5	3.7	2.6	4.2	2.4	2.4
9	5.1	3.8	4.3	3.4	3.7	1.7	7.8	3.1	2.2	3.6	2.4	2.3
10	4.8	3.7	3.2	5.5	3.0	2.3	8.2	2.8	2.2	3.4	2.4	2.3
11	4.5	3.7	4.9	4.0	2.6	2.0	4.5	2.6	2.7	3.2	2.3	4.1
12	4.7	3.5	4.5	3.7	2.5	3.7	3.7	2.5	2.6	3.0	2.6	4.9
13	5.2	3.5	3.0	3.7	2.5	3.6	3.1	2.6	5.6	2.9	2.5	4.0
14	5.2	3.3	2.8	4.0	2.4	10.8	2.6	3.4	3.7	2.8	2.6	3.1
15	5.1	3.2	3.6	4.1	2.3	12.3	7.4	5.2	2.5	2.8	2.9	2.8
16	4.3	3.1	13.5	4.2	2.3	10.4	7.9	5.7	2.2	2.8	2.8	2.7
17	4.3	3.1	16.3	3.5	2.2	11.3	7.5	5.3	2.0	2.7	2.7	2.7
18	4.0	3.0	15.2	3.2	2.2	7.4	10.3	4.1	2.3	2.7	3.3	3.3
19	3.4	3.0	10.1	3.1	2.1	4.5	12.3	4.3	5.3	3.7	3.7	4.3
20	3.6	2.9	14.9	3.0	2.0	3.4	9.9	5.1	8.4	4.3	3.4	4.9
21	3.6	2.9	18.5	3.0	1.9	3.1	5.4	6.8	8.4	3.5	2.9	4.9
22	6.5	3.4	18.1	2.9	2.3	2.8	3.8	8.2	8.0	3.0	2.8	4.1
23	16.5	3.0	10.5	2.8	2.1	2.6	3.2	5.9	6.1	2.9	2.8	3.4
24	18.9	3.0	6.1	2.7	1.9	2.2	7.5	4.0	4.0	2.7	2.6	3.1
25	16.2	3.0	6.0	2.6	1.9	2.2	5.0	3.4	4.8	2.7	2.5	2.9
26	11.3	3.9	5.3	2.6	2.3	3.0	4.3	4.0	4.1	2.7	2.5	2.8
27	10.4	3.8	5.5	2.5	2.6	2.4	3.0	4.6	5.8	2.5	2.5	2.7
28	9.8	3.8	5.8	4.2	3.2	2.3	2.9	4.7	5.9	2.5	2.4	2.6
29	8.6		5.6	4.7	2.3	2.1	3.5	4.9	5.3	2.5	2.4	4.0
30	7.0		5.6	4.2	2.2	2.0	6.9	5.8	3.8	2.8	2.2	3.6
31	6.3		5.5		1.9		11.0	4.9		2.5		5.8

a On account of a daily fluctuation caused by developed powers above, two readings a day were made during the last four months of 1905. The low days during this period can be attributed to stored water, and do not represent the natural flow.

WATER POWERS OF GEORGIA

Rating table for Oconee River near Greensboro.

JULY 26, 1903, TO DECEMBER 31, 1904.

Gage height	Dis-charge						
<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>
0.10	215	1.20	510	2.60	996	6.00	2,550
.20	235	1.30	540	2.80	1,068	6.50	2,880
.30	255	1.40	570	3.00	1,140	7.00	3,120
.40	280	1.50	605	3.20	1,220	8.00	3,740
.50	305	1.60	640	3.40	1,300	9.00	4,410
.60	330	1.70	675	3.60	1,384	10.00	5,100
.70	360	1.80	710	3.80	1,472	11.00	5,830
.80	390	1.90	745	4.00	1,560	12.00	6,600
.90	420	2.00	780	4.50	1,780		
1.00	450	2.20	852	5.00	2,020		
1.10	480	2.40	924	5.50	2,280		

JANUARY 1 TO DECEMBER 31, 1905.^a

0.20	195	1.90	690	3.60	1,340	6.60	2,880
.30	220	2.00	725	3.70	1,385	6.80	3,000
.40	245	2.10	760	3.80	1,430	7.00	3,120
.50	270	2.20	795	3.90	1,475	7.20	3,240
.60	295	2.30	830	4.00	1,520	7.40	3,360
.70	320	2.40	865	4.20	1,620	7.60	3,480
.80	345	2.50	900	4.40	1,720	7.80	3,610
.90	375	2.60	935	4.60	1,820	8.00	3,740
1.00	405	2.70	970	4.80	1,920	8.50	4,065
1.10	435	2.80	1,010	5.00	2,020	9.00	4,410
1.20	465	2.90	1,050	5.20	2,120	9.50	4,760
1.30	495	3.00	1,090	5.40	2,220	10.00	5,110
1.40	525	3.10	1,130	5.60	2,330	11.00	5,840
1.50	555	3.20	1,170	5.80	2,440	12.00	6,590
1.60	585	3.30	1,210	6.00	2,550	13.00	7,340
1.70	620	3.40	1,250	6.20	2,660	14.00	8,090
1.80	655	3.50	1,295	6.40	2,770		

^a Above gage height 10.4 feet the rating curve is a tangent, the difference being 75 per tenth.

JANUARY 1 TO DECEMBER, 1906.

<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>
1.70	620	3.00	1,090	4.80	1,670	6.20	2,660
1.80	655	3.10	1,130	4.40	1,720	6.40	2,770
1.90	690	3.20	1,170	4.50	1,770	6.60	2,880
2.00	725	3.30	1,210	4.60	1,820	6.80	3,000
2.10	760	3.40	1,250	4.70	1,870	7.00	3,120
2.20	795	3.50	1,295	4.80	1,920	8.00	3,740
2.30	830	3.60	1,340	4.90	1,970	9.00	4,410
2.40	865	3.70	1,385	5.00	2,020	10.00	5,110
2.50	900	3.80	1,430	5.20	2,120	11.00	5,840
2.60	935	3.90	1,475	5.40	2,220	12.00	6,590
2.70	970	4.00	1,520	5.60	2,330		
2.80	1,010	4.10	1,570	5.80	2,440		
2.90	1,050	4.20	1,620	6.00	2,550		

NOTE.—The last table is based on discharge measurements made during 1903-1906 and is well defined below gage height 10.5 feet. Above gage height 10.4 feet the rating curve is a tangent, the difference being 75 per tenth.

ALTAMAHA DRAINAGE BASIN, STREAM FLOW

Estimated monthly discharge of Oconee River near Greensboro.

[Drainage area, 1,100 square miles.]

Month	Discharge in second-feet			Run-off	
	Maximum	Minimum	Mean	Sec.-ft per sq. mile	Depth in inches
1903					
July (26 31).....	924	640	716	0.651	0.145
August.....	7,450	605	1,481	1.35	1.56
September.....	5,244	420	1,051	.955	1.07
October.....	710	510	610	.555	.640
November.....	1,428	640	790	.718	.801
December.....	924	605	718	.653	.753
1904					
January.....	1,924	640	868	.789	.910
February.....	4,070	780	1,576	1.43	1.54
March.....	3,676	960	1,464	1.33	1.53
April.....	1,472	780	941	.855	.954
May.....	1,780	420	656	.596	.687
June.....	1,180	360	578	.525	.586
July.....	1,428	360	508	.462	.533
August.....	6,522	540	1,848	1.23	1.42
September.....	1,472	280	481	.437	.488
October.....	390	215	278	.253	.292
November.....	710	380	468	.425	.474
December.....	1,876	510	812	.738	.851
The year.....	6,522	215	832	.756	10.26
1905 ^a					
January.....	4,065	555	970	0.882	1.02
February.....	6,965	690	2,497	2.27	2.36
March.....	1,170	760	937	.852	.982
April.....	865	585	698	.635	.708
May.....	3,420	555	1,158	1.05	1.215
June.....	1,010	435	648	.587	.65
July.....	5,990	405	1,195	1.09	1.26
August.....	2,330	220	978	.889	1.02
September.....	672	195	348	.316	.353
October.....	570	185	372	.338	.390
November.....	918	282	470	.427	.476
December.....	8,090	435	3,086	2.81	3.24
The year.....	8,090	185	1,113	1.01	13.67
1906					
January.....	11,800	1,250	4,100	3.73	4.30
February.....	2,070	1,010	1,330	1.21	1.26
March.....	11,500	725	3,640	3.31	3.82
April.....	2,330	900	1,430	1.35	1.51
May.....	2,120	690	971	.883	1.02
June.....	6,320	620	1,860	1.69	1.99
July.....	6,320	655	2,430	2.25	2.59
August.....	4,760	900	2,120	1.93	2.22
September.....	4,000	725	1,670	1.52	1.70
October.....	5,250	900	1,590	1.45	1.67
November.....	1,430	795	955	.863	.97
December.....	2,440	795	1,210	1.10	1.27
The year.....	11,800	620	1,950	1.77	24.22

^a For minimum flow in 1905 see note to gage-height table.

NOTE.—Values for 1906 are excellent.

OCONEE RIVER AT CAREY.

This station, which was established October 29, 1896, is located at an iron girder deck bridge on the Georgia Railroad at the station of Carey, 6 miles west of Greensboro, and just below the junction of the Apalachee and Oconee rivers.

Both banks are low and liable to overflow under the trestles to the end of embankments. The bed of the stream is rocky and the current good.

The top of the iron girder 20 feet from the left-bank end of the bridge on the downstream side is 41.13 feet above the datum of the gage heights.

The rating was evidently affected by the dam several miles below, and for this reason the station was abandoned March 31, 1898.

Discharge measurements of Oconee River at Carey.

Date	Gage height	Dis-charge	Date	Gage height	Dis-charge
1896			1897		
	<i>Feet</i>	<i>Sec.-ft.</i>		<i>Feet</i>	<i>Sec.-ft.</i>
October 29.....	1.68	644	June 9.....	2.50	1,385
November 17.....	2.08	836	July 30.....	1.80	1,103
November 25.....	1.90	795	October 4.....	1.08	381
1897			November 11.....	1.92	678
January 18.....	4.90	3,318	December 14.....	2.30	1,117
March 18.....	5.15	4,257	1898		
April 29.....	2.40	1,992	March 22.....	2.50	1,168
May 28.....	2.10	1,047	November 15.....	3.65	2,386

Daily gage height, in feet, of Oconee River at Carey.

Day	Nov.	Dec.	Day	Nov.	Dec.	Day	Nov.	Dec.	Day	Nov.	Dec.
1896			1896			1896			1896		
1.....	2.1	5.1	9.....	1.8	2.9	17.....	2.08	2.4	25.....	1.9	2.0
2.....	1.9	4.8	10.....	1.8	2.7	18.....		2.2	26.....	1.9	2.1
3.....	1.7	4.4	11.....	1.8	2.6	19.....		2.4	27.....	1.8	2.0
4.....	2.1	4.2	12.....	1.9	2.5	20.....		2.3	28.....	1.9	1.9
5.....	2.7	3.7	13.....	1.8	2.4	21.....		2.2	29.....	2.9	2.1
6.....	2.3	3.4	14.....	1.9	2.3	22.....		2.2	30.....	3.9	2.0
7.....	2.2	3.2	15.....	1.9	4.0	23.....		2.1	31.....		2.0
8.....	1.8	3.0	16.....	2.0	2.8	24.....		2.0			

ALTAMAHA DRAINAGE BASIN, STREAM FLOW

Daily gage height, in feet, of Oconee River at Carey.—Continued.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1897												
1.....	2.1	2.5	3.2	3.3	4.0	2.1	1.6	1.6	1.5	2.0	2.7
2.....	1.9	3.8	3.2	4.9	3.8	2.1	1.5	1.5	1.2	1.5	2.2	2.4
3.....	2.1	3.7	3.1	6.1	3.3	2.1	1.1	1.5	1.2	1.4	2.4	2.2
4.....	2.0	3.6	3.9	5.6	2.8	2.2	1.1	1.5	1.4	1.1	2.0	2.6
5.....	2.1	3.3	3.0	14.4	2.6	2.2	1.5	1.4	1.3	1.2	1.9	2.8
6.....	2.0	4.6	2.9	14.4	2.5	2.3	2.7	1.9	1.2	1.4	1.8	2.7
7.....	2.1	5.0	6.4	12.4	2.3	2.2	2.6	2.4	α 8	1.3	1.8	2.5
8.....	2.1	4.6	7.5	7.3	2.3	2.2	2.2	2.4	α 5	1.2	1.8	2.5
9.....	1.8	3.8	6.8	5.4	2.3	2.5	1.6	2.2	α 3	1.3	1.8	2.4
10.....	1.9	3.3	4.4	5.5	2.3	2.3	1.8	2.1	α 3	2.9	1.9	2.3
11.....	2.0	3.1	4.0	4.5	2.2	2.2	1.8	2.0	α 2	2.8	1.7	2.3
12.....	1.9	5.9	4.2	4.0	2.3	2.0	2.2	1.7	α 2	2.7	1.8	2.1
13.....	2.0	6.6	7.7	3.5	2.3	1.8	1.7	1.5	α 1	2.6	1.8	2.0
14.....	2.7	5.3	10.4	3.5	2.4	1.7	1.6	1.4	α 3	2.3	1.7	2.3
15.....	4.3	4.4	12.2	3.3	2.3	1.7	1.1	1.2	α 4	1.9	1.7	2.5
16.....	4.2	4.0	11.6	3.3	2.3	1.6	1.1	α 7	1.9	1.7	2.4
17.....	3.4	4.2	8.6	3.3	2.3	1.6	2.9	1.5	1.8	1.8	2.3
18.....	4.5	3.6	5.5	3.0	2.2	1.6	1.8	3.1	1.4	1.6	1.9	2.1
19.....	4.8	3.3	4.2	2.9	2.2	1.8	3.7	3.2	1.8	1.9	1.6	2.0
20.....	4.0	3.0	5.3	2.8	2.2	2.4	5.6	4.1	1.5	2.1	1.8	2.0
21.....	6.0	3.8	5.5	2.7	2.0	2.1	5.6	3.0	1.4	2.1	1.8	2.2
22.....	7.8	4.0	4.6	2.7	1.9	2.0	5.8	3.7	1.4	2.0	1.8	2.3
23.....	6.8	3.8	4.6	2.6	2.0	1.7	5.1	2.8	1.9	2.0	1.9	2.4
24.....	4.3	4.7	4.7	2.6	2.2	1.5	3.1	2.6	1.8	2.1	1.8	2.4
25.....	3.3	5.3	4.2	2.7	2.1	2.2	2.4	2.1	1.8	2.0	1.8	2.4
26.....	3.1	5.2	3.7	2.5	2.1	2.0	2.4	1.8	1.7	2.0	1.7	2.4
27.....	2.8	4.2	3.2	2.5	2.1	1.8	2.6	1.7	1.7	1.8	2.3	2.5
28.....	2.8	3.5	3.2	2.5	2.0	1.6	2.3	1.6	1.7	1.8	3.5	2.6
29.....	2.6	3.0	2.5	2.1	1.5	2.3	1.4	1.7	1.6	2.7	2.3
30.....	2.4	3.0	2.9	2.1	1.6	1.8	1.4	1.7	1.6	2.7	2.4
31.....	2.5	3.4	2.2	1.6	1.8	2.3

Day	Jan.	Feb.	Mar.	Day	Jan.	Feb.	Mar.	Day	Jan.	Feb.	Mar.
1893			1898			1898			1898		
1.....	2.2	2.7	2.3	12.....	2.3	2.3	2.3	23.....	2.4	2.2	2.4
2.....	2.1	2.5	2.2	13.....	2.2	2.3	2.2	24.....	2.4	2.2	2.4
3.....	2.0	2.4	2.2	14.....	2.2	2.3	2.6	25.....	2.5	2.2	2.3
4.....	2.0	2.4	2.5	15.....	2.1	2.3	3.5	26.....	5.0	2.1	2.2
5.....	2.1	2.5	2.8	16.....	2.1	2.3	3.9	27.....	5.7	2.1	2.2
6.....	2.1	2.4	2.7	17.....	2.1	2.3	3.5	28.....	4.5	2.1	2.3
7.....	2.1	2.4	2.4	18.....	2.1	2.3	3.9	29.....	3.5	2.3
8.....	2.1	2.4	2.4	19.....	2.0	2.3	3.1	30.....	3.0	2.3
9.....	2.0	2.4	2.4	20.....	2.0	2.3	2.6	31.....	2.8	2.5
10.....	2.1	2.4	2.3	21.....	2.7	2.3	2.4				
11.....	2.2	2.4	2.3	22.....	2.7	2.3	2.5				

α The low gage heights from September 7 to 16, 1897, inclusive, were caused not by a diminution of the flow of the stream, but by the drawing off of a dam several miles below.

Rating table for Oconee River at Carey, from October 29, 1896, to March 31, 1898.

Gage height	Dis-charge						
Feet	Sec.-ft.	Feet	Sec.-ft.	Feet	Sec.-ft.	Feet	Sec.-ft.
0.00	240	1.60	560	3.20	1,848	4.80	3,450
0.20	260	1.80	675	3.40	2,024	5.00	3,750
0.40	290	2.00	815	3.60	2,200	5.20	4,080
0.60	320	2.20	970	3.80	2,376	5.40	4,500
0.80	350	2.40	1,144	4.00	2,554	5.60	4,950
1.00	380	2.60	1,320	4.20	2,750	5.80	5,410
1.20	415	2.80	1,495	4.40	2,965	6.00	5,870
1.40	470	3.00	1,672	4.60	3,200	7.00	8,170

WATER POWERS OF GEORGIA

Estimated monthly discharge of Oconee River at Carey.

[Drainage area, 1,346 square miles.]

Month	Discharge in second-feet			Run-off	
	Maximum	Minimum	Mean	Sec.-ft. per sq. mile	Depth in inches
1896 ^a					
November ^b	2,464	615	882	0.66	0.74
December.....	3,910	740	1,498	1.11	1.28
1897					
January.....	10,000	675	2,114	1.57	1.81
February.....	7,250	1,232	2,905	2.16	2.25
March 1-13, 18-31.....	10,000	1,584	3,482	2.59	2.61
April 9-30.....	4,720	1,232	1,955	1.45	1.19
May.....	2,554	740	1,130	.84	.97
June.....	1,232	510	800	.59	.65
July.....	5,410	395	1,358	1.01	1.16
August.....	2,650	415	948	.70	.81
September.....	740	^c 250	460	.34	.38
October.....	1,584	395	740	.55	.63
November.....	2,112	560	829	.62	.69
December.....	1,496	815	1,116	.83	.95
1898					
January.....	5,180	815	1,340	1.00	1.15
February.....	1,408	890	1,079	.80	.83
March.....	2,464	970	1,800	.97	1.12

^a These estimates have been revised on the basis of the 1897 rating curve.

^b Discharge interpolated November 18 to 24, 1896.

^c The low-water height reported at Carey from September 7 to September 16, 1897, was probably caused by the opening for repairs of a dam 2 or 3 miles below this point. An inspection of the conditions at Macon and other stations shows that this period did not include the lowest water of the year but that the minimum occurred during the first two weeks in October. Leaving out of account this period of sudden apparent low water, the lowest gage reading at Carey was 1.10 on October 4. A measurement made on that day at 1.08 showed a discharge of 381 second-feet.

OCONEE RIVER AT FRALEYS FERRY, NEAR MILLEDGEVILLE.

This station is located at Fraleys Ferry, about 6 miles above Milledgeville, and about 4 miles below the mouth of Little River. This point being above the dam at Milledgeville, the river has a nearly natural flow, being but slightly affected by the dams a great distance upstream.

The channel is straight for some distance above and below the station. The current is moderate or slow at low stages. The bed is sandy and changing, but the rock shoals below will probably control the water level at the station.

Discharge measurements are made from the ferryboat or from a small boat controlled by the ferry cable along which the distances are marked. Measurements can be made at low and medium stages only, as the current is too great for safety in boat measurements at the higher stages.

During a short period in October and November, 1905, gage-height records were maintained by Charles F. Howe, who put in a temporary gage and has furnished the records to the Geological Survey. These gage heights, which are the mean of four readings daily, and the discharge measurements which were made, form a much more accurate basis for estimating the flow for the period which they cover than the records for the station at Milledgeville, 6 miles below. The bench mark is a nail driven horizontally into an ash tree on the right bank about 200 feet above the ferry; elevation, 10.00 feet above the datum of the gage.

Discharge measurements of Oconee River at Fraleys Ferry, near Milledgeville.

Date		Gage height	Dis-charge
1904		<i>Feet</i>	<i>Sec.-ft.</i>
June 29.....		4.90	1,080
September 20.....		4.85	547
1905			
November 24.....		5.02	985
1906			
May 23.....		5.59	1,540
October 12.....		6.02	2,260

Daily gage height, in feet, of Oconee River at Fraleys Ferry, near Milledgeville.

Day	Oct.	Nov.	Day	Oct.	Nov.	Day	Oct.	Nov.
1905			1905			1905		
1.....		4.85	12.....		6.0	22.....		4.65
2.....		4.85	13.....		5.6	23.....		4.55
3.....		4.75	14.....		5.2	24.....		4.55
4.....		4.7	15.....			25.....		4.45
5.....		4.7	16.....			26.....		4.8
6.....		4.6	17.....			27.....		4.8
7.....		4.65	18.....			28.....		4.85
8.....		4.8	19.....			29.....		
9.....		4.85	20.....		4.7	30.....		4.8
10.....		5.0	21.....		4.7	31.....		4.85
11.....		6.0						

WATER POWERS OF GEORGIA

Daily gage height, in feet, of Oconee River at Fraleys Ferry, near Milledgeville.
Continued.

Day	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1906								
1.....		5.4	5.6	8.8	6.8	7.2	5.6	5.6
2.....		5.4	5.6	8.2	7.2	(a)	5.6	5.6
3.....		5.6	6.0	7.5	6.8	(a)	5.6	5.7
4.....		6.3	6.8	7.7	6.0	8.7	5.6	5.7
5.....		6.3	6.3	7.9	5.8	8.4	5.6	5.6
6.....		5.9	5.6	7.3	5.6	8.8	5.6	5.7
7.....		5.6	6.4	7.0	5.5	8.0	5.6	5.8
8.....		5.6	6.9	6.6	5.5	7.0	5.6	5.8
9.....		5.5	8.6	6.3	5.5	6.4	5.6	5.7
10.....		5.6	8.8	6.0	5.4	6.2	5.6	5.8
11.....		5.6	7.4	5.8	5.6	6.2	5.6	5.9
12.....		5.9	6.3	5.8	5.6	6.0	5.7	6.5
13.....		(a)	6.2	6.0	6.6	6.0	5.8	6.4
14.....		(a)	7.0	6.4	6.6	5.9	5.7	6.1
15.....		(a)	7.9	7.4	6.0	5.9	5.9	6.0
16.....		(a)	8.2	7.3	5.5	5.9	6.0	5.8
17.....		(a)	7.9	8.2	5.4	5.8	6.1	5.9
18.....		(a)	8.4	7.0	5.9	5.9	6.1	6.0
19.....		8.6	11.0	6.4	7.2	6.0	6.4	7.3
20.....		7.4	8.2	6.8	8.0	6.4	6.6	7.4
21.....		6.6	7.2	7.3	8.0	6.2	6.2	7.0
22.....		7.0	7.4	7.1	7.8	6.0	6.0	6.7
23.....	5.6	6.8	7.2	6.8	7.0	5.9	5.9	6.4
24.....	5.5	6.0	8.0	6.6	7.1	5.8	5.8	6.2
25.....	5.5	5.8	7.2	6.2	7.1	5.8	5.8	6.0
26.....	5.6	5.8	6.6	6.2	6.6	5.8	5.7	5.9
27.....	5.8	6.2	6.2	5.4	7.2	5.8	5.6	5.9
28.....	6.0	5.9	6.0	7.2	7.5	5.7	5.6	5.9
29.....	5.9	5.6	6.6	6.8	7.0	5.6	5.7	6.6
30.....	5.7	5.6	8.5	7.0	6.6	5.6	5.6	6.8
31.....	5.5	8.8	6.8	5.6	7.6

a Water over the gage.

Rating table for Oconee River at Fraleys Ferry near Milledgeville, for 1905-6.

Gage height	Dis-charge						
<i>Feet.</i>	<i>Sec.-ft.</i>	<i>Feet.</i>	<i>Sec.-ft.</i>	<i>Feet.</i>	<i>Sec.-ft.</i>	<i>Feet.</i>	<i>Sec.-ft.</i>
4.30	530	5.00	1,000	5.70	1,770	6.40	2,360
4.40	580	5.10	1,080	5.80	1,900	6.50	3,040
4.50	640	5.20	1,180	5.90	2,040	6.60	3,220
4.60	700	5.30	1,280	6.00	2,190	6.70	3,410
4.70	770	5.40	1,400	6.10	2,350	6.80	3,600
4.80	840	5.50	1,520	6.20	2,520	6.90	3,800
4.90	920	5.60	1,640	6.30	2,690	7.00	4,000

NOTE.—The above table is based on five discharge measurements made during 1904-1906, and is well defined below gage height 6 feet.

OCONEE RIVER AT MILLEGEVILLE.

This station was established August 22, 1903, by M. R. Hall, though several discharge measurements were made before that time, the first being made October 19, 1895, by C. C. Babb. The bench mark to which the present gage is referred was used for each of these early measurements. The station is located at the iron highway bridge in the eastern part of Milledgeville.

At low water the river is about 300 feet wide, including two piers, and often a sand bar of considerable extent in the third span. This bar sometimes practically stops the third-span channel, leaving the river about 200 feet wide. The bed is sandy and shifting and the water is shallow and swift. These conditions are unfavorable to accurate measurements as well as a constant rating. The channel is only slightly curved. Both banks are high and will not overflow.

Discharge measurements are made from the downstream side of the bridge, the initial point for soundings being the end of the iron bridge at the right bank, downstream side. The bridge consists of four spans, 100 feet, 150 feet, 150 feet, and 80 feet long, respectively, beginning at the right-bank end, and short wooden trestles about 25 feet long at each end.

A standard chain gage, established in August, 1904, is fastened to the intermediate posts on the upstream side of the third panel of the second span from the right bank. The gage is read once each day by J. A. Brooks, who has been paid by the United States Weather Bureau since June 30, 1903. The bottom of the gage box is 43.80 feet above the datum of the gage, and the length of the chain is 45.80 feet. The bench mark is the top of the third floor beam from the pier on the east bank, downstream end; elevation, 39.00 feet above the datum of the gage.

WATER POWERS OF GEORGIA

Discharge measurements of Oconee River at Milledgeville.

Date	Gage height	Dis-charge	Date	Gage height	Dis-charge
1903			1904		
August 22	<i>Feet</i> 3.95	<i>Sec.-ft.</i> 2,301	June 28	<i>Feet</i> 1.14	723
September 11	2.39	1,141	August 18	3.40	2,256
September 12	2.27	1,042	September 19	.95	628
October 16	2.39	1,140	October 11	.87	335
December 16	3.05	1,908	October 11	.41	361
December 18	2.74	1,720	October 12	.49	410
1904			1905		
February 17	3.99	2,852	March 23	2.73	1,867
February 18	3.71	2,449	June 9	1.64	1,064
May 25	1.47	827	September 14	1.20	874
May 26	1.47	857	September 15	.95	712
June 10	2.04	1,213	November 23	1.16	856
June 28	1.12	703			

Daily gage height, in feet, of Oconee River at Milledgeville.^a

Day	Aug.	Sept.	Oct.	Nov.	Dec.	Day	Aug.	Sept.	Oct.	Nov.	Dec.
1903						1903					
1		2.5	2.5	2.55	2.7	17		17.3	3.5	2.8	2.9
2		2.45	2.5	2.55	2.65	18		3.6	5.7	3.4	2.85
3		2.4	2.4	2.55	2.65	19		5.3	3.6	3.2	2.75
4		2.4	2.4	2.65	2.65	20		3.9	3.0	2.9	2.75
5		2.35	2.4	3.9	2.75	21		3.4	2.9	2.85	3.0
6		2.4	2.3	3.8	2.75	22		3.2	2.75	2.85	2.95
7		2.4	2.25	3.7	2.75	23		3.1	2.65	2.85	2.95
8		2.2	3.1	3.2	2.7	24		3.0	2.6	2.85	3.0
9		3.5	2.65	3.1	2.65	25		3.2	2.9	2.85	3.0
10		2.5	2.6	2.7	3.4	26		3.1	2.85	2.45	3.9
11		2.5	2.4	2.85	3.4	27		3.0	2.6	2.4	2.75
12		2.3	2.25	2.7	3.2	28		2.85	2.6	2.5	2.7
13		2.1	2.2	2.85	2.95	29		2.75	2.6	2.5	2.7
14		2.45	2.35	2.85	3.0	30		2.65	2.5	2.5	2.7
15		3.4	2.3	2.85	3.1	31		2.55	2.55		2.9
16		17.3	2.4	2.8	3.1						

^a Owing to the irregular running of the mill above this station during the low-water period, the true mean gage height was not always obtained, although two readings were made each day. From this cause the gage heights below 0.5 foot are probably too low and in some cases gage heights above 0.5 foot may be artificially high.

ALTAMAHA DRAINAGE BASIN, STREAM FLOW

Daily gage height, in feet, of Oconee River at Milledgeville—Continued.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1904												
1	2.9	3.4	3.9	3.2	2.5	3.55	2.4	4.6	1.8	0.6	0.6	1.3
2	2.85	3.4	3.9	3.5	2.4	3.65	2.35	2.9	1.4	.5	.6	1.4
3	2.8	3.2	3.8	3.2	2.35	2.65	2.1	2.8	1.4	.5	.7	2.2
4	2.8	3.2	3.8	3.1	2.4	2.2	1.8	3.6	1.3	.9	1.1	2.0
5	2.8	3.1	3.8	2.9	2.3	1.8	1.6	2.8	1.3	.6	1.7	2.1
6	2.75	3.1	3.4	3.0	2.1	1.55	1.5	2.4	2.7	.5	1.3	3.2
7	2.75	3.1	4.4	3.1	2.1	1.65	1.4	4.6	2.5	.5	1.5	4.3
8	2.75	5.2	6.4	3.4	2.1	2.25	1.2	11.6	2.2	.5	1.5	4.1
9	2.75	5.2	7.4	3.7	2.1	2.75	1.2	7.2	1.8	.4	1.4	2.9
10	2.95	5.4	6.1	4.4	2.3	2.2	1.7	9.2	1.6	.3	1.3	2.4
11	2.95	9.5	4.7	3.6	3.5	1.7	2.2	11.6	1.3	.4	1.1	2.2
12	2.9	9.0	4.2	3.4	2.3	1.6	4.2	7.1	1.3	.5	1.3	2.1
13	3.0	6.7	3.9	3.0	2.2	2.1	2.1	5.2	1.3	.5	1.5	2.2
14	3.1	5.1	3.7	2.9	2.1	1.7	1.8	3.4	1.1	.5	1.8	2.0
15	3.1	4.6	3.9	2.75	2.1	1.5	1.4	2.8	1.2	.3	2.0	2.0
16	3.0	4.4	4.7	2.7	2.1	1.45	1.3	7.3	1.0	.2	1.8	2.4
17	3.0	4.0	4.0	2.7	2.1	1.45	1.1	5.5	1.2	.7	1.6	2.2
18	4.2	3.8	3.5	2.7	2.0	1.2	1.2	4.1	.9	.2	1.4	2.5
19	3.5	3.6	3.5	2.75	1.95	1.2	1.0	3.3	1.0	.2	1.3	2.3
20	3.4	3.6	3.4	2.7	1.8	1.1	1.2	2.7	.9	.3	1.2	2.0
21	3.1	3.7	3.3	2.7	1.75	1.0	.9	2.1	1.0	.3	1.1	2.0
22	3.2	6.9	3.3	2.65	1.75	1.4	1.0	1.9	1.0	.4	1.3	1.9
23	11.5	9.4	3.9	2.7	1.7	2.65	.6	1.8	.7	.4	1.4	1.8
24	8.95	8.1	6.1	2.75	1.65	2.0	1.5	1.6	.8	.4	1.5	1.7
25	5.7	6.3	6.2	2.6	1.6	1.65	1.8	2.1	.6	.3	1.7	1.7
26	4.5	5.1	4.6	2.5	1.45	1.4	2.4	1.9	.6	.3	1.9	1.3
27	3.8	4.4	4.1	2.75	1.25	1.4	1.8	2.1	.6	.3	1.6	1.8
28	3.6	4.1	4.3	2.85	1.45	1.1	1.4	2.6	.5	.6	1.3	5.4
29	3.6	4.1	3.8	2.75	1.45	2.0	1.4	2.1	.5	.8	1.2	4.3
30	3.6	3.4	2.6	1.6	1.6	1.8	1.4	2.0	.4	.7	1.4	3.9
31	3.4		3.3		2.55		2.4	1.8		.7		3.0
1905 ^b												
1	2.5	2.1	3.6	2.6	3.0	2.6	2.6	1.3	1.3	.3	.93	1.2
2	2.4	2.1	3.5	2.4	2.3	2.3	3.3	1.4	5.4	.7	1.0	1.1
3	2.3	2.1	3.3	2.4	4.0	2.2	6.4	1.2	4.4	.6	.92	2.3
4	2.5	2.1	3.1	2.4	4.0	2.1	5.4	1.0	3.4	1.6	.8	3.7
5	2.2	2.0	3.1	2.5	4.6	2.3	2.9	1.0	2.9	2.5	.77	11.4
6	2.0	2.3	3.0	2.9	4.7	2.0	2.3	.8	1.9	1.5	.75	11.6
7	2.4	3.0	2.9	3.1	3.7	2.0	3.0	.7	1.5	1.3	.7	5.4
8	2.6	4.9	2.9	2.9	5.2	1.8	3.0	1.1	1.2	1.15	.8	3.4
9	2.8	11.0	2.9	2.3	4.3	1.6	3.9	.9	1.0	.8	1.0	3.3
10	2.6	9.7	3.3	4.5	3.6	1.5	4.2	4.4	1.0	.87	1.2	9.6
11	2.4	8.5	3.3	4.3	3.1	1.4	3.6	5.0	1.0	.73	2.3	10.3
12	2.6	10.3	4.5	3.7	2.3	1.4	4.5	4.0	.9	1.0	3.7	10.2
13	3.3	21.0	6.2	5.9	2.5	1.5	4.8	6.8	.8	1.1	2.5	6.1
14	6.3	19.2	4.5	3.9	2.2	1.6	3.6	6.5	1.2	1.3	1.9	4.1
15	7.0	14.7	4.3	3.1	2.0	1.6	3.8	4.9	.9	1.1	1.7	6.1
16	5.0	10.0	3.7	3.2	2.0	1.5	2.7	4.9	1.0	.98	1.5	6.2
17	3.8	6.5	3.4	3.1	3.2	1.5	2.2	4.0	.8	1.1	1.3	5.0
18	3.0	5.3	3.1	2.8	2.7	2.5	1.9	13.0	.8	.32	1.2	4.2
19	2.8	4.6	3.1	2.7	2.4	2.1	1.8	5.7	.7	.93	1.0	3.5
20	2.9	4.3	3.0	2.6	2.1	1.9	1.7	2.7	.7	.9	1.0	4.4
21	2.9	7.8	4.2	2.4	1.9	1.7	2.1	2.1	.8	.35	1.1	13.3
22	2.7	10.2	4.7	2.4	2.2	2.5	1.8	1.8	.6	.7	1.2	13.1
23	2.5	9.6	3.6	2.5	3.3	4.7	1.7	1.8	.5	.63	1.1	15.1
24	2.4	3.6	3.2	2.4	6.6	4.3	1.5	2.1	.4	.68	1.1	10.5
25	2.4	6.3	3.1	2.3	7.2	3.2	2.1	3.4	.5	.63	1.3	6.5
26	2.2	4.9	3.0	2.4	6.2	2.3	2.1	2.8	.5	.37	1.1	5.0
27	2.0	4.3	3.0	2.5	4.9	2.1	1.9	3.6	.4	.37	1.1	4.3
28	2.0	3.9	2.9	2.5	3.5	2.0	1.7	2.0	1	1.03	1.2	3.9
29	1.9		2.7	2.3	3.1	2.2	1.5	1.6	.2	.95	1.6	6.6
30	2.0		2.6	3.1	3.0	2.7	1.2	1.4	.4	.92	1.3	6.1
31	1.8		2.6		3.5		1.5	1.2		.88		4.3

^a This height is doubtful.

^b From October 6 to November 6, 1905, an attempt was made to obtain a proper mean gage height by making six readings daily. For the rest of the time only one reading was made.

Rating table for Oconee River at Milledgeville from August 25, 1903, to December 31, 1904.^a

Gage height	Dis-charge						
<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>
0.20	290	1.30	785	2.80	1,760	8.00	7,040
.30	380	1.40	840	3.00	1,920	9.00	8,090
.40	370	1.50	895	3.20	2,090	10.00	9,140
.50	410	1.60	950	3.40	2,265	11.00	10,190
.60	450	1.70	1,010	3.60	2,450	12.00	11,240
.70	495	1.80	1,070	3.80	2,640	13.00	12,290
.80	540	1.90	1,130	4.00	2,840	14.00	13,340
.90	585	2.00	1,190	5.00	3,890	15.00	14,390
1.00	680	2.20	1,320	6.00	4,940	16.00	15,440
1.10	680	2.40	1,460	7.00	5,990	17.00	16,490
1.20	730	2.60	1,610				

^a Above 4-foot gage height, daily discharge estimates are based on a tangent, the difference being 105 per tenth.

Estimated monthly discharge of Oconee River at Milledgeville.^a

Month	Discharge in second-feet		
	Maximum	Minimum	Mean
1903			
August 25-31.....	2,090	1,573	1,823
September.....	16,800	1,255	2,998
October.....	4,625	1,320	1,702
November.....	2,740	1,573	1,872
December.....	2,740	1,648	1,911
1904			
January.....	10,720	1,723	2,643
February.....	8,615	2,005	3,903
March.....	6,410	2,175	3,152
April.....	3,260	1,535	1,926
May.....	2,355	758	1,229
June.....	2,498	630	1,138
July.....	3,050	450	1,019
August.....	10,820	950	3,138
September.....	1,685	370	755
October.....	585	6290	403
November.....	1,190	450	840
December.....	4,310	785	1,638
The year.....	10,820	290	1,815

^a These estimates are only approximately correct. No estimates were attempted for 1905.

^b See note under gage heights.

OCONEE RIVER AT DUBLIN.

A station was established by the United States Weather Bureau in 1894 at Dublin, Ga., about 60 miles above the junction of the Oconee with the Ocmulgee. Records were kept, with the exception of the summer months of 1896, until April 30, 1897, when the station was discontinued. In 1898 discharge measurements were commenced by the United States Geological Survey, and February 11 an observer was employed to read the gage. October 15, 1898, the

Weather Bureau again adopted the station and has maintained the gage and furnished gage heights to the Geological Survey continuously since that time.

The ordinary width of the river is about 235 feet. At a gage height of about 20 feet the left bank begins to overflow, and is practically covered to the end of the approach at 25 feet. This ground is thickly covered with a brushy growth, which will no doubt cause the velocity of the water overflowing it to be small. The right bank does not overflow. The bed of the stream is of loose rock, sand, and gravel. The channel is straight and the current is swift and fairly uniform, except where it is broken by the three bridge piers.

Discharge measurements are made from the iron highway bridge, which consists of a draw span between two other spans of 75 feet each. The total length of the bridge proper is 320 feet. On the left bank, which is low, there are 1,100 feet of iron-frame trestle approach. There is also a short trestle on the right bank, which is high. The initial point for soundings is the end of the bridge at the right bank, on the upstream side.

The gage is a heavy timber bolted to the downstream side of the center pier of the Wrightsville and Tennille Railroad bridge, 500 feet downstream from the highway bridge.

The bridge is a drawbridge, and the pier to which the gage is attached is the circular center pier of the draw span. A secondary sloping gage, reading from -1.6 to $+1.9$ feet, is attached to a solid rock on the right bank about 25 feet above the railroad bridge. The gage is read once each day by R. F. Mathis. Bench marks were established as follows: (1) The top of the upstream end of the floor beam on top of the first tubular pier of the wagon bridge from the right bank; elevation, 41.30 feet. (2) A point on the fifth step from the bottom at the south entrance of the court-house, 6 inches from the east end of the step; elevation, 82.51 feet.

WATER POWERS OF GEORGIA

Discharge measurements of Oconee River at Dublin.

Date	Gage height	Dis-charge	Date	Gage height	Dis-charge
	<i>Fect.</i>	<i>Sec.-ft.</i>		<i>Fect.</i>	<i>Sec.-ft.</i>
1897			1908		
May 5.....	6.10	6,400	April 3.....	15.40	20,160
June 7.....	1.90	2,861	April 4.....	14.95	19,800
June 8.....	1.77	2,680	June 6.....	8.81	9,804
June 9.....	1.50	2,488	June 6.....	8.51	9,432
June 10.....	1.43	2,488	June 15.....	4.47	5,017
November 7.....	.40	1,644	July 15.....	5.95	6,579
			August 24.....	4.61	4,475
1898			October 6.....	.12	1,713
February 11.....	.95	2,057	November 14.....	1.15	2,472
March 29.....	.65	1,927			
May 20.....	— .23	1,272	1904		
June 24.....	— .23	1,164	February 18.....	4.33	5,136
July 27.....	6.23	7,007	April 12.....	2.45	3,521
August 30.....	10.80	12,160	July 21.....	— .98	808
October 20.....	3.70	4,153	September 16.....	— .90	840
			September 17.....	— .95	798
1899			October 27.....	— 1.55	515
February 2.....	8.20	9,689	October 27.....	— 1.55	557
April 23.....	8.00	9,033	December 3.....	.45	1,968
June 8.....	.80	1,937			
September 15.....	.80	1,997	1905		
September 15.....	.50	1,903	March 15.....	7.03	8,233
December 14.....	3.90	4,028	April 25.....	1.14	2,631
			April 25.....	1.11	2,518
1900			June 13.....	— .60	1,187
April 12.....	4.25	4,680	June 13.....	— .60	1,192
December 7.....	7.30	7,991	July 31.....	— .62	1,201
			November 6.....	— .97	929
1901			November 6.....	— .98	882
February 20.....	5.00	5,341	November 9.....	— .99	856
May 7.....	3.40	3,949			
November 7.....	1.00	2,334	1906		
			March 6.....	3.14	4,320
1902			March 6.....	3.11	4,300
November 12.....	.27	1,651	May 23.....	.82	2,280
November 12.....	0.25	1,615	September 1.....	5.50	6,560
November 13.....	.27	1,619			

ALTAMAHA DRAINAGE BASIN, STREAM FLOW

179

Daily gage height, in feet, of Oconee River at Dublin.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1898												
1.....			0.5	1.0	4.0	-0.6	-1.0	5.8	11.8	0.8	3.6	5.5
2.....			.5	2.0	2.6	-.7	-1.1	4.3	13.0	.7	3.3	5.5
3.....			.5	2.3	1.9	-.7	-1.2	2.3	16.0	2.3	3.1	5.4
4.....			.9	2.0	1.7	-.8	-1.2	2.0	23.0	6.9	2.6	7.5
5.....			1.9	2.5	1.4	-.9	-1.3	1.6	24.6	8.7	2.3	8.5
6.....			3.9	6.0	1.1	-1.0	-1.2	2.0	23.3	9.4	2.1	9.6
7.....			3.0	7.8	1.0	-.1	-.9	4.2	21.2	10.5	2.0	11.1
8.....			2.6	8.5	.9	-.1	+.3	5.9	19.5	11.3	2.0	12.6
9.....			2.0	9.4	.8	-1.1	1.0	6.4	18.0	13.5	1.8	12.6
10.....			1.8	10.0	.7	-1.1	1.8	6.5	17.0	15.5	1.7	10.7
11.....		0.9	1.5	9.8	.6	-1.2	1.8	4.2	16.0	16.0	1.7	7.7
12.....		.9	1.4	6.5	.6	-1.2	2.8	3.4	14.8	14.5	1.6	6.7
13.....		.9	1.0	5.9	.3	-1.2	3.0	3.0	12.5	11.8	1.6	6.0
14.....		.9	.9	3.3	.2	-1.2	1.6	4.3	7.6	5.0	3.9	5.6
15.....		.9	.9	2.9	.1	-.7	2.9	5.5	4.7	3.8	6.7	5.2
16.....		.8	2.0	2.5	.0	-.6	4.6	6.5	3.6	3.5	7.2	4.6
17.....		.8	3.5	2.0	.0	-.4	4.0	6.4	3.0	3.2	7.6	4.2
18.....		.9	3.5	1.8	-.2	.0	3.2	4.6	3.0	3.0	8.9	4.6
19.....		1.0	2.8	1.7	-.2	+.9	1.8	5.9	2.7	3.0	11.0	3.0
20.....		1.5	3.1	1.5	-.3	.8	.9	6.0	2.3	2.8	13.0	4.0
21.....		1.5	2.4	1.4	-.3	.6	.5	5.9	2.2	4.3	14.3	4.4
22.....		1.4	1.9	1.4	-.4	.8	.0	5.0	2.0	5.6	15.0	5.0
23.....		1.1	1.5	1.3	-.4	.7	-.2	3.8	2.0	6.9	14.1	6.1
24.....		.9	1.1	1.8	-.4	-.3	+.1	2.5	1.8	7.5	12.3	6.5
25.....		.8	1.0	3.9	-.1	-.5	2.6	1.9	2.0	7.8	10.2	6.9
26.....		.7	1.0	5.5	+.2	-.7	5.1	1.6	2.8	6.3	8.3	6.7
27.....		.5	.9	6.0	.8	-.8	6.1	1.9	2.4	4.3	6.2	6.4
28.....		.5	.8	4.7	.6	-.9	7.0	7.0	1.5	3.5	5.2	5.6
29.....		.7	.4	4.9	-.1	-.9	6.7	10.5	1.2	3.1	5.0	5.2
30.....		.6	.4	5.4	-.3	-.9	6.0	10.9	.9	3.0	5.2	4.9
31.....		.6	.6	-.5	5.6	11.1	3.3	4.0
1899												
1.....	3.8	7.7	11.3	8.3	5.4	1.7	.5	2.9	2.5	-1.3	-.4	2.4
2.....	3.6	8.1	13.8	8.0	4.7	1.8	.6	2.3	2.9	-1.3	-.4	1.1
3.....	5.2	9.1	16.5	8.5	3.8	1.7	.4	2.0	2.7	-1.3	-.4	2.0
4.....	5.8	9.9	17.0	9.0	3.7	1.5	.2	1.7	2.1	-1.3	-.5	1.9
5.....	5.0	10.7	16.9	9.8	3.5	1.4	.1	1.5	1.5	-.8	-.5	1.7
6.....	4.7	12.7	16.2	9.5	4.1	1.2	.0	.9	1.1	.5	-.5	1.6
7.....	5.0	13.1	14.5	9.0	5.0	1.0	.2	.8	.8	2.4	-.5	1.3
8.....	7.8	15.0	12.7	8.6	4.8	.8	.4	.7	.3	5.1	-.6	1.1
9.....	8.6	20.1	11.0	8.0	4.4	.7	.0	.2	.2	7.2	-.6	.9
10.....	10.4	22.5	9.8	7.8	3.6	.6	-.1	-.3	.1	8.1	-.7	.7
11.....	12.2	21.7	8.6	7.5	3.0	.5	-.1	-.4	.0	8.6	-.7	.5
12.....	14.1	18.9	7.6	7.0	2.7	.4	-.2	-.2	.1	6.8	-.7	1.2
13.....	14.4	17.5	7.0	6.4	2.7	.3	-.3	-.1	.7	4.1	-.8	2.6
14.....	15.3	16.8	6.8	5.6	2.4	.3	-.4	-.1	1.5	1.7	-.8	3.3
15.....	14.8	15.5	6.7	5.2	2.3	.9	-.4	-.2	.8	1.1	-.1	4.1
16.....	14.5	13.7	7.3	5.0	2.1	1.2	-.4	-.3	.1	.6	.7	3.2
17.....	14.3	12.4	7.9	4.9	2.0	.7	-.5	-.5	-.3	.5	.1	2.5
18.....	13.7	12.5	8.3	4.8	1.9	.3	-.6	-.6	-.4	.5	.8	1.9
19.....	13.3	12.7	9.2	5.3	1.8	.3	-.6	-.7	-.5	.5	.1	1.5
20.....	13.1	13.3	10.1	5.8	1.7	.6	-.6	-.8	-.6	.4	-.2	1.3
21.....	12.8	13.6	10.9	5.6	1.6	.9	-.7	-.8	-.7	.4	-.3	1.2
22.....	12.6	13.0	12.6	5.5	1.5	.5	-.7	-.9	-.8	.2	-.4	1.2
23.....	11.3	12.0	14.2	5.2	1.5	.3	-.7	-.7	-.9	.0	-.3	1.4
24.....	8.3	10.8	13.4	5.0	1.8	.2	-.8	-.3	-.9	-.1	.1	1.4
25.....	7.8	9.8	11.9	4.8	2.1	.2	-.8	-.2	-1.0	-.3	1.5	2.3
26.....	7.3	9.0	10.0	5.9	1.8	.0	.3	2.5	-1.0	-.4	1.3	5.3
27.....	7.1	9.7	9.6	7.4	1.7	-.1	.7	3.0	-1.1	-.5	2.1	5.6
28.....	6.8	9.6	8.9	8.0	1.6	-.2	.9	3.0	-1.1	-.6	3.2	4.6
29.....	7.0	8.3	7.2	1.6	-.2	1.3	5.1	-1.1	-.7	4.4	3.9
30.....	7.4	8.1	6.1	1.6	-.4	4.7	4.5	-1.2	-.7	3.3	2.8
31.....	7.6	8.0	1.6	5.0	2.9	-.3	2.6

WATER POWERS OF GEORGIA

Daily gage height, in feet, of Oconee River at Dublin—Continued.

Day	Jan.	Feb.	Mar.	Apr.	May.	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1900												
1.....	2.4	1.7	8.0	8.8	8.3	1.6	19.0	4.7	.8	—	1.0	2.3
2.....	2.1	1.6	9.6	6.5	6.4	1.4	16.9	5.0	2.7	—	.9	1.8
3.....	1.8	1.6	10.4	5.3	6.9	1.3	14.8	3.7	2.3	—	3.7	1.6
4.....	1.7	1.6	11.0	4.8	7.3	1.2	12.7	2.9	2.1	—	4.7	1.8
5.....	1.6	1.8	11.7	4.5	7.5	1.9	10.1	2.5	1.5	.0	5.5	3.2
6.....	1.6	3.4	11.0	4.3	6.7	2.8	8.5	1.9	1.2	0.8	6.5	6.4
7.....	1.5	3.7	9.0	4.2	5.4	4.1	8.0	1.6	.5	1.2	6.6	7.2
8.....	1.4	3.5	6.6	4.0	4.1	5.0	5.5	1.6	.4	.9	4.8	7.6
9.....	1.2	3.1	5.8	3.7	3.9	6.0	3.9	1.5	.2	1.1	3.9	6.8
10.....	1.4	3.5	7.0	3.5	3.3	6.2	3.2	1.3	.2	1.2	2.6	4.5
11.....	1.9	7.9	8.0	3.3	3.0	6.2	2.6	.7	.0	1.0	1.8	3.3
12.....	2.4	10.2	8.5	3.9	2.7	5.7	2.8	.4	—	.3	1.3	2.7
13.....	4.3	11.9	8.7	5.0	2.5	4.3	6.6	.2	—	.6	1.2	2.3
14.....	5.4	16.4	8.0	5.9	2.3	3.0	6.1	.1	—	.7	1.0	2.3
15.....	5.7	22.0	7.1	6.3	2.2	2.9	5.5	.3	—	.6	1.0	5.2
16.....	4.9	24.4	6.4	5.0	2.1	5.0	4.7	1.1	.4	.6	.9	6.7
17.....	3.3	24.9	8.1	4.1	2.0	7.5	4.1	.8	4.8	.6	.8	8.1
18.....	2.9	24.1	8.7	3.4	1.9	8.3	2.8	.6	5.8	.5	.7	8.4
19.....	2.8	22.6	9.0	5.1	2.1	9.9	2.3	.5	6.0	.2	.9	6.4
20.....	3.2	20.0	9.1	8.2	3.7	10.3	2.0	.3	3.5	.1	.7	4.2
21.....	4.1	17.2	8.5	11.1	5.5	10.6	1.8	.1	1.9	.1	.7	4.6
22.....	4.7	14.0	7.4	15.6	5.3	10.2	1.5	.5	1.3	.0	1.1	6.8
23.....	4.4	10.7	7.3	16.9	3.6	7.9	1.2	.5	.7	.0	1.2	7.7
24.....	3.9	9.1	8.3	17.6	3.1	8.0	1.0	.4	.4	.7	.8	8.0
25.....	3.3	9.0	8.9	17.3	3.6	9.0	2.4	.3	.3	3.7	.8	8.2
26.....	2.9	8.7	9.5	17.0	5.8	9.9	3.1	1.3	.3	5.6	.7	6.5
27.....	2.4	8.1	9.6	17.1	5.0	11.6	2.1	.9	.3	5.5	1.7	4.8
28.....	2.2	7.4	9.8	16.0	3.4	16.7	1.7	.7	.2	3.0	3.5	3.8
29.....	2.0	10.2	13.6	3.0	20.0	1.7	.5	.2	2.1	5.3	3.4
30.....	1.8	10.4	11.4	2.2	20.8	5.9	.5	.0	1.9	3.4	3.3
31.....	1.7	10.2	1.9	5.2	.8	1.3	8.4
1901												
1.....	9.8	4.7	4.6	16.4	3.7	4.0	6.1	1.5	10.3	4.0	.8	1.0
2.....	10.4	6.1	4.2	16.1	3.5	6.3	6.5	1.4	10.5	4.3	.8	1.0
3.....	11.3	5.6	3.9	16.5	3.8	7.0	6.0	1.2	10.3	4.5	.8	1.0
4.....	12.5	6.7	3.7	16.6	3.0	7.5	5.8	1.2	9.4	5.1	.8	1.3
5.....	13.0	8.6	3.4	20.5	2.9	6.0	4.3	.8	6.3	4.8	.8	1.6
6.....	13.9	9.3	3.2	22.6	2.7	5.0	3.0	.5	3.4	3.9	.9	2.5
7.....	13.9	11.0	3.0	21.3	2.5	5.3	2.8	1.4	2.3	2.8	1.1	2.2
8.....	13.0	14.3	2.9	19.5	2.9	7.5	2.0	4.0	2.0	2.1	1.0	1.8
9.....	10.8	15.6	2.8	17.4	2.8	8.1	1.8	4.4	1.7	2.0	1.0	1.6
10.....	7.4	15.8	2.8	15.0	2.6	9.5	1.7	4.5	1.3	1.6	1.0	1.5
11.....	6.0	14.6	4.5	12.0	2.4	8.4	2.1	2.9	1.2	1.7	.9	1.5
12.....	5.4	13.8	5.5	8.2	2.1	7.5	2.1	1.7	1.0	1.7	.9	2.0
13.....	6.0	13.4	6.6	6.0	2.0	4.9	2.0	3.4	.8	1.6	.9	2.0
14.....	6.6	12.5	8.0	7.0	1.8	7.7	1.9	4.3	.7	2.0	.9	1.7
15.....	7.4	10.2	8.2	8.0	1.8	9.1	1.8	4.0	.6	2.5	.8	2.0
16.....	8.0	8.9	6.2	8.9	2.0	10.4	1.5	4.5	1.4	2.0	.9	5.5
17.....	8.6	6.8	5.1	9.6	2.2	11.2	2.4	4.5	1.4	1.7	.9	6.8
18.....	9.1	5.9	4.6	10.0	1.8	11.4	2.7	6.2	4.0	1.4	.9	7.4
19.....	9.6	5.4	4.2	9.8	1.7	11.3	2.5	6.5	11.4	1.3	.9	8.3
20.....	9.9	5.1	3.7	9.0	2.0	10.8	3.3	7.4	14.5	1.3	1.1	8.0
21.....	10.3	4.7	4.7	8.1	3.6	9.7	5.9	8.0	17.8	1.2	1.4	4.5
22.....	9.6	4.5	4.8	8.0	6.0	7.6	7.0	7.8	19.4	1.0	1.5	3.0
23.....	6.6	4.2	4.0	7.6	7.5	5.3	7.6	7.5	18.0	1.0	1.7	2.5
24.....	5.3	4.5	4.1	6.8	7.8	4.1	7.2	7.5	16.4	1.0	1.6	2.6
25.....	4.6	4.9	4.3	6.2	8.1	3.7	3.5	7.3	13.8	.9	1.4	3.0
26.....	4.8	4.9	4.3	5.0	6.6	4.5	2.9	7.2	8.3	.9	1.3	3.6
27.....	4.7	5.0	7.5	4.6	4.5	4.1	1.5	7.8	4.0	.9	1.3	3.7
28.....	5.0	5.2	9.3	4.1	4.6	6.3	1.4	8.6	3.1	.8	1.3	3.8
29.....	5.1	12.0	3.8	3.9	6.0	3.0	9.6	3.8	.8	1.2	6.0
30.....	5.6	15.1	3.8	3.1	5.5	2.3	10.0	4.1	.7	1.1	7.6
31.....	5.1	16.5	2.8	1.8	10.88	8.6

ALTAMAHA DRAINAGE BASIN, STREAM FLOW

Daily gage height, in feet, of Oconee River at Dublin—Continued.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1902												
1	10.0	4.0	11.0	15.3	3.4	1.0	.2	2.0	.7	2.8	.8	4.0
2	12.0	6.3	13.4	17.6	3.3	1.0	-.1	1.7	.5	1.7	.5	5.3
3	14.1	8.0	23.0	17.5	4.5	1.2	-.2	.8	.3	2.0	.2	6.1
4	14.9	9.5	25.5	17.1	5.5	1.3	-.2	.3	-.1	2.5	-.1	7.5
5	15.3	14.0	25.3	16.0	4.7	1.6	-.2	2.9	-.4	1.6	-.2	8.0
6	14.6	19.0	24.5	14.1	3.8	0.9	1.4	4.3	-.06	2.9	-.02	8.7
7	12.4	20.0	22.0	11.3	3.5	.7	.9	4.4	-.9	2.7	.3	9.0
8	7.0	19.5	19.0	9.0	3.0	.6	.7	3.5	-.11	2.4	.6	9.3
9	4.4	18.0	16.0	9.0	3.1	2.0	.2	2.0	-.12	1.8	.8	9.0
10	3.9	15.6	13.0	9.0	2.7	3.9	-.2	.9	-.12	1.0	.6	5.5
11	3.6	12.3	9.0	9.0	2.7	4.0	-.7	.5	-.13	.7	.5	3.5
12	3.2	7.3	7.5	8.5	2.7	3.0	1.0	1.0	1.2	.8	.4	3.2
13	3.0	5.0	6.5	7.0	2.5	1.3	2.5	2.4	2.0	.9	.3	3.0
14	2.8	4.3	6.0	6.0	2.3	1.0	4.5	1.3	1.5	1.0	.2	4.3
15	2.6	4.1	7.1	5.6	2.0	1.0	3.5	.7	.7	1.2	.1	4.9
16	2.5	4.1	9.8	5.5	2.2	1.2	4.4	1.0	.4	2.0	.0	3.3
17	2.4	4.8	12.7	5.5	3.0	4.5	5.1	2.3	.8	1.0	-.1	3.0
18	2.4	5.0	14.2	6.0	3.0	4.5	5.5	3.0	.6	.8	-.1	2.6
19	2.4	5.0	19.0	7.9	2.7	2.5	3.3	1.7	.2	.5	-.1	3.5
20	2.4	4.3	21.0	9.0	3.0	3.7	1.2	.8	-.2	.1	1.0	3.0
21	2.5	4.6	19.7	10.0	2.9	2.8	.8	.4	.3	-.2	2.0	2.0
22	3.1	4.5	13.0	10.0	2.8	2.0	.4	1.1	-.4	1.4	1.4	1.4
23	3.7	6.5	15.9	8.1	2.7	2.0	2.4	.5	.7	-.5	1.0	4.0
24	3.7	6.6	13.7	6.0	2.5	1.5	1.0	.2	.5	-.5	.7	5.5
25	3.4	7.0	11.6	5.0	2.3	1.1	.5	-.2	.2	-.6	.5	5.0
26	3.0	8.0	10.1	4.6	2.0	.7	1.7	-.4	.1	-.6	1.0	2.5
27	2.9	8.6	9.5	4.3	1.7	.5	1.0	-.4	1.0	-.3	4.4	2.0
28	2.8	9.6	9.1	3.9	1.5	.4	1.2	-.3	3.5	1.5	5.5	1.7
29	2.6	10.9	3.6	1.4	.3	2.0	.1	4.0	2.0	4.5	1.5
30	2.6	10.9	3.6	1.3	.2	1.8	.2	4.2	1.8	3.5	1.3
31	3.0	12.1	1.1	1.3	.5	1.5	1.0
1903												
1	1.0	4.3	7.9	15.1	3.4	3.3	4.2	.6	.4	.5	.3	.8
2	.9	3.8	9.0	14.9	3.1	2.8	3.2	.9	.4	.4	.3	.8
3	2.5	3.4	10.0	15.5	3.0	4.5	2.5	1.0	.0	.3	.6	.6
4	3.5	3.4	12.0	15.0	3.2	6.0	2.2	2.1	-.1	.1	.8	.7
5	4.0	4.0	13.5	14.1	4.8	7.5	2.3	4.2	-.2	.0	1.9	.8
6	5.0	5.8	13.4	12.9	6.0	8.4	1.8	4.6	-.1	-.1	3.3	.7
7	4.5	6.6	12.4	10.9	5.5	9.3	2.8	3.8	-.2	.1	3.0	.3
8	4.0	7.3	11.8	8.9	4.3	10.5	4.8	2.0	-.2	.3	3.0	.9
9	3.2	8.8	11.9	7.2	4.1	11.7	5.9	1.5	-.2	.6	2.2	.9
10	2.6	11.0	10.3	3.8	4.5	13.0	6.8	.9	-.2	.6	1.3	1.0
11	2.3	21.0	9.5	9.2	4.4	13.1	5.2	1.0	1.0	.4	1.1	1.4
12	2.3	24.0	3.8	10.0	3.9	11.2	3.5	1.0	-.1	.2	1.0	2.0
13	3.6	23.4	3.6	10.5	3.5	8.5	3.2	1.2	.0	.1	1.1	1.8
14	4.0	22.7	8.5	10.1	3.3	6.3	4.0	1.0	.1	.1	1.1	1.8
15	4.4	12.5	8.4	9.5	5.3	4.7	5.8	1.2	.5	.0	1.1	1.1
16	3.9	20.0	8.6	9.0	8.5	3.6	6.7	2.6	2.2	.0	1.0	1.3
17	3.2	18.4	3.4	8.5	9.8	3.2	7.3	3.8	6.5	.5	1.1	1.3
18	3.2	16.9	3.3	7.3	10.8	2.7	6.8	5.4	7.6	1.2	1.3	1.1
19	3.2	15.4	7.7	6.0	11.5	2.5	3.7	6.0	9.0	4.3	1.3	1.1
20	2.3	15.6	6.3	5.3	10.4	2.3	2.5	7.0	10.7	3.0	1.6	1.0
21	2.5	16.9	6.0	5.2	5.9	2.2	2.4	8.0	9.9	1.8	1.6	1.0
22	2.4	16.3	5.9	5.4	4.2	2.4	1.7	8.8	9.0	1.6	1.6	1.2
23	2.4	15.3	7.5	5.3	3.6	2.1	1.3	9.1	2.0	.9	1.0	1.5
24	2.3	14.3	3.3	4.5	3.0	2.6	1.2	5.0	1.5	.6	1.0	1.7
25	2.4	12.0	9.3	4.1	2.7	2.4	1.0	2.5	1.3	.5	.9	1.6
26	2.7	8.2	11.3	3.3	2.4	2.0	.9	1.8	1.0	.4	.9	2.5
27	3.3	6.3	13.4	3.9	2.3	2.1	.7	1.5	.9	.3	.9	3.7
28	5.7	6.3	15.1	4.7	2.3	3.5	.6	1.0	.8	.2	.9	3.5
29	6.0	17.0	4.3	2.3	3.9	.5	.9	.7	.2	.8	3.2
30	5.4	17.6	3.6	3.3	4.7	.5	.6	.5	.2	.8	2.6
31	5.0	16.7	3.36	.53	2.0

Daily gage height, in feet, of Oconee River at Dublin—Continued.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1904												
1.....	1.7	2.5	3.9	2.5	1.0	.0	-.1	-.5	.6	-.13	-.11	-.5
2.....	1.7	2.8	3.5	2.0	1.0	.8	.2	.8	.1	-.14	-.12	-.5
3.....	1.7	2.7	3.5	2.0	1.0	2.0	.6	1.4	-.3	-.13	-.11	.3
4.....	1.6	2.7	3.9	2.0	.7	1.3	.2	.9	-.4	-.13	-.10	1.2
5.....	1.6	2.7	4.0	1.8	.7	.5	-.4	1.5	-.5	-.13	-.8	1.2
6.....	1.6	2.0	3.9	1.6	.7	.3	-.6	2.4	-.5	-.13	-.5	1.3
7.....	1.5	2.0	3.9	1.6	.4	.1	-.7	1.6	.4	-.13	-.3	1.7
8.....	1.4	3.0	4.5	2.0	.4	.1	-.7	2.4	1.1	-.14	-.3	2.9
9.....	1.4	5.0	5.5	2.0	.3	.0	-.8	5.0	.6	-.13	-.4	3.0
10.....	1.6	7.0	5.5	2.7	.3	-.1	-.8	6.2	.2	-.13	-.7	2.0
11.....	1.4	8.5	6.8	3.0	.3	-.03	-.9	6.5	-.1	-.14	-.7	1.0
12.....	1.4	9.0	5.5	3.0	.3	-.5	-.7	6.8	-.4	-.13	-.5	.8
13.....	2.0	9.9	4.0	2.0	1.0	-.1	.2	6.9	-.7	-.14	-.5	.8
14.....	2.0	9.9	3.5	2.0	1.0	-.1	.3	6.6	-.7	-.14	-.3	.6
15.....	2.0	9.9	3.4	1.4	1.0	-.1	-.4	3.5	-.7	-.14	-.1	.5
16.....	2.0	7.5	3.4	1.0	.7	-.3	-.6	1.8	-.8	-.14	-.2	.5
17.....	2.0	5.5	3.4	1.0	.7	-.5	-.8	3.8	-.9	-.14	-.1	.8
18.....	2.0	4.5	3.4	1.0	.7	-.5	-.9	3.3	-.9	-.15	-.1	.3
19.....	3.0	4.0	3.0	1.0	.7	-.5	-.10	3.0	-.9	-.14	-.2	.9
20.....	2.8	3.5	2.9	1.0	.7	-.6	-.10	2.0	-.10	-.15	-.4	.9
21.....	2.6	4.0	2.5	1.0	.7	-.5	-.10	.9	-.10	-.15	-.4	.8
22.....	2.0	5.5	2.0	1.0	.4	-.5	-.10	.4	-.10	-.15	-.5	.6
23.....	2.9	7.0	2.0	1.0	.4	-.5	-.8	.1	-.10	-.15	-.5	.4
24.....	6.6	7.8	2.9	1.0	.4	-.1	-.3	-.1	-.11	-.15	-.4	.3
25.....	7.6	8.0	3.8	1.0	.0	-.1	-.6	.1	-.11	-.15	-.3	.2
26.....	7.8	8.3	5.0	1.0	.0	-.4	-.3	.3	-.11	-.15	-.1	.2
27.....	6.9	7.0	4.5	1.0	.0	-.8	-.2	.9	-.12	-.14	-.1	.3
28.....	4.4	5.0	4.0	1.0	-.2	-.9	-.1	2.5	-.12	-.14	-.1	.6
29.....	3.6	4.0	3.8	1.0	-.2	-.8	-.4	3.0	-.12	-.14	-.2	2.5
30.....	3.2	3.4	1.0	-.5	-.5	-.6	1.0	-.12	-.13	-.4	2.5
31.....	2.9	3.00	-.6	1.0	-.11	2.5
1905												
1.....	2.1	.7	5.4	1.8	1.4	2.2	.8	-.7	-.5	-.12	-.7	-.3
2.....	1.7	.7	4.4	1.7	1.7	1.6	1.3	-.6	-.3	-.12	-.6	-.4
3.....	1.1	.7	3.9	1.7	1.9	1.2	.9	-.8	1.2	-.13	-.6	-.2
4.....	1.0	.6	3.6	1.6	2.5	.9	3.3	-.3	2.8	-.12	-.8	.5
5.....	.4	.6	3.3	1.5	3.9	.6	4.3	-.9	1.8	-.11	-.9	4.0
6.....	.4	.7	3.0	1.6	4.0	.6	2.2	-.10	1.6	-.4	-.9	5.8
7.....	1.2	1.1	2.8	1.8	4.2	.6	.9	-.11	.8	-.1	-.9	6.4
8.....	1.5	1.8	2.7	2.3	3.3	.1	1.1	-.10	.1	-.4	-.9	6.6
9.....	1.5	3.8	2.5	2.1	3.3	-.1	4.4	-.10	-.3	-.6	-.9	5.4
10.....	1.6	5.9	2.8	2.1	3.3	-.3	5.5	-.8	-.5	-.6	-.8	3.4
11.....	1.5	7.7	3.3	3.1	2.4	-.4	5.0	.1	-.7	-.8	-.4	5.5
12.....	1.5	8.8	4.3	3.9	1.8	-.5	3.0	3.0	-.8	-.9	-.0	6.4
13.....	1.1	12.5	5.8	3.7	1.3	-.5	3.0	3.0	-.7	-.9	1.4	6.8
14.....	1.7	14.5	7.3	5.0	.9	-.5	3.8	4.2	-.6	-.7	1.2	7.1
15.....	4.2	16.8	7.3	5.3	.6	-.5	2.7	5.0	-.7	-.7	.2	7.0
16.....	5.0	19.5	6.6	4.0	.3	-.1	2.3	4.0	-.6	-.6	-.1	6.7
17.....	4.5	19.5	5.4	3.3	.6	-.3	1.4	3.8	-.7	-.7	-.1	6.0
18.....	3.3	18.0	4.4	2.9	1.2	-.3	.6	2.3	-.8	-.8	-.2	5.5
19.....	2.6	16.0	3.5	2.2	1.2	-.3	.2	4.9	-.9	-.9	-.4	4.2
20.....	1.6	13.8	3.0	2.0	.8	+.3	-.4	5.3	-.9	-.9	-.5	3.0
21.....	1.6	10.5	3.8	1.6	.4	-.1	-.2	3.0	-.10	-.9	-.5	6.3
22.....	1.6	8.5	4.8	1.6	.2	-.2	-.3	1.0	-.11	-.9	-.6	8.7
23.....	1.6	8.8	5.2	1.6	.4	+.2	-.2	.5	-.11	-.10	-.7	9.5
24.....	1.4	9.4	4.3	1.4	1.9	1.4	-.3	-.1	-.10	-.11	-.5	11.0
25.....	1.2	9.8	3.8	1.2	4.0	2.0	-.4	.1	-.12	-.11	-.2	13.5
26.....	1.2	10.3	3.3	1.1	5.5	1.7	-.5	1.2	-.12	-.10	-.4	14.6
27.....	.9	9.8	2.9	1.3	5.8	1.0	+.3	1.3	-.12	-.10	-.4	14.0
28.....	.7	7.5	2.6	1.3	4.3	.4	-.1	1.5	-.12	-.8	-.5	12.0
29.....	.6	2.3	1.2	2.8	.3	-.3	.3	-.12	-.7	-.4	8.0
30.....	.6	2.2	1.0	1.9	.3	-.3	.1	-.12	-.7	-.4	7.0
31.....	.7	1.9	1.7	-.5	-.3	-.7	7.2

ALTAMAHA DRAINAGE BASIN, STREAM FLOW

Daily gage height, in feet, of Oconee River at Dublin—Continued.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1906												
1.....	6.9	13.9	3.1	9.7	1.4	1.6	1.3	6.7	5.6	3.9	0.5	1.0
2.....	6.2	11.8	2.7	10.0	2.4	1.5	.9	7.3	7.5	2.7	.5	.9
3.....	5.6	8.9	2.7	9.2	2.4	1.5	.9	8.3	5.0	5.6	.2	.7
4.....	5.6	7.6	2.5	7.7	2.2	1.4	1.9	8.9	4.0	6.3	.2	.8
5.....	7.5	6.4	3.0	6.5	1.8	1.4	2.5	8.5	3.0	8.2	.7	.8
6.....	8.5	4.4	3.3	5.0	1.5	1.6	2.9	6.9	2.5	9.1	.7	.7
7.....	10.0	4.7	3.3	3.5	1.2	1.3	2.6	6.9	2.0	9.1	.6	.7
8.....	12.6	4.4	3.0	3.0	1.0	2.1	1.9	5.9	1.5	9.8	.5	1.0
9.....	14.4	5.7	4.0	3.0	1.5	1.3	3.9	4.5	1.5	10.0	.5	1.0
10.....	14.4	7.2	5.6	2.7	2.3	1.0	4.2	3.4	1.0	10.3	.7	1.0
11.....	13.3	6.2	6.9	2.5	3.0	.8	4.9	2.5	.9	9.0	.6	1.0
12.....	10.0	6.9	7.3	4.3	2.2	.6	6.2	1.7	.7	8.0	.6	1.0
13.....	6.4	6.5	6.5	5.0	1.5	.3	7.1	1.4	.7	4.0	.7	1.7
14.....	6.9	6.3	4.9	4.2	1.5	.3	6.0	1.5	1.0	2.0	.6	2.7
15.....	6.1	6.5	4.0	3.3	1.2	5.6	4.5	1.7	1.5	1.5	.7	3.6
16.....	5.7	5.5	3.5	2.9	.9	7.7	5.8	1.9	2.0	1.0	1.5	2.6
17.....	4.3	4.9	6.7	3.0	.8	11.1	6.5	2.0	2.5	.3	1.5	1.3
18.....	4.3	3.9	7.7	3.3	.8	14.7	7.2	2.4	2.0	1.0	1.3	1.5
19.....	4.4	3.3	9.5	3.2	.7	18.7	7.7	3.4	1.3	1.0	1.7	2.8
20.....	3.8	3.3	12.5	3.0	.7	18.2	8.0	4.5	1.2	1.5	2.0	2.0
21.....	3.7	3.5	15.0	2.4	.8	17.0	9.0	5.6	1.9	1.3	2.6	4.5
22.....	3.4	3.4	15.7	2.0	.9	14.6	9.9	4.3	4.5	2.0	2.3	5.3
23.....	4.2	4.6	15.7	2.2	1.0	13.0	10.2	5.5	5.0	2.5	2.0	4.5
24.....	4.5	4.4	16.4	1.8	1.0	6.8	9.0	6.0	6.0	1.5	1.7	3.5
25.....	9.2	4.0	17.5	1.7	1.2	3.9	8.0	5.0	4.3	1.0	1.5	3.0
26.....	14.7	3.2	16.7	1.6	1.4	2.0	7.4	4.2	3.8	1.0	1.7	3.0
27.....	19.1	3.0	14.0	1.4	1.3	1.6	8.0	3.0	3.7	.9	1.0	3.0
28.....	19.2	3.0	13.1	1.0	1.3	1.5	8.0	3.3	3.4	.7	1.0	1.7
29.....	13.8		9.0	.9	1.6	2.0	6.0	5.5	3.0	1.0	1.0	1.6
30.....	17.0		7.3	1.0	1.7	1.6	4.0	6.5	4.3	1.0	1.0	1.5
31.....	15.2		8.5		1.6		5.0	6.0		.7		2.0

WATER POWERS OF GEORGIA

Rating tables for Oconee River at Dublin.

FEBRUARY 11, 1898, TO DECEMBER 31, 1900.^a

Gage height	Dis-charge						
<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>
1.30	865	0.90	2,012	3.00	3,560	7.50	8,410
1.20	890	1.00	2,080	3.20	3,720	8.00	8,980
1.10	920	1.10	2,148	3.40	3,890	8.50	9,550
1.00	950	1.20	2,218	3.60	4,070	9.00	10,120
.90	982	1.30	2,288	3.80	4,260	9.50	10,690
.80	1,015	1.40	2,358	4.00	4,460	10.00	11,260
.70	1,055	1.50	2,428	4.20	4,672	11.00	12,400
.60	1,095	1.60	2,500	4.40	4,888	12.00	13,540
.50	1,140	1.70	2,572	4.60	5,108	13.00	14,680
.40	1,185	1.80	2,644	4.80	5,332	14.00	15,820
.30	1,242	1.90	2,717	5.00	5,560	15.00	16,960
.20	1,300	2.00	2,790	5.20	5,788	16.00	18,100
.10	1,362	2.10	2,864	5.40	6,016	17.00	19,240
.00	1,425	2.20	2,938	5.60	6,244	18.00	20,380
.10	1,488	2.30	3,013	5.80	6,472	19.00	21,520
.20	1,552	2.40	3,089	6.00	6,700	20.00	22,660
.30	1,616	2.50	3,166	6.20	6,928	21.00	23,800
.40	1,681	2.60	3,243	6.40	7,156	22.00	24,940
.50	1,746	2.70	3,321	6.60	7,384	23.00	26,080
.60	1,812	2.80	3,400	6.80	7,612	24.00	27,220
.70	1,878	2.90	3,480	7.00	7,840	25.00	28,360
.80	1,945						

Estimates based on this table above gage height 12 feet are from 5 to 25 per cent. too low, the percentage of error increasing gradually with the increase of stage above 12 feet.

JANUARY 1 TO DECEMBER 31, 1901.^b

0.50	2,080	1.60	2,680	2.70	3,417	3.80	4,287
.60	2,125	1.70	2,742	2.80	3,490	3.90	4,378
.70	2,173	1.80	2,805	2.90	3,564	4.00	4,472
.80	2,223	1.90	2,869	3.00	3,639	4.10	4,569
.90	2,275	2.00	2,934	3.10	3,715	4.20	4,670
1.00	2,329	2.10	3,000	3.20	3,792	4.30	4,775
1.10	2,385	2.20	3,067	3.30	3,870	4.40	4,883
1.20	2,442	2.30	3,135	3.40	3,949	4.50	4,993
1.30	2,500	2.40	3,204	3.50	4,030	4.60	5,105
1.40	2,559	2.50	3,274	3.60	4,113	4.70	5,218
1.50	2,619	2.60	3,345	3.70	4,199	4.80	5,332

JANUARY 1 TO DECEMBER 31, 1902.^c

1.30	900	0.00	1,475	1.20	2,210	2.80	3,410
1.20	935	.10	1,530	1.30	2,280	3.00	3,570
1.10	970	.20	1,585	1.40	2,350	3.20	3,740
1.00	1,010	.30	1,640	1.50	2,420	3.40	3,910
.90	1,050	.40	1,700	1.60	2,490	3.60	4,090
.80	1,090	.50	1,760	1.70	2,565	3.80	4,280
.70	1,135	.60	1,820	1.80	2,640	4.00	4,480
.60	1,180	.70	1,880	1.90	2,715	4.20	4,690
.50	1,225	.80	1,945	2.00	2,790	4.40	4,900
.40	1,270	.90	2,010	2.20	2,940	4.60	5,120
.30	1,320	1.00	2,075	2.40	3,090	4.80	5,340
.20	1,370	1.10	2,140	2.60	3,250	5.00	5,560
.10	1,420						

^a Above gage height 5.0 feet the rating curve is a tangent, the difference being 114 per tenth.

^b Above gage height 4.8 feet this table is the same as the 1900 table.

^c Above gage height 5.0 feet this table is the same as the 1900 table.

ALTAMAHA DRAINAGE BASIN, STREAM FLOW

Rating tables for Oconee River at Dublin—Continued.

JANUARY 1 TO DECEMBER 31, 1903.^a

Gage height	Dis-charge						
<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>
-0.20	1,530	1.20	2,410	5.00	5,470	12.00	14,620
-.10	1,530	1.40	2,550	5.50	6,020	13.00	16,270
.00	1,630	1.60	2,690	6.00	6,620	14.00	17,920
.10	1,685	1.80	2,830	6.50	7,220	15.00	19,620
.20	1,740	2.00	2,970	7.00	7,820	16.00	21,320
.30	1,800	2.20	3,120	7.50	8,420	17.00	23,020
.40	1,865	2.40	3,270	8.00	9,020	18.00	24,720
.50	1,930	2.60	3,420	8.50	9,645	19.00	26,420
.60	1,995	2.80	3,570	9.00	10,270	20.00	28,120
.70	2,060	3.00	3,720	9.50	10,945	21.00	29,820
.80	2,130	3.50	4,120	10.00	11,620	22.00	31,520
.90	2,200	4.00	4,520	10.50	12,345	23.00	33,220
1.00	2,270	4.50	4,970	11.00	13,070	24.00	34,920

JANUARY 1 TO DECEMBER 31, 1904.

-1.50	560	-0.30	1,305	1.60	2,800	5.00	5,790
-1.40	600	-.20	1,381	1.80	2,964	5.50	6,300
-1.30	640	-.10	1,457	2.00	3,130	6.00	6,830
-1.20	695	.00	1,534	2.20	3,296	6.50	7,380
-1.10	750	.20	1,638	2.40	3,462	7.00	7,930
-1.00	810	.40	1,842	2.60	3,630	7.50	8,505
-.90	874	.60	1,993	2.80	3,799	8.00	9,090
-.80	941	.80	2,154	3.00	3,969	8.50	9,660
-.70	1,011	1.00	2,312	3.50	4,402	9.00	10,330
-.60	1,081	1.20	2,473	4.00	4,850	9.50	10,980
-.50	1,154	1.40	2,636	4.50	5,310	10.00	10,630
-.40	1,229						

JANUARY 1 TO DECEMBER 31, 1905.^b

-1.30	690	.90	2,360	3.00	4,150	6.20	7,310
-1.20	750	1.00	2,440	3.10	4,240	6.40	7,530
-1.10	810	1.10	2,520	3.20	4,330	6.60	7,750
-1.00	875	1.20	2,605	3.30	4,420	6.80	7,970
-.90	945	1.30	2,690	3.40	4,510	7.00	8,190
-.80	1,015	1.40	2,775	3.50	4,600	7.50	8,790
-.70	1,090	1.50	2,860	3.60	4,695	8.00	9,390
-.60	1,165	1.60	2,945	3.70	4,790	8.50	9,990
-.50	1,240	1.70	3,030	3.80	4,885	9.00	10,640
-.40	1,320	1.80	3,115	3.90	4,980	9.50	11,290
-.30	1,400	1.90	3,200	4.00	5,075	10.00	11,990
-.20	1,480	2.00	3,285	4.20	5,265	11.00	13,430
-.10	1,560	2.10	3,370	4.40	5,455	12.00	14,930
.00	1,640	2.20	3,455	4.60	5,650	13.00	16,500
.10	1,720	2.30	3,540	4.80	5,850	14.00	18,100
.20	1,800	2.40	3,625	5.00	6,050	15.00	19,800
.30	1,880	2.50	3,710	5.20	6,250	16.00	21,500
.40	1,960	2.60	3,795	5.40	6,450	17.00	23,200
.50	2,040	2.70	3,880	5.60	6,650	18.00	24,900
.60	2,120	2.80	3,970	5.80	6,870	19.00	26,600
.70	2,200	2.90	4,060	6.00	7,090	20.00	28,300
.80	2,280						

^a The table becomes tangent above 14 feet, with a difference of 170 per tenth.

^b Above gage height 14 feet the rating curve is a tangent, the difference being 170 per tenth.

WATER POWERS OF GEORGIA

Rating tables for Oconee River at Dublin—Continued.

JANUARY 1 TO DECEMBER, 1906.

Gage height	Dis-charge						
<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>
0.20	1,800	1.60	2,945	3.00	4,150	5.80	6,870
.30	1,880	1.70	3,030	3.20	4,330	6.00	7,090
.40	1,960	1.80	3,115	3.40	4,510	7.00	8,190
.50	2,040	1.90	3,200	3.60	4,695	8.00	9,390
.60	2,120	2.00	3,285	3.80	4,885	9.00	10,640
.70	2,200	2.10	3,370	4.00	5,075	10.00	11,990
.80	2,280	2.20	3,455	4.20	5,265	11.00	13,430
.90	2,360	2.30	3,540	4.40	5,455	12.00	14,930
1.00	2,440	2.40	3,625	4.60	5,650	13.00	16,500
1.10	2,520	2.50	3,710	4.80	5,850	14.00	18,100
1.20	2,605	2.60	3,795	5.00	6,050	15.00	19,800
1.30	2,690	2.70	3,880	5.20	6,250		
1.40	2,775	2.80	3,970	5.40	6,450		
1.50	2,860	2.90	4,060	5.60	6,650		

NOTE—The above table is based on discharge measurements made during 1903-1906, and is well defined below gage height 7 feet. Above gage height 14 feet the rating curve is a tangent, the difference being 170 per tenth.

ALTAMAHA DRAINAGE BASIN, STREAM FLOW

Estimated monthly discharge of Oconee River at Dublin.

[Drainage area, 4,182 square miles.]

Month	Discharge in second-feet			Run-off	
	Maximum	Minimum	Mean	Sec.-ft. per sq. mile	Depth in inches
1898 <i>a</i>					
February 11-28.....	2,429	1,746	2,040	0.49	0.33
March.....	4,360	1,746	2,582	.62	.71
April.....	11,260	2,080	5,011	1.20	1.34
May.....	4,460	1,140	1,794	.43	.49
June.....	2,012	890	1,201	.29	.32
July.....	7,840	865	3,104	.74	.85
August.....	12,514	2,500	5,697	1.36	1.57
September.....	27,904	2,012	10,648	2.55	2.84
October.....	18,100	1,878	7,449	1.78	2.05
November.....	16,960	2,500	7,097	1.70	1.90
December.....	14,224	4,360	7,838	1.75	2.02
1899 <i>a</i>					
January.....	17,302	4,070	10,736	2.57	2.96
February.....	25,510	8,688	14,954	3.58	3.73
March.....	19,240	7,498	12,188	2.91	3.36
April.....	11,032	5,382	7,689	1.83	2.04
May.....	6,016	2,429	3,420	.82	.94
June.....	2,644	1,300	1,862	.45	.50
July.....	5,560	1,015	1,669	.40	.46
August.....	5,674	982	2,097	.50	.58
September.....	3,480	890	1,630	.39	.44
October.....	9,664	865	2,628	.63	.72
November.....	4,888	1,015	1,666	.40	.45
December.....	6,244	1,746	3,047	.73	.84
The year.....	25,510	865	5,294	1.27	17.02
1900 <i>a</i>					
January.....	6,358	2,218	3,506	.84	.97
February.....	28,246	2,500	12,002	2.87	2.99
March.....	13,198	6,472	9,874	2.36	2.73
April.....	19,924	3,805	9,512	2.27	2.53
May.....	9,322	2,717	4,754	1.14	1.31
June.....	23,572	2,218	8,371	2.00	2.23
July.....	21,520	2,080	6,396	1.53	1.76
August.....	5,560	1,488	2,314	.55	.63
September.....	6,700	1,242	2,371	.57	.64
October.....	6,244	1,242	2,233	.53	.61
November.....	7,384	1,878	3,220	.77	.86
December.....	9,436	2,500	5,846	1.40	1.61
The year.....	28,246	1,242	5,867	1.40	18.87
1901 <i>a</i>					
January.....	15,706	5,105	9,396	2.25	2.60
February.....	17,372	4,670	9,315	2.23	2.82
March.....	18,670	3,490	6,494	1.55	1.79
April.....	25,624	4,287	12,344	2.95	3.29
May.....	9,094	2,742	4,250	1.02	1.18
June.....	12,856	4,199	3,065	1.03	2.15
July.....	8,524	2,559	4,253	1.02	1.18
August.....	11,602	2,080	5,999	1.43	1.65
September.....	21,976	2,125	3,035	1.32	2.14
October.....	5,674	2,173	3,046	.73	.84
November.....	2,742	2,223	2,369	.56	.62
December.....	9,664	2,329	4,435	1.06	1.22
The year.....	25,624	2,080	5,600	1.55	20.98

a Daily estimates of discharge above gage height 12 feet for the years 1898 to 1902, inclusive, are from 5 to 25 per cent. too low, owing to insufficient data to properly determine the upper part of the original rating curve. The error gradually increases with the increase of stage above 12 feet. The estimates for these years were not revised because the number of days when the gage height was more than 12 feet was relatively small and hence the monthly estimates are but slightly affected.

WATER POWERS OF GEORGIA

Estimated monthly discharge of Oconee River at Dublin—Continued.

Month	Discharge in second-feet			Run-off	
	Maximum	Minimum	Mean	Sec.-ft. per sq. mile	Depth in inches
1902 ^a					
January.....	17,302	3,090	6,315	1.51	1.74
February.....	22,660	4,480	9,813	2.35	2.45
March.....	29,272	6,700	16,243	3.88	4.47
April.....	19,924	4,090	9,942	2.38	2.66
May.....	6,130	2,140	3,436	.82	.95
June.....	5,010	1,585	2,685	.64	.71
July.....	6,130	1,135	2,567	.61	.70
August.....	4,900	1,270	2,318	.54	.62
September.....	4,690	900	1,904	.46	.51
October.....	3,490	1,180	2,203	.53	.61
November.....	6,130	1,370	2,189	.52	.58
December.....	11,082	2,075	5,134	1.23	1.42
The year.....	29,272	900	5,409	1.29	17.48
1903					
January.....	6,620	2,200	4,090	.98	1.13
February.....	34,920	4,040	16,766	4.01	4.18
March.....	24,040	6,500	12,704	3.04	3.50
April.....	20,470	4,200	10,120	2.42	2.70
May.....	13,845	3,195	5,701	1.36	1.57
June.....	16,435	2,970	6,537	1.56	1.74
July.....	8,180	1,930	4,016	.96	1.11
August.....	10,405	1,930	3,964	.95	1.10
September.....	12,635	1,530	3,563	.85	.95
October.....	4,790	1,580	2,044	.49	.56
November.....	4,330	1,300	2,501	.60	.67
December.....	4,280	1,995	2,634	.63	.73
The year.....	34,920	1,530	6,220	1.49	19.94
1904					
January.....	8,850	2,636	3,897	.982	1.07
February.....	11,500	3,130	6,599	1.58	1.70
March.....	7,710	3,130	4,717	1.13	1.30
April.....	3,989	2,312	2,766	.661	.738
May.....	2,312	1,154	1,899	.454	.523
June.....	3,130	874	1,449	.346	.386
July.....	1,998	810	1,169	.230	.323
August.....	7,820	1,154	3,617	.865	.997
September.....	2,392	695	1,131	.270	.301
October.....	750	560	609	.146	.163
November.....	1,611	695	1,205	.288	.321
December.....	3,989	1,154	2,329	.557	.642
The year.....	11,500	560	2,616	.626	8.47
1905					
January.....	6,050	1,960	3,021	.722	.832
February.....	27,450	2,120	11,260	2.69	2.80
March.....	8,550	3,200	5,082	1.22	1.41
April.....	6,350	2,440	3,506	.838	.935
May.....	6,370	1,800	3,538	.846	.975
June.....	3,455	1,240	1,947	.466	.520
July.....	6,550	1,240	2,839	.679	.733
August.....	6,055	810	2,685	.642	.740
September.....	3,970	750	1,346	.322	.359
October.....	1,960	690	1,019	.244	.281
November.....	2,775	945	1,346	.322	.359
December.....	19,120	1,320	8,121	1.94	2.24
The year.....	27,450	690	3,310	.911	12.23

^a Daily estimates of discharge above gage height 12 feet for the years 1898 to 1902, inclusive, are from 5 to 25 per cent too low, owing to insufficient data to properly determine the upper part of the original rating curve. The error gradually increases with the increase of stage above 12 feet. The estimates for these years were not revised because the number of days when the gage height was more than 12 feet was relatively small and hence the monthly estimates are but slightly affected.

Estimated monthly discharge of Oconee River at Dublin—Continued.

Month	Discharge in second-feet			Run-off	
	Maximum	Minimum	Mean	Sec.-ft. per sq. mile	Depth in inches
1906					
January.....	26,900	4,510	11,800	2.82	3.25
February.....	17,900	4,150	6,920	1.66	1.73
March.....	24,000	3,710	10,400	2.49	2.87
April.....	12,000	2,360	4,990	1.19	1.33
May.....	4,150	2,200	2,810	.672	.77
June.....	25,100	1,880	7,480	1.79	2.00
July.....	12,300	2,360	6,820	1.63	1.88
August.....	10,500	2,780	5,910	1.41	1.63
September.....	8,790	2,200	4,190	1.00	1.12
October.....	12,400	1,880	5,280	1.26	1.45
November.....	3,970	1,800	2,540	.608	.68
December.....	6,350	2,200	3,320	.794	.92
The year.....	26,900	1,800	6,040	1.44	19.63

NOTE.—Values for 1906 are probably excellent except those for May which are fair, owing to erroneous gage heights.

APALACHEE RIVER NEAR BUCKHEAD.

This station was established February 13, 1901, by M. R. Hall. It is located at the iron wagon bridge over Apalachee River, about 3½ miles north of Buckhead.

At ordinary stages the channel is about 80 feet wide, and is only slightly curved above and below the bridge. The bed of the stream is part rock and part sand. The current is moderately swift and is somewhat broken and irregular on account of the ruins of old pier bases about 50 feet upstream. The right bank is low for a distance of 400 feet and will overflow at a gage height of 10 feet. The low portion is thickly covered with trees and a brushy growth, which will greatly retard the flood water passing over it. The left bank is high and will not overflow, except to a short distance up the steep slope.

Discharge measurements are made from the downstream side of the bridge, the initial point being the outside of the iron pier at the left bank, downstream side. The bridge is a single span 103 feet long, supported by tubular piers. Its trestle approaches are about 500 feet long on the right bank and about 100 feet on the left.

The original gage consisted of two sections. The first section, reading from 0 to 10 feet, was fastened to a small ash tree on the left bank about 100 feet below the bridge, and the second, reading from 6 to 20 feet, was nailed to the upstream post of the last wooden bent next to the iron bridge, on the right bank. March 22, 1905, a standard chain gage was attached to the upstream side of the bridge, in the third panel from the right bank; length of the chain, 30.70 feet. The gage is read once each day by G. A. J. Adams, except for three months during low water, when readings are made twice each

WATER POWERS OF GEORGIA

day. Bench marks were established as follows: (1) The top of the downstream end of the first floor beam from the right bank; elevation, 25.50 feet above datum of gage. (2) A copper plug set in solid rock 10 feet west of the upstream tubular pier on the right bank and 3 feet upstream from the line of the upper edge of the bridge; elevation, 3.73 feet above datum of gage.

Discharge measurements of the Apalachee River near Buckhead.

Date	Gage height	Dis-charge	Date	Gage height	Dis-charge
1901			1904		
February 13.....	<i>Feet</i> 3.78	<i>Sec.-ft.</i> 347	August 9.....	<i>Feet</i> 7.15	<i>Sec.-ft.</i> 1,877
February 19.....	3.00	647	August 9.....	7.80	1,903
March 20.....	4.62	1,038	September 21.....	.90	123
May 32.....	6.45	1,658	October 13.....	.80	91
August 9.....	2.56	545	October 13.....	.80	94
November 1.....	1.80	302	November 26.....	1.39	186
1902			1905		
February 8.....	3.95	821	March 23.....	2.30	379
June 7.....	1.52	262	May 11.....	1.74	278
July 19.....	1.50	253	June 8.....	1.44	223
1903			1906		
January 15.....	2.33	444	February 10.....	3.23	645
May 27.....	1.88	361	April 28.....	2.51	438
June 12.....	3.07	643	June 23.....	2.01	333
July 25.....	1.51	266	August 17.....	3.86	714
August 23.....	1.31	214	October 17.....	1.99	325
October 9.....	1.45	237			
December 1.....	1.00	255			
1904					
March 19.....	2.39	466			
May 12.....	1.83	311			
July 13.....	1.48	223			

Daily gage height, in feet, of Apalachee River near Buckhead.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1901												
1.....			2.6	4.9	2.7	6.1	3.5	2.0	3.5	2.2	1.7	1.9
2.....			2.6	5.3	2.6	3.6	3.0	1.9	3.0	2.2	1.7	2.0
3.....			2.6	14.0	2.6	3.1	2.7	1.8	2.3	2.4	1.7	2.0
4.....			2.6	13.8	2.5	3.0	2.6	1.9	2.6	2.5	1.75	2.5
5.....			2.5	7.5	2.5	2.9	2.5	1.8	2.4	2.6	1.9	2.4
6.....			2.5	5.3	2.6	2.8	2.4	1.8	2.2	2.4	1.9	2.2
7.....			2.4	4.5	2.5	8.5	2.1	2.0	2.1	2.2	1.8	2.1
8.....			2.4	4.0	2.4	8.5	2.0	6.5	2.1	2.2	1.8	2.0
9.....			2.4	3.6	2.4	3.5	2.9	2.7	2.0	2.1	1.8	2.2
10.....			2.5	3.4	2.3	3.1	2.5	2.5	2.0	2.1	1.8	3.0
11.....			4.5	3.2	9.3	2.9	2.4	4.0	1.9	2.0	1.8	2.3
12.....			5.7	3.1	2.2	2.8	2.3	6.0	1.9	1.9	1.8	2.2
13.....		3.73	3.5	3.1	2.6	2.7	2.1	3.5	1.8	1.9	1.8	2.2
14.....			3.0	7.0	2.4	4.0	2.0	3.1	1.8	1.85	1.85	2.1
15.....			2.7	6.7	2.3	4.5	1.9	3.0	1.8	1.85	1.85	8.0
16.....			2.6	5.5	2.2	4.5	3.0	5.0	1.9	1.8	1.8	7.0
17.....			2.5	4.1	2.2	6.0	2.7	10.5	4.0	1.8	1.8	6.0
18.....			2.5	3.7	2.1	4.5	2.5	5.7	10.5	1.8	1.8	4.5
19.....		3.0	2.4	3.9	2.4	4.0	4.0	4.5	12.5	1.8	1.9	4.1
20.....			2.4	5.0	2.8	3.8	6.0	4.0	7.0	1.8	2.1	4.0
21.....			2.7	4.3	4.4	3.5	6.0	4.0	5.0	1.8	2.1	3.8
22.....			2.6	3.5	6.8	3.2	3.0	4.5	3.2	1.8	2.2	3.6
23.....			2.5	3.3	3.5	3.5	2.5	4.0	3.0	1.8	2.2	3.6
24.....			2.9	3.2	3.0	2.8	2.2	3.5	2.3	1.75	2.0	4.2
25.....			3.0	3.1	2.6	2.5	2.1	4.0	2.7	1.75	1.9	3.9
26.....			7.5	3.0	2.4	5.0	2.6	3.8	2.6	1.75	1.9	3.6
27.....			11.5	2.9	2.3	4.0	2.9	3.6	2.4	1.75	1.9	3.6
28.....			8.0	2.9	2.3	2.9	3.0	4.5	2.2	1.75	1.9	4.5
29.....			7.0	2.8	2.2	3.8	3.0	7.0	2.4	1.75	1.9	6.5
30.....			6.0	2.7	2.2	4.0	2.5	5.5	2.2	1.75	1.9	13.0
31.....			6.3		3.5		2.2	3.8		1.7		15.5

ALTAMAHA DRAINAGE BASIN, STREAM FLOW

191

Daily gage height, in feet, of Apalachee River near Buckhead—Continued.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1902												
1	11.0	6.2	25.0	8.0	2.6	1.75	1.6	1.8	1.6	2.5	1.5	2.8
2	7.0	17.5	20.0	5.5	2.8	1.75	1.6	1.6	1.5	2.0	1.5	3.1
3	5.5	20.0	15.0	4.5	2.7	1.75	2.1	4.0	1.5	1.9	1.5	3.5
4	4.5	15.0	10.0	4.0	2.7	1.7	2.0	4.5	1.5	1.8	1.6	5.0
5	4.2	11.0	7.0	3.8	2.6	1.7	1.8	4.0	1.4	1.8	1.6	4.5
6	4.1	8.0	6.0	3.7	2.6	1.7	1.7	3.0	1.4	1.8	1.6	3.5
7	4.0	6.0	5.0	4.5	2.5	1.7	1.6	2.7	1.6	1.8	1.5	3.2
8	3.8	4.0	4.0	4.0	2.4	4.0	1.55	2.5	1.8	1.7	1.5	3.1
9	3.7	3.9	3.5	3.8	2.4	7.5	1.5	2.2	1.7	1.7	1.5	3.0
10	3.5	3.8	3.5	3.6	2.3	4.0	1.5	2.0	1.7	1.7	1.5	3.0
11	3.4	3.8	3.3	3.5	2.3	3.0	1.6	1.9	1.9	1.7	1.45	2.8
12	3.2	3.8	3.3	3.5	2.3	2.7	2.0	1.85	2.0	1.7	1.45	2.5
13	3.1	3.7	3.3	3.5	2.3	2.4	1.9	1.8	2.5	1.7	1.45	2.2
14	3.0	3.7	4.5	3.4	2.4	2.1	6.0	1.75	4.0	1.7	1.45	2.1
15	2.9	3.7	5.0	3.4	2.4	2.0	3.0	1.7	3.8	1.7	1.4	3.0
16	2.9	3.7	6.5	3.3	2.4	4.5	2.5	1.7	3.4	1.6	1.4	3.5
17	2.8	3.8	10.0	3.3	2.3	3.8	2.3	1.6	3.0	1.6	1.5	3.2
18	2.8	3.9	7.5	4.5	2.3	2.8	2.1	1.6	2.8	1.6	1.7	3.0
19	2.8	3.9	6.0	4.3	2.3	2.5	2.0	1.5	2.8	1.6	1.6	2.8
20	2.8	3.8	5.5	4.0	2.2	2.2	1.9	1.5	3.2	1.6	1.6	2.7
21	2.7	3.7	5.2	3.8	2.2	2.0	1.8	1.5	3.0	1.55	1.6	2.6
22	2.7	3.7	5.0	3.6	2.1	1.9	1.75	1.4	2.8	1.55	1.6	3.6
23	2.6	3.8	4.8	3.4	2.1	1.9	1.7	1.4	2.7	1.5	1.6	3.0
24	2.6	3.9	4.7	3.2	2.0	1.8	1.65	1.2	2.7	1.5	2.0	2.9
25	2.8	4.0	4.5	3.0	1.9	1.8	1.6	1.1	3.0	1.5	2.1	2.7
26	3.0	5.0	4.3	2.7	1.9	1.75	1.5	1.0	3.0	1.5	2.0	2.6
27	3.2	16.0	3.8	2.8	1.85	1.7	1.6	1.2	2.8	1.3	2.0	2.6
28	3.6	20.0	4.4	2.7	1.8	2.1	1.3	1.3	2.8	1.3	1.9	2.5
29	3.7		4.5	2.7	1.8	1.65	2.6	1.5	2.7	1.7	2.1	2.5
30	4.0		7.0	2.7	1.75	1.65	2.1	1.6	3.5	1.7	2.6	3.2
31	4.5		12.0		1.75		1.9	1.6		1.6		3.0
1903												
1	2.3	2.5	7.8	8.8	2.7	4.0	2.2	1.2	1.1	1.7	1.2	1.9
2	2.6	3.1	7.0	5.7	2.6	10.0	2.0	3.4	.9	1.7	1.2	1.9
3	2.5	3.4	6.0	5.0	2.7	8.5	2.1	3.1	1.6	1.7	1.2	1.9
4	2.3	4.2	4.5	4.5	3.1	4.4	2.2	4.7	1.5	1.7	2.9	1.9
5	2.6	4.5	4.2	4.4	3.4	5.5	2.0	2.9	1.5	1.8	2.7	1.8
6	2.7	5.5	4.0	4.2	2.8	9.0	2.4	3.1	1.4	1.1	2.4	1.9
7	2.6	5.9	4.0	4.1	2.7	9.2	2.0	2.1	.9	1.8	2.4	1.9
8	2.4	17.0	4.0	5.0	2.6	4.5	6.2	1.9	.9	1.7	2.0	1.8
9	2.4	15.0	3.8	9.5	2.7	3.3	4.2	1.8	1.2	1.7	1.4	2.0
10	2.0	11.0	5.5	7.0	2.6	3.2	2.3	1.6	1.5	1.7	2.0	2.0
11	2.0	10.0	7.0	4.9	2.5	4.0	2.7	1.7	1.4	1.5	2.0	2.0
12	3.0	13.0	5.0	4.2	2.4	3.7	2.5	1.6	1.3	1.4	1.9	2.0
13	2.9	9.0	4.4	3.3	2.4	3.5	4.2	1.9	1.2	1.7	1.8	2.0
14	2.6	7.1	4.0	6.0	2.7	2.7	8.5	1.9	1.3	1.7	1.9	1.8
15	2.4	5.2	3.9	4.9	3.2	2.5	10.0	2.4	1.9	1.7	1.9	1.9
16	2.3	4.5	3.8	4.5	4.6	2.3	3.8	3.3	7.5	1.9	1.8	1.9
17	2.3	7.2	3.6	3.9	4.0	2.1	2.7	3.5	8.5	1.8	1.9	1.9
18	2.2	6.5	3.4	3.5	2.8	2.1	2.7	7.0	4.3	2.1	2.0	1.8
19	2.2	5.2	3.2	3.0	2.5	2.0	2.3	3.7	2.5	1.8	2.0	1.9
20	2.15	4.5	3.0	3.1	2.4	2.0	2.1	2.3	2.1	1.9	1.9	1.9
21	2.4	4.0	3.1	3.5	2.3	2.6	2.1	2.2	1.9	1.8	1.9	1.8
22	2.3	4.0	7.0	3.2	2.2	2.7	2.0	2.1	1.8	1.8	2.0	1.9
23	2.3	3.6	10.0	3.0	2.2	2.2	1.9	1.8	1.7	1.7	1.5	1.9
24	2.2	3.2	15.0	2.9	2.2	2.0	1.8	1.7	1.6	1.7	1.9	1.8
25	2.2	2.9	13.2	2.8	2.1	1.9	1.8	1.8	1.8	1.5	1.9	1.8
26	2.1	3.0	7.0	3.5	2.0	2.0	1.7	1.9	1.9	1.8	2.0	1.8
27	2.0	3.1	4.9	3.4	1.9	2.8	1.6	1.7	1.8	1.8	2.0	1.7
28	3.0	6.2	4.1	3.0	1.8	2.8	1.5	1.6	1.5	1.7	2.0	1.7
29	2.8		4.5	2.8	1.9	3.0	1.4	1.3	1.6	1.5	1.5	1.8
30	2.5		8.0	2.7	2.0	3.4	1.4	1.5	1.7	1.4	1.9	1.9
31	2.4		11.0		2.0		1.3	1.4		1.3		

WATER POWERS OF GEORGIA

Daily gage height, in feet, of Apalachee River near Buckhead—Continued.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1904												
1.....	1.8	1.9	2.4	2.2	1.9	2.3	2.0	1.7	1.5	0.65	0.95	1.4
2.....	1.8	1.8	2.5	2.4	1.5	2.1	1.8	1.9	1.5	.65	1.25	1.5
3.....	1.9	1.8	2.5	2.2	1.8	1.5	1.3	2.1	1.4	α.5	1.2	1.9
4.....	1.8	1.9	2.4	2.1	1.9	1.3	1.4	3.0	1.6	.65	1.9	1.65
5.....	1.7	2.0	2.3	2.0	1.6	1.5	1.3	2.7	2.8	.65	1.85	2.25
6.....	1.7	2.1	2.4	2.0	1.7	1.4	1.2	2.4	2.3	.65	1.5	2.75
7.....	1.6	2.1	3.6	2.2	1.8	1.3	1.1	3.0	1.9	.75	α1.0	3.55
8.....	1.6	3.1	5.7	2.8	1.9	2.9	1.0	4.5	1.7	.8	1.45	2.65
9.....	1.5	4.0	4.8	4.0	2.0	2.4	3.0	5.7	1.6	.65	1.4	2.15
10.....	1.8	4.5	3.4	2.9	2.5	1.9	1.9	9.9	1.4	α.45	1.25	1.9
11.....	1.9	7.0	3.0	2.4	2.1	1.6	1.8	6.7	1.3	.65	1.35	1.8
12.....	1.9	6.5	2.8	2.3	2.0	1.6	1.7	6.4	1.3	.65	1.35	1.8
13.....	2.0	5.5	2.5	2.3	1.8	1.5	1.6	2.5	1.4	.6	1.9	1.7
14.....	2.0	3.1	2.3	2.2	1.7	1.5	1.5	2.6	1.4	.6	1.8	1.7
15.....	2.0	3.0	3.5	2.1	1.9	1.4	1.4	2.8	1.3	.65	1.85	1.7
16.....	2.0	2.8	3.3	2.0	1.8	1.4	1.2	3.5	1.2	.65	1.75	1.8
17.....	2.2	2.4	2.8	1.9	1.8	1.3	1.0	4.5	1.0	α.45	1.7	1.8
18.....	2.1	2.2	2.6	2.0	1.8	1.3	.8	2.6	.85	.55	1.7	2.0
19.....	2.1	2.5	2.4	2.1	1.7	1.0	1.0	2.8	α.65	.65	1.65	1.8
20.....	2.0	3.8	2.3	2.2	1.7	.7	1.2	2.0	.8	.65	1.45	1.9
21.....	2.1	4.0	2.2	2.3	1.6	2.0	1.0	1.7	.8	.65	α1.0	1.8
22.....	2.2	5.1	3.0	2.2	1.5	1.7	1.6	1.5	.8	.65	1.45	1.7
23.....	6.0	6.8	3.2	2.1	1.5	1.5	1.6	2.0	.75	.6	1.75	1.7
24.....	6.5	5.0	3.1	2.0	1.4	1.4	2.0	2.1	.75	α.4	1.65	1.6
25.....	2.7	3.5	2.9	1.9	1.4	1.3	1.2	2.3	.75	.7	1.7	1.5
26.....	2.5	3.0	2.7	2.1	1.4	1.3	1.6	2.0	α.55	.85	1.5	1.6
27.....	2.4	2.8	3.0	2.2	1.3	1.2	1.5	1.7	.6	1.4	1.45	1.6
28.....	2.4	2.6	2.7	2.3	1.3	1.2	1.5	2.0	1.05	1.05	α1.25	3.0
29.....	2.3	2.5	2.5	2.2	1.3	1.6	1.6	1.7	.9	.9	1.5	3.2
30.....	2.0	2.4	2.1	1.2	2.5	1.6	1.6	.75	.95	1.45	2.5
31.....	2.0	2.3	1.8	1.5	1.6	α.65	2.2
1905												
1.....	2.0	1.8	2.8	2.0	2.4	2.0	2.8	1.5	1.05	0.86	1.3	1.4
2.....	1.8	1.9	2.7	1.9	2.1	1.8	6.4	1.4	2.7	α.52	1.15	1.55
3.....	2.2	1.9	2.6	1.8	2.2	1.95	9.0	1.35	3.1	.62	1.1	4.6
4.....	2.0	1.8	2.5	2.0	3.5	2.1	3.3	1.3	2.1	1.05	1.1	13.7
5.....	1.9	1.9	2.5	2.2	3.3	1.65	2.0	1.25	1.72	1.45	1.1	10.5
6.....	1.8	2.0	2.4	2.2	3.4	1.85	2.3	1.0	1.4	1.3	α.71	5.5
7.....	2.2	2.5	2.4	2.25	2.4	1.65	5.4	α.4	1.15	1.15	1.35	2.35
8.....	2.1	3.4	2.3	2.25	2.5	1.55	10.2	1.0	1.1	1.1	1.3	3.2
9.....	2.1	4.5	2.5	2.25	2.25	1.5	5.5	1.95	1.0	α.51	1.25	6.4
10.....	2.0	5.6	2.5	2.25	2.2	1.45	3.0	4.3	.92	1.25	1.4	9.7
11.....	2.0	6.2	2.4	2.3	2.2	1.35	2.65	4.4	α.65	1.3	2.6	9.0
12.....	2.1	7.3	2.6	2.25	1.9	.85	2.7	4.4	.91	1.3	2.3	5.0
13.....	4.7	9.0	2.7	2.25	1.8	1.35	2.75	5.3	.94	1.25	1.95	4.2
14.....	5.0	11.4	3.1	2.2	1.7	1.4	2.6	3.6	.88	1.25	1.6	3.6
15.....	4.2	9.0	2.8	2.2	1.5	1.35	2.35	4.7	.95	1.2	1.55	3.6
16.....	3.0	5.3	2.7	2.2	2.1	1.35	1.9	3.4	.92	α.68	1.45	4.7
17.....	2.6	4.2	2.5	1.9	2.2	2.05	1.5	2.7	.88	1.2	1.45	3.8
18.....	2.2	3.7	2.4	2.2	2.0	1.5	1.75	7.6	α.52	1.15	1.45	3.0
19.....	2.3	3.3	2.2	2.0	1.8	1.0	1.7	2.7	.65	1.15	1.35	2.7
20.....	2.3	3.3	1.9	2.0	1.7	1.5	3.6	2.3	.78	1.1	1.0	4.2
21.....	2.2	5.6	2.4	1.9	1.5	1.35	1.95	1.65	.66	1.1	1.5	11.0
22.....	2.1	7.3	2.5	2.0	1.2	3.3	1.7	1.9	.75	.92	1.4	14.0
23.....	2.0	6.0	2.4	1.9	2.1	4.6	1.7	1.8	.82	α.59	1.4	9.9
24.....	1.9	4.8	2.35	1.8	3.3	3.4	1.0	1.7	.78	1.15	1.35	5.7
25.....	1.9	3.4	2.3	1.9	4.7	3.3	2.15	1.6	α.41	1.1	1.3	4.2
26.....	1.8	3.2	2.25	2.0	4.7	2.2	2.1	1.55	.68	1.15	1.3	3.7
27.....	1.8	3.0	2.2	1.9	3.1	1.85	1.75	1.4	.6	1.15	1.35	3.4
28.....	1.9	2.9	2.2	1.9	2.5	3.1	1.6	α.78	.67	1.1	1.65	3.8
29.....	1.9	2.2	1.8	2.9	2.35	1.5	1.2	.65	1.1	1.55	4.2
30.....	1.8	2.2	1.7	3.1	1.95	1.4	1.1	.65	α.85	1.4	4.0
31.....	1.8	2.0	2.2	1.65	1.0	1.35	4.0

α During low water the Monday gage heights are lower than natural flow on account of storing water on Sunday at High Shoals Factory, 25 miles above this station.

ALTAMAHA DRAINAGE BASIN, STREAM FLOW

Daily gage height, in feet, of Apalachee River near Buckhead—Continued.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1906												
1	3.5	4.2	2.5	4.9	2.9	2.05	2.3	9.0	2.6	3.5	2.3	2.1
2	4.2	3.9	2.55	4.3	2.6	2.0	2.1	5.4	4.0	4.8	2.35	2.15
3	4.8	3.6	2.7	3.8	2.35	4.5	2.5	3.8	3.2	5.7	2.3	2.2
4	13.0	3.4	2.95	3.6	2.3	3.6	3.1	4.3	2.5	7.2	2.3	2.3
5	14.2	3.3	2.7	3.4	2.4	2.6	2.5	6.2	2.35	6.1	2.3	2.3
6	9.8	3.4	2.7	3.3	2.3	2.35	2.0	4.2	2.25	4.8	2.3	2.3
7	6.4	3.4	2.9	3.2	3.3	2.2	2.15	3.5	2.2	3.5	2.3	2.4
8	5.2	3.5	3.7	3.0	4.4	2.1	3.6	3.4	2.15	3.1	2.3	2.5
9	4.9	3.4	6.3	2.95	3.7	2.0	10.0	3.6	1.9	2.7	2.35	2.2
10	4.1	3.3	6.4	4.3	2.3	2.05	8.7	2.7	1.7	2.65	2.35	2.35
11	3.3	3.3	4.3	4.1	2.45	2.1	3.5	2.85	2.0	2.55	2.35	2.35
12	3.8	3.2	2.5	3.5	2.3	2.3	3.6	2.65	2.35	2.5	2.6	3.4
13	4.7	3.1	2.85	3.1	2.25	7.6	2.9	2.4	3.1	2.4	2.55	3.0
14	4.2	3.0	3.0	2.5	2.2	11.5	2.4	2.7	2.7	2.2	2.5	2.75
15	3.7	3.0	7.0	3.9	2.15	13.1	4.2	7.0	2.3	2.2	2.6	2.6
16	3.5	2.95	12.5	3.4	2.15	13.2	6.7	7.7	1.9	2.3	2.55	2.2
17	3.4	2.8	10.5	3.1	2.1	10.5	5.4	3.6	1.7	2.2	2.5	1.9
18	3.1	2.8	6.0	2.9	2.1	13.9	7.5	3.1	2.1	2.15	3.0	2.45
19	3.0	2.6	7.2	2.75	2.1	8.0	9.6	3.8	5.7	2.5	3.5	2.6
20	3.1	2.7	14.3	2.6	2.0	4.0	5.8	3.0	6.0	2.7	3.8	3.5
21	2.9	3.1	15.3	2.6	1.9	3.4	4.1	2.9	6.8	2.5	3.1	3.8
22	6.3	3.2	9.4	2.6	2.05	3.0	3.2	2.8	5.2	2.3	2.7	3.5
23	19.9	3.9	5.7	2.45	2.05	2.3	6.0	2.85	4.3	2.45	2.65	3.1
24	15.1	2.75	4.7	2.45	2.1	2.6	5.8	2.95	3.8	2.45	2.6	2.6
25	8.0	2.7	3.6	2.5	2.2	2.4	6.4	3.1	3.4	2.5	2.45	2.4
26	7.8	2.7	3.0	2.5	2.35	3.4	3.2	2.4	3.3	2.4	2.4	2.35
27	9.4	2.7	3.1	2.5	2.55	2.85	2.7	3.4	3.5	2.3	2.4	2.3
28	8.3	2.6	4.5	2.6	2.5	2.45	2.55	3.6	3.6	2.3	2.4	2.85
29	6.8	5.1	3.0	2.4	2.4	3.0	3.5	3.8	2.3	2.3	3.55
30	5.5	5.2	4.1	2.2	2.3	6.2	3.6	3.1	2.35	2.15	3.8
31	4.8	6.9	2.1	8.2	2.95	2.2	4.6

Rating tables for Apalachee River near Buckhead.

MARCH 1 TO DECEMBER 31, 1901.

Gage height	Dis-charge						
<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>
1.70	280	3.70	827	5.70	1,377	9.40	2,395
1.80	305	3.80	855	5.80	1,405	9.60	2,450
1.90	333	3.90	882	5.90	1,432	9.80	2,505
2.00	360	4.00	910	6.00	1,460	10.00	2,560
2.10	388	4.10	937	6.20	1,515	10.50	2,697
2.20	415	4.20	965	6.40	1,570	11.00	2,835
2.30	442	4.30	992	6.60	1,625	12.00	3,110
2.40	470	4.40	1,020	6.80	1,680	13.00	3,385
2.50	497	4.50	1,047	7.00	1,735	14.00	3,660
2.60	525	4.60	1,075	7.20	1,790	15.00	3,935
2.70	552	4.70	1,102	7.40	1,845	16.00	4,210
2.80	580	4.80	1,130	7.60	1,900	17.00	4,485
2.90	607	4.90	1,157	7.80	1,955	18.00	4,760
3.00	635	5.00	1,185	8.00	2,010	19.00	5,035
3.10	662	5.10	1,212	8.20	2,065	20.00	5,310
3.20	690	5.20	1,240	8.40	2,120	21.00	5,585
3.30	717	5.30	1,267	8.60	2,175	22.00	5,860
3.40	745	5.40	1,295	8.80	2,230	23.00	6,135
3.50	772	5.50	1,322	9.00	2,285	24.00	6,410
3.60	800	5.60	1,350	9.20	2,340	25.00	6,685

JANUARY 1 TO DECEMBER 31, 1902.^a

1.00	205	1.40	241	1.80	310
1.20	219	1.60	271	2.00	360

^a Above gage height 2.0 feet this table is the same as the 1901 table.

WATER POWERS OF GEORGIA

Rating tables for Apalachee River near Buckhead—Continued.

JANUARY 1 TO DECEMBER 31, 1903.^a

Gage height	Discharge						
<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>
0.90	170	1.20	203	1.50	248	1.80	310
1.00	180	1.30	216	1.60	267		
1.10	191	1.40	231	1.70	288		

JANUARY 1 TO DECEMBER 31, 1904.^b

0.40	43	1.40	216	2.60	514	4.40	1,025
.50	55	1.50	238	2.80	568	4.60	1,085
.60	69	1.60	261	3.00	622	4.80	1,145
.70	84	1.70	284	3.20	678	5.00	1,205
.80	100	1.80	308	3.40	734	6.00	1,505
.90	117	1.90	338	3.60	791	7.00	1,805
1.00	135	2.00	368	3.80	849	8.00	2,105
1.10	154	2.20	409	4.00	907	9.00	2,405
1.20	174	2.40	461	4.20	965	10.00	2,705
1.30	195						

JANUARY 1 TO DECEMBER 31, 1905.^c

0.40	44	2.10	358	3.70	820	6.60	1,690
.50	54	2.20	384	3.80	850	6.80	1,750
.60	66	2.30	410	3.90	880	7.00	1,810
.70	78	2.40	436	4.00	910	7.20	1,870
.80	92	2.50	464	4.20	970	7.40	1,930
.90	108	2.60	492	4.40	1,030	7.60	1,990
1.00	124	2.70	520	4.60	1,090	7.80	2,050
1.10	142	2.80	550	4.80	1,150	8.00	2,110
1.20	160	2.90	580	5.00	1,210	8.50	2,260
1.30	180	3.00	610	5.20	1,270	9.00	2,410
1.40	200	3.10	640	5.40	1,330	9.50	2,560
1.50	220	3.20	670	5.60	1,390	10.00	2,710
1.60	242	3.30	700	5.80	1,450	11.00	3,010
1.70	264	3.40	730	6.00	1,510	12.00	3,310
1.80	286	3.50	760	6.20	1,570	13.00	3,610
1.90	310	3.60	790	6.40	1,630	14.00	3,910
2.00	334						

^a Above gage height 1.8 feet this table is the same as the 1902 table.^b Above gage height 4.2 feet the rating curve is a tangent, the difference being 30 per tenth.^c Above gage height 2.70 feet the rating curve is a tangent, the difference being 30 per tenth.

JANUARY 1 TO DECEMBER 31, 1906.

Gage height	Discharge						
<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>
1.70	264	2.20	384	2.70	520	3.20	670
1.80	286	2.30	410	2.80	550	3.30	700
1.90	310	2.40	436	2.90	580	3.40	730
2.00	334	2.50	464	3.00	610	3.50	760
2.10	358	2.60	492	3.10	640		

NOTE.—The above table is based on discharge measurements made during 1903-1906, and is fairly well defined below gage height 7.3 feet. Above gage height 3 feet the rating curve is a tangent, the difference being 30 per tenth.

ALTAMAHA DRAINAGE BASIN, STREAM FLOW

195

Estimated monthly discharge of Apalachee River near Buckhead.

[Drainage area 440 square miles.]

Month	Discharge in second-feet			Run-off	
	Maximum	Minimum	Mean	Sec.-ft. per sq. mile	Depth in inches
1901					
March	2,972	470	847	1.92	2.21
April	3,660	552	1,123	2.55	2.84
May	1,680	388	553	1.26	1.45
June	2,147	552	910	2.07	2.31
July	1,460	333	582	1.32	1.52
August	2,697	305	896	2.04	2.35
September	3,247	305	711	1.62	1.81
October	525	280	349	.79	.91
November	415	280	326	.74	.83
December	5,772	333	1,027	2.33	2.69
1902					
January	2,835	525	842	1.91	2.20
February	5,310	827	1,708	3.88	4.04
March	6,685	717	1,714	3.90	4.50
April	2,010	552	843	1.92	2.14
May	580	300	448	1.02	1.18
June	1,322	280	469	1.07	1.19
July	1,460	256	375	.85	.98
August	1,047	205	368	.84	.97
September	910	241	495	1.12	1.25
October	497	256	294	.67	.77
November	525	241	298	.68	.76
December	1,185	388	641	1.46	1.68
The year	6,685	205	708	1.61	21.66
1903					
January	635	360	481	1.09	1.26
February	4,485	497	1,522	3.46	3.60
March	3,985	635	1,406	3.20	3.69
April	2,422	552	1,009	2.29	2.55
May	1,075	310	529	1.18	1.36
June	2,560	334	854	1.94	2.16
July	2,560	216	593	1.35	1.56
August	1,735	203	495	1.12	1.29
September	2,147	170	407	.93	1.04
October	388	191	287	.65	.75
November	607	203	348	.79	.88
December	360	288	328	.75	.86
The year	4,485	170	688	1.56	21.00
1904					
January	1,655	238	438	0.995	1.15
February	1,805	308	751	1.71	1.84
March	1,415	409	596	1.35	1.56
April	907	333	425	.966	1.08
May	487	174	286	.650	.749
June	595	84	264	.600	.669
July	622	100	239	.543	.626
August	2,675	238	647	1.47	1.70
September	568	a 62	187	.425	.474
October	216	a 43	84.1	.191	.220
November	333	a 126	240	.545	.608
December	776	216	363	.825	.951
The year	2,675	43	377	.856	11.00

a See note to gage-height table.

WATER POWERS OF GEORGIA

Estimated monthly discharge of Apalachee River near Buckhead—Continued.

Month	Discharge in second-feet			Run off	
	Maximum	Minimum	Mean	Sec.-ft. per sq. mile	Depth in inches
1905					
January	1,210	286	423	.961	1.11
February	3,120	286	1,074	2.44	2.54
March	640	310	448	1.02	1.18
April	410	264	346	.786	.877
May	1,120	160	469	1.07	1.23
June	1,090	100	345	.734	.875
July	2,770	124	624	1.42	1.64
August	1,990	α 44	462	1.05	1.21
September	640	α 45	145	.380	.368
October	210	α 55	139	.316	.364
November	492	α 79	209	.475	.530
December	3,910	200	1,371	3.12	3.60
The year	3,910	α 44	505	1.15	15.52
1906					
January	5,680	580	1,650	3.75	4.32
February	970	492	658	1.50	1.56
March	4,300	464	1,380	3.14	3.62
April	1,180	450	675	1.53	1.71
May	1,080	310	449	1.02	1.18
June	3,880	334	1,110	2.52	2.81
July	2,710	334	1,090	2.48	1.86
August	2,410	436	894	2.03	2.34
September	1,750	264	674	1.53	1.71
October	1,870	371	623	1.42	1.64
November	850	371	478	1.09	1.22
December	1,690	310	538	1.22	1.41
The year	5,680	264	852	1.94	26.33

NOTE.—At times the accuracy of the above results may be more or less affected by daily fluctuations caused by stored water above, but otherwise the results can, in general, be accepted as excellent.

OHOOPEE RIVER NEAR REIDSVILLE.

This station was established June 13, 1903, by F. A. Murray. It is located at the wooden highway bridge, known as Sheppards Bridge, $4\frac{1}{2}$ miles west of Reidsville.

Discharge measurements are made from the downstream side of the bridge. The initial point for soundings is the outer edge of the first crossbeam at the left end of the bridge, downstream side. The original gage consisted of two 5-foot sections spiked to the bridge and a third section fastened to a cypress tree on the left bank above the bridge. June 10, 1905, the gage was changed to the right side of the second bent from the left bank; it is fastened to the bent in four 5-foot sections. The gage is read by J. D. Swain, who is paid by the Georgia Geological Survey. Bench marks were established as follows: (1) The top of the cap of the fifth bent from the left end of the bridge on the upstream side, opposite a point 106 feet from the initial point for soundings; elevation, 20.00 feet; (2) two

nails driven horizontally into the downstream side of a cypress tree on the left bank, about 120 feet above the bridge; elevation, 8.00 feet. Elevations refer to datum of gage.

Discharge measurements of Ochoopee River near Reidsville.

Date	Gage height	Dis-charge	Date	Gage height	Dis-charge
1903			1904		
	<i>Feet</i>	<i>Sec.-ft.</i>		<i>Feet</i>	<i>Sec.-ft.</i>
June 13.....	12.47	5,762	September 15.....	3.00	454
June 24.....	6.41	1,692	October 31a.....	.32	52
July 16.....	10.34	3,667	December 1.....	1.56	190
July 16.....	10.46	3,756	1905		
August 22.....	14.00	6,441	March 16.....	11.90	4,204
October 8.....	2.34	476	March 17.....	11.90	4,163
October 8.....	2.85	462	April 27.....	6.38	1,635
November 19.....	4.96	1,131	June 10.....	1.01	114
December 30.....	6.69	1,836	July 28.....	2.31	363
1904			November 30.....	.36	57
February 19.....	10.19	3,611	November 30.....	.34	56
April 13.....	4.53	1,038	1906		
July 28.....	2.28	369	March 8.....	7.75	2,220
September 13.....	4.20	823	May 26.....	3.57	642
September 13.....	4.20	858	August 30.....	9.09	3,130
September 14.....	3.63	628			
September 15.....	3.00	470			

a Wading 1,000 feet above the bridge. Three narrow channels.
 b Made at different section.

Daily gage height, in feet, of Ochoopee River near Reidsville.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1903												
1.....							8.6	2.0	4.6	3.3	2.4	3.9
2.....							8.3	2.1	4.3	3.1	2.4	3.7
3.....							8.4	2.7	4.5	2.9	2.4	3.6
4.....							7.7	3.4	4.0	2.8	3.1	3.4
5.....							6.8	3.7	3.5	2.6	3.9	3.3
6.....							6.0	4.0	3.4	2.5	4.6	3.2
7.....							5.5	3.9	3.2	2.7	5.2	3.1
8.....							5.5	3.3	3.5	2.9	5.3	3.1
9.....							5.7	3.1	3.5	2.9	5.7	3.3
10.....							6.0	3.6	3.2	2.7	5.0	3.4
11.....							7.3	4.2	2.3	2.6	5.1	3.6
12.....							6.6	5.3	2.4	2.3	4.8	3.6
13.....							6.5	4.6		2.2	4.7	3.5
14.....							7.4	3.8		2.1	4.1	3.5
15.....							9.7	3.8		2.0	5.3	3.4

Daily gage height, in feet, of Ohoopce River near Reidsville—Continued.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1903												
16.....							10.6	8.3		2.0	5.4	3.3
17.....							9.5	10.3		2.2	5.6	3.3
18.....							9.6	9.9		5.0	5.4	3.1
19.....							10.3	10.3		6.7	5.0	3.0
20.....							9.5	14.0	10.8	6.9	4.7	2.9
21.....							8.1	13.8	10.5	6.5	4.5	3.0
22.....							6.7	14.0	8.4	5.7	4.4	3.3
23.....							5.7	13.2	7.2	5.0	4.3	3.3
24.....						6.5	4.7	12.0	6.5	4.6	4.1	3.2
25.....						6.7	4.0	11.4	6.4	3.7	4.0	3.3
26.....						6.9	4.0	10.5	6.3	3.2	4.1	3.7
27.....						7.7	3.7	9.0	4.3	2.9	4.8	5.3
28.....						8.7	3.2	7.7	4.1	2.7	4.4	6.3
29.....						10.2	2.5	6.7	3.9	2.5	4.2	6.6
30.....						9.3	2.5	5.5	3.6	2.3	4.1	6.7
31.....							2.2	4.8		2.2		6.3
1904												
1.....	6.4	6.7	8.2	4.4	1.4	.9	.5	1.1	8.3	1.1	.3	1.6
2.....	6.6	6.4	7.8	4.8	1.4	1.6	.5	1.0	6.4	1.0	.3	1.4
3.....		6.0	7.3	4.1	1.3	1.3	.5	2.2	6.5	1.0	.7	1.6
4.....	6.1	5.6	7.0	3.8	1.3	1.5	.6	4.6	6.0	.9	1.05	1.8
5.....	6.0	5.3	7.1	3.5	1.3	1.2	1.0	6.2	5.2	.8	1.5	2.1
6.....	5.4	5.0	7.1	3.3	1.1	1.1	1.2	8.4	4.3	.8	1.5	2.8
7.....	4.8	4.8	7.1	3.0	1.1	1.0	1.1	9.0	4.8	.7	1.5	3.1
8.....	4.6	5.0	7.4	2.9	1.0	.9	1.0	9.8	5.6	.6	1.3	3.1
9.....	4.8	5.1	7.3	2.8	1.0	.7	.8	9.0	5.6	.7	1.0	3.0
10.....		6.0	8.0	3.8	1.0	.7	1.1	8.4	5.5	.7	.9	2.8
11.....		8.2	8.0	4.6	.9	.6	1.4	8.6	5.1	.7	.8	2.7
12.....		12.1	7.8	4.8	.9	.6	1.0	9.0	5.0	.7	.7	2.5
13.....		12.0	7.6	4.7	.8	.6	1.0	9.4	4.4	.6	1.0	2.5
14.....			7.5	4.4	.8	.5	.3	8.9	3.6	.6	1.5	2.4
15.....		11.5	7.1	3.4	.7	.5	.6	8.6	3.1	.7	1.9	2.3
16.....		11.2	6.9	3.1	.7	.5	.8	8.3	2.6	.6	2.0	2.2
17.....	2.6	11.0	6.6	2.8	.7	.5	.6	7.6	2.3	.6	1.8	2.2
18.....	2.4	10.7	6.2	2.3	.7	.4	.5	6.3	2.1	.5	1.7	2.2
19.....	2.4	10.1	5.9	2.1	.6	.4	.5	6.4	1.9	.5	1.3	2.1
20.....	2.3	9.4	5.7	2.0	.6	.5	.4	5.4	1.6	.4	1.2	2.1
21.....	2.3	9.3	5.3	1.9	.6	.4	.4	4.8	1.5	.4	1.1	2.0
22.....	2.9	9.8	5.1	1.8	.6	.9	.6	4.5	1.5	.4	1.0	2.0
23.....	3.1	10.1	4.9	1.8	.5	.3	2.3	3.9	2.1	.4	1.1	1.9
24.....	4.0	10.4	4.6	1.7	.5	.6	1.9	3.7	2.2	.4	1.6	1.9
25.....	4.8	10.2	4.7	1.6	.5	.6	1.7	3.9	1.9	.3	1.2	1.9
26.....	5.7	9.8	4.8	1.5	.5	.5	1.5	3.9	1.7	.3	2.7	1.8
27.....	6.4	9.3	4.6	1.4	.5	.5	1.5	3.9	1.5	.4	2.4	1.9
28.....	7.2		4.8	1.4	.5	.5	1.4	5.4	1.3	.4	2.2	2.0
29.....	7.8	8.5	4.9	1.5	.9	.5	1.5	6.3	1.2	.3	8.8	2.4
30.....	7.1		5.0	1.5	1.1	.5	1.5	9.2	1.2	.3	1.6	2.7
31.....	6.8		4.6		.8		1.3	9.2		.3		2.7
1905												
1.....	2.8	3.6	9.7	6.2	5.3	1.9	1.0	2.5	1.7	.7	.7	.6
2.....	2.9	3.7	9.1	5.9	5.3	1.7	1.2	2.4	1.5	.8	.6	.6
3.....	2.7	3.5	8.7	5.4	5.2	1.5	1.3	2.1	1.3	1.0	.6	.9
4.....	2.5	3.4	8.2	5.2	5.1	1.4	1.3	2.0	1.4	.9	.5	1.0
5.....	2.4	3.5	7.9	5.1	5.3	1.4	1.2	1.7	1.7	.8	.4	1.9
6.....	2.3	3.7	7.5	5.3	5.2	1.4	3.4	1.0	2.0	.7	.4	2.6
7.....	2.4	4.2	7.2	5.6	4.8	1.3	5.1	1.1	1.7	.6	.4	2.6
8.....	2.7	4.5	7.0	5.4	4.0	1.1	5.8	1.0	1.4	.6	.4	2.2
9.....	3.0	5.0	6.8	5.0	3.7	1.0	6.0	1.0	1.1	.5	.4	1.8
10.....	3.3	5.7	7.1	4.9	3.5	1.0	6.3	1.0	.9	.5	.4	1.9
11.....	3.3	5.9	7.4	5.2	3.2	.9	5.9	1.4	.8	.5	.4	2.0
12.....	3.5	6.8	8.9	5.5	2.9	.9	5.8	1.8	.8	.5	.4	2.1
13.....	3.9	8.6	10.5	6.1	2.7	.8	5.2	2.0	.7	.4	1.5	2.1
14.....	4.8	10.2	11.3	6.7	2.4	1.8	4.5	2.8	.7	.4	1.8	1.8
15.....	5.0	12.7	11.7	7.6	2.1	1.4	3.7	3.7	.9	.4	1.6	1.9

ALTAMAHA DRAINAGE BASIN, STREAM FLOW

199

Daily gage height, in feet, of Ochoopee River near Reidsville—Continued.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1905												
16.....	5.2	15.9	11.9	7.9	1.9	1.8	4.8	3.7	1.4	0.4	1.2	2.3
17.....	5.5	19.0	11.9	8.2	1.9	1.3	5.0	3.5	1.3	.4	1.1	2.3
18.....	5.5	15.0	11.6	7.3	2.3	1.4	4.7	3.3	1.5	.4	.9	3.2
19.....	5.1	14.6	11.3	7.2	2.7	1.4	5.0	3.3	1.3	.4	.9	3.3
20.....	4.9	13.7	11.1	7.2	2.8	1.5	5.7	3.1	1.0	.4	.8	3.0
21.....	4.7	11.8	10.4	6.5	2.7	1.3	4.7	3.0	.9	.4	.8	3.3
22.....	4.6	11.6	9.6	6.1	2.6	1.3	3.8	2.7	.8	.4	.7	4.1
23.....	4.5	12.0	9.0	6.8	2.4	1.3	3.0	2.5	.8	.4	.6	5.6
24.....	4.3	12.5	8.5	7.0	2.6	1.3	2.6	2.5	.6	.3	.6	6.8
25.....	4.2	12.2	8.3	7.2	3.0	1.2	2.1	2.1	.5	.3	.6	8.0
26.....	4.2	11.7	8.0	6.9	3.2	1.0	1.8	2.1	.5	.3	.6	7.9
27.....	4.1	11.1	7.9	6.2	3.2	1.2	1.7	2.8	.5	.4	.6	7.9
28.....	4.0	10.5	7.8	5.9	2.8	1.2	2.3	3.1	.5	.4	.6	7.6
29.....	3.8	7.4	5.6	2.2	1.0	2.9	2.9	.5	.7	.6	7.5
30.....	3.6	7.1	5.4	2.0	1.0	2.7	2.5	.6	.9	.6	7.8
31.....	3.6	6.7	2.0	2.6	2.18	8.2
1906												
1.....	3.8	3.7	6.2	6.3	1.1	3.5	4.6	8.6	8.1	3.2	1.2	1.0
2.....	3.8	3.8	6.0	6.1	1.0	2.8	3.7	8.4	7.2	3.4	1.2	.9
3.....	3.7	7.9	6.1	5.8	1.0	3.9	3.5	7.6	7.8	4.3	1.0	.9
4.....	3.9	7.5	7.9	5.5	1.0	5.0	3.5	7.3	7.0	5.2	.9	.8
5.....	9.0	7.2	8.1	5.1	1.0	7.6	4.7	7.4	6.3	6.5	.9	.8
6.....	9.1	6.9	7.6	4.7	1.4	9.9	5.0	7.5	5.1	5.0	.9	.7
7.....	9.3	6.5	7.5	4.4	1.9	9.5	5.1	6.8	4.9	4.7	.8	.7
8.....	9.6	6.5	7.7	4.1	2.9	8.9	5.8	5.9	4.3	4.3	.8	.9
9.....	9.2	7.2	8.1	3.7	3.5	7.8	6.0	4.3	3.8	4.0	.8	1.2
10.....	8.8	8.0	8.4	3.5	3.5	6.2	5.2	4.6	3.4	3.9	.8	1.7
11.....	3.3	8.5	8.2	3.3	3.3	4.4	4.2	4.0	2.9	3.7	.7	1.6
12.....	8.0	8.9	8.2	3.3	2.8	4.1	4.5	3.3	2.3	3.1	.7	1.4
13.....	7.7	9.2	8.0	3.0	2.0	6.0	4.2	3.6	2.9	2.7	.8	1.2
14.....	7.3	9.4	7.6	2.9	1.7	7.4	4.5	3.2	2.6	2.5	.8	1.0
15.....	7.1	9.5	7.1	3.0	1.5	8.4	4.9	2.9	3.7	2.3	.9	1.0
16.....	7.0	9.3	6.8	3.2	1.4	7.9	5.0	3.1	3.3	2.1	1.2	1.0
17.....	6.8	9.0	6.4	3.7	1.2	10.1	5.9	3.9	3.9	2.0	1.6	1.0
18.....	6.6	8.7	6.1	3.4	1.0	10.6	6.6	4.3	3.8	2.0	1.7	1.0
19.....	6.6	8.1	5.8	3.0	1.0	10.6	7.0	3.4	3.6	2.1	1.8	1.2
20.....	6.6	7.6	6.9	2.8	.9	11.0	7.8	2.9	3.4	2.3	1.8	1.7
21.....	6.3	7.5	7.6	2.7	.9	10.9	9.2	2.3	3.9	2.4	1.9	2.0
22.....	6.1	8.1	8.0	2.4	.9	10.0	8.4	2.8	3.4	2.4	1.8	2.3
23.....	6.5	8.2	8.7	2.2	.9	9.2	7.6	3.1	3.2	2.3	1.7	2.3
24.....	7.0	8.0	9.0	2.0	1.3	8.1	7.3	4.1	3.1	2.3	1.6	2.3
25.....	7.5	7.6	8.6	1.8	2.5	7.2	7.3	4.8	2.9	2.1	1.6	2.3
26.....	8.0	7.2	7.7	1.7	3.5	6.5	7.5	5.2	2.7	2.0	1.6	2.3
27.....	8.5	6.8	7.2	1.5	4.0	5.9	7.2	6.7	3.1	1.9	1.5	2.0
28.....	9.0	6.5	6.8	1.4	4.5	5.5	6.9	8.1	3.4	1.8	1.2	2.0
29.....	9.4	6.8	1.3	4.8	5.3	7.8	8.6	3.5	1.7	1.1	2.0
30.....	9.3	6.7	1.2	5.1	5.2	8.6	9.1	3.3	1.6	1.0	2.1
31.....	9.0	6.7	4.4	9.0	8.9	1.6	2.4

WATER POWERS OF GEORGIA

Rating tables for Ochopee River near Reidsville.

JUNE 23, 1903, TO DECEMBER 31, 1905.

Gage height	Dis-charge						
<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>
2.00	280	3.30	595	5.20	1,220	7.80	2,325
2.10	296	3.40	625	5.40	1,295	8.00	2,415
2.20	314	3.50	655	5.60	1,375	8.50	2,665
2.30	326	3.60	685	5.80	1,455	9.00	2,915
2.40	350	3.70	715	6.00	1,535	9.50	3,175
2.50	375	3.80	745	6.20	1,615	10.00	3,465
2.60	400	3.90	775	6.40	1,695	10.50	3,775
2.70	426	4.00	805	6.60	1,785	11.00	4,130
2.80	453	4.20	870	6.80	1,875	12.00	4,935
2.90	480	4.40	940	7.00	1,995	13.00	5,860
3.00	508	4.60	1,010	7.20	2,055	14.00	6,860
3.10	536	4.80	1,080	7.40	2,145		
3.20	565	5.00	1,150	7.60	2,235		


JANUARY 1, 1904, TO DECEMBER 31, 1905.

0.80	50	1.60	197	3.80	690	7.00	1,950
.40	57	1.70	213	4.00	755	7.50	2,184
.60	65	1.80	230	4.20	824	8.00	2,430
.80	74	1.90	247	4.40	895	8.50	2,685
1.00	83	2.00	265	4.60	968	9.00	2,950
1.20	93	2.20	302	4.80	1,043	9.50	3,222
1.40	104	2.40	341	5.00	1,120	10.00	3,500
1.60	115	2.60	382	5.20	1,198	11.00	4,120
1.80	127	2.80	425	5.40	1,277	12.00	4,820
2.00	140	3.00	470	5.60	1,357	13.00	5,590
2.20	153	3.20	519	5.80	1,438		
2.40	167	3.40	572	6.00	1,520		
2.60	182	3.60	629	6.50	1,728		


JANUARY 1 TO DECEMBER 31, 1906.

0.70	88	2.10	283	3.50	600	5.80	1,488
.80	93	2.20	302	3.60	629	6.00	1,520
.90	104	2.30	321	3.70	659	6.20	1,602
1.00	115	2.40	341	3.80	690	6.40	1,685
1.10	127	2.50	361	3.90	722	6.60	1,771
1.20	140	2.60	382	4.00	755	6.80	1,860
1.30	153	2.70	403	4.20	824	7.00	1,950
1.40	167	2.80	425	4.40	895	8.00	2,430
1.50	182	2.90	447	4.60	968	9.00	2,950
1.60	197	3.00	470	4.80	1,043	10.00	3,500
1.70	213	3.10	494	5.00	1,120	11.00	4,120
1.80	230	3.20	519	5.20	1,198		
1.90	247	3.30	545	5.40	1,277		
2.00	265	3.40	572	5.60	1,357		

NOTE.—The above table is based on discharge measurements made during 1903-1906 and is well defined.



INTERIOR VIEW OF THE ATLANTA WATER AND ELECTRIC POWER COMPANY'S POWER HOUSE, NEAR ROSWELL, GEORGIA, SHOWING THE SEVEN 2,200 VOLT ELECTRIC GENERATORS.



ALTAMAHA DRAINAGE BASIN, STREAM FLOW

201

Estimated monthly discharge of Ohoopsee River near Reidsville.

[Drainage area, 1,280 square miles.]

Month	Discharge in second-feet			Run-off	
	Maximum	Minimum	Mean	Sec-ft. per sq. mile	Depth in inches
1903					
June 24-30.....	3,585	1,740	2,455	1.92	0.500*
July.....	3,840	314	1,872	1.46	1.68
August.....	6,860	280	2,344	1.83	2.11
September 1-12 and 20-30 a.....	3,980	326	1,252	.978	.837
October.....	1,920	280	654	.511	.589*
November.....	1,415	350	966	.755	.842
December.....	1,830	480	775	.605	.698
1904					
January.....	2,330	821	1,062	.330	.957
February.....	4,894	1,048	2,877	2.25	2.43
March.....	2,531	968	1,703	1.33	1.53
April.....	1,043	167	495	.387	.432
May.....	167	65	101	.079	.091
June.....	230	57	91.8	.072	.080
July.....	321	57	125	.098	.113
August.....	3,388	115	1,811	1.41	1.63
September.....	2,582	140	747	.584	.652
October.....	127	50	74.0	.058	.067
November.....	403	50	170	.133	.143
December.....	494	167	316	.247	.285
The year.....	4,894	50	798	.623	3.42
1905					
January.....	1,317	321	744	.581	.670
February.....	10,390	572	3,512	2.74	2.85
March.....	4,746	1,815	2,989	2.34	2.70
April.....	2,531	1,081	1,625	1.27	1.42
May.....	1,237	247	588	.459	.529
June.....	247	98	154	.120	.134
July.....	1,643	115	750	.586	.676
August.....	659	115	349	.273	.315
September.....	265	65	126	.098	.109
October.....	115	50	69.4	.054	.062
November.....	230	57	89.9	.070	.078
December.....	2,531	74	360	.672	.775
The year.....	10,390	50	983	.772	10.32
1906					
January.....	3,280	1,560	2,470	1.93	2.22
February.....	3,220	1,730	2,420	1.89	1.97
March.....	2,950	1,440	2,140	1.67	1.92
April.....	1,640	140	619	.484	.54
May.....	1,160	104	359	.280	.32
June.....	4,120	425	2,210	1.73	1.93
July.....	3,060	600	1,600	1.25	1.44
August.....	3,000	321	1,370	1.07	1.23
September.....	2,480	321	858	.670	.75
October.....	1,730	197	520	.406	.47
November.....	247	83	146	.114	.13
December.....	341	83	189	.148	.17
The year.....	4,120	83	1,240	.970	13.09*

a Missing dates, gage out.

NOTE.—Values are rated as follows: January to April and June to October, excellent; May, November, and December, good.

MISCELLANEOUS MEASUREMENTS IN ALTAMAHA RIVER DRAINAGE
BASIN.

Alcovy River.—The following measurement was made October 7, 1904, from the wagon bridge at Henderson's mill, 4 miles from Newton Factory, on the road to Covington. The bench mark is the upstream edge of the bridge floor, 90 feet from the initial point for soundings, 11.00 feet above the datum of the gage.

Width, 40 feet; area, 43 square feet; mean velocity, 1.46 feet per second; gage height, 1.25 feet; discharge, 62 second-feet.

Beaverdam Creek.—This stream enters Oconee River from the left. The following measurement was made March 19, 1904, at Veazey Ford, 6 miles south of Greensboro, on the road to Sparta. The bench mark is a nail in a small ash tree on the left bank, 20 feet below the foot plank, 3.00 feet above the datum of the gage.

Width, 15 feet; area, 10 square feet; mean velocity, 1.70 feet per second; gage height, 1.50 feet; discharge, 17 feet.

Brazzell Creek.—The following measurement was made by wading at a narrow channel one fourth mile above the mouth and one-half mile from the regular gaging station on Ochoopee River at Reidsville. The gage height at the Ochoopee River station at the same time was 2.35 feet.

July 28, 1905. Width, 12 feet; area, 6.6 square feet; mean velocity, 0.85 foot per second; discharge, 5.6 second-feet.

Gladly Creek.—At the wagon bridge, $3\frac{1}{2}$ miles from Eatonton, this stream was discharging 7 second-feet on December 17, 1903, when the water surface was 6.14 feet below bridge floor 60 feet from right end of bridge going upstream.

Horse Creek.—This stream is a tributary of Ocmulgee River from the left. The measurement below was made September 8, 1904, $1\frac{1}{2}$ miles above the mouth of the creek, 10 miles north of Lumber City. The bench mark is a nail driven into the end of the second floor beam above the second bent from the left bank, 15.00 feet above the zero of the gage.

Width, 55 feet; area, 115 square feet; mean velocity, 1.03 feet per second; gage height, 3.17 feet; discharge, 118 second-feet.

Indian Creek.—This stream was measured at wagon bridge at Hudson's mill, 6 miles northwest of Eatonton. The bench mark

is at top of bridge floor, $27\frac{1}{2}$ feet from end of hand rail, right bank, upstream.

October 18, 1903: Height of bench mark above water, 8.79 feet; discharge, 85 second-feet.

December 17, 1903: Height of bench mark above water, 9.10 feet; discharge, 49 second-feet.

Jacks Creek.—A measurement was made from a foot log on the river road about one-fourth mile above Hayden's bridge, about one-half mile from Annistown. The bench mark is the head of a large wire nail driven into the downstream face of a double-trunk birch tree on the right bank, 20 feet below the road; elevation, 5.00 feet above the datum of the assumed gage.

January 28, 1905: Width, 8.5 feet; area, 3.7 square feet; mean velocity, 1.32 feet per second; gage height, 1.88 feet; discharge, 4.9 second-feet.

Little Ocmulgee River.—A measurement was made July 26, 1905, by wading about 90 feet upstream from the wagon bridge on which a bench mark was established in September, 1904, three-fourths mile northeast of Lumber City, Ga. The bench mark is the top of the downstream end of the cap of the second bent from the right bank; elevation, 23.00 feet above the datum of the assumed gage.

Width, 48 feet; area, 25 square feet; mean velocity, 1.64 feet per second; gage height, 1.46 feet; discharge, 41 second-feet.

This stream was measured also at a wooden wagon bridge $2\frac{1}{2}$ miles from Lumber City and one-eighth mile from Wilcox Station, Ga. The bench mark is the center of a lag screw driven into the end of the second floor beam from the right bank of the downstream side; elevation, 18.00 feet above the datum of the assumed gage.

September 7, 1904: Width, 100 feet; area, 488 square feet; mean velocity, 1.92 feet per second; gage height, 3.15 feet; discharge, 9.37 second-feet.

July 25, 1905: Width, 52.5 feet; area, 61.5 square feet; mean velocity, 0.58 foot per second; gage height, 1.25 feet; discharge, 35.5 second-feet.

Little River.—This stream enters Oconee River from the right. It was measured at a wagon bridge $6\frac{1}{4}$ miles northwest of Eaton-ton. The bench mark is top of bridge floor, 20 feet from end of bridge, on left bank going upstream.

October 18, 1903: Height of bench mark above water, 8.73 feet; discharge, 118 second-feet.

December 17, 1903: Height of bench mark above water, 9.07 feet; discharge, 88 second-feet.

A measurement was made from the wagon bridge 9 miles north of Milledgeville, 1 mile above the mouth of the river. The initial point for soundings is the end of the hand rail at the left bank. The bench mark is a copper brand in the top of the downstream end of the cross beam at the first pier from the left bank; elevation, 15.00 feet above the datum of the assumed gage.

July 28, 1904: Width, 89 feet; area, 65 square feet; mean velocity, 1.09 feet per second; gage height, 3.17 feet; discharge, 71 second-feet.

September 15, 1905: Width, 99 feet; area, 92 square feet; mean velocity, 1.23 feet per second; gage height, 3.51 feet; discharge, 113 second-feet.

November 24, 1905: Width, 119 feet; area, 132 square feet; mean velocity, 1.55 feet per second; gage height, 3.86 feet; discharge, 205 second-feet.

Ocmulgee River.—This stream was measured at Holton. The bench mark is two nails in upstream side of birch tree 20 feet above old ferry landing, right bank.

October 14, 1903: Height of bench mark above water, 7.1 feet; discharge, 893 second-feet.

October 14, 1903: Height of bench mark above water, 7.0 feet; discharge, 963 second-feet.

At Bridges Ferry, near Berner, this stream was discharging 1,535 second-feet on June 16, 1903; gage height, 3.77 feet. The bench mark is a nail in birch tree at upper side of ferry landing, on right bank; elevation, 10.91 feet above datum.

Ohoopce River.—At Jarrell Bridge, near Ohoopce, this stream was discharging 1,481 second-feet on June 8, 1903, when the water surface was 7.1 feet below the top of crossbeam, 58 feet from end of hand rail, on right bank going downstream.

A measurement was made July 29, 1905, at Lynn Bridge, near Ohoopce. The initial point for soundings was the end of the hand rail at the left bank, downstream side. The bench mark was the top of the upstream end of the cap of the bent, 64 feet from the left end of the hand rail; elevation, 19.00 feet above the datum of the assumed gage.

Width, 84 feet; area, 314 square feet; mean velocity, 0.57 foot per second; gage height, 4.22 feet; discharge, 180 second-feet.

Pendleton Creek.—This stream was measured at Gordon Bridge, $3\frac{1}{2}$ miles from Lyons. In 1903 the bench mark was a spike in a tupelo tree on right bank, 30 feet below bridge. This was carried away by a flood, and the 1905 measurement was dependent on a

new bench mark, the top of the downstream end of the cap of the third bent from the right-bank end of the bridge; elevation, 17.00 feet above the datum of the assumed gage.

June 8, 1903: Height of bench mark above water, 5.30 feet; discharge, 1,071 second-feet.

October 7, 1903: Height of bench mark above water, 11.60 feet; discharge, 100 second-feet.

October 7, 1903: Height of bench mark above water, 11.25 feet; discharge, 104 second-feet.

July 29, 1905: Width, 74 feet; area, 341 square feet; mean velocity, 1.23 feet per second; gage height, 7.58 feet; discharge, 438 second-feet.

Pole Bridge Creek.—This stream is a tributary of South River from the left near Lithonia. Measurements were made near the mouth of the creek, on the road between News Bridge and Parker Bridge.

July 16, 1904: Width, 15 feet; area, 7 square feet; mean velocity, 1.43 feet per second; discharge, 10 second-feet.

September 23, 1904: Width, 17 feet; area, 7 square feet; mean velocity, 1.00 foot per second; discharge, 7 second-feet.

Sanford Creek.—At wagon bridge, 3 miles from Eatonton, this stream was discharging 3.6 second-feet on December 17, 1903, when the water surface was 5.44 feet below bridge floor 21 feet from post on right bank.

Snapping Shoals Creek.—A measurement was made October 24, 1905, at a bridge about 80 feet above the mouth of Snapping Shoals Creek, 400 feet below the bridge on South River at Snapping Shoals. The bench mark is the top of the wooden stringer 13½ feet from the left-bank end; elevation, 12.00 feet above the datum of the assumed gage.

Width, 21 feet; area, 12 square feet; mean velocity, 1.17 feet per second; gage height, 0.54 foot; discharge, 14 second-feet.

South River.—A measurement was made on South River October 24, 1905, from a boat, just below the mouth of Snapping Shoals Creek, and about 500 feet below the wagon bridge at Snapping Shoals. The bench mark is the top of the downstream end of the first floor beam of the bridge to the left of the center pier; elevation, 26.00 feet above the datum of the assumed gage.

Width, 78 feet; area, 122 square feet; mean velocity, 1.18 feet per second; gage height, 3.00 feet; discharge, 144 second-feet.

A measurement was made October 7, 1904, at the wagon bridge,

10 miles from Jackson, on the road to Covington. The bench mark is the upstream end of floor beam, 66 feet from the initial point for soundings, 20.00 feet above the datum of the gage.

Width, 121 feet; area, 152 square feet; mean velocity, 0.90 foot per second; gage height, 1.10 feet; discharge, 137 second-feet.

Sugar Creek.—A measurement was made on this stream September 7, 1904, from the Southern Railway bridge, one-fourth mile north of Wilcox. The bench mark is the top of the steel girder, upstream side, 150 feet from the right end of the trestle, 25.00 feet above the datum of the gage.

Width, 41 feet; area, 117 square feet; mean velocity, 1.06 feet per second; gage height, 7.50 feet; discharge, 124 second-feet.

Another measurement was made July 25, 1905, at a new wagon bridge 75 feet upstream from the Southern Railway bridge at Wilcox. The bench mark is the top of the downstream wooden stringer 126 feet from the right end of the downstream hand rail of the bridge; elevation, 22.06 feet above the datum of the assumed gage.

Width, 15 feet; area, 18 square feet; mean velocity, 0.30 foot per second; gage height, 3.88 feet; discharge, 5.5 second-feet.

Swift Creek.—Near Lyons, this stream was discharging 31 second-feet on October 7, 1903.

Town Creek.—At wagon bridge, 1 mile east of Eatonton, this stream was discharging 2.7 second-feet on December 18, 1903, when the water surface was 8.57 feet below top of bridge floor, 24 feet from right end of bridge, going downstream.

Yellow River.—At Woods Bridge, near Almon, this stream was discharging 79 second-feet on September 12, 1903, when the water surface was 17.46 feet below top of crossbeam, 75 feet from right end of bridge going downstream.

At a wagon bridge near Lithonia this stream was discharging 104 second-feet on October 5, 1903, when the water surface was 16.25 feet, below top of wooden stringer on downstream side of bridge, at inside face of right-bank stone abutment.

A measurement was made at this place September 15, 1905. The bench mark is the top of the downstream corner of the right-bank stone abutment; elevation, 16.55 feet above the datum of the assumed gage.

Width, 28 feet; area, 40 square feet; mean velocity, 1.70 feet per second; gage height, 1.96 feet; discharge, 68 second-feet.

A measurement was made October 7, 1904, at the wagon bridge 11 miles from Jackson, on the road to Covington. The bench mark is the downstream edge of the bridge floor, 40 feet from the initial point for soundings, and is 8.00 feet above the datum of the gage.

Width, 113 feet; area, 229 square feet; mean velocity, 0.30 foot per second; gage height, 1.80 feet; discharge, 69 second-feet.

RIVER SURVEYS IN ALTAMAHA RIVER DRAINAGE BASIN.

SOUTH RIVER.

The elevations in the following lists are based upon an aluminum tablet at the Washington street entrance of the State capitol building at Atlanta, marked "1050 M. C.," the elevation of which is accepted as 1,049.546 feet above mean sea level.

The leveling on South River is adjusted to accord with elevations of precise-level bench marks at Constitution, Holton, and Macon, by the 1903 adjustment. The leveling was done in 1903 for the United States Geological Survey by Joseph Palmer, levelman, under the direction of F. A. Franck, field assistant.

Elevations on South River from Constitution to mouth.

Dis- tance	Description of points	Elevation above sea level
<i>Miles</i>		<i>Feet</i>
0.0	Iron post 4 feet east of signboard "Constitution," 25 feet south of railroad.....	847.006
1.0	60 feet below Southern Railway bridge, water surface.....	772
2.0	Black-gum tree opposite mouth of Intrenchment Creek.....	773.77
2.0	Water surface.....	770
2.3	Sycamore tree 35 feet south of creek, 50 feet east of road at McNeals Bridge.....	769.57
2.8	Water surface.....	768
3.9	Junction of South River and Sugar Creek, water surface.....	765
4.1	40 feet east of road at south approach, Surges Bridge.....	762
5.3	Mouth of small stream, water surface.....	754
6.3	15 feet below road, north approach of bridge.....	752
7.0	Kellers Bridge, iron bolt on north end.....	751.92
7.0	Kellers Bridge, water surface.....	750
7.06	Blue Creek, 100 yards below Kellers Bridge, water surface.....	748
8.0	Mouth small creek, water surface.....	743
9.1	Water surface.....	739
10.0	Shoal Creek Bridge, water surface.....	737
10.05	Mouth of Shoal Creek, water surface.....	737
10.4	15 feet above Waldrops Bridge, water surface.....	736
11.0	At mouth small stream, one-fourth mile below Waldrops Bridge, water surface.....	732
11.8	Fork Creek, 5 feet below bridge, water surface.....	730.8
12.0	Water surface.....	730
12.3	Lower end of island, water surface.....	729
12.6	Birch tree at small stream.....	733.2f
12.6	Water surface.....	728

Elevations on South River from Constitution to mouth—Continued.

Distance	Description of points	Elevation above sea level
Miles		Feet
13.5	Flake's mill, top of dam.....	726
13.6	Flake's mill, bottom of dam.....	720
13.6	In rapids below dam, water surface.....	719
14.0	Water surface.....	714
14.2	Below rapids, water surface.....	713
14.3	Above riff, water surface.....	713
14.32	Below riff, water surface.....	711
14.8	Water surface.....	710
15.0	Opposite mouth Snapfinger Creek, water surface.....	710
15.3	Above shoals just below Snapfinger Creek, water surface.....	709.7
15.35	Below shoals just below Snapfinger Creek, water surface.....	708
15.8	At mouth of Mathews Creek, water surface.....	701
16.1	100 feet below mouth of Cucumber Creek, water surface.....	698
16.3	Flat Shoals Bridge, on stone masonry, south side of river, east side of approach.....	708.71
16.5	Flat Shoals Bridge, water surface.....	698
16.3	Below Flat Shoals, water surface.....	686
18.0	Mouth of small stream, water surface.....	683
18.6	50 feet above small stream opposite Little Mountain, water surface.....	683
19.0	Water surface.....	682
19.9	At bend of river just below Little Mountain, water surface.....	681
20.6	Parkers Bridge on sweet-gum tree south side of river, 50 feet from bridge, 6 feet from road.....	678.76
20.6	Parkers Bridge, water surface.....	672
20.7	Opposite Pole Bridge Creek, water surface.....	670
22.0	50 feet below Albert Shoals Bridge, water surface.....	669.50
22.05	Mouth small stream, head of Albert Shoals, water surface.....	667
22.6	At old mill, water surface.....	660
22.6	Below falls, water surface.....	653
23.2	Opposite mouth of Crooked Creek, water surface.....	651
23.6	Daniels Bridge, top stone pier, lower side, right end.....	667.97
23.6	Daniels Bridge, water surface.....	649
23.7	Head of shoals below Daniels Bridge, water surface.....	647
23.75	Foot of shoals below Daniels Bridge, water surface.....	645
24.0	Mouth of small creek from right bank, water surface.....	644
24.5	25 feet below mouth of creek, right bank, water surface.....	643
24.8	Head of Pucket Shoals, water surface.....	642
.....	Foot of Pucket Shoals, water surface.....	639
24.9	Foot of lower Pucket Shoals, water surface.....	637
25.3	Head of shoals, Simms Bridge, water surface.....	636
.....	Foot of shoals, Simms Bridge, water surface.....	634
25.7	Opposite mouth of small creek, water surface.....	631
26.4	Sycamore tree, 50 feet above mouth of Knights Creek.....	639.28
26.4	Water surface.....	629
27.0	40 feet below creek, 1 mile below Knights Creek, water surface.....	626
27.2	At mouth of small creek, about 1¼ miles below Knights Creek, water surface.....	625
28.9	Water surface.....	621
29.2	Forty feet above mouth of small stream, water surface.....	620
30.0	Mouth of small stream, right bank, water surface.....	619
30.5	About one-half mile below small stream, water surface.....	618
30.8	Opposite mouth of Honey Creek, water surface.....	616
31.0	On oak tree, 25 feet above Oglesbys Bridge.....	622.02
31.0	Water surface.....	614
31.2	Mouth of Camp Creek, water surface.....	613
31.4	Mouth of small creek, about one-fourth mile below Oglesbys Bridge, water surface.....	612.2
33.0	Sixty feet above small stream, about 1 mile below Oglesbys Bridge, water surface.....	610
33.1	Mouth of small stream, water surface.....	610
33.9	Mouth of creek about 2 miles below Oglesbys Bridge, water surface.....	606
34.5	40 feet below mouth of small creek, water surface.....	604
35.0	Head of shoals (one-half mile) water surface.....	602
.....	Foot of shoals, water surface.....	601
35.5	Opposite bend in river.....	597
36.0	Peachstone Shoals Bridge, water oak.....	605.71
36.0	Peachstone Shoals Bridge, water surface.....	597
.....	Peachstone Shoals, head of dam.....	597
.....	Peachstone Shoals, foot of dam.....	595
36.1	Peachstone Shoals, foot of rapids.....	589
36.4	Water surface.....	588
38.0	Opposite mouth of Cotton River, water surface.....	587
38.4	Mouth of small stream, water surface.....	584
39.0	Mouth of small stream below sharp bend in river, water surface.....	580
39.6	Mouth of small creek, water surface.....	578
40.0	Mouth of small stream, water surface.....	575
40.1	Mouth of Walnut Creek, water surface.....	573
41.0	Red oak 30 feet below Butlers Bridge.....	587.15
41.0	Butlers Bridge, water surface.....	569

Elevations on South River from Constitution to mouth—Continued.

Distance	Description of points	Elevation above sea level
<i>Miles</i>		<i>Feet</i>
41.25	Mouth of small creek, water surface.....	568.5
41.7do	568
42.0	Water surface.....	566
43.0	Head of upper Snapping Shoals, water surface.....	562
43.02	Foot of upper Snapping Shoals, water surface.....	561
43.03	Head of Snapping Shoals, water surface.....	561
43.05	Foot of first falls, water surface.....	557
43.06	Head of second falls, 180 feet from first fall, water surface.....	556
43.1	Water oak 40 feet from north approach of Snapping Shoals Bridge.....	559.66
43.1	Water surface.....	542
43.2	Foot of rapids, water surface.....	541
43.8	60 feet above small stream, water surface.....	538
45.0	Island Shoals, at head of dam, water surface.....	536
.....	Island Shoals, at foot of dam, water surface.....	534
.....	Island Shoals at head, water surface.....	534
45.25	Island Shoals at foot, water surface.....	526
45.3	Island Shoals Bridge, white oak at south approach.....	534.89
45.3	Island Shoals Bridge, water surface.....	525
47.0	Mouth of creek, water surface.....	519
47.8	Water surface.....	518
49.0	Head of small shoals, water surface.....	512
49.4	Opposite shoals, water surface.....	511
50.0	Head of shoals one-fourth mile above Manns Bridge, water surface.....	509
.....	Foot of shoals, water surface.....	507
50.8	On hickory tree 20 feet below Manns Bridge.....	518.49
50.8	Water surface.....	508
51.0	At small Creek, water surface.....	501
51.5	About three-fourths of a mile below Manns Bridge, water surface.....	500

SURVEY OF OCMULGEE RIVER.

The elevations in the following lists are based upon an aluminum tablet at the Washington street entrance of the State capitol building at Atlanta, marked "1050 M. C.," the elevation of which is accepted as 1,049.546 feet above mean sea level.

The leveling on South River is adjusted to accord with elevations of precise-level bench marks at Constitution, Holton, and Macon, by the 1903 adjustment. The leveling was done in 1903 for the United States Geological Survey by Joseph Palmer, levelman, under the direction of F. A. Franck, field assistant.

WATER POWERS OF GEORGIA

Elevations on Ocmulgee River from junction of South and Yellow rivers to Macon.

Distance	Description of points	Elevation above sea level
<i>Miles</i>		<i>Feet</i>
52.1	Large pine tree opposite mouth of Yellow River.....	506.94
52.1	Head of shoals.....	498
53.5	Near end of island, water surface.....	487
54.0	Head of Lemon Shoals, water surface.....	486
54.02	Foot of Lemon Shoals, water surface.....	484
54.5	Large white oak opposite mouth of Alcovy River.....	494.27
54.5	Water surface.....	484
54.55	Head of shoals just below Alcovy River, water surface.....	483
54.56	Foot of shoals just below Alcovy River, water surface.....	482
54.6	Head of dam in left channel and also head of shoals in right channel at Kees Shoals, water surface.....	481
54.7	Foot of dam, water surface.....	479
54.75	Foot of shoals, water surface.....	477
56.0	Head of shoals one-fourth mile below Kees mill, water surface.....	475
56.0	Foot of shoals one-fourth mile below Kees mill, water surface.....	473
56.2	Water oak at mouth of Tussahaw Creek.....	482.12
56.2	Water surface.....	472
56.5	Dempseys Ferry and head of Cooks Shoals, water surface.....	472
56.6	Foot of Cooks Shoals, water surface.....	468
56.9	Head of Lloyds Shoals, water surface.....	465
57.2	End of small island, water surface.....	457
58.1	Opposite lower end of last island in shoals, water surface.....	445
58.8	Shoals, water surface.....	437
58.5	Foot of Lloyds Shoals, water surface.....	429
59.5	Pittmans Ferry, large beech tree.....	494.96
59.5	Pittmans Ferry, water surface.....	425
59.55	Head of shoals just below Pittmans Ferry.....	425
59.6	Foot of shoals, water surface.....	423
60.0	Hickory tree 30 feet above mouth of Yellow Water Creek.....	433.97
60.0	Water surface.....	422
61.3	Giles Ferry, large pine tree.....	430.01
61.3	Giles Ferry, water surface.....	420
61.35	Smiths Shoals, head of dam, water surface.....	420
61.35	Smith Shoals, foot of dam, water surface.....	418
61.9	Smiths Shoals, near lower end small island, water surface.....	417
62.8	Foot of Smith Shoals, water surface.....	408
63.0	Smith's Ferry, ash tree 20 feet above landing.....	410.44
63.0	Smith's Ferry, water surface.....	407
64.0	Head of Lamars Shoals, water surface.....	406
64.5	Lamars Shoals, head of dam, water surface.....	403
64.5	Lamars Shoals, foot of dam, water surface.....	398
65.0	Foot of Lamars Shoals, water surface.....	387.5
65.6	Lamars Ferry, water surface.....	384
66.2	Goodmans Ferry, large red oak.....	400.74
66.2	Goodmans Ferry, water surface.....	382
67.0	Mouth of Little Sandy Creek, water surface.....	381
69.1	About one-half mile above Wards Ferry, water surface.....	377
69.9	Wards Ferry, water oak.....	392.69
69.9	Wards Ferry, water surface.....	375
71.5	White paint mark on stone pier 2 feet from end, 4 feet west of western rail Southern Railway bridge over Big Sandy Creek.....	399.45
71.5	Water surface.....	374
72.0	Mouth of Big Sandy Creek, water surface.....	373
74.6	Bridges Ferry, large water oak.....	382.82
74.6	Bridges Ferry, water surface.....	370
75.0	Large dead oak about 4 miles below Bridges Ferry.....	388.15
75.0	Water surface.....	368
76.5	Large red oak, south bank, Towaliga River.....	379.34
76.5	Water surface.....	368
77.5	Head of Glovers Shoals, water surface.....	366
77.8	Glovers Shoals, head of dam, water surface.....	362
77.9	Glovers Shoals, foot of dam, water surface.....	355
78.0	Foot of Shoals at Juliette, water surface.....	351
79.4	Large beech tree 10 feet south of west approach Glovers Ferry.....	361.10
79.4	Water surface.....	346
80.6	Mitchells Ferry, red oak tree 10 feet south of west approach.....	361.74
80.6	Mitchells Ferry, water surface.....	344
81.6	Head of small shoals, water surface.....	343
81.6	Foot of small shoals, water surface.....	342
82.0	Head of small shoals, water surface.....	341
82.05	Foot of small shoals, water surface.....	339
82.5	About one-half mile below shoals water surface.....	337

Elevations on Ocmulgee River from junction of South and Yellow rivers to Macon—Continued.

Distance	Description of points	Elevation above sea level
<i>Miles</i>		<i>Feet</i>
84.5	Thunderwood tree opposite post on Southern Railway, 1 mile above Dames Ferry, 25 feet from river bank.....	340.79
84.5	Water surface.....	330
86.0	Dames Ferry, ash tree 10 feet south of western approach.....	335.63
86.0	Dames Ferry, water surface.....	328
87.0	Carsterpher's mill, head of dam, water surface.....	328
87.0	Carsterpher's mill, foot of dam, water surface.....	322
87.1	Foot of shoals, water surface.....	320
88.5	North abutment of Southern Railway bridge, over Rum Creek.....	347.32
88.5	Water surface.....	318
89.0	Popes Station, in front of top of west rail.....	348.23
89.0	Popes Ferry, water oak.....	326.88
89.0	Popes Ferry, water surface.....	318
89.8	Head of shoals about 1 mile below Popes.....	317
90.0	Foot of shoals.....	312
90.1	Mouth of Tobler Creek.....	312
90.6	Above small shoals, water surface.....	311
90.64	Below small shoals, water surface.....	310
91.2	Above small shoals, water surface.....	309
91.2	Below small shoals, water surface.....	307
92.6	Above small shoals, water surface.....	306
92.6	Below small shoals, water surface.....	304
93.6	Above shoals, water surface.....	302
93.0	Below shoals, water surface.....	300
94.0	Iron post marked "339. Morehead—1898" at Holton Station, Southern Railway, 35 feet north of station, 29 feet west of center of track.....	333.733
94.0	Water surface.....	299
95.0	Above shoals, about one-fourth mile above Beaverdam Creek, water surface.....	296
95.3	Foot of shoals, water surface.....	294
96.0	Head of shoals just above creek, water surface.....	294
96.0	Foot of shoals just above creek, water surface.....	291
96.8	Mouth of Beaverdam Creek, water surface.....	291
96.85	Head of shoals just below Beaverdam Creek, water surface.....	290
96.9	Foot of shoals just below Beaverdam Creek, water surface.....	289
97.1	Head of shoals about one-fourth mile below Beaverdam Creek, water surface.....	289
97.2	Foot of shoals, water surface.....	284
99.8	Virgin, point on west rail at upper switch.....	322.52
99.8	Virgin, water surface.....	282
100.3	About one-half mile below Virgin, water surface.....	281
102.0	Pine tree 100 feet below mouth of small creek just below Macon waterworks, and 30 feet east of right-hand track.....	301.88
102.0	Water surface.....	278
106.5	At Fifth Street Bridge, Macon, Ga.....	276
107.0	Check on tablet at P. O. corner Third and Mulberry streets, Macon.....	333.942

SURVEY OF YELLOW RIVER.

The elevations in the following lists are based upon an aluminum tablet at the Washington street entrance of the State capitol building at Atlanta, marked "1050 M. C.," the elevation of which is accepted as 1,049.546 feet above mean sea level. The initial point is a bench mark of flying levels on Ocmulgee River.

The leveling was done in 1903 for the United States Geological Survey by Joseph Palmer, levelman, under the direction of F. A. Franck, field assistant.

Elevations on Yellow River from mouth to Yellow River.

Distance	Description of points	Elevation above sea level
<i>Miles</i>		<i>Feet</i>
0.0	Pine opposite mouth of Yellow River.....	506.94
0.0	Water surface.....	500
0.5	Ash, 10 feet from bank, opposite Indian Fishery Shoals.....	517.24
	Foot of Indian Fishery Shoals, water surface.....	504
	Head of Indian Fishery Shoals, water surface.....	516
1.1	Mouth of small stream, water surface.....	516.6
2.5	Allens Bridge, maple 20 feet from stream on east bank.....	528.49
2.5	Allens Bridge, water surface.....	517
	Foot of Allens Shoals, water surface.....	517
	Head of Allens Shoals, water surface.....	519
3.3	Mouth of stream coming in from east, about 3 miles above Allens Shoals, water surface.....	520
4.7	Ash tree, west bank river, Lees Shoals.....	528.49
4.7	Foot of Lees Shoals, water surface.....	520
	Head of Lees Shoals, water surface.....	523
6.2	Picketts Bridge, white oak, east bank.....	539.23
6.2	Picketts Bridge, water surface.....	526
6.5	Water surface.....	527
7.5	100 feet below small stream, water surface.....	528
9.0	Mouth of small stream, water surface.....	529
10.7	Flat Shoals Bridge, white oak, west bank river.....	551.24
10.7	Flat Shoals Bridge, water surface.....	534
13.1	Small creek from west, water surface.....	537
13.8	White oak, foot of Langston Shoals, 15 feet from stream, west bank.....	549.69
13.8	Water surface.....	539
	Head of Langsdon Shoals, water surface.....	543
15.2	Near mouth of small stream, water surface.....	544
16.0	Below shoals, water surface.....	545
	Above shoals, water surface.....	547
16.9	Porterdale Shoals, white oak 10 feet from stream, west bank, 60 feet from foot of shoals.....	561.05
16.9	Porterdale Shoals, water surface.....	549
	Porterdale, foot of dam, water surface.....	604
	Porterdale, head of dam, water surface.....	616
17.7	Porterdale Bridge, white oak 20 feet from south approach.....	613.38
17.7	Porterdale Bridge, water surface.....	616
17.7	Porterdale, rod held on top steel post of railing at extremesouth end of steel bridge.....	627.81
18.7	River at sharp bend, water surface.....	616
20.8	Sweet gum 10 feet from stream, 60 feet above Browns Bridge.....	622.81
20.8	Water surface.....	616
	Three-fourths mile above Browns Bridge, water surface.....	616
21.5	About 1 mile above Browns Bridge, water surface.....	616
22.0	At mouth of Hurricane Creek, one-half mile below Woods Bridge, water surface.....	616
22.8	Woods Bridge, poplar tree.....	627.49
22.8	Woods Bridge, water surface.....	617
23.0	Chisel mark on large rock under Georgia Railroad bridge, west bank.....	642.05
23.0	Water surface.....	617
23.0	Foot of small shoal under Georgia Railroad bridge, water surface.....	617
23.2	About one-sixth mile above railroad bridge, water surface.....	619
23.7	Small creek, west bank, water surface.....	619.2
24.3	Hardwick Bridge, water oak on north bank.....	639.11
24.3	Hardwick Bridge, water surface.....	620.3
24.8	About one-half mile above bridge, water surface.....	620.7
25.0	Water surface.....	620.8
26.0	Water oak, opposite mouth of Haynes Creek.....	632.26
26.0	Water surface.....	624.6
27.1	Water surface.....	629
28.2	McDaniels Bridge, large water oak on west bank.....	644.17
28.2	McDaniels Bridge, water surface.....	632
	Foot of dam, McDaniels Mill, water surface.....	632
	Head of dam, McDaniels Mill, water surface.....	641
29.0	Bank, opposite small islands.....	641
30.5	Large white-oak 10 feet below Pinelog Bridge.....	650.55
30.5	Water surface.....	641
31.1	About one-half mile above bridge, water surface.....	641
32.2	Tall pine, left bank, 100 yards above Boartusk Creek.....	653.96
32.2	Water surface.....	644
32.6	Three-tenths mile below Milstead, water surface.....	645
32.8	Pine at foot of shoals at Milstead.....	657.41
32.8	Water surface.....	647
	In shoals, water surface.....	657
	In shoals, water surface.....	667
33.0	Foot of dam, water surface.....	677
33.0	Top of dam, water surface.....	692

ALTAMAHA DRAINAGE BASIN, RIVER SURVEYS

213

Elevations on Yellow River from mouth to Yellow River—Continued.

Dis- tance	Description of points	Elevation above sea level
<i>Miles</i>		<i>Feet</i>
33.0	Milstead, large white-oak 40 feet above bridge between main and side tracks south bank.....	701.33
33.0	Milstead, water surface.....	692
35.4	Ervins Bridge, hickory on west bank, 20 feet above bridge.....	697.83
35.4	Ervins Bridge, water surface.....	697
36.5	Water-oak, east bank, about 1 mile above bridge.....	700.62
36.3	Water surface.....	694
38.0	Water surface.....	697
38.5	Water surface.....	698
39.4	Johnstons Bridge, on top of iron bolt, extreme end of bridge, eastern entrance.....	717.53
39.4	Johnstons Bridge, water surface.....	702
40.2	About 0.6 mile above bridge, water surface.....	705
40.3	Water surface.....	707
40.8	Below small shoals, water surface.....	709
40.9	Above small shoals, water surface.....	711
40.9	White paint mark on stone masonry to old dam, west bank.....	722.88
40.9	Water surface.....	711
40.9	Head of old dam, water surface.....	712
41.3	Foot of small shoals, water surface.....	714
41.3	Head of small shoals, water surface.....	715
41.9	White oak, 20 feet from stream, opposite small shoals, east bank.....	730.91
41.9	Water surface.....	715
42.4	Head of shoals, water surface.....	717.6
42.4	White oak, opposite mouth of Mountain Creek.....	727.91
42.4	Foot of shoals, water surface.....	718
42.8	Head of shoals, water surface.....	720
42.8	Head of shoals, water surface.....	723
43.2	Rock Bridge, white paint mark on top of stone pier.....	740.60
43.2	Rock Bridge, water surface.....	724
43.7	Water surface.....	726
44.0	Ash tree, 10 feet from stream, west bank.....	728.48
44.0	Water surface.....	727
45.5	Hickory tree, opposite foot of shoals.....	748.83
45.5	Water surface.....	729
45.5	Head of shoals, water surface.....	733
46.2	Foot of shoals, opposite sand island below old Annistown, water surface.....	737
46.2	One-fourth mile below Haydens Bridge, water surface.....	738
46.6	In shoals, water surface.....	747
47.0	Annistown, foot of dam, water surface.....	760
47.0	Annistown, head of dam, water surface.....	771
47.2	Haydens Bridge, large birch on east bank.....	777.64
47.5	20 yards above creek, water surface.....	771
48.6	Chisel mark on large rock, opposite old mill, east bank.....	788.55
48.6	Water surface.....	722
48.6	Head of shoals, water surface.....	786
48.9	Head of shoals, water surface.....	787
49.1	About one-half mile above shoals, water surface.....	809.94
50.5	Sextons Bridge, on top iron bolt, stone pier.....	791
50.5	Water surface.....	808.42
51.7	Large pine, opposite shoals.....	793
51.7	Water surface.....	797
51.7	Foot of shoals, water surface.....	802
51.7	Head of shoals, water surface.....	818.17
53.0	Hickory tree at head of shoals.....	804
53.0	Water surface.....	807
54.0	Water surface.....	825.41
55.0	Yellow River Bridge, white oak.....	815
55.0	Yellow River Bridge, water surface.....	818
55.2	Head of shoals, water surface.....	834.86
55.7	Large water oak, about 100 yards above Simmons mill, east bank.....	819
57.3	Simmons Mill, below dam, water surface.....	826
57.3	Simmons Mill, head of dam, water surface.....	

SURVEY OF ALCOVY RIVER.

The elevations in the following lists are based upon an aluminum tablet at the Washington street entrance of the State capitol building at Atlanta, marked "1050 M. C.," the elevation of which is accepted

as 1,049.546 feet above mean sea level. The initial point is a bench mark of flying levels on Ocmulgee River.

The leveling was done in 1903 for the United States Geological Survey by Joseph Palmer, levelman, under the direction of F. A. Franck, field assistant.

Elevations on Alcovy River from mouth to Dabneys Bridge.

Dis- tance	Description of points	Elevation above sea level
<i>Miles</i>		<i>Feet</i>
0.0	White oak, west bank of Ocmulgee River, and opposite mouth of Alcovy River...	494.27
0.0	Water surface.....	484
1.0	Ash, right bank, upstream.....	493.73 ^u
1.0	Water surface.....	487
2.0	Ash, east bank, upstream.....	498.40 ^o
2.0	Water surface.....	492
3.9	Waters Bridge, right bank, spike in northeast corner.....	506.55 ^u
3.9	Waters Bridge, water surface.....	493
4.9	Ash on west bank.....	505.37 ^o
4.9	Water surface.....	497
5.9	Birch on left bank.....	505.51
5.9	Water surface.....	500
6.3	Foot of Mackey Shoals, ash, left bank opposite shoals.....	512.77 ^o
6.3	Water surface.....	502
6.4	Head of Mackeys Shoals, water surface.....	504
8.2	Birch opposite Mackeys Second Shoals at foot of left bank, upstream, nail in root of birch tree.....	518.5 ^o
8.2	Water surface.....	505
8.4	Head of Mackeys Second Shoals, water surface.....	508
9.0	Foot of Newton Factory Shoals, water surface.....	509
9.2	Newton Factory Shoals, black gum opposite dam at White's mill.....	562.86 ^u
9.2	White's mill, foot of dam, water surface.....	553
9.2	White's mill, head of dam, water surface.....	558
9.8	Lower side Newton Factory Bridge, top of bolt marked with white paint.....	592.81 ^u
9.8	Water surface.....	582
10.0	Head of Newton Factory Shoals, water surface.....	592
10.8	Red-oak tree about 1 mile above bridge.....	619.88 ^u
10.8	Water surface.....	593
11.5	Foot of shoals, water surface.....	594
11.55	Head of shoals, water surface.....	596
12.3	Water oak, left bank.....	604.50 ^u
12.3	Water surface.....	597
13.0	Beech tree opposite shoals.....	604.88 ^u
13.0	Water surface.....	598
.....	Head of shoals, water surface.....	600
13.3	Sweet-gum tree, east bank of river.....	612.85 ^u
14.0	One mile below Henderson's mill, water-oak, left bank.....	620.76
14.0	Water surface.....	602
15.0	Henderson's mill, post oak at bridge, right bank.....	618.99 ^u
15.0	Water surface.....	604
15.0	Henderson's mill, foot of dam, water surface.....	607
15.0	Henderson's mill, head of dam, water surface.....	613
18.3	Dabneys Bridge, water oak, west bank.....	627.22 ^u
18.3	Dabneys Bridge, water surface.....	615

SURVEY OF TOWALIGA RIVER.

The elevations in the following lists are based upon an aluminum tablet at the Washington street entrance of the State capitol building at Atlanta, marked "1050 M. C.," the elevation of which is accepted as 1,049.546 feet above mean sea level. The initial point is a bench mark of flying levels on Ocmulgee River.

The leveling was done in 1903 for the United States Geological

Survey by Joseph Palmer, levelman, under the direction of F. A. Franck, field assistant.

Elevations on Towaliga River from mouth to High Falls Bridge.

Dis- tance	Description of points	Elevation above sea level
<i>Miles</i>		<i>Feet</i>
0.0	Water oak, south side at mouth of river.....	379.34
0.0	Water surface.....	367
1.7	On root of beech tree, east bank, 50 feet from stream at Lamars Bridge.....	382
1.7	Water surface.....	371
2.2	Ash tree one-half mile above Lamars Bridge at mouth of small creek.....	377.36
2.2	Water surface.....	373
3.7	Water surface.....	376
4.0	Large pine tree 50 feet from river, west bank.....	412.45
4.0	Water surface.....	379
4.6	Water surface.....	382
6.0	Hunting Shoals Bridge, top of iron bolt on stone pier.....	412.80
6.0	Hunting Shoals Bridge, water surface.....	386
7.0	Twin water oak 10 feet from stream, north bank going up.....	389.49
7.0	Water surface.....	383
8.8	Jacksons Bridge, poplar tree, west bank.....	409.84
8.8	Jacksons Bridge, water surface.....	395
9.5	Water surface.....	397
10.5	Pine, 100 yards above creek, west bank, 10 feet from river.....	416.15
10.5	Water surface.....	400
11.8	Water oak, 10 feet below Wilsons Bridge.....	421.06
11.8	Water surface.....	406
12.3	Water oak about one-half mile above Wilsons Bridge, west bank.....	431.01
12.3	Water surface.....	410
13.3	North Fork, birch tree about 100 yards above junction of North and South forks.....	416.93
13.3	Water surface.....	414
14.0	Foot of shoals, water surface.....	418
14.0	Head of shoals, water surface.....	421
15.0	Foot of shoals, water surface.....	422
15.0	Head of shoals, water surface.....	428
15.0	Birch tree, north bank, opposite shoals.....	432.23
15.5	Foot of shoals, water surface.....	429
15.6	Head of shoals, water surface.....	434
16.0	Morans Bridge, right bank, white oak 20 feet below bridge.....	443.61
16.1	Morans Bridge, foot of shoals, water surface.....	437
16.1	Morans Bridge, head of shoals, water surface.....	439
17.4	Willow opposite shoals.....	449.74
17.4	Water surface.....	448
17.5	Foot of shoals, water surface.....	446
17.5	Head of shoals, water surface.....	450
18.0	Pine at mouth of Tobes Creek.....	457.48
18.0	Water surface.....	452
18.5	Foot of shoals, water surface.....	452
18.5	Head of shoals, water surface.....	454
18.7	Foot of small shoals, water surface.....	455
18.7	Head of small shoals, water surface.....	457
19.2	Birch tree, south bank, 20 feet above small stream.....	462.60
21.1	Foot of Long Shoals, white oak.....	474.31
21.1	Water surface.....	466
21.2	Foot of High Falls, water surface.....	492
21.3	High Falls Bridge, north approach, top of iron bolt, west side.....	563.32
21.3	Water surface.....	524
21.7	Head of Long Shoals, opposite old dam, water surface.....	561

SURVEY OF OCONEE AND MIDDLE OCONEE RIVERS.

The survey of Oconee River from Milledgeville to mouth of Apalachee River was made in 1885 by C. A. Locke, assistant engineer, U. S. Army. The survey of Oconee River above mouth of Apalachee River and of Middle Oconee River was made in July and August, 1902, by J. B. High, under the direction of B. M. Hall, of the United States Geological Survey.

WATER POWERS OF GEORGIA

Elevations on Oconee and Middle Oconee rivers above Milledgeville.

OCONEE RIVER.

Dis- tance	Description of points	Elevation above sea level
<i>Miles</i>		<i>Feet</i>
0	Below Treanor's milldam at Milledgeville, water surface.....	215.5
0	Above Treanor's milldam, water surface.....	222
3.7	Foot of Furman's Shoals, water surface.....	224.5
4.5	Oconee Electric Power Company's dam site, water surface.....	239.5
7.5	Fraleys Ferry, water surface.....	254
8.0	Below Fraleys Mill Shoal, water surface.....	256
8.4	Above Fraleys Mill Shoal, water surface.....	263
10.8	Mouth of Little River, water surface.....	266
13.4	Rock Landing, water surface.....	275
14.1	Ferry, water surface.....	277
15.4	Mouth of Crooked Creek (right bank), water surface.....	282
17.2	Mouth of Rocky Creek (right bank), water surface.....	290.5
22.7	Putnam Mineral Springs (right bank), water surface.....	305
23.9	Mouth of Log Dam Creek (left bank), water surface.....	307.5
24.6	Warrens Old Ferry, water surface.....	309
26.5	Mouth of Shoulderbone Creek (left bank), water surface.....	310.5
27.9	Ferry, water surface.....	313.3
29.5	Foot of Shoal, water surface.....	322
30.6	Rope Ferry on Laurens Shoals, water surface.....	332
31.9	Below Laurens milldam (8-foot dam), water surface.....	345
31.9	Above Laurens milldam (8-foot dam), water surface.....	353
32.3	Mouth of Richland Creek (left bank), water surface.....	353
33.1	Top of Laurens Shoals, end of pond, water surface.....	353
33.6	Foot of Methodist Fishery or Riley Shoals, water surface.....	354
34.3	Top of Methodist Fishery or Rileys Shoals, water surface.....	384
35.0	Ferry and old piers, below Spivey's mill, water surface.....	396
35.8	Top of Long Shoals, water surface.....	399
38.2	Foot of Hills Shoals, water surface.....	403
38.6	Top of Hills Shoals, water surface.....	404
45.8	Mouth of Sugar Creek (right bank), water surface.....	411
50.5	Below Parks milldam, water surface.....	416
50.5	Above Parks milldam, water surface.....	426
54.0	Georgia Railroad Bridge, Carey, water surface.....	426
54.0	E. M. base of rail, east end of Georgia Railroad bridge, Carey.....	465.93
58.8	Willis Ferry, cottonwood tree on left bank, north side of road.....	435.67
58.8	Willis Ferry, water surface.....	430
59.8	Ironwood tree on left bank, 25 feet below mouth of Town Creek.....	440.21
59.8	Mouth of Town Creek, water surface.....	430.3
65.0	Hickory on right bank, 10 feet from mouth of Greenbrier Creek.....	439.5
65.0	Mouth of Greenbrier Creek, water surface.....	437.6
65.7	Daniels Ferry, large water oak on right bank, 120 feet from river.....	451.14
65.7	Daniels Ferry, water surface.....	438
66.8	Leaning willow on right bank, opposite mouth of Fishing Creek.....	447.27
66.8	Mouth of Fishing Creek, water surface.....	440.6
68.4	Mouth of Harris Creek, water surface.....	444
69.0	One mile below Wrays Ferry and one-half mile above Harris Creek, water surface.....	445
70.0	Wrays Ferry, water surface.....	446.2
70.0	Wrays Ferry, box elder on right bank, 20 feet from river.....	462.39
71.2	Mouth of Allison Creek, water surface.....	448
71.2	Mouth of Allison Creek; birch on right bank.....	454.44
72.7	Mouth of Rose Creek, water surface.....	450.3
72.7	Large leaning willow, on right bank, 40 feet below Rose Creek.....	454.88
72.9	Scull Shoals, 125 feet above ferry, water surface.....	453.4
72.9	Scull Shoals, white oak on left bank, 125 feet above ferry.....	460.98
76.2	Mouth of Falling Creek, water surface.....	456.6
76.2	Maple leaning over Falling Creek, on left bank, 30 feet above mouth.....	464.78
78.6	Mouth of Big Creek, water surface.....	459.7
78.6	Large maple on left bank of Big Creek, 75 feet from mouth.....	464.05
83.3	Mouth of Shoal Creek, water surface.....	465
83.3	Sycamore on left bank of Shoal Creek, 3 feet from mouth.....	471.95
83.7	Foot of Barnetts Shoals, water surface.....	466.2
83.7	Foot of Barnetts Shoals, willow on left bank.....	474.9
86.0	Top of Barnetts Shoals, 600 feet below bridge, water surface.....	517.7
86.0	Large mulberry on left bank, 600 feet below Barnetts Bridge.....	532.2
86.1	Barnetts Bridge, water surface.....	517.3
86.1	Barnetts Bridge, nail in right bank pier, 1½ feet above ground.....	523.76
87.5	Mouth of Cedar Creek, water surface.....	518.3
88.9	Junction of North Oconee and Middle Oconee rivers, water surface.....	519.3
88.9	Twin willow on right bank, opposite mouth of North Oconee.....	528.62

ALTAMAHA DRAINAGE BASIN, RIVER SURVEYS

217

Elevations on Oconee and Middle Oconee rivers above Milledgeville—Continued.

MIDDLE OCONEE RIVER.

Dis- tance	Description of points	Elevation above sea level
<i>Miles</i>		<i>Feet</i>
89.5	Central Railroad bridge, water surface.....	525.3
90.8	Simonton's wagon bridge, water surface.....	530.2
90.8	Nail in left-bank pier, 2 feet from ground.....	544.08
92.0	Opposite mouth of Barbers Creek, water surface.....	536
93.5	Princeton Factory, 60 feet below end of tailrace, water surface.....	541
93.5	Sycamore on left bank, 100 feet above Princeton Bridge.....	546.31
93.7	Princeton Factory, headrace above wheels, water surface.....	557.4
95.0	Bobbin Mill Creek, water surface.....	558.9
95.0	Root of birch on left bank, 75 feet below Bobbin Mill creek.....	566.32
96.7	Below Jennings Shoal, water surface.....	561.5
96.7	Above Jennings Shoal, water surface.....	566.5
96.7	Ring cut on old masonry pier, 30 feet from river, left bank.....	575.08
97.9	River surface at Mitchells Bridge.....	572.2
97.9	Nail in upstream face of left bank pier, 5 feet from ground.....	577.15
98.8	Above dam at Athens electric plant, water surface.....	598.3
99.8	Seaboard Air Line railroad bridge, water surface.....	599
104.6	Foot of Tallassee Shoal, water surface.....	607.5
104.6	Large birch at mouth of tailrace, left bank.....	624.67
105.2	Crest of dam at Tallassee bridge water power, water surface.....	654.5
105.2	Spillway of headrace, Tallassee bridge water power, water surface.....	655
107.0	Upper end of pond, water surface.....	655
108.5	1,400 feet below Nixons Ford, water surface.....	659.5
108.5	Sycamore on right bank, 1400 feet below Nixons Ford.....	670.22
108.8	Above small shoal at Nixons Ford, water surface.....	662.8
109.4	Water surface.....	663.2
110.7	Water surface.....	666.6
111.4	Water surface.....	670
112.5	Lanier's pasture, water surface.....	672.6
112.9	Mouth of McCleskey's Branch, water surface.....	674.6
112.9	White oak on right bank, McCleskey Branch.....	692.35
113.5	Mouth of Beech Creek, water surface.....	674.6
113.5	Large hickory on left bank, opposite Beech Creek.....	686.52
114.8	Mouth of Mulberry Fork, water surface.....	677.6
114.8	Large wahoo, 5 feet from left bank, opposite Mulberry Fork.....	686.51
115.9	McElhannon Bridge, water surface.....	678
118.7	Bend of river, one-half mile below Johnson's Mill, water surface.....	690
119.2	Below Johnsons milldam, water surface.....	690.7
119.2	Above Johnsons milldam, water surface.....	698
119.2	Top of left bank iron pier, upstream truss, Johnsons Bridge.....	713.21
121.9	Shockleys Bridge, water surface.....	699.7
123.2	Howards Bridge, water surface.....	701
126.8	Mouth of Academy Branch, water surface.....	704.5
128.3	Gainesville, Jefferson and Southern Railroad bridge, water surface.....	715.8
128.3	Nail in base of first bent, upstream, left bank, over Pond Fork.....	725.1

SURVEY OF APALACHEE RIVER.

The survey of Apalachee River was made in July and August, 1902, by J. B. High, under the direction of B. M. Hall, of the United States Geological Survey.

Elevations on Apalachee River from mouth to High Shoals.

Dis- tance	Description of points	Elevation above sea level
<i>Miles</i>		<i>Feet</i>
0	Carey, water surface.....	426
1.5	Penick's Ferry, water surface.....	427.7
1.5	Penick's Ferry, sweet gum 50 feet from right bank.....	437.02
9.8	Below Reid's old dam, water surface.....	440.8
9.8	Above Reid's old dam, at mouth of Goose Creek, water surface.....	441.9
10.7	Reids Ferry Bridge, water surface.....	442
10.7	Reids Ferry Bridge, top of downstream iron pier, left bank.....	446.35
13.2	Mouth of Hard Labor Creek, water surface.....	444.4
13.2	Birch on right bank, 10 feet below mouth of Hard Labor Creek.....	449.76
16.3	Trimbles Bridge, water surface.....	452.4
16.3	Trimbles Bridge, large ash on island at center of bridge.....	455.63
21.8	Heads Bridge, top of upstream iron pier, right bank.....	500.53
21.8	Below Head's old milldam, water surface.....	477.3
21.8	Above Head's old milldam, water surface.....	480.8
21.9	Foot of Furlow Shoals, water surface.....	480.8
22.3	Base of rail, Central Railroad bridge.....	559.08
22.4	Top of Furlow Shoals, water surface.....	507.2
25.0	Mouth of Jacks Creek (river high from rain).....	517.9
25.0	Large hickory on Jacks Creek, 50 feet from right bank of river.....	526.23
27.1	Foot of shoals, 1,000 feet below Price's mill, water surface.....	544.6
27.3	Above dam at Price's mill, water surface.....	564
27.3	Bench mark cut in large rock on right bank, 50 feet below dam.....	565.9
31.6	Below foot of shoal, water surface.....	580.7
31.8	Near bridge at High Shoals Factory, water surface.....	623.8
31.8	Top of projection of rock basement, southwest corner High Shoals Factory.....	631.44

SURVEY OF MULBERRY FORK OF OCONEE RIVER.

The survey of Mulberry Fork of Oconee River was made in July and August, 1902, by J. B. High, under the direction of B. M. Hall, of the United States Geological Survey.

Elevations on Mulberry Fork of Oconee River from mouth up to Hoschton.

Dis- tance	Description of points	Elevation above sea level
<i>Miles</i>		<i>Feet</i>
0	Mouth of Mulberry Fork, water surface.....	677.6
0.3	Lower Mulberry Bridge, water surface.....	679.1
4.3	Hancocks Bridge, water surface.....	691
4.3	Hancocks Bridge, top of iron pile, right bank, downstream.....	702.79
9.8	Moons Bridge, water surface.....	707.5
12.8	Gainesville, Jefferson and Southern Railroad bridge, water surface.....	713.7
16.7	Mathis bridge, water surface.....	735.5
18.6	Mulberry Forks, 2 miles from Hoschton, water surface.....	739.2
18.6	Root of large post oak, left bank, 25 feet below fork.....	743.7

WATER POWER IN ALTAMAHA RIVER DRAINAGE
BASIN.

In the foregoing lists of water-surface elevations a complete statement of the fall and its distribution is given. The various points at which the surface elevations are shown are located by continued distances and reference to describable objects along the river. Records of the discharge at several hydrographic stations have been given, from which estimates of flow can be made for any point. To these is added a brief statement regarding the powers already developed, and some of the proposed grouping of the various shoals into proposed power developments.

WATER POWERS ON SOUTH RIVER.

From the Southern Railway bridge crossing South River near Constitution down to the head of Albert Shoals, a distance of 20 miles, the fall is about 100 feet. The stream is small, however, and only small amounts of power are obtainable. Flake's mill, about 13 miles from the beginning point, is the first power now utilized. At this place the dam is about 6 feet high and the working head, obtained by the use of a short canal, is about 11 feet.

At Flat Shoals, about 4 miles farther down the river, a new electric plant has been recently established. At Albert Shoals there is a fall of 16 feet in half a mile. This has been partly developed, but is not now used.

At Peachstone Shoals, 36 miles from the initial point, the power is developed by a low dam and a short canal, utilizing about 10 feet head, and operating Zackry's grist and cotton mill.

At Snapping Shoals, 7 miles below, the fall is 20 feet in 300 yards. This is partly utilized and operates De Loach's wood-working, flouring, and grist mills.

Three miles below is Island Shoals, where the fall is 10 feet in 250 yards and is partly developed at Haley's flour mill.

WATER POWERS ON OCMULGEE RIVER.

At the junction of Yellow and South rivers is the head of Barnes Shoals, where the fall is 9 feet in a short distance. A development here would have the additional water from Yellow River. Includ-

ing the last-mentioned shoal, the fall is 14 feet from Yellow River down to Alcovy River.

Below Alcovy River down to the foot of Lloyds Shoals, 1 mile above Pittmans Ferry, the fall is 55 feet in a little less than 5 miles.

The continuous shoals that make up this fall of 55 feet are known locally as Dotsons, BARNETTS, BARNES, and Capps and Lloyds. The most precipitous part of this slope is the lower half, which has a fall of 43 feet in $2\frac{1}{2}$ miles, and is known as Lloyds, or Capps and Lloyds, Shoals. Surveys have been made for a 60-foot development of this power, to back water to the foot of Barnes Shoals, near mouth of Yellow River, and to raise the water level 5 feet at the mouth of Alcovy River. This development can be made with a dam near foot of Lloyds Shoals, or as contemplated in the surveys mentioned, by a lower dam farther up, and a canal.

Smiths Shoals, extending from below Giles Ferry to Smith's mill, has a fall of 12 feet in $1\frac{1}{2}$ miles. This is partly developed for Smith's mill by a low dam and a long, small canal.

The next power below is at Lamar's mill, a large merchant mill for grinding corn and wheat. The fall here is about 20 feet in 1 mile. About 16 feet of the fall is partly developed by a wing dam and a short canal. If the dam were extended and raised 4 feet, the head would be 20 feet, without backing water on the next property above. The last three powers mentioned—Lloyd's, Smith's, and Lamar's—are above the Flovilla hydrographic station, located at Lamars Ferry.

The next power is at Juliette, where the fall is 15 feet in one-half mile. This is developed by a dam and a short canal, and operates the Glover Cotton Mills and the Juliette Milling Company's plant. From the tail water below the Glover mill to the mouth of Beaverdam Creek, below Holton, a distance of about 18 miles, there is a fall of about 60 feet. Macon capitalists have had surveys made for a proposed development of this fall, or a large portion of it.

WATER POWERS ON YELLOW RIVER.

Yellow River flows in a southeasterly direction, and joins South River, forming the Ocmulgee. It contains some valuable power sites, both developed and in a natural condition.

One-half mile above its mouth are the Indian Fishery Shoals,

where there is a fall of 12 feet in about 200 feet. The river is here about 300 feet wide. A gristmill and a cotton gin in operation use perhaps nine-tenths of the available power.

For 13 miles above, the river runs between high banks, alternating with low bottoms without any marked shoals (except at Lees, where there is a fall of $2\frac{1}{2}$ feet) to Langdons Shoals. The total fall in this 13 miles is 23 feet. Langdons Shoals has a 4-foot fall.

Three miles above, at Porterdale, is the finest power site on the river, where extensive developments have been made by the Bibb Manufacturing Company, which has a large cotton and twine factory at this point. Here there is a fall of 67 feet in one-half mile, with a 12-foot dam at the upper end of the shoal. The banks at the foot are very high, but gradually lower, until just above the dam large bottoms begin and continue for 5 miles. The water is backed up as far as the mouth of Hurricane Creek, 5 miles above.

The next power, McDaniels Shoals, has a 7-foot fall in a very short distance, and there is now a 6-foot dam operating a gristmill. At Milstead, Ga., $4\frac{1}{2}$ miles above, there is a fall of 45 feet in one-half mile. This power has recently been developed and is used to operate a large cotton mill.

Eleyen miles above is Annistown Shoals, with a 25-foot fall below the 11-foot dam, which formerly supplied storage for power used to operate a cotton mill. The banks here are all hard, unseamed rock, and the site could be developed into valuable property. Two and one-half miles above are some shoals with a 14-foot fall in half a mile. Above this point the river flows through a very rough country, having a fall of about 36 feet in 6 miles, but passing no important shoals until the next power is reached at Yellow River, Ga., the end of the survey. Here is a dam 7.3 feet high, which operates the Simon roller mills.

WATER POWER ON ALCOVY RIVER.

From the mouth of Alcovy River up to the foot of Whites Shoals, a distance of 9 miles, the fall is 25 feet. Whites Shoals and Newton Factory Shoals form one continuous series, with a fall of 83 feet in 1 mile. Here the river is in a gorge 300 feet wide, with banks over 100 feet high in several places. Near the middle of this shoal is an excellent site for a dam, from which a canal about one-half mile long

would be required. At the upper end of the shoals is another good site for a dam, which would have a much greater storage basin, as just above the gorge widens a great deal and a large volume of water could be stored through the dry season. This development would require a canal for the entire length of the shoals. An old corn mill is in operation at this point, using a small wooden dam to divert the water into its flumes. Many years ago a large cotton factory stood on this site, but was burned and never rebuilt.

Six miles above these shoals are Henderson Shoals, with a fall of 2 feet. To obtain power for a gristmill, a 6-foot dam has been erected, the backwater from which extends to Dabneys Bridge, 4 miles above.

WATER POWER ON TOWALIGA RIVER.

Towaliga River flows in a southeasterly direction and empties into Ocmulgee River. From its mouth up to the foot of High Falls, a distance of 21 miles, the fall is about 100 feet. The stream is narrow and swift, but has no marked shoals in this portion nor any favorable power sites. At High Shoals there is a fall of 95 feet in a distance of 1,000 yards, in the middle of which there is a sudden drop of 42 feet, known as High Falls. This is an excellent power site, for, although the low-water flow is small, there is a good basin above for storage. This power has been recently developed and an electric plant installed.

WATER POWERS ON OCONEE RIVER AND TRIBUTARIES.

At Milledgeville a large mill for grinding wheat and corn is operated by water power, the development for which is a low dam across Oconee River and a canal along the west bank about one-half mile long.

At the foot of Furmans Shoals, about 4 miles above Milledgeville, begins a very fine water power. The fall here is 41 feet up to the mouth of Little River, 7 miles above, about 30 feet of the fall being in half the distance. Extensive surveys for the development of the power have been made, and more recently it is proposed to develop about 50 feet of head, backing water above the mouth of Little River.

From the mouth of Little River to the foot of Laurens Shoals,

a distance of 19 miles, the fall is 56 feet, and is almost uniformly distributed.

At Laurens Shoals the fall is 31 feet in $3\frac{1}{2}$ miles. Immediately above, at Rileys or Methodist Fishery Shoals, the fall is 30 feet in three-fourth mile, and continuing up the river, the fall is 15 feet in the next $1\frac{1}{2}$ miles, to top of Long Shoals.

The last three shoals have a total fall of 77 feet from the foot of Laurens Shoals to the head of Long Shoals, a distance of $6\frac{1}{4}$ miles.

At Park's mill, $3\frac{1}{2}$ miles below the mouth of Apalachee River, the working head is 10 feet, developed by a dam of that height. In the 22 miles above Park's mill to foot of Scull Shoals the fall is only 25 feet. At Scull Shoals the fall is about 6 feet in several miles length.

At Barnetts Shoals there is a fine water power, the fall being 51 feet in a distance of $2\frac{1}{4}$ miles. About 3 miles above is the junction of North Oconee and Middle Oconee rivers. On each of these streams there are several developed water powers in the vicinity of Athens.

MINOR ATLANTIC DRAINAGE BASINS.

SATILLA RIVER DRAINAGE BASIN.

MISCELLANEOUS MEASUREMENTS.

Satilla River.—A measurement was made September 9, 1904, at the covered wagon bridge, 3 miles east of Waycross. The bench mark is the center of lag bolt driven into the left side of the first floor beam from the first pier from the left bank, 20.00 feet above the datum of the gage.

Width, 108 feet; area, 1,077 square feet; mean velocity, 1.07 feet per second; gage height, 8.2 feet; discharge, 1,150 second-feet.

Hurricane Creek.—This stream is an important tributary of Satilla River, entering from the north. A measurement was made on it on September 10, 1904, at Baxley's bridge, near Blackshear. The bench mark is a large nail driven into the downstream end of the floor beam over the second pier from the right bank, 15.00 feet above the datum of the gage.

Width, 67 feet; area, 415 square feet; mean velocity, 1.35 feet per second; gage height, 6.57 feet; discharge, 562 second-feet.

APALACHICOLA RIVER DRAINAGE BASIN.

DESCRIPTION OF BASIN.

The rivers flowing into the eastern portion of the Gulf of Mexico are for the most part similar in character to those in the Southern Atlantic drainage, though in their lower courses their flow is usually more sluggish.

Apalachicola River is formed by the union of Flint and Chattahoochee rivers at the Georgia-Florida line and flows in a southerly direction through Florida to the Gulf of Mexico. It is navigable, and boats run up Flint River to Albany and up the Chattahoochee River to Columbus.

Flint River rises a few miles south of Atlanta, in Fulton County, and flows in a southerly direction to Talbot County, southeasterly to Macon County, southerly to Worth County, and southwesterly to Apalachicola River. It drains the south-central portion of Georgia, extending from Atlanta south to the Florida line. Its tributaries are mainly large creeks with much fall. The principal ones among these are Whitewater, Redoak, Big Potato, Muckalee, Kinchafoonee, Ichawaynochaway, and Spring creeks.

Flint River has many good water powers on its course. Between Woodbury and Knoxville, Crawford County, a distance of about 45 miles, the river falls 334 feet. Very little of its power is yet developed.

Chattahoochee River rises in the Blue Ridge, in White County, and flows in a southwesterly direction until it reaches the Alabama line at the southwest corner of Troup County. From there it flows in a southerly direction, forming the western boundary of Georgia, until it flows into Apalachicola River at the southern boundary of the State. It drains almost all of the north-central, middle-west, and southwest portions of Georgia, and has a drainage area of 4,900 square miles at Columbus, which is at the fall line.

Soque River joins the Chattahoochee on the western edge of Habersham County. This river rises in Habersham County and flows in a southwesterly direction. It has considerable fall, dropping as much as 40 feet within a few hundred feet.

Farther down the Chattahoochee, at the west boundary of Hall County, Chestatee River enters. It rises in Lumpkin County and

flows in a southerly direction through a very hilly and steep country and has much fall all along its course.

From its source down to Columbus the Chattahoochee River is an excellent water-power stream. From the lower edge of Lumpkin County down to Columbus, Ga., there is a fall of over 850 feet, 366 feet of this fall being between West Point and Columbus. All along its course there are many small tributaries flowing from a high, hilly country. These have much fall, and many small water powers are available.

STREAM FLOW.

CHATTAHOOCHEE RIVER NEAR CORNELIA.

This station was established as a bench-mark station. It is located at Duncan Bridge, about 7 miles northwest of Cornelia, Ga., and 1 mile below the mouth of Soque River. Discharge measurements are made from the downstream side of the inclosed wooden highway bridge, the meter being lowered through holes cut in the floor or by raising a plank. The initial point for soundings is the end of the bridge at the left bank, downstream side. The channel is curved for about 500 feet above and straight for about 800 feet below the station. The current is moderate. The right bank is clean, and overflows for about 200 feet. The left bank is high, rocky, wooded, and does not overflow. The bed of the stream is composed of rock at the left and silt at the right bank, free from vegetation, and shifting. There is but one channel at all stages, broken by the piers of the bridge. A fish-trap dam about 800 feet below the bridge will probably affect the rating at this station. The bench mark is the top of downstream stringer at a point 59 feet from the left end of the bridge; elevation, 21.00 feet above datum.

Discharge measurements of Chattahoochee River near Cornelia, Ga.

Date	Gage height	Dis-charge
	<i>Feet</i>	<i>Sec.-ft.</i>
1904		
June 8.....	1.40	487
September 30.....	.95	253
October 29.....	.91	215

CHATTAHOOCHEE RIVER NEAR GAINESVILLE.

This station was established on June 26, 1901, $3\frac{1}{2}$ miles northwest of Gainesville, at Thompson's bridge and was discontinued December 31, 1903.

The channel is slightly curved for 1,000 feet above and below the station. The bed is of sand and is very changeable. The bridge from which discharge measurements were made is a three-span wooden structure supported on stone piers. At low water nearly the whole of the river flows through the center span, which is 100 feet long. It is entirely housed in, but holes are cut in the floor along the upstream side at intervals of 12 feet, through which the meter can be lowered for gaging. The initial point for soundings is the end of the bridge on the left-bank upstream side.

The gage as originally established was a 15-foot vertical rod, on the right bank about 50 feet below the bridge. A standard chain gage is attached to a beam on the upstream side of the bridge about 160 feet from the initial point for soundings; length of the chain from the end to marker, 34.68 feet. The observer was Jack Elrod. Bench mark No. 1 is the top of the downstream wooden stringer supporting the bridge floor, about 2 feet to the left of the first stone pier on the left bank; elevation, 31.00 feet above gage datum. Bench mark No. 2 is a copper plug set in solid rock on the hill about 50 feet from the river and 115 feet downstream from the bridge on the right bank; elevation, 42.73 feet above gage datum.

Discharge measurements of Chattahoochee River near Gainesville.

Date	Gage height	Dis-charge	Date	Gage height	Dis-charge
	<i>Feet</i>	<i>Sec.-ft.</i>		<i>Feet</i>	<i>Sec.-ft.</i>
1901			1903		
July 16.....	5.73	2,777	January 10.....	3.09	958
October 25.....	3.00	993	March 28.....	5.43	2,670
			April 24.....	4.80	2,248
1902			May 4.....	4.87	2,234
February 7.....	3.65	1,422	June 25.....	3.40	1,519
May 3.....	3.80	1,241	August 1.....	3.16	1,052
July 11.....	2.53	704	August 29.....	2.52	677
October 11.....	2.80	715	September 25.....	2.43	728
November 24.....	2.33	520	December 9.....	2.22	531

APALACHICOLA DRAINAGE BASIN, STREAM FLOW

227

Daily gage height, in feet, of Chattahoochee River near Gainesville.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1901												
1							3.8	2.8	5.1	4.0	3.0	2.3
2							3.6	2.8	5.0	3.9	3.0	2.3
3							3.5	2.8	4.6	3.7	2.9	2.3
4							3.4	2.7	4.5	3.5	2.9	2.4
5							3.2	12.0	4.1	4.0	2.9	2.4
6							3.3	8.5	4.0	4.1	3.0	2.4
7							3.2	5.2	3.9	4.0	3.0	2.6
8							3.4	5.0	3.7	4.0	2.8	2.8
9							3.2	3.2	4.1	3.9	2.8	3.6
10							3.2	4.8	4.0	3.9	2.8	4.6
11							3.1	4.8	5.5	3.7	2.8	4.3
12							3.0	2.9	5.5	3.8	2.7	4.1
13							3.0	3.6	4.2	3.6	2.7	4.0
14							3.1	3.2	3.8	3.5	2.7	4.0
15							3.1	2.8	3.5	3.6	2.6	3.9
16							6.5	5.6	3.9	3.5	2.6	3.4
17							4.5	6.8	11.0	3.4	2.5	3.8
18							5.5	5.8	6.0	3.4	2.5	3.6
19							8.6	3.5	4.6	3.4	2.4	3.7
20							5.9	4.8	4.2	3.4	2.8	3.9
21							5.0	6.5	3.8	3.3	2.7	4.6
22							4.9	12.0	3.4	3.3	2.5	4.2
23							3.8	15.0	3.2	3.2	2.5	4.0
24							3.1	6.5	3.8	3.0	2.8	4.6
25							3.0	5.6	3.7	3.1	2.7	4.4
26						4.0	2.8	6.0	3.5	3.1	2.5	4.2
27						8.6	3.2	5.0	4.0	3.1	2.4	5.6
28						5.1	3.0	5.5	3.8	3.1	2.4	9.6
29						4.2	3.1	7.0	3.9	3.1	2.3	28.4
30						5.6	2.8	6.5	3.8	3.0	2.2	12.6
31							3.0	6.0		3.0		8.4
1902												
1	8.0	4.9	14.0	5.5	3.1	3.5	2.3	3.1	4.2			
2	6.4	15.6	6.0	5.3	3.4	3.4	2.0	3.0	4.0			
3	6.3	10.4	5.9	5.0	4.6	3.2	7.9	4.2	4.5			
4	6.0	9.3	5.6	4.6	4.5	3.0	6.3	3.6	4.5			
5	5.6	6.1	5.0	4.2	4.2	3.0	4.2	2.8	4.6			
6	4.2	5.0	4.9	4.0	4.0	2.9	4.2	2.6	4.8			
7	3.6	4.1	4.8	3.9	4.6	2.9	4.0	3.0	4.5			
8	3.4	4.0	6.8	3.9	4.8	2.8	4.0	2.8	4.3			
9	3.4	3.9	5.6	3.6	4.3	2.8	3.8	3.1	4.9			
10	3.4	3.8	5.3	3.4	5.0	3.0	3.6	4.0	4.6			
11	3.3	3.6	5.0	3.4	4.9	3.0	3.5	4.6	4.8			
12	3.2	3.5	4.8	3.4	4.6	2.9	3.2	4.0	4.6			
13	3.2	3.6	4.6	3.3	4.8	2.9	3.0	3.6	4.5			
14	3.1	3.5	4.2	3.2	4.0	2.8	4.0	3.6	4.2			
15	3.0	3.3	4.6	3.1	4.0	2.8	3.8	3.6	4.6			
16	3.0	3.2	6.3	3.2	4.0	2.9	2.9	3.1	4.8			
17	2.9	3.1	5.6	3.3	4.0	3.0	4.6	3.6	4.0			
18	2.8	3.2	4.3	3.3	4.0	4.0	4.0	3.1	4.2			
19	2.8	3.3	4.2	3.3	4.1	3.8	3.6	3.6	4.6			
20	2.7	3.4	4.0	3.6	4.0	3.6	3.5	2.8	4.8			
21	2.6	3.0	4.0	3.4	3.9	4.2	3.4	2.8	4.6			
22	2.6	3.0	3.9	3.2	3.4	4.0	4.2	3.1	4.8			
23	2.6	2.9	3.8	3.3	6.0	4.0	3.6	4.0	4.0			
24	3.6	2.9	3.6	3.6	5.3	3.8	4.0	4.6	3.6			
25	3.8	2.9	3.6	3.4	5.0	3.4	3.1	4.0	3.7			
26	3.8	3.0	3.5	3.4	4.8	3.4	2.6	4.6	4.0			
27	3.7	6.0	7.6	3.4	4.6	3.4	2.5	4.0	4.6			
28	3.6	26.4	15.6	3.5	4.3	2.8	3.0	3.6				4.0
29	3.6		13.4	3.4	4.0	2.8	4.0	4.2				3.9
30	3.5		10.6	3.2	3.6	2.4	3.4	4.2				3.8
31	4.6		6.4		3.5		2.8	4.6				3.7

WATER POWERS OF GEORGIA

Daily gage height, in feet, of Chattahoochee River near Gainesville—Continued.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1903												
1	3.5	3.5	3.0	6.1	4.6	7.0	3.6	3.0	2.6	2.4	2.2	2.2
2	3.4	3.7	6.0	5.7	4.5	13.2	3.6	3.1	2.6	2.3	2.3	2.1
3	3.7	4.4	4.6	5.5	4.7	9.0	3.5	3.2	2.6	2.3	2.5	2.1
4	4.2	7.4	4.2	5.4	4.8	6.5	3.5	3.2	2.6	2.3	2.6	2.1
5	3.9	6.0	4.0	5.3	4.4	10.6	3.5	3.1	2.6	2.3	2.7	2.1
6	3.6	4.5	5.1	5.1	4.2	6.2	3.8	3.1	2.6	2.3	2.7	2.2
7	3.4	4.9	4.7	5.0	4.2	5.9	3.4	3.0	2.6	2.3	2.6	2.2
8	3.4	11.2	5.7	8.6	4.2	5.3	3.4	3.0	2.6	2.6	2.3	2.2
9	3.2	6.4	5.4	5.7	4.2	5.4	3.4	2.9	2.6	2.4	2.3	2.2
10	3.1	5.3	6.0	5.5	4.1	5.1	3.4	2.3	2.6	2.4	2.3	2.2
11	6.0	12.1	12.9	5.4	4.0	5.0	3.7	4.1	2.6	2.3	2.3	2.2
12	5.4	8.7	7.0	5.1	3.9	4.3	6.3	2.9	2.6	2.2	2.4	2.2
13	4.1	5.4	6.0	15.8	4.0	4.0	4.5	3.2	2.6	2.2	2.4	2.5
14	3.7	5.0	5.1	9.7	4.3	4.0	3.7	3.3	2.6	2.2	2.4	2.6
15	3.6	4.2	5.0	6.6	4.1	3.9	3.5	4.1	6.0	2.2	2.3	2.3
16	3.5	9.9	4.9	5.8	4.0	3.9	3.4	7.5	4.7	2.2	2.2	2.2
17	3.5	15.6	4.7	5.5	4.0	3.8	3.4	5.8	3.9	2.2	2.4	2.2
18	3.4	7.1	4.5	5.3	4.0	3.8	3.2	5.0	3.1	2.2	3.1	2.2
19	3.3	5.4	4.4	5.5	4.0	3.8	3.1	3.5	2.8	2.2	2.3	2.6
20	3.2	5.0	4.1	5.4	3.9	3.3	3.1	5.0	2.6	2.2	2.3	2.6
21	3.2	4.7	7.7	5.1	3.9	3.7	3.1	3.2	2.6	2.2	2.3	2.6
22	3.2	4.5	10.5	5.0	3.8	3.7	3.1	3.0	2.6	2.2	2.3	2.5
23	3.2	4.2	25.2	4.8	3.8	3.6	3.0	2.9	2.6	2.1	2.3	2.3
24	3.2	4.0	9.4	4.8	3.8	3.6	3.0	2.3	2.6	2.1	2.3	2.3
25	3.1	3.8	7.0	4.8	3.7	3.5	3.0	2.3	2.5	2.1	2.2	2.4
26	3.1	3.8	6.3	4.8	3.7	3.7	3.0	2.7	2.5	2.1	2.2	2.4
27	3.1	5.6	5.9	4.7	3.7	4.5	2.9	2.7	2.5	2.1	2.2	2.3
28	3.7	14.5	5.5	4.7	3.6	4.0	2.9	2.6	2.4	2.1	2.2	2.3
29	5.5	6.9	4.6	3.6	3.3	2.9	2.6	2.4	2.1	2.2	2.3
30	4.0	12.2	4.6	3.7	3.7	2.9	2.6	2.4	2.1	2.2	2.3
31	3.7	3.2	5.4	3.2	2.6	2.1	2.3

Rating table for Chattahoochee River near Gainesville from June 26, 1901, to December 31, 1903.^a

Gage height	Dis-charge						
Feet	Sec.-ft.	Feet	Sec.-ft.	Feet	Sec.-ft.	Feet	Sec.-ft.
2.00	350	3.90	1,535	6.60	3,340	12.00	6,850
2.10	415	4.00	1,650	6.80	3,470	13.00	7,500
2.20	480	4.10	1,715	7.00	3,600	14.00	8,150
2.30	545	4.20	1,780	7.20	3,730	15.00	8,800
2.40	610	4.30	1,845	7.40	3,860	16.00	9,450
2.50	675	4.40	1,910	7.60	3,990	17.00	10,100
2.60	740	4.50	1,975	7.80	4,120	18.00	10,750
2.70	805	4.60	2,040	8.00	4,250	19.00	11,400
2.80	870	4.70	2,105	8.20	4,380	20.00	12,050
2.90	935	4.80	2,170	8.40	4,510	21.00	12,700
3.00	1,000	4.90	2,235	8.60	4,640	22.00	13,350
3.10	1,065	5.00	2,300	8.80	4,770	23.00	14,000
3.20	1,130	5.20	2,430	9.00	4,900	24.00	14,650
3.30	1,195	5.40	2,560	9.20	5,030	25.00	15,300
3.40	1,260	5.60	2,690	9.40	5,160	26.00	15,950
3.50	1,325	5.80	2,820	9.60	5,290	27.00	16,600
3.60	1,390	6.00	2,950	9.80	5,420	28.00	17,250
3.70	1,455	6.20	3,080	10.00	5,550
3.80	1,520	6.40	3,210	11.00	6,200

^aThis rating table is based on a tangent, the difference being 65 per tenth.

Estimated monthly discharge of Chattahoochee River near Gainesville.

[Drainage area, 544 square miles.]

Month	Discharge in second-feet			Run-off	
	Maximum	Minimum	Mean	Sec.-ft. per sq. mile	Depth in inches
1901					
June 26-30.....	2,690	1,390	1,975	3.63	0.68
July.....	4,640	870	1,520	2.79	3.22
August.....	8,800	805	2,724	5.01	5.78
September.....	6,200	1,130	1,912	3.51	3.92
October.....	1,715	1,000	1,327	2.44	2.81
November.....	1,000	480	792	1.46	1.63
December.....	17,510	545	2,342	4.31	4.97
1902					
January.....	4,250	740	1,530	2.81	3.24
February.....	16,210	935	2,553	4.69	4.88
March.....	11,010	1,325	3,086	5.67	6.54
April.....	2,625	1,065	1,479	2.72	3.08
May.....	2,950	1,065	1,835	3.37	3.89
June.....	1,780	610	1,189	2.09	2.33
July.....	4,185	350	1,461	2.69	3.10
August.....	2,040	740	1,388	2.55	2.94
September 1-27.....	2,235	1,390	1,922	3.53	3.55
December 28-31.....	1,650	1,455	1,552	2.85	.42
1903					
January.....	2,950	1,065	1,442	2.65	3.06
February.....	9,190	1,325	3,247	5.97	6.22
March.....	15,430	1,650	3,602	6.62	7.63
April.....	9,320	2,040	2,861	5.26	5.87
May.....	2,560	1,390	1,709	3.14	3.62
June.....	7,680	1,325	2,361	4.34	4.84
July.....	3,145	935	1,273	2.84	2.70
August.....	3,925	740	1,258	2.81	2.66
September.....	2,950	610	833	1.62	1.81
October.....	740	415	497	.91	1.05
November.....	1,065	480	599	1.10	1.23
December.....	740	415	535	.98	1.13
The year.....	15,430	415	1,689	3.10	41.82

CHATTAHOOCHEE RIVER NEAR BUFORD.

This station was established June 24, 1901, at Stricklands Bridge, about 6 miles southwest of Buford. Discharge measurements are made from the upstream side of the bridge, which is a single-span, iron highway bridge, about 200 feet in length. The wire gage is fastened to the upstream guard timber on bridge floor. The bench mark is the top of the bridge floor, over the upstream end of the second crossbeam from the left bank; elevation, 33.00 feet above gage datum. This station was discontinued December 31, 1901.

Discharge measurements of Chattanooga River near Buford.

Date	Gage height	Dis-charge	Date	Gage height	Dis-charge
1901			1901		
April 12.....	Feet 3.40	Sec.-ft. 2,310	August 6.....	Feet 6.90	Sec.-ft. 5,758
June 14.....	3.47	2,559	October 24.....	2.46	1,638
July 17.....	5.38	3,893			

WATER POWERS OF GEORGIA

Daily gage height, in feet, of Chattahoochee River near Buford.

Day	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1901							
1.....		3.9	2.4	5.5	3.4	2.3	2.1
2.....		3.7	2.2	4.8	4.3	2.3	2.1
3.....		3.4	2.1	4.5	3.1	2.3	2.5
4.....		3.2	2.1	4.2	3.0	2.3	2.3
5.....		3.0	2.2	4.0	2.9	2.4	2.4
6.....		2.9	2.1	3.9	2.8	2.4	2.3
7.....		3.1	3.3	3.8	2.8	2.3	2.3
8.....		3.7	4.9	3.7	2.8	2.3	2.2
9.....		3.2	3.6	3.5	2.3	2.2	2.3
10.....		2.8	3.1	3.5	2.3	2.2	2.6
11.....		2.7	3.5	4.1	2.8	2.2	3.4
12.....		2.5	3.4	3.9	2.7	2.2	2.6
13.....		2.6	3.3	3.5	3.1	2.4	2.4
14.....		2.6	3.3	3.5	2.3	2.3	2.6
15.....		2.8	7.9	3.4	2.7	2.2	14.0
16.....		2.6	7.4	3.3	2.7	2.2	5.5
17.....		9.7	7.2	5.1	2.6	2.1	4.3
18.....		3.3	9.0	11.0	2.5	2.1	3.4
19.....		3.9	7.6	5.3	2.4	2.2	3.9
20.....		4.5	7.4	4.2	2.5	2.3	2.9
21.....		3.4	11.0	3.9	2.5	2.3	2.6
22.....		3.3	12.0	3.7	2.5	2.2	2.9
23.....		3.0	18.0	3.5	2.5	2.2	2.8
24.....	3.5	2.8	9.2	3.5	2.4	2.5	3.3
25.....	6.8	2.6	7.5	3.3	2.4	2.3	2.9
26.....	6.0	2.5	6.0	3.3	2.4	2.3	3.3
27.....	3.9	2.6	6.2	3.3	2.4	2.2	3.5
28.....	3.9	2.7	5.9	3.3	2.4	2.1	4.2
29.....	4.4	3.3	8.2	3.3	2.4	2.2	22.5
30.....	4.7	2.8	7.3	3.5	2.3	2.2	13.2
31.....		2.5	6.0	2.4	8.5

Rating table for Chattahoochee River near Buford from June 24 to December 31, 1901.^a

Gage height	Dis-charge						
<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>
2.10	1,450	3.80	2,700	5.50	4,200	8.40	7,312
2.20	1,500	3.90	2,780	5.60	4,300	8.60	7,536
2.30	1,560	4.00	2,860	5.70	4,400	8.80	7,760
2.40	1,630	4.10	2,940	5.80	4,500	9.00	7,984
2.50	1,700	4.20	3,020	5.90	4,600	9.20	8,208
2.60	1,775	4.30	3,105	6.00	4,700	9.40	8,432
2.70	1,850	4.40	3,190	6.20	4,900	9.60	8,656
2.80	1,925	4.50	3,275	6.40	5,100	9.80	8,880
2.90	2,000	4.60	3,360	6.60	5,300	10.00	9,104
3.00	2,075	4.70	3,445	6.80	5,520	10.50	9,664
3.10	2,150	4.80	3,530	7.00	5,744	11.00	10,224
3.20	2,225	4.90	3,620	7.20	5,968	12.00	11,344
3.30	2,305	5.00	3,710	7.40	6,192	13.00	12,464
3.40	2,380	5.10	3,800	7.60	6,416	14.00	13,584
3.50	2,460	5.20	3,900	7.80	6,640	15.00	14,704
3.60	2,540	5.30	4,000	8.00	6,864	22.50	23,100
3.70	2,620	5.40	4,100	8.20	7,088		

^a Above gage height 7.0 feet the rating curve is a tangent, the difference being 112 per tenth.

WATER POWERS OF GEORGIA

Discharge measurements of Chattahoochee River near Norcross.

Date	Gage height	Dis-charge	Date	Gage height	Dis-charge
1903			1904		
January 9.....	Feet 2.70	Sec.-ft. 1,837	October 11.....	Feet 1.82	Sec.-ft. 569
March 14.....	5.35	4,940	October 14.....	1.28	558
May 5.....	4.08	3,543	December 9.....	1.88	951
May 29.....	3.15	2,378	1905		
June 26.....	3.13	2,447	January 13.....	12.26	16,120
July 17.....	3.06	2,254	January 13.....	12.10	15,780
July 17.....	3.06	2,255	January 18.....	11.82	14,790
August 19.....	3.15	2,337	January 14.....	5.29	4,658
August 19.....	3.05	2,288	January 14.....	5.05	4,501
August 19.....	3.15	2,281	March 2.....	2.94	1,949
August 19.....	3.05	2,208	May 27.....	3.19	2,320
September 26.....	2.06	1,197	May 27.....	3.16	2,209
October 23.....	1.94	1,078	June 28.....	2.01	1,139
November 25 ^a	1.95	1,062	September 22.....	1.51	713
November 25.....	1.95	1,071	September 22.....	1.52	733
1904			October 23.....	1.90	1,035
January 19.....	2.19	1,419	October 23.....	1.92	1,054
January 19.....	2.19	1,362	October 23.....	1.90	1,042
February 20.....	3.45	2,607	December 9.....	8.56	9,521
April 7.....	2.50	1,496	1906		
June 7.....	2.54	1,571	February 9.....	3.11	2,190
June 20.....	1.53	662	June 11.....	2.53	1,630
August 9.....	8.62	9,938	July 23.....	3.70	2,870
August 9.....	6.57	6,624	August 25.....	3.45	2,670
August 10.....	3.60	2,658	October 27.....	3.60	2,790
September 23.....	1.22	537			
September 23.....	1.22	538			

^a Measurement taken at Warsaw Ferry, 1 mile above bridge.

Daily gage height, in feet, of Chattahoochee River near Norcross.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1903												
1.....		2.9	14.1	7.0	4.0	4.5	3.2	3.1	2.1	2.0	1.9	1.9
2.....		2.8	7.0	6.0	4.0	9.7	3.1	2.6	2.0	2.0	2.0	1.9
3.....		3.2	5.6	5.5	4.0	7.5	3.3	6.1	2.0	2.0	2.7	1.9
4.....		5.2	5.0	5.4	4.2	4.9	3.2	3.6	2.0	2.0	2.3	1.9
5.....		3.3	4.7	5.1	4.1	9.7	3.1	3.2	2.2	2.0	2.4	1.9
6.....		4.9	4.8	4.8	3.9	11.2	3.0	2.8	2.1	2.0	2.7	1.9
7.....		4.3	4.6	4.7	3.8	7.3	3.5	2.6	2.0	2.0	2.2	1.9
8.....		10.6	4.8	5.8	3.8	5.5	3.1	2.5	2.0	2.0	2.1	1.9
9.....	2.7	8.6	5.3	7.9	3.8	4.7	3.3	2.4	2.3	2.2	2.0	1.9
10.....	2.6	5.2	5.0	5.4	3.7	4.4	2.9	2.4	2.2	2.2	2.0	2.0
11.....	2.7	6.4	8.7	5.0	3.6	5.1	3.2	2.4	2.1	2.0	2.0	1.9
12.....	5.8	11.1	11.5	4.8	3.6	4.9	3.3	2.7	2.0	2.0	2.1	1.9
13.....	4.2	6.2	6.4	4.7	3.7	4.1	6.8	2.5	2.0	1.9	2.0	2.0
14.....	3.4	4.9	5.5	12.6	3.8	3.9	4.6	2.5	1.9	1.9	2.0	2.1
15.....	3.2	4.8	5.1	7.8	3.9	3.7	3.6	3.2	3.6	1.9	2.0	2.2
16.....	3.0	4.5	4.8	5.9	3.7	3.6	3.2	3.2	4.9	1.9	2.0	2.0
17.....	2.9	14.9	4.6	5.4	3.6	3.5	3.0	4.3	3.6	2.0	2.0	1.9
18.....	2.8	13.7	4.5	5.1	3.5	3.5	3.0	5.0	2.8	2.2	2.3	1.9
19.....	2.7	5.9	4.3	4.9	3.4	3.5	2.9	3.5	2.4	2.2	2.5	1.9
20.....	2.6	5.1	4.2	4.8	3.4	3.4	2.8	2.7	2.3	2.0	2.1	1.9

Estimated monthly discharge of Chattahoochee River near Buford.

[Drainage area, 1,050 square miles.]

Month	Discharge in second-feet			Run-off	
	Maximum	Minimum	Mean	Sec.-ft. per sq. mile	Depth in inches
1901					
June 24-30.....	5,520	2,460	3,554	3.38	0.88
July.....	8,768	1,700	2,507	2.39	2.76
August.....	18,064	1,450	4,985	4.75	5.48
September.....	10,224	2,300	3,081	2.89	3.22
October.....	3,105	1,560	1,863	1.77	2.04
November.....	1,630	1,450	1,537	1.46	1.63
December.....	23,100	1,450	3,624	3.45	3.98

CHATTAHOOCHEE RIVER NEAR NORCROSS.

This station was established June 10, 1902, by M. R. Hall. It is located at Medlock's toll bridge, about 4½ miles north of Norcross. This point is above the mouth of Johns Creek and below the mouth of Suwanee Creek.


The channel is slightly curved for 600 feet above and 700 feet below the station. The current is sluggish at low stages, but not excessively so, and the discharge measurements are considered good at the lowest stage. The right bank is high and will overflow only for 50 feet from the water's edge; the left bank will overflow for about 800 feet at a gage height of from 16 to 18 feet. The bed of the stream is sandy and probably changes.

Discharge measurements are made from the downstream side of the single-span bridge and its approaches. The initial point for soundings is 50 feet to the right of the center of the downstream tubular pier on the right bank.

The original gage was a vertical staff attached to an oak tree on the right bank 100 feet above the bridge. A chain gage, established March 14, 1903, was read in connection with the vertical gage until June 28, 1905, when a standard chain gage was attached to the downstream lower chord of the first panel from the right bank; length of chain, 30.36 feet. The gage is read twice each day by W. O. Medlock. The bench mark is the top of the iron pier on the right bank, downstream side; elevation, 27.00 feet.



VIEW OF THE OCOEE RIVER, NEAR THE GEORGIA-TENNESSEE STATE LINE, SHOWING WATER RAPIDS.



APALACHICOLA DRAINAGE BASIN, STREAM FLOW 233

Daily gage height, in feet, of Chattahoochee River near Norcross—Continued.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1903												
21.....	2.6	4.7	5.9	4.9	3.4	3.3	2.8	2.6	2.2	2.0	2.0	2.2
22.....	2.7	4.4	8.0	4.6	3.4	3.3	2.7	2.5	2.2	2.0	2.0	2.3
23.....	2.6	4.2	16.7	4.5	3.3	3.2	2.7	2.4	2.1	1.9	2.0	2.1
24.....	2.5	4.0	19.4	4.4	3.2	3.2	2.6	2.3	2.1	1.9	2.0	2.0
25.....	2.7	3.9	9.0	4.3	3.2	3.1	2.6	2.3	2.1	1.9	2.0	2.0
26.....	2.7	3.8	6.4	4.4	3.1	3.1	2.5	2.2	2.1	1.9	2.0	2.2
27.....	2.6	3.7	5.8	4.4	3.1	4.0	2.5	2.2	2.1	1.9	1.9	2.2
28.....	2.7	3.6	5.5	4.2	3.1	3.8	2.5	2.1	2.1	1.9	1.9	2.0
29.....	3.6	5.4	4.1	3.1	3.7	2.5	2.1	2.0	1.9	1.9	2.0
30.....	4.0	10.0	4.0	3.5	3.5	2.5	2.1	2.0	1.9	1.9	2.0
31.....	3.2	11.4	5.2	2.6	2.3	1.9	1.9
1904												
1.....	1.9	2.2	2.5	2.55	2.3	2.4	1.7	2.65	1.8	1.35	1.25	1.5
2.....	1.9	2.1	2.6	2.55	2.25	2.3	1.55	2.7	1.75	1.3	1.3	1.35
3.....	2.0	2.1	2.6	2.5	2.2	2.3	1.5	2.35	1.7	1.35	1.35	1.4
4.....	1.9	2.1	2.4	2.4	2.5	2.1	1.45	2.2	1.9	1.2	1.5	1.55
5.....	1.9	2.1	2.3	2.35	2.4	1.95	1.7	3.1	2.4	1.15	1.65	2.0
6.....	1.8	2.1	2.3	2.35	2.3	1.9	1.55	2.55	2.1	1.25	1.6	3.45
7.....	1.8	2.3	4.7	2.5	2.2	2.65	1.5	2.15	2.05	1.3	1.5	2.85
8.....	2.0	3.0	6.0	3.2	3.6	2.3	1.5	7.7	1.8	1.3	1.45	2.1
9.....	1.9	2.9	3.9	3.4	4.05	2.05	1.3	8.2	1.7	1.3	1.4	1.9
10.....	1.9	2.7	3.3	3.7	3.6	1.9	1.3	3.7	1.8	1.15	1.4	1.9
11.....	1.9	2.7	3.0	3.0	2.8	1.8	1.55	4.5	1.65	1.25	1.4	1.9
12.....	2.0	2.7	2.85	2.8	2.55	1.9	1.75	3.95	1.55	1.1	1.4	1.8
13.....	2.0	2.5	2.7	2.7	2.4	1.8	1.85	2.85	1.6	1.3	1.6	1.7
14.....	2.1	2.3	3.2	2.6	2.35	1.8	1.9	2.55	1.55	1.3	1.65	1.7
15.....	2.1	2.3	3.1	2.5	2.35	1.7	1.6	2.4	1.5	1.2	1.6	1.65
16.....	2.0	2.3	2.75	2.5	2.25	1.7	1.6	2.5	1.45	1.25	1.5	1.65
17.....	2.2	2.2	2.6	2.55	2.2	1.7	1.85	2.15	1.45	1.25	1.5	1.7
18.....	2.5	2.1	2.55	2.5	2.2	1.65	1.5	2.0	1.45	1.15	1.45	1.7
19.....	2.2	2.3	2.5	2.45	2.15	1.2	1.65	1.9	1.4	1.1	1.45	1.6
20.....	2.1	3.5	2.45	2.4	2.15	1.6	1.4	2.0	1.4	1.1	1.45	1.6
21.....	2.0	3.6	2.6	2.4	2.1	1.5	1.7	2.2	1.4	1.1	1.4	1.6
22.....	2.8	4.9	3.0	2.4	2.1	1.45	1.85	1.85	1.4	1.25	1.55	1.6
23.....	3.1	5.3	3.4	2.4	2.05	1.35	2.05	1.7	1.4	1.25	1.8	1.55
24.....	3.3	4.0	3.6	2.35	2.0	1.25	1.7	1.8	1.45	1.2	1.85	1.55
25.....	2.6	3.3	3.5	2.3	2.0	1.2	1.6	2.05	1.4	1.2	1.65	1.7
26.....	2.4	2.9	3.2	2.3	2.0	1.2	1.8	2.0	1.3	1.25	1.55	1.85
27.....	2.3	2.8	3.0	2.45	1.95	1.4	1.8	2.4	1.2	1.3	1.5	1.95
28.....	2.2	2.6	2.9	2.5	1.9	1.95	1.6	2.8	1.2	1.2	1.45	3.8
29.....	2.2	2.6	2.75	2.35	1.9	2.3	1.7	2.45	1.25	1.1	1.45	3.55
30.....	2.2	2.65	2.3	2.0	2.4	2.1	2.05	1.4	1.3	1.5	2.5
31.....	2.2	2.6	2.5	1.9	1.9	1.3	2.2
1905												
1.....	2.0	2.15	3.0	2.4	2.65	2.5	10.5	2.0	1.8	1.72	1.72	1.48
2.....	1.98	2.1	2.95	2.35	2.4	2.4	6.1	1.95	2.15	1.82	1.7	1.6
3.....	2.0	2.05	2.85	2.3	2.6	2.35	3.3	1.9	2.25	1.68	1.68	3.4
4.....	1.98	2.05	2.8	2.35	3.3	2.3	2.7	1.85	1.95	1.72	1.68	7.6
5.....	1.88	2.0	2.7	2.45	3.0	2.25	3.2	1.9	1.85	1.95	1.65	3.6
6.....	2.02	2.2	2.65	2.6	3.1	2.2	3.3	1.85	1.8	1.72	1.68	2.9
7.....	3.15	2.95	2.65	2.6	5.3	2.2	4.2	1.9	1.75	1.6	1.82	2.65
8.....	2.9	3.3	2.7	2.45	4.5	2.1	3.2	2.3	1.72	1.55	2.2	2.85
9.....	2.35	5.1	2.7	2.5	4.6	2.1	2.85	2.6	1.73	1.5	1.92	7.2
10.....	2.2	6.7	2.9	2.5	3.5	2.05	3.7	2.7	1.7	1.58	2.1	8.1
11.....	2.2	5.1	3.3	2.4	3.0	2.0	5.2	3.6	1.68	2.7	1.88	4.4
12.....	6.5	4.3	3.1	2.4	2.8	2.0	7.4	3.8	1.9	3.5	1.25	3.4
13.....	11.9	7.7	2.9	2.6	2.7	2.3	6.0	4.2	1.75	2.2	1.2	3.0
14.....	5.3	6.7	2.8	2.5	2.6	2.1	4.0	3.6	1.72	1.9	1.25	2.35
15.....	3.7	4.3	2.8	2.4	2.5	2.1	4.2	3.3	1.63	1.82	2.15	2.95
16.....	3.1	3.6	2.7	2.6	3.9	2.35	3.6	2.9	1.6	1.82	1.92	3.1
17.....	2.8	3.3	2.6	2.45	4.0	2.45	2.9	2.65	1.6	1.88	1.98	2.9
18.....	2.65	3.1	2.55	2.35	3.1	2.3	2.8	2.4	1.6	1.78	1.82	2.75
19.....	2.55	2.95	2.55	2.3	2.8	2.15	2.6	2.3	1.6	1.75	1.75	2.6
20.....	2.55	4.1	2.55	2.3	2.7	2.1	2.5	2.25	1.6	1.75	1.75	3.2

WATER POWERS OF GEORGIA

Daily gage height, in feet, of Chattahoochee River near Norcross—Continued.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1905 ^a												
21	2.5	11.5	2.65	2.3	2.6	2.6	2.7	2.2	1.55	1.7	1.95	5.8
22	2.35	6.9	3.2	2.3	2.8	2.6	2.7	2.1	1.52	1.68	1.88	5.2
23	2.2	5.1	2.85	2.3	4.0	2.7	2.4	2.25	1.53	1.62	1.78	3.8
24	2.2	4.2	2.7	2.2	6.0	2.3	2.2	2.5	1.5	1.62	1.57	3.8
25	2.1	3.8	2.6	2.2	4.0	2.15	2.25	2.4	1.47	1.68	1.52	3.4
26	2.1	3.6	2.6	2.2	3.4	2.0	2.2	2.2	1.48	1.82	1.8	3.2
27	2.25	3.3	2.5	2.3	3.2	2.1	2.15	2.3	1.6	2.2	1.8	2.95
28	2.95	3.2	2.5	2.4	3.0	2.05	2.1	2.0	1.25	1.95	1.75	2.9
29	2.1	2.4	2.4	2.9	2.4	2.1	1.9	1.42	1.8	1.75	3.0
30	2.1	2.5	2.6	2.8	2.25	2.2	1.85	1.47	1.75	1.52	3.1
31	2.1	2.5	2.6	2.2	1.85	1.75	2.85
1906												
1	2.75	3.65	2.6	5.1	3.15	2.6	2.45	5.2	6.2	6.2	3.45	3.1
2	2.65	3.5	2.6	4.4	3.05	2.7	2.3	4.3	5.0	7.8	3.4	3.1
3	6.0	3.4	2.9	4.2	3.0	3.1	2.3	4.2	4.3	11.0	3.85	3.1
4	14.6	3.3	4.4	3.95	3.7	2.75	2.8	3.8	4.1	10.4	3.3	3.1
5	12.2	3.25	3.45	3.8	3.3	2.8	2.6	4.4	5.0	7.0	3.3	3.0
6	5.5	3.3	3.05	3.7	3.15	2.85	2.75	3.85	5.8	6.2	3.3	3.0
7	4.4	3.2	2.95	3.7	4.0	2.7	5.0	4.2	4.8	6.6	3.3	3.1
8	4.0	3.15	4.0	3.6	3.6	2.5	3.8	3.75	5.5	5.6	3.3	3.05
9	3.95	3.1	4.0	3.6	3.2	2.5	5.2	3.85	4.8	5.0	3.25	3.0
10	3.7	3.05	3.45	3.9	3.05	2.45	4.0	3.15	6.0	4.8	3.2	3.2
11	3.5	3.0	3.25	3.65	2.9	2.5	3.0	3.1	4.4	4.5	3.2	5.7
12	3.9	3.0	3.0	3.5	2.9	2.65	3.3	3.0	4.8	4.4	3.25	4.4
13	4.2	3.0	3.0	3.4	2.9	5.0	3.4	3.6	4.0	4.2	3.2	3.6
14	3.75	3.0	3.45	3.35	2.8	4.85	3.9	3.45	3.7	4.1	3.15	3.4
15	3.55	2.95	11.5	3.6	2.8	3.9	7.7	5.4	3.5	4.0	3.3	3.3
16	3.8	2.9	11.1	3.85	2.75	3.85	6.6	6.8	3.4	4.0	3.35	3.2
17	3.9	2.8	5.4	3.55	2.7	3.35	4.7	3.9	3.3	3.9	3.3	3.8
18	3.6	2.8	4.3	3.4	2.7	3.05	8.0	7.3	3.7	4.2	3.85	5.4
19	3.5	2.8	9.0	3.3	2.65	2.9	7.6	8.6	7.0	6.0	6.0	4.4
20	3.4	2.8	14.2	3.3	2.65	2.8	5.6	7.8	7.6	4.4	4.9	4.3
21	3.25	2.8	6.8	3.2	2.6	2.65	5.7	6.8	6.0	4.0	4.1	4.2
22	4.5	2.9	5.2	3.2	2.6	2.5	4.7	4.1	5.9	3.95	3.85	3.85
23	9.4	2.85	4.6	3.15	2.6	2.5	5.1	4.1	5.1	3.85	3.65	3.65
24	6.5	2.75	4.2	3.1	2.5	2.5	5.8	3.8	5.8	3.8	3.45	3.45
25	4.8	2.7	4.0	3.1	2.5	3.05	5.0	3.45	4.8	3.75	3.4	3.35
26	4.4	2.7	3.85	3.1	3.0	2.7	3.8	3.4	5.3	3.7	3.3	3.25
27	4.8	2.7	3.9	3.2	4.2	2.6	3.6	3.9	4.4	3.6	3.3	3.2
28	4.8	2.7	4.4	3.6	3.4	2.4	3.75	4.5	4.2	3.55	3.25	3.4
29	4.6	4.2	3.4	2.9	2.5	4.2	5.2	5.1	3.5	3.15	3.85
30	4.1	5.2	3.25	2.75	2.8	4.6	8.2	5.8	3.5	3.1	3.65
31	3.85	7.0	2.65	5.3	10.8	3.5	8.4

^a Low gage heights can be accounted for as resulting from storage at the Gainesville water-power plant.

Rating table for Chattahoochee River near Norcross from January 9, 1903, to December 31, 1905.^a

Gage height	Dis-charge						
<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>
1.10	480	2.90	2,080	4.70	4,170	8.00	8,805
1.20	515	3.00	2,190	4.80	4,295	8.20	9,125
1.30	560	3.10	2,300	4.90	4,425	8.40	9,445
1.40	615	3.20	2,410	5.00	4,555	8.60	9,775
1.50	680	3.30	2,520	5.20	4,815	8.80	10,105
1.60	750	3.40	2,630	5.40	5,075	9.00	10,440
1.70	830	3.50	2,745	5.60	5,345	9.50	11,290
1.80	920	3.60	2,860	5.80	5,615	10.00	12,155
1.90	1,015	3.70	2,975	6.00	5,885	10.50	13,030
2.00	1,120	3.80	3,090	6.20	6,160	11.00	13,920
2.10	1,225	3.90	3,205	6.40	6,440	11.50	14,825
2.20	1,330	4.00	3,320	6.60	6,720	12.00	15,760
2.30	1,435	4.10	3,440	6.80	7,005	12.50	16,725
2.40	1,540	4.20	3,560	7.00	7,295	13.00	17,700
2.50	1,645	4.30	3,680	7.20	7,585	14.00	19,650
2.60	1,750	4.40	3,800	7.40	7,885	15.00	21,600
2.70	1,860	4.50	3,920	7.60	8,185	16.00	23,550
2.80	1,970	4.60	4,045	7.80	8,495		

^a Above gage height 12.20 the rating curve is a tangent, the difference being 195 per tenth.

JANUARY 1 TO DECEMBER 31, 1906.

<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i> ^c	<i>Sec.-ft.</i>
2.30	1,360	3.60	2,780	4.90	4,370	7.40	7,885
2.40	1,460	3.70	2,900	5.00	4,500	7.60	8,185
2.50	1,560	3.80	3,020	5.20	4,760	7.80	8,495
2.60	1,660	3.90	3,140	5.40	5,040	8.00	8,805
2.70	1,770	4.00	3,260	5.60	5,320	9.00	10,440
2.80	1,880	4.10	3,380	5.80	5,600	10.00	12,155
2.90	1,990	4.20	3,500	6.00	5,880	11.00	13,920
3.00	2,100	4.30	3,620	6.20	6,160	12.00	15,760
3.10	2,210	4.40	3,740	6.40	6,440	13.00	17,700
3.20	2,320	4.50	3,860	6.60	6,720	14.00	19,650
3.30	2,430	4.60	3,980	6.80	7,005	15.00	21,600
3.40	2,540	4.70	4,110	7.00	7,295		
3.50	2,660	4.80	4,240	7.20	7,585		

NOTE.—The above table is based on discharge measurements made during 1905-6 and is well defined.

WATER POWERS OF GEORGIA

Estimated monthly discharge of Chattahoochee River near Norcross.

[Drainage area, 1,170 square miles.]

Month	Discharge in second-feet			Run-off	
	Maximum	Minimum	Mean	Sec.-ft. per sq. mile	Depth in inches
1903					
January 9-31.....	5,615	1,645	2,281	1.95	1.67
February.....	21,400	1,970	6,450	5.51	5.74
March.....	30,180	3,560	8,167	6.98	8.05
April.....	16,920	3,320	5,214	4.46	4.98
May.....	4,815	2,300	2,923	2.50	2.88
June.....	14,280	2,300	4,463	3.81	4.25
July.....	7,005	1,645	2,343	2.00	2.31
August.....	6,020	1,225	2,055	1.76	2.03
September.....	4,425	1,015	1,466	1.25	1.40
October.....	1,330	1,015	1,103	.943	1.09
November.....	1,860	1,015	1,222	1.04	1.16
December.....	1,435	1,015	1,110	.949	1.09
1904					
January.....	2,520	920	1,306	1.12	1.29
February.....	4,945	1,225	1,967	1.68	1.81
March.....	5,885	1,435	2,227	1.90	2.19
April.....	2,975	1,435	1,729	1.43	1.65
May.....	3,330	1,015	1,510	1.29	1.49
June.....	1,805	515	987	.844	.942
July.....	1,225	560	814	.696	.802
August.....	9,125	350	2,079	1.73	2.05
September.....	1,540	515	764	.653	.729
October.....	588	430	530	.453	.522
November.....	968	537	639	.589	.657
December.....	3,090	538	1,119	.956	1.10
The year.....	9,125	480	1,310	1.12	15.23
1905					
January.....	15,570	948	2,238	1.91	2.20
February.....	14,820	1,120	3,753	3.21	3.34
March.....	2,520	1,540	1,899	1.62	1.87
April.....	1,750	1,350	1,540	1.32	1.47
May.....	5,885	1,540	2,552	2.18	2.51
June.....	1,860	1,120	1,381	1.18	1.32
July.....	13,030	1,225	2,786	2.33	2.74
August.....	3,560	968	1,609	1.38	1.59
September.....	1,332	538	824	.704	.786
October.....	2,745	630	991	.847	.976
November.....	1,330	515	893	.763	.851
December.....	3,445	667	3,225	2.76	3.13
The year.....	15,570	515	1,974	1.69	22.33
1906					
January.....	20,800	1,720	4,660	3.98	4.59
February.....	2,840	1,770	2,100	1.79	1.86
March.....	20,000	1,660	4,840	4.14	4.77
April.....	4,630	2,210	2,750	2.35	2.62
May.....	3,500	1,560	2,090	1.79	2.06
June.....	4,500	1,460	2,050	1.75	1.95
July.....	3,800	1,360	3,940	3.37	3.88
August.....	13,600	2,100	4,520	3.86	4.45
September.....	3,180	2,430	4,550	3.89	4.34
October.....	13,900	2,660	4,670	3.99	4.60
November.....	5,880	2,210	2,690	2.30	2.57
December.....	9,440	2,100	3,020	2.53	2.97
The year.....	20,800	1,360	3,490	2.98	40.60

NOTE.—Values for 1906 are excellent.

CHATTAHOOCHEE RIVER NEAR VININGS.

This station was established in 1905 at a new iron highway bridge 1 mile east of Vinings and about 10 miles northwest of Atlanta. It is about 10 miles below the developed power at Bull Sluice.

The current of the section is fairly good and regular. The bed is probably somewhat shifting, but there is a stretch of swift water immediately below, running among permanent rocks which will probably control the water level at the station. The left bank is high and will not overflow; the right bank is only about 20 feet above low water for a width of 900 feet and will overflow during very high floods.

Discharge measurements are made from a bridge of two 140-foot spans, with 50 feet of wooden approach at the left bank and 100 feet at the right bank.

No gage has been established. The effect of the water power above being to cause a great amount of fluctuation in the flow, the mean daily gage height can be obtained only by the use of an automatic recording gage, and until this is installed the measurements are made mainly as investigations relative to the accuracy of the rating in case the original Chattahoochee River station, which was located at Oakdale, 4 miles below, should be continued at this place. Gage heights are determined directly from the bench mark, which is the top of the upstream end of the second floor beam from the left bank; elevation, 31.00 feet above the datum of the assumed gage.

Discharge measurements of Chattahoochee River near Vinings.

Date	Gage height	Dis-charge
1905		
	<i>Feet</i>	<i>Sec.-ft.</i>
May 4.....	4.51	1,966
August 18.....	4.68	2,003
August 18.....	4.57	1,861
October 17.....	3.45	856
November 27.....	3.74	1,002
June 8.....	4.72	2,080
August 8.....	5.72	3,620

CHATTAHOOCHEE RIVER AT OAKDALE.

This station was established at Oakdale on October 17, 1895, by Cyrus C. Babb. It is located at the Southern Railway bridge, 1 mile above the mouth of Proctor Creek, 2 miles below the mouth of Peachtree Creek, one-fourth mile west of Chattahoochee, 1 mile east of Oakdale, and 8 miles northwest of Atlanta. The flow is obstructed by rafts, which have to be cleared from the channel occasionally. The channel is straight and the current swift. The banks are subject to overflow. The bed of the stream is constant, and the results are fairly good except at high stages, when the water flows through the trestlework.

Discharge measurements were made from the railway bridge, the initial point for soundings being the end of the iron bridge on the right bank, upstream side.

On July 1, 1898, the location of the station was changed to Mason and Turners Ferry, 1 mile below Oakdale. The gage at this point, known as the "Oakdale lower gage," is nailed to a tree on the right bank, 100 feet below the ferry, and set 1 foot lower than the gage at the Southern Railway bridge. On June 1, 1899, the lower gage was discontinued and the upper gage resumed and adopted by the United States Weather Bureau, the United States Geological Survey still receiving the records and making the current-meter discharge measurements at this point. The gage now used is in two sections, the first, reading from zero to 8 feet, fastened to a willow tree 100 feet above the bridge on the left bank; the second, reading from 8 to 26 feet, fastened to an ash tree 30 feet above the bridge on the left bank. It is set on the same datum as the old wire gage of the United States Geological Survey established at that point by Mr. Babb in 1895, and above referred to. Its zero point is 753.5 feet above sea level. The observer was J. B. Austin.

Bench mark No. 2 is a large bridge spike in a sycamore tree about 50 feet above the bridge on the left bank; elevation, 11.00 feet above the zero of the gage. Bench mark No. 3, determined by measuring down to the water, is the top of the iron girder, 40 feet from the initial point for soundings, on the upstream side of the bridge; elevation, 57.55 feet above the zero of the gage.

The station was discontinued by the Weather Bureau on November 30, 1904, but the single daily readings for several months before that time are not considered reliable as representing the flow of the river, on account of the operation of a large water-power plant above. Only the records for the first five months of that year are used.

The station was reestablished in 1905 at a new iron highway bridge just below the old Mason and Turners Ferry, where the Oakdale "lower gage" was maintained as a regular station during parts of the years 1898 and 1899. It is 1½ miles below the Southern Railway bridge where the Oakdale station was located.

Discharge measurements are made from the bridge of two 130-foot spans, with 300 feet of wooden approach at the right bank and 730 feet at the left. At high floods both banks will overflow to the

extent of the bridge approaches, but can not get beyond at either end. The current is mostly swift and is irregular at places.

Gage heights are determined directly from the bench mark, which is the top of the downstream end of the second floor beam from the right bank; elevation, 35.00 feet above the datum of the assumed gage.

Discharge measurements of Chattahoochee River at Oakdale.

Date	Gage height	Dis-charge	Date	Gage height	Dis-charge
1895			1899		
October 15.....	<i>Feet</i> 0.40	<i>Sec.-ft.</i> 1,096	March 11 c.....	<i>Feet</i> 4.35	<i>Sec.-ft.</i> 4,397
December 14.....	.69	1,380	May 1 c.....	3.80	3,452
1896			May 26 c.....	2.36	2,678
January 14.....	.70	1,361	June 14 c.....	3.92	4,788
January 15.....	.00	985	September 9.....	1.32	1,452
January 20.....	.33	1,153	October 6.....	.67	1,150
January 22.....	1.01	1,380	October 17.....	.54	1,083
January 23.....	.55	1,250	November 18.....	.42	988
January 24.....	.28	1,126	1900		
July 9.....	18.05	18,180	January 4.....	1.53	1,784
July 10.....	12.80	11,140	March 27.....	5.85	5,504
July 13.....	3.01	2,957	July 6.....	4.00	3,886
July 15.....	1.88	2,066	September 12.....	1.08	1,456
July 17.....	4.60	4,640	November 29.....	2.32	2,334
July 24.....	2.22	2,470	1901		
August 29.....	— .18	958	January 12.....	19.85	21,710
September 9.....	— .55	744	April 11.....	3.55	3,247
October 17.....	— .50	775	June 19.....	4.75	4,446
1897			July 30.....	3.16	2,983
April 24.....	2.90	3,065	October 24.....	1.90	1,896
April 27.....	2.70	2,703	1902		
May 22.....	1.65	2,055	January 14.....	2.50	2,477
May 25.....	1.50	2,014	January 25.....	2.50	2,104
May 31.....	1.35	1,929	February 3.....	16.70	17,590
May 31.....	1.35	2,008	February 4.....	7.20	6,573
June 9.....	1.44	1,991	June 23.....	1.85	1,902
June 16.....	.94	1,523	July 10.....	1.75	1,689
June 23.....	.57	1,306	September 16.....	1.10	1,300
July 20.....	12.90	15,620	November 1.....	.75	1,086
August 5.....	.34	1,276	November 20.....	1.12	1,234
August 27.....	.38	1,196	1903		
September 10.....	— .12	849	March 2.....	9.95	9,787
September 17.....	— .30	778	March 23.....	21.85	33,620
October 2.....	— .50	659	April 23.....	5.03	4,836
November 5.....	— .46	1,194	June 2.....	12.20	12,480
November 24.....	— .05	879	September 2.....	1.25	1,612
December 6.....	2.65	2,426	October 7.....	1.10	1,359
December 28.....	1.70	1,926	November 5.....	1.90	1,882
1898			1904		
January 21.....	1.71	2,165	February 11.....	3.28	2,926
February 23.....	.65	1,446	March 15.....	3.50	3,233
April 5.....	9.95	12,580	May 3.....	1.38	1,361
May 16.....	.85	1,501	June 29.....	.60	1,030
May 26.....	.80	1,459	1905		
May 28 a.....	b 1.30	1,088	April 28 d.....	e 4.11	1,284
June 1 a.....	b 1.35	1,137	May 25 d.....	e 8.16	4,687
June 30 a.....	b .80	782	May 25 d.....	e 8.30	4,845
July 23 a.....	b 2.45	2,292			
August 20 a.....	b 4.90	4,157			
September 5 a.....	b 20.10	24,410			
November 19 a.....	b 4.77	4,735			

a Discharge measurements made at Mason and Turners Ferry and referred to "Oakdale lower gage."

b Gage height from "Oakdale lower gage."

c Measurement made at Mason and Turners Ferry, but referred to the upper gage at Southern Railway bridge.

d Discharge measurement made at the bridge just below Mason and Turners Ferry.

e Gage heights referred to the bench mark on the bridge.

WATER POWERS OF GEORGIA

Daily gage height, in feet, of Chattahoochee River at Oukdale.

Day	Oct.	Nov.	Dec.	Day	Oct.	Nov.	Dec.	Day	Oct.	Nov.	Dec.	
1895				1895				1895				
1		0.75	0.5	12		1.35	1.1	23	0.2	0.5	2.0	
2		1.7	.5	13		1.0	1.0	24	.3	.5	1.2	
3		1.0	.55	14		.75	.65	25	.25	.5	1.0	
4		.6	.6	15	0.4	.6	.6	26	.2	.55	.55	
5		.5	.6	16	.4	.6	.55	27	.25	.55	.8	
6		.55	.5	17	.35	.55	.55	28	.25	.7	.75	
7		.45	.45	18	.3	.6	.5	29	.3	.75	.7	
8		.4	.4	19	.25	.5	.4	30	.5	.45	2.0	
9		.6	.4	20	.3	.55	.5	31	.5		2.95	
10		.8	.6	21	.2	.5	.65					
11		1.0	1.3	22	.25	.5	1.0					
Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1896												
1	3.2	1.7	1.4	1.4	0.75	0.25	-0.35	0.45	-0.4	0.2	0.5	0.65
2	2.0	1.55	1.35	1.7	.75	1.4	-.4	.5	-.6	.1	.5	1.2
3	1.0	1.75	1.43	2.75	.75	1.45	-.45	1.4	-.6	.05	.65	1.7
4	1.2	2.1	1.45	1.35	.7	2.1	+ .15	1.7	-.6	-.2	1.13	3.2
5	1.1	2.2	1.4	1.35	.65	1.6	-.2	.75	-.6	-.3	1.6	2.3
6	1.0	2.8	1.35	1.3	3.15	1.15	-.15	.4	+.6	-.35	1.35	1.3
7	.8	3.7	1.95	1.1	1.7	.6	+2.0	.2	-.6	-.4	1.2	1.15
8	.95	4.3	1.75	1.15	1.2	.4	12.25	.15	.55	-.5	1.1	1.0
9	1.2	5.8	1.55	1.05	.9	.7	17.7	.15	.55	-.5	1.0	1.0
10	1.25	6.55	1.5	1.05	.75	.7	18.45	.1	-.5	-.5	1.05	1.0
11	1.0	4.3	1.75	1.05	.65	.65	4.75	.05	-.5	-.6	1.05	.9
12	.85	3.3	1.85	1.0	.6	.5	3.25	.05	.55	-.6	1.6	.7
13	.8	2.8	1.55	1.0	.5	.3	3.1	.3	-.6	-.55	3.8	.6
14	.75	2.95	1.35	.9	.5	.2	2.9	.25	-.6	-.55	4.6	.65
15	.7	4.1	1.2	.9	.4	-.05	1.95	.05	-.6	-.55	2.6	.7
16	.85	2.9	1.15	.9	.3	+.05	3.0	.1	-.65	-.55	1.5	.65
17	2.4	2.55	1.1	.85	.3	-.05	4.4	.1	-.65	-.55	1.0	.65
18	2.35	2.2	1.35	.85	.25	+.1	2.7	.1	-.65	-.55	.8	.65
19	2.1	2.1	1.7	.85	.25	.15	1.75	-.1	-.65	-.55	.6	.65
20	1.5	1.8	1.65	.85	.2	.55	1.9	-.25	-.65	-.55	.5	.65
21	1.25	1.6	1.45	.75	.15	1.6	1.65	-.3	-.5	-.55	.4	.6
22	1.8	1.45	1.35	.75	.2	.45	1.9	-.3	-.15	-.5	.4	.55
23	6.3	1.55	1.4	.65	.2	.5	2.45	-.3	+.4	-.23	.3	.5
24	9.8	1.6	1.45	.7	1.1	.3	2.4	-.3	-.6	-.05	.25	.5
25	9.95	1.5	1.4	.65	1.55	.2	1.5	+1.0	-.1	+ .05	.2	.45
26	5.1	1.4	1.35	6.5	.65	-.1	1.3	-.1	-.4	.1	.2	.45
27	3.55	1.35	1.25	1.4	.85	+.45	.9	-.3	-.4	.15	.2	.4
28	2.65	1.3	1.2	1.7	.65	-.1	.3	-.3	+.2	.25	.2	.35
29	2.3	1.55	1.15	1.15	.95	-.2	.8	-.3	.45	.9	.2	.35
30	2.1		1.2	.85	.4	-.25	.8	-.35	.3	.65	.2	.3
31	1.8		1.2		.35		.5	-.4		.5		.25
1897												
1	.2	3.1	2.0	2.3	4.1	1.0	.5	.85	.5	-.5	.0	1.1
2	.2	4.5	1.8	4.1	3.2	1.0	.45	.8	.35	-.5	.35	.85
3	.2	4.9	1.8	5.0	2.3	1.15	.55	.9	.1	-.5	.35	1.2
4	.3	3.25	2.0	7.0	2.5	1.35	.55	.3	.2	-.45	.95	1.9
5	.4	3.7	1.9	12.3	2.4	1.15	1.15	.7	.1	-.5	.35	2.65
6	.4	4.1	9.0	17.0	2.25	1.05	.65	.65	.0	-.5	.3	2.6
7	.35	5.5	9.2	8.0	2.15	1.0	2.5	1.6	.0	-.5	.15	1.5
8	.35	5.0	5.5	5.4	2.05	.85	1.8	1.35	-.05	-.4	.15	1.1
9	.3	3.1	4.45	6.0	2.0	1.1	1.32	1.4	-.15	-.45	.1	.75
10	.3	2.4	4.05	5.0	1.95	1.0	2.45	1.2	-.15	-.45	.15	.6
11	.2	3.4	3.6	4.6	1.9	1.0	2.45	.95	-.2	+1.35	.1	.55
12	.2	4.0	6.4	4.1	1.9	.85	1.6	.8	-.2	1.5	.05	.5
13	.4	5.3	12.6	4.0	1.85	.75	1.2	.65	.15	1.4	.0	.5
14	3.0	4.0	10.0	4.55	1.9	.65	.85	.5	-.2	-.35	-.05	1.75
15	3.7	2.6	8.4	4.05	2.35	.55	.6	.45	.25	+ .15	-.1	1.8
16	2.3	2.6	6.8	4.0	1.85	.5	.5	.4	-.25	.0	-.05	1.9
17	2.4	2.4	5.45	3.5	1.7	1.55	4.2	2.9	.3	-.05	+1	1.65
18	4.0	2.1	6.1	2.2	1.5	1.0	2.45	1.25	.3	-.05	-.05	1.15
19	4.6	1.9	5.8	3.05	1.45	1.05	7.65	.95	.3	-.15	-.05	.65
20	5.5	2.5	5.55	3.0	1.35	.55	12.3	.65	-.35	.0	-.05	.75

Daily gage height, in feet, of Chattahoochee River at Oakdale—Continued

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1897												
21.....	7.5	2.5	5.0	2.8	1.35	1.85	10.3	0.55	-0.35	1.45	-0.05	0.95
22.....	6.85	2.9	4.3	2.75	1.4	.75	6.1	1.15	-.35	.35	-.05	1.95
23.....	3.9	5.1	4.5	2.7	1.4	.55	4.35	1.1	-.35	.15	-.05	2.95
24.....	3.2	4.5	4.0	2.7	1.35	.45	2.2	1.0	-.3	.0	-.1	1.75
25.....	2.0	3.6	3.9	2.65	1.3	.9	1.65	.6	-.25	.05	-.1	1.7
26.....	1.65	2.9	3.35	2.6	1.2	.55	2.85	.5	-.3	.05	-.1	2.25
27.....	.45	2.4	3.1	2.4	1.1	.45	2.3	.25	-.35	.05	+.5	1.95
28.....	1.1	2.05	3.0	2.1	1.05	.3	1.35	.2	-.35	-.05	1.35	1.85
29.....	1.25	2.75	2.0	1.0	1.0	1.2	.2	-.35	-.05	1.85	1.35
30.....	1.5	2.7	2.2	1.05	.75	1.1	.15	-.4	-.1	1.5	2.05
31.....	2.0	2.15	1.195	1.65	-.195
1898												
1.....	.75	1.5	.4	5.5	1.85	.25	α.95	α.2.3	α.3.1	α.2.4	α.3.1	α.3.7
2.....	.55	1.3	.4	3.45	1.6	.3	1.1	2.0	20.0	2.5	3.0	3.4
3.....	.55	1.05	.55	2.6	1.55	.25	.75	1.9	27.75	2.9	2.9	3.6
4.....	.5	1.0	.8	3.05	1.45	.2	.7	8.5	27.0	15.0	3.0	4.1
5.....	.55	.95	.85	3.7	1.35	.09	1.4	14.0	22.0	19.25	3.1	5.5
6.....	.55	1.0	.7	11.15	1.2	.03	1.1	16.0	15.0	23.5	3.8	4.75
7.....	.55	.95	.55	5.8	1.2	.0	1.85	9.0	12.0	16.25	3.5	4.1
8.....	.6	.8	.45	3.8	1.1	-.05	3.7	6.0	7.5	7.5	3.3	3.75
9.....	.65	.75	.35	2.95	1.1	-.02	5.1	3.8	5.5	6.5	2.9	3.4
10.....	.55	.7	.3	2.35	.9	-.1	4.75	4.3	5.1	5.5	2.8	3.1
11.....	.55	.7	.3	2.3	.9	-.13	3.5	4.5	4.75	4.9	3.1	3.0
12.....	.55	.7	.3	2.0	.9	-.2	2.3	5.8	4.4	4.5	3.8	3.3
13.....	.85	.65	.3	1.75	1.2	.0	1.85	4.1	4.2	4.3	3.1	3.1
14.....	1.25	.65	.5	1.75	.95	.13	2.5	7.5	3.9	4.0	3.6	2.95
15.....	1.0	.55	1.05	1.9	.85	.03	4.2	5.5	3.75	3.9	4.1	2.9
16.....	.85	.55	1.4	1.6	.8	.93	4.1	2.9	3.6	3.7	3.6	2.8
17.....	.8	.45	3.5	1.45	.7	-.05	2.5	2.85	3.4	3.5	3.7	2.75
18.....	.75	.6	1.75	1.3	.65	+1.5	1.85	2.4	3.3	5.7	4.05	2.85
19.....	.75	.9	1.5	1.15	.6	1.65	1.75	2.9	3.2	7.9	4.75	2.95
20.....	.9	1.05	1.05	1.2	.6	1.53	1.5	6.0	3.1	4.7	5.1	3.25
21.....	1.5	.75	.85	1.4	.6	1.75	1.4	6.5	3.3	4.3	4.5	3.95
22.....	2.3	.75	.75	1.35	.55	.35	1.45	4.5	2.9	4.9	3.75	3.5
23.....	1.5	.55	.55	1.4	1.2	.1	1.5	3.9	3.1	5.3	3.5	7.1
24.....	1.35	.55	.45	3.65	1.15	-.05	12.4	2.8	5.3	4.1	4.75	3.5
25.....	2.95	.45	.4	4.55	1.25	-.15	6.3	2.75	3.25	3.3	3.75	5.75
26.....	7.7	.4	.4	2.65	.8	-.15	3.4	2.9	2.95	3.5	3.5	4.1
27.....	6.8	.45	.4	2.25	.8	-.2	3.8	7.5	2.8	3.4	3.3	3.75
28.....	5.05	.6	1.15	2.85	.6	-.05	6.4	4.3	2.7	3.45	3.1	3.5
29.....	4.35	2.5	2.35	.3	-.07	5.85	2.8	2.6	3.3	3.75	2.95
30.....	3.05	6.3	1.85	.3	-.1	4.4	3.2	2.5	3.45	4.05	2.75
31.....	2.7	3.425	3.75	3.2	3.3	3.1
1899												
1.....	64.25	65.1	69.8	613.0	64.7	2.45	1.5	1.7	4.6	.4	.6	1.3
2.....	4.75	4.5	6.85	7.75	4.45	2.4	1.4	1.4	2.7	.1	.5	1.3
3.....	3.6	5.8	6.17	6.5	4.4	2.3	1.35	1.2	2.1	.1	.5	1.5
4.....	3.4	4.9	5.9	7.75	4.35	2.1	1.25	1.1	1.9	.1	.5	1.4
5.....	3.1	6.5	8.1	6.5	4.5	2.05	1.2	1.1	1.6	.4	.5	1.1
6.....	3.75	10.0	8.5	5.9	5.1	2.0	1.4	1.0	1.0	.6	.4	.9
7.....	6.75	16.0	6.4	6.5	4.6	2.0	1.4	.9	.9	1.6	.4	.8
8.....	6.1	21.5	5.9	7.75	4.35	2.05	1.4	.8	.8	1.5	.4	.8
9.....	5.25	13.4	5.5	7.5	4.25	2.05	1.4	.7	.7	2.0	.4	.8
10.....	4.7	9.5	5.25	7.1	4.1	2.1	1.3	.6	.7	1.2	.4	.8
11.....	6.3	6.4	5.1	6.8	4.0	2.15	1.3	.6	3.0	.9	.4	.7
12.....	4.75	5.5	5.0	5.75	3.95	2.75	1.1	.5	1.1	.7	.7	2.2
13.....	4.25	4.9	4.95	5.25	3.9	4.8	1.1	.5	.9	.7	.5	6.4
14.....	4.5	4.1	6.25	5.2	3.85	4.0	.9	.5	.8	.7	.5	3.1
15.....	5.5	4.6	10.0	5.1	3.8	2.9	.8	.5	.7	.6	.5	2.4
16.....	4.9	5.6	21.5	5.0	3.7	2.25	.8	.6	.6	.5	.6	1.8
17.....	4.75	7.25	24.25	5.25	3.6	2.05	.8	.6	.5	.5	.6	1.6
18.....	4.5	6.1	11.0	4.95	3.5	2.05	1.0	.6	.3	.6	.5	1.3
19.....	4.1	5.6	10.5	5.0	3.55	2.0	1.3	.5	.4	.6	.5	1.1
20.....	3.9	4.9	15.0	4.95	3.5	1.9	1.0	.4	.4	.8	.4	1.2

α Gage heights July 1 to December 31, 1898, were recorded from "Oakdale lower gage" at Mason and Turners Ferry.

β Gage heights January 1 to May 31, 1899, were recorded from "Oakdale lower gage" at Mason and Turners Ferry.

WATER POWERS OF GEORGIA

Daily gage height, in feet, of Chattahoochee River at Oakdale—Continued.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1899												
21	3.75	5.25	8.75	4.85	3.45	1.75	1.35	0.4	0.4	0.9	0.4	1.1
22	3.6	5.2	7.25	4.65	5.5	1.7	3.3	.4	.4	.7	.9	1.1
23	3.9	5.0	9.5	4.75	3.6	1.55	2.3	.3	.3	.6	2.0	3.4
24	4.25	4.9	9.0	4.95	3.5	1.55	1.9	.2	.3	.5	2.4	5.5
25	4.1	4.6	6.5	7.25	3.35	1.8	.3	.1	.3	.5	1.7	4.6
26	4.25	10.23	7.1	8.0	3.25	2.05	2.1	.2	.3	.4	3.0	3.4
27	3.7	22.13	6.2	6.25	3.15	2.2	2.1	5.2	.2	.5	2.8	2.4
28	3.45	18.88	6.1	5.25	3.1	2.0	5.9	3.4	.2	.5	2.7	2.0
29	3.25		7.9	5.0	3.2	1.8	3.4	1.4	.2	.9	2.1	2.1
30	3.5		6.45	4.8	6.1	1.6	3.3	3.2	.2	.7	1.8	1.3
31	4.65		12.3		3.4		3.2	2.8		.6		1.7
1900												
1	1.0	1.0	4.5	3.4	5.0	3.0	5.0	5.0	2.0	2.1	2.4	2.2
2	.7	1.0	5.9	3.1	4.8	3.7	4.5	4.5	2.0	2.1	2.4	2.2
3	.5	.9	4.3	3.0	4.5	4.0	6.0	4.0	2.0	2.1	3.0	2.1
4	.5	.9	3.6	2.7	4.0	4.7	7.5	4.0	1.9	3.0	2.8	2.3
5	.9	2.9	3.3	2.7	3.9	4.0	7.0	4.0	1.7	3.4	2.7	4.1
6	1.2	3.5	3.1	2.8	3.0	3.8	6.5	3.5	1.8	3.8	2.5	4.0
7	1.3	2.2	3.0	2.8	3.0	4.7	6.4	3.5	1.8	4.0	2.5	4.0
8	1.3	1.9	8.8	2.7	3.0	9.7	6.0	3.5	1.8	4.0	2.5	3.8
9	1.2	3.8	7.9	2.7	2.9	10.5	5.8	3.0	1.7	3.9	2.4	3.7
10	1.1	4.3	6.9	2.6	2.9	8.0	5.7	3.0	1.7	3.5	2.4	3.5
11	2.0	7.4	5.5	3.0	2.8	5.0	5.6	3.0	1.5	3.5	2.4	2.1
12	3.9	8.0	4.0	6.4	2.7	4.0	5.4	3.0	1.5	3.9	2.4	2.0
13	3.0	15.5	3.1	5.4	2.7	4.5	5.2	3.0	4.3	4.3	2.3	2.0
14	2.8	20.7	3.2	4.2	2.6	4.0	5.0	3.0	3.4	4.2	2.2	2.3
15	2.2	16.4	3.0	3.8	2.6	3.5	4.5	3.0	10.2	4.0	2.1	2.3
16	1.9	6.0	5.0	3.3	2.6	3.0	4.4	2.7	3.2	3.6	2.1	2.2
17	1.7	4.3	3.6	4.0	2.5	3.5	4.3	3.0	6.0	3.4	2.0	2.1
18	1.8	3.3	3.0	6.9	3.5	4.5	4.2	4.0	3.1	3.2	2.0	2.1
19	2.9	3.5	4.5	9.0	3.7	6.0	4.1	3.5	3.0	3.0	1.8	2.0
20	4.0	3.1	5.9	7.3	3.0	6.5	4.0	3.5	2.8	3.0	1.5	2.3
21	5.8	3.0	6.6	6.3	3.1	8.0	3.9	3.0	2.8	2.8	1.5	2.6
22	4.8	4.2	4.8	7.0	3.2	9.0	3.3	3.0	2.7	3.0	1.8	2.3
23	2.9	4.3	4.1	6.3	3.7	13.6	3.7	3.0	2.5	3.3	2.0	2.7
24	3.0	3.3	3.5	13.6	3.9	18.0	3.7	3.0	2.3	3.3	1.9	3.0
25	2.6	4.1	7.7	7.5	3.7	17.5	4.0	2.7	2.3	3.0	1.8	2.8
26	1.9	4.0	7.5	6.0	3.5	11.4	5.0	2.7	2.0	3.0	1.8	2.7
27	1.7	3.3	6.0	5.5	3.4	10.5	6.0	2.6	2.0	2.9	5.6	2.5
28	1.5	3.0	4.5	5.0	3.2	7.5	6.5	2.5	1.8	2.3	3.3	2.3
29	1.5		4.0	5.0	3.0	6.0	7.4	3.0	1.5	2.6	2.3	2.3
30	1.4		3.8	5.0	2.5	5.5	10.0	3.0	1.5	2.4	2.0	3.0
31	1.3		3.5		2.4		6.0	2.7		2.4		3.3
1901												
1	2.1	4.3	2.4	4.5	3.1	6.8	4.7	2.6	6.0	3.7	1.7	1.6
2	2.3	4.4	2.4	4.5	3.1	6.6	4.1	2.3	5.0	4.6	1.7	1.6
3	2.3	5.0	2.3	4.7	3.1	6.0	3.9	2.1	4.8	4.2	1.6	1.8
4	2.2	5.2	2.3	4.5	3.0	6.0	3.0	1.9	4.6	3.9	1.8	1.8
5	2.2	5.0	2.3	4.3	3.0	5.3	2.9	1.8	4.4	3.6	1.8	1.7
6	2.2	4.7	2.1	4.0	2.9	4.7	2.3	2.2	4.0	3.1	1.8	1.8
7	2.1	4.1	2.1	4.0	2.9	4.3	2.3	9.9	3.7	2.9	1.7	1.8
8	2.1	4.0	2.1	3.7	3.0	4.0	2.7	3.2	3.6	2.8	1.7	1.7
9	2.5	4.2	2.2	3.7	3.0	3.6	2.7	3.0	3.6	2.8	1.7	1.7
10	3.0	4.1	3.3	3.7	3.0	3.4	2.6	2.9	3.6	2.7	1.7	1.7
11	9.0	4.0	6.5	3.7	3.0	3.2	2.6	5.7	3.8	2.7	1.7	1.7
12	19.9	3.6	5.5	6.4	3.0	3.4	2.5	4.0	3.7	2.7	1.6	1.7
13	22.0	3.2	4.4	12.0	3.1	3.8	2.2	4.2	3.6	3.8	1.6	1.6
14	16.0	3.1	3.4	9.5	3.0	5.1	2.1	4.4	3.9	3.2	1.6	1.8
15	8.4	3.0	3.2	7.0	3.0	10.0	2.1	5.6	3.7	2.9	1.6	2.6
16	5.1	2.9	3.2	5.3	2.9	9.8	2.2	9.8	3.7	2.8	1.7	2.0
17	4.4	2.9	3.0	5.0	2.8	8.3	9.1	10.5	3.8	2.8	1.6	1.8
18	4.0	2.8	3.0	6.1	2.8	7.1	5.0	9.3	14.6	2.8	1.6	1.7
19	4.0	2.8	3.0	7.7	2.7	4.2	3.9	9.2	7.2	2.7	1.7	1.7
20	3.8	2.7	3.0	7.0	3.2	3.9	9.0	9.8	4.3	2.7	1.9	1.7

APALACHICOLA DRAINAGE BASIN, STREAM FLOW

243

Daily gage height, in feet, of Chattahoochee River at Oakdale—Continued.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1901												
21.....	3.7	2.7	3.2	5.8	7.1	3.7	4.2	10.8	3.9	2.7	1.8	1.7
22.....	3.7	2.6	3.2	6.0	13.7	3.5	3.0	17.5	3.9	2.5	1.7	1.7
23.....	3.4	2.6	3.1	5.4	20.0	3.4	2.9	19.3	3.8	2.3	1.8	1.7
24.....	3.7	2.5	3.2	5.1	7.8	3.2	2.7	16.4	3.8	2.1	1.8	1.9
25.....	3.8	2.5	5.3	4.8	6.0	3.2	2.6	10.3	3.6	2.0	1.8	1.8
26.....	3.5	2.5	10.5	4.8	5.2	4.9	2.4	10.1	3.4	2.0	1.8	1.8
27.....	3.6	2.4	23.5	4.5	4.0	4.2	2.8	9.8	3.1	1.8	1.7	1.8
28.....	3.4	2.4	17.0	4.2	3.7	3.9	2.6	9.1	2.9	1.7	1.7	2.4
29.....	3.1	9.5	3.5	3.1	3.9	2.7	8.7	3.2	1.7	1.7	22.0
30.....	4.6	7.3	3.1	3.1	3.8	3.1	6.8	3.6	1.7	1.6	27.0
31.....	4.3	5.0	7.1	3.0	6.6	1.7	25.0
1902												
1.....	9.2	7.2	25.0	7.1	3.4	3.2	2.6	2.1	2.4	2.1	.8	2.4
2.....	6.0	18.0	20.8	6.4	3.8	3.1	2.6	1.9	2.1	1.5	.7	2.6
3.....	5.1	19.2	10.3	6.2	3.8	3.1	3.4	1.3	2.1	1.6	.7	7.0
4.....	4.2	8.6	7.1	5.3	3.6	3.0	2.8	1.3	2.1	1.8	.5	8.6
5.....	3.7	6.0	7.8	5.2	3.6	2.8	2.6	1.3	2.4	1.5	.5	4.9
6.....	3.2	4.3	6.0	4.8	3.6	2.8	2.4	1.8	2.3	1.6	.7	4.1
7.....	3.1	3.2	5.2	4.9	3.6	2.8	2.4	1.9	2.1	2.1	.8	3.3
8.....	2.8	2.8	4.6	4.9	3.5	2.8	2.1	1.9	2.0	1.8	.8	2.4
9.....	2.5	2.8	4.4	5.0	3.5	2.8	2.1	1.3	3.5	1.6	1.0	1.9
10.....	2.3	2.7	4.1	4.4	3.5	2.7	1.8	1.3	3.2	1.5	1.2	1.8
11.....	2.3	2.7	3.8	4.2	3.6	2.7	1.8	1.9	2.8	1.4	1.3	1.6
12.....	2.3	2.8	3.6	4.2	3.8	2.7	3.6	1.3	2.3	1.8	1.0	1.6
13.....	2.3	2.8	5.5	3.8	3.6	2.7	2.4	1.3	2.3	2.1	.9	1.8
14.....	2.1	2.8	4.8	3.8	3.6	2.6	2.2	1.3	4.8	1.9	.7	1.6
15.....	2.1	2.8	5.7	3.8	3.6	2.8	2.6	1.7	3.5	1.4	.6	1.7
16.....	2.1	3.0	11.4	3.6	3.8	5.6	2.4	1.7	2.8	1.6	.8	5.4
17.....	2.1	3.2	8.0	3.8	3.8	4.2	2.2	1.7	2.4	1.2	.9	7.0
18.....	2.1	3.1	6.2	4.1	3.8	3.4	2.1	1.7	2.4	1.4	1.3	6.0
19.....	2.3	2.8	5.6	4.1	3.8	4.0	1.8	1.7	2.6	1.5	1.0	4.0
20.....	2.2	2.8	4.8	3.8	3.5	3.6	1.8	1.3	2.6	1.6	1.1	2.7
21.....	2.6	3.0	4.6	3.8	3.5	4.1	2.2	1.8	2.6	1.2	1.0	3.0
22.....	2.6	3.0	4.4	3.8	3.5	4.4	2.0	1.3	2.4	1.0	.8	2.9
23.....	2.5	2.8	4.1	3.8	3.4	4.2	1.9	1.6	2.1	.8	.8	2.4
24.....	2.4	2.8	4.1	3.6	3.2	4.2	1.8	1.6	2.1	.7	1.0	2.0
25.....	2.4	3.6	3.8	3.6	3.2	3.8	1.8	1.6	5.7	.5	.9	1.8
26.....	2.4	3.6	3.8	3.6	3.2	3.8	1.8	1.6	5.8	.8	4.8	1.7
27.....	2.4	3.8	4.2	3.6	3.2	3.0	1.8	1.5	4.6	.9	4.3	1.6
28.....	2.3	23.2	6.4	3.6	3.2	2.8	2.6	1.3	7.9	1.0	3.6	1.7
29.....	3.1	21.0	3.4	3.1	2.8	2.7	2.7	5.2	.9	1.9	2.0
30.....	4.0	21.7	3.5	3.1	2.3	2.5	2.6	3.1	.7	1.6	3.4
31.....	4.6	9.8	3.1	2.1	2.45	3.0
Day	Jan.	Feb.	Mar.	Nov.	Dec.	Day	Jan.	Feb.	Mar.	Nov.	Dec.	
1903												
1.....	2.6	3.0	19.4	1.0	1.0	17.....	2.5	24.0	5.9	1.3	1.3	
2.....	2.8	2.9	12.0	1.0	18.....	2.4	25.6	4.8	1.7	1.3	
3.....	3.1	3.4	7.2	1.5	1.0	19.....	2.2	9.4	4.6	1.5	1.3	
4.....	2.8	7.6	6.6	2.0	1.0	20.....	2.1	4.9	5.0	1.5	1.5	
5.....	2.5	10.2	5.8	2.0	1.0	21.....	2.0	2.7	11.4	1.5	1.6	
6.....	2.4	6.7	6.4	3.0	1.0	22.....	2.0	3.0	13.0	1.3	1.6	
7.....	2.6	7.7	5.8	2.0	1.0	23.....	1.9	3.2	21.0	1.5	1.5	
8.....	2.8	13.0	5.8	1.5	1.0	24.....	2.2	3.7	23.4	1.2	1.5	
9.....	2.7	15.6	5.5	1.5	1.0	25.....	2.5	4.1	22.4	1.1	1.5	
10.....	2.5	7.3	7.4	1.3	1.2	26.....	2.4	3.7	8.3	1.2	1.7	
11.....	3.3	11.0	12.4	1.3	1.2	27.....	2.0	4.2	7.5	1.0	1.7	
12.....	4.0	16.0	15.0	1.5	1.0	28.....	2.3	11.4	6.8	1.0	1.5	
13.....	4.9	10.6	11.4	1.4	1.3	29.....	2.7	10.8	1.0	1.5	
14.....	3.8	4.7	7.7	1.3	1.5	30.....	4.5	16.6	1.0	1.4	
15.....	3.2	5.8	6.8	1.2	1.5	31.....	3.4	15.8	1.3	
16.....	2.8	5.8	6.0	1.2	1.3							

WATER POWERS OF GEORGIA

Daily gage height, in feet, of Chattahoochee River at Oakdale—Continued.

Day	Jan.	Feb.	Mar.	Apr.	May	Day	Jan.	Feb.	Mar.	Apr.	May
1904						1904					
1.....	1.3	1.6	2.0	2.0	1.5	17.....	1.7	1.6	2.5	2.0	1.5
2.....	1.3	1.5	2.3	2.0	1.5	18.....	1.5	1.6	2.0	2.0	1.5
3.....	1.7	1.7	2.4	1.9	1.4	19.....	1.9	1.7	2.0	1.8	1.4
4.....	1.3	1.5	2.4	1.8	1.4	20.....	1.6	2.5	2.0	1.7	1.3
5.....	1.3	1.5	2.0	1.8	1.4	21.....	1.5	2.7	1.8	1.7	1.3
6.....	1.3	1.5	2.3	1.5	1.4	22.....	1.7	4.5	2.0	1.7	1.0
7.....	1.4	1.6	4.5	1.7	1.4	23.....	4.0	7.7	3.8	1.7	1.0
8.....	1.4	3.6	8.2	2.5	1.8	24.....	4.0	4.3	4.0	1.5	1.0
9.....	1.3	3.0	4.0	3.0	4.0	25.....	3.5	3.5	4.4	1.5	1.0
10.....	1.4	3.6	3.0	5.0	4.5	26.....	3.0	3.0	4.0	1.5	.8
11.....	1.4	4.0	2.3	3.0	2.7	27.....	3.0	2.8	3.0	1.7	.8
12.....	1.3	2.7	2.5	2.5	2.0	28.....	3.0	2.4	2.6	1.7	.8
13.....	1.5	2.0	2.2	2.2	1.8	29.....	3.5	2.0	2.3	1.5	.8
14.....	1.6	1.8	2.5	2.0	1.7	30.....	3.6	2.0	1.5	1.0
15.....	1.5	2.0	4.5	1.9	1.7	31.....	1.6	1.8	1.7
16.....	1.5	1.9	3.0	1.9	1.7						

Rating tables for Chattahoochee River at Oakdale.

OCTOBER 15, 1895, TO DECEMBER 31, 1896.^a

Gage height	Dis-charge						
<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>
—0.60	760	0.70	1,356	2.00	2,155	3.30	3,223
— .50	790	.80	1,412	2.10	2,227	3.40	3,315
— .40	821	.90	1,469	2.20	2,301	3.50	3,410
— .30	856	1.00	1,523	2.30	2,377	3.60	3,508
— .20	895	1.10	1,586	2.40	2,455	3.70	3,608
— .10	933	1.20	1,646	2.50	2,535	3.80	3,711
.00	985	1.30	1,707	2.60	2,616	3.90	3,817
.10	1,035	1.40	1,769	2.70	2,698	4.00	3,928
.20	1,086	1.50	1,832	2.80	2,782	4.20	4,154
.30	1,138	1.60	1,896	2.90	2,868	4.40	4,391
.40	1,191	1.70	1,961	3.00	2,956	4.60	4,640
.50	1,245	1.80	2,027	3.10	3,044	4.80	4,899
.60	1,300	1.90	2,085	3.20	3,133	5.00	5,170

JANUARY 1 TO DECEMBER 31, 1897.^b

—0.50	675	1.50	1,855	4.00	4,340	8.00	9,740
— .40	725	1.60	1,927	4.20	4,610	8.20	10,010
— .30	775	1.70	2,000	4.40	4,880	8.40	10,280
— .20	825	1.80	2,075	4.60	5,150	8.60	10,550
— .10	876	1.90	2,150	4.80	5,420	8.80	10,820
.00	928	2.00	2,226	5.00	5,690	9.00	11,090
.10	980	2.10	2,303	5.20	5,960	9.20	11,360
.20	1,035	2.20	2,380	5.40	6,230	9.40	11,630
.30	1,091	2.30	2,460	5.60	6,500	9.60	11,900
.40	1,148	2.40	2,540	5.80	6,770	9.80	12,170
.50	1,206	2.50	2,620	6.00	7,040	10.00	12,440
.60	1,266	2.60	2,702	6.20	7,310	11.00	13,790
.70	1,326	2.70	2,785	6.40	7,580	12.00	15,140
.80	1,388	2.80	2,870	6.60	7,850	13.00	16,490
.90	1,450	2.90	2,965	6.80	8,120	14.00	17,840
1.00	1,515	3.00	3,060	7.00	8,390	15.00	19,190
1.10	1,580	3.20	3,275	7.20	8,660	16.00	20,540
1.20	1,647	3.40	3,530	7.40	8,930	17.00	21,890
1.30	1,715	3.60	3,800	7.60	9,200		
1.40	1,785	3.80	4,070	7.80	9,470		

^a Discharge estimated above gage height, 5.0 feet.

^b Above gage height 3.40 the rating curve is a tangent, the difference being 135 per tenth.

Rating tables for Chattahoochee River at Oakdale—Continued.

JANUARY 1 TO JUNE 30, 1898.^a

Gage height	Dis-charge						
<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>
— 0.20	920	1.80	2,180	3.80	3,830	7.60	9,000
— .10	970	1.80	2,200	3.90	3,930	7.80	9,800
.00	1,020	2.00	2,270	4.00	4,030	8.00	9,600
.10	1,075	2.10	2,345	4.20	4,250	8.50	10,550
.20	1,130	2.20	2,420	4.40	4,470	9.00	11,100
.30	1,185	2.30	2,495	4.60	4,690	9.50	11,850
.40	1,240	2.40	2,570	4.80	4,920	10.00	12,600
.50	1,295	2.50	2,650	5.00	5,160	10.50	13,350
.60	1,350	2.60	2,730	5.20	5,420	11.00	14,100
.70	1,405	2.70	2,815	5.40	5,700	12.00	15,600
.80	1,470	2.80	2,900	5.60	6,000	13.00	17,100
.90	1,530	2.90	2,985	5.80	6,300	14.00	18,600
1.00	1,590	3.00	3,070	6.00	6,600	15.00	20,100
1.10	1,650	3.10	3,150	6.20	6,900	16.00	21,600
1.20	1,720	3.20	3,250	6.40	7,200	17.00	23,100
1.30	1,785	3.30	3,340	6.60	7,500	18.00	24,600
1.40	1,850	3.40	3,430	6.80	7,800	19.00	26,100
1.50	1,920	3.50	3,530	7.00	8,100	20.00	27,600
1.60	1,990	3.60	3,630	7.20	8,400		
1.70	2,060	3.70	3,730	7.40	8,700		

JULY 1, 1898, TO MAY 31, 1899.^b

0.70	730	3.80	3,050	7.20	7,260	13.00	14,800
.80	780	4.00	3,250	7.40	7,520	14.00	16,100
.90	840	4.20	3,450	7.60	7,780	15.00	17,400
1.00	900	4.40	3,650	7.80	8,040	16.00	18,700
1.20	1,020	4.60	3,900	8.00	8,300	17.00	20,000
1.40	1,150	4.80	4,150	8.20	8,560	18.00	21,300
1.60	1,280	5.00	4,400	8.40	8,820	19.00	22,600
1.80	1,420	5.20	4,660	8.60	9,080	20.00	23,900
2.00	1,560	5.40	4,920	8.80	9,340	21.00	25,200
2.20	1,700	5.60	5,180	9.00	9,600	22.00	26,500
2.40	1,850	5.80	5,440	9.20	9,860	23.00	27,800
2.60	2,000	6.00	5,700	9.40	10,120	24.00	29,100
2.80	2,150	6.20	5,960	9.60	10,380	25.00	30,400
3.00	2,300	6.40	6,220	9.80	10,640	26.00	31,700
3.20	2,470	6.60	6,480	10.00	10,900	27.00	33,000
3.40	2,650	6.80	6,740	11.00	12,200	28.00	34,300
3.60	2,850	7.00	7,000	12.00	13,500		

JUNE 1, 1899, TO DECEMBER 31, 1900.^c

0.10	870	1.30	1,560	2.50	2,540	3.70	3,720
.20	910	1.40	1,630	2.60	2,630	3.80	3,825
.30	950	1.50	1,700	2.70	2,720	3.90	3,930
.40	1,000	1.60	1,780	2.80	2,810	4.00	4,035
.50	1,050	1.70	1,860	2.90	2,905	4.20	4,250
.60	1,100	1.80	1,940	3.00	3,000	4.40	4,470
.70	1,160	1.90	2,020	3.10	3,100	4.60	4,700
.80	1,220	2.00	2,100	3.20	3,200	4.80	4,930
.90	1,280	2.10	2,185	3.30	3,300	5.00	5,160
1.00	1,350	2.20	2,270	3.40	3,405		
1.10	1,420	2.30	2,360	3.50	3,510		
1.20	1,490	2.40	2,450	3.60	3,615		

^a Above gage height 5.40 the rating curve is a tangent, the difference being 150 per tenth.

^b Applies only to the gage heights recorded from the lower gage at Mason and Turners Ferry. Above 5.0 feet the rating curve is a tangent, the difference being 130 per tenth.

^c Above gage height 5.0 feet the above table is the same as the table used from January 1 to June 30, 1898.

WATER POWERS OF GEORGIA

Rating tables for Chattahoochee River at Oakdale—Continued.

JANUARY 1 TO DECEMBER 31, 1901.^a

Gage height	Dis-charge						
<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>
1.60	1,690	3.50	3,210	5.40	5,256	8.60	8,904
1.70	1,758	3.60	3,305	5.50	5,370	8.80	9,132
1.80	1,827	3.70	3,402	5.60	5,484	9.00	9,360
1.90	1,898	3.80	3,500	5.70	5,598	9.20	9,588
2.00	1,970	3.90	3,600	5.80	5,712	9.40	9,816
2.10	2,044	4.00	3,702	5.90	5,826	9.60	10,044
2.20	2,119	4.10	3,805	6.00	5,940	9.80	10,272
2.30	2,195	4.20	3,909	6.20	6,168	10.00	10,500
2.40	2,272	4.30	4,014	6.40	6,396	10.50	11,070
2.50	2,350	4.40	4,121	6.60	6,624	11.00	11,640
2.60	2,430	4.50	4,230	6.80	6,852	11.50	12,210
2.70	2,511	4.60	4,344	7.00	7,080	12.00	12,780
2.80	2,593	4.70	4,458	7.20	7,308	12.50	13,350
2.90	2,676	4.80	4,572	7.40	7,536	13.00	13,920
3.00	2,760	4.90	4,686	7.60	7,764	13.50	14,490
3.10	2,846	5.00	4,800	7.80	7,992	14.00	15,060
3.20	2,934	5.10	4,914	8.00	8,220	14.50	15,630
3.30	3,024	5.20	5,028	8.20	8,448		
3.40	3,116	5.30	5,142	8.40	8,676		

JANUARY 1 TO DECEMBER 31, 1902.^b

0.50	950	1.60	1,620	2.70	2,415	3.80	3,450
.60	1,005	1.70	1,685	2.80	2,500	3.90	3,555
.70	1,060	1.80	1,750	2.90	2,585	4.00	3,665
.80	1,120	1.90	1,820	3.00	2,675	4.10	3,775
.90	1,180	2.00	1,890	3.10	2,765	4.20	3,885
1.00	1,240	2.10	1,960	3.20	2,855	4.30	4,000
1.10	1,300	2.20	2,030	3.30	2,950	4.40	4,115
1.20	1,360	2.30	2,105	3.40	3,045	4.50	4,230
1.30	1,425	2.40	2,180	3.50	3,145		
1.40	1,490	2.50	2,255	3.60	3,245		
1.50	1,555	2.60	2,335	3.70	3,345		

JANUARY 1, 1903, TO DECEMBER 31, 1904.

0.80	1,180	2.30	2,170	3.80	3,450	11.00	11,340
.90	1,240	2.40	2,245	3.90	3,545	12.00	12,540
1.00	1,300	2.50	2,320	4.00	3,640	13.00	13,840
1.10	1,360	2.60	2,400	4.50	4,140	14.00	15,140
1.20	1,420	2.70	2,480	5.00	4,640	15.00	16,540
1.30	1,480	2.80	2,560	5.50	5,140	16.00	17,940
1.40	1,545	2.90	2,645	6.00	5,640	17.00	19,400
1.50	1,610	3.00	2,730	6.50	6,190	18.00	20,960
1.60	1,675	3.10	2,815	7.00	6,740	19.00	22,800
1.70	1,740	3.20	2,900	7.50	7,290	20.00	25,000
1.80	1,810	3.30	2,990	8.00	7,840	21.00	27,800
1.90	1,880	3.40	3,080	8.50	8,390	22.00	31,800
2.00	1,950	3.50	3,170	9.00	8,940	23.00	34,800
2.10	2,020	3.60	3,260	9.50	9,540	24.00	38,300
2.20	2,095	3.70	3,355	10.00	10,140	25.00	41,800

^a Between gage heights 4.50 and 14.0 feet the rating curve is a tangent, the difference being 114 per tenth. Above gage height 14.0 feet the 1904 rating curve has been used to obtain revised estimates for 1901.

^b Between gage heights 4.5 and 14.0 feet the above table is the same as the 1901 table. Above gage height 14.0 feet the 1904 rating curve has been used to obtain revised estimates for 1902.

APALACHICOLA DRAINAGE BASIN, STREAM FLOW 247

Estimated monthly discharge of Chattahoochee River at Oakdale.

[Drainage area, 1,560 square miles.]

Month	Discharge in second-feet			Run-off	
	Maximum	Minimum	Mean	Sec.-ft. per sq. mile	Depth in inches
1895					
October 15-31.....	1,180	970	1,038	0.67	0.43
November.....	1,961	1,130	1,293	.83	.92
December.....	2,911	1,140	1,432	.92	1.06
1896					
January.....	12,000	1,356	2,321	1.81	2.09
February.....	7,400	1,707	2,787	1.77	1.90
March.....	2,120	1,586	1,790	1.15	1.33
April.....	2,740	1,323	1,599	1.02	1.14
May.....	3,088	1,060	1,384	.89	1.02
June.....	2,227	875	1,272	.82	.91
July.....	24,600	821	3,891	2.50	2.89
August.....	1,961	821	1,075	.69	.79
September.....	1,300	745	850	.54	.60
October.....	1,469	775	913	.58	.67
November.....	4,640	1,086	1,608	1.03	1.15
December.....	3,133	1,112	1,454	.98	1.07
The year.....	24,600	745	1,785	1.14	15.56
1897					
January.....	9,065	1,035	2,575	1.65	1.90
February.....	6,365	2,150	3,734	2.39	2.49
March.....	15,950	2,075	5,658	3.63	4.19
April.....	21,890	2,226	5,147	3.30	3.68
May.....	4,475	1,515	2,130	1.37	1.58
June.....	1,891	1,091	1,438	.92	1.02
July.....	15,545	1,177	3,360	2.15	2.48
August.....	2,965	1,007	1,452	.93	1.07
September.....	1,206	725	845	.54	.60
October.....	1,855	675	979	.63	.72
November.....	2,113	876	1,078	.69	.77
December.....	3,013	1,206	1,845	1.18	1.36
The year.....	21,890	675	2,520	1.62	21.86
1898					
January.....	9,150	1,295	2,288	1.47	1.69
February.....	1,920	1,240	1,450	.93	.97
March.....	10,200	1,185	1,984	1.27	1.46
April.....	14,325	1,688	3,425	2.20	2.45
May.....	2,165	1,158	1,566	1.00	1.15
June.....	2,095	920	1,181	.76	.84
July.....	14,020	730	2,806	1.80	2.08
August.....	18,700	1,490	4,774	3.06	3.53
September.....	33,975	1,925	7,434	4.77	5.31
October.....	28,450	1,850	6,096	3.91	4.51
November.....	4,530	2,150	2,889	1.92	2.14
December.....	8,950	2,112	3,179	2.09	2.35
The year.....	33,975	730	3,256	2.09	28.48
1899					
January.....	6,675	2,385	3,712	2.38	2.75
February.....	26,695	3,350	8,511	5.46	5.68
March.....	29,425	4,337	9,178	5.88	6.77
April.....	14,800	3,962	5,931	3.80	4.24
May.....	5,800	2,385	3,280	2.10	2.43
June.....	4,930	1,740	2,310	1.48	1.65
July.....	6,450	1,220	1,948	1.25	1.44
August.....	5,420	870	1,506	.97	1.12
September.....	4,700	910	1,413	.91	1.01
October.....	2,100	870	1,175	.75	.86
November.....	3,000	1,000	1,408	.90	1.00
December.....	7,200	1,160	2,242	1.44	1.66
The year.....	29,425	870	3,551	2.28	30.61

WATER POWERS OF GEORGIA

Estimated monthly discharge of Chattahoochee River at Oakdale—Continued.

Month	Discharge in second-feet			Run-off	
	Maximum	Minimum	Mean	Sec.-ft. per sq. mile	Depth in inches
1900					
January.....	6,300	1,050	2,275	1.46	1.68
February.....	28,650	1,280	5,929	3.80	3.95
March.....	10,800	3,000	5,137	3.29	3.79
April.....	18,000	2,630	5,484	3.52	3.92
May.....	5,160	2,450	3,295	2.11	2.44
June.....	24,600	3,000	8,207	5.26	5.87
July.....	12,600	3,720	5,847	3.75	4.32
August.....	5,160	2,540	3,275	2.10	2.43
September.....	12,900	1,700	3,277	2.10	2.34
October.....	4,360	2,185	3,234	2.07	2.39
November.....	6,000	1,700	2,436	1.56	1.74
December.....	4,140	2,100	2,753	1.76	2.03
The year.....	28,650	1,050	4,262	2.73	36.90
1901 ^a					
January.....	31,300	2,044	5,536	3.55	4.09
February.....	5,028	2,272	3,214	2.06	2.15
March.....	36,550	2,044	5,303	3.40	3.92
April.....	12,780	2,346	5,149	3.80	3.68
May.....	25,000	2,511	4,781	3.06	3.53
June.....	10,500	2,934	4,749	3.04	3.39
July.....	9,474	2,040	3,225	2.07	2.39
August.....	24,500	1,829	7,847	5.03	5.80
September.....	15,980	2,676	4,153	2.66	2.97
October.....	4,344	1,753	2,600	1.67	1.93
November.....	1,898	1,690	1,763	1.13	1.26
December.....	48,800	1,690	5,583	3.53	4.13
The year.....	48,800	1,690	4,492	2.88	39.24
1902 ^a					
January.....	9,588	1,960	2,881	1.85	2.13
February.....	35,500	2,415	5,738	3.71	3.86
March.....	41,800	3,245	8,984	5.76	6.64
April.....	7,194	3,045	4,065	2.61	2.91
May.....	3,450	2,765	3,150	2.02	2.33
June.....	5,484	2,335	3,004	1.93	2.15
July.....	3,245	1,750	2,113	1.35	1.56
August.....	2,415	1,555	1,736	1.14	1.31
September.....	8,106	1,890	2,983	1.88	2.10
October.....	1,960	950	1,470	.94	1.08
November.....	4,572	950	1,481	.95	1.06
December.....	8,904	1,620	3,032	1.94	2.24
The year.....	41,800	950	3,391	2.17	29.37
1903					
January.....	4,540	1,880	2,570	1.65	1.90
February.....	48,900	2,480	9,710	6.22	6.48
March.....	36,200	4,240	11,501	7.37	8.51
November.....	2,730	1,300	1,567	1.00	1.12
December.....	1,740	1,300	1,483	.95	1.10
1904					
January.....	3,640	1,480	1,993	1.23	1.48
February.....	7,510	1,610	2,504	1.61	1.74
March.....	8,060	1,810	2,749	1.76	2.08
April.....	4,640	1,610	1,983	1.27	1.42
May.....	4,140	1,180	1,699	1.09	1.26

^a Estimate revised above gage height 14.0 feet on the basis of the 1904 rating curve.

CHATTAHOOCHEE RIVER AT WEST POINT.

This station was established July 30, 1896, by M. R. Hall, and the gage is now maintained by the United States Weather Bureau. It is located at the Montgomery street wagon bridge.

The channel is straight for about 2,000 feet above and 3,000 feet below the station. The current has a fair velocity, except at low stages. The right bank is high and overflows only at high water, when most of the town is covered. The left bank is somewhat lower and overflows for about 800 feet at a gage height of 20 feet. The bed of the stream is of sand and gravel and is unstable.

The bridge from which discharge measurements are made is in three spans, with short approaches from each end. The floor of the bridge is about 24 feet above low water. The initial point for soundings is the end of the hand rail on the right bank, downstream side of the bridge. A standard chain gage is fastened to the outside of the iron railing of the downstream footway at a point 122 feet from the initial point for soundings; length of chain, 29.26 feet. Bench marks were established as follows: (1) The top of the downstream end of the second iron floor beam under the bridge floor from the right-bank end of the bridge; elevation, 24.19 feet. (2) The top of the thirty-eighth milepost on the Franklin and West Point survey of the United States Engineers. This post is a cast-iron cap 6 inches square, set in concrete, approximately on a level with the ground, and marked "U. S. 38." A raised point in the center of the cap is the bench mark; elevation, 15.68 feet. The location of this post is on the right bank of the river, 340 feet upstream from the wagon bridge and 50 feet from the edge of the river and 60 feet south of the Episcopal Church.

WATER POWERS OF GEORGIA

Discharge measurements of Chattahoochee River at West Point.

Date	Gage height	Dis-charge	Date	Gage height	Dis-charge
October 22.....	1895 Feet 1.76	Sec.-ft. 1,404	January 20.....	1900 Feet 4.65	Sec.-ft. 6,574.
June 29.....	1896 2.45	2,087	February 24.....	4.92	7,158.
July 30.....	2.45	2,430	August 22.....	2.80	2,755.
August 14.....	1.72	1,594	December 4.....	3.93	5,224.
September 5.....	1.20	1,006	March 12.....	1901 4.34	6,007.
September 25.....	1.15	1,030	August 6.....	3.00	3,435.
October 28.....	1.75	1,642	October 28.....	2.80	2,910.
January 23.....	1897 6.66	11,920	January 15.....	1902 3.50	4,364.
April 26.....	3.70	5,448	July 25.....	2.00	1,916.
May 4.....	4.13	6,236	January 6.....	1903 3.95	5,056.
May 19.....	3.00	3,557	April 22.....	5.39	8,713.
June 5.....	2.90	3,253	June 5.....	9.70	20,960.
June 19.....	2.59	2,934	June 6.....	13.30	25,620.
July 8.....	3.03	3,470	July 30.....	3.46	4,761.
July 23.....	5.01	7,853	July 31.....	4.07	5,993.
August 14.....	2.12	1,915	September 23.....	2.40	2,451.
September 4.....	1.80	1,690	September 24.....	2.32	2,416.
September 22.....	1.20	985	September 17.....	2.37	2,460.
November 9.....	1.71	1,345	February 3-4.....	1904 2.80	3,005.
November 23.....	1.60	1,322	April 7.....	2.83	3,144.
December 17.....	3.14	3,939	April 7.....	2.88	3,155.
January 18.....	1898 2.45	2,648	April 14.....	2.90	3,179.
February 18.....	2.43	2,464	April 14.....	2.90	3,180.
March 17.....	3.03	3,571	June 20.....	1.56	1,298.
April 6.....	9.20	19,890	June 20.....	1.56	1,306.
April 21.....	2.90	2,723	September 2.....	1.46	1,203.
April 26.....	4.52	6,704	September 3.....	2.00	1,862.
May 17.....	2.15	1,975	September 29.....	1.20	1,005.
June 11.....	1.40	1,161	September 30.....	1.27	1,010.
June 6.....	2.27	2,451	December 6.....	2.70	2,308.
August 5.....	8.82	18,510	March 24.....	1905 3.23	4,026.
September 2.....	7.55	15,070	June 6.....	2.30	2,048.
September 3.....	11.25	25,200	October 28.....	2.30	2,252.
October 5.....	13.90	37,530	January 24.....	1906 12.91	30,100.
October 29.....	3.33	4,409	January 24.....	11.92	27,100.
November 29.....	4.00	5,394	January 25.....	9.20	18,100.
March 14.....	1899 5.30	8,726	January 26.....	6.14	10,300.
April 24.....	4.72	7,144	February 15.....	3.60	4,390.
May 13.....	3.80	4,823	May 10.....	3.75	4,910.
June 26.....	3.06	3,234	June 9.....	2.78	3,120.
September 12.....	3.10	3,689	November 10.....	3.25	3,720.
October 18.....	2.07	2,033			
December 16.....	3.49	4,111			

APALACHICOLA DRAINAGE BASIN, STREAM FLOW

Daily gage height, in feet, of Chattahoochee River at West Point.

Day	Aug.	Sept.	Oct.	Nov.	Dec.	Day	Aug.	Sept.	Oct.	Nov.	Dec.
1896						1896					
1.....	2.7	1.3	4.1	1.7	4.2	17.....	1.6	0.85	1.1	3.0	3.0
2.....	3.9	1.2	4.0	2.0	4.0	18.....	1.55	.8	1.1	2.6	3.0
3.....	4.5	1.1	3.0	3.25	3.75	19.....	1.5	.8	1.1	2.55	2.9
4.....	6.0	1.05	2.6	3.0	3.6	20.....	1.45	.8	1.1	2.4	2.8
5.....	5.5	1.0	2.4	2.2	3.4	21.....	1.4	.8	1.15	2.25	2.7
6.....	5.0	1.0	2.0	2.6	3.2	22.....	1.4	3.3	1.5	2.25	2.6
7.....	3.65	1.0	1.9	5.5	3.1	23.....	1.3	3.0	1.5	2.2	2.4
8.....	3.2	1.05	1.5	4.3	3.1	24.....	1.2	2.5	1.75	2.2	2.2
9.....	2.75	1.1	1.3	3.45	3.05	25.....	3.0	2.0	1.75	2.9	2.15
10.....	2.6	1.05	1.25	2.3	3.0	26.....	2.0	1.7	1.7	1.9	2.1
11.....	2.2	.95	1.25	2.0	2.9	27.....	1.8	1.6	1.65	1.8	2.1
12.....	2.0	.85	1.2	2.15	2.8	28.....	1.75	1.4	1.6	2.0	2.05
13.....	1.85	.85	1.15	6.3	2.65	29.....	1.6	3.6	1.5	4.0	2.0
14.....	1.7	.9	1.15	5.0	2.5	30.....	1.5	4.2	1.5	4.3	1.95
15.....	1.6	.9	1.15	4.5	3.0	31.....	1.4	1.45	1.9
16.....	1.6	.85	1.15	3.3	3.1						

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1897												
1.....	1.9	3.15	3.65	4.0	3.9	2.65	1.9	2.9	1.8	1.1	1.3	2.5
2.....	1.9	4.4	3.6	4.0	4.0	2.7	1.9	3.0	1.7	1.1	1.3	2.5
3.....	1.9	7.0	3.5	3.95	3.8	2.8	2.0	3.2	1.65	1.05	1.3	2.5
4.....	1.95	7.4	3.5	4.4	3.75	2.85	2.3	2.8	1.65	1.05	1.5	2.4
5.....	2.0	7.1	3.6	3.5	3.65	2.9	3.0	2.8	1.6	1.0	2.3	2.6
6.....	2.0	6.0	4.1	10.2	3.6	2.95	3.5	2.5	1.6	1.0	2.0	2.75
7.....	2.0	6.0	10.95	11.0	3.6	2.8	2.5	2.4	1.5	1.0	1.8	2.85
8.....	1.95	5.2	9.3	10.5	3.6	2.7	3.0	2.2	1.5	.95	1.65	2.6
9.....	1.95	5.0	7.1	8.0	3.55	2.6	3.0	2.0	1.4	.95	1.7	2.6
10.....	1.9	4.7	5.5	7.1	3.5	2.6	2.9	1.9	1.4	.95	1.9	2.5
11.....	1.9	4.9	5.3	6.5	3.5	2.65	2.9	2.9	1.4	1.15	1.9	2.4
12.....	1.95	7.12	6.2	6.8	3.55	2.65	2.8	3.0	1.35	1.5	1.7	2.4
13.....	1.95	6.5	10.7	6.0	3.75	2.6	2.4	2.7	1.35	3.0	1.7	2.5
14.....	2.1	6.1	14.1	5.8	3.6	2.5	2.2	2.3	1.3	2.9	1.6	4.3
15.....	2.2	4.7	12.9	5.7	3.4	2.45	2.0	2.25	1.3	2.5	1.6	3.75
16.....	4.0	4.65	11.0	5.5	3.2	2.4	1.8	2.0	1.3	1.9	1.6	3.5
17.....	4.05	4.6	10.9	5.3	3.1	2.5	1.9	2.95	1.25	1.75	1.5	3.1
18.....	3.35	4.5	10.0	5.0	3.0	2.9	2.9	3.5	1.25	1.65	1.5	3.05
19.....	3.3	4.5	9.0	4.5	3.0	2.7	3.0	4.0	1.2	1.6	1.55	3.1
20.....	5.4	4.35	8.5	4.2	2.9	2.6	9.0	4.5	1.2	1.4	1.4	3.9
21.....	8.2	4.35	8.3	4.2	2.85	2.55	11.4	6.2	1.2	1.5	1.3	4.0
22.....	7.3	4.45	8.1	4.1	2.8	2.55	8.0	8.1	1.2	1.6	1.2	3.3
23.....	6.5	4.3	8.0	4.0	2.75	2.5	5.4	7.0	1.2	1.4	1.1	3.7
24.....	4.8	5.6	8.5	3.8	2.7	2.5	4.4	6.1	1.2	1.4	1.05	3.7
25.....	3.7	5.5	7.6	3.85	2.7	2.5	4.2	3.5	1.15	1.3	1.05	3.65
26.....	3.5	4.0	5.0	3.7	2.7	2.6	4.1	2.8	1.15	1.3	1.1	3.6
27.....	3.2	3.9	4.95	3.65	2.7	2.3	4.0	2.4	1.15	1.2	1.9	3.5
28.....	3.0	3.8	4.7	3.6	2.65	2.15	3.6	2.1	1.1	1.2	2.65	3.2
29.....	3.0	4.5	3.6	2.65	2.0	3.5	2.1	1.1	1.4	2.6	2.8
30.....	2.95	4.3	3.8	2.65	1.9	3.0	1.9	1.1	1.4	2.5	2.6
31.....	3.2	4.0	2.65	2.8	1.9	1.3	2.5
1898												
1.....	2.4	3.05	2.3	6.3	3.2	1.7	1.25	3.4	3.75	1.8	3.38	3.65
2.....	2.35	2.9	2.3	5.1	3.15	1.65	1.15	2.9	3.9	1.85	3.35	3.6
3.....	2.2	2.8	2.3	3.4	3.15	1.65	1.1	3.0	12.0	2.9	3.35	5.25
4.....	2.2	2.6	2.3	3.2	3.0	1.65	1.1	6.0	14.5	5.6	3.3	5.0
5.....	2.2	2.2	3.1	7.0	2.8	1.5	1.05	7.6	15.3	11.0	3.3	4.0
6.....	2.15	2.2	3.15	9.2	2.6	1.5	2.2	9.15	18.2	14.5	3.45	4.0
7.....	2.15	2.2	3.0	9.5	2.4	1.45	2.35	8.2	17.5	12.0	3.5	4.0
8.....	2.15	2.1	2.9	8.2	2.3	1.45	2.7	6.3	9.0	13.0	3.55	3.3
9.....	2.15	2.1	2.5	6.0	2.3	1.4	3.5	5.1	6.2	10.0	3.6	3.75
10.....	2.1	2.1	2.2	5.4	2.3	1.4	4.0	4.3	4.5	7.5	3.75	3.7
11.....	2.15	2.1	2.1	5.0	2.2	1.4	3.3	8.0	4.0	4.1	3.75	3.6
12.....	3.0	2.1	2.1	3.5	2.2	1.4	3.0	8.4	3.75	3.9	3.75	3.6
13.....	2.75	2.05	2.1	2.95	2.2	1.6	2.8	6.75	3.6	3.2	3.85	3.6
14.....	2.6	2.05	2.1	2.8	2.2	1.65	2.7	5.2	3.4	3.2	3.8	3.4
15.....	2.6	2.0	3.3	2.6	2.15	1.9	3.0	4.6	3.4	3.15	3.9	3.35

Daily gage height, in feet, of Chattahoochee River at West Point—Continued.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1898												
16.....	2.75	2.0	3.2	2.4	2.15	2.0	3.3	4.0	3.4	3.0	5.6	3.35
17.....	2.9	2.0	3.0	2.4	2.15	1.8	4.0	4.1	3.2	3.0	5.75	3.35
18.....	2.95	2.1	2.8	2.35	2.15	1.8	3.6	5.0	3.0	5.0	5.0	3.3
19.....	2.75	2.6	2.6	2.85	2.1	1.7	3.0	4.2	2.4	5.5	5.0	3.3
20.....	2.7	2.6	2.4	3.0	2.1	1.55	2.7	3.3	2.0	5.4	4.9	3.25
21.....	2.8	2.5	2.15	2.75	2.1	1.5	2.2	3.5	1.9	4.9	4.8	3.25
22.....	3.2	2.5	2.15	2.6	2.1	1.75	2.3	3.4	1.9	4.8	4.3	4.0
23.....	2.8	2.5	2.15	4.0	2.0	2.0	2.4	3.3	1.9	4.5	4.0	5.65
24.....	2.9	2.5	2.15	7.0	1.9	2.1	4.0	3.25	2.9	4.5	3.7	5.0
25.....	2.9	2.45	2.1	5.3	1.85	2.0	7.6	3.2	3.0	4.0	3.7	4.5
26.....	3.0	2.4	2.1	4.0	2.5	2.1	5.5	3.2	2.75	3.6	3.7	4.4
27.....	6.0	2.3	2.1	3.6	2.0	2.2	4.1	5.6	2.5	3.4	3.65	4.2
28.....	5.5	2.3	2.1	3.4	1.8	1.75	4.0	10.6	2.05	3.4	3.6	4.0
29.....	4.05	3.2	3.4	1.7	1.5	5.6	5.4	1.9	3.4	3.3	3.8
30.....	3.6	4.1	3.2	1.7	1.4	6.0	3.3	1.8	3.38	3.7	3.8
31.....	3.1	4.3	1.7	4.2	3.5	3.38	3.75
1899												
1.....	4.3	4.5	14.5	10.0	4.3	3.6	3.0	2.5	2.4	1.1	2.1	4.4
2.....	4.35	4.65	12.7	7.7	4.2	3.3	2.3	2.3	2.0	1.3	2.1	4.3
3.....	4.2	10.2	6.5	7.0	4.1	3.2	2.7	2.3	2.9	1.3	1.9	3.4
4.....	4.1	8.3	5.8	7.15	3.9	3.1	2.5	2.3	2.4	1.1	1.9	3.4
5.....	4.0	7.2	6.4	6.7	3.8	3.0	2.4	2.7	2.1	1.4	1.9	3.4
6.....	4.0	5.8	7.0	6.4	3.75	3.0	2.4	2.3	3.0	1.5	1.9	3.2
7.....	5.5	9.1	6.1	6.9	3.75	2.9	2.4	2.3	2.9	1.3	1.9	3.1
8.....	5.75	13.3	5.6	7.3	3.7	2.8	2.8	2.7	2.0	2.4	1.9	3.1
9.....	5.5	13.0	5.2	6.3	3.8	2.8	2.9	2.4	1.9	2.7	1.9	2.9
10.....	5.6	9.05	5.0	6.3	4.0	3.0	3.0	2.3	2.9	2.6	1.9	2.6
11.....	7.0	6.3	4.9	6.0	3.8	3.1	3.2	2.1	2.5	2.3	1.9	2.4
12.....	8.8	5.9	4.85	5.4	3.7	3.2	2.5	2.2	2.1	2.3	1.9	3.5
13.....	5.9	5.2	4.9	5.15	3.65	3.3	2.3	2.3	2.4	2.1	1.9	4.0
14.....	5.4	4.75	5.0	5.1	3.65	4.0	2.3	2.4	2.6	1.9	1.9	4.6
15.....	6.0	5.0	5.1	5.05	3.65	4.1	2.3	2.0	2.3	2.4	2.1	4.1
16.....	5.2	5.2	10.5	5.0	3.6	3.6	2.1	2.5	2.4	2.5	2.2	3.6
17.....	5.0	5.1	12.3	4.95	3.6	3.1	2.3	3.0	1.6	2.3	2.2	3.1
18.....	4.9	4.6	13.5	4.9	3.5	3.0	2.3	3.2	1.6	2.3	2.1	3.0
19.....	4.75	4.3	12.1	4.8	3.2	2.9	2.5	2.9	1.6	2.6	2.1	2.8
20.....	4.5	4.0	10.75	4.6	3.1	2.3	2.7	2.4	1.5	2.9	2.1	2.8
21.....	4.2	3.75	8.2	4.45	3.1	2.8	3.0	2.6	1.7	3.3	2.1	2.8
22.....	4.1	3.6	7.5	4.6	3.05	2.6	3.6	2.9	1.9	2.4	1.9	2.8
23.....	4.05	3.6	6.9	4.65	3.05	2.5	4.2	3.0	2.3	2.4	2.0	3.2
24.....	3.9	3.5	7.2	4.7	4.8	2.7	4.7	3.2	1.1	2.3	2.2	6.0
25.....	3.6	3.5	7.0	4.8	4.1	2.9	3.6	3.5	1.2	2.5	3.0	5.7
26.....	3.6	3.5	6.5	5.6	3.8	3.4	3.0	2.0	1.2	2.1	3.1	5.6
27.....	3.5	10.7	6.2	6.05	3.6	3.5	3.2	2.5	1.2	2.0	3.4	4.1
28.....	3.65	15.2	6.15	5.1	3.4	3.2	5.9	3.1	1.3	2.1	3.2	3.6
29.....	3.75	6.8	5.0	3.3	3.0	3.3	3.6	1.8	2.1	3.5	3.4
30.....	4.0	6.3	4.7	3.25	3.2	2.9	2.9	1.9	2.2	4.2	3.3
31.....	4.75	7.15	4.0	2.7	2.1	2.1	3.2
1900												
1.....	3.0	2.8	5.9	4.1	4.9	3.4	6.3	6.4	4.1	2.6	2.8	3.7
2.....	2.3	2.6	4.7	4.1	4.3	3.3	9.4	5.7	6.1	2.5	2.7	3.2
3.....	2.5	2.4	4.6	4.05	4.6	3.3	7.8	5.0	4.5	2.5	4.6	3.1
4.....	2.5	3.0	5.0	4.05	4.4	3.6	7.0	4.5	3.2	2.6	4.2	3.9
5.....	2.4	3.0	4.3	4.0	4.3	5.0	6.5	4.0	3.0	3.3	4.3	4.5
6.....	2.8	4.6	4.5	3.95	4.2	4.8	6.2	3.6	2.9	4.0	3.6	5.8
7.....	2.9	4.5	4.2	3.9	4.0	4.3	5.4	3.4	2.8	4.2	3.4	5.9
8.....	2.8	4.2	5.0	3.9	3.8	5.1	5.0	3.2	2.7	3.7	3.2	4.6
9.....	2.8	4.6	4.1	3.85	3.6	3.1	5.1	3.1	2.6	3.5	3.1	3.9
10.....	2.7	7.3	7.5	3.8	3.6	8.5	4.2	3.0	2.5	3.4	3.0	3.6
11.....	3.4	8.6	6.3	4.9	3.5	5.8	4.0	2.9	2.4	3.4	3.0	3.3
12.....	4.7	12.2	5.6	6.1	3.4	4.6	3.6	2.3	2.3	3.6	2.9	3.2
13.....	4.4	19.12	4.7	6.7	3.4	6.5	5.4	3.4	2.3	3.8	2.9	3.1
14.....	4.7	19.5	4.5	6.0	3.4	3.9	5.0	3.3	2.3	3.7	2.8	4.9
15.....	4.9	18.5	4.3	5.5	3.3	4.2	4.8	3.0	9.2	3.2	2.8	4.2

APALACHICOLA DRAINAGE BASIN, STREAM FLOW

Daily gage height, in feet, of Chattahoochee River at West Point—Continued.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1900												
16.....	4.6	12.4	4.5	4.2	3.3	6.4	4.5	3.0	12.6	3.0	2.7	3.7
17.....	3.7	5.9	4.3	4.0	3.2	6.0	4.3	2.9	3.3	3.0	2.7	3.5
18.....	3.4	5.5	4.1	6.0	3.2	7.0	4.1	2.9	3.0	2.9	2.7	3.3
19.....	3.9	4.7	5.0	7.7	3.7	8.4	4.0	2.8	5.7	2.9	2.7	3.0
20.....	4.6	4.5	5.2	8.5	3.6	6.0	3.8	2.8	4.3	2.8	2.7	5.8
21.....	4.3	4.6	5.2	7.4	3.5	4.5	3.6	2.8	3.2	2.8	2.6	6.5
22.....	5.1	4.6	6.3	7.0	3.4	3.8	3.5	2.8	3.0	3.0	2.8	6.4
23.....	4.2	4.7	6.2	7.5	3.4	4.6	3.8	2.9	2.9	4.6	2.9	6.0
24.....	3.3	4.8	5.8	7.0	5.0	16.4	3.7	3.5	2.8	5.0	3.0	5.3
25.....	3.7	4.8	6.1	9.2	4.4	17.8	3.6	3.8	2.8	4.9	3.2	4.8
26.....	3.3	5.0	6.5	8.0	4.2	14.6	3.6	3.4	2.7	3.4	3.8	4.2
27.....	3.2	4.6	5.8	6.0	4.0	12.2	4.0	3.2	2.7	3.2	4.5	4.1
28.....	3.0	4.9	5.4	4.8	3.6	8.4	6.1	3.0	2.7	3.0	4.0	3.9
29.....	3.0	5.3	4.5	3.5	5.6	6.7	2.9	2.6	2.9	5.0	3.6
30.....	2.9	5.1	5.2	3.4	6.7	12.6	3.3	2.6	2.8	4.6	3.8
31.....	2.9	4.5	3.4	9.2	3.9	2.8	7.2
1901												
1.....	7.3	4.7	4.7	7.3	4.0	6.7	3.9	3.6	5.3	3.4	2.6	2.5
2.....	7.2	4.6	4.6	6.7	4.0	6.0	4.5	3.0	5.6	6.3	2.6	2.4
3.....	7.0	4.6	4.4	6.2	4.0	7.1	5.0	2.9	4.6	5.1	2.6	2.9
4.....	6.1	12.6	4.2	10.3	4.0	6.9	4.9	2.8	3.9	4.4	2.5	3.2
5.....	5.3	13.8	4.0	8.6	4.0	5.3	4.2	2.9	3.8	3.6	2.9	3.1
6.....	4.7	10.2	3.9	6.4	3.9	5.5	3.7	3.0	3.3	3.3	2.8	3.1
7.....	4.0	6.4	3.7	6.2	3.9	6.4	3.5	4.8	3.6	3.1	2.7	3.0
8.....	3.9	6.3	3.5	6.0	3.9	5.9	3.3	6.4	3.5	3.0	2.6	3.0
9.....	3.9	7.0	3.5	5.1	3.9	4.7	3.2	6.0	3.4	2.9	2.6	2.9
10.....	3.8	6.5	3.4	4.6	3.8	4.2	3.1	4.0	3.3	2.9	2.6	3.5
11.....	5.0	6.2	4.1	4.0	3.8	4.0	3.0	3.9	3.1	2.9	2.6	3.3
12.....	13.3	6.0	4.2	3.8	3.8	3.8	3.0	5.3	3.1	2.9	2.5	3.2
13.....	15.0	5.4	4.5	5.2	3.8	4.0	3.0	4.2	4.7	3.0	2.5	3.0
14.....	14.7	4.8	4.0	10.4	3.7	4.9	2.9	4.0	4.0	3.1	2.5	3.2
15.....	12.4	4.5	3.9	8.5	3.9	4.7	2.8	3.8	3.9	3.8	2.5	6.4
16.....	6.1	4.4	3.7	6.9	3.8	7.9	3.4	6.8	3.4	3.5	2.5	7.1
17.....	5.0	4.3	3.7	6.0	3.8	7.6	6.6	10.4	5.0	3.2	2.5	7.6
18.....	6.0	4.2	3.6	5.2	4.0	7.4	3.4	7.6	10.4	3.2	2.4	6.3
19.....	5.3	4.2	3.4	6.4	4.2	6.2	3.1	10.1	12.7	3.2	2.5	4.4
20.....	4.8	4.0	3.4	7.6	4.5	4.5	6.4	7.8	7.8	3.1	3.0	3.6
21.....	4.6	3.9	3.6	7.0	3.4	4.2	4.2	6.5	4.3	3.0	3.4	3.3
22.....	4.4	3.9	3.8	6.2	15.7	4.0	3.9	8.2	4.1	2.8	3.5	3.3
23.....	4.3	3.8	4.0	5.5	17.2	3.9	3.7	14.1	3.3	2.8	3.1	3.2
24.....	4.2	3.8	4.3	5.0	12.3	3.8	3.2	17.1	3.6	2.8	2.9	3.1
25.....	4.1	4.6	4.0	4.8	10.5	3.7	3.0	13.6	3.4	2.3	2.8	3.9
26.....	4.0	4.2	3.9	4.6	6.2	3.7	2.9	8.2	3.4	2.7	2.7	4.6
27.....	3.9	4.0	9.6	4.4	5.5	4.7	2.8	7.1	3.3	2.7	2.6	5.4
28.....	4.0	3.9	12.1	4.2	5.0	4.2	2.8	6.0	3.3	2.7	2.6	6.8
29.....	4.9	13.0	4.1	4.3	4.0	3.9	5.3	3.3	2.7	2.5	19.0
30.....	4.8	5.9	4.1	5.6	3.8	4.1	5.3	3.5	2.7	2.5	25.0
31.....	4.7	7.3	7.0	4.0	5.5	2.7	20.0
1902												
1.....	19.0	7.7	20.0	14.0	4.0	4.6	2.0	3.1	2.8	3.8	2.0	3.6
2.....	17.6	15.5	17.3	8.3	4.0	3.5	2.0	2.3	2.2	3.2	2.0	3.7
3.....	3.3	17.1	17.6	6.1	4.7	3.3	1.9	2.1	2.1	2.9	2.0	7.0
4.....	7.5	14.9	15.9	5.5	4.4	3.1	2.7	2.0	2.2	2.4	2.0	6.7
5.....	5.1	9.2	8.4	5.3	4.0	2.9	2.5	2.2	3.0	3.0	2.0	7.4
6.....	4.7	7.5	6.7	5.4	3.9	2.9	2.8	2.4	2.8	3.0	5.7	5.5
7.....	4.2	5.4	5.9	5.5	3.8	2.8	2.6	3.1	2.4	2.6	4.3	4.4
8.....	4.1	5.2	5.6	6.2	3.7	2.8	2.4	2.4	2.0	2.6	3.3	3.3
9.....	4.0	4.7	5.4	5.1	3.8	2.7	2.3	2.1	2.3	2.5	3.3	3.4
10.....	3.9	4.3	5.2	4.9	4.0	2.7	2.2	1.8	2.6	2.2	2.7	3.2
11.....	3.8	4.0	5.0	4.7	3.9	2.7	3.2	2.0	2.2	2.2	2.5	3.0
12.....	3.7	4.0	4.9	4.7	3.8	2.6	3.0	1.8	2.2	2.6	2.4	3.0
13.....	3.6	4.0	6.3	4.6	3.8	2.6	3.6	2.1	2.3	2.5	2.3	3.0
14.....	3.4	3.9	5.9	4.5	3.7	2.6	3.4	2.3	2.3	2.7	2.3	3.0
15.....	3.4	4.6	6.1	4.5	3.6	2.6	3.2	2.0	2.5	2.8	2.2	2.9

WATER POWERS OF GEORGIA

Daily gage height, in feet, of Chattahoochee River at West Point—Continued.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1902												
16	3.3	5.3	8.7	4.5	4.4	2.5	3.1	1.7	2.5	2.4	2.2	7.0
17	3.3	4.9	16.2	4.5	4.2	2.5	3.0	2.0	2.3	2.4	2.2	10.1
18	3.2	4.3	11.4	5.5	3.9	2.9	3.9	2.1	2.0	2.4	2.4	7.6
19	3.5	4.4	8.8	4.9	3.8	2.7	3.6	1.9	1.9	2.2	2.7	6.1
20	3.9	4.9	7.0	4.7	3.7	2.8	3.3	1.6	1.9	2.1	2.7	4.5
21	5.4	4.5	5.5	4.5	3.6	2.9	3.3	1.6	2.0	2.0	2.7	3.9
22	5.0	4.2	5.3	4.3	3.5	2.8	3.4	1.6	1.9	2.0	2.5	4.5
23	4.3	4.1	4.9	3.9	3.5	2.7	3.3	1.8	2.1	2.0	2.3	4.4
24	3.8	4.0	5.1	3.9	3.4	2.5	3.2	1.5	1.9	2.0	2.3	5.0
25	3.7	4.6	6.0	3.9	3.3	2.4	2.0	1.4	3.0	2.9	2.3	4.1
26	3.7	4.7	6.2	3.8	3.3	2.3	1.9	1.2	3.3	1.9	5.7	3.7
27	3.6	4.9	6.4	3.8	3.3	2.3	1.9	1.3	5.3	3.4	4.9	3.4
28	4.5	18.0	11.4	3.9	3.2	2.2	1.8	1.5	5.0	3.2	4.5	3.3
29	4.1	14.9	3.9	3.1	2.2	2.0	3.0	4.5	2.7	3.5	3.2
30	4.4	14.9	4.0	3.0	2.1	2.2	4.1	3.8	2.2	3.0	3.7
31	4.9	14.6	2.9	2.4	3.0	2.1	4.1
1903												
1	4.1	3.7	11.6	12.2	4.4	5.7	4.0	3.8	2.2	2.1	2.0	2.2
2	3.4	11.2	10.2	4.4	6.7	3.7	3.0	2.2	2.1	2.1	2.2
3	4.1	3.3	11.3	7.0	4.4	6.1	3.5	3.7	2.2	2.0	2.2	2.2
4	4.1	3.6	7.4	6.4	4.4	8.8	3.6	3.8	2.1	2.0	2.5	2.2
5	4.1	6.4	7.0	6.1	4.4	9.3	4.1	4.6	2.1	2.0	3.5	2.2
6	4.0	6.9	6.4	5.7	4.3	10.8	3.3	4.5	2.1	2.0	2.8	2.3
7	3.8	6.2	6.1	5.5	5.4	11.9	4.0	4.0	2.3	2.0	2.6	2.3
8	3.6	18.5	5.7	5.4	5.2	11.4	4.0	3.3	2.1	2.0	2.3	2.3
9	3.4	20.1	5.3	9.2	4.8	6.7	4.3	2.9	2.1	2.5	2.5	2.4
10	3.3	13.9	6.1	8.0	4.5	6.1	4.0	2.8	2.0	2.2	2.3	2.5
11	3.3	12.0	7.6	6.8	4.3	5.1	3.7	2.8	2.0	2.1	2.3	2.5
12	4.1	14.9	9.2	5.7	4.2	6.1	3.7	2.7	2.2	2.1	2.3	2.4
13	4.2	12.8	10.2	6.2	6.6	5.1	3.6	2.9	2.0	2.0	2.5	2.4
14	5.2	10.1	8.7	6.9	5.9	4.6	6.4	3.0	2.0	2.0	2.5	2.4
15	4.2	6.4	6.3	8.2	12.7	4.2	6.1	2.8	3.5	2.0	2.4	2.4
16	3.8	5.5	5.9	10.1	9.0	4.0	4.5	4.0	4.7	2.0	2.4	2.4
17	3.6	14.5	5.6	6.3	6.1	3.9	3.7	4.3	5.3	2.5	2.3	2.4
18	3.5	15.9	5.3	5.6	4.8	3.8	3.4	4.7	4.5	2.5	2.7	2.3
19	3.3	14.6	5.0	5.3	4.4	3.7	3.2	5.7	3.4	2.4	2.9	2.3
20	3.2	14.2	4.9	7.2	4.2	3.6	3.1	5.1	3.0	2.3	2.7	2.3
21	3.2	6.3	5.7	7.2	4.1	3.6	3.0	3.8	2.6	2.3	2.6	2.6
22	3.2	5.5	8.2	5.7	4.0	3.8	2.9	3.1	2.5	2.2	2.5	2.6
23	3.1	5.1	13.1	5.1	3.9	3.6	2.9	2.9	2.4	2.1	2.4	2.6
24	3.1	4.9	14.7	4.9	3.8	3.6	2.9	2.7	2.4	2.0	2.3	2.6
25	3.2	4.6	14.6	4.7	3.7	3.5	3.1	2.6	2.3	2.0	2.3	2.5
26	3.2	4.5	15.2	5.1	3.6	4.0	3.0	2.5	2.3	2.0	2.3	3.0
27	3.2	4.4	14.3	5.0	3.6	4.5	2.8	2.4	2.2	2.0	2.3	3.0
28	3.5	3.3	6.4	4.9	3.6	5.0	2.7	2.3	2.1	2.0	2.3	2.8
29	3.7	7.0	4.6	3.6	5.2	2.7	2.3	2.1	2.0	2.2	2.7
30	3.5	12.0	4.5	3.6	4.7	3.0	2.3	2.1	2.0	2.2	2.5
31	3.9	13.5	5.5	4.0	2.3	2.0	2.4
1904												
1	2.4	2.9	3.3	2.9	2.5	3.0	2.5	2.6	2.3	1.2	1.2	1.7
2	2.3	2.9	3.2	2.9	2.5	3.6	2.3	2.7	1.4	1.2	.9	1.8
3	2.4	2.9	3.7	2.9	2.4	2.7	2.1	2.5	2.0	1.2	1.1	1.9
4	2.4	2.8	3.5	2.8	2.4	2.4	2.1	3.3	1.9	1.2	1.5	2.0
5	2.4	2.8	3.3	2.7	2.4	2.2	1.7	2.5	1.8	1.1	1.7	2.0
6	2.3	2.8	3.1	2.7	2.4	2.1	1.9	3.1	2.5	1.1	1.6	2.6
7	2.3	3.1	4.7	2.8	2.4	1.5	1.6	5.3	2.4	1.2	1.6	3.0
8	2.4	4.8	6.0	3.2	2.4	1.4	1.3	11.4	2.2	1.2	1.5	3.2
9	2.4	5.0	6.0	3.6	2.4	2.0	2.4	12.6	2.1	1.1	1.6	3.1
10	2.7	4.4	5.4	3.5	3.1	2.3	2.1	12.4	1.9	1.1	1.5	2.5
11	3.0	5.4	4.2	3.5	3.4	2.1	1.8	9.6	1.7	1.1	1.5	2.2
12	2.8	5.1	3.7	3.4	3.1	2.0	1.6	6.2	1.6	1.1	1.5	2.1
13	2.7	4.1	3.6	3.1	2.6	1.8	1.8	4.8	1.6	1.2	1.6	1.9
14	2.7	3.7	3.6	2.9	2.4	1.6	1.8	4.2	1.6	1.1	1.7	2.0
15	2.7	3.4	4.0	2.8	2.3	1.6	1.9	5.0	1.5	1.0	1.8	1.8

APALACHICOLA DRAINAGE BASIN, STREAM FLOW 255

Daily gage height, in feet, of Chattahoochee River at West Point—Continued.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1904												
16	2.6	3.3	4.2	2.7	2.3	1.6	1.4	4.0	1.5	1.0	1.7	1.8
17	3.5	3.2	3.7	2.7	2.3	1.6	1.4	3.9	1.4	1.0	1.6	1.8
18	3.6	3.0	3.4	2.7	2.3	1.5	1.7	3.4	1.4	1.1	1.6	1.8
19	3.3	3.1	3.2	2.7	2.2	1.5	1.4	3.0	1.4	1.0	1.6	1.8
20	3.1	3.7	3.1	2.7	2.1	1.5	2.0	2.9	1.3	1.1	1.6	1.8
21	2.8	4.0	3.0	2.7	2.0	1.5	1.7	2.3	1.3	1.2	1.6	1.7
22	3.3	5.4	3.0	2.7	2.0	1.4	2.0	2.4	1.4	.9	1.6	1.7
23	5.5	6.4	3.3	2.7	2.0	1.3	2.1	2.2	1.8	.9	1.8	1.7
24	5.1	6.1	3.3	2.6	1.9	1.7	2.3	2.2	1.9	.9	1.8	1.7
25	4.2	5.3	2.8	2.6	1.9	1.8	2.0	4.3	1.5	.9	1.8	1.9
26	3.8	4.3	3.8	2.6	1.9	1.4	1.9	5.1	1.4	.9	1.8	2.1
27	3.3	3.9	3.6	2.6	1.8	1.3	1.4	4.1	1.3	1.1	1.7	2.1
28	3.0	3.6	3.3	2.6	1.8	1.2	1.9	5.8	1.3	1.2	1.7	3.5
29	3.0	3.4	3.2	2.6	1.8	1.4	1.7	3.9	1.3	1.1	1.7	3.6
30	2.9		3.1	2.6	1.8	2.0	2.1	3.0	1.3	1.0	1.6	3.7
31	2.9		3.0		2.7		2.2	2.4		1.1		3.6
1905												
1	2.9	2.6	3.6	2.7	3.3	2.3	2.8	2.2	1.9	α 1.9	α 1.88	α 2.15
2	2.6	2.5	3.5	2.7	2.5	2.5	4.4	2.0	1.8	3.6	1.85	1.98
3	2.3	2.4	3.4	2.7	2.7	2.4	7.8	1.3	2.2	2.7	1.85	10.6
4	2.3	2.4	3.3	2.5	3.0	2.3	4.9	2.0	2.5	2.1	1.85	13.6
5	2.3	2.7	3.2	2.8	2.9	2.3	3.2	1.9	2.9	1.8	1.9	10.2
6	2.2	3.0	3.2	2.9	2.9	2.1	2.9	1.6	2.2	1.7	1.85	6.2
7	2.6	3.2	3.1	2.9	3.1	2.1	3.9	1.5	2.0	1.6	1.76	4.2
8	2.8	4.0	3.1	2.9	2.9	2.1	4.9	1.5	1.8	1.7	1.95	5.3
9	2.6	3.5	3.1	2.9	4.3	2.1	7.8	2.6	1.7	1.5	1.88	9.8
10	3.0	3.3	3.6	3.3	4.0	2.0	4.8	2.7	1.7	1.8	2.0	8.8
11	2.7	7.3	3.3	3.2	3.9	1.9	4.2	3.0	1.6	2.35	2.8	8.9
12	3.4	7.0	3.1	3.2	3.3	1.7	5.8	4.1	1.6	2.7	3.0	6.4
13	12.6	9.2	3.6	3.1	3.0	1.6	8.7	5.2	1.8	2.35	2.5	4.6
14	10.6	8.9	3.6	2.9	2.7	1.6	8.2	5.5	1.7	2.9	2.1	4.0
15	10.2	8.5	3.3	2.8	2.5	1.9	5.4	4.6	1.7	2.5	2.1	3.9
16	5.5	6.1	3.2	3.0	2.4	2.2	3.9	6.2	1.6	2.1	2.1	3.9
17	4.0	4.8	3.1	3.0	2.8	2.5	3.7	4.7	1.5	2.0	2.0	3.8
18	3.6	4.3	3.1	2.5	3.0	2.2	3.2	4.4	1.6	1.8	2.0	3.7
19	3.4	3.9	3.0	2.6	3.7	2.9	2.8	3.5	1.5	1.8	2.0	3.5
20	3.3	3.8	3.0	2.6	3.0	2.4	2.5	2.8	1.6	1.9	2.05	5.4
21	3.2	4.5	3.5	2.6	2.9	2.4	2.7	2.6	1.4	1.7	1.98	9.4
22	3.1	6.9	3.6	2.7	2.8	2.3	2.0	2.2	1.3	1.7	2.0	8.7
23	3.0	9.3	3.3	2.8	2.9	2.5	2.5	2.8	1.3	1.65	1.95	7.1
24	2.7	6.0	3.4	2.8	4.1	2.5	2.3	3.4	1.3	1.72	1.95	6.0
25	2.7	4.9	3.1	2.4	4.0	2.6	2.3	4.0	1.5	1.85	1.95	4.9
26	2.6	4.4	3.0	2.6	5.0	2.9	2.7	3.7	1.4	2.8	1.98	4.4
27	2.3	4.0	3.0	2.6	4.1	2.2	2.5	3.0	1.3	2.7	2.0	4.0
28	2.3	3.8	2.8	2.0	3.5	2.2	2.0	2.6	1.3	2.25	2.1	3.8
29	2.4		2.8	2.0	3.2	2.4	1.4	2.0	1.3	2.1	2.1	3.8
30	2.5		2.8	2.6	3.1	3.1	2.6	2.1	1.5	2.0	2.1	3.6
31	2.5		2.7		2.9		2.3	2.0		1.98		3.6
1906												
1	3.7	4.6	3.1	6.4	3.6	3.0	2.5	6.4	7.2	6.3	3.5	3.3
2	3.6	4.4	3.1	6.4	3.5	2.8	3.0	5.1	8.2	6.2	3.45	3.25
3	5.3	4.2	3.5	5.4	3.4	2.7	2.5	4.9	5.9	7.0	3.4	3.25
4	13.1	4.0	4.2	5.0	3.7	2.3	4.0	5.2	4.9	8.5	3.4	3.25
5	12.9	4.0	3.3	4.7	4.1	3.3	3.2	6.0	4.1	9.4	3.35	3.2
6	12.2	3.9	4.1	4.6	4.1	3.2	2.8	6.8	11.2	7.6	3.35	3.25
7	12.6	4.0	3.8	4.4	4.3	2.9	2.6	4.9	9.4	5.6	3.4	3.35
8	5.7	4.0	5.6	4.3	5.5	2.8	3.1	4.1	6.1	5.3	3.3	3.3
9	4.9	3.9	3.1	4.2	4.9	2.3	6.0	4.0	4.3	5.0	3.3	3.25
10	4.6	3.9	6.4	4.5	4.1	2.6	4.3	3.9	4.7	4.4	3.3	3.3
11	4.4	3.7	5.2	4.7	3.7	2.6	4.4	3.6	4.5	4.2	3.25	4.0
12	4.3	3.7	4.5	4.4	3.5	2.6	3.9	4.3	5.7	4.0	3.25	4.4
13	4.4	3.6	4.1	4.3	3.4	4.6	3.5	3.7	4.6	3.9	3.3	5.0
14	4.4	3.6	3.9	4.0	3.3	3.5	3.8	6.2	4.2	3.8	3.3	4.1
15	4.4	3.6	7.6	4.1	3.2	3.6	7.0	3.2	3.3	3.7	3.6	3.7

α From October 1 to December 31 two readings a day were made; before that only one reading.

WATER POWERS OF GEORGIA

Daily gage height, in feet, of Chattahoochee River at West Point—Continued.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1906												
16.....	4.2	3.6	11.6	4.1	3.2	6.8	6.8	5.6	3.5	3.7	3.55	3.5
17.....	4.1	3.5	11.7	4.0	3.1	5.2	7.6	6.1	3.4	3.6	3.6	3.75
18.....	4.1	3.4	11.0	4.1	3.0	4.6	6.5	5.2	3.3	10.6	4.5	3.8
19.....	4.2	3.4	11.0	3.9	3.0	3.8	8.5	5.9	3.3	12.3	5.0	5.0
20.....	4.1	3.4	18.9	3.8	2.95	3.6	8.6	7.5	4.0	7.8	5.1	5.6
21.....	4.0	3.4	17.6	3.8	2.9	3.4	6.4	6.8	7.4	6.2	5.5	5.1
22.....	5.4	3.4	15.1	3.8	2.5	3.15	5.1	6.4	6.5	4.7	4.6	4.7
23.....	11.6	3.4	9.2	3.8	3.0	3.0	5.7	5.0	5.9	4.3	4.1	4.3
24.....	13.4	3.3	6.0	3.5	2.8	2.8	3.0	4.3	5.3	4.0	3.6	4.1
25.....	9.8	3.4	5.2	3.6	2.8	2.7	5.5	4.5	5.3	3.95	3.65	3.8
26.....	6.6	3.4	4.9	3.7	2.8	2.6	5.6	4.0	5.4	3.85	3.5	3.6
27.....	5.7	3.2	4.8	3.5	3.3	3.1	5.4	3.6	4.3	3.75	3.45	3.6
28.....	5.4	3.2	7.2	3.1	3.4	3.1	3.9	4.2	4.5	3.55	3.4	3.65
29.....	5.4	7.6	3.5	3.9	3.0	4.0	4.0	4.5	3.55	3.35	4.0
30.....	5.3	6.5	3.8	3.4	2.8	4.3	5.4	5.0	3.55	3.3	4.4
31.....	4.9	6.6	3.1	5.0	6.0	3.5	7.0

Rating tables for Chattahoochee River at West Point.

AUGUST 1, 1896, TO DECEMBER 31, 1903.^a

Gage height	Dis-charge						
Feet	Sec.-ft.	Feet	Sec.-ft.	Feet	Sec.-ft.	Feet	Sec.-ft.
0.80	780	2.90	3,170	5.00	8,040	9.50	20,750
.90	820	3.00	3,340	5.20	8,592	10.00	22,200
1.00	870	3.10	3,520	5.40	9,144	10.50	23,650
1.10	930	3.20	3,700	5.60	9,696	11.00	25,100
1.20	1,000	3.30	3,890	5.80	10,248	11.50	26,590
1.30	1,090	3.40	4,080	6.00	10,800	12.00	28,800
1.40	1,180	3.50	4,280	6.20	11,352	12.50	31,110
1.50	1,280	3.60	4,480	6.40	11,904	13.00	33,410
1.60	1,380	3.70	4,700	6.60	12,456	13.50	35,710
1.70	1,490	3.80	4,920	6.80	13,008	14.00	38,030
1.80	1,600	3.90	5,140	7.00	13,560	15.00	42,630
1.90	1,720	4.00	5,370	7.20	14,112	16.00	47,230
2.00	1,840	4.10	5,620	7.40	14,664	17.00	51,830
2.10	1,970	4.20	5,880	7.60	15,216	18.00	56,430
2.20	2,100	4.30	6,140	7.80	15,768	19.00	61,030
2.30	2,240	4.40	6,400	8.00	16,400	20.00	65,630
2.40	2,380	4.50	6,670	8.20	16,980	21.00	70,230
2.50	2,530	4.60	6,940	8.40	17,560	22.00	74,830
2.60	2,680	4.70	7,215	8.60	18,140	23.00	79,430
2.70	2,840	4.80	7,490	8.80	18,720	24.00	84,030
2.80	3,000	4.90	7,765	9.00	19,300	25.00	88,630

^a Above gage height 14.00 feet the rating curve is a tangent, the difference being 460 per tenth. Below gage height 1.20 feet the above rating table has been revised.

Rating tables for Chattahoochee River at West Point—Continued.

JANUARY 1, 1904, TO DECEMBER 31, 1905.^a

Gage height	Dis-charge						
Feet	Sec.-ft.	Feet	Sec.-ft.	Feet	Sec.-ft.	Feet	Sec.-ft.
0.90	800	2.30	2,240	3.70	4,720	6.20	10,800
1.00	850	2.40	2,380	3.80	4,940	6.40	11,380
1.10	920	2.50	2,530	3.90	5,160	6.60	11,940
1.20	1,000	2.60	2,680	4.00	5,380	6.80	12,520
1.30	1,090	2.70	2,840	4.20	5,830	7.00	13,100
1.40	1,180	2.80	3,000	4.40	6,290	8.00	16,000
1.50	1,280	2.90	3,170	4.60	6,760	9.00	18,900
1.60	1,380	3.00	3,340	4.80	7,240	10.00	21,800
1.70	1,490	3.10	3,520	5.00	7,740	11.00	24,700
1.80	1,600	3.20	3,700	5.20	8,240	12.00	27,600
1.90	1,720	3.30	3,890	5.40	8,740	13.00	30,500
2.00	1,840	3.40	4,080	5.60	9,260	14.00	33,400
2.10	1,970	3.50	4,280	5.80	9,780		
2.20	2,100	3.60	4,500	6.00	10,300		

^a Above gage height 6.5 feet the rating curve is a tangent, the difference being 290 per tenth.

Rating table for Chattahoochee River at West Point, for 1906.

Gage height	Dis-charge						
Feet	Sec.-ft.	Feet	Sec.-ft.	Feet	Sec.-ft.	Feet	Sec.-ft.
2.50	2,530	3.70	4,630	4.90	7,290	8.00	14,900
2.60	2,680	3.80	4,880	5.00	7,520	9.00	17,740
2.70	2,840	3.90	5,090	5.20	7,980	10.00	20,700
2.80	3,000	4.00	5,300	5.40	8,440	11.00	23,860
2.90	3,170	4.10	5,510	5.60	8,920	12.00	27,100
3.00	3,340	4.20	5,730	5.80	9,400	13.00	30,500
3.10	3,520	4.30	5,950	6.00	9,880	14.00	33,900
3.20	3,700	4.40	6,170	6.20	10,360	15.00	37,350
3.30	3,890	4.50	6,390	6.40	10,840	16.00	40,800
3.40	4,080	4.60	6,610	6.60	11,320	17.00	44,250
3.50	4,280	4.70	6,830	6.80	11,820	18.00	47,700
3.60	4,480	4.80	7,060	7.00	12,320	19.00	51,150

NOTE.—The above table s based on discharge measurements made during 1903-1906 and is well defined.

Estimated monthly discharge of Chattahoochee River at West Point.

[Drainage area, 3,300 square miles.]

Month	Discharge in second-feet			Run-off	
	Maximum	Minimum	Mean	Sec.-ft. per sq. mile	Depth in inches
1896 ^a					
August.....	10,800	1,000	2,854	0.86	0.99
September.....	5,880	780	1,469	.44	.49
October.....	5,620	930	1,624	.49	.56
November.....	19,900	1,490	5,074	1.54	1.72
December.....	5,880	1,720	3,114	.94	1.08
1897 ^b					
January.....	17,000	1,720	4,270	1.29	1.49
February.....	14,700	3,610	8,532	2.59	2.70
March.....	38,500	4,280	14,392	4.36	5.03
April.....	25,100	4,480	9,513	2.88	3.21
May.....	5,370	2,760	3,788	1.15	1.33
June.....	3,260	1,720	2,647	.80	.89
July.....	26,300	1,600	5,140	1.56	1.80
August.....	16,700	1,720	4,253	1.29	1.49
September.....	1,600	930	1,138	.34	.38
October.....	3,340	845	1,290	.39	.45
November.....	2,760	900	1,474	.45	.50
December.....	6,140	2,380	3,536	1.07	1.23
The year.....	38,500	845	4,998	1.51	20.50

^a Estimates for 1896 were revised on the basis of the 1898 rating curve.

^b Estimates for 1897 were revised on the basis of the 1898 rating curve.

WATER POWERS OF GEORGIA

Estimated monthly discharge of Chattahoochee River at West Point—Continued.

[Drainage area, 3,300 square miles.]

Month	Discharge in second-feet			Run-off	
	Maximum	Minimum	Mean	Sec.-ft. per sq. mile	Depth in inches
1898 <i>a</i>					
January.....	10,800	1,970	3,321	1.01	1.16
February.....	3,430	1,840	2,319	.70	.78
March.....	6,140	1,970	2,785	.84	.97
April.....	20,750	2,310	6,931	2.10	2.34
May.....	3,700	1,540	2,235	.68	.78
June.....	2,100	1,150	1,491	.45	.50
July.....	15,240	900	4,202	1.29	1.49
August.....	23,940	3,170	8,615	2.61	3.01
September.....	57,350	1,600	11,080	3.36	3.75
October.....	40,330	1,600	9,511	2.88	3.32
November.....	10,110	3,390	5,904	1.79	2.00
December.....	3,334	3,795	5,272	1.60	1.84
The year.....	57,350	900	5,311	1.61	21.89
1899 <i>c</i>					
January.....	13,720	4,280	7,483	2.27	2.62
February.....	43,550	4,230	12,903	3.91	4.07
March.....	40,330	7,627	15,696	4.76	5.43
April.....	22,200	6,535	10,157	3.08	3.44
May.....	7,490	3,450	4,716	1.43	1.65
June.....	5,625	2,530	3,625	1.10	1.23
July.....	10,524	1,970	3,419	1.04	1.20
August.....	4,230	1,840	2,319	.85	.98
September.....	3,340	930	1,971	.60	.67
October.....	3,390	930	2,085	.63	.72
November.....	5,330	1,720	2,303	.70	.78
December.....	10,800	2,330	4,685	1.42	1.64
The year.....	43,550	930	5,989	1.82	24.43
1900					
January.....	8,316	2,330	4,554	1.38	1.59
February.....	63,330	2,330	14,652	4.44	4.62
March.....	16,690	5,625	8,941	2.71	3.13
April.....	19,380	4,920	9,563	2.90	3.23
May.....	8,040	3,700	5,024	1.52	1.75
June.....	55,510	3,890	13,983	4.24	4.73
July.....	31,570	4,230	9,277	2.81	3.24
August.....	11,904	3,000	4,418	1.34	1.54
September.....	31,570	2,100	6,212	1.88	2.10
October.....	8,040	2,530	4,094	1.24	1.43
November.....	8,040	2,630	4,054	1.23	1.37
December.....	14,112	3,340	6,571	1.99	2.29
The year.....	63,330	2,100	7,612	2.31	31.02
1901					
January.....	42,630	4,920	11,743	3.56	4.11
February.....	37,100	4,920	10,015	3.03	3.16
March.....	33,410	4,230	7,952	2.41	2.73
April.....	23,360	4,920	11,022	3.34	3.73
May.....	52,750	4,700	10,314	3.23	3.79
June.....	16,110	4,920	8,487	2.57	2.87
July.....	12,456	3,000	4,964	1.50	1.73
August.....	51,290	3,000	12,982	3.93	4.54
September.....	32,030	3,520	7,145	2.16	2.41
October.....	11,628	2,840	3,883	1.18	1.36
November.....	4,230	2,330	2,335	.86	.96
December.....	83,630	2,330	12,116	3.67	4.24
The year.....	83,630	2,330	8,664	2.62	35.63

a Estimates below gage height 1.20 feet for 1893 and 1899 have been revised.*c* Estimates below gage height 1.20 feet for 1898 and 1899 have been revised.

APALACHICOLA DRAINAGE BASIN, STREAM FLOW 259

Estimated monthly discharge of Chattahoochee River at West Point—Continued.

Month	Discharge in second-feet			Run-off	
	Maximum	Minimum	Mean	Sec.-ft. per sq. mile	Depth in inches
1902					
January.....	61,080	3,700	9,585	2.90	3.34
February.....	56,480	5,145	13,852	4.20	4.37
March.....	65,630	7,765	21,932	6.66	7.68
April.....	38,080	4,920	8,231	2.49	2.78
May.....	7,215	3,170	4,791	1.45	1.67
June.....	6,940	1,970	2,962	.90	1.00
July.....	5,145	1,600	2,988	.91	1.05
August.....	5,625	1,000	2,061	.62	.71
September.....	8,868	1,720	2,963	.90	1.00
October.....	4,920	1,720	2,603	.79	.91
November.....	9,972	1,840	3,460	1.05	1.17
December.....	22,490	3,170	7,187	2.18	2.51
The year.....	65,630	1,000	6,889	2.09	23.19
1903					
January.....	8,592	3,520	4,708	1.43	1.65
February.....	66,090	3,890	21,593	6.54	6.81
March.....	43,550	7,765	19,626	5.95	6.86
April.....	29,720	6,670	12,345	3.74	4.17
May.....	32,030	4,480	7,896	2.39	2.76
June.....	28,340	4,280	9,976	3.02	3.37
July.....	11,904	2,840	4,782	1.45	1.67
August.....	9,972	2,240	4,203	1.27	1.46
September.....	8,868	1,840	2,825	.86	.96
October.....	2,580	1,840	1,988	.80	.69
November.....	4,280	1,840	2,485	.75	.86
December.....	3,340	2,100	2,463	.75	.86
The year.....	66,090	1,840	7,908	2.40	32.10
1904					
January.....	9,000	2,240	3,520	1.07	1.23
February.....	11,380	3,000	5,447	1.65	1.78
March.....	10,300	3,340	4,858	1.47	1.70
April.....	4,500	2,680	3,107	.942	1.05
May.....	4,080	1,600	2,285	.692	.798
June.....	4,500	1,000	1,695	.514	.574
July.....	2,580	1,090	1,705	.517	.596
August.....	29,340	2,100	7,515	2.28	2.63
September.....	2,580	1,090	1,484	.450	.502
October.....	1,000	800	913	.277	.319
November.....	1,600	800	1,375	.417	.465
December.....	4,720	1,490	2,294	.695	.801
The year.....	29,340	800	3,016	.914	12.44
1905					
January.....	29,340	2,100	5,363	1.63	1.83
February.....	19,770	2,380	8,915	2.70	2.81
March.....	4,500	2,840	3,733	1.13	1.30
April.....	3,890	1,840	2,980	.888	.991
May.....	7,740	2,380	3,869	1.17	1.35
June.....	3,520	1,380	2,257	.684	.763
July.....	18,080	1,180	5,724	1.73	1.99
August.....	10,840	1,090	3,743	1.13	1.30
September.....	3,170	1,090	1,505	.456	.509
October.....	4,500	1,280	2,032	.616	.710
November.....	3,340	1,556	1,923	.583	.650
December.....	32,240	1,816	10,380	3.15	3.63
The year.....	32,240	1,090	4,365	1.32	17.88
1906					
January.....	31,900	4,480	11,700	3.55	4.09
February.....	6,610	3,700	4,660	1.41	1.47
March.....	50,800	3,520	14,200	4.30	4.96
April.....	10,800	3,520	5,880	1.78	1.99
May.....	8,680	2,530	4,270	1.29	1.49
June.....	16,600	2,680	4,840	1.47	1.64
July.....	16,600	2,530	7,660	2.32	2.68
August.....	15,400	4,480	8,110	2.46	2.84
September.....	24,500	3,890	8,540	2.59	2.89
October.....	23,100	4,280	8,840	2.68	3.09
November.....	3,680	3,800	4,700	1.42	1.58
December.....	12,300	3,700	5,360	1.62	1.87
The year.....	50,800	2,530	7,400	2.24	30.59

NOTE.—Values are probably excellent.

SOQUE RIVER NEAR DEMOREST.

This station was established July 16, 1904, by M. R. Hall. It is located at Cannon Bridge, on the road from Cornelia to Acorn, $2\frac{1}{2}$ miles from Demorest and about 4 miles above the mouth of the river.

The channel is curved for 500 feet above and slightly curved for 500 feet below the station. The current is swift. Both banks are high and wooded; the right overflows during extreme high water. The bed of the stream is composed largely of rock and is permanent. There is but one channel at all stages. Discharge measurements are made from the single-span wooden wagon bridge, which has a 28-foot approach on the left bank and a 90-foot approach on the right bank. The initial point for soundings is the end of the bridge on the upstream side at the left bank.

The gage is in two sections: The first is a vertical staff, reading from 0 to 10 feet, fastened to the sill and upstream post of the trestle bent at the left bank. An additional section, established September 12, 1905, is a vertical staff, reading from 0.7 foot to 6 feet, fastened to the stump of an ironwood tree on the right bank about 20 feet above the bridge. The gage is read once each day by Charles Cannon. Bench marks were established as follows: (1) The top of the upstream end of the right-bank wooden pier, marked with white paint; elevation, 21.20 feet. (2) A nail in the stump of the ironwood tree to which the second section of the gage is attached; elevation, 6.00 feet. Elevations refer to the datum of the gage.

APALACHICOLA DRAINAGE BASIN, STREAM FLOW

Discharge measurements of Soque River near Demorest.

Date	Gage height	Dis-charge	Date	Gage height	Dis-charge
1904			1905		
June 8.....	<i>Feet</i> 1.74	<i>Sec.-ft.</i> 182	September 6.....	<i>Feet</i> 1.81	<i>Sec.-ft.</i> 196
July 16.....	1.46	123	September 12.....	1.81	196
August 24.....	1.81	202	October 23.....	1.71	168
October 28.....	1.81	102	1906		
October 28.....	1.81	101	January 23.....	4.16	1,080
November 23.....	1.58	150	January 23.....	3.81	905
1905			June 27.....	2.08	242
March 2.....	2.12	287	July 27.....	2.82	488
May 27.....	2.41	334	October 1.....	3.48	790
July 19.....	2.26	327	October 2.....	5.83	1,750
			October 2.....	5.37	1,770

Daily gage height, in feet, of Soque River near Demorest.

Day	July	Aug.	Sept.	Oct.	Nov.	Dec.	Day	July	Aug.	Sept.	Oct.	Nov.	Dec.
1904							1904						
1.....		1.25	1.65	1.4	1.35	1.4	17.....	1.4	1.8	1.5	1.3	1.4	1.5
2.....		2.1	1.65	1.35	1.4	1.4	18.....	1.35	1.8	1.45	1.3	1.4	1.5
3.....		2.15	1.6	1.35	1.4	1.45	19.....	1.4	1.75	1.5	1.3	1.4	1.55
4.....		1.7	2.75	1.35	1.65	1.55	20.....	1.4	2.2	1.45	1.3	1.4	1.5
5.....		2.0	2.6	1.35	1.6	3.05	21.....	1.4	1.75	1.6	1.25	1.4	1.5
6.....		3.45	2.0	1.35	1.5	2.3	22.....	3.7	1.7	1.5	1.25	1.45	1.45
7.....		1.6	1.85	1.4	1.4	1.7	23.....	1.55	1.6	1.4	1.3	1.6	1.45
8.....		5.25	2.1	1.4	1.4	1.65	24.....	1.5	1.65	1.4	1.3	1.65	1.45
9.....		2.9	1.85	1.35	1.35	1.55	25.....	2.3	2.3	1.45	1.3	1.5	1.7
10.....		2.7	1.7	1.4	1.35	1.5	26.....	1.6	2.35	1.45	1.3	1.45	1.65
11.....		1.95	1.6	1.35	1.35	1.45	27.....	1.45	2.4	1.5	1.3	1.4	2.4
12.....		2.4	1.6	1.35	1.4	1.45	28.....	1.4	2.1	1.45	1.3	1.4	2.3
13.....		2.0	1.6	1.35	1.45	1.55	29.....	1.65	2.0	1.4	1.3	1.4	2.1
14.....		1.95	1.55	1.35	1.45	1.5	30.....	1.5	1.75	1.4	1.3	1.4	1.85
15.....		1.8	1.5	1.3	1.4	1.5	31.....	2.7	1.7		1.35		1.7
16.....	1.45	1.85	1.5	1.3	1.4	1.5							

WATER POWERS OF GEORGIA

Daily gage, in feet, of Soque River near Demorest—Continued.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1905												
1	1.7	1.75	2.25	1.9	1.9	2.0	8.6	2.0	1.6	1.8	1.75	1.7
2	1.65	1.75	2.2	1.85	1.95	2.0	3.1	1.9	1.9	1.8	1.75	1.7
3	1.65	1.8	2.1	1.85	2.1	2.1	2.3	2.0	1.9	1.85	1.7	6.8
4	1.6	1.8	2.1	1.8	2.0	2.1	2.0	2.0	1.85	1.75	1.7	3.2
5	1.6	1.85	2.05	2.0	1.95	2.1	1.9	1.9	1.85	1.7	1.7	2.2
6	2.25	1.9	2.0	2.0	3.5	2.0	3.9	1.9	1.8	1.7	1.75	2.1
7	2.7	2.0	2.0	1.9	3.35	2.0	3.1	2.7	1.8	1.7	1.7	2.0
8	1.9	2.0	2.0	1.9	2.4	2.0	2.1	2.7	1.8	1.75	1.7	1.95
9	1.85	3.5	2.1	1.85	2.2	2.9	2.1	2.3	1.8	3.5	1.7	6.6
10	1.85	3.4	2.4	1.8	2.1	3.0	3.1	2.8	1.8	2.4	1.75	3.0
11	1.8	3.1	2.15	1.8	2.05	2.6	3.0	4.2	1.8	2.2	1.75	2.5
12	7.4	3.3	2.2	1.85	2.05	2.4	3.5	3.5	1.75	2.0	1.7	2.3
13	3.8	3.4	2.15	1.85	2.0	2.2	2.7	2.6	1.8	1.9	1.7	2.2
14	2.15	3.1	2.1	1.8	1.9	1.95	6.9	2.5	1.8	1.85	1.7	2.1
15	2.1	2.3	2.1	1.8	3.7	1.8	4.3	3.4	1.8	1.8	1.7	2.1
16	2.0	2.6	2.05	1.8	3.4	1.95	4.3	2.1	1.8	1.8	1.7	2.2
17	1.9	2.2	2.05	1.8	2.9	2.1	2.7	2.1	1.75	1.8	1.65	2.1
18	1.9	2.2	2.0	1.8	2.1	2.0	2.3	2.1	1.75	1.8	1.65	2.1
19	1.85	2.1	2.0	1.8	2.05	2.8	2.2	2.1	1.75	1.8	1.7	2.0
20	1.85	7.1	2.0	1.85	2.0	2.6	4.1	2.1	1.8	1.85	1.7	3.1
21	1.8	5.4	2.0	1.8	2.0	2.6	2.7	2.0	1.8	1.8	1.7	3.6
22	1.8	3.1	2.0	1.85	2.1	2.4	2.6	2.0	1.75	1.7	1.7	2.4
23	1.8	2.3	2.0	1.85	4.0	2.2	2.4	2.2	1.75	1.7	1.7	2.4
24	1.75	2.6	1.95	1.8	2.8	2.1	2.1	2.1	1.75	1.7	1.7	2.4
25	1.75	2.5	1.95	1.8	2.4	1.95	2.1	2.1	1.75	1.75	1.75	2.4
26	1.7	2.4	1.95	2.2	2.4	1.85	2.0	2.3	1.8	2.1	1.9	2.4
27	2.0	2.35	1.95	2.0	2.4	1.8	1.95	2.1	1.8	2.0	1.8	2.2
28	1.9	2.25	1.95	1.9	2.2	1.8	2.0	1.95	1.75	1.8	1.75	2.4
29	1.8	1.95	1.95	2.8	1.85	2.1	2.0	1.7	1.8	1.7	2.2
30	1.7	1.9	1.9	2.7	1.9	2.1	1.75	1.8	1.75	1.7	2.2
31	1.7	1.9	2.1	2.1	1.65	1.75	2.1
1906												
1	2.1	2.65	2.2	2.75	2.5	2.2	2.05	2.85	4.4	4.4	2.55	2.4
2	2.05	2.55	2.15	2.75	2.5	2.25	2.05	2.7	3.7	5.6	2.5	2.4
3	3.2	2.5	2.25	2.7	3.0	2.3	2.05	3.0	3.0	7.5	2.5	2.4
4	5.8	2.45	2.2	2.65	2.75	2.6	2.0	2.75	6.4	3.8	2.6	2.45
5	3.6	2.4	2.2	2.7	2.5	2.3	2.1	2.7	5.2	2.5	2.6	2.4
6	3.0	2.35	2.25	2.65	2.5	2.3	3.3	2.6	3.5	2.3	2.55	2.45
7	2.4	2.35	2.2	2.65	2.85	2.2	2.45	2.75	3.2	2.35	2.55	2.45
8	2.35	2.3	3.2	2.65	2.5	2.2	3.0	2.7	2.85	3.7	2.55	2.45
9	2.5	2.3	2.5	2.8	2.4	2.2	2.85	2.6	2.8	3.5	2.55	2.5
10	2.4	2.3	2.3	2.75	2.4	2.2	2.7	2.6	4.3	3.1	2.6	2.55
11	3.0	2.25	2.25	2.7	2.4	2.25	2.95	2.65	3.8	2.8	2.6	6.1
12	2.9	2.4	2.2	2.6	2.35	5.0	2.9	2.5	3.9	2.45	2.55	4.3
13	2.7	2.3	2.25	2.55	2.35	3.2	2.65	2.4	3.6	2.35	2.55	3.0
14	2.55	2.25	2.3	2.6	2.3	2.35	2.1	2.35	2.9	2.8	2.5	2.9
15	2.45	2.25	3.1	2.9	2.25	2.8	5.0	4.8	2.85	3.1	2.5	2.35
16	2.65	2.2	3.4	2.8	2.25	2.75	2.8	3.0	2.5	3.15	2.7	2.95
17	2.55	2.2	3.1	2.75	2.2	2.55	2.8	2.8	2.35	3.9	2.65	4.8
18	2.4	2.2	3.7	2.55	2.2	2.4	4.6	13.5	5.8	4.8	2.65	3.6
19	2.3	2.2	3.3	2.5	2.2	2.35	3.2	4.0	5.0	3.8	4.0	3.4
20	2.25	2.2	3.8	2.5	2.25	2.25	2.9	3.4	4.0	3.4	3.8	2.95
21	2.2	2.25	3.2	2.5	2.25	2.2	2.95	2.9	3.2	3.1	3.6	2.9
22	6.7	2.4	3.1	2.45	2.2	2.2	5.5	2.8	6.2	3.0	3.2	2.85
23	5.6	2.2	2.35	2.45	2.2	2.2	4.4	3.2	5.3	2.95	3.0	2.6
24	3.4	2.2	2.7	2.45	2.2	2.5	3.2	2.9	4.0	2.9	2.3	2.6
25	2.8	2.2	2.65	2.4	2.25	2.2	2.95	2.8	3.6	2.85	2.6	2.55
26	2.55	2.2	2.5	2.4	2.45	2.15	2.7	2.7	3.7	2.8	2.55	2.55
27	2.45	2.25	3.2	2.5	3.2	2.1	2.75	2.65	3.8	2.8	2.5	2.7
28	2.95	2.2	3.1	3.0	3.0	2.1	2.9	2.6	3.8	2.75	2.45	2.8
29	2.9	3.2	2.55	2.3	2.3	2.75	3.2	3.3	2.7	2.5	2.75
30	2.7	4.0	2.5	2.35	2.2	2.7	4.9	4.2	2.65	2.45	2.9
31	2.6	2.85	2.25	3.4	6.2	2.6	6.2

a Maximum gage height 17.0 feet.

Rating tables for Soque River near Demorest.

JULY 16 TO DECEMBER 31, 1904.^a

Gage height	Dis-charge						
<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>
1.25	93	1.50	132	1.80	198	2.10	282
1.30	100	1.60	152	1.90	224	2.20	314
1.40	115	1.70	174	2.00	252		

JANUARY 1 TO DECEMBER 31, 1905.^b

1.60	151	2.50	393	3.30	685	5.00	1,500
1.70	171	2.60	425	3.40	725	6.00	2,000
1.80	193	2.70	450	3.50	770	7.00	2,500
1.90	217	2.80	495	3.60	815	8.00	3,000
2.00	243	2.90	531	3.70	860	9.00	3,500
2.10	271	3.00	568	3.80	905	10.00	4,000
2.20	300	3.10	606	3.90	950	11.00	4,500
2.30	330	3.20	645	4.00	1,000	12.00	5,000
2.40	361						

^a Discharge estimated above gage height 2.20 feet.

^b Above gage height 4.0 feet the rating curve is a tangent, the difference being 50 per tenth.

JANUARY 1 TO DECEMBER 31, 1906.

2.00	243	3.00	568	4.00	1,000	5.80	2,070
2.10	271	3.10	606	4.20	1,100	6.00	2,220
2.20	300	3.20	645	4.40	1,200	6.20	2,370
2.30	330	3.30	685	4.60	1,310	6.40	2,520
2.40	361	3.40	725	4.80	1,420	6.60	2,680
2.50	393	3.50	770	5.00	1,540	6.80	2,840
2.60	425	3.60	815	5.20	1,665	7.00	3,000
2.70	460	3.70	860	5.40	1,795	8.00	3,880
2.80	495	3.80	905	5.60	1,930	9.00	4,780
2.90	531	3.90	950				

NOTE.—The above table is based on discharge measurements made during 1904-1906 and is well defined below gage height 6 feet. Above gage height 7.4 feet the rating curve is a tangent, the difference being 90 per tenth.

Estimated monthly discharge of Soque River near Demorest.

[Drainage area 112 square miles.]

Month	Discharge in second-feet			Run-off	
	Maximum	Minimum	Mean	Sec.-ft. per sq. mile	Depth in inches
1904					
July 16-31.....	980	108	218	1.95	1.16
August.....	1,745	93	322	2.88	3.32
September.....	525	115	174	1.55	1.73
October.....	115	93	104	.929	1.07
November.....	163	108	122	1.09	1.22
December.....	666	115	183	1.63	1.88
1905					
January.....	2,700	151	314	2.80	3.22
February.....	2,550	182	527	4.71	4.90
March.....	361	217	257	2.29	2.64
April.....	300	193	210	1.88	2.10
May.....	1,000	217	390	3.48	4.01
June.....	4,950	198	455	4.06	4.53
July.....	3,300	217	626	5.59	6.44
August.....	1,100	161	343	3.06	3.53
September.....	217	151	190	1.70	1.90
October.....	770	171	222	1.98	2.28
November.....	217	161	175	1.56	1.74
December.....	2,400	171	474	4.23	4.88
The year.....	4,950	151	349	3.12	42.18

WATER POWERS OF GEORGIA

Estimated monthly discharge of Soque River near Demorest—Continued.

Month	Discharge in second-feet			Run-off	
	Maximum	Minimum	Mean	Sec.-ft. per sq. mile	Depth in inches
1906					
January	4,060	257	781	6.53	7.53
February	443	300	352	2.96	3.08
March	4,150	286	729	6.51	7.50
April	568	361	455	3.83	4.33
May	645	300	374	3.34	3.85
June	1,540	271	395	3.54	3.95
July	1,860	243	601	5.37	6.19
August	8,830	346	1,070	9.55	11.01
September	2,520	346	1,010	9.02	10.06
October	3,430	330	751	6.71	7.74
November	1,000	377	477	4.26	4.75
December	2,370	361	643	5.74	6.62
The year	8,830	257	629	5.62	76.61

SWEETWATER CREEK NEAR AUSTELL.^a

This station was established May 6, 1904, by M. R. Hall. It is located at the south side of Lithia Springs Park, near Austell.

The channel is straight for about 300 feet above and 200 feet below the gage. The current is sluggish above the gage; below it is swift for about 50 feet at several places, with sluggish water between. Both banks are high and wooded, the right being composed of rock, and are not liable to overflow. There is but one channel at all stages. Discharge measurements are made from a boat at low and ordinary stages about 400 yards below the gage. High-water measurements are made from Strickland's wagon bridge, 1½ miles down stream.

The gage is in two sections: The first is an inclined staff, reading to 8 feet, fastened to solid rock on the right bank; the second is a vertical staff, reading from 8 to 16 feet, fastened to a maple tree on the right bank about 100 feet upstream. The gage is read twice each day by J. L. Causey. Bench marks are: (1) A nail in a small maple on the right bank about 200 feet below the gage; elevation, 5.00 feet. (2) A cross cut on a large rock about 10 feet south of the sloping section of the gage; elevation, 10.00 feet. Elevations refer to the datum of the gage.

^a No monthly estimates have been attempted on account of the erratic plotting of the discharge measurements.



FOREST FALLS, NEAR WHIGHAM, GRADY COUNTY, GEORGIA.



Discharge measurements of Sweetwater Creek near Austell

Date	Gage height	Dis-charge	Date	Gage height	Dis-charge
1904			1905		
	<i>Feet</i>	<i>Sec.-ft.</i>		<i>Feet</i>	<i>Sec.-ft.</i>
May 6 <i>a</i>	1.63	122	January 18.....	3.02	227
June 16 <i>b</i>	1.15	61	January 18.....	3.01	220
June 16 <i>a</i>	1.20	64	March 7 <i>e</i>	2.30	200
July 9 <i>a</i>	1.40	85	May 10 <i>f</i>	2.13	147
July 29 <i>a</i>	2.70	254	May 10 <i>f</i>	2.10	136
August 30 <i>a</i>	2.35	173	August 16 <i>g</i>	4.44	448
August 31 <i>c</i>	1.96	122	August 16 <i>g</i>	4.44	438
October 1 <i>d</i>	1.24	61	October 7 <i>f</i>	1.91	123
October 1 <i>d</i>	1.28	60	October 7 <i>f</i>	1.89	119

a Strickland's bridge. *e* 1,000 feet below gage.
b Boat 100 yards below gage. *f* At boat landing below gage.
c Wading 100 yards below gage. *g* Measurement made one-third mile east of Austell, Ga.
d 1,000 feet above gage.

Daily gage height, in feet, of Sweetwater Creek near Austell.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1904												
1.....						3.4	1.9	1.5	1.9	0.9	0.9	1.65
2.....						2.5	1.45	1.6	1.7	.65	1.05	1.6
3.....						1.9	1.3	4.4	1.6	1.05	.95	1.8
4.....						1.6	1.25	2.9	3.0	.7	1.6	1.85
5.....						1.5	1.2	3.9	2.65	1.05	1.8	2.5
6.....						1.5	1.1	3.85	2.05	.75	1.7	3.65
7.....						1.95	1.05	2.3	1.7	.95	1.4	2.6
8.....						1.7	1.35	11.9	1.65	.9	1.35	2.25
9.....						1.45	1.35	16.3	1.6	.65	1.25	2.05
10.....						1.3	1.15	11.4	1.45	.9	1.25	2.05
11.....						1.2	1.1	4.95	1.4	.9	1.25	2.2
12.....						1.2	1.05	6.3	1.3	.85	1.3	2.0
13.....						1.1	1.15	4.3	1.25	.9	1.65	1.85
14.....						1.0	.9	3.45	1.25	.95	2.1	1.75
15.....						1.0	1.0	3.25	1.35	.85	1.75	1.75
16.....						1.15	1.05	4.55	1.1	.55	1.45	1.8
17.....						1.0	.55	3.2	.9	1.0	1.4	1.85
18.....					1.5	1.0	1.0	3.45	1.2	.7	1.35	1.75
19.....					1.5	1.0	.75	2.4	1.2	.7	1.45	1.8
20.....					1.45	1.9	.75	1.95	1.05	.85	1.4	1.65
21.....					1.45	2.8	.75	2.15	1.1	.7	1.45	1.65
22.....					1.35	3.5	.9	2.0	1.1	.75	1.8	1.6
23.....					1.3	2.15	1.15	1.95	1.0	.6	2.4	1.7
24.....					1.3	1.7	.7	2.65	1.15	1.0	2.0	1.65
25.....					1.25	1.3	1.05	4.05	1.0	.9	1.75	1.65
26.....					1.15	1.15	1.0	5.5	1.05	.9	1.6	1.65
27.....					1.2	1.2	.9	7.15	.85	.85	1.45	1.75
28.....					1.2	2.4	1.25	6.0	1.1	.85	1.6	3.45
29.....					1.15	5.6	2.5	3.1	1.05	.9	1.5	3.25
30.....					1.3	2.85	2.2	2.35	.95	.5	1.5	3.2
31.....					2.55		1.65	2.1		.95		2.5

WATER POWERS OF GEORGIA

Daily gage height, in feet, of Sweetwater Creek near Austell—Continued.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1905												
1	2.1	3.0	3.1	2.35	2.75	1.75	4.0	1.8	1.85	7.2	1.85	2.05
2	2.05	2.6	3.0	2.35	2.35	1.7	3.6	1.65	1.95	5.4	1.7	2.45
3	2.1	2.45	3.0	2.35	2.45	1.6	2.55	1.65	2.1	2.8	1.55	9.6
4	2.05	2.55	2.3	2.3	2.55	1.6	2.2	1.65	3.3	2.45	1.75	12.9
5	2.0	2.45	2.3	2.55	2.35	1.65	5.6	1.5	2.7	2.35	1.75	6.7
6	3.3	2.5	2.3	2.9	2.45	1.55	4.6	1.4	2.55	2.05	1.75	4.0
7	2.8	2.55	2.3	2.3	2.1	1.35	7.0	1.7	1.65	1.85	1.75	3.6
8	2.75	4.4	2.3	2.75	2.15	1.45	11.6	1.45	1.55	1.7	1.8	5.8
9	2.55	7.2	2.35	2.3	2.4	1.25	8.6	1.8	1.55	1.6	1.8	10.2
10	2.3	10.2	3.4	2.65	2.1	1.25	8.8	3.1	1.6	1.65	2.6	11.6
11	2.8	3.6	4.0	2.6	1.95	1.05	9.2	3.4	1.1	2.4	3.4	10.4
12	11.2	6.0	4.1	2.6	1.75	1.0	16.7	4.7	1.65	2.35	3.0	6.4
13	14.4	6.5	3.6	2.5	1.65	1.15	10.7	8.2	1.65	2.2	2.5	4.0
14	11.4	6.8	3.2	2.4	1.65	1.45	5.1	4.4	1.7	2.0	2.2	3.4
15	4.7	6.4	3.0	2.55	1.7	1.55	3.4	3.9	1.35	1.95	2.1	3.5
16	3.4	6.0	2.9	2.8	2.85	1.55	2.9	4.4	1.85	2.0	2.0	3.5
17	3.5	5.6	2.3	2.55	4.0	1.45	2.65	3.9	1.45	2.1	1.95	3.6
18	3.0	5.3	2.75	2.5	2.7	1.35	2.3	3.8	1.6	1.4	1.95	3.5
19	3.0	5.2	2.7	2.4	2.05	1.5	2.25	3.6	1.5	1.8	1.95	3.6
20	3.2	6.6	2.85	2.4	1.9	1.95	2.3	2.8	1.4	1.7	2.0	5.2
21	3.0	7.1	3.7	2.3	1.85	1.4	2.1	2.65	1.35	1.75	1.95	6.4
22	2.8	6.9	3.7	2.2	2.45	1.7	2.1	2.85	1.25	1.65	2.05	6.1
23	2.45	5.5	3.1	2.2	2.9	2.3	1.85	3.9	1.25	1.65	1.9	5.7
24	2.4	4.4	2.85	2.2	5.1	2.7	1.75	5.8	1.4	1.65	1.95	5.2
25	2.2	3.7	2.55	2.15	4.5	2.5	2.35	6.5	1.4	1.85	2.1	4.9
26	2.1	3.4	2.5	2.2	3.3	2.1	2.4	4.1	1.35	2.4	2.5	4.4
27	2.25	3.2	2.5	2.2	2.7	2.85	1.9	2.8	1.3	2.4	2.65	4.0
28	2.2	3.2	2.45	2.1	2.4	3.0	1.75	2.05	1.15	2.2	2.6	3.6
29	2.25		2.4	2.5	2.3	3.6	1.9	1.9	1.15	2.0	2.25	3.6
30	2.4		2.5	2.6	2.3	2.7	2.15	1.7	1.65	1.8	2.02	3.4
31	3.2		2.4		2.0		1.8	1.7		1.75		3.4

MULBERRY CREEK NEAR COLUMBUS.

This station was established June 23, 1904, by W. E. Hall. It is located at Mitchells Bridge, about 16 miles north of Columbus and 12 miles south of Hamilton. Mulberry Creek is a tributary of Chattahoochee River, entering it about 6 miles west of the station.

The channel is straight for about 50 feet above and 200 feet below the bridge. The current is rather sluggish above and swift below the station. Both banks are high and not liable to overflow; the right is clean; the left is wooded and covered with brush. The bed of the stream is composed of rock and sand, with but one channel at all stages, broken by one wooden pier. The bottom is very uneven, causing the current to change direction during low water. Discharge measurements are made from the downstream side of the two-span highway bridge, resting upon stone abutments and center wooden pile bent. The initial point for soundings is the left end of the bridge on the downstream side.

Gage heights are determined directly from the bench mark, which is the top of the downstream end of the wooden cap of center pile bent; elevation, 32.00 feet above the datum of the assumed gage.

Discharge measurements of Mulberry Creek near Columbus.

Date	Gage height	Dis-charge	Date	Gage height	Dis-charge
	<i>Feet</i>	<i>Sec.-ft.</i>		<i>Feet</i>	<i>Sec.-ft.</i>
1904			1905		
June 23	1.40	58	June 17.....	1.63	77
September 21.....	1.23	32	June 17.....	1.63	82
September 21.....	1.23	33	September 26.....	1.00	16.6
			September 26.....	1.01	17.7

FLINT RIVER AT MOLINA.

In May, 1897, a station was established on Flint River at the bridge of the Georgia Midland division of the Southern Railway, about half-way from Atlanta to Columbus. The alternate filling and washing out of the sand in an eddy about one-half mile below the station so affected the stream that the fluctuations shown by the gage had no fixed relation to the quantity of water flowing in the river. After this fact developed the station was abandoned and re-established near Woodbury, at the Macon and Birmingham railroad bridge, about 3 miles lower down the river.

The following discharge measurements were made at the Molina station before it was abandoned. They are accurate, and as they are nearly distributed over a period of one year—from May, 1897, to May, 1898—they give a fair idea of the flow of the stream during that time. Measurement No. 5 shows the lowest discharge and is undoubtedly very near the minimum of this stream for 1897.

Discharge measurements of Flint River at Molina.

Date	Gage height	Dis-charge	Date	Gage height	Dis-charge
	<i>Feet</i>	<i>Sec.-ft.</i>		<i>Feet</i>	<i>Sec.-ft.</i>
1897			1898		
May 21.....		641	February 23.....		458
June 7.....		707	April 21.....		877
June 23.....		697	May 23.....		313
August 25.....		2,843			
November 8.....		264			
December 7.....		588			

FLINT RIVER NEAR WOODBURY.

Measurements of the flow of Flint River were made during 1897 and 1898 at Molina, but the river bed was so shifting that the station was discontinued June 2, 1898. Two measurements were made in 1899 at the Macon and Birmingham Railroad bridge near Woodbury, 5 miles below the Molina station. March 29, 1900, a gage was put in near this bridge and the station was reestablished.

The channel above and below the station is slightly curved for 800 feet. Above gage height 10 feet the banks are subject to overflow for a width of 300 or 400 feet, but all water passes beneath the bridge and its approaches. The bridge and its piers are oblique to the direction of the current, and the bed is rough and irregular and mostly permanent.

Discharge measurements are made from the Macon and Birmingham Railroad bridge. This is a two-span iron bridge, each span being 150 feet long and supported by brick piers. There are wooden trestle approaches about 150 feet long on the right bank and 225 feet long on the left. The initial point for soundings is the end of the iron bridge on the right bank, downstream side.

The gage is in 5-foot sections; the part reading from zero to 10 feet is attached to a willow tree on the left bank about 300 feet above the bridge and 50 feet below Riggins's old ferry; the section reading from 10 to 15 feet is fastened to a sweetgum tree 50 feet from the left bank and 150 feet upstream from the bridge. This gage was maintained by the Georgia Geological Survey until November 1, 1900, when it was adopted by the United States Weather Bureau. The observer is G. A. Wright, who is paid by the Weather Bureau. Bench marks were established as follows: (1) The top of the downstream end of the second and third crossbeams from the left-bank end of the bridge; elevation, 27.00 feet; (2) a copper plug set in solid rock on the west side of the river about 100 feet from the water and 100 feet upstream from a point opposite the gage; elevation, 16.29 feet. Elevations refer to the datum of the gage, which is 660 feet above sea level.

Discharge measurements of Flint River near Woodbury.

Date	Gage height	Dis-charge	Date	Gage height	Dis-charge
1899			1903		
June 29.....	<i>Feet</i> 0.80	<i>Sec.-ft.</i> 590	June 29.....	<i>Feet</i> 1.48	<i>Sec.-ft.</i> 1,591
August 29.....	.50	461	July 30.....	.37	508
1900			September 30.....	.28	387
March 29.....	2.20	2,329	1904		
May 2.....	2.85	3,220	February 11.....	2.81	3,095
December 12.....	.85	998	February 23.....	3.80	4,114
December 21.....	4.35	5,423	March 30.....	.74	620
1901			July 7.....	.00	256
February 4.....	4.02	4,901	August 25.....	.30	388
March 5.....	1.18	985	October 4 ^b	— .25	178
May 17.....	.82	565	1905		
August 15.....	.90	813	March 10.....	.91	844
September 6.....	.60	532	April 21.....	.52	544
1902			June 3.....	.08	307
June 30.....	.00	292	September 19.....	— .28	178
July 16.....	1.20	1,226	1906		
July 31.....	.12	329	February 10.....	1.40	1,440
October 6.....	1.45	1,520	April 12.....	1.22	1,180
1903			May 29.....	.52	564
April 22.....	2.45	2,679	June 15.....	2.13	2,260
February 12 ^a	9.20	16,290	September 11.....	1.06	937
March 26.....	5.45	8,861	November 15.....	.93	776

^a This is a flood measurement, stage being high for this station. Results considered fairly accurate.

^b Taken from boat one-half mile above bridge.

WATER POWERS OF GEORGIA

Daily gage height, in feet, of Flint River near Woodbury.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1900												
1				1.3	1.9	0.6	2.9	2.5	0.4	0.2	0.4	0.7
2				1.2	1.5	.5	2.8	1.7	.7	.1	1.2	.6
3				1.2	1.3	.6	4.5	1.2	.6	.2	2.0	.5
4				1.1	1.4	1.0	4.3	1.0	.4	.5	3.3	1.8
5				1.1	1.2	1.4	3.7	1.2	.3	1.5	2.8	2.3
6				1.1	1.0	1.6	2.4	.8	.2	1.8	1.3	2.1
7				1.0	.9	1.5	1.8	.6	.2	1.2	1.0	1.8
8				1.0	.8	1.4	1.4	.5	.2	1.0	.8	1.4
9				1.0	.7	1.3	1.1	.4	.1	1.8	.7	1.3
10				1.2	.8	1.3	1.0	.4	.1	.7	.6	1.0
11				1.3	.6	1.6	.9	.3	.2	.5	.5	.9
12				2.1	.7	1.0	1.6	.3	.2	.5	.6	.8
13				2.4	.7	.7	1.5	.7	.1	.6	.5	.8
14				2.1	.6	.6	1.6	.4	.1	.6	.5	2.4
15				1.6	.6	.5	1.3	.3	1.3	.5	.5	3.3
16				1.4	.5	1.0	1.0	.4	1.6	.4	.4	2.7
17				1.2	.6	4.1	.8	.4	1.5	.4	.5	2.1
18				2.0	.5	4.0	.7	.5	1.3	.3	.5	1.6
19				4.6	1.0	3.8	.6	.4	1.1	.2	.6	1.3
20				5.2	.8	6.0	.5	.3	.8	.2	.5	2.1
21				5.8	.7	5.0	.8	.3	.4	.3	.6	4.3
22				5.0	.6	2.4	.6	.2	.3	.3	.7	3.9
23				2.8	.5	2.0	.5	.1	.3	.6	.6	3.5
24				2.6	1.0	9.0	1.1	.2	.2	.9	.7	2.8
25				2.4	1.5	3.5	.8	.1	.3	1.0	.7	2.1
26				2.2	1.3	8.0	1.0	.3	.2	1.1	1.5	1.7
27				1.9	.9	7.0	1.2	.3	.2	.7	1.6	1.4
28				1.7	.7	5.9	1.2	.2	.2	.5	1.2	1.3
29			2.2	1.5	.6	5.1	1.6	.2	.2	.4	1.0	1.2
30			1.9	1.2	.5	4.1	2.4	.3	.1	.4	.8	1.3
31			1.6		.5		3.0	.4		.3		2.2
1901												
1	2.7	1.7	1.3	5.0	1.1	2.7	2.1	.3	1.0	.9	.4	.6
2	3.7	1.6	1.2	4.4	1.0	3.0	1.6	.7	1.1	1.4	.5	.7
3	4.7	1.5	1.2	7.6	1.0	2.8	1.5	.7	.9	2.7	.5	.9
4	4.4	3.7	1.2	6.4	1.0	2.5	1.2	.5	.8	1.7	.6	1.0
5	3.5	4.3	1.1	5.2	.9	1.9	.9	.4	.6	1.1	.5	1.1
6	2.6	5.4	1.1	3.7	.9	1.6	.9	1.0	.6	1.1	.5	.9
7	2.1	4.3	1.0	2.6	.8	1.8	1.6	1.5	.5	.8	.6	.8
8	1.8	3.0	1.0	2.1	.9	2.6	1.1	1.2	.5	.7	.6	.7
9	1.6	3.4	1.0	1.8	.8	3.2	1.1	.9	.5	.6	.5	.8
10	1.5	3.3	1.2	1.6	.8	1.8	1.0	.7	.4	.7	.5	.7
11	1.6	2.8	2.0	1.5	.7	1.4	.8	.6	.4	.6	.6	1.1
12	3.3	2.4	1.8	1.4	.7	1.1	.6	.8	.4	.6	.5	1.0
13	4.2	2.2	1.5	1.6	.8	1.2	.5	.9	.5	.5	.6	.9
14	4.5	2.0	1.4	2.1	1.0	2.1	.4	.7	.8	.7	.6	.8
15	3.9	1.7	1.2	2.0	1.1	1.8	.4	.9	1.0	.6	.6	.9
16	2.9	1.6	1.1	1.9	.9	1.7	.6	1.8	1.2	.5	.5	3.1
17	4.2	1.5	1.0	1.7	.8	1.6	.8	3.0	.9	.6	.6	2.2
18	3.4	1.4	1.0	1.6	.9	1.5	1.0	2.5	3.4	.5	.5	1.5
19	2.3	1.4	1.0	2.8	.8	1.2	1.4	2.0	4.6	.5	.6	1.2
20	2.0	1.3	1.1	2.9	1.2	1.1	.9	1.7	4.8	.4	.7	1.0
21	1.7	1.3	1.2	2.7	3.1	.9	.9	1.9	3.1	.4	.8	.8
22	1.6	1.3	1.2	2.3	9.0	.8	.8	2.5	1.9	.5	.8	.7
23	1.5	1.4	1.1	1.9	10.0	1.2	.8	6.1	1.2	.5	.7	.8
24	1.4	1.5	1.6	1.7	8.0	1.4	.5	8.0	.9	.4	.6	1.1
25	1.7	1.5	1.7	1.4	5.0	1.0	.4	7.0	.8	.5	.5	1.2
26	1.6	1.6	4.2	1.3	2.8	.8	.4	5.6	.7	.4	.6	1.3
27	1.5	1.5	4.9	1.3	2.0	.7	.4	3.2	.7	.4	.7	1.2
28	1.6	1.4	3.6	1.2	1.6	1.0	.5	4.1	.8	.5	.6	1.5
29	1.6		2.3	1.2	1.4	1.3	.7	2.9	.8	.4	.6	3.2
30	1.5		2.1	1.1	1.3	1.5	.7	2.0	1.0	.4	.5	10.6
31	1.8		5.6		1.7		.6	1.3		.3		10.0

APALACHICOLA DRAINAGE BASIN, STREAM FLOW

Daily gage height, in feet, of Flint River near Woodbury—Continued.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1902												
1.....	8.0	3.2	12.0	4.6	1.0	.4	.1	.1	.4	1.4	1.2	1.8
2.....	5.0	8.5	1.0	2.9	1.0	.5	.0	.1	.3	1.2	.5	1.7
3.....	2.9	11.0	9.5	2.3	.9	.8	.0	.0	.2	.9	.4	2.3
4.....	2.0	9.5	5.4	2.0	.8	.6	.2	.2	.3	.6	.3	3.2
5.....	1.6	8.0	3.0	1.9	.8	.5	.1	.7	.7	1.1	.4	3.0
6.....	1.4	3.6	2.5	1.8	.7	.4	.1	1.5	.4	1.6	.5	2.3
7.....	1.3	2.5	2.3	1.7	.7	.3	.1	1.1	.2	.8	.9	1.6
8.....	1.2	2.0	2.1	2.8	.7	1.8	.2	.6	.1	.4	1.3	1.3
9.....	1.2	1.7	1.9	2.7	1.2	.9	.1	.3	.2	.3	.9	1.2
10.....	1.1	1.6	1.8	2.3	.9	.6	.2	.2	.3	.2	.6	.9
11.....	1.2	1.5	1.7	1.9	.8	.5	.3	.1	.4	.4	.5	.8
12.....	1.1	1.4	1.6	1.7	.7	.4	1.9	.3	.2	.6	.4	.9
13.....	1.0	1.3	1.6	1.5	.6	.3	1.0	.6	.1	.5	.4	1.0
14.....	.9	1.3	2.0	1.5	.8	.3	.6	.3	.1	.4	.3	.9
15.....	1.0	1.6	2.3	1.6	.7	.4	.7	.2	.1	.3	.3	.8
16.....	1.0	1.3	2.8	1.5	1.7	1.0	1.3	.4	.0	.3	.2	1.0
17.....	1.0	1.3	10.0	1.6	2.3	.8	.7	.2	.0	.2	.4	2.0
18.....	1.0	1.6	9.0	2.8	1.7	.6	.3	.1	.1	.2	.9	2.9
19.....	1.0	1.5	6.7	2.4	1.4	.5	.2	.0	.1	.1	.8	3.0
20.....	1.1	1.6	4.0	1.9	1.2	.4	.1	.0	.0	.1	.8	2.0
21.....	1.2	1.9	2.5	1.6	.9	.3	.0	.0	.0	.2	.7	1.4
22.....	1.6	1.8	2.3	1.4	.8	.3	.1	.5	.0	.2	.6	1.5
23.....	1.5	1.7	2.1	1.3	.7	.3	.1	.2	.0	.1	.5	1.6
24.....	1.3	1.6	2.0	1.2	.6	.2	.0	.1	.0	.1	.4	1.4
25.....	1.2	2.0	2.7	1.3	.6	.2	.0	.0	1.5	.0	.4	1.3
26.....	1.3	2.5	2.5	1.4	.5	.1	.0	.0	1.6	.2	2.9	1.2
27.....	1.2	2.6	2.4	1.3	1.6	.1	.0	.0	1.5	1.0	2.8	1.1
28.....	1.2	14.0	4.5	1.2	.5	1.1	.0	.5	1.4	1.5	2.0	1.0
29.....	1.3	8.0	1.1	.4	.1	.1	1.3	1.3	2.0	1.5	1.1
30.....	1.2	8.5	1.1	.4	.0	.2	1.2	1.8	1.7	1.0	1.2
31.....	1.5	6.831	.4	1.4	1.3
1903												
1.....	1.2	1.0	4.7	4.5	1.0	1.2	1.0	.6	.1	.2	.3	.3
2.....	1.1	.9	3.7	3.9	.9	1.5	.9	.7	.2	.2	.4	.3
3.....	1.0	.9	2.9	3.0	1.0	1.3	2.5	.8	.1	.2	.3	.3
4.....	1.2	1.0	3.0	2.7	1.1	1.4	1.1	1.0	.0	.2	.4	.4
5.....	1.1	1.2	4.2	2.3	1.0	2.2	.9	1.5	.2	.2	.5	.4
6.....	1.0	1.2	3.6	2.0	.9	2.5	.8	2.5	.1	.1	.6	.4
7.....	.9	1.5	2.9	1.7	2.0	2.9	2.0	1.4	.1	.2	.5	.6
8.....	.8	13.0	2.4	1.8	1.9	2.8	1.2	1.0	.0	.5	.4	.5
9.....	.7	11.5	2.2	2.2	1.8	2.4	1.3	.8	.0	.3	.4	.6
10.....	.6	10.0	2.4	2.1	1.5	2.2	1.0	1.3	.0	.5	.3	.9
11.....	.6	9.0	3.0	2.3	1.3	1.5	.9	.9	.0	.3	.4	.3
12.....	.5	9.5	3.1	2.2	1.0	1.2	.8	.5	.0	.3	.4	.7
13.....	1.5	7.5	2.6	3.1	1.1	.9	1.7	.6	.0	.2	.5	.6
14.....	1.2	5.7	2.0	2.9	1.3	.6	2.8	.8	.2	.2	.4	.3
15.....	1.1	3.8	2.1	2.5	4.6	.3	2.4	.9	5.3	.1	.4	.7
16.....	1.0	2.7	1.9	2.2	6.0	.5	2.0	1.0	5.9	.2	.5	.6
17.....	.9	7.0	1.8	1.9	4.1	.6	1.6	1.2	4.2	.6	.5	.5
18.....	.8	6.4	1.7	1.7	2.7	.5	1.0	2.7	2.7	1.1	.3	.5
19.....	.7	5.4	1.6	1.4	1.8	.5	.6	6.0	1.6	.7	.7	.4
20.....	.8	3.9	1.5	2.1	1.5	.5	1.0	3.6	1.2	.5	.6	.6
21.....	.9	2.7	1.4	2.9	1.3	.4	.6	2.0	.8	.4	.5	.9
22.....	.8	2.0	1.3	2.5	1.2	.5	.4	1.4	.7	.4	.6	.9
23.....	.7	1.7	5.6	1.9	1.1	.5	.2	1.1	.6	.3	.5	.3
24.....	.8	1.5	7.5	1.5	1.0	.5	.1	.9	.5	.3	.5	.7
25.....	.9	1.4	5.3	1.3	.9	.4	.2	.5	.4	.2	.4	.6
26.....	.9	1.3	5.8	2.2	.8	.5	.8	.4	.4	.3	.5	.5
27.....	.8	1.4	3.7	2.0	.7	1.9	.6	.2	.3	.2	.4	.4
28.....	1.4	3.0	2.2	1.5	.6	1.5	.4	.3	.4	.2	.4	.3
29.....	1.5	2.5	1.2	.8	1.6	.3	.2	.3	.3	.4	.7
30.....	1.3	4.5	1.1	.9	1.3	.2	.1	.3	.3	.4	.7
31.....	1.1	4.985	.326

WATER POWERS OF GEORGIA

Daily gage height, in feet, of Flint River near Woodbury—Continued.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1904												
1.....	0.5	0.9	1.2	0.7	0.4	1.1	0.3	0.4	0.2	-0.25	-0.35	0.1
2.....	.5	.9	1.3	.6	.4	1.0	.2	1.3	.1	-.3	-.3	.2
3.....	.6	.8	1.5	.7	.5	.8	.1	1.1	.1	-.3	-.2	.3
4.....	.7	.7	1.6	.6	.6	.5	.1	1.2	.5	-.3	.0	.4
5.....	.6	.8	2.0	.6	.5	.3	.0	2.2	.8	-.3	.0	.5
6.....	.5	.7	2.5	.7	.5	1.0	.0	2.1	.7	-.35	.1	.9
7.....	.6	.8	2.3	.8	.4	.8	.0	2.2	.3	-.35	.0	.9
8.....	.7	2.6	2.2	.9	.3	.6	-.05	8.7	.2	-.4	.0	.7
9.....	.6	2.5	2.1	1.9	.2	.5	.1	6.5	.2	-.4	-.1	.5
10.....	.8	2.3	1.9	1.4	.3	.4	.1	5.0	.1	-.4	-.05	.5
11.....	1.2	2.3	1.5	1.0	.3	.4	.6	5.0	.0	-.35	-.05	.4
12.....	1.0	2.5	1.3	.8	.3	.3	.0	3.5	.0	-.35	-.05	.3
13.....	.9	2.2	1.1	.7	.2	.0	.2	3.0	.0	-.4	.1	.3
14.....	.8	2.0	1.2	.6	.1	.0	.2	1.2	-.05	-.4	.2	.3
15.....	.7	1.7	1.4	.6	.2	-.05 ^a	.0	1.5	-.1	-.4	.2	.3
16.....	.8	1.4	1.2	.6	.2	-.05	-.05	1.4	-.1	-.4	.1	.3
17.....	1.3	1.2	1.0	.5	.1	-.05	-.1	.9	-.1	-.45	.1	.3
18.....	1.5	1.1	1.0	.5	.2	-.05	-.1	.5	-.1	-.45	.1	.2
19.....	1.4	1.2	.9	.4	.1	-.05	.1	.5	-.15	-.4	.1	.2
20.....	1.2	1.4	.9	.5	.1	-.05	.1	.4	-.2	-.4	.0	.2
21.....	1.0	1.5	.8	.4	.1	-.05	-.05	.3	-.15	-.45	.0	.2
22.....	1.1	2.6	.9	.4	.0	-.05	.2	.3	-.15	-.45	.1	.3
23.....	3.2	3.0	.9	.5	.0	-.05	.1	.3	-.2	-.45	.1	.2
24.....	3.0	2.9	.9	.4	.0	-.05	.8	.4	-.25	-.5	.2	.2
25.....	2.7	2.5	.8	.5	.0	-.05	1.0	.3	-.15	-.45	.2	.4
26.....	1.9	2.0	.9	.4	.0	.0	.4	.7	-.3	-.4	.1	.5
27.....	1.5	1.9	.9	.5	.0	.0	.2	.1	-.2	-.35	.1	.6
28.....	1.2	1.4	.8	.4	.0	.0	.1	.3	-.2	-.4	.1	1.3
29.....	1.1	1.2	.9	.4	.0	.4	.0	.6	-.25	-.35	.1	1.5
30.....	1.0	.8	.8	.5	.0	.4	.1	.5	-.25	-.35	.1	1.3
31.....	.9	.8	.8	.8	1.0	.2	.2	.3	-.4	.2	.1	1.1
1905												
1.....	.9	.5	1.0	.6	.7	.1	1.7	.1	.0	.3	.2	.4
2.....	.6	.5	.9	.5	.6	.1	2.6	.0	.0	.6	.1	.3
3.....	.7	.4	.8	.5	.7	.2	2.6	-.1	.2	.6	.1	2.9
4.....	.6	.4	.7	.5	1.2	.1	1.5	-.1	.6	.6	.1	4.0
5.....	.5	.5	.6	1.0	1.4	.2	1.3	-.2	.6	.7	.1	5.0
6.....	.5	.6	.8	1.2	1.3	.1	1.0	-.2	.3	.4	.0	4.4
7.....	.6	1.0	.8	1.1	.9	.0	.6	-.3	.3	.2	.1	3.4
8.....	.7	1.9	.8	1.0	.6	.0	.7	.2	.1	.0	.1	2.1
9.....	.6	3.0	.8	.9	.8	.1	.6	.5	.0	.1	.1	2.7
10.....	.5	3.2	.9	1.1	.8	-.1	.5	2.2	-.1	.0	.2	2.9
11.....	.4	2.7	1.0	1.1	.7	-.2	.9	2.3	-.2	.1	.9	3.0
12.....	.9	3.5	1.1	1.0	.5	-.2	1.2	2.3	-.2	.3	1.1	2.7
13.....	2.1	5.4	1.3	1.1	.4	-.1	1.2	2.1	.0	.4	1.0	2.1
14.....	2.0	6.3	1.2	1.0	.3	.1	.7	2.0	.0	.4	.8	1.7
15.....	1.9	4.9	1.0	.8	.3	.3	.6	1.8	-.1	.3	.6	1.5
16.....	1.6	3.5	.9	.8	.4	.5	.5	2.6	-.2	.3	.5	1.5
17.....	1.3	2.5	.9	.8	.5	.2	.4	3.9	-.2	.2	.4	1.4
18.....	1.0	2.1	.8	.7	.5	.1	.2	2.6	-.3	.1	.3	1.3
19.....	.8	1.7	.7	.6	.3	.1	.1	1.5	-.3	.1	.2	1.2
20.....	.8	1.5	.6	.6	.2	.0	.4	.8	-.3	.1	.2	2.5
21.....	.8	2.0	1.0	.6	.3	.0	.1	.6	-.3	.0	.2	5.3
22.....	.7	2.0	1.1	.5	.4	.1	.3	.4	-.4	.0	.1	5.4
23.....	.6	1.8	1.3	.5	.4	.3	.0	.3	-.4	.0	.1	4.8
24.....	.6	1.7	1.2	.5	.8	.4	.1	.4	-.4	.0	.2	4.5
25.....	.5	1.5	1.0	.5	.7	.4	.3	1.2	-.4	.1	.2	2.3
26.....	.4	1.3	.8	.4	.5	.2	.1	1.0	-.5	.3	.2	2.2
27.....	.4	1.1	.7	.4	.4	.2	.0	.9	-.4	.6	.2	1.7
28.....	.3	1.0	.7	.4	.3	.1	.1	.7	-.4	.5	.2	1.6
29.....	.3	.6	.5	.5	.3	.2	.3	.3	-.4	.3	.2	1.5
30.....	.4	.6	.6	.6	.2	.3	.1	.1	-.2	.3	.3	1.4
31.....	.5	.5	.5	.5	.2	.2	.1	.1	-.2	.2	.1	1.3

^a June 15 to 25 observer reported "below zero," but stated afterwards that he did not think it went as much as 1 tenth below.

Daily gage height, in feet, of Flint River near Woodbury—Continued.

Day	Jan.	Feb.	Mar.	April	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1906												
1.....	1.3	1.6	0.8	2.5	0.5	0.3	0.2	1.3	0.9	1.6	0.6	0.7
2.....	1.3	1.5	.9	2.1	.5	.3	1.0	1.0	.9	2.1	.7	.7
3.....	1.7	1.4	1.1	1.8	.5	.3	.4	1.0	1.3	2.6	.7	.7
4.....	4.5	1.2	1.5	1.6	.8	.4	1.5	1.1	.9	2.6	.6	.7
5.....	4.7	1.2	1.4	1.4	1.2	.6	1.0	3.5	.8	2.2	.6	.6
6.....	4.9	1.2	1.1	1.3	1.1	.5	.6	3.3	3.6	3.0	.6	.7
7.....	4.0	1.3	1.0	1.2	1.0	.3	.4	1.9	2.7	2.3	.6	.6
8.....	2.9	1.4	1.9	1.2	1.4	.2	.5	1.7	1.1	1.6	.6	.7
9.....	2.0	1.5	3.2	1.2	1.3	.2	1.3	1.7	.8	1.0	.5	.8
10.....	1.7	1.5	3.2	1.5	1.1	.5	1.5	1.3	1.2	.8	.6	.8
11.....	1.5	1.4	2.3	1.4	.9	.3	1.0	1.1	1.0	.7	.6	.9
12.....	1.7	1.2	2.2	1.3	.8	.2	3.6	1.2	1.0	.6	.6	1.0
13.....	1.8	1.2	1.3	1.1	.6	4.3	2.3	1.2	1.4	.6	.6	1.0
14.....	1.8	1.2	1.5	1.0	.6	5.9	1.6	2.1	1.3	.5	.5	.9
15.....	1.7	1.3	2.3	1.3	.5	6.2	1.8	2.9	.8	.5	.9	.9
16.....	1.5	1.2	3.9	1.2	.5	6.2	1.5	3.5	.6	.5	1.0	.8
17.....	1.4	1.1	3.9	1.0	.4	4.5	1.2	2.1	.5	.5	.9	.8
18.....	1.3	1.0	3.5	.9	.4	2.5	1.2	1.0	.4	1.3	1.7	1.1
19.....	1.3	1.0	3.0	.9	.4	1.7	2.3	1.2	.8	3.8	2.4	1.2
20.....	1.3	1.0	7.5	.8	.3	1.7	2.1	.8	1.4	3.1	2.0	1.6
21.....	1.3	1.0	7.8	.8	.4	1.2	1.7	.6	1.4	2.9	1.7	1.7
22.....	2.7	1.1	7.3	.8	.4	.8	1.1	.8	1.8	1.8	1.3	1.6
23.....	4.7	1.1	5.2	.7	.4	.7	2.6	1.7	1.6	1.5	1.1	1.3
24.....	6.3	1.0	2.9	.7	.4	.6	3.1	2.7	1.5	1.2	1.0	1.1
25.....	5.6	1.0	2.1	.6	.3	.5	2.5	1.2	1.4	1.0	.9	1.0
26.....	3.7	.9	1.7	.6	.4	.4	1.7	.9	1.5	.9	.8	.9
27.....	3.0	.9	1.6	.6	.6	.4	1.8	1.1	1.2	.9	.3	.8
28.....	2.6	.9	2.3	.6	.6	.4	1.7	1.8	1.0	.8	.8	.9
29.....	2.3		3.1	.5	.5	.3	1.1	1.5	1.0	.7	.7	1.2
30.....	2.0		3.6	.6	.5	.3	1.7	3.0	.8	.7	.7	1.4
31.....	1.8		2.9				1.4	1.4		.7		2.2

Rating tables for Flint River near Woodbury.

APRIL 1, 1900, TO DECEMBER 31, 1901.^a

Gage height	Dis-charge						
Feet	Sec.-ft.	Feet	Sec.-ft.	Feet	Sec.-ft.	Feet	Sec.-ft.
0.00	350	1.10	390	2.20	2,340	3.30	3,880
.10	370	1.20	1,000	2.30	2,430	3.40	4,020
.20	400	1.30	1,120	2.40	2,620	3.50	4,160
.30	430	1.40	1,245	2.50	2,760	3.60	4,300
.40	460	1.50	1,370	2.60	2,900	3.70	4,440
.50	495	1.60	1,500	2.70	3,040	3.80	4,580
.60	530	1.70	1,640	2.80	3,180	3.90	4,720
.70	565	1.80	1,780	2.90	3,320	4.00	4,860
.80	600	1.90	1,920	3.00	3,460	4.10	5,000
.90	720	2.00	2,060	3.10	3,600		
1.00	800	2.10	2,200	3.20	3,740		

JANUARY 1, 1902, TO DECEMBER 31, 1903.^b

0.00	290	1.80	1,920	3.60	4,240	6.80	10,260
.10	320	1.90	2,040	3.70	4,390	7.00	10,750
.20	360	2.00	2,160	3.80	4,540	7.20	11,250
.30	410	2.10	2,280	3.90	4,690	7.40	11,750
.40	470	2.20	2,400	4.00	4,840	7.60	12,250
.50	540	2.30	2,520	4.20	5,160	7.80	12,750
.60	620	2.40	2,640	4.40	5,480	8.00	13,250
.70	705	2.50	2,760	4.60	5,820	8.20	13,750
.80	800	2.60	2,880	4.80	6,160	8.40	14,250
.90	900	2.70	3,020	5.00	6,520	8.60	14,750
1.00	1,005	2.80	3,150	5.20	6,880	8.80	15,250
1.10	1,115	2.90	3,280	5.40	7,260	9.00	15,750
1.20	1,225	3.00	3,410	5.60	7,640	10.00	18,250
1.30	1,340	3.10	3,545	5.80	8,040	11.00	21,250
1.40	1,455	3.20	3,680	6.00	8,450	12.00	23,750
1.50	1,570	3.30	3,820	6.20	8,880	13.00	26,250
1.60	1,685	3.40	3,960	6.40	9,320	14.00	28,750
1.70	1,800	3.50	4,100	6.60	9,780	15.00	31,250

^a Between gage height 1.60 and 4.10 feet the rating curve is a tangent, the difference being 140 per tenth. Above gage height 4.10 the 1902 curve has been used to obtain revised estimates for 1900 and 1901.

^b Above gage height 6.90 feet the rating curve is a tangent, the difference being 250 per tenth.

WATER POWERS OF GEORGIA

Rating tables for Flint River near Woodbury—Continued.

JANUARY 1, 1904, TO DECEMBER 31, 1905.^a

Gage height	Dis-charge						
Feet	Sec.-ft.	Feet	Sec.-ft.	Feet	Sec.-ft.	Feet	Sec.-ft.
— 0.50	120	— .30	180	— .10	240	.10	320
— .40	150	— .20	200	.00	280		

^a Above gage height 0.10 feet this table is the same as the 1903 table.

JANUARY 1 TO DECEMBER 31, 1906.

0.00	280	1.10	1,050	2.20	2,220	3.60	4,160
.10	320	1.20	1,140	2.30	2,340	3.80	4,480
.20	370	1.30	1,230	2.40	2,460	4.00	4,800
.30	420	1.40	1,320	2.50	2,580	4.20	5,140
.40	480	1.50	1,420	2.60	2,720	4.40	5,480
.50	540	1.60	1,520	2.70	2,860	4.60	5,820
.60	610	1.70	1,630	2.80	3,000	4.80	6,160
.70	690	1.80	1,740	2.90	3,140	5.00	6,520
.80	780	1.90	1,860	3.00	3,280	6.00	8,450
.90	870	2.00	1,980	3.20	3,560	7.00	10,750
1.00	960	2.10	2,100	3.40	3,850	8.00	13,250

NOTE.—The above table is based on discharge measurements made during 1904-1906, and is fairly well defined below gage height 5 feet.

Estimated monthly discharge of Flint River near Woodbury.

[Drainage area, 988 square miles.]

Month	Discharge in second-feet			Run-off	
	Maximum	Minimum	Mean	Sec.-ft. per sq. mile	Depth in inches
1900					
April.....	8,040	800	2,244	2.27	2.53
May.....	1,920	490	757	.77	.89
June.....	15,750	490	4,127	4.18	4.66
July.....	5,650	490	1,680	1.70	1.96
August.....	2,760	370	611	.62	.71
September.....	1,500	370	557	.56	.62
October.....	1,780	370	641	.65	.75
November.....	3,880	460	911	.92	1.03
December.....	5,320	490	1,928	1.95	2.25
1901 ^a					
January.....	5,990	1,245	2,814	2.85	3.29
February.....	7,260	1,120	2,416	2.45	2.55
March.....	7,640	800	1,799	1.82	2.10
April.....	12,250	890	2,951	2.99	3.34
May.....	13,250	580	2,670	2.70	3.11
June.....	3,740	580	1,617	1.64	1.83
July.....	2,200	460	780	.79	.91
August.....	13,250	460	2,657	2.69	3.10
September.....	6,160	460	1,259	1.27	1.42
October.....	3,040	430	679	.69	.80
November.....	650	460	526	.53	.59
December.....	19,750	530	2,379	2.41	2.78
The year.....	19,750	430	1,879	1.90	25.32
1902					
January.....	13,250	900	1,891	1.91	2.20
February.....	30,250	1,340	5,143	5.21	5.43
March.....	24,250	1,685	6,721	6.80	7.84
April.....	5,820	1,115	2,042	2.07	2.31
May.....	2,520	410	934	.95	1.10
June.....	1,920	290	552	.56	.62
July.....	2,040	290	470	.48	.55
August.....	1,570	290	512	.52	.60
September.....	1,920	290	609	.62	.69
October.....	2,160	290	752	.76	.88
November.....	3,280	360	900	.91	1.02
December.....	3,680	800	1,676	1.70	1.96
The year.....	30,250	290	1,850	1.87	25.20

^a Estimates above gage height 4.1 feet have been revised on the basis of the 1902 rating curve.

APALACHICOLA DRAINAGE BASIN, STREAM FLOW 275

Estimated monthly discharge of Flint River near Woodbury—Continued.

Month	Discharge in second-feet			Run-off	
	Maximum	Minimum	Mean	Sec.-ft. per sq. mile	Depth in inches
1903					
January.....	1,570	540	977	.99	1.14
February.....	25,750	900	6,508	6.59	6.86
March.....	12,000	1,455	3,915	3.96	4.57
April.....	5,650	1,115	2,460	2.49	2.78
May.....	8,450	620	1,755	1.78	2.05
June.....	3,280	410	1,315	1.33	1.48
July.....	3,150	320	1,107	1.12	1.29
August.....	8,450	320	1,363	1.38	1.59
September.....	8,240	290	1,203	1.22	1.36
October.....	1,115	320	451	.46	.53
November.....	800	410	985	1.00	1.12
December.....	900	410	629	.64	.74
The year.....	25,750	290	1,889	1.91	25.51
1904					
January.....	3,680	540	1,207	1.22	1.41
February.....	3,410	705	1,338	1.36	2.01
March.....	2,760	800	1,326	1.34	1.55
April.....	2,040	470	687	.695	.775
May.....	1,005	280	394	.399	.460
June.....	1,115	260	442	.447	.499
July.....	1,005	240	368	.372	.429
August.....	15,000	320	2,198	2.22	2.56
September.....	800	180	302	.306	.341
October.....	195	120	155	.157	.181
November.....	360	165	295	.299	.334
December.....	1,570	320	586	.593	.684
The year.....	15,000	120	816	.826	11.23
1905					
January.....	2,280	410	837	.847	.976
February.....	9,100	470	2,454	2.43	2.53
March.....	1,340	540	885	.896	1.03
April.....	1,225	470	751	.760	.848
May.....	1,455	360	627	.635	.732
June.....	540	210	334	.338	.377
July.....	2,890	240	789	.799	.921
August.....	4,690	180	1,164	1.13	1.36
September.....	620	120	251	.254	.283
October.....	800	240	412	.417	.481
November.....	1,115	280	446	.451	.503
December.....	7,260	410	3,016	3.05	3.52
The year.....	9,100	120	997	1.01	13.61
1906					
January.....	9,100	1,230	2,950	2.98	3.44
February.....	1,520	870	1,130	1.14	1.19
March.....	12,800	780	3,520	3.56	4.10
April.....	2,590	540	1,080	1.09	1.22
May.....	1,320	420	663	.670	.77
June.....	8,880	370	1,810	1.83	2.04
July.....	4,160	370	1,540	1.56	1.80
August.....	4,000	610	1,690	1.71	1.97
September.....	4,160	480	1,210	1.22	1.36
October.....	4,430	540	1,500	1.52	1.75
November.....	2,460	540	893	.902	1.01
December.....	2,220	610	978	.988	1.14
The year.....	12,800	370	1,580	1.60	21.79

NOTE.—Values for 1906 are excellent.

FLINT RIVER NEAR MONTEZUMA.

This station is located at the iron highway bridge about 1 mile west of Montezuma. Some discharge measurements had already been made at this point when the United States Weather Bureau established a standard chain gage on the bridge, late in 1904. During 1905 the daily gage heights were furnished by the Weather Bureau.

The channel is slightly curved above and below the station, which is near the point of reverse between the curves. The current is moderate. The right bank, which is mostly covered with a dense growth of brush, will overflow for a great distance at about 12 feet above low water; the left bank is not apt to overflow. The bed is sandy and probably shifting and the current is slow at low stage, especially near the left bank.

Discharge measurements are made from the bridge of two 100-foot spans, with a short trestle approach on the left bank and a very long one across the marshy ground on the right bank. The initial point for soundings is the end of the left-bank approach, downstream side.

The gage is located on the upstream side of the right span of the bridge near the middle pier. The bench mark is the top of the upstream tubular pier at the middle of the bridge; elevation, 28.00 feet above the datum of the gage.

Discharge measurements of Flint River near Montezuma.

Date	Width	Area of section	Gage height	Dis-charge
July 18..... 1901.....	<i>Feet</i> 173	<i>Sq. ft.</i> 1,930	<i>Feet</i> 4.38	<i>Sec.-ft.</i> 2,400
September 21..... 1904.....	188	1,300	1.85	971
August 23..... 1905.....	198	1,550	3.15	1,610
August 31.....	198	1,390	2.41	1,250
October 12.....	195	1,330	2.25	1,150
April 11..... 1906.....	202	2,200	6.38	3,420
June 16.....	225	3,260	11.92	8,110
November 30.....	196	1,490	3.94	1,960

APALACHICOLA DRAINAGE BASIN, STREAM FLOW

Daily gage height, in feet, of Flint River near Montezuma.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1905												
1.....	5.1	3.2	6.0	4.3	3.6	4.0	3.3	1.8	2.3	1.8	2.1	2.4
2.....	4.4	3.2	5.8	4.0	3.6	3.5	5.1	1.9	3.3	4.1	2.1	2.3
3.....	4.1	3.2	5.6	4.0	4.5	3.0	6.5	1.9	4.6	4.0	2.0	2.6
4.....	4.7	3.2	5.5	4.0	5.3	3.0	7.5	1.8	4.2	3.2	2.0	3.9
5.....	3.4	3.2	5.1	4.0	6.0	3.0	7.5	1.7	4.0	3.3	2.0	7.0
6.....	3.4	3.5	5.0	4.3	5.7	3.2	5.8	1.6	3.8	3.0	2.0	8.2
7.....	3.5	3.7	5.0	4.8	5.6	2.9	5.0	1.5	3.4	3.4	2.0	9.0
8.....	3.6	5.4	4.8	5.2	6.3	2.7	3.9	1.4	3.2	2.9	2.0	9.7
9.....	3.6	7.4	4.7	5.0	6.2	2.4	3.2	1.3	2.5	2.4	1.9	9.9
10.....	3.6	9.2	4.7	4.9	5.7	2.2	2.5	2.3	2.0	2.2	2.0	8.8
11.....	3.5	10.5	6.0	4.7	4.8	2.2	2.5	5.2	1.8	2.0	2.6	8.7
12.....	3.4	12.0	6.4	4.5	4.3	2.0	3.0	6.6	1.7	2.2	4.1	8.5
13.....	4.0	14.0	6.7	5.6	3.9	2.0	4.0	7.0	1.6	2.4	4.7	8.6
14.....	4.6	15.0	8.2	7.6	3.5	2.1	4.4	7.6	2.7	2.4	4.6	8.2
15.....	7.6	17.3	3.6	8.5	3.2	2.3	4.0	8.2	2.9	2.2	4.6	7.0
16.....	7.2	17.1	6.7	7.1	3.2	2.4	3.7	7.7	2.3	2.1	4.0	6.2
17.....	6.4	15.5	6.0	5.7	5.1	2.5	3.0	7.4	1.9	2.1	3.2	5.6
18.....	5.7	13.9	5.5	5.0	6.6	3.1	2.8	7.1	1.6	2.2	2.9	5.5
19.....	5.0	12.5	5.2	4.7	5.6	3.2	2.5	7.7	1.5	2.1	2.5	5.4
20.....	5.0	10.0	5.0	4.3	4.8	2.5	2.3	7.4	1.5	2.0	2.5	5.6
21.....	5.0	9.0	5.8	4.2	3.6	2.3	2.1	5.0	1.4	2.0	2.5	8.0
22.....	4.3	8.5	6.4	4.1	3.5	2.2	2.0	3.7	1.4	1.9	3.6	10.0
23.....	4.0	9.0	8.0	4.1	3.3	2.3	2.0	3.1	1.3	1.9	3.7	11.7
24.....	4.0	9.3	7.2	4.3	4.6	2.5	2.0	3.0	1.3	1.8	3.8	13.7
25.....	3.9	9.5	6.6	4.0	6.0	3.4	2.0	3.0	1.2	1.8	3.0	13.9
26.....	3.7	8.0	6.0	3.7	6.2	2.9	2.1	3.7	1.1	1.8	2.4	13.0
27.....	3.6	7.2	5.7	3.8	5.2	2.4	2.3	4.3	1.0	2.4	2.5	11.3
28.....	3.3	6.5	5.2	3.9	5.0	2.4	2.2	3.5	1.2	3.7	2.4	9.4
29.....	3.2	4.9	3.8	4.2	2.5	2.0	3.2	1.2	3.4	2.4	7.9
30.....	3.2	4.7	3.7	3.6	2.9	1.9	2.8	1.4	3.0	2.4	6.8
31.....	3.2	4.5	3.7	1.8	2.5	2.2	6.6
1906												
1.....	6.5	8.5	4.9	11.8	3.4	2.3	3.0	5.4	8.8	4.5	2.9	3.7
2.....	6.3	7.6	4.9	10.0	3.4	2.3	3.0	5.6	6.6	4.4	2.9	3.6
3.....	6.2	7.0	5.1	8.1	3.4	2.7	3.6	5.5	5.4	7.2	2.8	3.6
4.....	7.4	6.7	5.7	7.0	3.5	2.7	3.5	5.3	5.3	10.0	2.8	3.6
5.....	10.4	6.3	5.6	6.9	4.0	2.7	3.4	5.0	6.5	11.9	2.8	3.5
6.....	12.4	6.1	5.5	6.8	4.4	2.9	4.0	4.6	5.1	12.4	2.8	3.5
7.....	13.0	5.9	5.4	6.6	5.2	3.2	3.8	4.4	5.6	12.0	2.8	3.6
8.....	13.4	6.0	5.6	6.4	6.0	3.0	3.4	4.1	10.3	10.2	2.7	3.9
9.....	12.0	6.5	6.7	6.2	6.4	2.9	3.2	3.0	11.4	9.0	2.7	4.0
10.....	11.4	7.5	8.5	6.4	6.2	2.6	6.3	6.5	11.7	8.0	2.7	4.0
11.....	10.6	8.0	8.0	6.6	5.6	2.5	6.9	6.0	9.0	6.5	2.9	4.0
12.....	8.0	7.7	7.6	6.7	4.8	2.5	5.5	6.0	7.0	5.8	3.1	3.8
13.....	7.0	7.0	7.0	6.6	4.2	3.0	5.0	5.5	6.0	5.0	3.3	3.7
14.....	6.9	6.5	7.4	6.3	3.8	3.3	8.4	6.0	5.5	4.6	3.5	3.7
15.....	7.2	6.4	6.6	6.4	3.5	3.3	8.6	5.8	7.5	4.4	3.8	3.7
16.....	7.0	6.2	6.0	6.6	3.2	10.6	7.6	7.0	5.7	4.2	4.6	3.8
17.....	6.9	6.0	6.0	6.4	3.1	11.9	6.4	7.8	5.0	4.0	5.0	3.9
18.....	6.8	5.7	9.0	6.0	3.0	12.6	6.0	7.0	4.8	3.7	5.5	4.2
19.....	6.8	5.7	9.6	5.6	2.8	13.0	5.9	6.7	4.7	3.6	5.8	4.2
20.....	6.4	5.7	10.5	5.0	2.7	12.1	6.7	6.0	4.4	7.3	5.6	4.8
21.....	6.0	5.7	10.8	4.5	2.7	10.0	7.0	5.0	4.0	7.8	6.0	6.2
22.....	6.1	5.7	12.0	4.2	2.6	8.0	7.2	4.4	5.8	9.7	6.6	7.0
23.....	11.4	6.6	13.7	4.0	2.5	7.0	6.4	6.0	5.4	7.7	6.0	7.6
24.....	12.2	6.0	14.4	3.8	2.7	6.1	6.0	6.9	4.6	5.0	5.5	6.5
25.....	14.2	5.7	13.8	3.6	3.0	5.6	9.3	7.5	4.0	4.0	5.2	5.2
26.....	15.0	5.4	12.1	3.5	3.1	5.0	10.0	7.2	4.0	3.5	4.6	4.8
27.....	14.3	5.2	9.0	3.5	3.4	4.4	9.6	6.5	4.0	3.3	4.0	4.6
28.....	12.0	5.0	7.8	3.5	3.4	3.6	8.4	6.0	4.4	3.2	3.8	4.5
29.....	11.6	6.8	3.5	3.2	3.4	7.0	5.6	5.0	3.1	3.7	4.6
30.....	9.8	6.4	3.4	3.0	3.2	6.6	5.4	4.7	3.0	3.7	5.0
31.....	10.0	8.0	2.9	6.0	8.0	3.0	5.2

WATER POWERS OF GEORGIA

Rating table for Flint River near Montezuma, for 1905-6.

Gage height	Dis-charge						
<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>
1.00	640	2.40	1,215	3.80	1,900	6.40	3,550
1.10	675	2.50	1,260	3.90	1,955	6.60	3,690
1.20	710	2.60	1,305	4.00	2,010	6.80	3,840
1.30	750	2.70	1,350	4.20	2,120	7.00	3,990
1.40	790	2.80	1,400	4.40	2,240	8.00	4,750
1.50	830	2.90	1,450	4.60	2,360	9.00	5,570
1.60	870	3.00	1,500	4.80	2,480	10.00	6,420
1.70	910	3.10	1,550	5.00	2,600	11.00	7,300
1.80	950	3.20	1,600	5.20	2,725	12.00	8,200
1.90	990	3.30	1,650	5.40	2,855	13.00	9,160
2.00	1,035	3.40	1,700	5.60	2,980	14.00	10,200
2.10	1,080	3.50	1,750	5.80	3,130	15.00	11,270
2.20	1,125	3.60	1,800	6.00	3,270	16.00	12,400
2.30	1,170	3.70	1,850	6.20	3,410	17.00	13,580

NOTE.—The above table is based on discharge measurements made during 1901-1906, and is well defined between gage heights 1.8 feet and 6 feet.

Monthly discharge of Flint River near Montezuma, for 1905-6.

[Drainage area 2,700 square miles.]

Month	Discharge in second-feet			Run-off	
	Maximum	Minimum	Mean	Sec.-ft. per sq. mile	Depth in inches
1905					
January	4,440	1,600	2,280	0.826	0.95
February	13,900	1,600	5,980	2.20	2.29
March	5,230	2,300	3,200	1.19	1.37
April	5,150	1,850	2,480	.918	1.02
May	3,690	1,600	2,470	.915	1.05
June	2,010	1,040	1,350	.500	.56
July	4,360	950	1,770	.656	.76
August	4,910	750	2,250	.833	.96
September	2,360	640	1,140	.422	.47
October	2,060	950	1,280	.474	.55
November	2,420	990	1,430	.530	.59
December	10,100	1,170	4,910	1.82	2.10
The year	13,900	640	2,540	.940	12.67
1906					
January	11,300	3,270	6,170	2.29	2.64
February	5,150	2,600	3,540	1.81	1.86
March	10,600	2,540	4,970	1.84	2.12
April	8,020	1,700	3,280	1.21	1.35
May	3,550	1,260	1,900	.704	.81
June	9,160	1,260	3,270	1.21	1.35
July	6,420	1,500	3,420	1.27	1.46
August	4,750	2,050	3,310	1.23	1.42
September	7,930	2,010	3,430	1.27	1.42
October	3,530	1,500	3,620	1.34	1.54
November	3,690	1,350	2,070	.767	.86
December	4,410	1,750	2,310	.856	.99
The year	11,300	1,260	3,440	1.27	17.32

NOTE.—Values for 1905 and 1906 are excellent.

FLINT RIVER AT ALBANY.

This station was originally established by the United States Weather Bureau April 10, 1893, and has been maintained from that date to the present. Discharge measurements by the Geological Survey were begun at this station in 1901, and the gage-height records furnished by the Weather Bureau have been used, except for a portion of the year 1903. The present observer, D. W. Brosnan, is paid by the Weather Bureau.

The channel above the station is straight for about 1,000 feet and is rough. Below the station the channel is straight for 700 feet. The river overflows both banks, but only under the approaches to the bridge. The bed is constant, but rough, and the current is irregular.

Discharge measurements are made from the Atlantic Coast Line two-span railroad bridge, which is 325 feet long, with 475 feet of trestle approach on the right bank and 240 feet on the left bank. The initial point for soundings is the center of the tubular iron pier on the upstream side of the bridge on the left bank.

The gage was washed out and replaced in 1898. It was again injured in 1902, and was replaced by a new gage June 17, 1902. The new gage was set 0.75 foot lower than the old gage as it existed prior to June 17, 1902. The gage heights were corrected from January 1 to June 17, 1902, inclusive, to correspond with the new gage. The Weather Bureau gage is attached to the Dougherty County Bridge, located about 700 feet below the Atlantic Coast Line bridge. It is in three sections. No. 1 is attached to the crib around the middle piers and extends to 4 feet above zero; No. 2 is spiked to a green cypress tree just above the bridge on the west bank of the river, and reads from 2 to 17 feet; No. 3 is spiked to a cedar post 16 feet high. This section begins at 17 feet and reads to 32 feet, which is $2\frac{1}{2}$ feet above any high water known since 1840.

A standard chain gage belonging to the United States Geological Survey was installed April 20, 1904. It is fastened to the hand railing of the downstream footway of the Dougherty County Bridge near the middle of the west span. The gage was accurately set to correspond with the bench marks previously established, and its readings agree with the standard portion of the Weather Bureau

gage. The bottom of the box is 45.34 feet above the zero of the gage, and the length of the chain is 47.34 feet.

Bench marks were established as follows: (1) A copper plug set in the downstream corner of the brick abutment on the right bank under the Dougherty County Bridge; elevation, 33.81 feet. (2) The top of the first crossbeam from the right bank, upstream end of the railroad bridge; elevation, 43.20 feet.

Discharge measurements of Flint River at Albany.

Date	Gage height	Dis-charge	Date	Gage height	Dis-charge
1901			1904		
	<i>Feet</i>	<i>Sec.-ft.</i>		<i>Feet</i>	<i>Sec.-ft.</i>
March 9.....	4.75	5,364	April 19.....	2.78	4,474
March 26.....	8.05	10,680	June 18.....	.25	2,111
April 18.....	8.70	10,720	September 22.....	.20	2,044
July 19.....	2.63	4,256	September 23.....	.20	2,104
1902			November 15.....	1.11	3,080
June 25.....	1.90	3,386	November 16.....	1.20	3,056
June 25.....	1.90	3,440	November 21.....	.63	2,423
September 26.....	1.20	2,492	November 21.....	.61	2,378
December 4.....	6.11	8,006	1905		
1903			April 26.....	4.38	6,398
March 6.....	13.68	18,630	August 25.....	1.42	3,073
May 21.....	16.80	23,120	August 28.....	1.82	3,634
July 3.....	5.65	7,744	October 14.....	.79	2,640
September 18.....	13.06	16,640	1906		
October 14.....	1.90	3,484	February 12.....	9.62	13,300
December 22.....	3.25	5,035	February 13.....	9.06	12,800
			April 14.....	4.90	6,910
			June 14.....	3.64	5,560
			August 13.....	3.35	4,720
			November 28.....	2.33	3,930

APALACHICOLA DRAINAGE BASIN, STREAM FLOW 28R

Daily gage height, in feet, of Flint River at Albany.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1902												
1	6.8	3.8	9.6	8.9	4.8	4.3	2.6	3.0	2.3	2.2	1.8	2.2
2	6.1	5.0	11.8	9.3	4.8	3.6	2.3	3.0	2.0	2.0	1.7	3.6
3	6.7	6.8	15.0	9.8	4.9	2.8	2.0	2.8	1.8	1.8	1.6	4.2
4	6.9	9.0	19.6	9.8	5.1	2.6	2.0	2.4	1.6	1.7	1.7	6.1
5	6.8	11.9	20.9	10.5	5.0	2.5	2.2	2.4	1.6	1.7	1.5	7.3
6	6.6	12.6	22.7	10.8	5.1	2.5	2.1	2.5	1.4	1.8	1.1	7.9
7	7.5	13.3	22.9	9.9	4.8	2.6	1.8	2.8	1.6	1.7	.6	8.2
8	8.3	14.5	19.7	8.8	4.6	2.9	1.7	3.1	1.4	1.3	.4	8.9
9	9.1	14.8	17.6	8.7	3.9	4.1	1.7	3.1	1.3	1.4	.2	9.4
10	9.9	15.9	15.1	7.9	3.7	4.1	1.6	2.9	2.5	1.2	.1	9.9
11	10.8	16.1	11.2	7.8	3.8	4.3	1.4	2.7	3.2	1.0	.4	10.4
12	14.0	14.0	10.4	7.5	3.6	4.5	1.1	2.7	3.2	.9	.6	9.7
13	13.3	11.9	9.8	7.2	3.5	4.5	1.3	2.5	3.4	.8	.9	8.2
14	13.8	10.4	9.5	7.2	3.1	4.9	1.5	2.9	3.4	.7	.9	7.6
15	14.5	7.8	8.9	7.0	2.6	4.8	2.2	3.8	3.6	.7	1.1	6.4
16	14.3	6.9	11.5	7.5	2.5	4.5	2.1	3.6	3.9	.7	.8	6.0
17	12.1	6.6	16.3	7.6	2.6	4.9	2.0	3.4	4.3	.6	.6	5.4
18	10.8	6.0	17.0	7.5	3.0	4.3	1.9	3.4	4.4	.7	.4	5.1
19	10.1	7.6	15.6	7.6	3.3	3.9	1.8	3.2	3.9	.5	.4	4.7
20	9.8	7.8	14.1	7.8	3.6	3.7	1.8	3.1	3.7	.4	.3	4.4
21	8.6	8.9	12.3	7.9	3.1	3.1	1.8	2.9	3.9	.9	.1	4.9
22	7.1	9.8	11.7	8.0	2.8	2.8	1.9	2.2	4.1	1.2	.2	5.5
23	6.5	10.3	11.4	8.1	2.5	2.6	2.2	2.1	4.0	1.3	.4	5.7
24	5.1	9.7	10.8	7.9	2.6	2.6	2.6	1.9	4.0	1.8	.4	5.3
25	4.6	8.8	10.7	7.8	3.1	1.9	2.9	1.9	3.2	1.9	.5	6.1
26	4.4	8.1	10.5	7.6	3.5	2.3	2.9	1.8	1.2	2.1	.6	6.3
27	4.3	7.8	9.9	6.8	3.6	2.2	3.2	2.0	2.6	2.0	.9	6.9
28	4.3	7.9	9.6	6.5	3.8	2.2	3.4	2.2	2.4	1.8	.9	7.1
29	4.3	7.9	9.6	5.6	4.3	2.0	3.4	2.4	2.2	1.7	1.3	6.6
30	4.2	7.9	8.7	4.8	4.6	2.0	3.4	2.4	2.0	1.6	1.8	5.7
31	3.9	7.9	7.9	4.6	4.6	4.6	3.2	2.3	2.0	1.9	1.9	4.3
1903												
1	4.1	4.5	8.1	14.4	5.9	4.8	6.5	2.4	2.5	2.6	1.7	3.1
2	3.5	4.9	7.0	13.7	4.6	4.4	6.4	2.3	2.4	2.5	1.7	2.9
3	3.0	5.3	7.9	13.0	4.7	4.5	5.8	2.2	2.4	2.4	1.9	2.3
4	3.2	5.6	8.5	13.0	4.0	5.6	4.7	2.1	2.3	2.3	2.9	2.3
5	3.4	5.4	9.6	13.0	3.9	7.3	4.0	2.5	2.2	2.2	5.0	2.7
6	3.9	5.1	13.5	12.6	3.7	9.0	4.6	3.4	2.0	2.1	7.5	2.7
7	4.2	5.1	14.5	11.5	4.5	11.4	4.5	5.4	1.9	2.0	7.8	2.6
8	4.2	5.0	13.9	10.0	5.2	13.2	4.3	6.5	1.8	2.0	6.7	2.6
9	4.2	5.0	13.5	9.0	5.9	13.7	4.7	6.9	1.7	1.9	5.5	2.9
10	4.6	5.4	11.7	8.5	6.9	13.1	6.0	7.0	1.5	1.9	4.6	3.2
11	4.7	7.2	11.6	9.0	7.7	12.4	6.6	5.5	1.4	2.0	3.9	3.5
12	5.2	8.9	10.7	9.6	8.0	11.5	7.2	4.6	1.2	2.1	3.7	3.7
13	5.2	15.3	9.3	10.1	9.0	9.4	8.2	4.3	1.1	2.1	3.8	3.3
14	5.4	21.6	8.7	10.9	9.2	7.0	8.3	4.0	1.5	1.9	4.0	3.3
15	5.4	22.3	8.5	11.0	9.8	5.5	7.4	4.1	6.6	1.7	3.9	3.6
16	5.4	24.6	8.5	11.5	11.9	4.4	6.4	4.4	11.8	1.6	3.8	3.5
17	5.2	25.0	8.5	12.0	16.3	3.8	6.3	5.2	12.3	1.9	3.7	3.4
18	4.7	24.1	8.0	12.3	16.7	3.4	6.2	6.8	13.0	2.5	3.6	3.3
19	4.7	22.6	7.5	12.5	15.7	3.2	5.5	8.0	13.4	3.2	3.6	3.1
20	4.4	21.8	7.0	12.0	16.0	3.1	4.1	9.1	15.0	3.9	3.6	3.1
21	4.4	19.7	6.5	10.0	16.7	3.1	3.6	10.0	16.8	4.2	3.5	3.1
22	4.6	16.2	6.5	8.0	16.6	3.0	3.0	10.7	17.0	3.6	3.5	3.3
23	4.6	14.1	6.3	7.6	14.5	3.0	2.5	10.8	15.4	3.0	3.4	3.3
24	4.1	13.9	6.5	7.6	10.0	3.5	2.3	10.7	10.7	2.5	3.3	3.7
25	3.7	12.6	7.0	7.7	6.3	4.1	2.6	10.7	4.8	2.3	3.3	3.7
26	3.5	11.2	7.1	7.3	5.5	3.7	3.0	10.6	4.0	2.1	3.2	5.0
27	3.3	10.6	9.0	6.2	4.9	3.5	3.4	10.6	3.7	2.0	3.3	6.2
28	3.4	9.1	10.0	5.4	4.2	3.6	3.9	7.3	3.4	1.9	3.3	7.1
29	3.6	8.6	11.8	5.3	4.4	4.7	3.6	3.3	3.2	1.8	3.3	7.3
30	4.1	14.4	14.4	5.2	4.5	6.0	2.8	2.9	2.8	1.8	3.2	6.8
31	4.3	14.8	14.8	5.0	5.0	5.0	2.6	2.6	2.6	1.7	3.2	6.1

WATER POWERS OF GEORGIA

Daily gage height, in feet, of Flint River at Albany—Continued.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1904												
1.....	5.2	6.3	8.2	4.2	2.0	0.9	0.5	1.1	5.3	-0.1	-0.3	0.5
2.....	4.4	5.9	7.3	3.9	2.0	1.5	1.5	1.6	3.1	-1.1	-1.3	.6
3.....	4.2	5.6	6.7	3.7	1.9	2.6	1.5	1.6	2.2	-1.1	-1.2	.7
4.....	4.2	5.2	6.4	3.6	1.9	2.7	1.1	2.9	1.8	-2.1	.1	1.6
5.....	4.1	5.0	6.3	3.4	2.4	2.4	.8	5.5	1.6	-3.1	.5	2.3
6.....	4.0	4.7	6.6	3.2	2.5	1.9	.6	5.9	1.5	-3.3	.8	3.6
7.....	3.9	4.8	7.0	3.3	2.2	1.5	.5	5.6	1.7	-3.3	.9	3.6
8.....	4.4	5.2	7.3	4.1	1.9	1.3	.5	6.4	2.3	-3.3	.8	3.5
9.....	4.7	6.4	7.3	5.0	1.7	1.1	.4	7.2	2.3	-2.2	.6	3.4
10.....	5.1	8.8	7.8	5.4	1.6	1.3	.4	7.8	1.9	-2.2	.4	3.1
11.....	6.0	12.9	8.1	5.9	1.6	1.2	.4	8.3	1.5	-2.2	.3	2.6
12.....	6.4	16.9	8.1	5.9	1.6	1.0	.7	9.4	1.1	-3.3	.3	2.4
13.....	7.0	19.2	7.5	5.4	1.5	.8	.9	10.8	1.0	-3.3	.4	2.0
14.....	7.0	18.7	6.8	4.7	1.3	.7	.7	11.1	1.0	-3.3	.7	1.8
15.....	6.8	17.2	6.4	3.8	1.3	.6	1.4	13.1	.6	-3.3	1.1	1.6
16.....	6.4	15.8	6.2	3.4	1.3	.5	1.0	13.2	.6	-3.3	1.2	1.5
17.....	6.0	14.8	6.2	3.2	1.4	.4	.7	12.1	.5	-3.3	1.1	1.4
18.....	5.9	13.3	6.1	3.0	1.5	.3	.5	8.0	.4	-4.4	.9	1.4
19.....	5.8	10.5	5.8	2.7	1.9	.2	.4	4.9	.4	-4.4	.8	1.5
20.....	6.0	8.5	5.2	2.5	1.9	.2	.2	4.7	.3	-4.4	.7	1.6
21.....	6.0	8.4	5.0	2.4	1.7	.2	.2	2.9	.2	-4.4	.7	1.6
22.....	5.8	9.3	4.8	2.4	1.4	.1	.2	2.5	.2	-4.4	.6	1.4
23.....	6.8	10.5	4.5	2.4	1.1	.3	.4	2.1	.2	-4.4	.7	1.3
24.....	8.1	10.9	4.2	2.3	1.0	.5	.9	2.0	.2	-4.4	.9	1.2
25.....	9.5	10.9	4.2	2.3	.8	.5	1.4	2.0	.1	-4.4	1.1	1.2
26.....	9.7	10.6	4.1	2.2	.8	.4	1.2	2.2	.1	-5.5	1.1	1.2
27.....	10.0	10.4	4.5	2.2	.7	.4	1.0	2.3	.1	-5.5	1.0	1.2
28.....	10.4	10.1	5.0	2.1	.6	.3	1.2	4.0	.0	-5.5	.9	1.6
29.....	10.3	9.4	4.9	2.0	.5	.3	1.0	4.1	.0	-4.4	.7	2.3
30.....	9.0	4.8	2.0	.6	.3	.7	6.0	.0	-4.4	.6	3.2
31.....	7.0	4.39	1.0	6.4	-3.3	4.1
1905												
1.....	4.2	2.2	8.0	5.0	4.6	2.8	1.9	.5	.8	.0	1.2	.8
2.....	3.8	2.4	7.2	4.7	4.2	3.1	2.4	.4	.8	1.0	.8	.7
3.....	3.1	2.3	6.7	4.5	4.9	3.2	3.0	.4	1.1	1.3	.7	1.1
4.....	2.6	2.3	6.3	4.2	5.9	2.7	4.0	.4	1.6	2.5	.6	1.3
5.....	2.2	2.2	5.9	4.1	6.4	2.2	4.4	.5	2.5	2.2	.6	2.2
6.....	2.0	2.2	5.7	4.1	6.7	2.0	4.4	.4	2.0	2.0	.4	3.6
7.....	2.3	2.6	5.5	4.0	6.6	2.0	4.0	.2	1.6	1.3	.6	4.5
8.....	2.7	3.2	5.2	4.2	6.1	2.0	2.9	.1	1.5	1.6	.5	5.1
9.....	2.7	5.2	5.1	5.0	5.5	1.7	2.2	.2	1.1	1.6	.3	6.0
10.....	2.5	6.7	5.8	5.4	5.4	1.4	1.6	.5	.7	1.3	.4	6.6
11.....	2.3	8.3	6.0	5.6	4.8	1.2	1.5	1.2	.5	1.7	.8	7.0
12.....	2.1	10.9	7.8	6.0	4.0	1.1	1.6	3.1	.3	.9	1.2	6.9
13.....	2.6	15.5	9.6	7.9	3.6	1.0	1.7	4.2	.5	.8	1.9	6.5
14.....	3.4	18.4	10.7	9.4	3.1	1.0	1.5	5.9	.3	.8	3.1	6.0
15.....	4.6	21.4	10.3	10.6	2.7	1.4	1.3	5.6	.2	.3	2.4	6.4
16.....	6.0	25.2	10.1	9.8	2.5	1.6	1.8	5.8	.1	.8	2.7	6.3
17.....	6.4	25.3	9.3	9.1	2.7	1.6	2.0	5.8	.4	.9	1.7	5.7
18.....	6.1	24.5	8.1	7.6	3.7	1.9	1.8	5.2	.4	.9	1.6	5.55
19.....	5.6	23.8	7.0	6.3	4.8	2.0	1.4	4.6	.2	.5	1.2	5.3
20.....	4.8	22.7	6.3	5.4	5.0	2.4	1.2	4.5	.1	.7	1.2	6.3
21.....	4.0	21.2	8.0	4.8	4.3	1.8	1.0	4.6	.0	.5	1.0	6.0
22.....	3.6	19.1	9.3	4.7	3.5	2.0	.9	3.8	.0	.4	.8	6.8
23.....	3.4	17.0	10.1	4.9	2.8	1.6	.7	2.4	-1.1	.4	.6	9.2
24.....	3.3	14.0	9.7	4.9	4.3	1.9	.7	1.7	-1.1	.3	.6	10.9
25.....	3.3	12.0	9.5	4.7	4.5	2.4	.8	1.4	-2.2	.0	.8	11.3
26.....	3.1	11.1	9.1	4.4	5.1	2.5	.8	1.3	-2.2	.5	.7	12.6
27.....	2.9	10.1	8.2	4.4	5.3	2.2	.7	1.6	-3.3	.4	.8	13.4
28.....	2.8	9.0	7.2	4.4	5.4	1.5	.5	1.7	-4.4	.6	1.0	13.6
29.....	2.5	6.4	4.6	4.4	1.4	.8	1.7	-2.2	1.3	1.0	13.3
30.....	2.3	5.8	4.7	3.7	1.8	.8	1.3	-3.3	1.3	.9	11.9
31.....	2.2	5.4	3.07	1.1	1.4	9.8

Daily gage height, in feet, of Flint River at Albany—Continued.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1906												
1.....	7.9	14.1	4.6	7.9	1.8	2.7	2.0	5.8	5.1	2.8	2.2	1.9
2.....	7.3	11.6	4.3	9.1	1.8	2.4	1.9	5.4	5.9	2.7	2.0	1.8
3.....	6.9	9.0	5.1	10.4	1.7	1.9	2.1	5.0	6.1	2.7	2.0	1.8
4.....	7.9	7.5	6.4	10.2	1.7	1.8	2.5	4.9	5.0	3.7	1.9	1.7
5.....	8.6	6.5	7.2	8.8	3.1	1.7	2.5	4.6	4.2	5.8	1.8	1.7
6.....	10.2	6.1	8.0	7.1	4.2	1.6	2.8	3.8	4.0	6.9	1.8	1.7
7.....	10.5	5.8	7.9	6.0	5.1	1.9	2.8	3.2	4.0	8.5	1.8	1.8
8.....	11.1	6.2	7.7	5.3	6.4	2.1	2.7	4.2	5.2	9.3	1.8	1.9
9.....	12.0	6.8	7.7	4.9	7.2	1.8	2.8	5.1	7.6	9.7	1.8	2.0
10.....	12.7	7.3	7.9	4.6	7.1	1.2	2.9	5.6	9.7	9.0	1.7	2.0
11.....	12.9	9.2	8.5	4.5	6.3	1.5	5.0	5.8	10.2	7.7	1.7	2.1
12.....	12.5	9.7	8.9	4.5	5.5	1.4	5.6	4.8	9.9	6.5	1.6	2.3
13.....	11.2	9.3	9.1	4.8	4.6	2.0	5.3	3.6	7.8	4.2	1.6	2.0
14.....	8.8	8.9	9.2	4.9	3.8	3.3	6.5	3.4	6.0	2.5	1.5	2.0
15.....	7.9	7.9	8.8	4.7	3.1	4.9	7.6	3.6	4.5	2.2	1.8	2.2
16.....	7.6	7.0	8.1	4.5	2.6	7.3	7.9	3.5	4.5	2.0	2.0	2.1
17.....	7.1	6.6	6.7	4.5	2.3	9.5	8.1	4.0	4.4	2.0	2.1	2.0
18.....	6.7	6.4	6.2	4.4	2.3	10.4	8.3	5.3	4.3	2.1	3.0	1.8
19.....	6.3	6.0	6.2	4.3	2.2	10.4	8.4	5.5	3.5	2.1	3.5	1.8
20.....	6.0	5.5	8.0	3.9	2.2	10.6	7.7	5.7	2.6	2.0	3.1	2.1
21.....	5.8	5.2	9.0	3.5	2.1	11.1	7.4	5.9	2.0	3.4	2.9	3.0
22.....	6.2	5.6	10.4	3.3	2.2	11.4	7.3	5.3	1.7	4.8	3.5	3.6
23.....	8.1	5.9	10.8	3.2	2.5	10.4	7.0	4.3	2.3	6.7	4.3	4.6
24.....	13.2	6.4	11.2	2.9	2.6	8.0	6.4	4.1	3.6	7.1	4.0	5.0
25.....	17.0	6.3	12.1	2.6	2.6	5.2	5.7	5.3	3.7	6.7	3.6	5.0
26.....	17.5	6.0	13.1	2.5	2.8	3.5	6.2	6.1	3.4	5.5	3.3	4.2
27.....	18.1	5.5	13.7	2.4	3.7	2.8	7.0	6.2	3.1	3.7	2.6	3.5
28.....	18.0	5.0	13.6	2.3	4.2	2.5	7.4	5.5	3.1	3.2	2.4	3.0
29.....	17.1	12.2	2.1	4.5	2.4	7.8	5.3	3.0	2.8	2.2	2.8
30.....	16.3	9.0	1.9	4.0	2.6	7.2	5.0	3.0	2.5	2.1	2.9
31.....	15.9	8.0	3.4	6.2	4.6	2.4	3.5

Rating tables for Flint River at Albany.

JANUARY 1 TO DECEMBER 31, 1902.^a

Gage height		Dis-charge		Gage height		Dis-charge		Gage height		Dis-charge	
Feet	Sec.-ft.	Feet	Sec.-ft.	Feet	Sec.-ft.	Feet	Sec.-ft.	Feet	Sec.-ft.	Feet	Sec.-ft.
0.10	1,380	2.30	3,855	5.00	6,895	9.40	11,845				
.20	1,495	2.40	3,970	5.20	7,120	9.60	12,070				
.30	1,605	2.50	4,080	5.40	7,345	9.80	12,295				
.40	1,720	2.60	4,195	5.60	7,590	10.00	12,520				
.50	1,830	2.70	4,305	5.80	7,795	10.50	13,083				
.60	1,945	2.80	4,420	6.00	8,020	11.00	13,645				
.70	2,055	2.90	4,530	6.20	8,245	11.50	14,208				
.80	2,170	3.00	4,645	6.40	8,470	12.00	14,770				
.90	2,280	3.10	4,753	6.60	8,695	13.00	15,895				
1.00	2,395	3.20	4,870	6.80	8,920	14.00	17,020				
1.10	2,505	3.30	4,983	7.00	9,145	15.00	18,145				
1.20	2,620	3.40	5,095	7.20	9,370	16.00	19,270				
1.30	2,730	3.50	5,208	7.40	9,595	17.00	20,395				
1.40	2,845	3.60	5,320	7.60	9,820	18.00	21,520				
1.50	2,955	3.70	5,433	7.80	10,045	19.00	22,645				
1.60	3,070	3.80	5,545	8.00	10,270	20.00	23,770				
1.70	3,180	3.90	5,658	8.20	10,495	21.00	24,895				
1.80	3,295	4.00	5,770	8.40	10,720	22.00	26,020				
1.90	3,405	4.20	5,995	8.60	10,945	23.00	27,145				
2.00	3,520	4.40	6,220	8.80	11,170						
2.10	3,630	4.60	6,445	9.00	11,395						
2.20	3,745	4.80	6,670	9.20	11,620						

^a This rating table is based on a tangent throughout, the difference being 112.5 per tenth.

WATER POWERS OF GEORGIA

Rating tables for Flint River at Albany—Continued.

JANUARY 1 TO DECEMBER 31, 1903.^a

Gage height	Dis-charge						
<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>
1.10	2,610	2.60	4,300	4.50	6,595	12.00	15,970
1.20	2,720	2.70	4,415	5.00	7,220	12.50	16,650
1.30	2,830	2.80	4,530	5.50	7,845	13.00	17,350
1.40	2,940	2.90	4,645	6.00	8,470	14.00	18,350
1.50	3,050	3.00	4,760	6.50	9,095	15.00	20,400
1.60	3,160	3.10	4,875	7.00	9,720	16.00	21,950
1.70	3,270	3.20	4,995	7.50	10,345	17.00	23,500
1.80	3,380	3.30	5,115	8.00	10,970	18.00	25,050
1.90	3,495	3.40	5,235	8.50	11,595	19.00	26,600
2.00	3,610	3.50	5,355	9.00	12,220	20.00	28,150
2.10	3,725	3.60	5,475	9.50	12,845	21.00	29,700
2.20	3,840	3.70	5,595	10.00	13,470	22.00	31,250
2.30	3,955	3.80	5,720	10.50	14,095	23.00	32,800
2.40	4,070	3.90	5,845	11.00	14,720	24.00	34,350
2.50	4,185	4.00	5,970	11.50	15,345	25.00	35,900

^a Above gage height 13.50 feet the curve becomes a tangent, with a difference of 155 per tenth.

JANUARY 1, 1904, TO DECEMBER 31, 1905.

-0.50	1,480	1.50	3,235	3.50	5,225	7.00	9,150
- .40	1,560	1.60	3,330	3.60	5,330	7.20	9,380
- .30	1,645	1.70	3,425	3.70	5,435	7.40	9,610
- .20	1,730	1.80	3,520	3.80	5,540	7.60	9,840
- .10	1,815	1.90	3,615	3.90	5,645	7.80	10,070
.00	1,900	2.00	3,710	4.00	5,750	8.00	10,300
.10	1,985	2.10	3,805	4.20	5,970	8.50	10,900
.20	2,070	2.20	3,900	4.40	6,190	9.00	11,500
.30	2,155	2.30	4,000	4.60	6,410	9.50	12,100
.40	2,240	2.40	4,100	4.80	6,630	10.00	12,700
.50	2,330	2.50	4,200	5.00	6,850	11.00	14,000
.60	2,420	2.60	4,300	5.20	7,080	12.00	15,350
.70	2,510	2.70	4,400	5.40	7,310	13.00	16,750
.80	2,600	2.80	4,500	5.60	7,540	14.00	18,300
.90	2,690	2.90	4,600	5.80	7,770	15.00	20,000
1.00	2,780	3.00	4,700	6.00	8,000	16.00	21,700
1.10	2,870	3.10	4,805	6.20	8,230	17.00	23,400
1.20	2,960	3.20	4,910	6.40	8,460	18.00	25,200
1.30	3,050	3.30	5,015	6.60	8,690	19.00	27,000
1.40	3,140	3.40	5,120	6.80	8,920	20.00	28,900

JANUARY 1 TO DECEMBER 31, 1906.

1.20	2,960	2.60	4,300	4.00	5,785	6.80	9,170
1.30	3,050	2.70	4,400	4.20	6,015	7.00	9,420
1.40	3,140	2.80	4,500	4.40	6,245	8.00	10,670
1.50	3,235	2.90	4,600	4.60	6,475	9.00	11,920
1.60	3,330	3.00	4,700	4.80	6,705	10.00	13,170
1.70	3,425	3.10	4,805	5.00	6,940	11.00	14,420
1.80	3,520	3.20	4,910	5.20	7,180	12.00	15,750
1.90	3,615	3.30	5,015	5.40	7,420	13.00	17,150
2.00	3,710	3.40	5,120	5.60	7,670	14.00	18,630
2.10	3,805	3.50	5,230	5.80	7,920	15.00	20,140
2.20	3,900	3.60	5,340	6.00	8,170	16.00	21,700
2.30	4,000	3.70	5,450	6.20	8,420	17.00	23,300
2.40	4,100	3.80	5,560	6.40	8,670	18.00	24,900
2.50	4,200	3.90	5,670	6.60	8,920		

NOTE.—The above table is based on eighteen discharge measurements made during 1904-1906 and earlier high-water measurements. It is well defined.

APALACHICOLA DRAINAGE BASIN, STREAM FLOW

285

Estimated monthly discharge of Flint River at Albany.

[Drainage area, 5,000 square miles.]

Month	Discharge in second-feet			Run-off	
	Maximum	Minimum	Mean	Sec.-ft. per sq. mile	Depth in inches
1902					
January	17,533	5,653	10,472	2.09	2.41
February	19,333	5,545	12,279	2.46	2.56
March	27,033	10,158	16,251	3.25	3.75
April	13,420	6,670	10,274	2.05	2.29
May	7,008	4,080	5,509	1.10	1.27
June	6,733	3,405	5,020	1.00	1.12
July	5,095	2,505	3,737	.75	.86
August	5,545	3,295	4,296	.86	.99
September	6,220	2,620	4,442	.89	.99
October	3,745	1,720	2,793	.56	.65
November	3,295	1,380	2,176	.44	.49
December	12,970	3,745	8,565	1.71	1.97
The year	27,033	1,380	7,151	1.43	19.35
1903					
January	7,720	4,760	6,305	1.26	1.45
February	35,900	6,595	17,694	3.54	3.69
March	20,090	8,845	13,001	2.60	3.00
April	19,470	7,470	13,510	2.70	3.01
May	23,035	5,595	11,769	2.35	2.71
June	18,385	4,760	8,869	1.77	1.97
July	11,345	3,955	7,076	1.42	1.64
August	14,470	3,725	8,529	1.71	1.97
September	23,500	2,610	8,709	1.74	1.94
October	6,220	3,160	3,976	.80	.92
November	10,720	3,270	5,337	1.17	1.31
December	10,095	4,300	5,789	1.16	1.34
The year	35,900	2,610	9,255	1.85	24.95
1904					
January	13,220	5,645	8,553	1.71	1.97
February	27,330	6,520	13,550	2.71	2.92
March	10,540	5,860	8,068	1.61	1.86
April	7,885	3,710	5,175	1.04	1.16
May	4,200	2,330	2,215	.643	.741
June	4,400	1,935	2,683	.537	.599
July	3,235	2,070	2,587	.517	.596
August	17,060	2,870	7,949	1.59	1.83
September	7,195	1,900	2,872	.574	.640
October	1,815	1,430	1,629	.326	.376
November	2,960	1,645	2,457	.491	.543
December	5,860	2,330	3,723	.745	.859
The year	27,330	1,430	5,205	1.04	14.10
1905					
January	8,460	3,710	5,156	1.03	1.19
February	38,970	3,900	17,540	3.51	3.66
March	13,610	6,985	9,862	1.97	2.27
April	13,430	5,750	7,622	1.52	1.70
May	3,305	4,200	6,343	1.27	1.46
June	4,910	2,730	3,636	.727	.811
July	6,190	2,330	3,532	.706	.814
August	7,585	1,985	4,140	.828	.955
September	4,200	1,560	2,343	.469	.523
October	4,200	1,900	2,794	.559	.644
November	4,805	2,155	2,854	.571	.637
December	17,680	2,510	9,232	1.85	2.13
The year	38,970	1,560	6,255	1.25	16.79

Estimated monthly discharge of Flint River at Albany—Continued.

Month	Discharge in second-feet			Run-off	
	Maximum	Minimum	Mean	Sec.-ft. per sq. mile	Depth in inches
1906					
January.....	25,100	7,920	14,600	2.92	3.37
February.....	18,800	6,940	9,760	1.95	2.03
March.....	18,200	6,130	11,600	2.32	2.68
April.....	13,700	3,620	6,900	1.38	1.54
May.....	9,670	3,420	5,370	1.07	1.23
June.....	14,900	2,960	6,840	1.37	1.53
July.....	11,200	3,620	7,720	1.54	1.78
August.....	8,420	4,910	6,790	1.36	1.57
September.....	13,400	3,420	6,800	1.36	1.52
October.....	12,800	3,710	6,660	1.33	1.53
November.....	6,130	3,240	4,110	.822	.92
December.....	6,940	3,420	4,310	.862	.99
The year.....	25,100	2,960	7,620	1.52	20.69

NOTE.—Values for 1906 are excellent.

BIG POTATO CREEK NEAR THOMASTON.

This station was established in 1904. It is located at the highway bridge about 5 miles southwest of Thomaston, 200 yards above Daniel's old gristmill.

The channel is curved for about 200 feet above and straight for 300 feet below the station. The current is fairly swift, except at very low stages. Both banks are subject to occasional overflow. The bed of the stream is composed of rock and gravel, free from vegetation, and probably constant. There is but one channel at all stages, broken during the higher water by the piers of the bridge. Discharge measurements are made from the downstream side of the single-span iron bridge, which has trestle approaches of about 100 feet at each end. The initial point for soundings is the left end of the bridge on the downstream side.

Gage heights are determined directly from the bench marks, which are as follows: (1) The top of the downstream end of the first floor beam from the left bank; elevation, 23.00 feet. (2) A chisel mark on the intermediate post at the downstream end of the second-floor beam; elevation, 28.00 feet. Elevations refer to the datum of the assumed gage.

Discharge measurements of Big Potato Creek near Thomaston.^a

Date	Gage height	Dis-charge	Date	Gage height	Dis-charge
1904			1904		
March 31.....	<i>Feet</i> 2.32	<i>Sec.-ft.</i> 164	October 5.....	<i>Feet</i> 1.70	<i>Sec.-ft.</i> 50
May 24.....	1.75	60	1905		
July 6.....	1.80	61	September 21b.....	1.60	31
September 23.....	1.74	49	September 21c.....	1.53	20
September 23.....	1.72	47			
October 5.....	1.69	43			

^a There is a mill some distance above this point, which affects the flow more than was at first thought, making the discharge measurements of little or no value.

^b 700 feet below bridge.

^c Measured at Daniel's mill bridge.

MUCKALEE CREEK NEAR LEESBURG.

This station was established in 1905 in connection with the regular station on Kinchafoonee Creek. It is located about 3 miles east of Leesburg, at a wooden highway bridge consisting of two truss spans, with trestle approaches of about 50 feet on each side.

The current is slow at low water. The right bank will overflow at moderately high water for a long distance. Gage heights are determined directly from the bench mark, which is the top of the upstream end of the wooden cap of the middle bent of the bridge; elevation, 17.00 feet above the datum of the assumed gage.

Discharge measurements of Muckalee Creek near Leesburg.

Date	Gage height	Dis-charge
1905		
August 30.....	<i>Feet</i> 2.02	<i>Sec.-ft.</i> 192
October 13.....	2.75	228
1906		
June 15.....	7.02	1,160

MUCKALEE CREEK NEAR ALBANY.

This station was established March 9, 1903, as a temporary station, by F. A. Murray, and was discontinued December 31, 1903. It was located at a wagon bridge 3 miles north of Albany, and a short distance below the mouth of Kinchafoonee Creek.

The channel was straight for 300 feet above the station and for 200 feet below, and the current was regular and of moderate velocity. Both banks were high and did not overflow. The bed was rocky

WATER POWERS OF GEORGIA

and probably permanent, the river flowing in one channel at all stages. Backwater from the Flint River affected the discharge at high stages. Discharge measurements were made from the single-span highway bridge and its approaches. During 1905 the station was deeply covered with water by a large water-power development just below.

Discharge measurements of Muckalee Creek near Albany.

Date	Gage height	Dis-charge	Date	Gage height	Dis-charge
1901			1903		
March 9.....	<i>Feet</i> 2.30	<i>Sec.-ft.</i> 1,777	May 22.....	<i>Feet</i> 7.40	<i>Sec.-ft.</i> 2,529
March 26.....	4.60	3,244	July 2.....	1.88	1,473
April 18.....	3.02	2,600	September 19.....	6.22	4,195
July 19.....	1.36	1,001	October 15.....	.72	644
1902			December 22.....	1.59	1,343
June 25.....	.97	746	1904		
September 27.....	.90	690	April 22.....	1.45	1,051
December 4.....	2.50	2,180	June 18.....	.33	419
1903			September 22.....	.35	455
March 6.....	6.60	5,141	November 16.....	.95	832

Gage heights for 1901 and 1902 were obtained by measuring down from bench mark to water.

Daily gage height, in feet, of Muckalee Creek near Albany.

Day	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1903										
1.....		4.8	1.6	1.9	1.9	1.2	1.1	1.3	1.0	1.6
2.....		5.0	1.6	1.8	2.0	1.3	1.1	1.3	1.1	1.6
3.....		4.9	1.6	1.7	1.9	1.3	1.0	1.2	1.5	1.6
4.....		4.9	1.6	1.9	1.9	1.2	1.0	1.2	2.0	1.6
5.....		4.9	2.0	2.6	1.7	1.2	1.0	1.2	2.5	1.6
6.....		4.8	2.7	3.1	1.7	1.3	.9	1.2	2.8	1.6
7.....		4.4	2.7	3.3	1.6	1.5	.9	1.1	2.8	1.6
8.....		3.9	2.8	2.9	1.7	1.6	.9	1.1	2.7	1.6
9.....	4.8	3.0	3.0	2.5	1.9	11.6	.9	1.1	2.5	1.6
10.....	4.6	2.8	3.2	2.1	2.2	1.6	.8	1.1	2.3	1.6
11.....	4.4	2.7	3.2	2.0	2.6	1.6	.8	1.0	2.2	1.6
12.....	4.2	2.7	3.5	1.9	2.6	1.6	.8	1.0	2.1	1.6
13.....	3.0	3.0	3.9	1.8	2.6	1.6	.8	1.0	2.1	1.6
14.....	2.8	3.5	4.6	1.8	2.7	1.7	1.6	1.0	2.1	1.6
15.....	2.8	4.0	5.6	1.7	2.7	1.8	4.1	1.0	2.0	1.6
16.....	2.8	5.3	8.8	1.5	2.5	1.9	6.5	1.0	2.0	1.6
17.....	2.8	5.4	12.6	1.5	2.1	2.1	8.6	1.0	2.0	1.6
18.....	2.8	5.0	11.9	1.5	1.7	2.7	8.0	1.0	2.0	1.6
19.....	2.8	4.6	7.9	1.4	1.6	3.1	7.1	1.5	2.0	1.6
20.....	2.8	3.0	7.8	1.4	1.5	3.5	6.0	1.5	2.0	1.6
21.....	2.9	2.8	7.6	1.4	1.3	3.7	6.0	1.3	2.0	1.6
22.....	2.9	2.6	7.6	1.4	1.2	4.0	6.0	1.3	2.0	1.6
23.....	2.9	2.5	6.0	1.3	1.2	3.0	5.2	1.2	1.9	1.6
24.....	2.9	2.4	4.5	1.5	1.2	2.3	2.6	1.1	1.9	1.6
25.....	2.9	2.4	3.7	1.6	1.3	2.0	1.5	1.1	1.8	1.6
26.....	3.0	2.3	2.6	1.5	1.3	1.8	1.5	1.0	1.8	1.6
27.....	3.0	2.1	2.1	1.6	1.4	1.6	1.5	1.0	1.7	1.9
28.....	3.0	1.8	2.0	1.6	1.5	1.4	1.5	1.0	1.6	2.4
29.....	3.2	1.7	2.0	1.6	1.3	1.2	1.4	1.0	1.6	2.6
30.....	4.4	1.7	1.9	1.8	1.3	1.2	1.4	1.0	1.6	2.6
31.....	4.6		1.9		1.3	1.2		1.0		2.6

Rating table for Muckalee Creek near Albany, from March 9 to December 31. 1903 ^a

Gage height	Dis-charge						
<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>
0.80	675	1.90	1,390	3.00	2,160	4.10	2,930
.90	720	2.00	1,460	3.10	2,230	4.20	3,000
1.00	770	2.10	1,530	3.20	2,300	4.30	3,070
1.10	830	2.20	1,600	3.30	2,370	4.40	3,140
1.20	900	2.30	1,670	3.40	2,440	4.50	3,210
1.30	970	2.40	1,740	3.50	2,510	4.60	3,280
1.40	1,040	2.50	1,810	3.60	2,580	4.70	3,350
1.50	1,110	2.60	1,880	3.70	2,650	4.80	3,420
1.60	1,180	2.70	1,950	3.80	2,720	4.90	3,490
1.70	1,250	2.80	2,020	3.90	2,790	5.00	3,560
1.80	1,320	2.90	2,090	4.00	2,860		

^a Backwater from Flint River greatly affects the rating above gage height 5.0 feet.

Estimated monthly discharge of Muckalee Creek near Albany.

Month	Discharge in second-feet		
	Maximum	Minimum	Mean
1903			
March 9-31	3,420	2,020	2,382
April.....	3,840	1,250	2,508
May 1-14 and 24-31 ^a	3,280	1,180	1,928
June.....	2,370	970	1,357
July.....	1,950	900	1,311
August.....	2,860	900	1,388
September 1-15 and 23-30 ^a	3,700	675	1,120
October.....	1,110	770	850
November.....	2,020	770	1,451
December.....	1,880	1,180	1,205

^a Discharges for missing days not given on account of backwater.

KINCHAFOONEE CREEK NEAR LEESBURG.

This station was established August 30, 1905, by F. A. Murray. It is located at the iron highway bridge 1 mile east of Leesburg, Ga.

The channel is nearly straight for about 400 feet above and below the station, and the current is mostly swift. The right bank is lower than the bridge and will probably overflow at times around the end of the bridge approach; the left bank will not overflow. The bed of the stream is sandy, and the current is good, except for a small amount of sluggish water at the left bank.

Discharge measurements are made from the downstream side of the single-span bridge. The initial point for soundings is the left end of the bridge.

A standard chain gage was installed May 12, 1906, and set to read the same as the old vertical gage. It is attached to the downstream

lower chord. The bottom of the box is 24.09 feet above the zero of the gage, and the length of the chain is 26.09 feet. The gage is read by H. B. Johnson. The bench mark is a cross on a boulder embedded in the earth opposite the left end of the bridge approach and 25 feet upstream; elevation, 23.09 feet above gage datum.

Discharge measurements of Kinchafoonee Creek near Leesburg, in 1905-1907.

Date	Hydrographer	Width	Area of section	Gage height	Dis-charge
		<i>Feet</i>	<i>Sq. ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>
1905					
August 30	F. A. Murray	90	180	0.98	216
October 13.....	W. E. Hall	90	238	1.70	323
1906					
February 14	W. E. Hall	130	759	6.67	1,490
April 13.....	do.....	115	438	3.87	736
June 15.....	F. A. Murray	152	888	6.94	1,750
November 29.....	W. E. Hall	105	333	2.44	463
1907					
January 19.....	M. R. Hall	107	342	2.72	503

Daily gage height, in feet, of Kinchafoonee Creek near Leesburg.

Day	Aug.	Sept.	Oct.	Nov.	Dec.	Day	Aug.	Sept.	Oct.	Nov.	Dec.
1905						1905					
1.....		1.0	1.8	1.45	1.7	17.....		1.1	1.4	1.8	
2.....		1.0	3.0	1.35		18.....		1.0	1.35	1.6	
3.....		1.1	2.9	1.3		19.....		1.0	1.3	1.55	
4.....		1.3	2.6	1.25		20.....		.9	1.25	1.5	
5.....		1.5	2.4	1.2		21.....		.8	1.2	1.4	
6.....		1.3	2.0	1.2		22.....		.8	1.2	1.4	
7.....		1.2	1.9	1.2		23.....		.7	1.2	1.4	
8.....		1.1	1.8	1.2		24.....		.7	1.2	1.4	
9.....		1.0	1.7	1.2		25.....		.7	1.2	1.4	
10.....		1.0	1.6	1.3		26.....		.6	1.2	1.5	
11.....		.9	1.6	1.9		27.....		.6	1.3	1.6	
12.....		.8	1.7	1.3		28.....		.6	1.5	1.7	
13.....		.7	1.8	2.3		29.....		.8	1.55	1.8	
14.....		.8	1.9	2.5		30.....	1.0	1.0	1.5	1.7	
15.....		.9	1.7	2.3		31.....	1.0		1.5		
16.....		1.0	1.6	2.0							

APALACHICOLA DRAINAGE BASIN, STREAM FLOW 291

Daily gage height, in feet, of Kinchafoonee Creek near Leesburg—Continued.

Day	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1906									
1.....		2.0	2.3	2.5	3.3	3.5	2.8	2.5	2.4
2.....		2.0	2.1	2.4	3.6	3.3	3.4	2.5	2.3
3.....		1.9	1.9	2.5	3.5	3.1	4.1	2.5	2.3
4.....		2.0	1.8	2.7	3.1	2.9	5.2	2.7	2.3
5.....		3.6	2.0	2.9	2.7	2.3	5.0	2.9	2.3
6.....		5.0	2.3	3.0	2.5	3.4	5.1	2.7	2.2
7.....		5.5	2.5	2.9	2.7	5.6	5.2	2.5	2.3
8.....		6.0	2.1	2.3	2.9	7.7	5.3	2.3	2.3
9.....		6.5	1.4	3.0	3.3	10.5	4.9	2.3	2.3
10.....		5.9	1.1	3.6	2.3	9.7	4.5	2.2	2.3
11.....		4.8	1.0	4.5	2.0	7.1	3.9	2.2	2.3
12.....	3.8	4.6	2.3	5.9	2.1	4.4	3.0	2.2	2.4
13.....	3.8	3.7	4.1	7.1	2.2	3.8	2.3	2.1	2.5
14.....	3.8	2.9	5.6	8.2	2.3	3.1	2.1	2.0	2.5
15.....	3.7	2.7	7.2	6.8	2.5	2.9	2.0	2.5	2.5
16.....	3.3	2.5	11.5	5.1	2.6	2.7	1.9	2.9	2.4
17.....	2.9	2.3	10.0	5.2	2.6	2.5	1.3	3.1	2.4
18.....	3.3	2.2	8.6	5.8	2.5	2.3	1.9	3.3	2.5
19.....	3.4	2.5	7.3	5.3	2.2	2.2	2.6	3.4	3.0
20.....	2.9	2.4	7.2	4.9	1.9	2.1	3.5	3.5	3.6
21.....	2.7	2.3	7.1	4.7	1.7	2.0	4.7	3.5	4.2
22.....	2.6	2.2	7.3	4.9	1.7	1.8	6.3	3.3	4.8
23.....	2.5	2.1	5.5	5.1	2.3	1.9	7.3	3.1	5.0
24.....	2.5	2.2	4.6	4.3	3.1	2.0	6.5	2.8	4.5
25.....	2.3	2.7	3.7	3.9	3.5	1.3	4.9	2.7	3.9
26.....	2.2	3.4	3.3	3.6	3.4	1.6	3.4	2.6	3.2
27.....	2.1	3.9	2.9	3.1	3.3	1.3	2.9	2.5	3.2
28.....	2.1	4.5	2.3	3.0	3.4	2.0	2.3	2.5	2.7
29.....	2.1	4.3	2.7	3.6	3.5	2.1	2.7	2.4	2.3
30.....	2.0	3.6	2.6	4.5	3.7	2.3	2.7	2.4	3.0
31.....		2.5		4.1	3.6		2.6		3.3

Rating table for Kinchafoonee Creek near Leesburg, for 1905-6.

Gage height		Dis-charge		Gage height		Dis-charge		Gage height		Dis-charge	
Feet	Sec.-ft.	Feet	Sec.-ft.	Feet	Sec.-ft.	Feet	Sec.-ft.	Feet	Sec.-ft.	Feet	Sec.-ft.
0.60	164	2.00	380	3.40	638	5.60	1,189				
.70	177	2.10	397	3.50	658	5.80	1,251				
.80	191	2.20	414	3.60	679	6.00	1,315				
.90	205	2.30	432	3.70	700	6.20	1,381				
1.00	220	2.40	450	3.80	721	6.40	1,447				
1.10	235	2.50	468	3.90	743	6.60	1,515				
1.20	250	2.60	486	4.00	765	6.80	1,583				
1.30	266	2.70	504	4.20	811	7.00	1,653				
1.40	282	2.80	522	4.40	859	8.00	2,015				
1.50	298	2.90	541	4.60	909	9.00	2,400				
1.60	314	3.00	560	4.80	961	10.00	2,800				
1.70	330	3.10	579	5.00	1,015	11.00	3,200				
1.80	346	3.20	598	5.20	1,071						
1.90	363	3.30	618	5.40	1,129						

NOTE—The above table is based on seven discharge measurements made during 1905-1907 and is well defined below gage height 4 feet.

WATER POWERS OF GEORGIA

Monthly discharge of Kinchafoonee Creek near Leesburg.

Month	Discharge in second-feet		
	Maximum	Minimum	Mean
1905			
September.....	298	164	211
October.....	560	250	328
November.....	522	250	311
1906			
April 12-30.....	748	380	556
May.....	1,480	363	668
June.....	3,400	220	969
July.....	2,090	450	870
August.....	721	380	528
September.....	3,000	314	754
October.....	1,940	346	768
November.....	658	380	500
December.....	1,020	414	548

NOTE—Values for 1905 and 1906 are excellent.

KINCHAFOONEE CREEK NEAR ALBANY.

This station was established as a temporary station March 9, 1903, by F. A. Murray, and was discontinued December 31, 1903. It was located at the wagon bridge .3 miles north of Albany, Ga., 200 feet below the Central of Georgia Railroad bridge and about one-half mile above the mouth of the creek.

The channel is curved both above and below the station. Both banks are high and all water passes beneath the bridge and its approaches. The bed is probably somewhat shifting.

Discharge measurements were made from the single-span highway bridge and its approaches, which cross the river at an angle to the direction of the current.

During 1905 the station was deeply covered with water by a large water-power development just below.

Discharge measurements of Kinchafoonee Creek near Albany.

Date	Gage height	Dis-charge	Date	Gage height	Dis-charge
1901		<i>Feet</i>	1903		<i>Feet</i>
March 9.....	2.25	1,208	March 26.....	4.28	3,886
March 26.....	3.25	1,920	May 22.....	3.32	1,682
April 18.....	2.82	1,741	July 2.....	1.84	944
July 19.....	1.59	714	September 19.....	3.29	2,051
1902			October 15.....	.98	422
June 25.....	1.15	477	December 22.....	1.76	851
September 27.....	1.20	499	1904		
December 4.....	2.40	1,196	June 18.....	.62	258
			September 22.....	.65	296
			November 16.....	1.12	585

Gage heights for discharge measurements made during the years 1901 and 1902 were obtained by measuring down from the bench mark to surface of the water.

Daily gage height, in feet, of Kinchafoonee Creek near Albany.

Day	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1903										
1		2.9	1.5	1.9	1.8	1.2	1.0	1.2	0.9	1.6
2		2.9	1.5	1.6	1.8	1.3	1.0	1.1	1.1	1.6
3		2.8	1.5	1.5	1.8	1.3	1.0	1.1	1.5	1.6
4		2.8	1.5	1.8	1.9	1.2	1.0	1.1	2.0	1.6
5		2.8	1.9	2.0	1.7	1.2	1.0	1.1	2.5	1.6
6		2.7	2.6	2.6	1.6	1.2	.9	1.1	2.8	1.6
7		2.6	2.6	2.9	1.7	1.3	.9	1.0	2.8	1.6
8		2.5	2.7	3.2	1.9	1.5	.9	1.0	2.7	1.6
9	3.2	2.4	2.9	2.8	2.2	1.5	.9	1.0	2.5	1.6
10	3.0	2.4	2.7	2.4	2.6	1.5	.8	1.0	2.3	1.6
11	2.8	2.4	2.7	2.0	2.6	1.5	.8	1.0	2.2	1.6
12	2.6	2.4	2.9	1.9	2.6	1.5	.8	.9	2.1	1.6
13	2.4	2.5	3.1	1.7	2.6	1.6	.8	.9	2.1	1.6
14	2.2	2.6	3.6	1.7	2.7	1.7	1.6	.9	2.1	1.6
15	2.2	3.0	4.6	1.6	2.7	1.8	3.9	.8	2.0	1.6
16	2.2	3.4	8.6	1.5	2.5	1.8	4.3	.8	2.0	1.6
17	2.2	3.6	11.8	1.4	2.1	1.8	4.6	.8	2.0	1.6
18	2.2	3.5	9.3	1.3	1.7	2.4	4.2	.8	2.0	1.6
19	2.2	3.0	6.6	1.3	1.5	2.8	3.3	1.4	2.0	1.6
20	2.2	2.8	5.2	1.3	1.3	3.2	2.9	1.4	2.0	1.6
21	2.3	2.7	4.6	1.3	1.3	3.7	2.7	1.3	2.0	1.6
22	2.3	2.6	3.7	1.2	1.2	3.9	2.5	1.3	2.0	1.6
23	2.3	2.5	2.9	1.2	1.2	2.9	2.1	1.0	1.9	1.6
24	2.4	2.4	2.7	1.4	1.2	2.2	1.5	.9	1.9	1.6
25	2.4	2.2	2.6	1.5	1.2	1.9	1.4	.9	1.8	1.6
26	2.5	2.0	2.3	1.4	1.3	1.7	1.3	.9	1.8	1.6
27	2.5	1.8	2.0	1.5	1.4	1.5	1.3	.9	1.7	1.9
28	2.5	1.7	1.9	1.5	1.5	1.3	1.3	.9	1.6	2.4
29	2.6	1.7	2.0	1.6	1.3	1.1	1.2	.9	1.6	2.6
30	2.7	1.6	2.0	1.8	1.3	1.1	1.2	.9	1.6	2.6
31	2.8		2.0		1.3	1.0		.9		2.6

Rating table for Kinchafoonee Creek near Albany from March 9 to December 31, 1903.

Gage height	Dis-charge						
<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>
0.80	332	2.10	1,070	3.80	2,330	6.40	3,300
.90	381	2.20	1,135	4.00	2,490	6.60	3,900
1.00	432	2.30	1,200	4.20	2,630	6.80	4,000
1.10	485	2.40	1,265	4.40	2,760	7.00	4,100
1.20	539	2.50	1,330	4.60	2,880	7.50	4,350
1.30	594	2.60	1,400	4.80	3,000	8.00	4,600
1.40	650	2.70	1,470	5.00	3,100	8.50	4,850
1.50	707	2.80	1,540	5.20	3,200	9.00	5,100
1.60	765	2.90	1,615	5.40	3,300	9.50	5,350
1.70	824	3.00	1,690	5.60	3,400	10.00	5,600
1.80	884	3.20	1,850	5.80	3,500	11.00	6,100
1.90	945	3.40	2,010	6.00	3,600	12.00	6,600
2.00	1,007	3.60	2,170	6.20	3,700		

WATER POWERS OF GEORGIA

Estimated monthly discharge of Kinchafoonee Creek near Albany.

Month	Discharge in second-feet		
	Maximum	Minimum	Mean
1908			
March 9-31.....	1,850	1,135	1,314
April.....	2,170	765	1,398
May.....	6,500	707	1,954
June.....	1,850	539	874
July.....	1,470	539	892
August.....	2,410	432	911
September.....	2,880	332	984
October.....	650	332	438
November.....	1,540	381	1,006
December.....	1,400	765	848

ICHAWAYNOCHAWAY CREEK AT MILFORD, GA.

This station is located at the wagon bridge at Milford, Ga. When first established, on August 29, 1905, the bridge was an old wooden structure, which was shortly afterwards replaced by a new steel bridge, with one span of 110 feet, with short trestle approaches at both ends. The temporary vertical gage was also replaced by a standard chain gage, attached to the downstream side of the new bridge; length of chain, 23.46 feet. The observer is W. J. Kidd.

The current is moderately swift and is broken by old bridge timbers still remaining in the channel. The station is about 100 feet above the remains of an old wooden dam, which retains the water at a higher level than it would otherwise have. Gage heights for 1905 and 1906 are from the chain gage described above, but future records will be from a gage located below the dam.

Discharge measurements of Ichawaynochaway Creek at Milford.

Date	Hydrographer	Width	Area of section	Gage height	Discharge
1905					
August 29.....	F. A. Murray.....	111	458	2.89	364
October 16.....	W. E. Hall.....	116	452	3.05	386
1906					
February 15.....	W. E. Hall.....	137	666	4.65	1,390
April 18.....	do.....	123	574	3.78	715
April 18.....	do.....	123	574	3.76	693
June 13.....	F. A. Murray.....	144	718	4.80	1,770
August 14.....	W. E. Hall.....	120	555	3.45	726
November 26.....	do.....	125	493	3.46	592
1907					
January 22.....	M. R. Hall.....	120	496	3.56	690
January 22.....	do.....	120	499	3.57	705

APALACHICOLA DRAINAGE BASIN, STREAM FLOW 295

Daily gage height, in feet, of Ichawaynochaway Creek at Milford.

Day	Aug.	Sept.	Oct.	Nov.	Dec.	Day	Aug.	Sept.	Oct.	Nov.	Dec.
1905						1905					
1		2.8	3.2	3.05	2.95	17		2.8	3.05	3.55	4.05
2		2.8	3.4	3.0	2.9	18		2.75	3.2	3.5	4.0
3		2.8	3.5	3.0	2.9	19		2.7	3.2	3.4	4.0
4		2.75	3.6	3.0	2.95	20		2.65	3.1	3.3	4.15
5		2.7	3.6	3.1	3.0	21		2.6	3.1	3.25	4.7
6		2.7	3.7	3.1	3.1	22		2.6	3.0	3.2	5.0
7		2.65	3.7	3.15	3.25	23		2.55	3.1	3.15	5.5
8		2.6	3.5	3.25	3.4	24		2.55	3.2	3.1	6.0
9		2.6	3.1	3.35	3.5	25		2.5	3.35	3.05	5.9
10		2.55	3.15	3.4	3.6	26		2.5	3.5	3.0	5.4
11		2.55	3.2	3.45	3.65	27		2.5	3.45	3.0	4.9
12		2.7	3.3	3.5	3.7	28		2.45	3.3	3.0	4.9
13		2.9	3.4	3.55	3.9	29		2.9	2.62	3.2	4.7
14		3.0	3.4	3.6	4.0	30		2.85	2.92	3.15	4.5
15		3.0	3.2	3.6	4.05	31		2.8	3.05	3.0	4.4
16		2.9	3.0	3.6	4.05						

Daily gage height, in feet, of Ichawaynochaway Creek at Milford, for 1906.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1906												
1	4.4	4.9	4.1	4.3	3.1	3.7	3.9	3.4	4.4	3.5	3.2	4.3
2	4.4	4.8	4.05	4.2	3.1	3.6	3.8	3.35	4.1	3.7	3.25	4.3
3	4.6	4.7	4.0	4.1	3.3	3.5	3.7	3.3	4.1	4.0	3.25	4.2
4	5.0	4.6	4.0	4.05	3.5	3.4	3.6	3.3	4.2	4.4	3.25	4.1
5	5.6	4.5	4.2	4.0	4.0	3.3	3.5	3.2	4.3	4.8	3.3	4.0
6	6.0	4.5	4.8	3.9	4.8	3.2	3.5	3.2	4.2	4.7	3.3	3.9
7	5.8	4.6	5.4	3.8	5.3	3.25	3.6	3.3	4.0	4.3	3.3	3.8
8	5.2	4.7	5.0	3.9	5.8	3.3	3.3	3.3	4.1	4.0	3.3	3.7
9	4.8	5.0	4.6	4.0	5.3	3.3	4.0	3.2	4.2	3.7	3.3	3.6
10	4.7	5.3	4.5	4.05	5.6	3.35	4.1	3.2	4.3	3.5	3.3	3.5
11	4.6	5.5	4.4	4.1	5.3	3.4	4.4	3.3	4.05	3.4	3.3	3.4
12	4.45	5.2	4.3	4.0	4.6	3.45	4.3	3.4	3.9	3.3	3.3	3.4
13	4.3	5.0	4.35	3.9	4.1	4.5	5.2	3.35	3.7	3.2	3.35	3.4
14	4.2	4.9	4.4	3.8	3.7	10.9	5.0	3.35	3.5	3.1	3.4	3.4
15	4.0	4.8	4.45	3.8	3.55	11.6	4.6	3.4	3.4	3.0	3.4	3.5
16	4.0	4.7	4.35	3.8	3.4	11.5	4.4	3.45	3.3	2.9	3.4	3.6
17	4.0	4.6	4.3	3.85	3.3	8.6	4.4	3.5	3.3	3.2	4.5	3.7
18	3.9	4.5	4.35	3.8	3.2	6.7	6.2	3.45	3.25	3.6	4.55	3.8
19	3.9	4.4	4.4	3.7	3.1	5.1	5.8	3.45	3.2	3.7	4.5	3.9
20	4.0	4.35	4.4	3.65	3.1	4.7	5.2	3.5	3.1	3.8	4.55	4.0
21	4.1	4.35	4.45	3.6	3.2	4.6	4.6	3.6	3.1	3.8	4.6	4.1
22	4.8	4.4	4.45	3.55	3.3	4.5	4.2	3.7	3.0	3.7	4.7	4.25
23	6.8	4.45	4.45	3.5	3.4	4.35	4.0	3.8	3.0	3.3	4.6	4.4
24	10.3	4.45	4.5	3.45	3.7	4.3	3.9	4.1	2.9	3.2	4.5	4.6
25	10.9	4.4	4.5	3.4	4.1	4.1	3.8	4.5	2.9	3.0	4.4	4.7
26	8.0	4.3	4.5	3.35	4.4	3.9	3.7	4.3	3.0	3.1	4.4	4.6
27	6.5	4.2	4.45	3.3	4.5	3.65	3.6	4.2	3.2	3.2	4.35	4.5
28	6.0	4.15	4.45	3.25	4.55	3.5	3.6	4.0	3.35	3.2	4.3	4.3
29	5.5		4.4	3.2	4.6	3.4	3.55	3.85	3.5	3.3	4.3	4.2
30	5.3		4.35	3.15	4.4	3.6	3.5	3.6	3.5	3.2	4.3	4.1
31	5.1		4.3		3.9		3.4	3.9		3.2		4.1

Rating table for Ichawaynochaway Creek at Milford, for 1905-6.

Gage height	Dis-charge						
<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>
2.40	170	3.30	540	4.20	1,120	6.00	2,800
2.50	200	3.40	595	4.30	1,200	7.00	3,800
2.60	235	3.50	650	4.40	1,280	8.00	4,800
2.70	270	3.60	710	4.50	1,360	9.00	5,800
2.80	310	3.70	770	4.60	1,445	10.00	6,800
2.90	350	3.80	835	4.70	1,530	11.00	7,800
3.00	395	3.90	900	4.80	1,620		
3.10	440	4.00	970	4.90	1,710		
3.20	490	4.10	1,045	5.00	1,800		

NOTE.—The above table is based on ten discharge measurements made during 1905-1907 and is not well defined.

Monthly discharge of Ichawaynochaway Creek at Milford, for 1905-6.


Month	Discharge in second-feet		
	Maximum	Minimum	Mean
1905			
September.....	395	185	270
October.....	770	395	539
November.....	710	395	516
December.....	2,800	350	1,130
1906			
January.....	7,700	900	2,190
February.....	2,300	1,080	1,500
March.....	2,200	970	1,310
April.....	1,200	465	814
May.....	3,100	440	1,110
June.....	8,400	490	1,840
July.....	3,000	595	1,150
August.....	1,360	490	703
September.....	1,280	350	742
October.....	1,620	350	711
November.....	1,530	490	913
December.....	1,530	595	976
The year.....	8,400	350	1,160

NOTE.—Values for 1905 and 1906 good.

MISCELLANEOUS DISCHARGE MEASUREMENTS IN APALACHICOLA RIVER DRAINAGE BASIN

Beaverdam Creek.—This stream is a tributary of Soque River, entering from the right. A measurement was made May 13, 1904, from the bridge about 1 mile from Clarkesville, on the road to Nacoochee, Ga. The bench mark is the top of the brace from hand rail to large birch on the upper side of the bridge at the right bank, 12.00 feet above the datum of the gage.

Width, 22 feet; area, 12 square feet; mean velocity, 1.50 feet per second; gage height, 0.45 foot; discharge, 18 second-feet.



TOCCOA FALLS, HABERSHAM COUNTY, GEORGIA.



Big Potato Creek.—Before the section now adopted as a regular bench-mark station was found, two measurements of Big Potato Creek were made at the covered wagon bridge, $2\frac{1}{2}$ miles from Thomaston, just below the Macon and Birmingham Railroad trestle. The bench mark is the top of the downstream lower stringer at sounding point 80. The elevation above gage zero is 15.00 feet.

January 15, 1904: Width, 82 feet; area, 188 square feet; mean velocity, 0.85 foot per second; gage height, 3.30 feet; discharge, 160 second-feet.

March 31, 1904: Width, 72 feet; area, 175 square feet; mean velocity, 0.74 foot per second; gage height, 3.25 feet; discharge, 130 second-feet.

Blue Spring.—This spring is of considerable local note. It is about one-half mile from the left bank of Flint River and about 4 miles below Albany, on the county road leading to Hardaway. Measurements were made from the foot log over the outlet of the main spring as follows:

April 19, 1904: Width, 25 feet; area, 45 square feet; mean velocity, 3.00 feet per second; gage height, 3.29 feet; discharge, 135 second-feet.

September 23, 1904: Width, 28 feet; area, 30 square feet; mean velocity, 1.47 feet per second; gage height, 2.85 feet; discharge, 44 second-feet.

November 16, 1904: Width, 22 feet; area, 21 square feet; mean velocity, 1.24 feet per second; gage height, 2.77 feet; discharge, 26.4 second-feet.

April 26, 1905: Width, 33 feet; area, 30 square feet; mean velocity, 2.30 feet per second; discharge, 69 second-feet.

Buck Creek.—This stream enters Flint River from the right about 1 mile west of Montezuma, Ga. A measurement was made August 23, 1905, at an old tramroad trestle about 1 mile above the mouth of the creek. The bench mark is the top of the upstream end of the cap of the first bent from the left edge of the stream; elevation, 12.00 feet above the datum of the assumed gage.

Width, 49 feet; area, 118 square feet; mean velocity, 1.42 feet per second; gage height, 2.20 feet; discharge, 167 second-feet.

Chattahoochee River.—A measurement was made September 25, 1905, from a boat held by cable stretched across the channels of the river about 8 miles upstream from Columbus and about $1\frac{1}{2}$ miles above the mouth of Standingboy Creek. The bench mark is the top of a large wire nail which is driven into the base of an ash tree which stands about 25 feet below Narramore's spring branch; elevation, 5.00 feet above the datum of the assumed gage.

Width, 282 feet; area, 1,150 square feet; mean velocity, 0.98 foot per second; gage height, 1.75 feet; discharge, 1,125 second-feet.

Chickasawhatchee Creek.—A measurement was made August 26, 1905, at McRainey Bridge, about 10 miles west of Newton, Ga. The initial point for soundings is the end of the bridge at the left bank, downstream side. The bench mark is the top of the downstream end of the middle bent of the bridge; elevation, 12.50 feet above the datum of the assumed gage.

Width, 35 feet; area, 38 square feet; mean velocity, 0.92 foot per second; gage height, 0.80 foot; discharge, 35 second-feet.

Coolawhahee Creek.—A measurement was made August 28, 1905, from the downstream side of a wooden wagon bridge about 1 mile north of Newton, Ga. The bench mark is the top of the downstream end of the floor plank at a point 1 foot to the left of the center post; elevation, 11.50 feet above the datum of the assumed gage.

Width, 23 feet; area, 24 square feet; mean velocity, 1.62 feet per second; gage height, 0.70 foot; discharge, 25.5 second-feet.

Deep Creek.—This stream is a tributary of Soque River. A measurement was made May 13, 1904, from the wooden bridge on Burton road, about 3 miles from Clarkesville.

Width, 25 feet; area, 26 square feet; mean velocity, 1.58 feet per second; discharge, 41 second-feet.

Elkins Creek.—Measurements were made during 1905 at a wooden wagon bridge 1 mile north of Thunder, Ga., about 200 feet below a small gristmill. As the flow at low water depends on the operation of the mill, the measured discharges do not give the natural flow of the stream. The bench mark is a notch and copper nails on the upstream main brace of the truss of the bridge, 8½ feet from the left end of the truss; elevation, 24.00 feet above the datum of the assumed gage.

April 21, 1905: Width, 42 feet; area, 38 square feet; mean velocity, 1.79 feet per second; gage height, 2.07 feet; discharge, 68 second-feet.

September 27, 1905: Width, 28 feet; area, 10 square feet; mean velocity, 0.73 foot per second; gage height, 1.45 feet; discharge, 7.3 second-feet.

Flint River.—A measurement was made September 24, 1904, from the wooden bridge 5 miles from Concord. The bench mark is the top of the first post from the right bank on the downstream side of the bridge, 12.00 feet above the datum of the gage.

Width, 92 feet; area, 184 square feet; mean velocity, 0.43 foot per second; gage height, 2.05 feet; discharge, 79 second-feet.

A measurement was made September 21, 1904, at the highway bridge, about 1 mile northwest of Montezuma. The bench mark is the top of the upstream pier at the left bank, which was 26.15 feet above the water surface. The gage height given is that taken from the temporary gage belonging to the United States Weather Bureau.

Width, 188 feet; area, 1,300 square feet; mean velocity, 0.75 foot per second; gage height, 10.63 feet; discharge, 971 second-feet.

A measurement was made September 20, 1905, at Parkers Bridge, about 7 miles west of Thomaston, Ga. The bench mark is the top of the upstream end of the first floor beam from the middle pier in the first iron span from the right bank; elevation, 35.00 feet above the datum of the assumed gage.

Width, 136 feet; area, 158 square feet; mean velocity, 1.39 feet per second; gage height, 5.00 feet; discharge, 219 second-feet.

Measurements were made at Powells Bridge, 3 miles above the regular gaging station at Woodbury. The bench mark is the top of the right upstream post of first pier from the right bank, 15.00 feet above the datum of the gage.

January 16, 1904: Width, 139 feet; area, 527 square feet; mean velocity, 1.39 feet per second; gage height, 5.88 feet; discharge, 730 second-feet.

September 22, 1904: Width, 116 feet; area, 332 square feet; mean velocity, 0.43 foot per second; gage height, 4.54 feet; discharge, 144 second-feet.

October 4, 1904: Width, 115 feet; area, 314 square feet; mean velocity, 0.34 foot per second; gage height, 4.40 feet; discharge, 107 second-feet.

April 21, 1905: Width, 143 feet; area, 479 square feet; mean velocity, 1.05 feet per second; gage height, 5.47 feet; discharge, 502 second-feet.

Hazel Creek.—This stream is a tributary of Soque River, entering from the left. Measurements were made from the bridge 1 mile from Demorest, on the road to Porter Mills. The bench mark is the top of the upper end of second floor beam from the right bank, 15.00 feet above the datum of the assumed gage.

May 13, 1904: Width, 25 feet; area, 30 square feet; mean velocity, 1.47 feet per second; gage height, 1.85 feet; discharge, 44 second-feet.

September 5, 1905: Width, 27 feet; area, 24 square feet; mean velocity, 1.37 feet per second; gage height, 0.82 foot; discharge, 33 second-feet.

October 23, 1905: Width, 27 feet; area, 20 square feet; mean velocity, 1.15 feet per second; gage height, 0.71 foot; discharge, 23 second-feet.

Ichawaynochaway Creek.—A measurement was made August 26, 1905, from the downstream side of Barnetts Bridge, 10 miles southwest of Newton, Ga. The initial point for soundings is the left end of the bridge approach, downstream side. The bench mark is the top of the downstream end of the second iron crossbeam from the left-bank pier; elevation, 29.50 feet above the datum of the assumed gage.

Width, 84 feet; area, 196 square feet; mean velocity, 2.62 feet per second; gage height, 1.30 feet; discharge, 513 second-feet.

A measurement was made August 26, 1905, from the downstream side of Rentz Bridge, about 12 miles west of Newton, Ga. The initial point for soundings is the end of the downstream hand rail at the left bank. The bench mark is the top of the downstream end of the cap of the bent which stands in the middle of the creek; elevation, 14.50 feet above the datum of the assumed gage.

Width, 76 feet; area, 355 square feet; mean velocity, 1.31 feet per second; gage height, 2.20 feet; discharge, 465 second-feet.

A measurement was made April 27, 1905, at the Central of Georgia Railway bridge, $1\frac{1}{4}$ miles from Williamsburg, Ga. The bench mark is the top of the downstream end of the third bent from the left bank; elevation, 20.00 feet above the datum of the assumed gage.

Width, 92 feet; area, 727 square feet; mean velocity, 1.06 feet per second; gage height, 7.66 feet; discharge, 767 second-feet.

Nickajack Creek.—This stream enters Chattahoochee River from the right, about 1 mile below the old gaging station at Oakdale. Measurements were made by wading about 100 feet above the Southern Railway bridge near Nickajack. The bench mark is the top of the second upstream iron girder from the left end of the bridge, 12 feet from the end, which rests on the center pier, 15.00 feet above the datum of the gage.

October 8, 1904: Width, 16 feet; area 10 square feet; mean velocity, 1.00 foot per second; gage height, 0.92 foot; discharge, 10 second-feet.

October 8, 1904: Width, 16 feet; area, 11 square feet; mean velocity, 1.19 feet per second; gage height, 0.94 foot; discharge, 12.6 second-feet.

North Fork of Peachtree Creek.—A measurement was made May 20, 1904, from the Cheshire Bridge, $1\frac{1}{2}$ miles above the Southern Railway bridge at Armour. The bench mark is the top of a bent

nail in the bottom of the twelfth rail post from the right end of the bridge, 16.00 feet above the datum of the gage.

Width, 11 feet; area, 14 square feet; mean velocity, 1.71 feet per second; gage height, 0.90 foot; discharge, 24 second-feet.

Peachtree Creek.—This stream is a tributary of Chattahoochee River. A measurement was made May 20, 1904, from the Southern Railway bridge at Armour. The bench mark is the top of the middle stringer at its center on the downstream side of the bridge, 15.00 feet above the datum of the gage.

Width, 27 feet; area, 27 square feet; mean velocity, 1.22 feet per second; gage height, 0.17 foot; discharge, 33 second-feet.

Measurements were made at the wagon bridge 1 mile north of Brookwood, on the Peachtree road, and 6 miles north of Atlanta, Ga. The bench mark is the top of the iron plate on the first upright from the right end of the bridge, downstream side, 28.00 feet above the datum of the gage.

April 9, 1904: Width, 44 feet; area, 37 square feet; mean velocity, 1.54 feet per second; gage height, 1.12 feet; discharge, 57 second-feet.

May 20, 1904: Width, 43 feet; area, 25 square feet; mean velocity, 1.52 feet per second; gage height, 0.68 foot; discharge, 38 second-feet.

Peavine Creek.—This stream is the South Fork of Peachtree Creek. A measurement was made May 20, 1904, from the wooden bridge on the Cheshire Bridge road, about 1 mile east of Armour, Ga. The bench mark is the top of the head of the upper bolt used to bolt the second rail post from the right end of the bridge to the stringer at the lower side of the bridge. Its elevation is 16.00 feet above the datum of the gage.

Width, 14 feet; area, 13 square feet; mean velocity, 1.23 feet per second; gage height, 0.85 foot; discharge, 16 second-feet.

Red Oak Creek.—This stream enters Flint River from the right, 3 miles above the regular gaging station on Flint River near Woodbury, Ga. Measurements were made at a wooden wagon bridge about 1 mile above the mouth of the creek. The bench mark is the top of the first post from the right-bank edge, downstream side, 15 feet from a large white-oak tree; elevation, 20.00 feet above the datum of the assumed gage.

January 16, 1904: Width, 68 feet; area, 134 square feet; mean velocity, 1.24 feet per second; gage height, 4.12 feet; discharge, 166 second-feet.

October 4, 1904: Width, 18 feet; area, 27 square feet; mean velocity, 0.68 foot per second; gage height, 2.65 feet; discharge, 18 second-feet.

September 27, 1905: Width, 32 feet; area, 12 square feet; mean velocity, 0.83 foot per second; gage height, 2.25 feet; discharge, 10 second-feet.

May 29, 1906: Width, 62 feet; area, 157 square feet; gage height, 3.31 feet; discharge, 75 second-feet.

Rottenwood Creek.—This stream enters Chattahoochee River from the right. Measurements were made by wading at a point about 200 feet above the old Thornton dam, near Vinings, 2 miles above the mouth of the creek. The creek was believed to be at its lowest stage. The bench mark is a nail driven into rock on the right bank at the measuring section, marked "B. M." Its elevation is 3.00 feet above the datum of the gage.

October 4, 1904: Width, 9 feet; area, 6 square feet; mean velocity, 0.84 foot per second; gage height, 0.26 foot; discharge, 4.8 second-feet.

October 4, 1904: Width, 9 feet; area, 6 square feet; mean velocity, 0.82 foot per second; gage height, 0.26 foot; discharge, 4.9 second-feet.

October 4, 1904: Width, 9 feet; area, 6 square feet; mean velocity, 0.72 foot per second; gage height, 0.25 foot; discharge, 4.3 second-feet.

Soque River.—Measurements were made from Wall's bridge, 2½ miles above Clarkesville. The bench mark is the top of a nail driven into a large leaning birch tree about 20 feet above the bridge on the left bank, 6.00 feet above the datum of the gage.

March 17, 1904: Width, 36 feet; area, 65 square feet; mean velocity, 1.83 feet per second; gage height, 1.35 feet; discharge, 119 second-feet.

March 17, 1904: Width, 36 feet; area, 63 square feet; mean velocity, 1.82 feet per second; gage height, 1.35 feet; discharge, 115 second-feet.

May 13, 1904: Width, 36 feet; area, 62 square feet; mean velocity, 1.92 feet per second; gage height, 1.45 feet; discharge, 119 second-feet.

Measurements were made at McHalister's bridge, about 7 miles from Cornelia and 1 mile above the mouth of the river. The bench mark is the top of the downstream end of the first wooden floor beam from the left bank, 22.00 feet above the datum of the gage.

March 18, 1904: Width, 74 feet; area, 152 square feet; mean velocity, 1.62 feet per second; gage height, 1.85 feet; discharge, 246 second-feet.

July 16, 1904: Width, 72 feet; area, 88 square feet; mean velocity, 1.47 feet per second; gage height, 1.25 feet; discharge, 130 second-feet.

Sweetwater Creek.—This stream enters Chattahoochee River from the right below the old station at Oakdale, Ga. A measurement was made March 15, 1904, at Adair's bridge, 2 miles north of Lithia Springs, and above the regular station on Sweetwater Creek near Austell, Ga. The bench mark is the top of the downstream end of the cap of first wooden bent from the left end of the bridge, 10.00 feet above the datum of the gage.

Width, 66 feet; area, 295 square feet; mean velocity, 1.37 feet per second; gage height, 1.50 feet; discharge, 404 second-feet.

A measurement was made March 15, 1904, at Ferguson's mill bridge, 5 miles from Austell. The bench mark is a nail driven into the river side of a birch tree on the right bank 12 feet below the bridge, 5.00 feet above the datum of the gage.

Width, 129 feet; area, 484 square feet; mean velocity, 1.67 feet per second; gage height, 1.50 feet; discharge, 807 second-feet.

Warm Springs.—These springs are located one-half mile from Warm Springs, Ga., a station on the Southern Railway. Two discharge measurements were made March 10, 1905, about 300 feet below the springs and about 75 feet above the mouth of the branch, which is formed by the united flow of the several springs. April 20, 1905, two measurements were made about 6 feet below the end of the stone walls at the outlet from the bath house.

March 10, 1905: Width, 5 feet; area, 2.8 square feet; mean velocity, 1.14 feet per second; discharge, 3.2 second-feet.

April 20, 1905: Width, 4 feet; area, 1.52 square feet; mean velocity, 0.97 foot per second; discharge, 1.47 second-feet.

April 20, 1905: Width, 2.6 feet; area, 2.12 square feet; mean velocity, 0.69 foot per second; discharge, 1.48 second-feet.

White Oak Creek.—This stream enters Flint River from the right, about 13 miles above the regular gaging station on Flint River at Woodbury, Ga. A measurement was made March 29, 1904, at the wagon bridge one-half mile west of Warnersville. The bench mark is the top of the first post on the downstream side of the bridge, 13.00 feet above the datum of the gage.

Width, 38 feet; area, 163 square feet; mean velocity, 0.71 foot per second; gage height, 1.25 feet; discharge, 115 second-feet.

A measurement was made March 29, 1904, at the double bridges one-half mile from Riverview. The bench mark is the top of the first post, 9.00 feet above the datum of the gage.

Width, 61 feet; area, 222 square feet; mean velocity, 0.50 foot per second; gage height, 2.36 feet; discharge, 112 second-feet.

Whitewater Creek.—This stream enters Flint River from the right. A measurement was made August 31, 1905, from the downstream side of a wooden highway bridge, locally known as the Lower Whitewater Bridge, about 4 miles northwest of Montezuma, Ga. The bench mark is the top of the downstream end of the cap of the third bent from the right bank; elevation, 12.00 feet above the datum of the assumed gage.

Width, 71 feet; area, 275 square feet; mean velocity, 0.94 foot per second; gage height, 2.14 feet; discharge, 260 second-feet.

RIVER SURVEYS IN APALACHICOLA RIVER DRAINAGE BASIN.

CHATTAHOOCHEE RIVER.^a

The elevations along Chattahoochee River are based on the following surveys:

The portion from Columbus to West Point was surveyed in August, 1902, by W. E. Hall, levelman, under the direction of B. M. Hall, United States Geological Survey. The portion from West Point to Franklin was surveyed in 1899 by the Corps of Engineers, United States Army. The portion from Franklin to Oakdale was surveyed in 1903 by Joseph Palmer, levelman, under the direction of Fred A. Franck, United States Geological Survey. The elevations along this part of the stream are based on an aluminum tablet at the Washington street entrance to the State capitol building at Atlanta, marked "1050 M. C." The portion from Oakdale to the mouth of Chestatee River was surveyed in 1902 by Felder Furlow, levelman, under the direction of B. M. Hall, United States Geological Survey. The elevations between the mouth of Chestatee

^a For survey of Chattahoochee River from junction with Flint River to Columbus, Ga., see Report of Chief of Engineers, U. S. A., 1872, pp. 584, 623; and Report of Chief of Engineers, U. S. A., 1873, pp. 699-700.

River and Nacoochee were determined in 1903 by Joseph Palmer, levelman, under the direction of F. A. Franck, field assistant, United States Geological Survey. These elevations are based on an aluminum tablet at Nacoochee, marked "1439 Atlanta," in the ledge of rock 200 feet west of ford of Chattahoochee River, the elevation of which is now accepted as 1,348.259 feet above main sea level. The adjustment of this line was accomplished in conjunction with leveling on the Chestatee and Soque rivers, tied at Willow and Clarkesville, and by an extra check at Pole, to primary level circuits, and accords with the 1903 adjustment of the precise level net.

In order to give a continuous profile of the river, the levels of these several surveys have been adjusted to accord with the elevations determined for the portion between Franklin and Oakdale. It is not expected, however, that the bench marks of one survey will exactly accord with those of another.

Elevations on Chattahoochee River from Columbus up to Nacoochee.

Distance	Description of points	Elevation above sea level
<i>Miles</i>		<i>Feet</i>
0.00	Tail water 100 feet below Eagle and Phoenix dam tailrace.....	190
0.02	Above Eagle and Phoenix dam, water surface.....	216.2
0.74	100 feet below City Mills dam, water surface.....	216.6
0.75	Above City Mills dam, water surface.....	225
2.06	100 feet below Columbus Power Company's dam, water surface.....	226
2.08	Top of Columbus Power Company's dam, water surface.....	226
2.6	Bench mark on solid rock on east bank at lower land line of Chattahoochee Falls Company's property.....	270.75
2.8	Upper end of Columbus Power Company's backwater from dam, water surface.....	266
3.29	600 feet below old Clapp factory, water surface.....	276
3.44	Above old Clapp factory, water surface.....	300.3
3.56	Mouth of Roaring Creek (from Georgia bank), water surface.....	300.6
3.97	Water at upper line of Chattahoochee Falls Company's property, water surface.....	305.3
5.54	Bench mark on root of small water-oak tree on east bank of river, 400 feet below mouth of Standingboy Creek.....	321.6
5.62	Mouth of Standingboy Creek, water surface.....	315.6
6.49	Upper end of Narramores Island, water surface.....	316.1
7.21	Bench mark on mulberry tree, 40 feet below wire fence between Narramore and Biggers.....	328.71
7.21	Land line between Narramore and Biggers, water surface.....	317.6
7.55	Bench mark on large water oak 10 feet below land line between J. L. and B. A. Biggers.....	332.64
7.55	Land line between J. L. and B. A. Biggers, water surface.....	318.2
8.06	Ford to Island, water surface.....	319.7
8.82	Water surface.....	323.4
9.11	Opposite mouth of creek from west bank, water surface.....	323.5
10.07	Lower end of Allie Bigger's Island, water surface.....	323.6
10.26	Land line between Allie Biggers and Geo. Ogletree, water surface.....	323.7
10.87	Upper end of Allie Bigger's Island, water surface.....	324.7
11.08	Bench mark on large maple on bank opposite foot of shoals on Ogletree's land.....	340.52
11.08	Foot of shoals on Ogletree's land, water surface.....	326.5
11.82	Water surface.....	330.5
11.4	Bench mark on large ironwood tree near water.....	337.95
11.4	Water surface.....	335.3
11.51do.....	334.3
12.14	Bench mark on large dead cedar 10 feet below mouth of Cowpen Creek.....	351.19
12.14	Mouth of Cowpen Creek, water surface.....	345.9
12.51	Water surface.....	349.4
12.67do.....	350.1
12.69do.....	351.1
13.44	Bench mark on pine tree 75 feet below mouth of Mulberry Creek.....	367.23
13.44	Mouth of Mulberry Creek, water surface.....	362.8
14.54	Water surface.....	366.5
14.9do.....	368.2
15.53do.....	375.9
16.91	Near mouth of Sue Slaton Branch, water surface.....	390.6
17.5	Bartlett's Ferry, water surface.....	394.7
17.63	Water surface.....	400
18.2	Mouth of Mossy Creek, water surface.....	411.8
19.31	Lower end of Harrington Island, water surface.....	431
19.77	Water surface.....	442.5
19.86	Lower end of Phipps Island, water surface.....	443.6
20.85	Water surface.....	461.3
21.08do.....	467.1
21.45	Lower end of Hargetts Island, water surface.....	475.8
22.33	Mouth of Mountain Oak Creek, water surface.....	480.7
22.39	Water surface.....	482.5
23.16	Foot of shoals, water surface.....	482.6
23.54	Blantons Ferry, water surface.....	484.1
24.37	Houstons Ferry, water surface.....	491.3
28.12	Below River View dam, west side, water surface.....	518
28.14	Above River View dam, water surface.....	529
30.17	Below dam at Langdale mills, water surface.....	532
30.2	Top of dam or water above dam.....	542
33.99	Water surface.....	550
35.0	West Point milepost 35, from Franklin.....	565.14
35.0	West Point, zero of gage.....	549.46
35.0	West Point, wagon bridge, water surface (gage height, 2.0 feet).....	561.5
35.5	Mouth of Oseligee Creek, water surface.....	555.9
36.0	Milepost 37, from Franklin.....	571.15
36.0	Water surface.....	556.6
37.0	Milepost 36, from Franklin.....	572.68
37.0	Water surface.....	556.9
37.6	Water at mouth of Anderson Creek.....	557.6
38.0	Milepost 35, from Franklin.....	577.94

APALACHICOLA DRAINAGE BASIN, RIVER SURVEYS 307

Elevations on Chattahoochee River from Columbus up to Nacoochee—Continued.

Dis- tance	Description of points	Elevation above sea level
<i>Miles</i>		<i>Feet</i>
38.0	Water surface.....	558.2
38.3	Opposite mouth of Maple Creek, east.....	558.9
39.0	Milepost 34, from Franklin.....	571.95
39.0	Water surface.....	560.8
40.0	Milepost 33, from Franklin.....	575.60
40.0	Head of Henderson Island, water surface.....	561
40.3	Potts Island, water surface.....	562.5
41.0	Milepost 32, from Franklin.....	574.38
41.0	Water surface.....	564.6
42.0	Milepost 31, from Franklin.....	579.48
42.0	Water surface.....	568.1
42.2	Lower end Hughleys Island, water surface.....	569.7
43.0	Milepost 30, from Franklin.....	582.36
43.0	Upper end Hughleys Island, water surface.....	572.8
43.5	Mouth of Wohadkee Creek, west side, water surface.....	577.1
44.0	Milepost 29, from Franklin.....	591.71
44.0	Water surface.....	576.3
44.5	Hunters old ferry, water surface.....	576.9
45.0	Milepost 28, from Franklin.....	593.43
45.0	Water surface.....	576.9
45.3	Double Mills bridge, water surface.....	576.9
46.0	Milepost 27, from Franklin.....	592.51
46.0	Water surface.....	579.9
47.0	Milepost 26, from Franklin.....	590.42
47.0	Water surface.....	580
48.0	Milepost 25, from Franklin.....	593.61
48.0	Water surface.....	580.7
48.5	Mouth of Whitewater Creek, water surface.....	580.8
49.0	Milepost 24, from Franklin.....	595.51
49.0	Water surface.....	581.2
50.0	Milepost 23, from Franklin.....	597.48
50.0	Water surface.....	583
50.5	McGees Bridge, water surface.....	583.1
51.0	Milepost 22, from Franklin.....	596.29
51.0	Opposite mouth of Yellow Jacket Creek, east side, water surface.....	583.4
51.3	Lower end of Birdsday Island, water surface.....	584.1
51.8	Upper end of Birdsday Island, water surface.....	586.6
51.9	Lower end of Reids Island, water surface.....	586.9
52.0	Milepost 21, from Franklin.....	603.06
52.0	Water surface.....	586.9
52.8	Upper end of Reids Island, water surface.....	587
53.0	Milepost 20, from Franklin.....	600.75
53.0	Water surface.....	589.9
54.0	Milepost 19, from Franklin.....	608.55
54.0	Water surface.....	591.3
54.3	Head of shoals, water surface.....	592.8
55.0	Milepost 18, from Franklin.....	608.34
55.0	Water surface.....	593.7
55.3do.....	594
56.0	Milepost 17, from Franklin.....	602.29
56.0	Water surface.....	595.4
56.3	Mouth of Wolf Creek, water surface.....	595.7
57.0	Milepost 16, from Franklin.....	613.71
57.0	Water surface.....	596.2
57.9	Moodys Bridge, water surface.....	596.8
58.0	Milepost 15, from Franklin.....	615.80
58.0	Water surface.....	597.1
59.0	Milepost 14, from Franklin.....	615
59.2	Mouth of Haralson Creek, water surface.....	599.4
59.9	Lower end of Swanson Island, water surface.....	599.6
60.0	Milepost 13, from Franklin.....	616.99
60.0	Water surface.....	599.9
60.5	Upper end of Swanson Island, water surface.....	600.8
61.0	Milepost 12, from Franklin.....	618.30
61.0	Water at head of Swanson Shoals, water surface.....	605.2
61.4	Water surface.....	605.8
62.0	Milepost 11, from Franklin.....	622.13
62.0	Water surface.....	607.3
62.5do.....	607.7
63.0	Milepost 10, from Franklin.....	630.21
63.0	Water surface.....	608
64.0	Milepost 9, from Franklin.....	627.71
64.0	Water surface.....	608.2
64.1	Opposite mouth of Potato Creek, east side, water surface.....	608.7
64.5	Philpots Ferry, water surface.....	609.2

Elevations on Chattahoochee River from Columbus up to Nacoochee—Continued.

Distance	Description of points	Elevation above sea level
<i>Miles</i>		<i>Feet</i>
64.3	Opposite mouth of New River, from east side, water surface.....	609.3
65.0	Milepost 8, from Franklin.....	634.66
65.0	Water surface.....	609.6
65.5do.....	609.6
66.0	Milepost 7, from Franklin.....	628.50
66.0	Water surface.....	610.4
66.2	Foot of Jackson Shoals, water surface.....	610.4
66.7	Mouth of Brushy Creek, from west side, water surface.....	611.5
67.0	Milepost 6, from Franklin.....	628.18
67.0	Water surface.....	613
67.7	Mouth of branch, water surface.....	618
67.8	Head of Jacksons Shoals, water surface.....	618.7
68.0	Milepost 5, from Franklin.....	629.75
68.0	Water surface.....	618.7
69.0	Milepost 4, from Franklin.....	631.45
69.0	Foot of Linville Shoals, water surface.....	618.7
69.4	Head of Linville Shoals, water surface.....	620
70.0	Milepost 3, from Franklin.....	637.91
70.0	Water surface.....	620.8
70.6	Mouth of Hillabeehatchee Creek, west side, water surface.....	621.7
71.0	Milepost 2, from Franklin.....	636.01
71.0	Water surface.....	622
71.5do.....	622.4
72.0	Milepost 1, from Franklin.....	636.10
72.0	Water surface.....	623.1
72.4do.....	624.6
72.6do.....	625
73.0	Milepost 0, from Franklin.....	634.86
73.0	Franklin, above bridge, water surface.....	626
73.0	Franklin, rivet on top of left iron pier, east approach, wagon bridge.....	655.17
73.0	Franklin, water surface.....	626
	Franklin, bronze tablet, marked "695 A," in south side of court-house.....	694.742
74.0	Foot of shoal, surface of water.....	627
74.2	Centralhatchee Creek, birch tree opposite mouth.....	633.49
74.2	Water surface.....	628
75.3	Foot of Shoals, water surface.....	628
76.0	Head of Shoal, water surface.....	632
77.0	Foot of shoal, water surface.....	632
77.2	Head of shoal, water surface.....	634
77.3	Foot of shoal, water surface.....	634
78.0	Head of shoal, water surface.....	638
79.0	Bushyhead Shoals, white oak opposite foot.....	648.15
79.0	Water surface.....	638
79.5	Head of Bushyhead Shoals, birch at head of island.....	653.32
79.5	Water surface.....	645
80.0	Head of shoal, water surface.....	658.73
80.0	Water surface.....	650
	Fishtrap Shoal, foot of, water surface.....	648
81.1	Fishtrap Shoal, elm tree on rock bluff opposite center.....	670.26
81.1	Water surface.....	652
81.7	Fishtrap Shoal, head of, water surface.....	657
82.7	Sweet gum, right bank, one-fourth mile below Pink Creek.....	664.97
82.7	Water surface.....	658
83.0	Mouth of Pink Creek, water surface.....	658
84.9	Hollingsworth Ferry, water oak, right bank.....	673.31
84.9	Hollingsworth Ferry, water surface.....	658
86.0	Bench mark on pine.....	678.8
86.0	Water surface.....	659
87.1	Mouth of Yellow Dirt Creek, water surface.....	660
87.3	Sweet gum tree one fourth mile above Yellow-Dirt Creek.....	679.8
87.3	Water surface.....	662
88.0	Browns Ferry, walnut tree, right bank.....	681.96
88.0	Browns Ferry, water surface.....	662
89.0	Birch tree on right bank at mouth of Whooping Creek.....	670.2
89.0	Water surface.....	664
90.4	Foot of small shoal, water surface.....	666
90.45	Head of small shoal, water surface.....	667
91.9	Culpepper Creek, red oak on right bank at mouth.....	678.04
91.9	Water surface.....	667
92.6	Foot of McIntosh Shoal, sweet-gum tree.....	679.49
92.6	Water surface.....	668
93.1	Head of McIntosh Shoal, water surface.....	676
94.1	Houstons Ferry, foot of shoal, catalpa tree.....	684.02
94.1	Water surface.....	677
94.4	Head of Hanson Shoal, water surface.....	678

Elevations on Chattahoochee River from Columbus up to Nacoochee—Continued.

Dis- tance	Description of points	Elevation above sea level
<i>Miles</i>		<i>Feet</i>
95.3	Foot of Friesdell Shoal, water surface	679
95.4	Head of Friesdell Shoal, water surface	680
96.2	Foot of small shoal, water surface	681
96.3	Head of shoal just below Rees Ferry, water surface	682
96.6	Rees Ferry, ash tree, right bank	698.86
96.6	Water surface	682
97.3	Poplar tree, one-half mile below Central of Georgia Railway bridge	699.76
97.3	Water surface	682
97.9	Willow on right bank, 40 feet above Central of Georgia Railway bridge	692.12
97.9	Water surface	684
98.7	Foot of shoals, water surface	684
98.8	Head of shoals below Moores Ferry, water surface	685
99.4	Moores Ferry, large birch, right bank	702.85
99.4	Moores Ferry, water surface	686
100.3	Foot of shoal below Snake Creek, water surface	687
100.5	Willow tree, 100 yards above mouth of Snake Creek	696.72
100.5	Water surface	688
102.0	Water oak opposite lower end of island	703.37
102.0	Water surface	689
102.9	Pine opposite head of island, right bank	709.11
102.9	Water surface	692
104.6	Hutchinson Ferry, maple on right bank, 20 feet from river	709.12
104.6	Hutchinson Ferry, water surface	694
105.9	Foot of Mederis shoal, mouth of Wolf Creek, water surface	698
106.2	White oak, side of rock bluff, right bank	716.81
106.2	Water surface	702
106.6	Head of Mederis Shoal, water surface	704
106.9	Foot of Ballard Shoal, water surface	704
107.1	Head of Ballard Shoals, willow 10 feet from river, right bank	711.13
107.1	Water surface	705
108.4	Jones Ferry, pine tree on left bank	718.6
108.4	Jones Ferry, water surface	706
109.9	Defers Ferry, large birch on left bank	722.92
109.9	Defers Ferry, water surface	709
111.4	Walnut about 2 miles below Big Bear Creek, and near a point opposite mouth of Dog River	725.5
111.4	Water surface	710
112.5	One mile below Big Bear Creek, water surface	711
113.5	Poplar at mouth of Big Bear Creek	780.85
113.5	Water surface	712
114.6	Pumpkintown Ferry, large birch left bank, 15 feet from river	727.94
114.6	Pumpkintown Ferry, water surface	712
116.0	Riverton Ferry, sycamore 10 feet from river on left bank	720.64
116.0	Riverton Ferry, water surface	714
116.3	Mouth of Pea Creek, water surface	714
116.7	Foot of Redmans Shoal, water surface	714
116.8	Head of Redmans Shoal, sycamore on left bank, 10 feet from river	728.58
116.8	Water surface	716
117.4	Brocks Ferry, white oak on left bank, 10 feet from river	730.49
117.4	Brocks Ferry, water surface	716
119.1	One mile below Campbellton Ferry, water surface	718
120.1	Campbellton Ferry, sycamore 10 feet from river, left bank	728.69
120.1	Campbellton Ferry, water surface	719
121.0	Walnut on left bank, one-fourth mile below Camp Creek	741.78
121.0	Water surface	719
121.4	Mouth Camp Creek, ash tree, left bank	736.13
121.4	Water surface	720
123.2	Walnut, on left bank, 70 feet from river	746.29
123.2	Water surface	721
123.7	Water surface	721
125.2	Dupres Ferry, elm tree on left bank	738.09
125.2	Dupres Ferry, water surface	723
126.7	Large walnut on left bank	747.58
126.7	Water surface	725
127.7	Aderholts Ferry, large sycamore opposite mouth of Sweetwater Creek	744.73
127.7	Aderholts Ferry, water surface	726
129.6	Sweet gum, left bank	742.16
129.6	Water surface	727
130.6	Walnut on left bank, just above Buzzard Roost Island	752.9
130.6	Water surface	729
131.6	Walnut on left bank, opposite a point near the mouth of Landers Creek	746.41
131.6	Water surface	730
132.6	Walnut, 40 feet from river, left bank	755.1
132.6	Water surface	732

Elevations on Chattahoochee River from Columbus up to Nacoochee—Continued.

Distance	Description of points	Elevation above sea level
<i>Miles</i>		
133.9	Garretts Bridge, water oak, left bank.....	752.94
133.9	Garretts Bridge, water surface.....	735
134.6	Sycamore, 10 feet from left bank, at old ferry.....	751.35
134.6	Water surface.....	736
135.5	Mouth of Nickajack Creek, water surface.....	736
136.4	Three hundred feet below Mason and Turners Ferry and 200 feet from river, hickory tree, left bank.....	754.38
136.4	Water surface.....	738
137.5	Near mouth of Proctors Creek, willow tree, left bank.....	741.82
137.5	Water surface.....	739
138.0	Oakdale, United States Geological Survey gaging station, water surface (gage 1.7).....	739.5
138.0	Oakdale, zero of gage at Southern Railway bridge.....	737.8
138.6	Water surface.....	740
140.1	White oak, 50 feet from river, 70 feet below mouth of Peachtree Creek.....	763.37
140.1	Mouth of Peachtree Creek, from east bank, water surface.....	742.6
140.6	Mouth of small branch, water surface.....	744.1
141.1	Rock-bluff, east bank, water surface.....	745.1
141.5	Water surface.....	745.7
141.7	Foot of shoals, water surface.....	746.2
141.8	Water surface.....	743.3
142.1	Water surface.....	751.2
142.5	Paces Ferry, willow tree, upper side of east bank landing.....	761
142.5	Paces Ferry, water surface.....	752.7
142.7	Water surface.....	752.9
143.0	Birch tree at mouth of Little Nancy Creek, west bank of river, lower bank of creek.....	768.06
143.0	Water surface.....	754
143.1	Lower end of Long Island (Thornton place), water surface.....	755.2
143.2	Water surface.....	757.3
143.4	Pace's mill site, water surface.....	759.5
143.7	Large ash tree at mouth of Rottenwood Creek, lower side of creek.....	771
143.7	Water surface.....	762
144.0	Opposite mouth of Long Island Creek, water surface.....	764.3
144.2	Water surface.....	764.4
144.4	Sweet-gum tree at "The Narrows".....	765.71
144.4	Water surface.....	770.3
144.6	Water surface.....	772.4
144.8	Water surface.....	776.8
145.0	Water surface.....	780.6
145.5	Powers Ferry, white-oak tree, west bank.....	794.21
145.5	Water surface.....	780.8
146.0	Land line between Power and McKenzie.....	787.2
147.4	Heards Ferry forked ash tree, mouth of Soap Creek, lower bank.....	799.46
147.4	Heards Ferry, water surface.....	790.3
149.1	Johnsons Ferry, large water-oak tree, west landing, downstream side of road. (This is old bench mark marked 118.52).....	806
149.1	Johnsons Ferry, water surface.....	793.3
150.9	Dam site, Bull Sluice water power (dam is being built here), water surface.....	800
151.2	Water surface.....	803.6
151.4	Water surface.....	804.8
151.5	Water surface.....	806.2
152.0	Large red oak, 150 feet from river, and 200 feet below Power's old mill.....	837.66
152.1	Water surface.....	820.4
152.1	Above Power's old mill dam, water surface.....	823.6
152.2	Water surface.....	824.5
152.5	Water surface.....	829.2
152.7	Water surface.....	829.5
152.8	Birch, mouth of Willioe Creek, upper bank.....	836.04
152.8	Water surface.....	831.4
153.6	Water surface.....	835.3
153.9	Large water-oak above mouth of branch.....	842.12
153.9	Mouth of branch, west bank of river, water surface.....	835.9
154.2	Water surface.....	839.1
154.3	Water surface.....	841
154.6	Water surface.....	843.9
154.8	Water surface.....	846.1
155.2	Mouth of Vickers Creek, sweet-gum tree, lower bank of creek.....	851.78
155.2	Water surface.....	849.6
156.7	Near mouth of Seven Creek, water surface.....	852.6
157.0	Foot of Ford Island, water surface.....	855.4
157.1	Water surface.....	857.3

APALACHICOLA DRAINAGE BASIN, RIVER SURVEYS 311

Elevations on Chattahoochee River from Columbus up to Nacoochee—Continued.

Distance	Description of points	Elevation above sea level
<i>Miles</i>		<i>Feet</i>
157.4	Water surface.....	859
157.4	Water surface.....	859.1
157.9	Jetts Ferry root of 4 willows upper side, west landing.....	866.97
157.9	Water surface.....	862
158.7	Water surface.....	862.5
159.2	Water surface.....	862.7
160.5	Nesbits Ferry, large birch, west landing.....	870.65
160.5	Nesbits Ferry, water surface.....	863.2
162.5	Holcombs Ferry, water-oak at west landing, fifty feet from river, upper side of road.....	881.17
162.5	Holcombs Ferry, water surface.....	865.6
163.0	Water surface.....	867.8
163.2	Mouth Holcombs Mill Branch, west side river.....	869.2
163.6	Water surface.....	869.9
164.6	Water surface.....	874
164.9	Foot of Jones Shoals, water surface.....	875.6
165.3	Head of Jones Shoals, water surface.....	880.5
165.35	Jones Ferry, large oak, west landing, 50 feet from river.....	886.5
165.35	Jones Ferry, water surface.....	880.5
166.7	Water surface.....	880.7
167.6	Medlocks Bridge, top of iron tubular pier west bank, down stream.....	906.40
167.6	Medlocks Bridge, water surface.....	880.7
168.0	West landing of McClure or Warsaw Ferry, birch 100 feet from bank.....	897.40
168.0	Water surface.....	882
170.4	Abbotts Ferry, water surface.....	884
171.6	Rogers Ferry, large beech tree, west landing, on downstream side of road.....	894.78
171.6	Rogers Ferry, water surface.....	885.7
174.3	Littles Ferry, west landing, twin persimmon tree 100 feet from bank, on downstream side of road.....	905.35
174.3	Littles Ferry, water surface.....	889.3
176.1	Hutchins Ferry, west landing, large walnut tree 150 feet from bank, on downstream side of road.....	914.69
176.1	Hutchins Ferry, water surface.....	895.6
177.7	Terry's Ferry, sycamore tree at upper side of west landing.....	909.16
177.7	Terry's Ferry, water surface.....	898.8
180.13	Stricklands Bridge, top of stone pier, west bank.....	938.14
180.3	Stricklands Bridge, center of pulley of wire gage (U. S. G. S. gage; height at time, 1.1 foot).....	986.34
180.3	Water surface.....	908.9
180.3	Walnut on edge of road, 75 feet from approach of bridge, west side of river.....	930.84
180.9	Mouth of small branch from west side, water surface.....	905.4
182.4	Parker Ferry (no longer used as ferry), water surface.....	913.4
182.9	Water surface.....	918
183.3	Water surface.....	919.3
183.5	Head Winding Shoals at upper end of island, water surface.....	921.2
184.0	Pirkles Ferry, poplar tree on edge of road near west landing.....	932.18
184.0	Water surface.....	922.8
184.5	Forked hickory tree on Pirkle's upper land line, 50 feet from west bank of river.....	940.33
184.5	Water surface.....	926.9
185.1	Water surface.....	927.5
186.0	Shadburns Ferry, sycamore tree, west landing.....	935.96
186.0	Water surface.....	923.4
189.0	Walnut tree 100 feet west of bank at Light's old ferry place.....	958.46
189.8	Top of cylindrical iron pier, downstream, east bank, wagon bridge opposite Flowery Branch.....	961.48
189.8	Water surface.....	938.5
190.9	Water surface.....	936.5
192.9	Below dam at gristmill, water surface.....	944.4
192.9	Above dam at gristmill, water surface.....	953.2
192.9	Oak tree just above gristmill, on east side of river.....	950.7
192.9	Browns Bridge, water surface.....	953.2
193.5	Near Brown's house, west side of river, water surface.....	953.7
193.8	Mouth of Brown Creek from west side, water surface.....	954
195.4	Near Keiths Bridge, mouth of Chestatee River, nail in root of walnut tree.....	964.37
197.1	Head of shoals above mouth of river, water surface.....	956
199.1	Nail in root of walnut tree, north bank.....	989.71
199.1	Foot of shoals, water surface.....	960
199.1	Head of shoals, water surface.....	963
201.1	Nail in root of large walnut tree at edge of public road opposite small shoal.....	985.61
201.1	Water surface.....	965
201.6	Water surface.....	966
202.2	Iron bridge, nail in root of large walnut tree.....	980.26
202.2	Foot of shoals, water surface.....	967

Elevations on Chattahoochee River from Columbus up to Nacoochee—Continued.

Dis- tance	Description of points	Elevation above sea level
<i>Miles</i>		<i>Feet</i>
202.7	Head of shoals, water surface.....	972
203.7	Thompson Bridge, nail in root of large walnut tree.....	998.36
203.7	Thompson Bridge, water surface.....	977
204.3	Little River, foot of shoals at mouth, water surface.....	978
204.8	Head of shoals, water surface.....	984
205.4	Nail in root of white oak on north side of bluff, 100 yards below North Georgia Electric Company's new dam.....	1,004.04
205.4	Water surface.....	985
206.4	Chattahoochee Park, nail in birch tree on east side of river and at sharp bend.....	1,004.27
	Foot of shoals, water surface.....	996
	Head of shoals, water surface.....	1,010
207.6	Spike in root of large oak tree near small store building near Gainesville.....	1,028.32
207.6	Bridge, water surface.....	1,011
208.6	Nail in root of willow on south bank 6 feet from water.....	1,014.94
208.6	Water surface.....	1,012
209.3	Foot of shoals, water surface.....	1,012
	Head of shoals, water surface.....	1,014
211.6	Clarks Bridge, east side of river, large maple tree, nail in root of.....	1,039.81
211.6	Clarks Bridge, water surface.....	1,017
212.6	Small bluff, north side of river, poplar tree, nail in root of.....	1,045.27
212.6	Water surface.....	1,020
214.6	Red-oak tree, nail in root of.....	1,043.29
	Foot of shoals, water surface.....	1,025
214.9	Foot of shoals, water surface.....	1,028
	Head of shoals, water surface.....	1,032
216.6	Savage Ferry, nail in notch of oak post.....	1,051.3
216.6	Water surface.....	1,034
217.6	Left bank of river, nail in root of birch tree.....	1,050.46
217.6	Water surface.....	1,037
219.3	North bank of river, nail in root of water oak tree.....	1,046.76
219.3	Water surface.....	1,038
219.3	Head of shoals, water surface.....	1,040
220.3	Seven Island Shoals, opposite foot of, large poplar tree, nail in root of.....	1,066.94
	Foot of shoals, water surface.....	1,040
	Head of shoals, water surface.....	1,044
221.0	Flat Creek, 1 mile above mouth of, nail in root of poplar tree.....	1,045.84
221.0	Water surface.....	1,045
221.9	Lulu Bridge, 60 feet below, on north bank of river, red oak tree, nail in root of.....	1,065.6
221.9	Water surface.....	1,049
224.2	Walnut tree, in large open bottom, left bank of river, nail in root of.....	1,076.23
224.2	Water surface.....	1,053
225.2	Belton Bridge, 100 yards below, right bank of river, walnut tree, nail in root of.....	1,076.64
225.2	Water surface.....	1,056
227.2	Right bank of river, pine tree, nail in root of.....	1,092.99
227.2	Foot of shoals, water surface.....	1,061
227.3	Head of shoals, water surface.....	1,069
228.0	Nail in root of birch tree.....	1,085.79
228.0	Water surface.....	1,070
	Foot of shoals, water surface.....	1,071
	Head of shoals, water surface.....	1,073
228.5	Head of shoals, on side of bluff, large pine opposite, nail in root of.....	1,092.33
228.5	Water surface.....	1,082
228.6	Harrisons Shoals, foot of, water surface.....	1,084
229.5	Harrisons Shoals, opposite, nail in root of oak tree.....	1,101.7
229.5	Harrisons Shoals, water surface.....	1,087
229.5	Harrisons Shoals, head of, mouth of Mossy Creek, water surface.....	1,087
229.6	Mountain Island Shoals, foot of, water surface.....	1,088
	Head of shoals, water surface.....	1,096
229.9	Head of shoals opposite, nail in root of white oak.....	1,109.78
230.6	Foot of shoals, water surface.....	1,101
230.6	Head of shoals, water surface.....	1,106
230.6	Perkins Shoals, opposite foot of, nail in root of water oak.....	1,113.68
230.6	Perkins Shoals, foot of, water surface.....	1,107
230.6	Perkins Shoals, head of, water surface.....	1,113
232.7	Foot of shoals, water surface.....	1,115
	Head of shoals, water surface.....	1,123
232.8	Head of shoals, north bank of river, opposite, nail in root of black gum tree.....	1,127.76
233.6	Foot of shoals, water surface.....	1,127
233.6	Head of shoals, water surface.....	1,130
233.7	Duncans Bridge, 30 feet below, nail in red oak tree.....	1,148.9
233.8	Foot of shoals, water surface.....	1,131
234.0	Head of shoals, water surface.....	1,135
234.0	Head of shoals, opposite, nail in root of water oak.....	1,155.41
234.7	Soque River, south bank, at mouth, nail in root of birch tree.....	1,147.82
234.7	Water surface.....	1,137

Elevations on Chattahoochee River from Columbus up to Nacoochee—Continued.

Distance	Description of points	Elevation above sea level
<i>Miles</i>		<i>Feet</i>
234.7	Soque River, mouth of, in forks of river, nail in root of pine stump	1,148.86
235.0	Head of shoals, water surface	1,144
235.2	Foot of shoals, water surface	1,149
235.4	Head of shoals, water surface	1,159
235.4	Head of shoals, opposite, on west bank of river, nail in root of red oak	1,165.2
235.9	Long Shoals, head of, water surface	1,178
236.2	Foot of shoals, water surface	1,178
	Head of shoals, water surface	1,216
237.2	Head of shoals, root of hickory tree	1,222.10
237.7	Irwins Bridge, 10 feet below, left bank of river, nail in root of poplar tree	1,223.37
237.7	Water surface	1,216
238.0	Irwins Bridge, just above, water surface	1,222
238.6	Head of shoals, water surface	1,228
238.9	Foot of shoals, water surface	1,229
	Head of shoals, water surface	1,242
238.9	Blue Creek, water surface	1,243
239.0	Blue Creek, 100 yards below mouth of, nail in root of red oak tree	1,256.09
239.6	Amos Ford, on west bank, large birch tree, nail in root of	1,256.09
239.6	Amos Ford, water surface	1,244
239.9	Water surface	1,247
240.4	Head of shoals, water surface	1,250
241.4	Allens Bridge, west end of, red oak tree, nail in root of	1,266.49
241.4	Allens Bridge, water surface	1,256
	Head of shoals, water surface	1,259
242.2	Foot of shoals, water surface	1,260
	Head of shoals, water surface	1,263
242.2	Head of shoals, opposite, nail in root of birch tree	1,264.18
242.7	Foot of shoals, water surface	1,271
	Head of shoals, water surface	1,274
242.9	Shoals, opposite, head of, nail in root of pine tree	1,280.73
243.9	Foot of shoals, water surface	1,276
244.4	Head of shoals, water surface	1,280
244.4	Shoals, red oak, opposite head of, nail in root of	1,285.53
244.6	Sharp bend of river, water oak tree, nail in root of	1,304.53
	Water surface	1,292
245.9	Suspension footbridge, poplar tree at, nail in root of	1,305.97
245.9	Water surface	1,297
247.2	Foot of shoals, water surface	1,299
	Head of shoals, water surface	1,306
248.4	Sautee Creek, near mouth of, in Nacoochee Valley, water surface	1,309
250.4	Sautee Creek, ford near mouth, water surface	1,389
250.4	Nacoochee post-office, 200 feet west of ford at Chattahoochee River, 6 feet above surface of road, on ledge of rock aluminum tablet marked "1349 Atlanta"	1,348.269

SURVEY OF SOQUE RIVER:

The elevations in the following list are based on an aluminum table at the north side of east entrance to the court-house at Clarkesville, marked "1372 ATLANTA," the elevation of which is accepted as 1,371.991 feet above mean sea level in accord with the 1903 adjustment of the precise level net.

The leveling was done by Joseph Palmer, levelman, in September, 1903, under the direction of F. A. Franck, field assistant, United States Geological Survey.

Elevations on Soque River from mouth up to Clarkesville.

Dis- tance	Description of points	Elevation above sea level
<i>Miles</i>		<i>Feet</i>
0.0	Soque River, mouth, at junction with Chattahoochee River, nail in root of birch tree, on south bank.....	1,147.82
0.0	Soque River, mouth of, water surface.....	1,137
1.8	McAllister's Bridge, near north end, nail in root of white oak tree.....	1,156.30
1.6	McAllister's Bridge, water surface.....	1,142
	Foot of shoals.....	1,142
	Head of shoals.....	1,149
4.0	New Bridge, hickory on north bank, nail in root.....	1,171.71
4.0	New Bridge, water surface.....	1,152
4.1	Foot of shoals, water surface.....	1,153
	Head of shoals, water surface.....	1,156
4.7	Foot of shoals, water surface.....	1,156
	Head of shoals, water surface.....	1,162
5.6	Foot of shoals, water surface.....	1,166
5.7	Head of shoals, water surface.....	1,181
6.1	Porters mills, foot of Porter Shoals, water surface.....	1,189
6.1	Head of Porters Shoals, water surface.....	1,237
6.1	Near north end of wagon bridge, red oak tree, nail in root of.....	1,246.13
6.2	Foot of upper shoals, water surface.....	1,238
	Head of upper shoals, water surface.....	1,253
6.3	200 yards above factory, near river, on root of water oak.....	1,262.75
7.3	Foot of shoals, water surface.....	1,261
7.3	Left bank of river, nail in root of sycamore tree.....	1,287.37
7.3	Water surface.....	1,284
8.8	Clarkesville, Habersham County courthouse, on north side of east entrance aluminum tablet marked "1372 ATLANTA.".....	1,371.991
8.8	Clarkesville, water surface.....	1,289

SURVEY OF CHESTATEE RIVER.

The elevations in the following list are based upon a bronze tablet 2.5 miles north of Willow, in rock on the west side of the river at a fork of the road, marked "1529 ATLANTA," the elevation of which is accepted as 1,528.649 feet above mean sea level in accord with the 1903 adjustment of the precise level net.

The leveling was done by Joseph Palmer, levelman, in October, 1903, under the direction of F. A. Franck, field assistant, United States Geological Survey.

Elevations on Chestatee River from mouth to Willow.

Distance	Description of points	Elevation above sea level
Miles		Feet
0.0	Bench mark, nail in root of walnut tree near Keiths Bridge mouth of Chestatee River, near Chestatee	964.87
1.1	Bench mark, nail in red-oak tree, 40 feet from east bank, near mouth of branch	981.76
3.1	Walnut tree, nail, 20 feet from river, in open field	975.87
3.1	Water surface	960
4.3	Water surface	963
5.1	Sycamore tree, nail, east bank of river	974.48
5.1	Water surface	964
6.8	Water surface	970
6.9	Root of red-oak tree, nail, 40 feet below mouth of Langleys Creek, east side	989.34
6.9	Water surface	972
7.3	Foot of dam at mill, water surface	977
7.8	Top of dam at mill, water surface	983
7.9	Top of iron bolt, west side of east approach, painted white	1,001.28
7.9	Water surface	984
8.1	Root of pine stump, nail, near Boldings Bridge, 40 feet from river, east bank	999.56
8.9	Red-oak tree, nail in root, 40 feet from river, east bank	1,003.69
9.2	Mouth of small creek, water surface	993
10.8	Water surface	1,000
11.0	Foot of dam, water surface	1,003
11.9	Top of dam, water surface	1,005
12.0	Foot of shoals, water surface	1,020.21
12.0	White oak tree, nail in root, at side of rock bluff, left bank	1,009
12.0	Water surface	1,012
13.0	Robinsons Ford, water surface	1,025.30
13.0	Red-oak tree, nail in root, 10 feet from river at Robinsons ford	1,014
13.0	Foot of small shoal, water surface	1,016
13.0	Head of small shoal, water surface	1,017
14.2	Water surface	1,043.27
14.3	Red-oak tree, nail in root, 50 yards below mouth of Yellow Creek	1,022
14.3	Water surface	1,049.28
15.2	Pine tree, nail in root, opposite shoals	1,024
15.2	Foot of shoals, water surface	1,027
15.2	Top of shoals, water surface	1,062.63
17.4	Small pine tree, nail in root, 50 feet from river on east bank	1,028
17.4	Water surface	1,089
17.5	Foot of small dam, water surface	1,043
17.5	Head of small dam, water surface	1,060.43
17.5	Iron bolt, top of center pier, west side new bridge at Newbridge	1,043
17.5	Foot of North Georgia Electric Company's dam, water surface	1,070
17.7	Top of North Georgia Electric Company's dam, water surface	1,079.43
19.8	Pine tree, nail in root, left bank	1,070
20.9	Head of shoal, water surface	1,075
21.5	Foot of shoal, water surface	1,079
21.6	Head of shoal, water surface	1,104.71
22.6	Brierpatch Bridge, top of iron bolt, south side of east approach	1,082
22.6	Brierpatch Bridge, water surface	1,084
23.5	Foot of small shoal	1,106.49
23.8	Red-oak tree, nail in root, near mouth of branch	1,089
23.8	Water surface	1,114.62
24.9	Persimmon tree, nail in root	1,092
24.9	Foot of dam, water surface	1,104
24.9	Top of old dam at stamping mill, water surface	1,106
27.1	Foot of shoals, water surface	1,109
27.1	Iron bridge, water surface	1,121.86
27.3	Beech tree, nail in root, 60 feet below iron bridge	1,115
27.5	Foot of Chestatee dam, water surface	1,119
27.5	Top of Chestatee dam, water surface	1,122
29.9	Foot of shoal, water surface	1,125
30.1	Top of shoal, water surface	1,150.10
30.7	Beardens Bridge, iron bolt, top of stone pier on west approach	1,130
30.7	Beardens Bridge, water surface	1,133
31.8	Three-fourths mile south of gorge dam, water surface	1,138
31.8	Foot of shoals below dam, water surface	1,159.21
31.9	Hickory tree, nail, 40 feet below the gorge dam	1,150
32.8	Foot of shoal, water surface	1,155
33.1	Top of shoal, water surface	1,166.95
33.7	White-oak tree, nail in root	1,160
33.7	Water surface	1,163
33.7	Foot of shoal, water surface	1,169
34.2	Top of shoal, water surface	1,183.54
34.9	White-pine tree, nail in root, right bank of river	1,174
34.9	Foot of shoals, water surface	1,187
35.1	Head of shoals, water surface	1,189
35.8	Foot of shoals, water surface	1,189

Elevations on Chestatee River from mouth to Willow—Continued.

Dis- tance	Description of points	Elevation above sea level
<i>Miles</i>		<i>Feet</i>
36.0	Head of shoals, water surface.....	1,200
36.1	Hickory tree, nail in root.....	1,214.34
36.1	Foot of shoals, water surface.....	1,201
36.3	Top of shoals, water surface.....	1,206
36.5	Foot of shoals, water surface.....	1,207
36.5	Large rock, right bank, 100 yards below ford, marked "X" with chisel.....	1,218.11
36.6	Grindle lower ford, water surface.....	1,209
	White-oak tree, on side of rock bluff, in fork between Chestatee and Tesnatee rivers.....	1,231.37
37.0	Foot of shoals at mouth of Tesnatee River, water surface.....	1,215
37.4	Head of shoals, water surface.....	1,262
37.7	Large birch tree, nail in root near ford.....	1,265.45
37.8	Foot of shoals at Grindle ford, water surface.....	1,263
38.3	Head of shoals, water surface.....	1,293
	Sweet-gum tree, nail, left bank, opposite foot of shoals.....	1,303.10
	Foot of shoals, water surface.....	1,296
38.9	Head of shoals, water surface.....	1,304
39.2	Foot of bridge at old gold stamp mill, water surface.....	1,305
39.5	Nail in red-oak tree, on left bank, 10 feet below Garnetts bridge.....	1,318.35
39.5	Water surface.....	1,309
	Bottom of old dam, Garnetts dam, water surface.....	1,317
	Top of old dam, Garnetts dam, water surface.....	1,321
39.7	Nail in root of spruce pine at mouth of small creek, opposite center of shoals..	1,335.59
40.4	Foot of shoals, water surface.....	1,323
	Head of shoals, water surface.....	1,346
40.8	Nail in root of hickory, 60 feet below foot of shoals, left bank.....	1,364.25
41.3	Foot of shoals, water surface.....	1,353
41.7	Head of shoals, water surface.....	1,377
	Nail in root of large white-oak tree, left bank, opposite shoals.....	1,388.79
42.3	Foot of shoals, water surface.....	1,378
42.5	Head of shoals, water surface.....	1,384
	Foot of Crooked Shoals, water surface.....	1,386
42.8	Head of Crooked Shoals, water surface.....	1,390
43.0	Nail in root of red-oak tree, right bank, in sharp bend of river.....	1,404.53
43.0	Water surface.....	1,394
43.5	Foot of shoals.....	1,399
43.7	Nail in root of red-oak tree, on right bank, opposite shoals.....	1,425.41
43.7	Water surface.....	1,405
43.9	Foot of large shoals, water surface.....	1,406
44.0	Head of large shoals, water surface.....	1,415
44.7	Nail in root of red-oak tree, on right bank.....	1,437.94
44.7	Water surface.....	1,416
45.0	Foot of shoals, water surface.....	1,422
45.2	Head of shoals, water surface.....	1,428
	Foot of shoals, water surface.....	1,438
	Head of shoals, water surface.....	1,443
46.1	Foot of shoals, water surface.....	1,444
46.7	Foot of shoals, water surface.....	1,446
46.7	Head of shoals, water surface.....	1,446
46.7	Nail in root of maple tree, west side of the river.....	1,447.54
46.4	Water surface.....	1,449
47.7	Nail in root of walnut tree, near west end of bridge.....	1,461.37
47.7	Water surface.....	1,454
47.7	Willow, Ga., 2½ miles north, bronze tablet cemented in rock, on west side of river at fork of road, marked "1529 ATLANTA".....	1,523.649

SURVEY OF FLINT RIVER.

In May, 1900, a survey was made of Flint River from the Geological Survey gaging station, about 3 miles east of Woodbury, Ga., on the Macon and Birmingham Railroad bridge over the river, to the line of the Creek Agency Reserve near Roberta and Knoxville, a distance of 45.4 miles downstream. The work was done by Mr. D. L. Wardroper, under the supervision of B. M. Hall, resident

hydrographer. In this 45 miles the river cuts through Pine Mountain, the western coast range of the State, and descends with a total fall of 334 feet. The elevations are all above sea level, being taken from the track of the Atlanta and Columbus line of the Southern Railway, in front of the station at Woodbury, which is 780 feet above sea level. From this the zero of the Woodbury River gage was found to be 659.63 feet above sea level.

Elevations on Flint River from Woodbury to line of Creek Agency Reserve near Roberta.

Distance	Description of points	Elevation above sea level
<i>Miles</i>		<i>Feet</i>
0.0	Zero of gage at Woodbury Station, water surface.....	659.63
.0	Woodbury gaging station, water surface.....	661.0
.0	Bench mark No. 1, top of northwest corner of bearing stone under south truss at west end of M. and B. R. R. bridge.....	681.1
.6	One-fourth mile below mouth of Cane Creek, water surface.....	660.0
2.3	Two hundred feet above Meltons upper ford, water surface.....	641.8
2.5	Nine hundred feet below Meltons upper ford, water surface.....	637.2
5.0	Bench mark No. 2, nail in leaning catalpa tree at Miltons boat landing on right bank of river.....	638.8
5.2	Five thousand feet below Brown Creek, water surface.....	633.9
7.1	Mouth of Pigeon Creek, water surface.....	620.8
7.1	Bench mark No. 3, nail in pine tree on left bank, 200 feet below mouth of Pigeon Creek.....	628.5
9.1	Six hundred feet above Passleys ford, water surface.....	596.6
9.8	Twelve hundred feet below Passleys Creek, water surface.....	586.9
12.1	Bench mark No. 4, nail in pine tree on left bank, 100 feet below mouth of Valley Creek.....	566.5
12.1	Mouth of Valley Creek, water surface.....	562.2
13.2	Double-bridge ford 800 feet above Womble Creek, water surface.....	552.8
15.5	End of line between districts Nos. 1 and 23, water surface.....	522.0
15.5	Bench mark No. 5, white oak on top of slope on left bank, 100 feet below field, opposite line between districts Nos. 1 and 3.....	531.8
15.8	Bench mark No. 6, sweet-gum tree in field 50 feet below Talbotton and Thomaston road, about 150 feet from river.....	516.7
17.3	Eight hundred feet below mouth of Earls Creek, water surface.....	512.0
17.6	Talbotton and Thomaston road, water surface.....	507.3
18.5	Top of yellow Jacket Shoals, 450 feet below Tablotton and Thomaston road, water surface.....	499.6
20.3	Nine hundred feet above mouth of Lazer Creek, water surface.....	427.0
23.4	Water surface.....	416.6
23.5	Water surface.....	411.9
24.6	Bench mark No. 7, top of west end of wooden cap on north masonry abutment of wagon bridge at Flat Shoals road.....	431.6
25.0	Twenty-three hundred feet below new bridge at Flat Shoals road, water surface.....	409.3
26.3	Twenty-nine hundred feet above mouth of Big Potato Creek, water surface.....	402.5
26.8	Bench mark No. 8, nail in water oak on right bank of Big Potato Creek, 200 feet above mouth.....	413.6
26.9	Bench mark No. 9, nail in root of sweet-gum tree south of road at Parkers Ferry.....	417.7
27.5	Thirty-five hundred feet below mouth of Big Potato Creek, water surface.....	400.5
27.6	Thirty-nine hundred feet below mouth of Big Potato Creek, water surface.....	398.9
28.7	One hundred feet below Hatchasofkee Creek, water surface.....	396.6
30.0	Nineteen hundred feet above Elliotts Ferry, water surface.....	374.0
32.3	Six hundred feet above Walkers Ferry, water surface.....	359.4
37.5	Eight hundred and eighty feet below Ducks Creek, water surface.....	349.3
	Bench mark No. 10 nail in leaning ash tree on right bank of Swift Creek, 3,000 feet from its mouth, 100 feet from north end of bridge.....	377.1
	Bench mark No. 11 nail in root of beech tree at south end of bridge mentioned in description of bench mark No. 10.....	379.7
41.1	Fifty-five hundred feet above Grays Ferry, water surface.....	345.9
42.4	Bench mark No. 12, nail in root of sweet gum opposite boat landing at Grays Ferry, left bank.....	353.1
43.9	Twenty-nine hundred feet below mouth of Auchumkee Creek, water surface.....	339.7
44.0	Water surface.....	335.2
44.7	Water surface.....	334.9
45.0	Eighty-nine hundred feet below mouth of Auchumkee Creek, water surface.....	328.8
45.5	Water surface.....	327.0
46.9	Bench mark No. 13, tin cap on root of red oak 20 feet west of north of the north-south line on west boundary of lot No.176, fourteenth district, of Taylor County.....	352.9

WATER POWER IN APALACHICOLA RIVER DRAINAGE
BASIN.

CHATTAHOOCHEE RIVER.

In the foregoing lists of water-surface elevations several surveys have been put together, so as to give a continuous chain of elevations, and, for the main river, the distance of each point noted is given in miles above Columbus. Objects along the river are also noted and serve to locate and make it possible to identify each point at which the surface elevation is given.

The fall at any point or between any points can therefore be determined, and the amount of water flowing at it can be estimated from the records of the hydrographic stations at West Point, Oakdale, Norcross, Buford, and Gainesville, and from miscellaneous measurements.

At Columbus is the fall line, and immediately above are located the largest falls on the river. Here a large amount of water power has been in use for many years.

The developed water powers are: (1) Eagle and Phoenix dam, operating the Eagle and Phoenix, and Muscogee mills; fall 26 feet. (2) City Mills dam; fall 9 feet. (3) Columbus Power Company's dam and tailrace; fall 40 feet. The last mentioned was completed in 1902. The stone dam is located above the foot of the shoals, a considerable portion of the head being obtained by excavating for the tail-water. Water is backed three-fourths mile above the dam, and reaches the foot of a very fine shoal, the Chattahoochee Falls Company's property, where there is a fall of 40 feet in little more than 1 mile. The old Clapp factory was located on this property and the power was supplied by a wing dam, about half of the fall being used. The present owners of the property have secured water rights along the river above, which will enable them to develop a much higher head and will also give a larger storage. The fall from the upper line of the original property to foot of shoals on Ogle-tree's land is 21 feet in 7 miles. From this point up to the lower end of Hargetts Island, 10 miles above, the fall is 150 feet.

Along this portion of the river the banks are high and rocky. The river is mostly wide and full of islands, but at several places the

banks come close together, affording excellent sites for high dams, in some cases not more than 600 feet long.

In the 7 miles from Hargetts Island to the foot of Riverview dam the fall is 42 feet. At the Riverview mills and Langdale mills there are developed powers, each using 10 or 12 feet of fall.

Above the Langdale mills up to West Point the amount of fall is small. Between West Point and Franklin the fall is 75 feet in 38 miles, averaging about 2 feet a mile. The fall is not uniformly distributed, however, and it is probable that some really good power developments could be made.

At Franklin, where there is an excellent site for a dam, extensive surveys have been made for one 32 feet high, which would back water 8½ miles, to the head of Fishtrap Shoals. This proposed development includes Bushyhead Shoals and several others not so large.

From here to the foot of McIntosh Shoals the fall is only 11 feet in 11 miles. At McIntosh Shoals there is a fall of 8 feet in one-half mile.

Above this shoal up to the mouth of Peachtree Creek, above Atlanta, the fall is 66 feet in 47 miles. Three miles above is the dam site of a proposed development of 32 feet, for which complete surveys have been made.

At Bull Sluice, 4 miles below Roswell, is the new electric power plant of the Atlanta Water Power and Electric Company. The dam is a massive concrete structure, 48 feet high, which with the 2-foot flashboards, gives a head of 50 feet. This plant is fully equipped with the most modern type of water wheels and electric generators. The combined capacity of the water wheels is greatly in excess of the normal low-water flow of the river, thus providing for a large increase of power from stored water, and at times when the flow of the river is increased. The power is all transmitted electrically to Atlanta. Backwater from this dam, when flashboards are used, reaches a point just under the wagon bridge at Roswell.

In the 26 miles above Roswell, reaching to Bowmans Island, near Buford, there is a fall of about 57 feet, the drop being as much as 5 or 6 feet to the mile in a few places. At Bowmans Island is a proposed site for a 50-foot dam to back water 14 miles up to mouth of Chestatee River.

From the mouth of Chestatee River, up to the mouth of Little River, there are a number of small shoals aggregating 28 feet of fall. Beginning a short distance above Little River is a series of shoals, which has recently been developed by the North Georgia Electric Company. The dam of this plant is located a quarter of a mile above the foot of the shoals, leaving about 7 feet of the fall undeveloped. It is a log crib structure entirely filled with rock and is 36 feet high. The power is transmitted electrically from the plant. Backwater extends 8 miles, to above Clarks Bridge. In the next 11 miles, up to Belton, the fall is about 30 feet and includes several shoals and some good sites for dams.

In the next 9 miles, extending to mouth of Soque River, the fall is 81 feet, including Harrisons Shoals, Perkins Shoals, and a series of shoals above and below Duncans Bridge, the latter series having a fall of 20 feet in $1\frac{1}{4}$ miles.

Above the mouth of the Soque River is a series of shoals, with a total fall of 106 feet in $4\frac{1}{4}$ miles. Along this part of the river the banks are steep and rocky, and there are numerous good dam sites.

WATER POWERS ON SOQUE RIVER.

In $5\frac{1}{2}$ miles above the mouth of the river the fall is 30 feet, including several small shoals. One mile downstream from Porter Mills there is an undeveloped fall of 6 feet in about 50 yards, with 7 feet of fall above, to the foot of Porter Shoals. At Porter Mills is the Porter Shoals, an almost vertical drop of 48 feet and by far the best waterfall on the river. This is partly developed by a small wing dam, the power being used to operate Porter's woolen and cotton factory, 4 miles from Demorest, the nearest railroad point.

About 500 feet upstream is Porters Upper Shoal, with a 15-foot fall, also partly developed by a small dam, and supplying power for factory No. 2 of the same company. A much greater head could be obtained here by increasing the height of the dam. One and one-half miles above Porter Mills is a good water-power site, known as the Old Factory Shoals, where there is a fall of 23 feet in a distance of 600 feet. This was utilized at one time, but all signs of the dam have vanished.

WATER POWERS ON CHESTATEE RIVER.

From the mouth of the river up to the foot of the North Georgia Electric Company's dam, at Newbridge, a distance of $17\frac{1}{2}$ miles, the fall is 83 feet. This includes three small dams and a number of undeveloped shoals, but no especially favorable sites for large powers.

The North Georgia Electric Company's dam is 27 feet high, and is made of log cribs filled with rock, and backs water about $3\frac{1}{4}$ miles. Above this dam there is a large amount of fall and many good power sites, some of which are developed and used to operate machinery connected with gold mining. Most of the undeveloped powers are owned or controlled by various mining companies.

WATER POWERS ON FLINT RIVER.

The country rock in the Flint River basin over the range of the preceding elevations is vitrified sandstone or quartzite, forming fine bluffs and occasional narrow gorges suitable for dam sites. It is easily quarried, and comes out in square blocks that are excellent for building dams.

The first shoals, known as the Dripping Rock Shoals, begin near the mouth of Cane Creek, about 3,000 feet below the bridge, and fall 23.7 feet in about 2 miles. In the next 2 miles, or to a point about 1 mile below the mouth of Pigeon Creek, the river falls only 6 feet. Then shoals begin which have a practically uniform fall of 10.5 feet per mile for a distance of $8\frac{1}{2}$ miles; or to Double Bridges (Gibson's old ferry), the total fall in that distance being 90 feet. From that point to the north boundary of the twenty-third land district the fall is 20 feet in a distance of 4,700 feet. In the next 3 miles, or to the head of the Yellow Jacket Shoals, there is a total fall of 22 feet.

The Yellow Jacket Shoals are the finest on the river. They are below Pigeon Creek and above Lazer Creek (sometimes called Eliza Creek), near Rowland, in Upson County, about midway between Talbotton and Thomaston, in the heart of the cotton belt of Georgia. They have a fall of 65 feet in a distance of 7,900 feet, or $1\frac{1}{2}$ miles, all of which can be utilized. In fact a much larger head would be available by building a 42-foot dam at the head of the Yellow Jacket Shoals and taking the water in a canal to a point opposite the foot

of the shoals. This would cover a fall of 107 feet, 7 feet of which would be sufficient for storage and canal grades, leaving a net working head of 100 feet. A dam of this height would back the water about 4 miles. There would be no trouble from flood water on the wheels, for the river is very precipitous below the foot of the Yellow Jacket Shoals, having an average fall of 6 feet to the mile in the next 10 miles, the most precipitous part being a fall of about 25 feet between Hatchasofkee Creek and Elliotts Ferry, a distance of about 2 miles. Elliotts Ferry is between the mouths of Mountain Creek and Deep Gulch Creek.

Below Elliotts Ferry the river falls 13 feet in the next 2 miles, or to Walker's Ferry, and then assumes a practically uniform grade of 1.7 feet to the mile for the next 11 miles, or to a point one-half mile below the mouth of Auchumkee Creek, in Crawford County, which is at the head of small shoals having a fall of 10 feet in a distance of 1 mile. This is practically the point where the river crosses the fall line and enters the younger geologic formations. The survey ended here.

Along the portion of the river surveyed there are several large tributaries which have fine shoals. The most notable of these is Big Potato Creek, near Thomaston, in Upson County, which has three shoals near its mouth, surveyed in 1891 by C. C. Anderson, assistant State Geologist, and reported by him to be as follows: Rogers Shoals, 81 feet fall in a distance of 3,500 feet; Nelson Shoals, 115 feet fall in a distance of 2,700 feet, and Daniels Shoals, 13 feet fall in a distance of 150 feet.

About 10 miles above Woodbury there is a fine water power on Flint River, 1 mile from Neal, on the Southern Railway. It is known as the Flat Shoals and has a fall of 32 feet in a distance of 3,000 feet. There is a natural storage basin just above these shoals, where it is estimated that a 2-foot dam would store the low-water flow of the river for twelve hours, and that a 4-foot dam would store it for thirty-eight hours. This power is not included in the survey described, but was surveyed separately by B. M. Hall. It can be developed by a canal 3,000 feet long, or by a dam at the foot of the shoals, where there is a narrow shut-in.

MOBILE RIVER DRAINAGE BASIN

DESCRIPTION OF BASIN.

The drainage basin of the Mobile River is the largest in Georgia and Alabama, and is designated the Mobile basin because its waters all enter the Gulf through Mobile River at Mobile, Ala. At its headwaters, Cartecay and Ellijay rivers unite at Ellijay to form Coosawattee River, which, just above Resaca, unites with the Conasauga to form Oostanaula River. At Rome, Ga., the Oostanaula and the Etowah unite to form Coosa River. Six miles above Montgomery, Ala., the Coosa and the Tallapoosa unite to form Alabama River, and not far from the coast the Tombigbee unites with the Alabama to form Mobile River, which flows into Mobile Bay, an arm of the Gulf of Mexico.

Cahaba River is the principal tributary of the Alabama and joins it about 10 miles below Selma. Hillabee Creek flows into Tallapoosa River just above Sturdevant and near Alexander. Talladega Creek is a tributary of the Coosa.

Tombigbee River rises in the northeastern part of Mississippi and enters Alabama in Pickens County. Its principal tributary is the Black Warrior, which is formed by the junction of Mulberry Fork and Sipsey Fork. Locust Fork enters the Black Warrior some distance below the junction.

This paper discusses only the gaging stations in the Mobile drainage basin which are located in the State of Georgia. For stations located in Alabama and Mississippi the reader is referred to Water-Supply Paper No. 107, Water Powers of Alabama and Mississippi, and to the Reports of Progress of Stream Measurements, published by the United States Geological Survey.

STREAM FLOW.

ETOWAH RIVER NEAR BALLGROUND.

This station was established in 1905. It is located at an iron highway bridge about $2\frac{1}{2}$ miles south of Ballground, and half a mile below the mouth of Long Swamp Creek.

The channel is nearly straight for 300 feet above and 600 feet below the station, and the current is moderately swift and fairly good

for measurement. The left bank is high and will not overflow, but the right bank is low and cultivated for about 500 feet and will overflow at a gage height of about 16 feet above low water. The bed of the river is partly rock.

Discharge measurements are made from the bridge of two iron spans. The left span is 110 feet long, and spans the entire river except at floods. The other span, which is over low ground on the right bank, is 100 feet long, and there is also 90 feet of wooded trestle on the right bank. Gage heights are determined directly from the bench mark, which is the top of the upstream end of the first floor beam to the left of the middle pier; elevation, 28.00 feet above the datum of the assumed gage.

Discharge measurements of Etowah River near Ballground.

Date	Gage height	Discharge
1905	<i>Feet</i>	<i>Sec-ft.</i>
June 24.....	3.10	763
November 15.....	2.24	408

ETOWAH RIVER AT CANTON.

This station was established in 1892 by the United States Weather Bureau, and it was only in 1896 that measurements were begun by the United States Geological Survey. It is located at the wagon bridge in Canton, one-half mile above the mouth of Canton Creek and 1,000 feet upstream from the Atlanta, Knoxville and Northern Railway station.

The channel is straight for 1,000 feet above and 500 feet below the bridge. The current is affected by a fish-trap dam about 1 foot high, which has caused much trouble by being occasionally washed away and built up again. Up to gage height 3 feet the river is only 116 feet wide and flows between the piers on its lower banks. Up to about 14 feet it is confined between its upper banks, which are the abutments at the outer ends of the approaches, but above 14 feet it begins to overflow the bottom lands. The bed is fairly constant.

Discharge measurements are made from the upstream side of the iron highway bridge. The initial point for soundings is the river side of the right-bank pier at the end of the main span. The gage

is a heavy vertical timber, fastened to the edge of the left-bank pier, on the upstream side. The gage is read once each day by J. M. McAfee, who is paid by the United States Weather Bureau for six months of the year and by the Georgia Geological Survey for the other six months. Bench marks were established as follows: (1) A cut on a silver-maple tree on the east side of the road, 20 feet from the end of the bridge, on the south or left bank of the river; elevation, 20.36 feet. (2) The top of the iron bar on the top of the left-bank pier at the end of the center span of the bridge, upstream side; elevation, 23.39 feet. Elevations refer to the datum of the gage.

WATER POWERS OF GEORGIA

Discharge measurements of Etowah River at Canton.

Date	Gage height	Dis-charge	Date	Gage height	Dis-charge
1896	<i>Feet</i>	<i>Sec.-ft.</i>	1901	<i>Feet</i>	<i>Sec.-ft.</i>
April 29.....	0.05	590	April 25.....	1.50	1,684
July 7.....	.59	862	August 16.....	2.85	2,781
September 9.....	— .65	218	November 2.....	.25	686
October 28.....	.45	783	1902		
October 28.....	2.25	2,327	March 29.....	15.10	12,060
November 27.....	— .05	449	April 26.....	.90	1,199
1897			July 12.....	.51	779
March 17.....	2.60	2,656	August 16.....	.20	419
May 5.....	.75	1,264	November 22.....	.44	410
June 16.....	1.27	1,682	1903		
August 28.....	— .30	449	January 28.....	1.07	922
September 21.....	— .60	284	March 27.....	2.50	2,562
November 12.....	.23	346	April 27.....	1.80	1,873
December 13.....	.33	514	June 25.....	.94	1,166
1898			June 25.....	.98	1,119
January 13.....	.60	761	September 4.....	.51	570
March 5.....	.33	621	September 4.....	.51	575
March 19.....	5.60	5,124	October 10.....	.60	513
May 20.....	.60	627	1904		
June 4.....	.22	495	January 15.....	.50	542
July 19.....	.25	413	March 3.....	.78	821
August 30.....	.65	1,062	May 17.....	.18	497
September 6.....	3.25	3,190	July 26.....	.04	328
September 7.....	2.00	2,104	July 26.....	.04	324
November 13.....	.90	1,223	September 1.....	.06	374
December 10.....	.70	1,064	October 8.....	— .38	197
1899			October 8.....	— .25	227
April 27.....	1.92	2,087	October 13.....	— .38	171
June 23.....	.25	770	1905		
September 27.....	— .19	406	January 21.....	.67	720
November 10.....	— .10	420	January 21.....	.67	710
1900			January 21.....	.67	689
February 27.....	.80	1,113	April 20.....	.61	716
May 19.....	1.05	1,351	June 3.....	.49	786
December 1.....	.55	816	October 18.....	.14	531
1901			October 18.....	.14	531
February 5.....	2.85	2,578	November 17.....	.14	434
			November 17.....	.14	434

Daily gage height, in feet, of Etowah River at Canton.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1896												
1.....	0.6	1.8	0.6							0.0	0.0	1.0
2.....	.6	1.8	.5							— .2	— .1	1.0
3.....	.6	1.8	.5							— .3	— .1	.6
4.....	.6	1.8	.5							— .3	.0	.3
5.....	.6	1.8	.5							— .4	+2.8	.3
6.....	.6	2.0	.5							— .4	.8	.2
7.....	.5	3.0	.8							— .5	.6	.1
8.....	.7	3.0	.8							— .5	.6	.1
9.....	.7	3.5	.8							— .65	.5	.1
10.....	.7	2.0	.8							— .6	— .4	.1
11.....	.7	1.8	.8							— .6	— .3	.4
12.....	.7	1.8	.8							— .65	— .4	.9
13.....	.7	1.8	.8							— .7	— .2	3.6
14.....	.7	1.0	.8							— .75	— .3	1.0
15.....	.7	1.0	.7							— .6	— .4	.7
16.....	.7	1.0	.8							— .55	— .4	.7
17.....	1.0	1.0	.8							— .65	— .4	.4
18.....	.8	1.0	.7							— .75	— .4	.2
19.....	.8	1.0	1.0							— .75	— .4	.0
20.....	.8	1.0	1.0							— .75	— .5	.0

MOBILE DRAINAGE BASIN, STREAM FLOW

Daily gage height, in feet, of Etowah River at Canton—Continued.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1896												
21.....	0.8	1.0	1.0						-0.75	-0.5	0.0	0.0
22.....	1.0	.8	.8						.6	.5	.0	.0
23.....	3.8	.8	.8						.1	.5	.0	.0
24.....	5.8	.8	.8						.3	.0	.0	.0
25.....	8.0	.8	.6						.4	.1	.0	.0
26.....	2.0	.6	.6						.6	.1	.0	.0
27.....	2.0	.6	.6						.6	.1	.0	.0
28.....	2.0	.6	.6						.6	+2.25	.0	.1
29.....	1.8	.6	.6						.6	1.1	.0	.1
30.....	1.8		.6						.7	1.0	1.0	.1
31.....	1.8		a1.0							.0	1.4	.1
1897												
1.....	.1	.6	.8	1.6	2.0	.1	.0	.2	.8	.7	.2	.6
2.....	.1	2.2	.6	2.0	1.8	.1	.0	.0	.0	.7	.3	.6
3.....	.1	1.0	.6	2.0	1.8	.7	.0	.0	.3	.7	.3	.6
4.....	.1	.8	.6	2.6	1.6	.5	.0	.0	.4	.5	.6	.6
5.....	.1	.8	.6	11.2	.7	.5	.0	.0	.4	.4	.5	2.0
6.....	.1	.9	3.6	5.0	.7	.5	.0	.6	.5	.3	.5	1.0
7.....	.1	.8	4.0	3.0	.7	.4	.4	.3	.5	.3	.3	.9
8.....	.1	.8	2.0	2.0	.6	.4	.4	.3	.5	.4	.3	.8
9.....	.1	.8	1.8	3.0	.6	.3	.4	.6	.6	.4	.3	.8
10.....	.1	.8	1.8	2.6	.5	.3	.3	.6	.6	.4	.2	.8
11.....	.1	.8	1.8	2.4	.5	.2	.3	.6	.6	+1.2	.2	.8
12.....	.1	.8	2.8	2.2	.5	.1	.2	.4	.6	1.0	.2	.6
13.....	.1	1.8	7.2	2.0	.5	.1	.2	.4	.6	.8	.2	.8
14.....	2.2	1.0	6.8	2.0	.4	.1	.2	.2	.6	.8	.2	.9
15.....	1.8	.8	4.0	2.0	.4	.0	.1	.2	.6	.6	.2	.9
16.....	.9	.8	3.6	1.8	.4	3.0	.1	.2	.6	.6	.2	.8
17.....	.5	.7	2.6	1.8	.4	1.0	.9	1.0	.6	.6	.2	.7
18.....	2.0	.6	2.4	1.4	.4	.8	.9	1.0	.6	.4	.2	.7
19.....	1.6	.6	2.0	1.4	.4	.6	1.0	.8	.6	.4	.1	.8
20.....	3.6	.6	2.8	1.2	.4	.4	2.0	.6	.6	.6	.1	.8
21.....	3.0	.8	2.0	1.2	.3	.4	7.1	.4	.6	.4	.2	.9
22.....	2.0	.8	1.0	1.0	.3	.3	2.5	.2	.6	.4	.2	1.0
23.....	1.0	1.6	1.8	1.0	.2	.3	1.0	.0	.5	.4	.2	.9
24.....	.8	1.0	1.8	1.0	.1	.3	.8	.0	.5	.4	.2	.8
25.....	.7	1.0	1.6	1.0	.1	.3	.8	.0	.5	.4	.8	.8
26.....	.7	.8	1.6	.8	.1	.2	.6	.1	.8	.4	.6	.8
27.....	.7	.8	1.4	.8	.1	.1	.6	.2	.6	.3	.6	.7
28.....	.6	.8	1.2	.8	.1	.1	.5	.3	.5	.3	.6	.6
29.....	.6		1.2	1.0	.1	.1	.5	.4	.6	.3	.3	.6
30.....	.6		1.2	1.0	.1	.1	.4	.4	.6	.3	.6	.6
31.....	.6		1.2		.1		2	+1.0		.2		.5
1898												
1.....	.5	.8	.3	1.6	.6	.6	.3	.4	.4	.4	.8	1.6
2.....	.5	.8	.3	1.4	.6	.4	.2	.4	11.5	.4	.8	1.6
3.....	.3	.8	.6	1.2	.6	.3	.2	2.0	9.0	.3	.7	1.6
4.....	.3	.7	.6	1.0	.5	.2	.2	3.4	4.0	9.0	.7	2.0
5.....	.2	.6	.4	2.0	.5	.2	.4	3.0	2.0	13.5	.7	2.4
6.....	.2	.6	.4	3.6	.4	.2	.4	2.0	3.0	4.0	.8	2.4
7.....	.3	.6	.4	3.0	.4	.2	.8	3.0	2.4	2.4	.7	2.2
8.....	.3	.6	.3	1.8	.4	.2	1.8	3.0	1.6	2.0	.6	2.2
9.....	.3	.5	.2	1.0	.4	.2	.8	2.0	1.4	1.6	.6	2.1
10.....	.4	.5	.2	.8	.4	.1	.8	4.0	1.4	1.4	.7	2.0
11.....	.6	.4	.2	.8	.3	.1	.9	6.0	1.6	1.2	.8	2.0
12.....	.8	.4	.2	.6	.3	.1	2.9	4.0	1.4	1.2	.7	1.8
13.....	.8	.4	.2	.6	.3	.1	2.0	3.5	1.4	1.1	.7	1.8
14.....	.6	.4	.1	.6	.3	.7	1.8	2.0	1.0	1.1	.6	1.8
15.....	.6	.4	.4	.5	.3	.6	1.6	1.8	1.0	1.0	.8	1.7
16.....	.8	.4	4.0	.5	.3	.6	1.4	1.6	1.0	1.0	.8	1.7
17.....	.8	.4	3.0	.4	.3	.5	1.2	1.4	.8	1.0	.8	1.7
18.....	.8	.3	.8	.4	.2	.5	.6	1.2	.8	4.2	.9	1.6
19.....	.9	.3	.6	.8	.2	.4	.2	1.0	.6	3.0	1.0	1.6
20.....	.9	.4	.6	.6	.2	.4	.2	.8	.6	2.0	1.2	1.6


α Weather Bureau discontinued observations March 31, 1896; Geological Survey began observations September 9, 1896.

WATER POWERS OF GEORGIA

Daily gage height, in feet, of Etowah River at Canton—Continued.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1898												
21.....	.8	0.5	0.4	0.7	0.2	0.4	0.2	0.6	0.4	2.0	1.2	1.6
22.....	.3	.4	.4	.6	.2	.4	.3	.4	.4	2.0	1.6	1.5
23.....	.9	.4	.4	.8	.8	.3	.3	.4	.4	1.8	2.0	1.4
24.....	.9	.4	.3	2.0	.8	.3	7.3	.4	.8	1.6	1.8	1.4
25.....	2.0	.3	.2	.9	.6	.3	2.0	.4	.6	1.4	1.6	1.4
26.....	5.6	.3	.2	.3	.6	.3	2.0	.4	.6	1.2	1.6	1.4
27.....	4.0	.3	.1	.3	.5	.3	1.8	3.6	.4	1.0	1.5	1.4
28.....	2.6	.3	.2	.3	.4	.3	1.8	2.4	.4	1.0	1.5	1.4
29.....	1.3	5.0	.6	.4	.3	1.8	1.8	.4	.9	2.0	1.2
30.....	1.0	4.0	.6	.4	.3	1.8	1.0	.4	.8	1.8	1.2
31.....	.9	3.08	1.8	.68	1.8
1899												
1.....	1.8	1.6	3.0	2.4	1.6	1.0	1.4	1.4	.8	-.4	-.1	.1
2.....	1.8	1.6	2.8	2.2	1.5	1.4	1.4	1.4	.6	-.4	-.1	.4
3.....	1.8	1.8	2.8	2.0	1.4	1.4	1.4	1.8	.6	-.5	-.1	.4
4.....	1.8	2.8	2.6	3.8	1.4	4.4	1.2	1.6	.6	-.5	-.1	.4
5.....	1.8	3.0	2.4	3.0	1.4	3.0	1.2	1.6	.6	-.5	-.1	.2
6.....	1.8	6.2	2.0	2.8	1.4	1.0	1.0	1.4	.6	.0	-.1	.2
7.....	1.6	8.0	1.8	2.8	1.4	1.0	1.4	1.2	.5	.2	-.1	.2
8.....	1.4	4.0	1.8	4.0	1.4	1.0	1.6	1.6	.5	.2	-.1	.2
9.....	1.4	3.2	1.6	3.0	1.6	1.0	4.0	1.8	.4	.2	-.1	.2
10.....	1.4	3.0	1.5	2.8	1.6	1.0	2.0	1.6	.4	.1	-.1	.2
11.....	1.4	2.0	1.5	2.0	1.4	1.4	1.8	1.6	.4	.1	-.1	.3
12.....	1.8	(a)	1.4	1.8	1.4	1.6	1.6	1.6	.4	.1	-.1	2.8
13.....	1.8	(a)	1.4	1.8	1.4	1.6	1.4	1.4	.4	.0	-.1	.3
14.....	2.8	(a)	3.6	1.8	1.8	1.4	1.4	1.2	.4	.0	-.1	.3
15.....	2.6	3.0	7.0	1.8	1.8	1.4	1.8	1.2	.4	.0	-.0	.2
16.....	2.4	2.0	18.2	1.6	1.8	1.4	1.9	1.0	.4	.0	.0	.2
17.....	2.3	2.0	18.0	1.6	1.6	1.4	1.8	1.0	.3	.0	.1	.2
18.....	2.3	2.0	4.0	1.6	1.6	1.4	1.8	.8	.3	.0	.0	.1
19.....	2.2	2.0	4.0	1.4	1.6	1.4	1.8	.8	.3	.0	.0	.1
20.....	2.2	1.8	3.0	1.4	1.4	1.3	1.6	1.4	.2	-.1	.0	.1
21.....	2.0	1.8	2.0	1.4	1.4	1.3	1.6	1.4	.1	-.1	.0	.1
22.....	1.8	1.8	2.0	1.4	1.4	1.3	1.6	1.2	.0	-.1	.0	.1
23.....	1.8	1.8	2.0	1.4	1.4	1.2	1.6	1.0	.0	-.1	.9	.8
24.....	2.0	1.6	1.8	1.8	1.4	1.2	1.4	1.0	.0	-.1	.7	3.0
25.....	2.8	1.4	1.8	4.8	1.4	1.2	1.2	.8	-.1	-.1	.7	3.0
26.....	2.0	1.8	2.8	3.0	1.2	1.0	1.2	.8	-.1	-.1	1.1	2.0
27.....	1.8	10.0	2.0	2.8	1.2	1.0	1.2	1.4	-.1	.0	.7	2.3
28.....	1.8	5.0	1.8	2.0	1.2	1.0	1.2	1.2	-.2	.0	.5	1.8
29.....	1.8	2.8	1.8	1.2	1.0	1.2	1.0	.3	-.1	.1	.6
30.....	10.0	2.0	1.2	1.0	1.1	1.0	.3	-.1	.1	.6
31.....	5.0	2.6	1.0	1.0	.8	-.16
1900												
1.....	.6	.6	.8	1.4	1.2	1.4	1.7	1.0	.6	.3	1.3	.6
2.....	.6	.8	.8	1.0	1.2	1.4	1.7	1.0	.6	.2	1.4	.6
3.....	.6	1.0	.8	.3	1.2	2.4	1.8	1.0	.6	.2	1.6	.5
4.....	.6	1.0	.8	.3	1.2	2.0	1.8	1.0	.6	1.6	1.6	2.3
5.....	.6	1.2	.8	.3	1.1	3.0	1.8	1.0	.6	1.5	1.4	2.6
6.....	.6	1.2	.8	.3	1.1	3.0	2.4	.8	.6	1.3	1.4	1.3
7.....	.6	1.2	.8	.3	1.1	6.0	2.2	.8	.6	1.3	1.4	1.0
8.....	.6	2.7	3.4	.3	1.1	6.0	1.8	.8	.6	2.2	1.4	.3
9.....	.6	2.5	5.4	.3	1.1	4.0	1.3	.8	.6	3.1	1.4	.3
10.....	.6	1.8	2.2	.3	1.0	1.2	.6	.6	2.0	1.4	.7
11.....	.6	2.7	1.6	.3	1.0	1.0	.6	.6	2.0	1.4	.6
12.....	1.6	14.2	1.0	2.3	1.0	1.0	.6	.6	2.0	1.4	.6
13.....	1.0	6.0	.9	2.6	1.0	1.0	.6	.6	2.6	1.4	.5
14.....	.6	3.1	.8	2.2	1.0	3.0	.6	.6	2.3	1.4	.4
15.....	.6	2.0	.8	2.0	.9	1.8	.6	3.6	2.0	1.2	.4
16.....	.4	1.5	.9	1.8	.9	1.2	.8	5.0	1.5	1.2	.4
17.....	.4	1.5	.9	1.8	.9	1.2	1.7	3.1	1.4	1.2	.4
18.....	.4	1.0	.9	2.3	.9	1.2	2.3	2.3	1.3	1.2	.3
19.....	1.0	1.0	.9	3.6	1.2	1.0	2.3	1.6	1.0	1.4	.3
20.....	1.0	1.0	5.2	2.0	1.1	1.0	2.0	1.4	1.0	2.1	2.3

a Gage covered with ice February 12 to 14, 1899.



FLAT SHOALS ON THE FLINT RIVER, BETWEEN PIKE AND MERIWETHER COUNTIES, GEORGIA.

MOBILE DRAINAGE BASIN, STREAM FLOW

Daily gage height, in feet, of Etowah River at Canton—Continued.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1900												
21.....	.4	1.0	3.6	5.0	1.0	1.0	1.0	.8	1.0	4.6	2.1
22.....	.4	1.0	1.8	3.0	1.0	1.0	1.0	.7	1.0	3.7	1.3
23.....	.4	1.0	1.8	2.0	1.0	1.0	1.0	.6	2.6	3.0	1.0
24.....	.4	1.0	2.8	4.0	1.8	1.0	3.0	.6	7.2	2.1	1.0
25.....	.4	1.0	2.1	2.0	1.4	1.0	2.0	.6	3.5	2.0	1.0
26.....	.4	1.0	3.6	1.8	1.2	1.0	1.0	.6	2.7	4.0	.8
27.....	.4	.8	2.0	1.6	1.2	1.5	.6	.6	2.5	2.2	.8
28.....	.4	.8	2.0	1.0	1.0	2.8	.6	.4	2.0	2.0	.7
29.....	.4	2.0	1.0	1.0	3.5	.6	.4	1.8	1.0	.7
30.....	.4	1.9	1.4	1.0	4.0	.6	.3	1.4	.7	.7
31.....	.6	1.9	1.0	2.0	.6	1.3	2.3
1901												
1.....	2.1	1.2	.8	1.8	1.0	4.6	1.7	.6	2.4	.7	.5	.6
2.....	1.3	1.0	.8	3.6	.9	2.4	1.2	.6	2.3	.8	.5	.8
3.....	1.3	1.3	.7	4.8	.9	2.0	1.0	.5	2.2	2.9	.5	.8
4.....	.9	6.0	.7	3.4	.8	3.6	.8	.5	2.0	2.8	.5	.9
5.....	.7	4.1	.7	2.5	.8	3.0	.7	.5	1.8	2.0	.6	.9
6.....	.7	2.0	.6	2.3	.8	2.8	.7	.4	1.7	1.0	.6	.9
7.....	.7	2.0	.6	2.0	.9	3.4	2.6	1.1	1.5	.9	.6	.9
8.....	.6	1.8	.6	1.9	.9	1.3	1.8	.7	1.3	.8	.6	.9
9.....	.6	4.0	.6	1.3	.9	1.2	1.0	.6	1.1	.6	.6	.9
10.....	.6	3.1	.8	1.0	.9	1.2	.9	.5	1.0	.6	.6	1.2
11.....	6.4	3.0	.9	.9	.9	1.0	.8	.8	.9	.6	.7	1.1
12.....	14.0	2.6	.8	.8	.9	.8	.7	1.9	.9	.6	.7	1.1
13.....	4.5	2.3	.9	1.7	.8	1.4	.7	1.4	.8	.6	.7	1.1
14.....	2.1	2.1	.9	3.0	.8	2.35	.6	1.2	.8	.5	.7	1.2
15.....	1.8	1.8	.9	2.5	.9	5.3	.6	1.5	.7	.5	.7	4.0
16.....	1.4	1.8	.8	2.0	.9	4.65	.6	2.5	.7	.5	.6	3.4
17.....	1.1	1.8	.8	1.7	.8	3.2	.8	3.2	1.5	.5	.6	3.0
18.....	1.0	1.8	.7	1.3	.8	3.1	1.7	2.8	2.8	.4	.6	2.0
19.....	1.0	1.8	.7	4.0	.8	2.8	1.9	5.0	1.4	.4	.7	1.7
20.....	1.0	1.6	.7	4.2	2.7	1.7	1.6	3.2	1.0	.4	.7	1.5
21.....	.8	1.5	.6	3.3	12.2	1.5	1.1	5.2	.9	.3	.7	1.3
22.....	.8	1.3	.6	2.6	16.6	1.3	1.0	7.0	.8	.3	.7	1.2
23.....	.7	1.2	.6	2.4	5.7	1.2	.8	13.0	.7	.3	.8	1.2
24.....	.9	1.0	.8	1.8	3.1	1.1	.7	3.2	.7	.2	1.0	1.1
25.....	.9	.9	.8	1.6	2.3	1.0	.6	2.5	.6	.2	1.0	1.2
26.....	.9	.9	17.0	1.5	2.4	.9	.5	2.3	.6	.2	.9	1.2
27.....	1.0	.8	6.8	1.4	2.0	3.6	.9	2.1	.6	.2	.8	2.4
28.....	1.3	.8	3.4	1.3	1.8	3.9	.8	3.9	.7	.2	.7	3.6
29.....	1.2	3.0	1.2	1.6	2.3	.7	2.7	.8	.2	.7	20.0
30.....	1.0	2.0	1.1	1.4	2.1	.7	2.5	.7	.1	.7	17.0
31.....	1.3	1.8	2.47	2.41	4.0
1902												
1.....	3.7	5.6	10.8	2.3	.5	.4	.4	.5	.8	2.3	.6	2.7
2.....	3.3	11.8	4.3	2.4	1.0	.6	.4	.5	.8	1.8	.5	4.0
3.....	3.0	5.4	3.1	2.1	1.1	.6	.3	.5	1.2	.8	.5	4.2
4.....	2.9	3.1	3.0	1.8	1.0	.3	.4	.5	1.2	.8	.5	2.1
5.....	2.8	2.7	2.8	1.6	.9	.3	.4	.4	1.4	.8	.5	2.8
6.....	2.5	2.3	2.3	1.5	.8	.3	.4	.4	1.4	.6	.8	1.8
7.....	2.2	2.2	2.5	1.4	.7	.3	.4	.4	1.0	.6	.7	1.2
8.....	2.0	2.1	2.1	1.4	.7	1.3	.4	.4	1.0	.6	.7	1.1
9.....	1.9	2.0	1.9	1.3	.6	2.0	.4	.4	1.0	.8	.6	1.1
10.....	1.7	1.8	1.8	1.3	.5	1.8	.4	1.0	1.0	.8	.7	1.0
11.....	1.6	1.6	1.7	1.3	.6	1.0	.3	1.0	1.0	.7	.7	.9
12.....	1.6	1.5	1.7	1.2	.5	1.0	.4	1.2	.8	.7	.8	.9
13.....	1.5	1.3	1.6	1.1	.6	1.0	.3	1.0	.8	.7	.8	.8
14.....	1.5	1.2	1.5	1.0	.6	1.0	.3	.8	.8	.7	.8	.8
15.....	1.4	1.2	1.4	1.0	.5	1.0	.4	.8	.8	.5	.8	.3
16.....	1.4	1.1	1.8	1.0	.5	1.0	.4	.2	1.8	.5	.9	1.7
17.....	1.4	1.0	3.1	1.0	.5	2.4	.4	.8	1.0	.5	.9	1.6
18.....	1.4	1.2	2.45	2.0	.6	.8	1.0	.7	.9	1.6
19.....	1.5	1.2	1.7	1.7	.4	1.0	.6	.6	1.0	.9	1.0	1.5
20.....	1.7	1.0	1.6	1.3	.5	1.0	.7	.6	.8	.9	.9	1.5

WATER POWERS OF GEORGIA

Daily gage height, in feet, of Etowah River at Canton—Continued.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1902												
21.....	1.7	0.9	1.6	1.0	0.5	1.0	0.6	0.6	0.8	0.8	0.8	1.5
22.....	1.7	.7	1.5	.8	.4	.8	.6	.6	.8	.8	.4	1.5
23.....	1.6	.7	1.5	.7	.4	.8	.5	.6	.6	.8	.7	1.5
24.....	1.9	.6	1.5	.7	.4	.6	.8	.6	3.0	.8	.6	1.4
25.....	2.0	.5	1.5	.6	.4	.5	.8	.6	1.0	.8	2.1	1.4
26.....	1.9	.5	1.4	.9	.4	.5	.8	.4	1.0	.8	4.3	3.5
27.....	2.0	.5	1.4	.6	.5	.5	.7	.4	1.0	.8	3.1	3.6
28.....	3.0	18.8	2.5	.6	.3	.4	.4	.4	.8	.8	2.5	3.6
29.....	3.8		16.0	.6	.3	.4	.4	.4	.8	.8	2.1	3.0
30.....	3.6		5.4	.6	.3	.4	.4	.8	.8	.8	2.2	3.0
31.....	3.4		3.2		.3		.6			.8		3.0
1903												
1.....	2.5	1.0	9.2	3.9	1.7	4.5	1.2	.6	.5	.5	.7	.4
2.....	1.5	1.1	4.0	3.4	1.7	7.2	1.2	.8	.5	.5	.8	.4
3.....	1.0	1.6	2.0	2.9	1.6	4.7	1.1	1.1	.5	.5	1.0	.4
4.....	1.0	3.2	2.5	2.8	1.8	4.0	1.7	.7	.5	.5	1.0	.4
5.....	1.0	4.0	2.4	2.5	1.6	10.8	1.1	.7	.6	.5	1.5	.4
6.....	.8	2.0	2.9	2.3	1.4	7.5	1.0	.7	.6	.5	1.0	.4
7.....	.8	2.6	2.3	2.2	1.4	6.0	1.0	.7	.5	.5	.7	.4
8.....	.8	8.0	2.5	3.4	1.4	2.5	1.3	.6	.5	.5	.5	.4
9.....	.8	4.2	2.6	3.4	1.4	2.5	1.2	.6	.5	.5	.5	.4
10.....	.7	2.5	3.5	2.5	1.3	2.6	1.2	.6	.5	.6	.5	.4
11.....	2.8	7.0	11.0	2.2	1.8	2.5	1.2	.6	.4	.6	.5	.4
12.....	2.0	6.2	5.5	2.2	1.3	2.0	1.2	.7	.4	.6	.5	.4
13.....	1.3	3.1	3.5	5.2	1.3	1.6	5.3	.7	.4	.6	.5	.5
14.....	1.3	2.1	2.9	6.0	1.3	1.5	2.7	.7	.4	.6	.5	.5
15.....	1.6	2.8	2.5	3.2	1.2	1.3	2.0	2.5	1.0	.6	.5	.4
16.....	1.6	9.9	2.3	2.5	1.2	1.2	2.0	1.0	1.9	.6	.5	.4
17.....	1.4	17.7	2.2	2.4	1.1	1.2	2.0	1.0	.8	.8	.5	.4
18.....	1.4	5.1	2.0	2.3	1.1	1.2	1.9	2.2	.7	1.0	.8	.4
19.....	1.3	3.2	1.9	2.1	1.1	1.2	1.7	1.0	.5	.8	.6	.4
20.....	1.3	2.5	1.8	2.1	1.1	1.1	1.6	.9	.5	.8	.6	.5
21.....	1.3	2.4	5.5	2.2	1.1	1.1	1.6	.8	.5	.7	.5	.4
22.....	1.3	2.1	3.3	2.1	1.1	1.0	1.4	.8	.5	.7	.5	.4
23.....	1.6	2.0	13.0	2.0	1.0	1.0	1.2	.7	.5	.6	.5	.4
24.....	1.4	1.7	6.7	1.8	.9	1.0	1.0	.6	.5	.6	.5	.4
25.....	1.2	1.5	5.5	1.7	.9	1.0	.9	.5	.5	.6	.5	.6
26.....	1.2	1.6	3.0	2.3	.9	1.0	.8	.5	.5	.6	.5	.5
27.....	1.2	1.5	2.6	1.8	.9	1.1	.7	.5	.5	.7	.5	.5
28.....	1.2	15.0	2.4	1.7	.9	3.0	.7	.5	.5	.7	.5	.6
29.....	1.2		2.9	1.7	.9	1.7	.7	.5	.5	.7	.4	.6
30.....	1.2		12.2	1.7	1.8	1.5	.6	.5	.5	.7	.4	.5
31.....	1.2		5.5		2.6		.6	.5		.7		.5
1904												
1.....	.4	.6	.7	.6	.5	1.3	.5	.5	.1	-.4	.0	.4
2.....	.4	.6	.7	.6	.4	.6	.4	1.2	.1	-.4	.1	.4
3.....	.4	.6	.9	.6	.3	.3	.3	1.2	.1	-.3	.2	.4
4.....	.4	.6	.7	.4	.3	.1	.2	.5	.3	-.3	.3	.5
5.....	.4	.6	.7	.4	.3	.0	.6	2.5	.3	-.4	.4	.8
6.....	.4	.6	.7	.4	.2	.0	.4	.8	.3	-.3	.3	2.0
7.....	.5	.7	2.1	.7	.2	.5	.2	.4	.1	-.3	.2	.8
8.....	.5	1.6	1.7	1.0	.8	.2	.3	8.0	.0	-.35	.2	.6
9.....	.5	1.0	.9	.9	1.1	.0	.1	4.0	.0	-.4	.2	.6
10.....	.5	.6	.8	.8	.6	-.1	.0	1.0	.0	-.4	.2	.5
11.....	.6	.6	.8	.7	.3	-.1	.0	.8	-.1	-.3	.2	.6
12.....	.6	.6	.8	.7	.3	-.1	.2	1.1	-.1	-.3	.2	.5
13.....	.6	.7	.8	.6	.3	-.1	.8	.8	-.2	-.4	.4	.4
14.....	.6	.7	2.0	.5	.3	-.1	.3	.5	-.1	-.4	.6	.4
15.....	.5	.7	1.2	.5	.3	-.2	.1	.4	-.2	-.4	.4	.4
16.....	.5	.7	.8	.5	.2	-.2	.0	.3	-.3	-.3	.8	.4
17.....	1.1	.7	.8	.5	.2	-.2	.5	.3	-.3	-.3	.3	.4
18.....	.9	.6	.7	.5	.2	-.2	.2	.2	-.3	-.3	.3	.4
19.....	.7	.8	.7	.5	.2	-.3	.4	.1	-.3	-.3	.3	.4
20.....	.6	2.5	.6	.5	.1	-.3	.0	.2	-.3	-.3	.3	.4

MOBILE DRAINAGE BASIN, STREAM FLOW

337

Daily gage height, in feet, of Etowah River at Canton—Continued.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1904												
21	.5	1.2	.6	.5	.1	.2	.0	.2	-.3	-.3	.3	.4
22	.7	2.6	1.2	.6	.0	.1	-.1	.0	-.3	-.2	.4	.5
23	1.7	1.0	.6	.5	.0	.2	.1	.1	-.3	-.1	.7	.5
24	1.0	1.0	.6	.4	.0	-.3	.1	.7	-.4	-.2	.5	.5
25	.7	.8	.8	.4	.0	.1	.0	.5	-.4	-.1	.4	.6
26	.7	.8	.8	.5	-.1	.0	.1	.3	-.4	.0	.3	.6
27	.7	.7	.8	.5	-.1	-.1	-.1	.4	-.4	.0	.3	.6
28	.7	.6	.7	.5	-.2	.1	.0	.3	-.2	.0	.3	2.5
29	.8	.6	.7	.5	-.3	.6	.0	.1	-.2	.0	.3	1.0
30	.7		.7	.5	-.3	3.8	.0	.1	-.3	.0	.3	.7
31			.6		1.3		.0	0		.0		.6
1905												
1	.5	.5	.7	.7	.8	.6	1.7	.5	.2	.5	.1	.3
2	.5	.5	.7	.7	.7	.6	1.0	.4	2.0	.4	.0	.3
3	.5	.5	.6	.7	.6	.5	.8	.3	.6	.4	.0	15.2
4	.6	.5	.6	.7	.5	.5	.6	.2	.5	.3	.0	7.5
5	.5	.6	.6	.8	.9	.5	1.8	.2	.4	.3	.0	1.8
6	.6	.8	.7	.9	.9	.5	.7	.2	.3	.2	.0	1.2
7	1.4	1.2	.8	.9	2.5	.5	1.7	.2	2.2	.2	.0	9.9
8	.8	1.2	.8	.9	1.4	.5	.9	.4	2.1	.1	.1	1.0
9	.7	3.7	.8	1.3	2.3	.4	1.7	.7	.2	.0	.1	6.5
10	.6	4.0	1.7	1.0	1.1	.4	2.1	.4	.1	.1	.2	8.4
11	.7	2.0	1.0	.7	.9	.4	7.0	2.0	.1	3.0	.3	1.8
12	9.4	1.5	1.0	1.0	.7	.4	4.0	2.5	.5	1.1	.2	1.0
13	10.0	4.3	.9	1.0	.7	1.2	2.0	2.0	.3	.4	.2	.8
14	2.2	2.3	.9	.7	.6	.5	1.5	1.0	.2	.2	.2	.6
15	1.0	1.8	.8	.7	1.0	.7	1.2	1.5	.0	.1	.1	.8
16	1.0	1.0	.8	1.0	4.0	.6	.9	1.0	.0	.3	.1	.7
17	.8	1.0	.7	.7	.9	.7	.7	.8	.0	.2	.1	.6
18	.8	.9	.7	.7	.8	.6	.5	.5	.0	.1	.1	.6
19	.8	.9	.7	.7	.7	.6	.5	.5	.0	.1	.1	.6
20	.7	1.8	.7	.6	.7	1.4	.7	.4	.0	.0	.2	.9
21	.7	9.9	3.0	.6	.7	2.3	.4	.4	.0	.0	.4	8.1
22	.6	3.9	1.5	.7	.7	3.7	.4	.3	.0	.0	.4	2.0
23	.6	2.0	1.0	.6	1.0	2.0	.4	.3	.1	.0	.2	1.6
24	.5	1.3	1.0	.6	6.5	1.1	.4	.3	-.1	.0	.2	1.3
25	.5	1.0	.9	.6	1.9	.9	.4	.8	-.1	.1	.4	1.0
26	.5	.8	.9	.6	1.2	.9	.4	.3	-.1	.2	.5	.8
27	.5	.8	.9	.6	1.1	.8	.3	.3	-.1	.5	.3	.7
28	.5	.8	.8	.6	1.0	1.2	.3	.2	-.1	.3	.3	.7
29	.5		.8	.6	.9	1.1	1.3	.2	.0	.2	.3	1.2
30	.6		.8	1.3	.9	.9	.5	.2	.0	.1	.2	1.0
31	.6		.8		.8		.7	.2		.1		.8

Rating tables for Etowah River at Canton.

JANUARY 1 TO DECEMBER 31, 1896.

Gage height	Dis-charge						
Feet	Sec.-ft.	Feet	Sec.-ft.	Feet	Sec.-ft.	Feet	Sec.-ft.
-0.75	200	0.50	810	1.80	1,880	3.20	3,460
-0.70	210	0.60	870	1.90	1,970	3.40	3,700
-0.60	240	0.70	950	2.00	2,060	3.60	3,940
-0.50	270	0.80	1,025	2.10	2,160	3.80	4,100
-0.40	320	0.90	1,110	2.20	2,260	4.00	4,350
-0.30	360	1.00	1,180	2.30	2,370	4.20	4,600
-0.20	410	1.10	1,250	2.40	2,480	4.40	4,850
-0.10	470	1.20	1,340	2.50	2,590	4.60	5,100
0.00	510	1.30	1,430	2.60	2,700	4.80	5,350
0.10	565	1.40	1,520	2.70	2,830	5.00	5,600
0.20	625	1.50	1,610	2.80	2,960		
0.30	680	1.60	1,700	2.90	3,100		
0.40	750	1.70	1,790	3.00	3,225		

WATER POWERS OF GEORGIA

Rating tables for Etowah River at Canton—Continued.

JANUARY 1 TO OCTOBER 10, 1897, AND JULY 24 TO DECEMBER 31, 1898.^a

Gage height	Dis-charge						
<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>
-0.70	244	0.60	1,059	1.90	2,067	8.00	7,130
-0.60	284	.70	1,129	2.00	2,150	9.00	7,960
-0.50	344	.80	1,200	2.20	2,316	10.00	8,790
-0.40	405	.90	1,273	2.40	2,482	11.00	9,620
-0.30	467	1.00	1,347	2.60	2,648	12.00	10,450
-0.20	530	1.10	1,422	2.80	2,814	13.00	11,280
-0.10	593	1.20	1,498	3.00	2,980	14.00	12,110
0.00	657	1.30	1,576	3.50	3,395	15.00	12,940
.10	722	1.40	1,655	4.00	3,810	16.00	13,770
.20	788	1.50	1,735	4.50	4,225	17.00	14,600
.30	855	1.60	1,818	5.00	4,640	18.00	15,430
.40	922	1.70	1,901	6.00	5,470	19.00	16,260
.50	990	1.80	1,984	7.00	6,300	20.00	17,090

OCTOBER 11 TO DECEMBER 31, 1897.

0.10	385	0.60	763	1.10	1,198	1.60	1,633
0.20	415	0.70	850	1.20	1,285	1.70	1,720
0.30	502	0.80	937	1.30	1,372	1.80	1,807
0.40	589	0.90	1,024	1.40	1,459	1.90	1,894
0.50	676	1.00	1,111	1.50	1,546	2.00	1,981

JANUARY 1 TO JULY 23, 1898.^b

0.00	270	1.30	1,379	2.60	2,562	3.90	3,720
0.10	325	1.40	1,470	2.70	2,653	4.00	3,800
0.20	380	1.50	1,561	2.80	2,744	4.10	3,884
0.30	470	1.60	1,652	2.90	2,835	4.20	3,968
0.40	560	1.70	1,743	3.00	2,926	4.30	4,052
0.50	651	1.80	1,834	3.10	3,017	4.40	4,136
0.60	742	1.90	1,925	3.20	3,108	4.50	4,220
0.70	833	2.00	2,016	3.30	3,199	4.60	4,304
0.80	924	2.10	2,107	3.40	3,290	4.70	4,388
0.90	1,015	2.20	2,198	3.50	3,375	4.80	4,472
1.00	1,106	2.30	2,289	3.60	3,460	4.90	4,556
1.10	1,197	2.40	2,380	3.70	3,550	5.00	4,640
1.20	1,288	2.50	2,471	3.80	3,640		

JANUARY 1, 1899, TO JULY 31, 1902.^c

-0.50	225	0.10	590	0.70	1,071	1.30	1,569
-0.40	275	.20	665	.80	1,154	1.40	1,652
-0.30	325	.30	740	.90	1,237	1.50	1,735
-0.20	385	.40	820	1.00	1,320		
-0.10	450	.50	905	1.10	1,403		
.00	515	.60	988	1.20	1,486		

AUGUST 1 TO DECEMBER 31, 1902.

0.20	350	1.30	1,130	2.40	2,120	3.50	3,110
.30	380	1.40	1,220	2.50	2,210	3.60	3,200
.40	420	1.50	1,310	2.60	2,300	3.70	3,290
.50	470	1.60	1,400	2.70	2,390	3.80	3,380
.60	530	1.70	1,490	2.80	2,480	3.90	3,470
.70	600	1.80	1,580	2.90	2,570	4.00	3,560
.80	680	1.90	1,670	3.00	2,660	4.20	3,740
.90	770	2.00	1,760	3.10	2,750	4.40	3,920
1.00	860	2.10	1,850	3.20	2,840		
1.10	950	2.20	1,940	3.30	2,930		
1.20	1,040	2.30	2,030	3.40	3,020		

^a Above gage height 1.50 this table is a tangent, the difference being 83 per tenth.^b Above gage height 5.00 feet this table is the same as the 1897 table. For the period July 24 to December 31, 1898, use the table which is applicable from January 1 to October 10, 1897.^c Above gage height 1.50 feet this table is the same as the table from January 1 to October 10, 1897.

Rating tables for Etowah River at Canton—Continued.

JANUARY 1 TO AUGUST 15, 1903.^a

Gage height	Dis-charge						
<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>
0.60	800	1.30	1,450	2.00	2,080	2.70	2,710
.70	900	1.40	1,540	2.10	2,170	2.80	2,800
.80	1,000	1.50	1,630	2.20	2,260	2.90	2,890
.90	1,090	1.60	1,720	2.30	2,350	3.00	2,980
1.00	1,180	1.70	1,810	2.40	2,440		
1.10	1,270	1.80	1,900	2.50	2,530		
1.20	1,360	1.90	1,990	2.60	2,620		

AUGUST 16 TO DECEMBER 31, 1903.

0.40	430	0.90	780	1.40	1,220	1.90	1,670
.50	500	1.00	860	1.50	1,310	2.00	1,760
.60	570	1.10	950	1.60	1,400	2.10	1,850
.70	640	1.20	1,040	1.70	1,490	2.20	1,940
.80	710	1.30	1,130	1.80	1,580	2.30	2,030

JANUARY 1 TO DECEMBER 31, 1904.^b

—0.40	190	0.20	415	0.80	840	3.00	2,820
— .30	215	.30	470	.90	930	4.00	3,720
— .20	245	.40	532	1.00	1,020	5.00	4,620
— .10	280	.50	600	1.50	1,470	6.00	5,520
.00	320	.60	675	2.00	1,920	7.00	6,420
.10	365	.70	755	2.50	2,370	8.00	7,320

^a Above gage height 3.00 feet this table is the same as the 1899 table.

^b Above gage height 1.00 foot the rating curve is a tangent, the difference being 90 per tenth.

Estimated monthly discharge of Etowah River at Canton.

[Drainage area, 604 square miles.]

Month	Discharge in second-feet			Run-off	
	Maximum	Minimum	Mean	Sec.-ft. per sq. mile	Depth in inches
1896					
January.....	6,600	810	1,509	2.50	2.88
February.....	3,850	870	1,608	2.65	2.86
March.....	1,180	810	970	1.61	1.86
September 9-30.....	950	200	280	.46	.38
October.....	2,320	270	476	.79	.91
November.....	3,940	470	906	1.50	1.67
December.....	1,180	470	598	.99	1.14
The year.....	9,786	244	1,134	1.87	25.35
1897					
January.....	3,478	593	1,194	1.98	2.28
February.....	2,316	1,059	1,291	2.14	2.23
March.....	6,466	1,059	2,335	3.86	4.45
April.....	9,786	1,200	2,238	3.71	4.14
May.....	2,150	722	1,036	1.72	1.98
June.....	2,980	657	941	1.56	1.74
July.....	6,383	657	1,186	1.96	2.26
August.....	1,347	405	859	1.42	1.64
September.....	1,200	284	355	.59	.65
October.....	1,285	244	533	.97	1.12
November.....	987	335	563	.96	1.07
December.....	1,981	676	934	1.55	1.79
The year.....	9,786	244	1,134	1.87	25.35
1898					
January.....	5,138	380	1,121	1.86	2.14
February.....	924	470	625	.98	1.02
March.....	4,640	310	1,014	1.68	1.94
April.....	3,460	560	1,160	1.92	2.14
May.....	924	380	584	.97	1.12
June.....	833	310	497	.82	.91
July.....	6,549	380	1,888	2.30	2.66
August.....	5,470	922	2,087	3.46	3.99
September.....	10,085	922	1,964	3.25	3.62
October.....	11,695	855	2,286	3.78	4.36
November.....	2,150	1,059	1,409	2.33	2.60
December.....	2,483	1,498	1,913	3.17	3.66
The year.....	11,695	310	1,337	2.21	30.16

WATER POWERS OF GEORGIA

Estimated monthly discharge of Etowah River at Canton—Continued.

Month	Discharge in second-feet			Run-off	
	Maximum	Minimum	Mean	Sec.-ft. per sq. mile	Depth in inches
1899					
January.....	8,790	1,652	2,396	3.97	4.58
February 25 days.....	8,790	1,652	2,987	4.95	4.30
March.....	15,596	1,652	3,382	5.60	6.45
April.....	4,474	1,652	2,344	3.88	4.33
May.....	1,984	1,320	1,631	2.78	3.21
June.....	4,142	1,320	1,644	2.72	3.08
July.....	3,810	1,320	1,770	2.98	3.38
August.....	1,984	1,154	1,534	2.54	2.93
September.....	1,154	325	729	1.21	1.35
October.....	665	225	472	.78	.90
November.....	1,403	450	614	1.02	1.14
December.....	2,980	590	1,098	1.82	2.10
The year.....	15,596	225	1,721	2.85	38.55
1900					
January.....	1,818	820	976	1.62	1.87
February.....	12,276	988	2,138	3.54	3.68
March.....	4,972	1,154	1,989	3.29	3.79
April.....	4,640	1,154	1,956	3.24	3.61
May.....	1,984	1,237	1,395	2.31	2.67
June 1-9.....	5,470	1,652	3,183	5.27	1.76
July.....	3,810	1,320	1,853	3.07	3.54
August.....	2,980	988	1,871	2.27	2.62
September.....	4,640	740	1,847	2.23	2.49
October.....	6,466	665	2,038	3.37	3.88
November.....	4,308	1,071	1,970	3.26	3.63
December.....	2,814	740	1,264	2.09	2.41
The year.....	17,090	590	1,938	3.21	43.56
1901					
January.....	14,185	988	1,965	3.25	3.75
February.....	5,470	1,154	2,135	3.53	3.68
March.....	14,600	988	1,890	3.13	3.61
April.....	4,474	1,154	2,299	3.81	4.25
May.....	14,268	1,154	2,394	3.96	4.57
June.....	4,889	1,154	2,442	4.04	4.51
July.....	2,648	905	1,317	2.18	2.51
August.....	11,280	820	2,533	4.19	4.83
September.....	2,814	988	1,483	2.46	2.74
October.....	2,897	590	1,039	1.72	1.96
November.....	1,320	905	1,052	1.74	1.94
December.....	17,090	988	2,715	4.50	5.19
The year.....	17,090	590	1,938	3.21	43.56
1902					
January.....	3,644	1,652	2,300	3.81	4.39
February.....	16,094	905	2,698	4.47	4.65
March.....	13,770	1,652	2,929	4.85	5.59
April.....	2,814	988	1,533	2.54	2.83
May.....	1,403	740	950	1.57	1.81
June.....	2,482	740	1,215	2.01	2.24
July.....	1,154	740	920	1.52	1.75
August.....	1,040	350	562	.98	1.07
September.....	2,660	530	897	1.49	1.66
October.....	2,430	470	725	1.20	1.38
November.....	3,830	420	978	1.62	1.81
December.....	3,740	680	1,737	2.88	3.32
The year.....	16,094	350	1,454	2.41	32.50
1903					
January.....	2,800	900	2,136	3.54	4.08
February.....	15,181	1,180	3,934	6.62	6.79
March.....	11,280	1,900	4,004	6.63	7.64
April.....	5,470	1,810	2,618	4.34	4.84
May.....	2,620	1,090	1,450	2.40	2.77
June.....	9,454	1,180	2,640	4.37	4.88
July.....	4,889	800	1,544	2.66	2.95
August.....	2,530	500	856	1.42	1.64
September.....	1,670	430	558	.92	1.03
October.....	860	500	598	.99	1.14
November.....	1,310	430	586	.97	1.08
December.....	570	430	459	.76	.88
The year.....	15,181	430	1,782	2.95	39.72

Estimated monthly discharge of Etowah River at Canton—Continued.

Month	Discharge in second-feet			Run-off	
	Maximum	Minimum	Mean	Sec.-ft. per sq. mile	Depth in inches
1904					
January.....	1,650	532	720	1.19	1.37
February.....	2,460	675	916	1.52	1.64
March.....	2,010	675	914	1.51	1.74
April.....	1,020	532	650	1.08	1.20
May.....	1,290	215	469	.776	.895
June.....	3,540	215	479	.798	.885
July.....	840	280	418	.692	.798
August.....	7,320	320	979	1.62	1.87
September.....	470	190	278	.460	.513
October.....	320	190	236	.391	.451
November.....	775	320	480	.795	.887
December.....	2,370	532	724	1.20	1.33
The year.....	7,320	190	605	1.00	13.63

ETOWAH RIVER AT ROME.

Measurements were made at this station for several years in connection with the measurements of Coosa River at Rome. Measurements were referred to a bench mark on the bridge, and the gage put in July 1, 1903, by J. M. Giles was referred to the same bench mark. This gage is located at the Second Avenue Bridge in the city of Rome, Ga., about 1 mile above the mouth of the river.

The channel is curved for 1,000 feet above and below the station. Both banks are high and overflow only under the approaches to the bridge. The bed of the stream is of rock and is permanent, but the channel is obstructed by the crib of an old pier foundation in the middle of the river. Discharge measurements have been made from the sidewalk on the upstream side of the single-span iron bridge and its approaches. The initial point for soundings is the center of the post at the end of the iron hand rail on the right bank, upstream side. The gage is a vertical timber driven into the bed of the river and spiked to a birch tree on the left bank about 50 feet below the bridge. The bench mark is the top of the downstream end of the third crossbeam from the left bank end of the bridge; elevation, 43.00 feet above the zero of the gage. The station was discontinued December 31, 1903.

WATER POWERS OF GEORGIA

Discharge measurements of Etowah River at Rome.

Date		Gage height	Dis-charge	Date		Gage height	Dis-charge
1903		<i>Feet</i>	<i>Sec.-ft.</i>	1903		<i>Feet</i>	<i>Sec.-ft.</i>
March 14		9.55	6,316	July 18		2.98	2,376
June 5		13.65	17,130	September 4		1.20	1,293
July 1		3.27	2,986	November 28		1.01	1,080
July 3		3.15	2,704				

Daily gage height, in feet, of Etowah River at Rome.

Day	July	Aug.	Sept.	Oct.	Nov.	Dec.	Day	July	Aug.	Sept.	Oct.	Nov.	Dec.
1903							1903						
1	3.3	3.0	1.0	1.0	1.0	1.0	17	3.4	2.9	2.0	1.2	1.3	1.0
2	3.0	3.6	.9	1.0	1.0	1.0	18	3.2	2.7	1.9		1.5	1.0
3	3.3	3.4	.8	.9	1.3	1.0	19	3.1	2.4	1.8		2.2	1.0
4	3.0	3.3	.7	.8	1.9	1.0	20	3.0	2.2	1.8		1.8	1.0
5	3.5	4.0	.6	.8	2.8	1.0	21	2.9	2.0	1.7		1.3	1.0
6	2.7	3.2	.6	.8	2.2	1.0	22	2.8	1.7	1.6		1.2	1.0
7	2.7	2.9	.6	.7	2.0	1.0	23	2.7	1.6	1.5		1.1	1.0
8	3.1	2.7	.6	.8	1.8	1.0	24	2.5	1.6	1.5		1.1	1.1
9	3.4	2.3	.5	1.0	1.3	1.0	25	2.4	1.5	1.4		1.1	1.2
10	3.3	2.1	.5	1.7	1.0	1.2	26	2.3	1.4	1.3		1.0	1.3
11	3.2	1.9	.5	1.6	1.1	1.1	27	2.4	1.3	1.2		1.0	1.3
12	3.2	1.8	.5	1.4	1.0	1.0	28	2.4	1.3	1.2		1.0	1.3
13	3.6	1.7	.5	1.1	1.6	1.0	29	2.3	1.2	1.1		1.0	1.3
14	9.0	1.6	.6	1.1	1.5	1.0	30	2.9	1.2	1.1	1.1	1.0	1.3
15	6.4	1.8	1.0	1.0	1.3	1.0	31	2.8	1.1		1.0		1.2
16	4.6	4.1	2.0	1.0	1.3	1.0							

Rating table for Etowah River at Rome from July 1 to December 31, 1903.

Gage height	Discharge						
<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>
0.50	900	1.80	1,598	3.20	2,772	5.80	6,180
.60	944	1.90	1,665	3.40	2,010	6.00	6,470
.70	989	2.00	1,733	3.60	2,250	6.20	6,770
.80	1,035	2.10	1,801	3.80	3,490	6.40	7,070
.90	1,082	2.20	1,869	4.00	3,730	6.60	7,375
1.00	1,130	2.30	1,937	4.20	3,975	6.80	7,685
1.10	1,179	2.40	2,005	4.40	4,224	7.00	8,000
1.20	1,230	2.50	2,077	4.60	4,478	7.50	8,800
1.30	1,285	2.60	2,155	4.80	4,741	8.00	9,600
1.40	1,344	2.70	2,241	5.00	5,020	8.50	10,400
1.50	1,405	2.80	2,335	5.20	5,310	9.00	11,200
1.60	1,468	2.90	2,437	5.40	5,600		
1.70	1,532	3.00	2,546	5.60	5,890		

Estimated monthly discharge of Etowah River at Rome.

[Drainage area 1,854 square miles.]

Month	Discharge in second-feet			Run-off	
	Maximum	Minimum	Mean	Sec.-ft. per sq. mile	Depth in inches
1903					
July	11,200	1,937	3,246	1.75	2.02
August	3,852	1,179	2,001	1.08	1.25
September	1,733	900	1,206	.65	.73
October 1-17 and 29-31	1,532	989	1,162	.63	.47
November	2,335	1,130	1,359	.73	.81
December	1,285	1,130	1,168	.63	.73

ETOWAH RIVER NEAR ROME.

This station was established August 17, 1904, by M. R. Hall. It is located at Freemans Ferry, about 5 miles above Rome.

The channel is straight for about 3,000 feet above and 1,000 feet below the station. The current is swift. There is a small shoal of rock about 50 feet below the gaging section. About 1,000 feet below there is an old fish-trap dam, but this has not been used for years, and is probably constant. Both banks are high, but are subject to overflow during high water. The bed of the stream is composed of small rock and pebbles, and is uniform and permanent. There is but one channel at all stages, the water being about 2.5 feet deep at low water. Discharge measurements are made from a small boat, the meter being suspended from the ferry cable. Measurements can be made from the bridge at Rome, as no large quantity of water enters the river between the ferry and that place. The initial point for soundings is the center of the windlass for the ferry cable on the left bank of the river.

The original gage, reading from 0 to 7 feet, is attached to a sycamore tree at left edge of river, about 250 feet below the ferry. A second section, reading from 7 to 20 feet, is attached to a post 10 feet upstream from the first section and 10 feet from the edge of the river at low water. A third section, reading from 20 to 30 feet, is attached to a maple tree opposite the post and 15 feet farther from the water's edge. The gage is read once each day by W. A. Gresham, who is paid by the Georgia Geological Survey. Bench marks were established as follows: (1) Head of lag screw driven into root of maple, to which gage 20 to 30 feet is attached; elevation, 19.26 feet. (2) Center mark on copper plug set horizontally in brick wall of F. B. Freeman's residence, on east end of house, near northeast corner, just below floor level; elevation, 27.99 feet. Elevations refer to the datum of the gage.

WATER POWERS OF GEORGIA

Discharge measurements of Etowah River near Rome.

Date	Gage height	Dis-charge	Date	Gage height	Dis-charge
1904			1905		
	<i>Feet</i>	<i>Sec.-ft.</i>		<i>Feet</i>	<i>Sec.-ft.</i>
August 18 <i>a</i>	2.00	1,049	October 9.....	1.76	862
August 18 <i>b</i>	2.03	1,064	October 9.....	1.76	850
September 27 <i>b</i>	1.37	470	1906		
October 15 <i>b</i>	1.26	397	May 8.....	3.85	3,690
November 8 <i>b</i>	1.50	574	June 27.....	3.30	2,350
1905			October 16.....	2.88	2,180
February 28.....	3.10	2,468	October 16.....	2.89	2,160
May 12.....	2.40	1,618			
July 24.....	2.11	1,168			

a At Rome, Second Avenue Bridge.*b* At Freeman's Ferry, 5 miles above Rome.

Daily gage height, in feet, of Etowah River near Rome.

Day	Aug.	Sept.	Oct.	Nov.	Dec.	Day	Aug.	Sept.	Oct.	Nov.	Dec.
1904						1904					
1.....		1.75	1.3	1.3	1.55	17.....	2.1	1.4	1.3	1.6	1.7
2.....		1.75	1.3	1.3	1.55	18.....	2.05	1.4	<i>a</i> 1.3	1.55	1.75
3.....		1.7	1.25	1.5	1.6	19.....	2.1	1.4	1.25	1.55	1.7
4.....		1.7	1.35	1.4	1.7	20.....	1.85	1.4	1.35	1.55	1.7
5.....		1.75	1.3	1.5	1.8	21.....	1.8	1.4	1.3	1.55	1.65
6.....		1.8	1.3	1.6	3.1	22.....	2.5	1.4	1.3	1.55	1.6
7.....		1.7	1.3	1.55	3.0	23.....	1.7	1.4	1.3	1.6	1.6
8.....		1.65	1.3	1.55	2.2	24.....	3.4	1.4	1.2	1.9	1.6
9.....		1.6	1.25	1.55	1.9	25.....	<i>a</i> 3.0	1.35	1.25	1.75	1.6
10.....		<i>a</i> 1.6	1.2	1.55	1.8	26.....	2.1	1.35	1.3	1.6	1.7
11.....		1.6	1.35	1.4	1.9	27.....	<i>a</i> 2.5	1.35	1.3	1.6	1.7
12.....		1.6	1.35	1.4	1.95	28.....	2.8	1.35	1.3	1.55	3.0
13.....		1.5	1.4	<i>a</i> 1.5	1.8	29.....	2.3	1.35	1.3	1.55	3.4
14.....		1.5	1.3	1.6	1.7	30.....	1.9	1.35	1.3	1.55	2.5
15.....		1.5	1.3	1.75	1.7	31.....	1.9	1.3	2.0
16.....		1.45	1.3	1.6	1.65						

a Gage height interpolated August 25 and 27, September 10, October 18, and November 13, 1904.

MOBILE DRAINAGE BASIN, STREAM FLOW

Daily gage height, in feet, of Etowah River near Rome—Continued.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1905												
1	2.0	2.3	3.0	2.5	2.9	2.4	2.4	2.1	1.9	2.7	1.9	2.0
2	2.0	2.3	2.9	2.5	2.5	2.3	3.2	2.1	2.0	2.3	1.8	2.1
3	1.9	2.2	2.8	2.5	2.4	2.3	2.9	2.1	2.5	2.1	1.7	5.2
4	2.0	2.1	2.8	2.4	2.4	2.3	2.4	2.1	3.0	2.0	1.7	16.2
5	1.9	2.1	2.7	2.4	3.0	2.4	2.5	2.1	2.9	1.8	1.6	9.1
6	2.3	2.2	2.7	2.7	2.7	2.3	2.8	2.1	2.0	1.8	1.6	3.9
7	2.6	2.25	2.6	2.7	2.7	2.3	4.6	2.1	1.9	1.7	1.6	3.0
8	2.35	3.0	2.6	2.7	3.3	2.2	4.1	2.1	1.9	1.7	1.5	4.1
9	2.3	7.4	2.7	2.6	2.8	2.2	4.4	2.0	1.8	1.6	1.6	13.5
10	2.2	3.7	2.9	2.8	3.3	2.2	4.8	2.5	1.8	2.1	2.1	9.4
11	3.4	5.9	3.3	2.6	2.7	2.2	3.9	2.9	1.8	3.0	2.1	4.5
12	4.7	4.3	2.9	2.6	2.5	2.2	7.0	3.8	2.9	3.7	2.0	3.8
13	15.7	4.5	2.9	3.0	2.4	2.2	6.0	3.1	3.0	2.6	2.0	4.1
14	9.3	7.4	2.8	2.9	2.3	2.3	4.0	2.9	2.1	2.5	1.9	4.5
15	6.2	4.7	2.7	2.7	2.3	2.6	2.9	5.1	2.0	2.3	1.8	4.9
16	3.1	3.7	2.6	2.7	4.9	2.5	2.7	4.0	1.9	2.4	1.8	3.8
17	2.8	3.3	2.5	2.9	4.8	2.5	2.5	3.4	1.8	2.3	1.7	3.6
18	2.5	3.2	2.5	2.6	3.8	2.3	2.4	2.6	1.8	2.3	1.6	3.2
19	2.5	3.0	2.5	2.5	2.7	2.3	2.4	2.5	1.8	2.3	3.3	2.9
20	2.5	3.3	2.6	2.4	2.4	2.5	2.3	2.5	1.7	2.2	2.0	4.0
21	2.5	11.0	4.2	2.4	2.8	2.9	2.3	2.4	1.8	2.1	1.9
22	2.5	10.0	4.5	2.5	3.5	2.5	2.4	2.3	1.7	2.0	1.8
23	2.4	5.3	3.5	2.5	4.2	2.6	2.3	2.3	1.7	1.9	1.8
24	2.35	4.5	3.0	2.4	9.0	3.8	2.1	3.0	1.7	1.9	1.9	4.2
25	2.35	3.3	2.9	2.4	4.8	2.6	2.1	3.0	1.7	2.0	2.1	3.8
26	2.2	3.5	2.8	2.4	3.6	2.3	2.2	2.6	1.6	2.2	2.0	3.5
27	2.0	3.2	2.7	2.4	3.6	2.3	2.1	2.3	1.6	2.3	2.4	3.2
28	2.0	3.1	2.7	2.4	3.2	2.8	2.1	2.3	1.6	2.4	2.3	3.2
29	2.0	2.6	2.3	2.8	3.0	2.3	2.2	1.6	1.9	2.3	3.3
30	1.9	2.5	2.6	2.8	2.3	2.0	1.7	1.9	2.0	3.3
31	2.4	2.5	2.5	2.2	1.9	8.0
1906												
1	2.9	3.8	2.6	5.4	3.3	2.7	2.6	4.0	3.4	10.8	2.75	2.8
2	2.8	3.5	2.6	5.0	3.1	2.9	2.5	3.9	3.1	8.8	2.75	2.8
3	3.9	3.4	4.3	4.5	3.0	3.0	2.5	3.8	2.8	7.9	2.7	2.8
4	15.4	3.4	5.6	4.1	3.5	3.0	2.9	3.7	2.7	6.8	2.7	2.8
5	13.3	3.3	4.9	4.0	3.3	2.9	2.3	3.6	2.7	4.8	2.7	2.7
6	6.5	3.3	3.5	3.9	3.1	2.8	2.6	3.5	5.5	4.5	2.7	2.7
7	4.3	3.2	3.0	3.8	4.0	2.7	3.0	3.3	4.0	4.1	2.7	2.7
8	3.9	3.2	3.0	3.7	4.2	2.6	2.7	3.1	3.9	4.0	2.65	2.7
9	4.0	3.2	4.8	3.6	3.3	2.6	2.6	2.8	4.8	3.3	2.65	2.7
10	5.8	3.1	4.0	4.5	3.0	2.5	3.2	2.7	3.3	3.4	2.6	2.9
11	3.5	3.1	3.5	4.0	2.9	2.5	3.0	3.2	3.3	3.2	2.6	5.8
12	3.5	3.0	3.2	3.5	2.9	3.0	2.3	2.8	3.2	3.2	2.6	5.0
13	3.7	3.0	3.1	3.4	2.8	7.3	2.6	2.7	3.1	3.0	2.6	3.6
14	3.5	3.0	3.2	3.4	2.8	9.5	2.5	2.9	2.9	3.0	2.6	3.6
15	3.4	3.0	16.4	4.0	2.3	7.7	5.5	3.2	2.8	2.9	2.65	3.5
16	3.0	3.0	16.7	3.7	2.7	7.8	4.7	4.0	2.6	2.3	2.7	3.2
17	4.0	2.9	9.4	3.5	2.7	6.5	3.5	4.2	2.5	2.35	2.8	3.0
18	3.6	2.9	5.8	3.5	2.6	3.6	10.5	4.9	2.5	4.0	3.0	4.8
19	3.4	2.8	14.3	3.4	2.6	3.3	3.8	5.0	3.1	8.5	12.9	4.5
20	3.5	2.3	22.7	3.3	2.6	3.1	6.0	3.3	4.8	4.5	10.5	4.0
21	3.2	2.3	20.0	3.3	2.6	3.0	4.3	4.2	3.6	3.6	9.0	4.0
22	7.3	2.9	10.0	3.2	2.6	2.9	4.7	4.0	3.6	3.3	9.0	3.8
23	11.3	3.0	5.3	3.2	2.6	2.8	4.3	4.0	3.5	3.2	8.5	3.4
24	10.7	2.3	4.5	3.1	2.5	2.7	5.3	3.9	3.5	3.1	7.5	3.4
25	5.5	2.3	4.2	3.1	2.5	2.7	3.6	3.5	3.4	3.0	4.0	3.2
26	4.5	2.8	4.0	3.1	2.5	4.4	3.2	3.3	3.4	3.0	3.0	3.0
27	4.5	2.7	4.1	3.0	5.1	3.4	3.0	3.2	3.3	2.9	3.0	3.4
28	4.7	2.7	4.9	3.2	3.7	3.0	2.9	3.0	3.2	2.9	2.9	3.4
29	4.5	5.5	3.5	3.2	2.8	3.3	4.0	3.0	2.3	2.9	3.8
30	4.2	6.0	3.4	2.9	2.7	4.6	4.2	3.2	2.3	2.8	3.7
31	4.0	7.1	2.3	4.4	3.9	2.3	9.8

WATER POWERS OF GEORGIA

Rating table for Etowah River near Rome, from August 17, 1904, to December 31, 1905.^a

Gage height	Dis-charge						
<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>
1.20	360	1.80	830	2.40	1,500	3.00	2,320
1.30	425	1.90	930	2.50	1,625	3.20	2,625
1.40	495	2.00	1,035	2.60	1,755	3.40	2,950
1.50	570	2.10	1,145	2.70	1,890		
1.60	650	2.20	1,260	2.80	2,030		
1.70	735	2.30	1,380	2.90	2,175		

^a This station was established for low-water records, and only these are reliable. The above rating table is applicable only to gage heights less than 3.5 feet. As it does not apply to the higher gage heights no monthly estimates have been made for 1905.

Rating table for Etowah River near Rome, for 1905-6.

Gage height	Dis-charge						
<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>
1.50	570	2.90	2,175	4.60	5,100	9.00	15,180
1.60	650	3.00	2,320	4.80	5,480	10.00	17,880
1.70	735	3.10	2,470	5.00	5,860	11.00	20,700
1.80	830	3.20	2,625	5.20	6,260	12.00	23,600
1.90	930	3.30	2,785	5.40	6,660	13.00	26,660
2.00	1,035	3.40	2,950	5.60	7,080	14.00	29,800
2.10	1,145	3.50	3,120	5.80	7,500	15.00	33,000
2.20	1,260	3.60	3,295	6.00	7,930	16.00	36,300
2.30	1,380	3.70	3,470	6.20	8,370	17.00	39,600
2.40	1,500	3.80	3,645	6.40	8,820	18.00	43,000
2.50	1,625	3.90	3,820	6.60	9,280	19.00	46,500
2.60	1,755	4.00	4,000	6.80	9,740	20.00	50,000
2.70	1,890	4.20	4,360	7.00	10,200		
2.80	2,030	4.40	4,720	8.00	12,600		

NOTE.—The above table is based on discharge measurements made during 1904-1906 and is well defined below gage height 4 feet. Above gage height 7 feet the curve becomes uncertain and is only approximate at the high stages.

Estimated monthly discharge of Etowah River near Rome.

[Drainage area, 1,854 square miles.]

Month	Discharge in second-feet			Run-off	
	Maximum	Minimum	Mean	Sec.-ft. per sq. mile	Depth in inches
1904					
August (17-31)	2,950	735	1,384	0.746	0.416
September	830	460	588	.317	.354
October	495	360	423	.223	.263
November	930	425	614	.331	.369
December	2,950	610	1,027	.554	.639

Estimated monthly discharge of Etowah River near Rome—Continued.

[Drainage area, 1,800 square miles.]

Month	Discharge in second-feet			Run-off	
	Maximum	Minimum	Mean	Sec.-ft. per sq. mile	Depth in inches
1905					
January.....	35,300	930	3,350	1.86	2.14
February.....	20,700	1,140	5,250	2.92	3.04
March.....	4,910	1,620	2,160	1.20	1.38
April.....	2,320	1,380	1,720	.956	1.07
May.....	15,200	1,380	2,940	1.63	1.88
June.....	3,640	1,260	1,610	.894	1.00
July.....	10,200	1,140	2,650	1.47	1.70
August.....	6,060	930	1,840	1.02	1.18
September.....	2,320	650	1,050	.583	.65
October.....	3,470	650	1,310	.723	.84
November.....	2,780	570	985	.547	.61
December.....	37,000	1,040	α7,130	3.96	4.56
The year.....	37,000	570	2,670	1.43	20.05
1906					
January.....	34,300	2,030	6,990	3.88	4.47
February.....	3,640	1,890	2,410	1.34	1.40
March.....	59,400	1,760	11,700	6.50	7.49
April.....	6,660	2,320	3,460	1.92	2.14
May.....	6,060	1,620	2,430	1.35	1.56
June.....	16,500	1,620	3,900	2.17	2.42
July.....	19,300	1,620	4,170	2.32	2.63
August.....	5,360	1,890	3,350	1.86	2.14
September.....	6,870	1,620	2,940	1.63	1.82
October.....	20,100	2,030	4,750	2.64	3.04
November.....	26,400	1,760	5,010	2.78	3.10
December.....	17,300	1,890	3,580	1.99	2.29
The year.....	59,400	1,620	4,560	2.53	34.55

α December 21-23 estimated.

NOTE.—Values for 1905 and 1906 are excellent, except March, 1906, which is good.

AMICALOLA RIVER NEAR BALLGROUND.

This station was established in 1905. It is located at Hollenshed's Bridge, one-fourth of a mile above Heard's mill, and about 15 miles northeast of Ballground.

Discharge measurements are made from the two-span covered bridge, about 150 feet in total length. The meter can be let down through the floor at the side of the bridge, but the current here is rough and not good for measurements. Some of the measurements were made about forty feet below the bridge. The stream is important, and a good section is difficult to find, but it is probable that a better place than this will be found.

Gage heights are determined directly from the bench marks, which is a point on top of the downstream end of the wooden floor beam, 25 feet from the left-bank pier; elevation, 17.00 feet above the datum of the assumed gage.

WATER POWERS OF GEORGIA

Discharge measurements of Amicalola Creek near Ballground.

Date	Gage height	Dis-charge
1905		
June 23.....	<i>Feet</i> 1.58	<i>Sec.-ft.</i> 184
November 16 <i>a</i>	1.35	108
November 16 <i>a</i>	1.35	100

a Made at different section.

LONG SWAMP CREEK NEAR BALLGROUND.

This station was established in 1905. It is located at a wooden wagon bridge about 2 miles southeast from Ballground, and half a mile above the mouth of the creek, which empties into Etowah River.

The current is swift at the station, also above and below it. The bed is sandy, and the water is shallow. Measurements are made from the downstream side of the wooden bridge of three spans. The middle span, which includes all of the creek at all but high stages, is 50 feet long, and the two end spans are 35 feet each. Gage heights are determined directly from the bench mark, which is a nail driven horizontally into the upstream side of a large sycamore tree on the right bank about 100 feet below the bridge; elevation, 8.00 feet above the datum of the assumed gage.

Discharge measurements of Long Swamp Creek near Ballground.

Date	Gage height	Dis-charge
1905		
June 24.....	<i>Feet</i> 1.27	<i>Sec.-ft.</i> 93
November 15.....	.84	50

COOSA RIVER AT ROME.

Coosa River is formed at Rome by the junction of Etowah and Oostanaula rivers. Both the tributary rivers rise in the northern part of Georgia and flow for the most part through a hilly, broken country, well wooded, about one-fourth of the land being under cultivation. The channel of the Etowah is straight and the current swift and unobstructed, but the Oostanaula is rather sluggish and somewhat obstructed by piers. The banks are high and are liable to overflow at high stages. The gage is in two sections: The first,

0 to 5 feet, is fastened to the downstream left-hand corner of the cofferdam around the center pier of the turn span; the second, 5 to 44 feet, is fastened to the downstream side of the same pier. The zero of the gage is 576 feet above sea level.

The measurements at Rome are made on the Oostanaula and the Etowah just above their junction. The Etowah is measured at the Second Avenue Bridge, and the Oostanaula at the Fifth Avenue Bridge in Rome, and the results are added to give the flow of the Coosa. The gage height is taken from the United States Weather Bureau gage at the Fifth Avenue Bridge on the Oostanaula. There is practically no fall on Oostanaula River from the Fifth Avenue Bridge to the junction; hence the gage is used as a Coosa River gage, and the gage heights are considered as gage heights of Coosa River. The Weather Bureau established this gage in 1890, but now maintains it only from November 1 to April 30; W. M. Towers, the observer, has, however, furnished the Geological Survey with monthly reports of the daily gage height for the entire year.

The station was discontinued December 31, 1903, on account of the uncertain velocity at low stages of the Oostanaula section.

WATER POWERS OF GEORGIA

Discharge measurements of Coosa River at Rome.

Date	Gage height	Dis-charge	Date	Gage height	Dis-charge
September 29..... 1896	<i>Feet</i> 0.20	<i>Sec.-ft.</i> 1,209	May 19..... 1900	<i>Feet</i> 2.30	<i>Sec.-ft.</i> 4,496
May 7..... 1897	2.75	4,646	September 13.....	.90	1,992
October 5.....	.15	990	December 8.....	3.73	6,066
May 11..... 1898	1.90	2,946	January 23..... 1901	3.60	6,454
September 17.....	2.60	3,913	April 5.....	9.90	16,690
October 11.....	5.05	8,324	June 22.....	3.70	6,030
October 22.....	4.10	6,489	October 15.....	3.15	5,388
November 30.....	3.90	6,059	June 24..... 1902	1.30	2,483
January 25..... 1899	3.80	6,540	October 8.....	.80	1,800
January 25.....	3.60	5,982	November 8.....	1.10	2,332
May 19.....	2.75	4,394	March 14..... 1903	9.70	16,150
June 16.....	2.40	3,362	June 5.....	12.55	25,010
August 4.....	1.45	2,885	July 1.....	2.80	5,305
October 13.....	.60	1,769	July 3.....	2.70	4,053
February 21..... 1900	4.80	8,115	July 18.....	2.85	4,403
			September 4.....	.90	2,211
			November 28.....	.75	1,892

Daily gage height, in feet, of Coosa River at Rome.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1..... 1897	1.0	2.8	3.3	7.1	4.1	1.8	1.7	0.8	1.0	0.0	0.5	1.1
2.....	1.0	9.7	3.2	7.5	4.0	2.3	1.5	.7	.5	.0	.9	1.0
3.....	1.0	11.5	3.1	8.2	3.5	2.0	1.0	1.2	.3	.0	1.0	1.2
4.....	1.0	9.6	3.3	9.4	3.3	3.0	.9	1.0	.5	-.1	1.0	2.3
5.....	1.0	8.2	3.5	14.8	3.0	2.4	2.0	.3	.4	-.1	1.0	3.2
6.....	1.3	5.2	7.6	18.9	3.0	2.0	1.9	.8	.3	-.1	.8	3.7
7.....	1.1	5.0	19.7	17.0	3.0	2.0	1.9	1.9	.3	-.1	.8	3.2
8.....	1.1	4.3	18.9	14.7	2.3	2.0	3.0	2.0	.2	-.1	.3	2.2
9.....	1.0	5.0	15.4	12.1	2.6	2.0	2.1	2.0	.1	-.1	.3	1.9
10.....	1.0	4.4	13.5	9.6	2.6	1.9	1.9	1.6	.0	-.1	.7	1.7
11.....	.9	4.5	12.0	7.2	2.6	1.9	2.5	2.4	.0	-.1	.7	1.5
12.....	.9	7.4	11.5	6.2	3.0	1.9	2.8	1.8	.0	1.1	.7	1.4
13.....	.9	8.7	18.6	5.8	3.4	1.8	2.0	1.3	.0	1.6	.7	1.3
14.....	2.3	7.2	21.3	5.0	4.0	1.7	1.6	.8	.0	1.3	.6	2.2
15.....	6.2	5.5	23.8	6.0	5.0	1.7	1.3	.6	.0	1.0	.6	4.0
16.....	5.0	4.5	23.4	7.4	4.0	2.0	1.0	.6	.0	.8	.6	3.5
17.....	3.5	4.0	22.6	7.0	3.3	2.3	5.2	2.1	.0	.7	.6	2.5
18.....	3.9	3.7	21.4	5.0	2.8	2.3	4.2	3.2	-.1	.6	.6	2.2
19.....	5.0	3.4	19.7	4.5	2.7	2.0	4.8	2.4	.2	.6	.6	1.8
20.....	3.5	3.0	18.9	4.0	2.6	1.8	8.8	1.4	-.2	.6	.6	1.7
21.....	8.7	4.0	17.7	3.8	2.5	1.6	12.8	1.3	-.2	1.5	.6	3.2
22.....	9.5	3.9	15.3	3.7	2.4	1.5	7.3	1.5	-.2	1.3	.5	4.1
23.....	5.7	5.6	13.7	3.5	2.4	1.5	4.4	1.5	-.2	1.0	.6	5.8
24.....	4.0	11.7	12.9	3.5	2.4	1.4	3.9	1.5	-.2	.8	.5	5.3
25.....	3.5	8.6	9.1	3.5	2.3	1.3	2.6	1.1	-.3	.8	.5	3.7
26.....	3.0	6.7	6.0	3.5	2.2	1.2	2.6	.8	-.3	.7	.5	2.3
27.....	2.5	4.7	5.2	3.4	2.1	1.2	3.8	.5	-.4	.7	.5	3.3
28.....	2.5	3.5	4.3	3.4	2.0	1.0	3.0	.4	-.4	.7	.9	2.0
29.....	2.5	4.5	3.4	2.0	1.1	2.4	.4	-.4	.6	1.1	2.3
30.....	2.3	4.2	3.2	1.9	2.0	1.4	.4	-.4	.5	1.1	2.0
31.....	2.2	4.0	1.9	1.2	.55	2.0

MOBILE DRAINAGE BASIN, STREAM FLOW

Daily gage height, in feet, of Coosa River, at Rome—Continued.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1898												
1	1.8	3.6	1.2	9.0	2.3	1.4	1.2	4.8	2.0	2.0	2.2	4.2
2	1.8	3.1	1.2	6.1	2.6	1.4	1.0	4.4	7.8	2.0	2.2	4.0
3	1.7	2.8	1.2	4.2	2.4	1.4	1.0	3.2	21.7	2.0	2.2	3.8
4	1.7	2.6	1.2	3.6	2.3	1.4	1.0	4.4	24.3	4.9	2.2	3.8
5	1.6	2.4	1.2	9.9	2.2	1.3	1.0	8.0	22.2	22.0	2.0	4.3
6	1.6	2.2	1.2	17.2	2.1	1.3	1.3	5.6	20.0	23.8	2.2	5.0
7	1.3	2.0	1.2	14.5	2.0	1.3	2.0	4.4	17.6	19.0	2.6	4.3
8	1.3	1.8	1.2	10.9	2.0	1.3	2.8	4.4	16.4	18.4	2.4	4.0
9	1.3	1.8	1.2	7.0	2.0	1.3	3.2	3.4	9.7	16.6	2.3	3.7
10	1.3	1.7	1.2	4.1	2.0	1.3	1.7	3.0	5.0	14.0	2.1	3.4
11	1.4	1.5	1.2	4.0	2.0	1.3	2.8	9.9	5.4	5.6	2.0	3.3
12	2.0	1.5	1.2	3.8	1.9	1.2	2.0	7.2	4.6	4.2	2.0	3.3
13	2.0	1.3	1.2	3.6	1.8	1.4	1.8	4.2	3.8	3.8	2.0	3.2
14	4.0	1.3	1.3	3.5	1.8	1.3	1.6	3.4	3.2	3.7	2.3	3.0
15	3.8	1.3	1.6	3.5	1.7	1.8	3.7	3.0	3.0	3.5	2.3	3.0
16	3.6	1.3	3.7	3.4	1.6	1.7	3.7	2.5	2.9	3.2	2.9	2.8
17	3.6	1.2	7.3	3.0	1.5	1.8	2.2	2.0	2.7	3.1	2.9	2.7
18	3.2	1.2	5.3	3.0	1.5	1.3	1.9	2.2	2.5	6.5	4.0	2.6
19	2.8	1.2	3.7	3.0	1.5	2.2	1.7	2.2	2.3	9.0	5.0	2.6
20	4.4	1.2	3.0	3.6	1.4	3.5	1.6	3.2	2.2	6.0	4.5	2.6
21	6.5	1.2	2.5	3.6	1.4	3.2	1.5	2.8	2.2	4.2	5.0	2.8
22	6.4	1.2	2.5	3.2	1.4	3.0	1.4	3.9	2.3	3.9	4.0	2.9
23	5.0	1.2	2.3	3.0	1.4	2.3	1.3	2.2	2.6	4.0	5.0	3.2
24	4.5	1.2	2.2	7.2	1.4	2.6	1.3	2.2	4.1	3.9	7.0	3.6
25	7.0	1.2	2.1	8.2	1.4	2.0	3.7	1.9	3.1	3.5	4.7	3.0
26	14.0	1.2	2.0	6.0	1.4	1.8	3.8	2.7	3.0	3.3	3.9	2.9
27	14.6	1.2	1.9	4.6	1.4	1.8	2.9	4.0	2.7	3.1	4.5	2.7
28	11.6	1.2	1.8	4.0	1.4	1.8	3.7	4.4	2.5	3.0	4.3	2.6
29	8.6	2.0	3.7	1.4	1.6	4.2	3.4	2.3	2.8	4.3	2.5
30	4.6	3.5	3.2	1.4	1.4	4.1	2.0	2.1	2.6	3.9	2.4
31	3.9	11.4	1.4	4.2	2.3	2.4	2.4
1899												
1	3.0	6.9	19.7	13.2	4.0	3.0	1.7	2.2	3.4	4	7	1.1
2	3.4	7.8	15.0	10.6	3.7	2.6	1.5	1.9	2.0	3	6	1.1
3	3.0	6.0	3.6	7.9	3.7	2.6	1.0	1.7	1.6	3	5	1.5
4	2.7	9.2	6.6	7.2	3.5	2.0	3.9	1.5	1.4	3	5	1.3
5	2.6	15.3	7.8	9.5	3.5	2.0	2.0	1.4	1.3	3	4	1.1
6	2.6	18.2	9.0	8.2	3.5	2.0	1.9	1.5	1.3	5	4	1.0
7	3.6	27.8	3.0	8.2	3.7	2.0	1.9	1.6	1.2	7	3	.9
8	5.9	24.0	6.3	15.0	3.7	1.9	3.0	1.5	1.0	7	3	.8
9	5.9	22.4	5.7	13.4	3.6	1.3	2.1	1.8	1.0	8	3	.8
10	4.9	21.0	5.4	11.2	3.5	1.3	1.9	1.6	1.0	6	3	.8
11	4.0	19.0	5.2	9.5	3.3	1.3	2.5	1.4	2.9	1.0	3	.8
12	4.5	16.5	4.9	7.0	3.1	2.2	2.3	1.4	2.3	.9	3	2.8
13	4.0	7.0	4.5	6.4	3.1	3.3	2.0	1.2	1.5	.7	3	6.1
14	3.8	5.0	6.0	5.9	3.0	4.0	1.6	1.1	1.0	.7	4	5.0
15	3.6	5.0	16.6	5.6	3.0	3.5	1.3	1.3	.9	.6	4	3.2
16	3.6	5.5	27.7	5.4	2.9	2.5	1.8	1.9	.8	.6	5	2.0
17	4.0	8.9	29.2	5.2	2.3	2.1	5.2	1.6	.6	.6	9	1.3
18	4.2	9.5	25.3	4.8	2.8	2.0	4.2	1.4	.6	.6	7	1.7
19	4.0	8.5	24.9	4.7	2.8	2.0	4.3	1.1	.6	.6	5	1.3
20	3.7	7.7	26.2	4.6	2.8	2.0	3.8	.9	.7	.6	5	1.6
21	3.3	6.8	24.6	4.3	2.6	1.3	12.8	.9	.7	.7	5	2.0
22	3.2	6.9	23.0	4.1	2.6	2.2	7.9	.8	.6	.7	4	2.0
23	3.1	7.3	22.6	4.0	2.4	1.7	4.3	.8	.6	.6	1.0	1.8
24	3.5	6.6	21.9	5.4	2.6	1.7	3.9	.7	.5	.5	2.1	7.2
25	3.8	5.8	13.0	7.4	2.5	1.7	2.6	.7	.5	.4	1.5	7.5
26	3.3	5.5	10.5	9.1	2.4	1.7	2.6	.7	.5	.4	2.5	5.0
27	3.3	19.1	7.7	6.7	2.2	2.1	3.3	2.5	.5	.4	3.0	3.5
28	3.0	23.4	6.3	5.5	2.2	1.9	3.0	2.5	.6	.4	2.2	3.0
29	3.0	3.8	4.8	2.0	1.9	2.4	2.5	.5	.4	1.9	3.0
30	2.9	9.3	4.2	2.0	1.8	1.4	2.0	.4	.5	1.4	3.4
31	4.4	10.2	3.3	1.2	2.53	2.0

WATER POWERS OF GEORGIA

Daily gage height, in feet, of Coosa River, at Rome—Continued.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1900												
1	2.0	2.0	4.2	4.4	6.2	2.4	10.5	3.4	1.5	1.2	2.1	3.2
2	1.6	1.8	5.8	4.2	4.8	2.5	8.0	3.2	1.5	1.2	2.2	2.8
3	1.5	1.6	5.6	4.0	4.0	2.8	8.0	3.0	1.7	1.0	2.0	2.6
4	1.5	2.0	4.4	4.0	4.0	4.2	7.0	2.8	1.7	1.0	2.3	3.5
5	1.5	3.0	4.1	4.0	3.8	4.2	5.5	2.6	1.5	.9	2.3	7.4
6	1.5	3.8	3.8	4.0	3.7	4.2	4.2	2.5	1.5	.9	2.1	6.8
7	1.5	2.8	5.0	3.8	3.6	4.8	3.8	2.2	1.4	.9	2.1	5.2
8	1.5	2.4	8.2	3.8	3.4	13.0	3.8	2.2	1.0	3.8	2.0	3.8
9	1.5	4.0	15.0	3.6	3.0	12.6	4.3	2.0	1.0	5.9	1.9	3.6
10	1.5	6.9	13.4	3.5	3.0	8.0	4.3	2.0	.8	2.6	1.8	3.2
11	2.0	7.0	10.3	6.0	3.0	5.9	3.8	1.8	.8	2.0	1.8	2.8
12	7.0	6.4	7.5	11.0	3.0	5.0	3.4	1.8	.8	1.8	1.6	2.6
13	9.0	22.6	5.5	7.4	2.5	5.2	3.8	1.8	.8	2.5	1.5	2.6
14	7.2	27.2	4.8	5.5	2.4	5.3	3.4	1.7	.8	3.2	1.5	2.4
15	5.5	25.3	4.2	4.5	2.4	4.2	3.4	2.0	6.5	3.0	1.5	2.2
16	3.5	21.2	5.3	5.6	2.4	3.8	3.3	1.7	11.1	2.0	1.5	2.2
17	3.0	18.0	5.6	6.2	2.4	4.8	3.1	1.6	7.0	1.6	1.5	2.2
18	2.9	10.7	4.5	11.0	2.4	6.0	3.0	1.8	3.2	1.5	1.4	2.0
19	5.0	5.0	5.2	11.1	2.9	6.5	2.8	2.2	2.3	1.5	1.4	2.0
20	11.3	4.0	15.9	11.4	3.0	7.2	2.6	2.0	2.0	1.4	1.6	2.8
21	10.6	4.1	17.5	13.6	2.6	4.2	2.5	1.6	1.8	1.8	1.8	6.7
22	8.5	6.8	14.6	12.7	2.5	3.6	2.4	1.6	1.8	1.8	2.1	8.0
23	5.8	7.6	10.4	10.5	2.3	5.5	2.4	1.6	1.6	1.6	2.1	7.0
24	4.0	6.0	7.2	8.6	2.9	14.2	2.4	1.9	1.6	1.6	2.0	6.6
25	3.4	5.8	8.3	8.5	3.2	18.2	3.6	2.4	1.5	1.5	5.0	6.6
26	3.1	5.2	13.0	6.5	2.7	17.0	2.3	2.0	1.5	1.5	11.0	5.6
27	2.8	4.6	12.1	5.3	2.6	15.5	6.2	1.8	1.4	1.4	11.5	4.0
28	2.6	4.0	8.9	4.8	2.5	15.6	6.8	1.6	1.4	2.2	8.6	3.8
29	2.4	5.8	4.3	2.4	14.2	6.2	1.5	1.3	2.2	7.0	3.6
30	2.1	5.7	6.0	2.9	10.0	4.5	1.5	1.3	2.1	4.0	3.5
31	2.0	5.3	3.0	4.0	1.5	2.1	5.6
1901												
1	7.4	6.4	3.0	8.8	4.0	10.6	3.6	1.8	6.4	2.6	1.2	1.3
2	6.4	5.8	3.0	8.6	3.8	7.6	3.0	1.8	5.8	2.6	1.2	1.3
3	5.2	5.5	3.0	13.0	3.8	5.6	3.0	1.8	3.7	3.2	1.2	1.3
4	4.2	15.8	3.0	13.0	3.8	6.4	2.6	1.6	3.4	3.0	1.2	1.5
5	4.0	18.5	3.0	10.0	3.6	5.0	2.4	1.6	3.0	2.8	1.2	2.0
6	3.8	13.8	3.0	7.9	3.5	4.0	2.2	2.6	2.9	2.2	1.2	1.8
7	3.5	9.5	3.0	6.4	3.5	7.0	5.2	5.3	2.6	2.0	1.2	1.8
8	3.2	6.5	3.0	5.6	3.4	7.6	4.8	5.9	2.2	1.9	1.1	1.8
9	3.0	9.6	2.8	5.2	3.3	5.4	3.3	3.0	2.0	1.9	1.1	1.8
10	2.8	12.5	5.5	4.5	3.1	4.3	2.6	2.6	2.0	1.8	1.1	1.8
11	8.8	10.5	7.8	4.3	3.0	4.0	2.4	2.5	2.0	1.7	1.0	2.6
12	23.5	7.6	8.0	4.2	2.9	3.8	2.3	3.4	2.0	1.6	1.0	2.6
13	27.0	6.5	6.7	4.3	2.8	3.8	2.0	3.0	1.8	1.8	1.0	2.1
14	23.8	5.6	4.8	10.4	2.8	4.0	2.0	2.3	2.0	2.0	1.0	2.2
15	21.4	5.0	4.0	10.1	2.7	4.3	2.0	4.5	3.0	3.2	1.0	16.4
16	19.8	4.8	3.6	7.7	2.6	6.9	1.9	7.2	2.4	2.6	1.0	17.6
17	17.4	4.2	3.2	5.8	2.6	6.0	1.7	10.5	6.0	2.4	1.0	14.7
18	8.9	4.2	3.0	5.2	2.5	5.0	5.5	9.8	11.2	2.4	1.0	14.0
19	5.0	4.2	3.0	9.0	2.5	4.8	3.0	10.8	11.1	2.0	1.0	13.0
20	4.0	4.0	3.0	18.6	3.0	4.0	3.0	12.5	7.0	1.8	1.0	5.6
21	3.8	3.8	3.0	17.2	10.0	3.8	2.4	10.8	3.9	1.8	1.6	3.0
22	3.8	3.7	3.0	15.5	23.6	3.6	2.4	14.5	3.7	1.6	1.2	2.0
23	3.8	3.6	3.0	14.6	26.4	3.6	2.4	20.8	3.3	1.6	1.4	2.0
24	3.8	3.6	3.6	12.7	21.3	3.6	2.0	23.2	2.8	1.6	1.4	3.6
25	6.7	3.5	3.6	6.8	18.9	2.7	2.0	18.3	2.6	1.6	1.3	4.0
26	6.6	3.2	22.0	5.6	16.5	2.7	1.9	13.1	2.5	1.4	1.3	3.7
27	5.4	3.2	27.0	4.8	11.1	3.2	1.7	6.6	2.3	1.3	1.3	5.7
28	5.2	3.0	24.5	4.4	5.5	3.0	2.8	8.3	2.0	1.3	1.3	6.0
29	5.0	21.3	4.2	4.9	3.6	1.9	7.5	2.0	1.3	1.3	21.5
30	4.6	19.2	4.1	4.7	3.6	1.9	6.2	2.5	1.3	1.8	29.8
31	6.8	16.1	5.4	1.6	5.6	1.2	32.6

MOBILE DRAINAGE BASIN, STREAM FLOW

347

Daily gage height, in feet, of Coosa River, at Rome—Continued.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1902												
1	28.0	11.8	28.5	21.3	2.9	1.8	1.0	1.2	1.0	1.6	.2	1.9
2	24.6	22.0	27.6	14.8	2.9	1.7	1.0	1.0	.8	1.6	.2	2.0
3	21.9	24.0	24.1	7.2	3.7	1.7	1.1	.8	1.2	1.6	.2	6.2
4	17.6	20.0	21.6	5.8	3.4	1.7	1.0	.8	1.0	1.5	.2	6.8
5	6.6	15.6	19.2	5.7	3.2	1.7	.9	1.5	1.2	1.0	.2	5.8
6	5.6	9.8	14.0	5.2	3.0	1.7	.9	1.4	1.0	2.0	.4	5.0
7	4.6	6.3	10.1	6.7	2.9	1.7	1.0	1.2	.8	1.4	2.0	4.0
8	4.2	5.7	8.7	6.7	2.8	1.7	.9	1.2	.6	.9	1.6	2.7
9	4.0	5.0	7.2	7.7	2.6	2.0	.9	.6	.9	.8	1.0	2.5
10	3.9	4.6	7.0	6.6	2.6	1.9	.9	.4	1.0	.7	.8	1.9
11	3.6	4.4	6.6	5.6	2.5	1.9	.9	.3	.9	2.3	.8	1.6
12	3.5	4.0	6.0	5.0	2.4	1.8	1.4	.3	.7	2.2	.7	1.4
13	3.4	3.9	5.6	4.7	2.3	1.7	1.5	1.0	.6	2.2	.6	1.2
14	3.2	3.8	5.5	4.5	2.3	1.7	1.8	.6	2.5	2.0	.6	1.2
15	3.0	3.8	5.0	4.4	2.3	1.6	1.4	.6	1.9	1.8	.6	1.1
16	2.8	4.0	7.0	4.3	2.4	1.6	2.0	.8	1.0	1.6	.6	2.4
17	2.7	4.5	14.0	4.5	2.5	1.6	1.4	.6	.7	1.5	.6	4.3
18	2.7	4.7	11.6	5.7	2.3	1.5	1.2	.5	.4	1.3	.9	4.5
19	3.0	4.5	8.6	5.0	2.3	1.5	1.0	.4	.4	1.1	1.5	3.8
20	3.2	4.0	6.2	4.0	2.4	1.9	1.0	1.0	.4	.9	1.3	3.0
21	3.6	4.0	5.6	3.9	2.4	1.6	.9	1.3	1.0	.8	1.1	4.9
22	4.2	5.0	5.1	3.8	2.3	1.8	.8	1.0	.8	.7	1.1	5.8
23	5.0	5.6	5.0	3.7	2.3	1.5	.8	.9	.6	.6	1.0	5.8
24	4.0	5.3	4.7	3.5	2.1	1.3	.7	.7	.3	.5	.9	5.2
25	3.9	5.0	4.7	3.3	2.0	1.3	.6	.5	2.2	.4	1.6	3.8
26	3.6	5.5	4.6	3.2	2.0	1.2	.5	.5	4.0	.3	3.1	3.0
27	3.6	5.5	4.2	3.2	2.0	1.2	.5	.6	3.3	.2	4.8	2.6
28	4.2	22.7	5.0	3.0	1.8	1.1	.5	1.2	2.0	.4	3.8	2.2
29	6.5	20.6	3.0	1.8	1.0	.7	1.7	2.0	.4	2.4	2.2
30	5.8	28.9	2.9	1.8	1.0	2.0	1.0	1.8	.3	2.2	2.6
31	5.4	26.8	1.8	1.6	1.03	4.0
1903												
1	3.0	2.3	28.6	24.9	3.6	6.0	3.0	2.8	1.0	.4	.7	.9
2	3.9	2.8	27.1	22.0	3.6	7.7	3.2	2.6	.9	.4	.7	.9
3	3.9	4.2	24.0	19.5	3.6	9.0	2.9	3.0	.9	.4	.8	.8
4	5.0	8.4	22.3	14.6	3.5	7.5	2.7	3.3	.9	.3	1.5	.7
5	4.3	13.2	20.5	8.0	3.5	11.7	2.6	3.2	.8	.3	1.5	.7
6	4.0	13.4	15.4	7.0	3.3	17.1	2.6	6.2	.7	.3	2.0	.7
7	3.7	9.7	9.9	6.4	3.4	11.7	2.6	4.6	.7	.2	2.0	.7
8	3.0	13.7	7.7	7.7	3.5	6.9	2.4	3.6	.6	.5	1.6	.7
9	2.8	21.6	6.6	10.5	3.5	5.3	2.6	3.4	.6	1.4	1.4	.7
10	2.4	16.5	10.5	8.4	3.4	4.4	2.6	3.0	.6	1.6	1.3	.7
11	3.0	15.1	11.6	6.7	3.3	4.3	2.5	2.6	.6	1.5	1.2	.7
12	5.0	21.8	16.0	6.3	3.3	6.0	2.9	2.2	.6	1.4	1.2	.6
13	5.0	19.6	14.0	5.6	3.0	4.6	5.9	2.0	.6	1.3	1.2	.6
14	4.8	14.5	10.1	14.3	3.0	4.2	11.1	2.0	.6	1.1	1.2	.6
15	3.9	11.1	9.4	13.0	3.1	4.0	6.7	1.6	.6	.9	1.0	.6
16	2.5	8.7	7.8	9.5	3.3	3.8	3.7	4.3	.9	.3	1.0	.6
17	2.4	24.7	6.8	7.4	3.0	3.4	3.5	3.2	1.7	1.2	1.0	.6
18	2.4	28.7	6.3	6.2	3.0	3.0	3.3	2.3	2.0	1.3	1.0	.6
19	2.4	25.5	5.7	5.3	2.8	2.4	3.0	2.2	1.5	1.2	1.5	.6
20	2.4	21.0	5.3	5.7	2.5	2.7	2.9	2.1	1.2	1.0	1.4	.6
21	2.2	15.2	11.0	5.8	2.5	2.5	2.5	2.0	.9	.8	1.3	.7
22	2.0	7.1	11.6	5.5	2.6	2.4	2.4	2.0	.8	.8	1.2	1.3
23	2.0	5.8	16.9	4.9	2.6	2.2	3.0	1.9	.7	.7	1.1	1.3
24	2.0	5.1	22.6	4.7	2.5	2.2	3.0	1.8	.5	.7	1.0	1.0
25	2.0	4.8	20.6	4.4	2.5	2.2	2.6	1.6	.5	.7	1.0	.9
26	2.0	4.5	16.0	4.9	2.3	2.2	2.4	1.5	.5	.6	1.0	.9
27	2.0	4.0	9.7	4.7	2.1	2.4	2.1	1.4	.5	.6	1.0	.9
28	2.4	23.1	6.9	4.0	2.0	6.8	2.0	1.4	.5	.5	.9	.9
29	3.2	7.8	3.9	2.0	6.8	1.8	1.3	.4	.4	.9	.9
30	4.2	22.5	3.7	2.4	4.0	2.3	1.3	.4	.4	.9	.9
31	3.8	27.6	6.7	2.6	1.279

WATER POWERS OF GEORGIA

Rating tables for Coosa River at Rome.

JANUARY 1, 1897, TO DECEMBER 31, 1898.^a

Gage height	Dis-charge						
<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>
— 0.40	900	1.70	2,690	3.80	5,910	7.80	13,710
— .30	985	1.80	2,810	3.90	6,105	8.00	14,100
— .20	970	1.90	2,930	4.00	6,300	8.50	15,075
— .10	1,010	2.00	3,060	4.20	6,690	9.00	16,050
.00	1,070	2.10	3,190	4.40	7,080	10.00	18,000
.10	1,140	2.20	3,320	4.60	7,470	11.00	19,950
.20	1,210	2.30	3,460	4.80	7,860	12.00	21,900
.30	1,280	2.40	3,610	5.00	8,250	13.00	23,850
.40	1,360	2.50	3,760	5.20	8,640	14.00	25,800
.50	1,440	2.60	3,910	5.40	9,030	15.00	27,750
.60	1,520	2.70	4,060	5.60	9,420	16.00	29,700
.70	1,610	2.80	4,220	5.80	9,810	17.00	31,650
.80	1,700	2.90	4,380	6.00	10,200	18.00	33,600
.90	1,800	3.00	4,540	6.20	10,590	19.00	35,550
1.00	1,900	3.10	4,700	6.40	10,980	20.00	37,500
1.10	2,000	3.20	4,860	6.60	11,370	21.00	39,450
1.20	2,110	3.30	5,020	6.80	11,760	22.00	41,400
1.30	2,220	3.40	5,180	7.00	12,150	23.00	43,350
1.40	2,330	3.50	5,340	7.20	12,540	24.00	45,300
1.50	2,450	3.60	5,520	7.40	12,930		
1.60	2,570	3.70	5,715	7.60	13,320		

JANUARY 1 TO DECEMBER 31, 1899.^b

0.30	1,470	2.50	3,900	4.70	8,107	10.00	18,760
.40	1,550	2.60	4,060	4.80	8,308	11.00	20,770
.50	1,630	2.70	4,220	4.90	8,509	12.00	22,780
.60	1,710	2.80	4,380	5.00	8,710	13.00	24,790
.70	1,790	2.90	4,540	5.20	9,112	14.00	26,800
.80	1,870	3.00	4,700	5.40	9,514	15.00	28,810
.90	1,950	3.10	4,900	5.60	9,916	16.00	30,820
1.00	2,030	3.20	5,100	5.80	10,318	17.00	32,830
1.10	2,124	3.30	5,300	6.00	10,720	18.00	34,840
1.20	2,218	3.40	5,500	6.20	11,122	19.00	36,850
1.30	2,312	3.50	5,700	6.40	11,524	20.00	38,860
1.40	2,406	3.60	5,900	6.60	11,926	21.00	40,870
1.50	2,500	3.70	6,100	6.80	12,328	22.00	42,880
1.60	2,620	3.80	6,300	7.00	12,730	23.00	44,890
1.70	2,740	3.90	6,500	7.20	13,132	24.00	46,900
1.80	2,860	4.00	6,700	7.40	13,534	25.00	48,910
1.90	2,980	4.10	6,901	7.60	13,936	26.00	50,920
2.00	3,100	4.20	7,102	7.80	14,338	27.00	52,930
2.10	3,260	4.30	7,303	8.00	14,740	28.00	54,940
2.20	3,420	4.40	7,504	8.50	15,745	29.00	56,950
2.30	3,580	4.50	7,705	9.00	16,750	30.00	58,960
2.40	3,740	4.60	7,906	9.50	17,755		

JANUARY 1, 1900, TO DECEMBER 31, 1901.^c

0.80	1,980	1.70	2,985	2.60	4,300	3.50	5,755
.90	2,020	1.80	3,120	2.70	4,450	3.60	5,930
1.00	2,110	1.90	3,260	2.80	4,600	3.70	6,115
1.10	2,230	2.00	3,400	2.90	4,750	3.80	6,300
1.20	2,350	2.10	3,550	3.00	4,900	3.90	6,500
1.30	2,475	2.20	3,700	3.10	5,065	4.00	6,700
1.40	2,600	2.30	3,850	3.20	5,230		
1.50	2,725	2.40	4,000	3.30	5,405		
1.60	2,850	2.50	4,150	3.40	5,580		

JANUARY 1 TO DECEMBER 31, 1902.^d

0.20	1,410	0.50	1,635	0.70	1,810	0.90	2,005
.30	1,480	.60	1,720	.80	1,905	1.00	2,110
.40	1,555						

^a Above gage height 4.00 feet the rating curve is a tangent, the difference being 195 per tenth.^b Above gage height 4.00 feet the rating curve is a tangent, the difference being 201 per tenth.^c Above gage height 4.00 feet this table is the same as the 1899 table.^d Above gage height 1.00 foot this table is the same as the 1901 table.

MOBILE DRAINAGE BASIN, STREAM FLOW

Rating tables for Coosa River at Rome—Continued.

JANUARY 1 TO DECEMBER 31, 1903.^a

Gage height	Dis-charge						
<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>
0.20	1,280	1.20	2,530	2.20	3,910	3.40	5,725
.30	1,390	1.30	2,660	2.30	4,055	3.60	6,055
.40	1,510	1.40	2,790	2.40	4,200	3.80	6,400
.50	1,630	1.50	2,920	2.50	4,345	4.00	6,760
.60	1,750	1.60	3,060	2.60	4,495	4.20	7,140
.70	1,880	1.70	3,200	2.70	4,645	4.40	7,520
.80	2,010	1.80	3,340	2.80	4,795	4.60	7,910
.90	2,140	1.90	3,480	2.90	4,945	4.80	8,310
1.00	2,270	2.00	3,620	3.00	5,095	5.00	8,710
1.10	2,400	2.10	3,765	3.20	5,405		

^a Above gage height 5.00 feet this table is the same as the 1899 table.

Estimated monthly discharge of Coosa River at Rome.

[Drainage area, 4,006 square miles.]

Month	Discharge in second-feet			Run-off	
	Maximum	Minimum	Mean	Sec.-ft. per sq. mile	Depth in inches
1897					
January.....	17,025	1,800	4,320	1.20	1.38
February.....	20,925	4,220	10,100	2.52	2.62
March.....	44,910	4,700	22,537	5.63	6.49
April.....	35,150	43,600	12,304	3.07	3.43
May.....	8,250	2,930	4,421	1.10	1.27
June.....	4,540	1,900	2,884	.72	.80
July.....	23,460	1,800	5,184	1.30	1.50
August.....	4,860	1,360	2,256	.56	.64
September.....	1,900	900	1,106	.28	.31
October.....	2,570	1,010	1,513	.38	.44
November.....	2,000	1,440	1,626	.41	.46
December.....	9,310	1,900	4,086	1.02	1.18
The year.....	44,910	900	6,070	1.52	20.52
1898					
January.....	26,970	22,200	7,272	1.82	2.10
February.....	5,520	2,110	2,705	.68	.71
March.....	20,730	2,110	4,384	1.10	1.27
April.....	32,040	4,540	9,430	2.36	2.63
May.....	4,220	2,330	2,778	.69	.79
June.....	5,520	2,110	2,866	.72	.80
July.....	6,690	1,900	3,670	9.17	10.59
August.....	17,305	2,930	6,079	1.52	1.75
September.....	45,385	3,060	12,114	3.03	2.26
October.....	44,910	3,060	11,330	2.96	3.41
November.....	12,150	3,060	5,213	1.30	1.45
December.....	8,250	3,610	4,996	1.25	1.44
The year.....	45,385	1,900	6,111	2.22	29.20
1899					
January.....	10,519	4,060	6,092	1.52	1.75
February.....	54,538	8,710	22,536	5.62	5.85
March.....	57,352	7,705	26,314	6.57	7.57
April.....	28,810	6,700	13,333	3.33	3.72
May.....	6,700	3,100	4,783	1.19	1.37
June.....	6,700	2,740	3,489	.87	9.97
July.....	24,388	1,950	5,499	1.37	1.58
August.....	3,900	1,790	2,596	.65	.75
September.....	5,500	1,550	2,219	.55	.61
October.....	2,030	1,470	1,684	.42	.48
November.....	4,700	1,470	2,009	.50	.56
December.....	13,735	1,870	4,314	1.08	1.25
The year.....	57,352	1,470	7,906	1.97	26.46

WATER POWERS OF GEORGIA

Estimated monthly discharge of Coosa River at Rome—Continued.

Month	Discharge in second-feet			Run-off	
	Maximum	Minimum	Mean	Sec.-ft. per sq. mile	Depth in inches
1900					
January.....	21,373	2,725	6,854	1.71	1.97
February.....	53,332	2,850	14,736	3.63	3.33
March.....	33,835	6,300	14,714	3.67	4.33
April.....	25,996	5,755	12,050	3.01	3.36
May.....	11,122	3,850	5,129	1.23	1.43
June.....	35,242	4,000	14,154	3.53	3.94
July.....	19,765	4,000	7,539	1.89	2.13
August.....	5,530	2,725	3,488	.87	1.00
September.....	20,971	1,930	3,960	.99	1.10
October.....	10,519	2,010	3,408	.85	.98
November.....	21,775	2,600	5,433	1.36	1.52
December.....	14,740	3,400	7,096	1.77	2.04
The year.....	53,332	1,930	8,213	2.05	27.73
1901					
January.....	52,980	4,600	15,450	3.86	4.45
February.....	35,845	4,900	12,136	3.04	3.17
March.....	52,930	4,600	13,406	3.34	3.85
April.....	36,046	6,901	15,578	3.88	4.33
May.....	51,724	4,150	12,533	3.12	3.60
June.....	19,966	4,450	8,316	2.08	2.32
July.....	9,715	2,850	4,441	1.10	1.27
August.....	45,292	2,850	13,780	3.44	3.97
September.....	21,172	3,120	6,389	1.59	1.77
October.....	5,230	2,350	3,414	.85	.98
November.....	2,850	2,110	2,316	.53	.65
December.....	64,186	2,475	13,423	3.35	3.86
The year.....	64,186	2,110	10,103	2.52	34.22
1902					
January.....	54,940	4,450	11,816	2.95	3.40
February.....	46,900	6,300	14,812	3.70	3.85
March.....	56,749	7,102	21,957	5.43	6.32
April.....	41,473	4,750	10,015	2.50	2.79
May.....	6,115	3,120	4,089	1.02	1.13
June.....	3,400	2,110	2,336	.71	.79
July.....	3,400	1,635	2,214	.55	.63
August.....	2,985	1,430	1,993	.50	.58
September.....	6,700	1,430	2,505	.63	.70
October.....	3,350	1,410	2,346	.59	.63
November.....	3,308	1,410	2,572	.64	.71
December.....	12,328	2,225	5,885	1.47	1.69
The year.....	56,749	1,410	6,920	1.73	23.32
1903					
January.....	3,710	3,620	5,442	1.36	1.57
February.....	56,347	4,795	25,376	6.34	6.60
March.....	56,146	9,313	27,111	6.73	7.82
April.....	43,709	6,225	15,788	3.95	4.41
May.....	12,127	3,620	5,273	1.32	1.52
June.....	35,031	3,910	9,594	2.40	2.63
July.....	20,971	3,340	5,616	1.40	1.61
August.....	11,122	2,530	4,472	1.12	1.29
September.....	3,620	1,510	2,002	.50	.56
October.....	3,060	1,230	2,002	.50	.53
November.....	3,620	1,830	2,512	.63	.70
December.....	2,660	1,750	1,935	.50	.53
The year.....	56,347	1,230	8,932	2.23	29.92

OOSTANAULA RIVER AT RESACA.

This station is located at the bridge of the Western and Atlantic Railway, in the town of Resaca, 800 feet south of the depot. It is a United States Weather Bureau station at which the gage readings are maintained for half the year only. During the years 1896 to 1898, inclusive, the United States Geological Survey maintained the gage for the other half of the year, making the gage height record complete, but for other years only the half-year records of the Weather Bureau are available. No estimates of discharge were made from 1901 until the beginning of 1905, when the station was reestablished.

The channel is slightly curved, the same curve extending about 300 feet above and below the bridge. The current is moderate, becoming rather sluggish at low water. The right bank is rock at the edge of the water, and has a solid stone abutment and railroad embankment above high-water level. The left bank is low, cultivated, and overflows during high water 480 feet to the end of the trestle. The bed of the stream is composed of rock near the right bank, but other parts appear to be sandy; to the left of the pier it is nearly filled up with logs and brush. There is one channel, broken by one pier at ordinary water.

Discharge measurements are made from the downstream side of the iron bridge, which consists of three spans of 120 feet each, and 480 feet of trestle approach at the left bank. The left span of the bridge is entirely outside of the river, except at high water. Measurements are also made from a boat at the ferry about 200 feet above the bridge, where the section is somewhat better. The initial point for soundings is the end of the bridge at the right bank, downstream side.

Gage heights are observed from the United States Weather Bureau gage, which is a heavy timber attached vertically to the downstream side of the center pier of the bridge. Bench marks were established as follows: (1) The top of the downstream end of the second crossbeam from the right bank; elevation, 38.94 feet. (2) A cross mark on the top of the limestone boulder on the north side of the river, about 130 feet from the end of the railroad bridge and 40 feet west of the railroad track; elevation, 34.23 feet. Elevations refer to the datum of the gage.

WATER POWERS OF GEORGIA

Discharge measurements of Oostanaula River at Resaca.

Date	Gage height	Dis-charge	Date	Gage height	Dis-charge
1896	<i>Feet</i>	<i>Sec.-ft.</i>	1900	<i>Feet</i>	<i>Sec.-ft.</i>
July 27.....	2.90	1,133	April 30.....	8.00	5,118
August 19.....	1.47	492	May 15.....	3.60	1,466
October 13.....	1.70	601	May 25.....	3.75	1,539
1897			December 11.....	4.30	1,919
May 25.....	3.43	1,535	1904		
May 29.....	3.26	1,389	September 26 ^a95	273
June 23.....	2.44	972	November 25 ^a	1.57	427
September 23.....	1.20	406	December 21.....	1.79	389
November 14.....	1.46	510	1905		
December 24.....	7.10	4,642	March 14.....	5.10	2,521
December 30.....	3.42	1,630	June 7.....	3.30	1,339
1898			September 26.....	1.91	596
May 21.....	2.65	1,100	1906		
July 29.....	5.41	2,567	January 2.....	4.60	2,170
August 20.....	3.79	1,311	May 22.....	3.42	1,510
August 27.....	4.65	2,397	June 6.....	5.51	3,080
1899			June 23.....	4.37	2,120
April 26.....	8.05	5,146	July 26.....	5.97	3,290
May 20.....	4.15	1,871			
June 9.....	3.10	1,171			
June 21.....	3.05	1,087			
October 14.....	1.75	644			

^a Made at different sections.

MOBILE DRAINAGE BASIN, STREAM FLOW

Daily gage height, in feet, of Oostanaula River at Resaca.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1896												
1.....	5.5	3.9	3.7	4.8	2.1	1.2	6.5	1.5	9.25
2.....	4.6	3.9	3.7	11.8	2.3	1.25	3.7	1.4	6.7
3.....	4.2	4.6	3.7	11.6	2.65	1.2	2.05	1.4	4.6
4.....	3.8	4.8	3.6	11.7	2.4	1.25	1.65	1.35	3.95
5.....	3.4	4.5	3.5	6.6	2.15	1.15	1.5	1.9	3.5
6.....	3.0	10.7	3.4	5.4	2.0	1.15	1.4	3.15	3.2
7.....	2.9	16.7	3.8	5.0	1.9	1.3	1.3	2.1	3.0
8.....	3.3	15.5	4.2	4.9	1.8	1.1	1.3	2.0	2.9
9.....	4.0	15.9	3.9	4.8	1.75	1.1	1.3	2.1	3.0
10.....	4.0	14.1	3.6	4.3	1.75	1.05	1.2	1.85	3.5
11.....	3.5	9.3	3.4	4.2	1.65	1.0	1.2	1.7	3.3
12.....	3.4	6.9	4.5	4.0	1.65	1.0	1.2	3.0	3.1
13.....	3.3	5.0	4.9	3.8	1.7	1.5	1.55	13.65	2.9
14.....	3.1	9.1	4.0	3.7	1.6	1.25	1.65	11.35	2.8
15.....	3.0	9.7	3.7	3.6	1.6	1.1	1.5	11.1	4.2
16.....	2.9	7.8	3.6	3.6	1.7	1.05	1.45	4.25	3.9
17.....	3.7	6.4	6.5	3.6	1.7	1.0	1.35	3.3	3.3
18.....	4.0	5.7	3.4	3.5	1.7	1.0	1.3	3.0	3.0
19.....	3.3	5.3	6.6	3.5	1.5	.95	1.2	2.7	3.0
20.....	3.4	5.0	7.8	3.4	1.85	.9	1.15	2.6	2.9
21.....	3.2	4.7	7.1	3.3	1.3	.9	1.15	2.5	2.8
22.....	3.4	4.3	5.8	3.2	1.25	.85	1.2	2.35	2.6
23.....	5.7	4.1	5.2	3.3	1.2	1.95	1.2	2.4	2.55
24.....	10.3	4.0	4.9	4.2	1.5	1.55	1.35	2.35	2.55
25.....	11.5	4.0	5.3	3.7	3.2	1.25	1.9	2.25	2.4
26.....	10.0	3.9	5.0	3.3	2.8	1.2	1.6	2.2	2.3
27.....	6.2	3.8	4.7	3.1	1.95	1.1	1.5	2.1	2.25
28.....	5.2	3.7	4.4	3.4	1.7	1.1	1.4	2.15	2.2
29.....	4.7	3.7	4.2	3.4	1.5	1.7	1.95	3.8	2.2
30.....	4.3	4.0	3.3	1.4	3.35	1.55	8.7	2.2
31.....	4.0	4.6	3.1	1.3	2.2
1897												
1.....	2.2	3.8	4.6	7.3	5.4	4.25	2.6	2.45	2.3	1.0	1.35	1.85
2.....	2.2	13.9	4.4	11.4	5.05	3.5	2.25	2.3	1.9	1.05	2.05	1.65
3.....	2.2	14.0	4.2	12.4	4.6	3.5	2.2	3.0	1.9	1.05	2.3	2.0
4.....	2.2	13.2	4.3	12.5	4.4	3.65	2.15	2.4	1.8	.95	2.1	4.65
5.....	3.0	8.7	5.9	18.5	4.25	3.35	2.2	2.5	1.3	.95	1.9	5.1
6.....	3.05	6.2	10.5	20.3	4.1	3.15	2.55	3.15	1.6	1.05	1.75	5.7
7.....	2.75	7.3	13.0	19.6	4.0	3.0	6.2	4.0	1.5	1.1	1.65	4.3
8.....	2.5	7.6	13.8	16.3	3.95	2.9	3.6	3.45	1.45	1.05	1.55	3.1
9.....	2.4	7.0	13.0	10.1	3.85	3.0	2.8	2.85	1.4	1.05	1.55	2.6
10.....	2.3	6.0	16.2	10.4	3.85	3.15	2.8	2.5	1.4	1.05	1.55	2.35
11.....	2.25	5.8	10.7	8.6	3.95	2.9	3.25	3.2	1.4	1.1	1.55	2.2
12.....	2.25	8.6	16.5	7.6	4.9	2.75	3.3	2.75	1.4	2.05	1.5	2.2
13.....	2.25	9.8	21.7	6.8	5.45	2.7	2.9	2.5	1.35	3.0	1.45	2.1
14.....	5.45	7.7	21.7	6.4	8.45	2.6	2.65	2.15	1.3	1.8	1.45	4.15
15.....	7.5	6.4	24.6	6.8	8.75	2.55	2.3	2.1	1.3	1.6	1.45	5.3
16.....	5.1	5.7	26.0	8.2	5.7	2.6	2.15	2.1	1.3	1.45	1.4	4.45
17.....	4.1	5.4	25.3	7.0	4.7	2.7	3.1	2.55	1.3	1.35	1.4	3.4
18.....	5.4	4.7	23.3	6.2	4.4	2.9	2.9	3.0	1.4	1.2	1.45	2.9
19.....	5.2	4.5	21.3	5.8	4.1	2.75	3.4	2.2	1.25	1.15	1.45	2.75
20.....	4.4	4.5	18.9	5.5	3.95	2.6	11.8	2.1	1.2	2.15	1.4	5.25
21.....	9.6	5.0	13.2	5.3	3.85	2.6	7.35	2.0	1.15	2.05	1.4	6.2
22.....	8.7	4.6	18.4	5.1	3.8	2.45	9.0	2.2	1.15	2.0	1.4	8.45
23.....	6.1	11.4	17.5	4.9	3.75	2.35	7.2	2.6	1.15	1.8	1.4	9.25
24.....	5.0	12.0	12.7	4.8	3.6	2.35	4.2	2.5	1.15	1.75	1.45	7.5
25.....	3.1	10.6	8.4	4.8	3.5	2.45	3.25	2.2	1.15	1.5	1.4	4.95
26.....	4.0	6.7	7.6	4.7	3.35	2.45	4.05	2.05	1.15	1.4	1.4	4.45
27.....	3.7	5.7	6.7	4.7	3.3	2.3	4.4	2.0	1.15	1.35	1.55	4.9
28.....	3.4	5.1	6.6	4.6	3.25	2.25	3.9	1.85	1.1	1.35	1.8	4.25
29.....	2.7	6.0	4.4	3.25	3.5	3.2	1.75	1.2	1.35	1.75	3.75
30.....	3.1	6.0	4.3	3.15	2.9	2.8	1.7	1.0	1.3	1.75	3.4
31.....	3.5	6.0	3.5	3.5	2.55	1.85	1.3	3.2

MOBILE DRAINAGE BASIN, STREAM FLOW

Daily gage height, in feet, of Oostanaula River at Resaca—Continued.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1900												
1.....	(a)	3.1	6.0	5.8	6.8	3.3					2.8	4.5
2.....	(a)	3.0	7.3	5.4	5.7	3.5					2.9	4.2
3.....	(a)	3.0	6.8	5.3	5.5	4.0					3.0	4.0
4.....	(a)	3.1	5.9	5.6	5.3	5.5					4.6	6.0
5.....	(a)	4.3	5.4	6.3	4.8	5.0					4.5	8.6
6.....	(a)	4.2	5.1	6.0	4.6	7.7					3.7	6.3
7.....	(a)	2.7	3.7	6.9	5.2	4.4	7.9				3.5	8.0
8.....		2.6	3.5	11.3	5.0	4.0	13.0				3.0	5.6
9.....		2.4	5.6	15.5	4.8	3.9	10.8				2.9	5.0
10.....		2.5	9.1	14.2	4.6	3.8	7.5				2.8	4.8
11.....		4.2	7.3	11.1	7.2	3.7	5.6				2.8	4.2
12.....		11.3	7.8	7.6	11.6	3.6	5.8				2.8	4.0
13.....		11.3	20.3	6.7	9.8	3.6	6.8				2.7	4.0
14.....		9.9	23.0	6.0	7.4	3.4	6.6				2.7	4.0
15.....		6.1	23.5	5.6	6.2	3.4	5.6				2.7	4.0
16.....		4.9	20.8	7.3	5.8	3.4	4.8				2.7	3.9
17.....		4.3	13.7	6.9	6.8	3.3	6.6				2.6	3.5
18.....		4.1	6.5	5.9	11.9	3.3	6.8				2.6	3.4
19.....		6.1	5.5	6.0	12.0	3.3	10.9				2.6	3.4
20.....		13.1	5.2	16.9	10.4	3.9	7.0				2.7	3.8
21.....		12.1	5.3	17.2	11.8	3.8	6.5				2.8	10.9
22.....		10.2	9.1	13.8	11.6	3.7	4.8				3.6	9.3
23.....		6.0	8.9	8.8	9.7	3.6	9.9				3.4	6.8
24.....		5.2	7.3	7.7	7.7	3.7	12.8				3.3	9.0
25.....		4.8	7.0	8.0	7.2	3.8	14.0				3.7	8.7
26.....		4.4	6.7	12.2	6.2	4.0	15.0				14.4	6.7
27.....		4.0	6.0	10.8	5.8	4.0	17.2				13.0	5.6
28.....		3.7	5.5	8.3	5.6	3.7	17.5				12.2	4.6
29.....		3.6		7.2	5.5	3.6	13.0				7.6	5.4
30.....		3.5		6.6	7.8	3.6	9.6				5.2	5.2
31.....		3.4		6.2		3.4						7.7

a Frozen

Day	Jan.	Feb.	Mar.	Apr.	Nov.	Dec.	Day	Jan.	Feb.	Mar.	Apr.	Nov.	Dec.
1901						1901							
1.....	9.4	8.4	4.0	8.3		2.9	17.....	8.9	5.3	5.0	6.8	2.9	22.8
2.....	7.6	6.9	4.0	9.3		2.3	18.....	6.8	5.6	4.8	6.4	2.3	20.0
3.....	6.0	6.4	4.0	14.2		3.2	19.....	6.0	5.4	4.7	12.8	2.9	9.6
4.....	5.6	15.7	4.0	13.2		4.2	20.....	5.8	5.4	4.7	19.8	3.3	5.3
5.....	5.0	16.1	4.0	11.7		4.0	21.....	5.4	5.2	5.2	20.8	3.4	4.8
6.....	4.6	12.7	4.4	8.3		3.5	22.....	5.4	5.0	5.0	20.7	3.3	4.1
7.....	4.0	8.4	4.5	7.6		3.6	23.....	5.2	4.8	4.8	18.0	3.0	4.3
8.....	4.0	7.2	4.2	6.8		3.4	24.....	6.0	4.8	5.2	9.6	3.9	6.1
9.....	4.0	12.2	4.4	6.4		3.4	25.....	9.1	4.6	5.8	7.7	3.7	6.0
10.....	4.0	13.4	9.2	6.2		4.0	26.....	7.8	4.5	21.2	6.9	3.5	5.4
11.....	11.6	9.0	12.0	5.7		4.5	27.....	6.4	4.4	25.4	6.6	3.2	8.9
12.....	21.8	8.0	10.9	5.6		4.3	28.....	6.8	4.3	25.8	6.2	3.1	10.2
13.....	25.7	7.2	8.4	5.6	3.3	3.9	29.....	6.4		23.2	6.0	3.0	19.3
14.....	26.7	6.6	6.2	11.6	3.0	4.0	30.....	6.7		17.2	5.8	2.9	23.8
15.....	24.0	6.4	5.6	10.6	3.1	19.7	31.....	9.7		9.6			26.6
16.....	18.8	5.9	5.2	7.9	3.0	22.4							

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1905												
1.....	3.6	3.4	5.4	4.0	8.2	4.2	6.0	2.6	2.0	1.9	2.2	2.4
2.....	3.0	3.2	5.2	4.0	5.8	4.0	5.6	2.3	3.2	1.9	2.1	2.5
3.....	2.6	3.0	5.0	4.0	5.0	3.8	4.4	2.0	3.6	1.95	2.1	14.1
4.....	3.0	3.0	4.5	3.8	5.8	3.8	3.6	1.8	2.6	2.8	2.1	13.8
5.....	4.0	3.2	4.2	4.2	5.6	3.6	3.2	1.6	2.8	3.1	2.1	9.6

WATER POWERS OF GEORGIA

Daily gage height, in feet, of Oostanaula River at Resaca—Continued.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1905												
6.....	3.6	6.5	4.3	4.8	5.2	3.6	3.0	1.8	2.4	2.7	2.1	5.4
7.....	4.6	9.0	4.5	4.6	4.8	3.4	3.4	2.0	2.2	2.1	2.1	4.6
8.....	5.4	9.5	4.5	4.4	4.6	3.4	3.6	2.3	2.0	2.0	2.2	8.6
9.....	4.0	18.0	4.5	4.4	6.4	3.6	3.6	6.0	1.8	1.9	2.2	17.4
10.....	3.8	19.8	7.6	3.8	5.8	3.2	4.8	4.6	1.8	1.9	2.2	18.2
11.....	3.8	18.5	8.6	3.8	5.2	3.0	5.0	4.2	1.6	3.1	2.2	12.4
12.....	9.0	17.0	7.0	4.0	4.8	2.8	7.4	4.6	5.0	5.2	2.2	7.6
13.....	14.2	13.0	6.8	4.0	4.2	3.2	8.8	7.6	4.0	3.7	2.1	5.4
14.....	20.2	12.0	5.2	3.8	3.8	3.0	5.8	4.2	3.4	2.9	2.1	5.1
15.....	13.2	10.0	5.0	4.2	3.6	2.8	4.0	6.2	2.8	2.6	2.0	7.4
16.....	6.0	7.5	4.7	5.0	10.3	2.8	3.8	6.8	2.2	2.9	2.1	8.6
17.....	5.0	6.5	4.6	4.8	9.6	3.0	4.0	8.8	2.2	2.9	2.1	7.4
18.....	4.6	6.0	4.5	4.6	8.0	3.2	3.6	5.4	2.0	2.75	2.1	5.9
19.....	4.2	5.8	4.2	4.6	6.3	3.8	3.2	4.7	1.8	2.4	2.1	5.2
20.....	4.8	10.2	4.3	4.4	5.2	3.2	3.0	3.8	1.8	2.3	2.2	5.4
21.....	4.2	20.2	8.5	3.8	4.6	3.2	3.0	3.4	1.8	2.2	3.0	12.8
22.....	4.0	22.0	9.2	4.0	4.6	4.0	3.0	2.8	1.8	2.1	2.4	12.4
23.....	4.0	20.6	6.5	4.0	5.2	6.0	3.0	2.8	1.8	2.1	2.2	11.4
24.....	3.5	18.6	5.5	3.8	14.0	5.0	2.8	3.0	1.8	2.0	2.2	10.0
25.....	3.5	8.6	5.2	3.6	11.0	3.8	2.8	4.0	1.8	2.1	2.3	9.6
26.....	3.4	7.2	4.6	3.6	8.6	3.4	2.8	3.8	1.9	2.4	2.9	7.6
27.....	3.2	6.5	4.6	4.0	6.8	3.2	2.4	3.4	1.9	2.9	2.5	6.4
28.....	3.2	6.0	4.4	6.6	5.4	5.2	2.4	2.8	1.85	2.7	2.3	5.6
29.....	3.0	4.2	6.2	5.0	4.2	4.0	2.6	1.85	2.4	2.3	6.1
30.....	3.2	4.2	9.2	4.6	4.2	3.0	2.4	1.85	2.4	2.5	5.9
31.....	3.5	4.0	4.6	2.8	2.2	2.4	5.2
1906												
1.....	4.8	6.6	3.8	11.8	4.6	3.6	3.8	6.3	9.6	17.3	4.0	4.2
2.....	4.6	6.4	3.8	3.8	4.4	3.6	3.8	7.6	3.3	17.6	4.0	4.0
3.....	8.6	5.8	6.8	7.6	4.4	4.6	3.6	5.9	5.0	18.1	4.0	3.8
4.....	17.5	5.4	10.6	6.6	7.0	4.2	3.6	6.4	5.0	17.8	3.9	3.8
5.....	17.6	5.0	9.2	6.2	5.4	4.2	3.4	8.6	4.6	15.9	3.9	3.6
6.....	13.6	5.2	6.2	6.2	5.0	6.6	3.4	7.4	4.8	12.6	3.9	3.8
7.....	7.6	5.0	5.4	6.0	6.0	4.6	3.4	7.9	4.9	11.0	3.8	4.6
8.....	6.4	4.8	5.8	5.8	5.4	4.0	3.2	6.0	4.5	10.7	3.8	4.6
9.....	7.2	4.8	6.2	5.6	5.2	3.8	3.2	5.2	5.9	8.2	3.7	4.8
10.....	6.8	4.8	5.4	8.6	4.8	3.8	3.4	4.9	4.9	6.6	3.7	6.4
11.....	6.2	4.6	4.0	7.0	4.6	3.6	3.4	5.2	4.9	6.0	3.6	8.6
12.....	6.8	4.2	4.8	6.2	4.2	3.8	3.2	4.5	7.2	5.6	3.6	7.3
13.....	6.2	4.2	4.6	5.8	4.2	10.6	3.2	4.4	7.5	5.2	3.6	6.4
14.....	5.9	4.2	4.4	5.2	4.0	17.5	3.6	3.6	6.5	5.0	3.5	5.8
15.....	6.0	4.2	19.1	6.6	4.0	17.0	9.0	5.0	4.8	4.8	4.4	4.6
16.....	5.6	4.0	21.8	6.4	4.0	15.6	8.6	7.5	4.3	4.7	4.4	4.2
17.....	6.2	4.0	20.8	5.6	3.9	13.2	9.8	6.2	4.0	4.6	4.8	4.6
18.....	5.6	4.0	13.4	5.2	3.8	7.6	14.6	5.2	3.8	9.4	7.8	8.6
19.....	5.6	3.8	13.4	5.0	3.8	6.0	15.4	5.8	6.6	13.8	23.0	9.6
20.....	5.4	3.8	19.6	4.8	3.8	5.2	16.4	5.1	7.5	11.5	29.0	8.4
21.....	5.2	3.8	17.2	4.8	3.6	5.0	14.6	5.1	6.9	7.4	30.0	7.6
22.....	10.2	5.0	12.4	4.4	3.6	4.6	10.0	4.6	6.2	5.8	27.8	6.6
23.....	17.2	4.2	8.2	4.4	3.4	4.4	12.2	4.9	6.2	5.4	24.0	6.4
24.....	17.4	4.2	7.4	4.4	3.2	4.8	11.0	4.8	6.4	5.1	16.0	6.4
25.....	11.4	4.0	6.6	4.4	3.2	5.8	8.6	5.2	6.0	4.9	7.6	6.8
26.....	8.4	4.0	6.2	4.4	3.2	5.0	6.0	4.9	5.2	4.7	5.8	6.6
27.....	8.2	3.8	6.7	4.4	6.4	4.6	5.4	5.8	4.7	4.6	5.4	6.8
28.....	9.2	3.8	8.2	5.6	4.4	4.0	5.0	5.1	4.4	4.4	4.9	6.0
29.....	8.2	9.2	5.4	4.0	3.8	5.8	4.8	4.3	4.3	4.7	6.0
30.....	7.8	10.8	5.2	4.0	3.8	8.1	5.9	6.3	4.2	4.5	7.5
31.....	7.8	13.8	3.8	7.4	7.8	4.2	14.2

MOBILE DRAINAGE BASIN, STREAM FLOW

Rating tables for Oostanaula River at Resaca.

JANUARY 1, 1896, TO DECEMBER 31, 1897.^a

Gage height	Dis-charge	Gage height	Dis-charge	Gage height	Dis-charge	Gage height	Dis-charge
<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet.</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>
0.80	304	2.60	1,025	4.40	2,340	7.40	4,890
.90	326	2.70	1,079	4.50	2,425	7.60	5,060
1.00	350	2.80	1,134	4.60	2,510	7.80	5,230
1.10	373	2.90	1,191	4.70	2,595	8.00	5,400
1.20	408	3.00	1,250	4.80	2,680	9.00	6,800
1.30	440	3.10	1,312	4.90	2,765	10.00	7,200
1.40	475	3.20	1,377	5.00	2,850	11.00	8,100
1.50	512	3.30	1,444	5.20	3,020	12.00	9,000
1.60	552	3.40	1,514	5.40	3,190	13.00	9,900
1.70	594	3.50	1,588	5.60	3,360	14.00	10,800
1.80	637	3.60	1,665	5.80	3,530	15.00	11,700
1.90	681	3.70	1,745	6.00	3,700	16.00	12,600
2.00	727	3.80	1,830	6.20	3,870	18.00	14,400
2.10	774	3.90	1,915	6.40	4,040	20.00	16,200
2.20	822	4.00	2,000	6.60	4,210	22.00	18,000
2.30	871	4.10	2,085	6.80	4,380	24.00	19,800
2.40	921	4.20	2,170	7.00	4,550	26.00	21,600
2.50	972	4.30	2,255	7.20	4,720		

JANUARY 1 TO DECEMBER 31, 1898.^b

1.70	594	3.30	1,425	4.90	2,500	7.80	5,430
1.80	637	3.40	1,485	5.00	2,585	8.00	5,650
1.90	681	3.50	1,550	5.20	2,765	8.50	6,200
2.00	727	3.60	1,615	5.40	2,955	9.00	6,750
2.10	774	3.70	1,680	5.60	3,140	9.50	7,300
2.20	822	3.80	1,745	5.80	3,325	10.00	7,850
2.30	873	3.90	1,810	6.00	3,525	11.00	8,950
2.40	924	4.00	1,875	6.20	3,715	12.00	10,050
2.50	976	4.10	1,940	6.40	3,910	13.00	11,150
2.60	1,030	4.20	2,005	6.60	4,110	14.00	12,250
2.70	1,085	4.30	2,070	6.80	4,330	15.00	13,350
2.80	1,140	4.40	2,135	7.00	4,550	17.00	15,550
2.90	1,195	4.50	2,205	7.20	4,770	19.00	17,750
3.00	1,250	4.60	2,275	7.40	4,990	21.00	19,950
3.10	1,305	4.70	2,345	7.60	5,210	23.00	22,150
3.20	1,365	4.80	2,420				

^a Above gage height 8.00 feet the rating curve is a tangent, the difference being 90 per tenth.

^b Above gage height 7.00 feet the rating curve is a tangent, the difference being 110 per tenth.

JANUARY 1 TO DECEMBER 31, 1899.^c

1.60	600	3.40	1,275	5.40	2,690	9.00	5,990
1.70	625	3.50	1,325	5.60	2,870	9.50	6,450
1.80	650	3.60	1,380	5.80	3,050	10.00	6,910
1.90	675	3.70	1,435	6.00	3,230	10.50	7,370
2.00	705	3.80	1,490	6.20	3,414	11.00	7,830
2.10	735	3.90	1,550	6.40	3,598	11.50	8,290
2.20	770	4.00	1,610	6.60	3,782	12.00	8,750
2.30	805	4.10	1,670	6.80	3,966	13.00	9,670
2.40	840	4.20	1,730	7.00	4,150	14.00	10,590
2.50	880	4.30	1,795	7.20	4,334	15.00	11,510
2.60	920	4.40	1,860	7.40	4,518	17.00	13,350
2.70	960	4.50	1,930	7.60	4,702	19.00	15,190
2.80	1,000	4.60	2,005	7.80	4,886	21.00	17,030
2.90	1,040	4.70	2,080	8.00	5,070	23.00	18,870
3.00	1,080	4.80	2,160	8.20	5,254	25.00	20,710
3.10	1,125	4.90	2,240	8.40	5,438	27.00	22,550
3.20	1,175	5.00	2,330	8.60	5,622	29.00	24,390
3.30	1,225	5.20	2,510	8.80	5,806		

^c Above gage height 6.00 feet the rating curve is a tangent, the difference being 92 per tenth.

WATER POWERS OF GEORGIA

Rating table for Oostanaula River at Resaca—Continued.

JANUARY 1, 1900, TO DECEMBER 31, 1901.*a*

Gage height	Dis-charge						
<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>
2.40	840	3.20	1,220	4.00	1,700	4.70	2,150
2.50	880	3.30	1,280	4.10	1,760	4.80	2,220
2.60	920	3.40	1,340	4.20	1,820	4.90	2,290
2.70	960	3.50	1,400	4.30	1,880	5.00	2,360
2.80	1,000	3.60	1,460	4.40	1,940	5.10	2,440
2.90	1,050	3.70	1,520	4.50	2,010	5.20	2,520
3.00	1,100	3.80	1,580	4.60	2,080	5.30	2,600
3.10	1,160	3.90	1,640				

JANUARY 1 TO DECEMBER 31, 1905.*b*

1.60	455	3.20	1,275	4.70	2,250	7.40	4,320
1.70	495	3.30	1,335	4.80	2,320	7.60	4,480
1.80	540	3.40	1,395	4.90	2,390	7.80	4,640
1.90	585	3.50	1,455	5.00	2,460	8.00	4,800
2.00	630	3.60	1,520	5.20	2,600	8.20	4,980
2.10	680	3.70	1,585	5.40	2,750	8.40	5,160
2.20	730	3.80	1,650	5.60	2,900	8.60	5,340
2.30	780	3.90	1,715	5.80	3,050	8.80	5,520
2.40	830	4.00	1,780	6.00	3,200	9.00	5,700
2.50	880	4.10	1,845	6.20	3,360	9.20	5,880
2.60	935	4.20	1,910	6.40	3,520	9.40	6,060
2.70	990	4.30	1,975	6.60	3,680	9.60	6,240
2.80	1,045	4.40	2,040	6.80	3,840	9.80	6,420
2.90	1,100	4.50	2,110	7.00	4,000	10.00	6,600
3.00	1,155	4.60	2,180	7.20	4,160	11.00	7,500
3.10	1,215						

JANUARY 1 TO DECEMBER 31, 1906.*c*

3.20	1,290	4.60	2,230	6.00	3,340	8.80	6,060
3.30	1,350	4.70	2,305	6.20	3,520	9.00	6,280
3.40	1,410	4.80	2,380	6.40	3,700	10.00	7,420
3.50	1,475	4.90	2,455	6.60	3,880	11.00	8,640
3.60	1,540	5.00	2,530	6.80	4,060	12.00	9,980
3.70	1,605	5.10	2,610	7.00	4,250	13.00	11,280
3.80	1,670	5.20	2,690	7.20	4,450	14.00	12,680
3.90	1,735	5.30	2,770	7.40	4,650	15.00	14,120
4.00	1,800	5.40	2,850	7.60	4,850	16.00	15,600
4.10	1,870	5.50	2,930	7.80	5,050	17.00	17,100
4.20	1,940	5.60	3,010	8.00	5,250	18.00	18,600
4.30	2,010	5.70	3,090	8.20	5,450		
4.40	2,080	5.80	3,170	8.40	5,650		
4.50	2,155	5.90	3,250	8.60	5,850		

a Above gage height 5.3 feet this table is the same as the 1899 table.*b* Above gage height 11.00 feet the rating curve is a tangent, the difference being 100 per tenth.*c* This table is based on eleven discharge measurements made during 1904-1906 and is well defined below gage height 6 feet. Above gage height 16 feet the rating curve is a tangent, the difference being 150 per tenth.

Estimated monthly discharge of Oostanaula River at Resaca.

[Drainage area, 1,614 square miles.]

Month	Discharge in second-feet			Run-off	
	Maximum	Minimum	Mean	Sec.-ft. per sq. mile	Depth in inches
1896 <i>a</i>					
January.....	8,550	1,191	2,526	1.56	1.80
February.....	13,230	1,745	4,555	2.82	3.04
March.....	5,760	1,514	2,598	1.61	1.86
April.....	8,820	1,312	2,610	1.62	1.87
August.....	1,377	408	655	.41	.47
September.....	5,717	315	584	.36	.40
October.....	4,125	393	652	.40	.47
November.....	10,480	458	1,920	1.19	1.33
December.....	6,525	322	1,546	.96	1.10

a The estimates for 1896 have been revised on the basis of the 1897 rating curve.

Estimated monthly discharge of Oostanaula River at Resaca—Continued.

Month	Discharge in second-feet			Run-off	
	Maximum	Minimum	Mean	Sec.-ft. per sq. mile	Depth in inches
1897					
January.....	6,760	322	2,097	1.30	1.50
February 5-22.....	10,800	2,425	5,081	3.15	3.28
March.....	21,600	2,170	10,740	6.65	7.67
April 11-30.....	16,470	2,255	5,933	3.68	4.11
May.....	6,040	1,344	2,340	1.45	1.67
June.....	2,212	846	1,198	.74	.83
July.....	8,600	798	2,004	1.24	1.43
August.....	2,000	594	969	.60	.69
September.....	871	350	479	.30	.33
October.....	1,250	338	506	.31	.36
November.....	871	475	551	.34	.38
December.....	6,460	575	2,233	1.38	1.59
The year.....	21,600	338	2,844	1.76	23.84
1898					
January.....	15,660	1,030	4,262	2.64	3.04
February.....	2,720	1,085	1,487	.92	.96
March.....	10,600	1,030	2,449	1.52	1.75
April.....	16,320	2,170	4,909	3.04	3.39
May.....	2,205	348	1,311	.81	.94
June.....	2,860	616	1,124	.69	.78
July.....	2,860	594	1,203	.74	.86
August.....	4,715	1,030	2,034	1.29	1.49
September.....	19,950	1,053	5,169	3.20	3.57
October.....	22,150	976	5,362	3.32	3.83
November.....	5,430	1,485	2,435	1.51	1.63
December.....	4,110	1,615	2,258	1.40	1.61
The year.....	22,150	594	2,838	1.76	23.89
1899					
January.....	6,312	1,670	2,777	1.72	1.98
February.....	22,090	3,552	9,627	5.96	6.21
March.....	24,022	3,230	10,416	6.45	7.44
April.....	10,866	2,690	5,163	3.20	3.57
November.....	1,490	600	735	.46	.52
December.....	5,162	675	1,633	1.04	1.20
1900					
January 7 to 31.....	9,762	840	3,362	2.08	1.93
February.....	19,330	1,100	5,470	3.39	3.53
March.....	13,534	2,430	5,760	3.57	4.11
April.....	8,750	2,080	4,530	2.81	3.13
May.....	3,966	1,230	1,760	1.09	1.26
June.....	13,810	1,230	5,583	3.46	3.86
November.....	10,958	920	2,207	1.37	1.53
December.....	7,738	1,340	3,059	1.90	2.19
1901					
January.....	22,274	1,700	6,222	3.86	4.45
February.....	12,522	1,330	4,655	2.88	3.00
March.....	21,446	1,700	5,597	3.47	4.00
April.....	16,846	2,370	6,639	4.15	4.63
November 13-30.....	1,640	1,000	1,211	.75	.50
December.....	22,132	1,000	5,953	3.69	4.25
1905					
January.....	16,700	935	2,376	1.78	2.05
February.....	18,500	1,155	7,512	4.65	4.84
March.....	5,880	1,780	2,756	1.71	1.97
April.....	5,880	1,520	2,123	1.32	1.47
May.....	10,500	1,520	3,476	2.15	2.43
June.....	3,200	1,045	1,572	.974	1.09
July.....	5,520	830	1,793	1.11	1.23
August.....	5,520	455	1,735	1.07	1.23
September.....	2,460	455	818	.507	.566
October.....	2,600	585	922	.571	.658
November.....	1,155	630	752	.466	.520
December.....	14,700	830	5,409	3.35	3.86
The year.....	18,500	455	2,645	1.64	22.01

Estimated monthly discharge of Oostanaula River at Resaca—Continued.

Month	Discharge in second-feet			Run-off	
	Maximum	Minimum	Mean	Sec.-ft. per sq. mile	Depth in inches
1906					
January.....	18,000	2,280	6,330	3.93	4.53
February.....	3,880	1,670	2,220	1.38	1.44
March.....	24,300	1,670	7,760	4.82	5.56
April.....	9,670	2,080	3,410	2.12	2.36
May.....	4,250	1,290	2,100	1.80	1.50
June.....	17,800	1,540	4,220	2.62	2.92
July.....	16,200	1,290	4,880	3.03	3.49
August.....	5,350	2,080	3,320	2.06	2.38
September.....	6,940	1,670	3,180	1.98	2.21
October.....	18,800	1,940	6,460	4.01	4.62
November.....	36,600	1,480	7,560	4.70	5.24
December.....	18,000	1,540	3,710	2.30	2.65
The year.....	36,600	1,290	4,600	2.86	38.90

NOTE.—Values are rated as follows: March and November good; remainder of 1906 excellent.

COOSAWATTEE RIVER AT CARTERS.

This river, which is formed by the junction of Ellijay and Cartecay rivers at Ellijay, flows in a southwesterly direction, joining the Conasauga to form the Oostanaula. Its drainage area is for the most part mountainous and covered with forest growth. The gaging station was established August 15, 1896, by M. R. Hall, at the iron highway bridge at Carters, Murray County, Ga. Carters is at the head of navigation, small boats running to Rome, Ga., and the Coosa River below. It is at the foot of the great shoals made by this stream in cutting through the Cohutta Mountains. The channel is curved for 1,000 feet above and 500 feet below the station. The current is swift and broken. Both banks are high, but overflow at flood stages. The bed of the stream is of gravel and is not liable to change. Discharge measurements are made from the single-span highway bridge and its approaches. The initial point for soundings is the land side of the pier on the right bank.

A standard chain gage is attached to the downstream side of the bridge in the third panel from the right bank; length of chain, 36.57 feet. The observer is R. P. Messer, who reads the gage once a day. Bench marks were established as follows: (1) The top of the cylindrical iron pier at the right bank, downstream side; elevation, 30.35 feet. (2) The top of a stone post set into the ground on the north side of the river, about 300 feet from the end of the iron bridge and on the west side of the road leading toward Carter's mill; elevation, 22.15 feet. Elevations refer to the datum of the gage.



A VIEW OF THE LOCKS OF THE AUGUSTA CANAL, LOOKING TOWARD THE CITY OF AUGUSTA.

MOBILE DRAINAGE BASIN, STREAM FLOW

Discharge measurements of Coosawattee River at Carters.

Date	Gage height	Dis-charge	Date	Gage height	Dis-charge
	<i>Feet</i>	<i>Sec.-ft.</i>		<i>Feet</i>	<i>Sec.-ft.</i>
1896			1900		
August 15.....	0.90	320	November 17.....	1.37	453
August 17.....	.95	319	November 26.....	4.08	1,899
October 10.....	.55	228	December 22.....	2.70	1,132
1897			1901		
May 22.....	2.10	815	April 20.....	7.00	3,917
May 24.....	1.95	771	June 21.....	2.92	1,283
May 26.....	1.83	712	October 25.....	1.95	717
May 28.....	1.85	698	1902		
June 1.....	1.90	723	April 28.....	2.72	1,088
June 28.....	1.33	474	August 8.....	.95	313
July 15.....	1.50	544	November 4.....	.85	273
July 22.....	2.41	1,079	December 30.....	2.30	902
September 17.....	.70	251	1903		
September 27.....	.60	216	March 18.....	3.56	1,588
November 15.....	.77	243	July 22.....	2.35	963
November 24.....	.75	263	September 8.....	1.22	444
December 14.....	2.71	1,117	September 8.....	1.22	456
December 22.....	3.54	1,661	October 16.....	1.07	374
1898			December 31.....	1.26	416
January 26.....	5.70	3,052	1904		
March 18.....	1.80	697	March 15.....	2.60	1,045
March 30.....	5.87	3,079	May 26.....	1.30	427
March 30.....	5.35	2,782	June 25.....	.99	322
May 28.....	1.36	495	August 23.....	.85	312
June 25.....	1.12	385	September 27.....	.50	202
July 28.....	2.55	1,019	December 21.....	.82	275
August 25.....	1.77	686	December 21.....	.73	235
November 22.....	4.05	2,006	1905		
1899			March 13.....	2.10	848
January 28.....	2.14	868	March 28.....	2.21	917
March 14.....	8.95	5,240	June 6.....	1.77	694
March 14.....	7.70	4,682	September 23.....	1.02	361
May 26.....	2.35	906	December 30.....	2.39	942
June 22.....	1.75	653	December 30.....	2.39	951
October 19.....	1.10	377	1906		
1900			March 17.....	4.38	2,140
April 28.....	2.60	1,075	March 30.....	8.25	4,540
May 11.....	2.15	811	June 5.....	7.90	4,660
May 24.....	2.05	731			
August 13.....	1.58	576			
September 7.....	1.25	423			

WATER POWERS OF GEORGIA

Daily gage height, in feet, of Coosawattee River at Carters.

Day	Aug.	Sept.	Oct.	Nov.	Dec.	Day	Aug.	Sept.	Oct.	Nov.	Dec.	
1896						1896						
1.....		0.75	1.25	0.8	2.5	17.....	0.95	0.5	0.65	0.95	2.35	
2.....		.75	1.1	.85	2.25	18.....	.9	.5	.6	.9	2.2	
3.....		.75	1.0	1.0	2.0	19.....	.85	.45	.6	.9	2.05	
4.....		.7	.95	1.05	2.0	20.....	.8	.5	.55	.9	2.0	
5.....		.7	.95	3.1	1.9	21.....	.8	.5	.55	.85	1.85	
6.....		.65	.9	1.25	1.8	22.....	.8	.55	.6	.85	1.85	
7.....		.65	.8	1.0	1.8	23.....	.75	.65	.8	.85	1.8	
8.....		.6	.7	1.0	1.75	24.....	.95	.75	1.3	.9	1.7	
9.....		.6	.6	.9	1.65	25.....	.95	.65	.95	1.0	1.6	
10.....		.65	.5	.9	1.6	26.....	.95	.6	.6	1.0	1.5	
11.....		.7	.5	6.05	1.5	27.....	.9	.6	.6	.95	1.5	
12.....		.65	.8	3.5	1.4	28.....	.9	.55	.7	1.25	1.45	
13.....		.6	.9	2.6	1.4	29.....	.85	1.6	1.25	1.25	1.4	
14.....		.55	.8	1.4	1.35	30.....	.85	1.4	.9	3.5	1.4	
15.....		.55	.75	1.0	2.5	31.....	.8		.8		1.85	
16.....		.55	.7	.9	2.5							
Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1897												
1.....	1.3	1.4	2.05	4.05	4.0	1.9	1.4	1.35	1.0	0.6	0.8	0.75
2.....	1.25	4.0	1.95	4.1	3.25	1.9	1.4	1.35	1.0	.6	.8	.75
3.....	1.25	3.0	1.85	5.0	2.75	1.9	1.3	1.3	.95	.6	1.5	.9
4.....	1.25	2.15	1.85	9.0	2.5	2.2	1.3	1.3	.95	.6	1.0	2.2
5.....	1.2	2.4	1.8	15.0	2.4	2.0	1.3	1.4	.9	.55	.7	3.5
6.....	1.2	2.4	9.0	4.5	2.35	1.9	1.4	2.5	.9	.55	.6	1.9
7.....	1.2	2.5	5.1	4.0	2.3	1.8	1.7	2.0	.9	.55	.6	1.8
8.....	1.2	2.55	4.0	3.5	2.2	1.8	1.6	1.8	.8	.55	.7	1.8
9.....	1.15	2.55	3.5	5.5	2.15	1.7	1.6	1.6	.75	.55	.7	1.5
10.....	1.15	2.5	3.5	5.0	2.2	1.6	1.6	1.6	.75	.55	.8	1.5
11.....	1.15	2.5	3.6	4.5	2.5	1.6	1.7	1.5	.7	.55	.8	2.1
12.....	1.2	2.7	21.15	4.3	3.5	1.6	1.5	1.4	.7	2.5	.7	1.3
13.....	4.15	2.5	11.5	4.0	2.5	1.5	1.4	1.3	.7	1.1	.7	2.0
14.....	2.2	2.5	13.62	3.5	2.5	1.5	1.4	1.2	.7	1.0	.7	2.7
15.....	2.1	2.1	10.0	4.5	2.4	1.5	1.5	1.1	.7	1.0	.6	2.5
16.....	2.1	2.1	8.0	3.5	2.3	2.7	1.5	1.1	.65	.9	.6	2.4
17.....	2.2	2.05	5.5	3.3	2.3	1.3	1.5	1.1	.7	.8	.7	2.4
18.....	2.0	2.0	5.0	3.25	2.3	1.6	1.7	1.1	.65	.7	.7	2.6
19.....	2.0	2.0	6.0	3.2	2.2	1.5	9.9	1.05	.6	.7	.7	2.7
20.....	3.15	2.0	6.0	3.1	2.2	1.5	3.5	1.05	.6	1.45	.7	2.5
21.....	4.1	2.05	5.1	3.0	2.1	1.5	2.4	1.05	.6	1.4	.65	3.0
22.....	2.15	2.1	5.0	3.95	2.1	1.4	3.0	1.05	.6	1.1	.65	3.1
23.....	2.1	7.0	4.8	3.95	2.0	1.4	2.0	1.0	.6	.8	.65	2.9
24.....	2.0	3.5	4.5	3.9	2.0	1.5	1.5	1.0	.6	.8	.7	2.8
25.....	2.0	2.5	4.0	3.8	1.9	1.4	1.5	.9	.6	.7	.7	2.5
26.....	1.9	2.4	3.75	3.7	1.9	1.4	1.9	.9	.6	.7	.7	2.2
27.....	1.7	2.3	3.5	3.65	1.8	1.4	1.6	.8	.6	.6	.7	2.0
28.....	1.5	2.2	3.35	3.6	1.8	1.4	1.5	.8	.6	.6	.7	1.8
29.....	1.4		3.25	3.5	1.8	2.5	1.4	.9	.6	.6	.75	1.5
30.....	1.3		3.1	3.5	2.5	1.5	1.4	3.5	.65	.6	.75	1.4
31.....	1.2		3.0		2.0		1.4	1.5		.55		1.3
1898												
1.....	1.2	2.0	1.4	2.9	2.05	1.2	.95	2.0	2.0	1.4	2.05	2.5
2.....	1.1	2.0	1.4	2.9	2.0	1.2	.9	2.05	13.2	1.6	2.0	2.4
3.....	1.0	2.0	1.3	2.9	1.9	1.1	.9	2.0	11.5	1.75	2.0	2.0
4.....	1.0	1.95	1.3	3.0	1.9	1.1	.9	2.1	7.0	20.5	2.0	1.9
5.....	1.0	1.95	1.2	13.5	1.8	1.1	1.0	2.0	5.0	23.0	1.9	1.8
6.....	.9	1.9	1.1	7.0	1.8	1.05	1.1	2.15	4.0	11.5	2.0	1.7
7.....	.9	1.9	1.1	5.0	1.8	1.05	1.05	1.95	3.2	5.0	1.9	1.7
8.....	.95	1.8	1.1	4.2	1.7	1.0	1.1	2.0	3.0	3.5	1.9	1.6
9.....	.95	1.8	1.05	3.5	1.7	1.0	1.1	2.0	2.5	3.0	1.8	1.7
10.....	1.1	1.8	1.00	3.0	1.6	1.05	1.0	2.25	2.2	3.9	1.7	1.5
11.....	1.5	1.7	1.0	2.3	1.6	1.0	1.0	4.7	2.0	2.8	1.8	1.6
12.....	2.0	1.7	1.05	2.0	1.5	1.1	1.1	3.5	1.9	2.6	1.9	1.6
13.....	2.5	1.6	1.1	2.0	1.5	1.4	1.1	3.0	1.8	2.4	2.0	1.7
14.....	2.0	1.6	2.0	1.9	1.45	1.6	1.3	2.5	1.5	2.3	2.1	1.7
15.....	1.8	1.6	1.9	2.05	1.45	1.7	1.4	2.25	1.4	2.3	2.05	1.6

MOBILE DRAINAGE BASIN, STREAM FLOW

363

Daily gage height, in feet, of Coosawattee River at Carters—Continued.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1898												
16	1.8	1.55	1.8	2.1	1.4	1.6	1.1	2.1	1.3	2.2	2.0	1.8
17	1.7	1.55	1.8	2.1	1.4	1.6	1.2	2.5	1.2	2.2	1.9	1.9
18	1.7	1.5	1.7	2.1	1.4	1.5	1.1	3.0	1.25	4.7	1.9	1.8
19	2.05	1.5	1.7	2.05	1.3	1.8	1.1	2.5	1.3	3.2	2.0	1.7
20	2.3	1.5	1.6	2.1	1.3	2.0	1.05	2.3	1.3	3.0	1.9	1.7
21	2.1	1.45	1.6	2.05	1.3	1.8	1.0	9.5	1.2	2.5	1.8	1.8
22	2.5	1.3	1.5	2.0	1.35	1.7	1.0	3.0	1.2	2.5	2.5	2.0
23	2.5	1.3	1.4	2.5	1.35	1.4	1.1	2.0	1.25	2.5	2.4	2.1
24	2.1	1.2	1.4	3.5	1.4	1.2	1.1	1.6	1.3	2.5	2.4	2.0
25	3.0	1.2	1.6	4.0	1.6	1.05	1.2	1.8	1.2	2.4	2.3	2.0
26	6.1	1.2	1.6	3.0	1.5	1.0	1.3	1.6	1.2	2.4	2.3	1.9
27	3.5	1.5	1.5	2.2	1.5	1.0	1.5	1.5	1.2	2.3	2.4	1.9
28	2.8	1.5	1.5	2.2	1.5	1.05	3.5	1.5	1.2	2.3	2.5	1.8
29	2.5	3.5	2.1	1.4	.9	2.5	1.5	1.3	2.2	2.8	1.7
30	2.5	6.5	2.1	1.3	.95	2.0	1.6	1.3	2.1	2.7	1.7
31	2.1	4.0	1.25	3.0	1.7	2.1	1.8
1899												
1	1.8	2.5	5.0	5.1	3.4	2.0	1.4	1.9	1.0	.75	.95	.85
2	1.9	3.0	4.5	5.0	3.3	1.95	1.5	1.8	1.05	.75	.9	1.3
3	1.9	3.5	3.5	5.2	3.2	1.95	1.4	1.8	1.0	.7	.9	1.2
4	2.0	15.8	3.5	6.0	3.0	1.9	1.4	1.7	1.0	.65	.9	1.2
5	2.05	14.0	6.1	5.8	2.9	2.0	1.45	1.6	.95	.65	.85	1.1
6	2.1	13.2	4.8	5.5	2.9	2.0	1.4	1.5	1.0	.7	.85	1.0
7	2.0	12.5	4.5	5.5	2.8	1.9	1.3	1.45	.95	.7	.8	1.1
8	3.0	3.0	4.0	4.8	2.7	1.9	1.3	1.5	.9	1.5	.8	1.0
9	2.0	6.0	3.2	4.0	2.65	1.85	1.6	1.5	.9	1.2	.9	.9
10	2.0	6.0	3.0	3.7	2.6	1.85	1.5	1.4	.9	1.0	.8	.9
11	2.1	5.0	3.5	3.6	2.5	1.9	1.5	1.4	.95	.9	.8	1.1
12	2.0	4.0	3.5	3.5	2.5	3.2	1.4	1.3	.9	.9	.9	7.4
13	1.9	4.0	4.0	3.4	2.6	3.0	1.4	1.3	.9	.95	.9	5.0
14	1.9	4.5	4.5	3.0	2.6	2.5	1.4	1.6	.9	.9	1.0	3.0
15	2.0	4.5	19.0	3.0	2.5	2.3	1.35	1.5	.85	.9	.9	2.0
16	2.2	4.0	12.0	3.1	2.5	2.2	1.3	1.4	.85	.9	.9	1.5
17	2.8	5.0	10.0	4.0	2.4	2.1	1.7	1.2	.85	.9	1.0	1.3
18	2.6	4.7	9.0	4.0	2.3	2.0	1.5	1.2	.8	.85	1.05	1.1
19	2.4	3.6	7.5	3.75	2.3	1.9	1.6	1.15	.85	.85	1.0	1.1
20	2.3	3.5	6.0	3.5	2.2	1.9	1.8	1.15	.85	.9	1.1	1.2
21	2.1	4.0	5.0	3.4	2.2	1.8	2.2	1.1	.8	.9	1.1	1.2
22	2.1	3.5	8.0	3.5	2.3	1.7	3.0	1.1	.8	.9	1.0	1.4
23	2.0	3.4	7.0	3.5	2.2	1.7	2.5	1.1	.85	.85	.9	1.5
24	2.0	3.5	6.5	4.0	2.15	1.7	2.0	1.05	.85	.85	1.0	3.0
25	2.5	4.0	5.0	6.0	2.15	1.6	2.0	1.05	.8	.8	1.0	2.0
26	2.3	5.0	5.0	5.0	2.1	1.6	3.2	1.1	.8	.8	1.2	1.5
27	2.1	15.0	5.2	4.0	2.1	1.5	3.0	1.1	.8	.75	1.1	1.3
28	2.1	7.0	4.8	4.0	2.05	1.5	3.0	1.05	.8	.8	1.05	1.2
29	2.1	4.5	3.7	2.05	1.4	2.2	1.15	.75	1.0	1.0	1.2
30	2.2	4.6	3.6	2.0	1.45	1.9	1.2	.8	1.0	1.0	1.1
31	2.4	4.4	2.0	2.0	1.19	1.1
1900												
1	1.2	1.4	3.0	2.4	2.7	1.9	3.5	2.0	1.4
2	1.2	1.4	3.1	2.4	2.6	2.0	3.5	2.0	1.4
3	1.1	1.3	2.7	2.5	2.5	2.0	5.0	1.9	1.5
4	1.1	1.4	2.8	2.6	2.4	2.0	4.8	1.9	1.5	1.6
5	1.0	1.5	4.75	2.5	2.3	2.1	4.0	1.8	1.4	1.8
6	1.0	1.7	4.75	2.6	2.2	2.2	3.8	1.7	1.5	1.7
7	1.1	1.8	4.9	2.6	2.2	5.0	3.6	1.7	1.5	1.6
8	1.1	2.0	5.2	2.5	2.1	3.0	3.5	1.7	1.6	1.6
9	1.2	4.1	5.0	2.6	2.4	5.0	3.4	1.6	1.6	1.6
10	4.0	2.5	4.6	2.7	2.2	4.5	3.5	1.6	1.5	1.5
11	4.3	2.5	3.1	4.0	2.0	3.0	3.4	1.6	1.5	1.4
12	7.0	8.5	2.9	5.0	1.9	2.2	3.3	1.6	1.4	1.4
13	3.5	20.5	3.0	3.0	1.7	2.0	3.0	1.5	1.4	1.5
14	2.0	5.4	2.9	2.5	1.7	2.4	2.8	1.5	1.3	1.6
15	1.9	4.0	2.8	2.6	1.8	2.6	2.6	1.4	1.3	1.7

WATER POWERS OF GEORGIA

Daily gage height, in feet, of Coosawattee River at Carters—Continued.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1900												
16.....	1.7	3.2	2.5	2.7	1.8	3.0	2.6	1.4	1.3	1.6
17.....	1.7	2.8	2.5	2.8	2.1	3.0	2.4	1.5	1.4	1.8
18.....	2.0	2.7	3.0	3.0	2.0	3.4	2.2	1.5	1.4	2.0
19.....	4.3	2.5	7.5	3.5	1.9	5.0	2.0	1.5	1.4	4.0
20.....	4.0	2.2	4.0	3.7	1.8	5.6	2.0	1.6	1.3	4.2
21.....	2.5	3.0	3.5	4.5	1.7	4.2	2.0	1.6	1.3	3.2
22.....	2.2	3.2	3.0	3.5	1.7	4.7	1.9	1.8	1.4	2.6
23.....	2.0	3.1	2.9	3.0	1.8	4.5	1.8	2.0	1.4	2.7
24.....	2.0	3.05	2.5	2.9	1.9	4.0	2.0	2.5	1.6	2.6
25.....	1.9	3.0	2.0	2.8	2.0	5.0	2.2	1.9	3.5	2.5
26.....	1.8	3.0	5.0	2.7	2.1	6.0	3.5	5.0	2.5
27.....	1.8	2.9	3.6	2.8	2.0	6.5	5.2	4.0	2.4
28.....	1.7	2.5	3.5	3.0	1.9	5.0	3.2	2.5	2.3
29.....	1.6	3.1	3.1	1.8	4.5	2.4	1.5	2.4
30.....	1.5	3.0	3.0	1.8	4.0	2.3	1.5	2.5
31.....	1.5	2.8	1.9	2.2	2.6
1901												
1.....	3.1	4.0	2.3	5.0	3.0	5.0	3.3	1.7	3.7	2.6	1.8	2.0
2.....	3.0	3.0	2.2	8.0	2.9	3.8	3.2	2.0	3.5	2.6	1.7	2.3
3.....	2.5	6.75	2.2	6.0	2.9	3.5	3.0	2.1	3.0	2.5	1.7	2.5
4.....	2.5	6.0	2.3	5.0	2.8	3.4	2.8	2.5	3.0	2.5	1.7	2.5
5.....	2.4	8.5	2.2	4.5	2.8	3.3	2.8	5.0	2.7	2.4	1.8	2.6
6.....	2.2	5.0	2.3	4.5	2.6	3.1	2.6	4.5	2.6	2.4	1.8	2.8
7.....	2.1	4.0	2.3	4.2	2.6	3.0	3.0	3.0	2.5	2.3	1.7	2.9
8.....	2.1	4.0	2.2	4.0	2.5	3.2	2.8	2.5	2.5	2.2	1.8	3.0
9.....	2.05	6.5	2.1	3.9	2.5	3.2	2.6	2.0	2.4	2.2	1.9	3.1
10.....	2.0	5.2	4.8	3.9	2.4	3.4	2.6	2.25	2.4	2.1	1.8	3.0
11.....	16.5	5.0	3.6	3.8	2.4	3.5	2.5	2.0	2.6	2.1	1.8	2.9
12.....	6.0	4.5	3.2	3.5	2.3	4.0	2.4	2.5	2.7	2.0	1.7	2.9
13.....	6.0	4.0	3.0	3.5	2.4	4.5	2.5	3.0	2.5	2.0	1.7	3.0
14.....	5.0	3.5	2.8	3.2	2.5	5.0	2.4	9.0	2.5	2.0	1.8	13.0
15.....	4.1	3.2	2.7	4.6	2.4	5.2	2.3	4.5	3.0	1.9	1.8	9.0
16.....	3.6	3.0	2.6	4.2	2.5	4.8	2.2	5.0	19.0	1.9	1.9	6.0
17.....	3.2	3.0	2.5	4.0	2.5	4.0	2.0	4.5	7.0	1.8	1.8	4.5
18.....	3.0	3.0	2.6	4.0	3.0	3.5	1.8	5.0	4.5	1.8	1.9	3.0
19.....	3.0	2.9	2.7	12.0	3.0	3.0	1.6	5.0	4.0	1.8	1.9	2.9
20.....	2.5	2.9	2.6	7.0	4.0	2.8	1.8	6.0	3.5	1.9	1.8	2.9
21.....	2.5	2.8	2.5	6.0	19.5	2.6	2.0	17.0	3.5	1.9	1.8	2.8
22.....	2.7	2.8	2.5	5.0	12.0	2.6	2.2	15.0	3.4	1.8	1.9	2.8
23.....	2.8	2.6	2.7	4.1	3.0	2.5	2.3	10.0	3.2	1.8	1.9	3.0
24.....	3.0	2.6	3.2	3.8	6.0	2.5	2.0	8.0	3.1	1.7	2.0	2.9
25.....	3.0	2.5	14.65	3.7	5.0	2.4	2.0	7.0	3.0	1.7	2.0	3.0
26.....	2.6	2.4	18.3	3.5	5.0	2.4	2.0	6.5	3.0	1.8	2.1	3.1
27.....	2.6	2.5	9.0	3.4	4.5	2.6	1.9	6.0	2.9	1.8	2.0	5.5
28.....	2.4	2.4	7.0	3.2	4.5	2.6	1.8	4.0	2.8	1.8	1.9	9.0
29.....	2.4	7.0	3.0	4.4	3.0	1.7	4.0	2.6	1.8	1.8	21.5
30.....	2.5	6.0	3.0	4.2	3.5	1.6	4.2	2.7	1.9	1.8	13.0
31.....	3.5	6.2	4.0	1.5	4.0	1.9	11.0
1902												
1.....	9.0	11.0	15.0	4.0	3.0	1.7	1.7	.9	.9	1.0	.7	2.5
2.....	7.0	9.0	15.0	3.9	3.0	1.7	1.7	.8	.8	1.0	.7	3.0
3.....	6.0	7.5	10.0	3.8	2.9	1.8	1.6	.9	1.0	.9	.8	5.0
4.....	5.0	5.0	9.0	4.0	2.7	1.8	1.6	.8	.9	.9	.8	4.0
5.....	4.0	4.0	8.0	3.8	2.5	1.8	1.6	.8	1.0	1.0	.8	3.0
6.....	3.0	3.9	6.5	3.4	2.7	1.7	1.6	.9	.9	.9	1.0	2.0
7.....	2.9	3.8	5.0	3.6	2.6	1.9	1.7	.9	.8	.8	2.0	1.3
8.....	2.9	3.3	4.0	3.8	2.5	2.5	1.5	.8	1.0	.8	1.7	1.7
9.....	2.8	3.7	3.5	3.7	2.4	2.3	1.5	.8	.9	.8	.9	1.5
10.....	2.8	3.7	3.5	3.4	2.4	1.8	1.5	1.0	.8	.9	.9	1.4
11.....	2.7	3.6	3.9	3.3	2.4	1.7	1.6	2.1	.8	1.4	.8	1.2
12.....	2.7	3.3	3.8	3.3	2.3	1.7	1.5	1.3	2.0	1.0	.7	1.1
13.....	2.8	3.5	3.7	3.3	2.3	1.6	1.5	1.5	1.5	.9	.7	1.1
14.....	2.8	3.4	3.5	3.2	2.2	1.6	1.4	1.0	1.1	2.5	.8	1.0
15.....	2.7	3.4	3.4	3.2	2.2	1.7	1.4	.9	.9	1.4	.8	1.0

MOBILE DRAINAGE BASIN, STREAM FLOW

365

Daily gage height, in feet, of Coosawattee River at Carters—Continued.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1902												
16.....	2.6	3.5	6.4	3.1	2.3	1.8	1.3	.9	.8	1.2	.7	3.0
17.....	2.6	3.5	5.2	3.1	2.3	1.7	1.3	.9	.8	.9	1.6	2.0
18.....	2.5	3.5	3.8	3.2	2.5	1.5	1.3	1.0	.8	.9	1.5	1.8
19.....	2.6	3.6	4.7	3.0	2.3	1.5	1.2	.9	.9	.8	1.1	1.7
20.....	2.5	3.7	4.4	2.9	2.2	1.4	1.2	.8	1.9	.8	.9	1.6
21.....	2.4	3.8	3.4	2.9	2.4	1.4	1.2	.9	1.1	.8	.9	6.5
22.....	2.5	4.0	3.3	2.8	2.2	1.5	1.2	1.0	.9	.9	1.0	4.0
23.....	2.5	4.0	3.3	2.9	2.1	1.5	1.1	.9	.9	.9	1.2	2.5
24.....	2.4	3.8	3.3	2.9	2.0	1.6	1.1	.8	1.0	.8	1.5	2.0
25.....	2.4	3.6	3.3	2.9	1.9	1.6	1.1	.8	1.2	.8	6.5	1.7
26.....	2.4	3.5	3.4	2.8	2.0	1.5	1.0	.8	2.0	.8	4.5	1.5
27.....	2.5	4.0	3.5	2.8	2.0	1.4	1.0	.9	1.3	.7	4.0	1.3
28.....	2.5	3.0	4.2	2.8	1.9	1.4	.9	1.0	1.1	.7	3.5	1.2
29.....	2.6	18.0	2.9	1.9	1.5	.9	1.4	.9	.8	3.0	2.2
30.....	2.9	5.0	3.0	1.8	1.6	.9	1.1	.9	.8	2.5	2.8
31.....	3.5	4.7	1.89	.98	1.0
1903												
1.....	1.7	2.0	9.2	6.0	3.4	4.5	2.6	2.2	1.3	1.0	1.2	1.1
2.....	2.0	2.5	5.4	5.2	3.2	5.0	2.5	2.3	1.2	1.0	1.2	1.1
3.....	2.5	3.0	4.6	4.9	3.2	5.2	2.4	2.4	1.2	1.0	1.4	1.2
4.....	2.0	10.0	4.1	5.0	3.1	5.0	2.3	2.5	1.2	1.0	1.3	1.2
5.....	1.6	9.0	4.1	4.4	3.0	6.8	2.3	2.4	1.2	1.0	1.2	1.2
6.....	1.6	7.0	5.0	4.2	2.8	5.5	2.2	2.3	1.3	.9	1.2	1.1
7.....	1.5	8.0	3.7	4.1	2.8	4.2	2.1	2.2	1.3	.9	1.1	1.05
8.....	1.4	7.0	5.9	8.0	2.7	3.5	2.0	2.1	1.2	2.0	1.1	1.05
9.....	1.4	6.0	4.6	4.1	2.7	3.6	2.2	2.3	1.2	1.4	1.05	1.1
10.....	1.2	6.0	5.1	4.2	2.7	3.0	2.3	2.4	1.15	1.2	1.05	1.1
11.....	3.3	9.0	8.9	4.0	2.6	4.7	2.5	2.3	1.1	1.0	1.2	1.1
12.....	2.7	6.5	4.8	3.8	2.6	4.2	3.0	2.2	1.05	1.05	1.3	1.2
13.....	2.4	4.5	4.3	10.0	2.5	3.5	9.0	2.1	1.05	1.0	1.1	1.4
14.....	2.1	4.0	4.2	5.4	2.5	3.4	6.0	2.1	1.1	1.0	1.1	1.3
15.....	2.0	4.0	4.0	4.8	2.4	3.0	4.2	2.0	1.2	1.0	1.1	1.3
16.....	2.0	10.5	3.8	4.4	2.5	2.8	3.8	2.2	1.6	1.05	1.2	1.2
17.....	1.9	9.0	3.7	4.1	2.5	2.6	3.5	2.1	1.4	1.6	2.8	1.2
18.....	2.0	6.0	3.4	3.9	2.5	2.5	3.0	2.0	1.3	1.3	2.6	1.2
19.....	1.9	4.2	3.4	4.0	2.4	2.4	2.3	1.9	1.2	1.2	2.4	1.2
20.....	1.8	4.0	3.3	4.0	2.4	2.2	2.4	1.8	1.1	1.2	2.0	1.5
21.....	1.8	3.5	4.3	3.9	2.6	2.2	2.3	1.7	1.1	1.1	1.9	1.2
22.....	1.7	3.3	6.1	3.9	2.4	2.0	2.2	1.6	1.1	1.05	1.7	1.1
23.....	1.7	3.2	18.2	3.8	2.4	2.1	2.1	1.5	1.05	1.0	1.4	1.1
24.....	1.6	3.1	8.1	3.8	2.5	2.2	2.2	1.4	1.1	1.0	1.3	1.2
25.....	1.6	3.0	5.2	3.7	2.6	3.0	2.1	1.4	1.1	1.05	1.2	1.2
26.....	1.5	2.9	4.6	3.7	2.6	3.5	2.0	1.3	1.05	1.1	1.2	1.7
27.....	1.5	3.4	4.2	3.6	2.4	4.0	2.0	1.3	1.05	1.1	1.2	1.4
28.....	1.5	21.5	4.4	3.5	2.3	3.0	2.2	1.2	1.05	1.0	1.3	1.2
29.....	2.5	6.4	3.6	3.0	3.0	2.1	1.2	1.05	1.0	1.2	1.1
30.....	2.2	21.0	3.5	3.5	2.9	2.2	1.2	1.05	1.1	1.1	1.1
31.....	2.0	7.8	5.0	2.4	1.3	1.2	1.1
1904												
1.....	1.2	1.5	1.7	2.2	1.7	2.0	1.1	5.0	.8	.5	.4	2.0
2.....	1.1	1.5	1.7	2.2	1.7	1.8	1.0	2.0	.7	.5	.4	2.2
3.....	1.4	1.5	1.7	2.1	1.7	1.5	1.0	1.5	.7	.5	.4	1.8
4.....	1.1	1.5	3.5	2.0	2.0	1.3	1.0	1.3	.7	.45	.7	1.6
5.....	1.1	1.4	3.75	1.9	1.8	1.2	1.0	1.6	.9	.45	.6	1.8
6.....	1.1	1.3	3.0	1.9	1.7	3.1	1.4	1.2	.8	.45	.6	1.6
7.....	1.1	1.4	3.0	1.9	1.7	3.0	1.3	1.1	.7	.45	.5	1.4
8.....	1.1	2.8	2.5	4.0	4.45	2.0	1.3	1.6	.7	.45	.5	1.3
9.....	1.1	2.6	2.2	3.0	3.0	1.8	1.5	2.0	.6	.4	.5	1.2
10.....	1.1	1.8	2.1	2.5	2.0	1.6	1.2	1.5	.6	.4	.5	1.1
11.....	1.3	1.6	2.0	2.3	1.8	1.3	1.0	1.4	.6	.4	.4	1.0
12.....	1.3	1.5	1.9	2.2	1.7	1.3	2.05	1.3	.6	.4	.4	1.0
13.....	1.3	1.5	1.8	2.0	1.7	1.2	1.7	1.1	.5	.4	.4	1.0
14.....	1.3	1.4	4.8	1.9	1.7	1.2	1.2	1.0	.5	.4	.4	.9
15.....	1.2	1.7	2.8	1.9	1.6	1.2	1.0	1.0	.7	.4	.4	.9

WATER POWERS OF GEORGIA

Daily gage height, in feet, of Coosawatee River at Carters—Continued.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1904												
16.....	1.3	1.7	2.2	1.9	1.6	1.2	1.0	1.0	.6	.4	.4	.9
17.....	2.3	1.6	2.1	1.8	1.6	1.1	1.8	1.0	.6	.4	.4	.85
18.....	1.9	1.6	2.0	1.8	1.6	1.1	1.3	1.0	.5	.4	.4	.85
19.....	1.5	3.4	1.8	1.8	1.5	1.1	1.0	.9	.5	.4	.4	.85
20.....	1.4	3.0	1.8	1.8	1.5	1.0	1.0	.9	.4	.4	.4	.85
21.....	1.4	2.3	1.8	1.8	1.5	3.0	.9	.9	.4	.4	.4	.85
22.....	4.35	4.3	2.0	1.8	1.5	2.0	1.8	.8	.4	.4	.5	.85
23.....	3.0	3.5	5.2	1.8	1.4	1.5	1.5	.8	.5	.4	.6	.8
24.....	2.3	2.4	3.8	1.7	1.4	1.2	1.0	.8	.5	.4	.6	.8
25.....	2.0	2.2	2.9	1.7	1.3	1.0	1.0	.9	.5	.4	.6	1.0
26.....	1.7	2.1	2.3	4.0	1.3	1.0	1.0	1.0	.45	.4	.6	1.3
27.....	1.6	2.0	2.3	2.5	1.3	1.0	.9	.9	.5	.4	.6	3.9
28.....	1.5	1.8	2.6	2.0	1.2	1.2	1.1	1.0	.5	.4	.5	4.0
29.....	1.5	1.8	2.5	1.8	1.2	1.2	1.0	.9	.5	.4	.5	2.0
30.....	1.5	2.4	1.7	1.2	1.8	1.0	.9	.5	.4	1.8	1.8
31.....	1.5	2.3	3.79	.84	1.8
1905												
1.....	1.3	1.4	3.0	2.4	2.5	2.0	1.9	1.5	1.4	1.0	1.1	1.1
2.....	1.8	1.5	3.0	2.2	2.0	2.0	1.8	1.5	4.2	1.0	1.1	2.0
3.....	1.8	1.4	2.3	2.1	2.0	1.95	1.8	1.4	3.5	1.1	1.1	18.2
4.....	1.8	1.4	2.7	2.0	1.9	1.8	1.8	1.4	2.0	1.0	1.0	9.0
5.....	1.7	1.4	2.6	2.0	1.9	1.8	1.9	1.35	1.6	1.0	1.0	4.0
6.....	1.7	1.5	2.3	2.3	2.3	1.75	2.0	1.35	1.4	.9	1.0	3.0
7.....	1.1	3.0	2.2	2.2	2.3	1.75	2.0	1.35	1.4	.9	1.0	3.0
8.....	1.2	9.5	2.2	2.2	2.2	1.7	1.9	1.6	1.35	.9	1.0	12.0
9.....	1.3	13.0	2.5	2.1	2.1	1.7	2.0	1.6	1.3	1.0	1.0	9.6
10.....	1.2	5.0	3.0	2.1	2.0	1.8	3.0	2.0	1.3	1.0	1.0	4.5
11.....	1.1	4.0	4.2	2.3	2.0	1.8	5.0	4.0	1.3	3.0	.9	2.5
12.....	14.5	4.0	3.2	2.5	1.9	1.7	5.5	3.0	6.0	1.8	.9	2.5
13.....	7.3	6.0	2.4	2.4	1.9	1.7	4.0	2.5	2.0	1.8	.9	2.5
14.....	4.2	4.0	2.3	2.3	1.85	1.7	2.0	2.0	1.5	1.8	.9	2.5
15.....	3.6	3.0	2.3	2.2	3.5	1.9	1.9	3.5	1.4	1.6	.9	2.5
16.....	3.1	3.0	2.2	2.0	5.5	1.8	1.9	3.0	1.3	1.4	.9	2.3
17.....	3.0	2.6	2.2	2.0	3.3	1.8	1.8	2.5	1.3	1.4	.9	2.2
18.....	2.8	2.6	2.1	1.95	2.5	1.7	1.8	2.4	1.2	1.4	.9	2.2
19.....	2.6	2.3	2.0	1.95	3.3	1.8	1.8	2.0	1.2	1.3	1.0	2.1
20.....	2.4	14.0	2.0	1.8	2.4	1.8	1.7	2.0	1.15	1.3	1.0	2.1
21.....	2.3	10.0	6.5	1.8	2.2	1.75	1.7	1.8	1.15	1.4	1.0	5.0
22.....	2.0	6.0	3.5	1.85	7.0	1.9	1.7	1.8	1.1	1.4	.9	4.0
23.....	1.8	4.0	3.0	1.9	4.0	1.9	1.8	1.7	1.05	1.3	.9	3.6
24.....	1.6	3.5	2.6	2.0	3.5	1.8	2.0	1.7	1.0	1.3	1.1	3.2
25.....	1.4	3.0	2.5	2.0	3.0	1.8	1.8	1.6	1.0	1.2	2.0	3.0
26.....	1.2	3.5	2.4	1.9	2.3	1.9	1.8	1.6	1.0	1.2	2.1	2.5
27.....	1.1	3.3	2.3	2.5	2.5	3.5	1.7	1.5	1.0	1.2	1.5	2.5
28.....	1.2	3.2	2.2	2.1	2.3	3.0	1.7	1.4	1.0	1.2	1.1	2.4
29.....	1.3	2.2	2.0	2.3	2.0	1.6	1.4	1.0	1.3	1.1	2.4
30.....	1.3	2.5	3.5	2.2	2.0	1.6	1.4	1.0	1.3	1.1	2.4
31.....	1.4	2.5	2.2	1.5	1.4	1.2	2.4
1906												
1.....	2.4	3.2	2.3	4.6	2.3	2.5	2.1	3.0	2.3	7.0	2.3	2.9
2.....	3.0	3.2	2.4	4.0	2.3	3.0	2.1	4.0	2.3	6.0	2.3	2.3
3.....	10.5	3.1	5.0	3.9	4.2	2.6	2.4	3.5	2.7	5.6	2.3	2.3
4.....	4.0	3.1	4.0	3.7	3.3	2.5	2.5	3.0	2.6	5.0	2.2	2.3
5.....	3.0	3.0	3.0	3.5	3.0	5.5	2.3	7.0	2.6	5.0	2.2	2.7
6.....	2.6	3.0	2.9	3.6	5.0	3.0	2.2	5.0	2.5	4.8	2.1	2.3
7.....	2.5	3.2	2.3	4.0	3.9	2.5	2.2	3.5	2.5	4.5	2.1	2.3
8.....	2.5	3.2	2.3	3.8	3.6	2.5	2.1	3.0	7.0	4.3	2.1	2.7
9.....	2.8	3.0	2.3	5.0	3.0	2.4	2.3	2.6	4.0	3.5	2.2	2.7
10.....	3.0	2.9	2.7	4.5	2.3	2.4	2.3	2.3	3.5	3.3	2.3	4.5
11.....	3.5	2.9	2.7	4.0	2.6	2.3	2.2	3.0	3.4	3.1	2.4	3.2
12.....	3.0	2.3	2.7	3.0	2.6	2.7	2.2	2.3	3.0	3.0	2.4	3.0
13.....	2.5	2.7	3.0	2.8	2.5	14.0	2.1	2.6	2.3	2.9	2.3	2.3
14.....	2.5	2.6	4.0	2.8	2.5	5.5	3.5	2.6	2.7	2.8	2.3	2.3
15.....	2.5	2.5	18.8	4.0	2.5	8.0	2.5	2.5	2.7	2.7	2.4	2.3

MOBILE DRAINAGE BASIN, STREAM FLOW

Daily gage height, in feet, of Coosawattee River at Carters—Continued.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1906												
16.....	3.6	2.4	6.0	3.6	2.4	5.0	2.0	2.5	2.6	2.6	2.4	3.0
17.....	3.5	2.4	5.0	3.4	2.4	4.5	3.0	2.5	2.5	2.6	2.6	3.6
18.....	3.5	2.4	4.8	3.2	2.3	3.5	5.5	2.6	2.5	5.0	13.2	4.0
19.....	3.6	2.4	13.0	3.1	2.3	3.0	8.2	2.8	5.0	3.5	26.0	4.8
20.....	3.6	2.4	7.0	3.0	2.2	2.8	5.0	2.7	4.0	3.3	9.4	3.8
21.....	3.8	2.4	5.0	3.0	2.2	2.7	4.2	2.6	3.0	3.1	5.4	3.7
22.....	10.5	2.6	4.0	3.0	2.1	2.6	5.0	2.5	2.8	3.0	4.8	3.7
23.....	11.0	2.5	3.8	2.9	2.1	2.5	4.6	2.5	2.5	3.8	4.0	3.6
24.....	6.5	2.5	3.7	2.9	2.1	3.1	4.0	2.8	2.6	3.6	3.6	3.6
25.....	4.5	2.5	3.6	2.8	2.1	3.0	3.5	2.7	4.2	3.4	3.4	3.6
26.....	4.0	2.4	3.5	2.8	7.0	2.9	3.0	2.6	2.8	3.2	3.2	3.5
27.....	3.5	2.4	4.3	2.7	3.0	2.8	3.5	2.6	2.6	3.0	3.1	3.5
28.....	3.5	2.4	4.2	4.0	2.8	2.5	3.5	2.8	2.5	2.6	3.05	4.5
29.....	3.4	4.1	3.0	2.6	2.4	4.0	2.7	2.5	2.4	3.0	5.0
30.....	3.4	8.5	3.0	2.5	2.3	4.7	2.6	4.0	2.4	3.0	5.0
31.....	3.3	5.4	2.5	3.1	3.0	2.4	9.0

Rating tables for Coosawattee River at Carters.

AUGUST 17, 1896, TO DECEMBER 31, 1897.^a

Gage height	Dis-charge						
<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>
0.40	158	1.90	722	3.30	1,506	5.40	2,308
.50	188	2.00	771	3.40	1,568	5.60	2,932
.60	219	2.10	821	3.50	1,630	5.80	3,056
.70	250	2.20	872	3.60	1,692	6.00	3,180
.80	284	2.30	924	3.70	1,754	7.00	3,800
.90	318	2.40	977	3.80	1,816	8.00	4,420
1.00	353	2.50	1,031	3.90	1,878	9.00	5,040
1.10	388	2.60	1,086	4.00	1,940	10.00	5,660
1.20	423	2.70	1,143	4.20	2,064	12.00	7,160
1.30	460	2.80	1,201	4.40	2,188	14.00	8,660
1.40	499	2.90	1,260	4.60	2,312	16.00	10,160
1.50	540	3.00	1,320	4.80	2,436	18.00	11,660
1.60	583	3.10	1,382	5.00	2,560	20.00	13,160
1.70	628	3.20	1,444	5.20	2,684	22.00	14,660
1.80	674						

JANUARY 1 TO DECEMBER 31, 1898.^b

0.90	318	2.00	771	3.10	1,380	4.10	2,043
1.00	355	2.10	821	3.20	1,440	4.20	2,120
1.10	388	2.20	872	3.30	1,500	4.30	2,199
1.20	423	2.30	924	3.40	1,560	4.40	2,280
1.30	460	2.40	977	3.50	1,623	4.50	2,350
1.40	499	2.50	1,031	3.60	1,690	4.60	2,420
1.50	540	2.60	1,086	3.70	1,760	4.70	2,480
1.60	583	2.70	1,143	3.80	1,830	4.80	2,540
1.70	628	2.80	1,201	3.90	1,900	4.90	2,600
1.80	674	2.90	1,260	4.00	1,970	5.00	2,660
1.90	722	3.00	1,320				

^a Between gage height 3.00 and 10.00 feet the rating curve is a tangent, the difference being 62 per tenth. Above gage height 10.00 feet the rating curve is a tangent with a difference of 75 per tenth.

^b Above gage height 5.00 feet the table is the same as that for 1899.

WATER POWERS OF GEORGIA

Rating tables for Coosawatee River at Carters—Continued.

JANUARY 1 TO DECEMBER 31, 1899.^a

Gage height	Dis-charge						
<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>
0.60	230	2.50	1,031	4.60	2,378	8.20	4,826
.70	250	2.60	1,086	4.80	2,514	8.40	4,962
.80	280	2.70	1,142	5.00	2,650	8.60	5,098
.90	310	2.80	1,200	5.20	2,786	8.80	5,234
1.00	345	2.90	1,250	5.40	2,922	9.00	5,370
1.10	382	3.00	1,318	5.60	3,058	9.50	5,710
1.20	420	3.10	1,378	5.80	3,194	10.00	6,050
1.30	457	3.20	1,440	6.00	3,330	10.50	6,390
1.40	495	3.30	1,503	6.20	3,466	11.00	6,730
1.50	537	3.40	1,566	6.40	3,602	11.50	7,070
1.60	580	3.50	1,632	6.60	3,738	12.00	7,410
1.70	627	3.60	1,698	6.80	3,874	13.00	8,090
1.80	675	3.70	1,766	7.00	4,010	14.00	8,770
1.90	722	3.80	1,834	7.20	4,146	15.00	9,450
2.00	770	3.90	1,902	7.40	4,282	16.00	10,130
2.10	820	4.00	1,970	7.60	4,418	17.00	10,810
2.20	872	4.20	2,106	7.80	4,554	18.00	11,490
2.30	924	4.40	2,242	8.00	4,690	19.00	12,170
2.40	977						

JANUARY 1, 1900, TO DECEMBER 31, 1901.^b

1.00	355	3.10	1,345	5.20	2,694	9.20	5,574
1.10	390	3.20	1,400	5.40	2,833	9.40	5,718
1.20	425	3.30	1,455	5.60	2,982	9.60	5,862
1.30	460	3.40	1,510	5.80	3,126	9.80	6,006
1.40	495	3.50	1,567	6.00	3,270	10.00	6,150
1.50	535	3.60	1,625	6.20	3,414	10.50	6,510
1.60	575	3.70	1,687	6.40	3,558	11.00	6,870
1.70	622	3.80	1,750	6.60	3,702	11.50	7,230
1.80	670	3.90	1,812	6.80	3,846	12.00	7,590
1.90	717	4.00	1,875	7.00	3,990	12.50	7,950
2.00	765	4.10	1,942	7.20	4,134	13.00	8,310
2.10	815	4.20	2,010	7.40	4,278	14.00	9,030
2.20	865	4.30	2,077	7.60	4,422	15.00	9,750
2.30	917	4.40	2,145	7.80	4,566	16.00	10,470
2.40	970	4.50	2,212	8.00	4,710	17.00	11,190
2.50	1,022	4.60	2,280	8.20	4,854	18.00	11,910
2.60	1,075	4.70	2,347	8.40	4,998	19.00	12,630
2.70	1,127	4.80	2,415	8.60	5,142	20.00	13,350
2.80	1,180	4.90	2,482	8.80	5,286	22.00	14,790
2.90	1,235	5.00	2,550	9.00	5,430	24.00	16,230
3.00	1,290						

JANUARY 1, 1902, TO DECEMBER 31, 1903.^c

0.70	250	0.90	310	1.10	382	1.30	455
.80	280	1.00	345	1.20	420	1.40	495

JANUARY 1 TO DECEMBER 31, 1904.^d

0.40	184	1.50	512	2.60	1,058	3.60	1,620
.50	202	1.60	557	2.70	1,112	3.70	1,680
.60	222	1.70	603	2.80	1,166	3.80	1,740
.70	244	1.80	650	2.90	1,220	3.90	1,805
.80	269	1.90	698	3.00	1,275	4.00	1,870
.90	296	2.00	747	3.10	1,330	4.20	2,000
1.00	326	2.10	797	3.20	1,385	4.40	2,130
1.10	358	2.20	848	3.30	1,440	4.60	2,270
1.20	393	2.30	900	3.40	1,500	4.80	2,410
1.30	430	2.40	952	3.50	1,560	5.00	2,550
1.40	470	2.50	1,005				

^a Above gage height 4.00 feet the rating curve is a tangent, the difference being 68 per tenth.^b Above gage height 5.00 feet the rating curve is a tangent, the difference being 72 per tenth.^c Above gage height 1.40 feet this table is the same as the 1901 table.^d Above gage height 5.00 feet this table is the same as the 1901 table.

MOBILE DRAINAGE BASIN, STREAM FLOW

Rating tables for Coosawattee River at Carters—Continued.

JANUARY 1 TO DECEMBER 31, 1905.^a

Gage height	Dis-charge						
<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>
0.90	825	1.50	560	2.10	830	2.60	1,070
1.00	860	1.60	605	2.20	875	2.70	1,120
1.10	400	1.70	650	2.30	920	2.80	1,170
1.20	440	1.80	695	2.40	970	2.90	1,220
1.30	480	1.90	740	2.50	1,020	3.00	1,275
1.40	520	2.00	785				

^a Above gage height 3.0 feet the rating curve is the same as the 1904 table.

Rating table for Coosawattee River at Carters, for 1906.

Gage height	Dis-charge						
<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>
2.00	785	2.80	1,170	3.60	1,620	4.80	2,410
2.10	830	2.90	1,220	3.70	1,680	5.00	2,550
2.20	875	3.00	1,275	3.80	1,740	5.20	2,694
2.30	920	3.10	1,330	3.90	1,805	5.40	2,838
2.40	970	3.20	1,385	4.00	1,870	5.60	2,982
2.50	1,020	3.30	1,440	4.20	2,000	5.80	3,126
2.60	1,070	3.40	1,500	4.40	2,130	6.00	3,270
2.70	1,120	3.50	1,560	4.60	2,270	7.00	3,990

NOTE.—The above table is based on discharge measurements made during 1902-1906 and is well defined below gage height 8 feet. Above gage height 5 feet the rating curve is a tangent, the difference being 72 per tenth.

Estimated monthly discharge of Coosawattee River at Carters.

[Drainage area, 531 square miles]

Month	Discharge in second-feet			Run-off	
	Maximum	Minimum	Mean	Sec.-ft. per sq. mile	Depth in inches
1896 ^a					
August 17-31.....	336	267	307	0.58	0.32
September.....	583	173	245	.46	.51
October.....	490	188	284	.53	.62
November.....	3,211	284	583	1.11	1.24
December.....	1,031	480	684	1.29	1.49
1897					
January.....	2,033	405	710	1.33	1.53
February.....	3,800	499	1,092	2.05	2.14
March.....	14,022	698	2,908	5.47	6.31
April.....	9,410	1,320	1,852	3.48	3.88
May.....	1,940	674	959	1.80	2.08
June.....	1,143	499	638	1.19	1.33
July.....	5,600	460	787	1.48	1.71
August.....	1,630	284	496	0.93	1.07
September.....	353	219	259	0.49	0.55
October.....	1,031	205	293	0.55	0.63
November.....	540	219	263	0.49	0.55
December.....	1,630	265	444	0.83	0.95
The year.....	14,022	205	891	1.67	22.73

^a The estimates for 1896 were revised on the basis of the 1897 rating curve.

WATER POWERS OF GEORGIA

Estimated monthly discharge of Coosawatee River at Carters—Continued.

Month	Discharge in second-feet			Run-off	
	Maximum	Minimum	Mean	Sec.-ft. per sq. mile	Depth in inches
1898 <i>a</i>					
January.....	4,690	313	937	1.76	2.03
February.....	771	423	601	1.13	1.18
March.....	3,670	355	699	1.31	1.51
April.....	8,430	722	1,470	2.76	3.08
May.....	796	442	566	1.06	1.22
June.....	771	313	459	0.86	0.95
July.....	1,624	313	491	0.92	1.06
August.....	5,710	541	1,062	1.99	2.29
September.....	8,226	423	1,300	2.45	2.73
October.....	14,890	499	2,159	4.06	4.68
November.....	1,200	627	323	1.55	1.73
December.....	1,031	541	689	1.30	1.50
The year.....	14,890	313	938	1.76	23.96
1899					
January.....	1,318	675	353	1.60	1.84
February.....	9,994	1,081	3,448	6.48	6.75
March.....	12,170	1,318	3,224	6.06	6.99
April.....	3,330	1,318	2,112	3.97	4.43
May.....	1,566	770	1,033	1.94	2.24
June.....	1,440	495	750	1.41	1.57
July.....	1,440	457	698	1.31	1.51
August.....	722	363	476	0.89	1.02
September.....	363	265	305	0.57	0.63
October.....	537	240	305	0.57	0.66
November.....	420	280	329	0.62	0.69
December.....	4,282	310	691	1.30	1.50
The year.....	12,170	240	1,185	2.23	23.83
1900					
January.....	3,990	365	912	1.71	1.97
February.....	13,710	455	1,707	3.21	3.34
March.....	4,350	765	1,645	3.09	3.56
April.....	2,550	970	1,294	2.43	2.71
May.....	1,127	622	783	1.47	1.69
June.....	3,630	717	1,747	3.23	3.66
July.....	2,694	670	1,344	2.53	2.92
August 1-25.....	1,022	495	632	1.19	1.11
November 4-30.....	2,550	455	693	1.30	1.30
December.....	2,010	495	337	1.57	1.81
1901					
January.....	14,790	765	1,625	3.06	3.53
February.....	5,070	970	1,371	3.52	3.67
March.....	14,070	315	2,214	4.17	4.81
April.....	9,750	1,290	2,306	4.34	4.84
May.....	16,950	917	2,153	4.06	4.68
June.....	2,694	970	1,533	2.90	3.24
July.....	1,455	535	923	1.74	2.01
August.....	16,230	622	2,773	5.23	6.03
September.....	12,630	970	1,761	3.32	3.70
October.....	1,075	622	783	1.47	1.69
November.....	315	622	636	1.29	1.44
December.....	15,510	765	2,689	5.06	5.83
The year.....	16,950	535	1,777	3.35	45.47
1902					
January.....	5,430	970	1,487	2.80	3.23
February.....	15,510	1,510	2,622	4.94	5.14
March.....	11,910	1,455	3,127	5.89	6.79
April.....	1,875	1,180	1,437	2.71	3.02
May.....	1,290	670	927	1.76	2.02
June.....	1,022	495	614	1.16	1.29
July.....	622	310	469	0.88	1.01
August.....	315	280	350	0.66	0.76
September.....	765	280	375	0.71	0.79
October.....	1,022	250	337	0.63	0.73
November.....	3,630	250	676	1.27	1.42
December.....	3,630	345	914	1.72	1.98
The year.....	15,510	250	1,111	2.09	23.18

*a*Estimates for 1898 have been revised above gage height 5.0 feet on the basis of the 1899 rating curve.

MOBILE DRAINAGE BASIN, STREAM FLOW

371

Estimated monthly discharge of Coosawattee River at Carters—Continued.

Month	Discharge in second-feet			Run-off	
	Maximum	Minimum	Mean	Sec.-ft. per sq. mile	Depth in inches
1903					
January.....	1,455	420	721	1.36	1.57
February.....	14,430	765	3,294	6.20	6.46
March.....	14,070	1,455	3,295	6.20	7.15
April.....	6,150	1,565	2,244	4.23	4.72
May.....	2,550	917	1,172	2.21	2.55
June.....	3,846	765	1,631	3.07	3.43
July.....	5,430	765	1,233	2.32	2.67
August.....	1,022	420	729	1.37	1.58
September.....	575	364	408	.77	.86
October.....	765	310	389	.73	.84
November.....	1,180	364	512	.96	1.07
December.....	622	364	421	.79	.91
The year.....	14,430	310	1,337	2.52	33.81
1904					
January.....	2,097	358	575	1.08	1.24
February.....	2,410	430	791	1.49	1.61
March.....	2,694	602	1,063	2.00	2.31
April.....	1,870	603	823	1.55	1.73
May.....	2,165	393	659	1.24	1.43
June.....	1,330	326	549	1.03	1.15
July.....	772	296	408	.763	.885
August.....	2,550	269	453	.853	.983
September.....	296	184	220	.414	.462
October.....	202	184	187	.352	.406
November.....	650	184	215	.405	.452
December.....	1,870	269	524	.987	1.14
The year.....	2,694	184	539	1.01	13.80
1905					
January.....	9,390	400	1,140	2.15	2.48
February.....	9,030	520	2,264	4.26	4.44
March.....	3,630	785	1,144	2.15	2.43
April.....	1,560	695	858	1.62	1.81
May.....	3,990	718	1,147	2.16	2.49
June.....	1,560	650	752	1.42	1.58
July.....	2,910	560	837	1.67	1.92
August.....	1,870	500	759	1.43	1.65
September.....	3,270	360	652	1.23	1.37
October.....	1,275	325	490	.923	1.06
November.....	830	325	394	.742	.828
December.....	12,050	400	2,026	3.82	4.40
The year.....	12,050	325	1,043	1.96	26.51
1906					
January.....	6,870	970	1,990	3.75	4.32
February.....	1,330	970	1,130	2.13	2.22
March.....	12,500	920	2,480	4.67	5.33
April.....	2,550	1,120	1,550	2.92	3.26
May.....	3,990	830	1,260	2.37	2.73
June.....	9,030	920	1,710	3.22	3.59
July.....	4,850	785	1,510	2.84	3.27
August.....	3,990	1,020	1,320	2.49	2.87
September.....	3,990	1,020	1,380	2.60	2.90
October.....	3,990	970	1,710	3.22	3.71
November.....	17,700	830	2,140	4.03	4.50
December.....	5,430	1,120	1,670	3.15	3.63
The year.....	17,700	785	1,650	3.12	42.33

NOTE.—Values are rated as follows: January, February, April to October, and December, are excellent; March and November are only good, owing to liability of backwater at high stages.

CARTECAY RIVER NEAR CARTECAY.

This station was established June 27, 1904, by M. R. Hall. It is located at the Cartecay Bridge on the public road 6 miles upstream from Ellijay and 1½ miles northwest of Cartecay. Turkey Creek enters from the south side and Owltown Creek from the north side between this point and Ellijay. There is probably no considerable interference from dams above the station.

The channel is straight for about 500 feet above and below the station. The current is swift. Both banks are high, but are subject to overflow. The bed of the stream is composed of boulders and is probably permanent, the water flowing in one channel.

Discharge measurements are made from the downstream side of the single 60-foot span wooden bridge. The bridge has an approach on the right bank of 24 feet and on the left bank of 26 feet. The initial point for soundings is the edge of the abutment on the right bank, downstream side.

The gage is a vertical 10-foot timber, fastened to the sill and downstream post of the trestle bent at the right bank. It is read once each day by S. A. Burrell. The bench mark is the top of the downstream end of the first floor beam from the right bank, marked by nails and white paint; elevation, 16.50 feet above the datum of the gage.

Discharge measurements of Cartecay River near Cartecay.

Date	Gage height	Dis-charge	Date	Gage height	Dis-charge
1904			1905		
	<i>Feet</i>	<i>Sec.-ft.</i>		<i>Feet</i>	<i>Sec.-ft.</i>
May 9.....	1.30	176	April 19.....	1.20	167
June 27.....	.90	86	June 22.....	1.45	230
August 31.....	.85	94	October 16.....	1.07	137
October 12.....	.65	70			
December 13.....	.80	78			

Daily gage height, in feet, of Cartecay River near Cartecay.

Day	July	Aug.	Sept.	Oct.	Nov.	Dec.	Day	July	Aug.	Sept.	Oct.	Nov.	Dec.
1904							1904						
1.....	1.1	1.1	0.8	0.9	0.75	1.15	17.....	1.3	1.3	1.3	0.7	0.75	0.9
2.....	1.1	1.2	.85		.8	.9	18.....	1.5	1.25	2.1	.7	.8	.85
3.....	1.3	2.4	1.2		.8	1.1	19.....	3.05	3.55	.9	.75	.85	.8
4.....	1.5	1.65	1.1		.85	1.0	20.....	3.05	2.15	.9	.6	.9	.75
5.....	1.7	2.3	.9		.9	1.5	21.....	2.2	1.9	.85	.65	.8	.75
6.....	1.75	2.85	.9		.8	1.2	22.....	1.7	1.7	.8	.75	.95	.7
7.....	3.3	1.9	.85		.85	1.2	23.....	1.6	1.3	2.3	.75	.95	.7
8.....	2.2	1.7	.8		.9	1.1	24.....	2.2	1.25	2.15	.75	.9	.9
9.....	1.4	1.5	1.4		.95	1.0	25.....	1.95	3.35	.95	.65	.85	1.1
10.....	1.3	1.45	.85		.9	1.0	26.....	1.3	2.7	1.9	.6	.8	.9
11.....	1.35	1.4	.8		1.2	.9	27.....	1.25	1.6	.8	.65	.8	.9
12.....	3.5	2.65	.8	.65	1.3	.9	28.....	1.7	1.15	.8	.7	.85	2.5
13.....	5.4	2.1	.85		1.1	.8	29.....	1.25	1.1	1.2	.75	.85	2.2
14.....	2.3	1.7	.8		.95	.8	30.....	1.1	.9	.9	.7	1.3	1.2
15.....	2.1	1.5	.75		.9	.85	31.....		.85		.7		.9
16.....	1.3	1.35	.8		.8	.85							

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1905												
1.....	0.9	0.95	1.45	1.3	1.7	1.5	1.6	1.1	1.15	1.3	0.9	1.1
2.....		.95	.95	1.4	1.3	1.7	1.4	1.0	1.15	1.2	1.3	1.3
3.....		.95	.9	1.4	1.25	1.6	1.35	1.4	1.0	1.2	1.2	1.2
4.....		.95	.85	1.3	1.2	1.5	1.2	1.4	.95	1.25	1.7	1.2
5.....		.9	.9	1.35	1.6	1.45	1.2	1.35	.9	1.2	1.4	1.1
6.....	1.55	1.1	1.4	1.5	1.4	1.15	1.2	.9	1.2	1.3	1.1	1.8
7.....	1.2	1.1	1.45	1.3	1.4	1.1	1.2	.95	1.15	1.2	1.1	1.4
8.....	1.1	2.1	1.3	1.25	1.9	1.15	1.2	1.6	1.1	1.1	.95	1.3
9.....	1.1	2.9	1.3	1.2	1.6	1.1	1.15	1.9	1.15	1.0	.95	2.5
10.....	1.2	2.8	1.65	1.1	1.5	1.1	1.15	1.8	1.15	1.0	.9	2.0
11.....	1.2	1.6	1.3	1.1	1.35	1.1	1.2	1.6	1.2	1.0	.9	1.7
12.....	9.7	1.4	1.3	1.7	1.3	1.0	4.3	1.5	1.9	1.1	.85	1.6
13.....	2.5	2.8	1.25	1.4	1.3	1.0	3.6	1.5	1.4	1.1	.85	1.6
14.....	1.7	1.6	1.2	1.3	1.25	1.1	2.7	1.6	1.3	1.1	.9	1.6
15.....	1.6	1.5	1.2	1.35	1.3	1.1	2.1	1.6	1.2	1.0	.9	1.5
16.....	1.4	1.5	1.2	1.3	2.1	1.6	1.9	3.6	1.2	.9	.9	1.5
17.....	1.45	1.4	1.25	1.3	1.6	1.4	1.3	2.9	1.15	.9	.9	1.4
18.....	1.35	1.4	1.25	1.3	1.4	1.2	1.3	2.1	1.15	.95	1.0	1.4
19.....	1.3	1.35	1.2	1.25	1.4	1.2	1.25	1.6	1.1	1.0	1.7	1.4
20.....	1.2	6.5	1.6	1.25	1.3	1.2	1.25	1.5	1.1	1.0	1.5	2.0
21.....	1.2	3.6	2.6	1.25	1.3	1.6	1.2	1.4	1.1	.9	1.3	1.7
22.....	1.15	2.2	1.8	1.2	2.6	2.3	1.2	1.35	.9	1.1	1.1	1.7
23.....	1.15	1.9	1.6	1.2	1.8	1.9	1.2	1.3	.9	1.1	1.1	1.6
24.....	1.2	1.7	1.5	1.25	1.7	1.6	1.1	1.3	.9	1.1	1.1	1.5
25.....	1.1	1.7	1.5	1.2	1.6	1.5	1.1	1.25	.95	1.3	1.5	1.4
26.....	1.1	1.65	1.5	1.25	1.6	1.5	1.1	1.2	.95	1.2	1.4	1.4
27.....	1.0	1.65	1.4	1.5	1.5	1.4	1.2	1.2	.9	1.1	1.3	1.3
28.....	1.0	1.5	1.3	1.3	1.4	1.4	1.2	1.2	1.0	1.1	1.2	1.3
29.....	1.0		1.3	1.9	1.4	1.3	1.15	1.15	1.0	1.1	1.4	1.25
30.....	1.15		1.6	1.8	1.35	1.9	1.15	1.1	1.6	.9	1.2	1.2
31.....	1.1		1.4		1.6		1.15	1.1		.9		1.2

Rating table for Cartecay River near Cartecay, from July 1, 1904, to December 31, 1905.^a

Gage height	Dis-charge						
Feet	Sec.-ft.	Feet	Sec.-ft.	Feet	Sec.-ft.	Feet	Sec.-ft.
0.60	56	1.00	113	1.40	215	1.80	366
.70	67	1.10	134	1.50	249	1.90	411
.80	80	1.20	158	1.60	286	2.00	456
.90	95	1.30	185	1.70	326		

^aAs the highest measurement is at 1.5 feet the table has not been extended beyond 2 feet. For that reason no monthly estimates have been made. The table as given covers the low-water period.

ELLIJAY RIVER, AT ELLIJAY.

This station was established June 28, 1904, by M. R. Hall. It is located at a wagon bridge about one-half mile east of Ellijay, and about the same distance above the junction of Ellijay and Cartecay rivers.

The channel is straight for about 500 feet above and below the station. The right bank is about 12 feet high and the left about 10 feet. Both banks are bordered by fields and are subject to overflow. There is one channel, broken by one wooden pier. The bed of the stream is composed of rock, and the current ranges from very swift above the station to sluggish below.

Discharge measurements are made from the open wooden wagon bridge, which has two 40-foot spans and 50-foot approaches on each bank. The initial point for soundings is the end of the bridge at the right bank on the downstream side.

A gage staff, reading from 2 to 6 feet, is nailed to the downstream vertical post at the right bank, and a bench mark established for reference. Regular gage readings are not maintained. The bench mark is a small nail and white paint mark in the downstream vertical post at the right bank; elevation, 7.00 feet above datum of the assumed gage.

Discharge measurements of Ellijay River at Ellijay.

Date	Gage height	Dis-charge	Date	Gage height	Dis-charge
December 9..... 1903	<i>Feet</i>	<i>Sec.-ft.</i> 76	December 14..... 1904	<i>Feet</i> 1.20	<i>Sec.-ft.</i> 66
May 10..... 1904	1.80	154	April 18..... 1905	1.70	145
June 28.....	1.35	94	June 21.....	1.78	156
August 30.....	1.22	68	October 16.....	1.42	114
October 12.....	1.07	42			

MOUNTAINTOWN CREEK NEAR ELLIJAY.

This station was established May 10, 1904, by O. P. Hall. It is located at the covered bridge, known as Charles Bridge, about 4 miles west of Ellijay, and about the same distance above the mouth of the creek. This bridge consists of a single span of 54 feet, with short trestle approaches at either end. Discharge measurements are made either from the bridge, where the meter is lowered through

holes in the floor; or at a foot log half a mile below. The initial point for soundings is the end of the trestle approach at the right bank.

The channel is straight for about 500 feet above and 100 feet below the station. Both banks are high and not liable to overflow. The bed of the stream is rocky. The water is shallow and swift at the bridge, the better section being at the foot log below the bridge.

Gage heights are determined directly from the bench mark, which is a nail driven into the vertical post of the main bent under the right end of the bridge 6 feet above the top of the mud sill of the bent; elevation, 7.00 feet above the datum of the assumed gage.

Discharge measurements of Mountaintown Creek near Ellijay.

Date	Gage height	Dis-charge	Date	Gage height	Dis-charge
1904			1905		
	<i>Feet</i>	<i>Sec.-ft.</i>		<i>Feet</i>	<i>Sec.-ft.</i>
May 10.....	1.17	157	April 19.....	1.05	152
August 31.....	.85	79	October 17.....	.93	92
October 12.....	.75	31			

TALKING ROCK CREEK NEAR CARTERS.

This station was established May 26, 1904, by O. P. Hall. It is located about 3 miles above the mouth of Talking Rock Creek and about the same distance east of Carters. Numerous measurements of the creek had previously been made in connection with measurements at the Coosawattee River station.

Both banks are high and will probably not overflow. There is one channel at all stages. The section is a good one. Discharge measurements are made from a boat just above R. L. Hill's boat landing, or by wading at a shoal a short distance below. Gage heights are determined directly from the bench mark, which is a nail in a large elm tree on the left bank at R. L. Hill's boat landing; elevation, 7.50 feet above the datum of the assumed gage.

Discharge measurements of Talking Rock Creek near Carters.

Date	Gage height	Dis-charge	Date	Gage height	Dis-charge
1904			1905		
	<i>Feet</i>	<i>Sec.-ft.</i>		<i>Feet</i>	<i>Sec.-ft.</i>
May 26.....	1.24	49	June 6.....	1.59	143
June 25.....	1.08	34	September 28.....	1.16	51
August 23.....	1.07	40			

BIG CEDAR CREEK NEAR CAVESPRING.

This station was established in 1905. It is located at the wagon bridge about 3 miles north of Cavespring, 1 mile below the Southern Railway bridge, and half a mile below the mouth of Little Cedar Creek.

The channel is straight for about 200 feet above and 300 feet below the bridge. The right bank is low and will overflow to the extent of the 100-foot wooden approach. The left bank is high and will not overflow. The bed is of sand and mud, and is therefore probably shifting. The current is sluggish at low stages. Measurements are made from the single iron span 91 feet long. The initial point for soundings is the end of the bridge at the left bank, upstream.

Gage heights are determined directly from the bench mark, which is the top of the upstream end of the second floor beam from the right-bank end of the bridge; elevation, 20.00 feet above the datum of the assumed gage.

Discharge measurement of Big Cedar Creek near Cavespring.

Date	Gage height	Dis-charge
July 25.....	1905 Feet 2.70	Sec.-ft. 117

TALLAPOOSA RIVER AT BUCHANAN BRIDGE, NEAR TALLAPOOSA.

This station was established October 21, 1901, by M. R. Hall. It is located at Buchanan Bridge, about 4 miles north of Tallapoosa, and about 2 miles above the station on Tallapoosa River at Adderhold Bridge. Discharge measurements are made from the single-span iron highway bridge, which has a trestle approach of 100 feet on the right bank and of 50 feet on the left bank. The initial point for soundings is the end of the bridge at the right bank, downstream side. The channel is straight for about 800 feet above and 1,000 feet below the station. The current is moderate above and swift below the measuring section and the banks rarely overflow. The bed of the stream is composed of rock and gravel, free from vegetation, and is probably constant; there is but one channel at



COTTON MILL OF THE JOHN P. KING MANUFACTURING COMPANY, AUGUSTA, GEORGIA.

all stages, broken at the higher levels by the piers and trestlework of the bridge. The bench mark is the top of the downstream end of the center floor beam, the third from either end; elevation, 25.25 feet above gage datum.

Discharge measurements of Tallapoosa River at Buchanan Bridge, near Tallapoosa.

Date	Gage height	Dis-charge	Date	Gage height	Dis-charge
1904			1904		
March 26.....	<i>Feet</i> 1.55	<i>Sec.-ft.</i> 180	August 31.....	<i>Feet</i> 0.81	<i>Sec.-ft.</i> 59
May 14.....	.83	39	September 26.....	.71	33
July 19.....	.65	22	1906		
			June 29.....	1.09	97

TALLAPOOSA RIVER AT ADDERHOLD BRIDGE, NEAR TALLAPOOSA.

This station was established on January 7, 1901, by M. R. Hall. It is located at Adderhold Bridge, about 2 miles north of Tallapoosa, and about 2 miles below the station on Tallapoosa River at Buchanan Bridge. Discharge measurements are made from the downstream side of the single-span iron highway bridge, which has trestle approaches at either end. The initial point for sounding is the end of the bridge at the left bank, downstream side. The channel is straight for about 300 feet above and 500 feet below the station. The current is swift above and sluggish below. Both banks are wooded and are subject to overflow under the trestle approaches during high water. The bed of the stream is composed of sand, and is probably constant. There is but one channel at all stages, broken during the higher levels by the piers and trestlework of the bridge. The bench mark is the top of the downstream end of the first floor beam from the left bank; elevation, 22.00 feet above gage datum.

Discharge measurements of Tallapoosa River at Adderhold Bridge, near Tallapoosa.

Date	Gage height	Dis-charge	Date	Gage height	Dis-charge
1904			1904		
March 9.....	<i>Feet</i> 1.20	<i>Sec.-ft.</i> 274	July 19.....	<i>Feet</i> 0.80	<i>Sec.-ft.</i> 32
March 26.....	1.22	218	August 31.....	.65	80
May 14.....	.60	59	September 26.....	.39	50

MISCELLANEOUS MEASUREMENTS IN MOBILE RIVER DRAINAGE BASIN.

The following is a list of miscellaneous discharge measurements made in Mobile River drainage basin in Georgia:

Big Cedar Creek.—This stream enters Coosa River about 6 miles northwest of Cavespring. Measurements were made from the upstream side of a single-span steel bridge $2\frac{1}{2}$ miles northwest of Cavespring and one-fourth mile above the Southern Railway bridge. The bench mark is the top of the second iron floor beam from the right end of the bridge, upstream side, 17.00 feet above the datum of the assumed gage.

January 21, 1904: Width, 62 feet; area, 207 square feet; mean velocity, 0.37 foot per second; gage height, 3.13 feet; discharge, 78 second-feet.

September 28, 1904: Width, 67 feet; area, 177 square feet; mean velocity, 0.29 foot per second; gage height, 3.00 feet; discharge, 51 second-feet.

July 25, 1905: Width, 68 feet; area, 186 square feet; mean velocity, 0.42 foot per second; gage height, 3.13 feet; discharge, 77 second-feet.

July 14, 1906: Width, 77 feet; area, 230 square feet; gage height, 3.32 feet; discharge, 124 second-feet.

A measurement was made May 14, 1906, from a single-span iron wagon bridge, 3 miles north of Cavespring, near Wetsels Ford. The bench mark is the top of the upstream end of the second cross beam from the right end of the bridge; elevation, 20 feet above the datum of the assumed gage.

Width, 61 feet; area, 239 square feet; gage height, 2.92 feet; discharge, 161 second-feet.

Cave Spring.—This spring is tributary to Little Cedar Creek. A measurement was made January 21, 1904, at the footbridge at Cavespring. The water surface was $16\frac{1}{2}$ inches below the upstream side of the bridge floor, 6 inches from the right end of the bridge.

Width, 13 feet; area, 5.6 square feet; mean velocity, 0.94 foot per second; discharge, 5.3 second-feet.

Conasauga River.—This stream is a tributary of Oostanaula River. A measurement was made November 25, 1904, from a boat at Fites Ferry, 2 miles from Resaca, Ga. The bench mark is a small nail in a large leaning willow tree on the left bank, about 200 feet below the ferry, 5.00 feet above the datum of the gage.

Width, 130 feet; area, 219 square feet; mean velocity, 0.74 foot per second; gage height, 2.65 feet; discharge, 163 second-feet.

Etowah River.—A measurement was made July 27, 1904, at Fields Bridge, about 6 miles below Canton. The bench mark is a chisel cut and white paint mark at intermediate post, the second floor beam of the main span from the left end of the bridge, downstream side, 36.00 feet above the datum of the gage.

Width, 89 feet; area, 307 square feet; mean velocity, 1.05 feet per second; gage height, 2.67 feet; discharge, 322 second-feet.

February 23, 1906: Width: 337 feet; area, 1,820 square feet; gage height, 5.63 feet; discharge, 1,780 second-feet.

Measurements were also made at Hardins Bridge, 4 miles south of Kingston, Ga., as follows:

January 24, 1904: Width, 188 feet; area, 1,178 square feet; mean velocity, 1.60 feet per second; gage height, 3.45 feet; discharge, 1,894 second-feet.

April 14, 1904: Width, 188 feet; area, 1,154 square feet; mean velocity 1.21 feet per second; gage height, 3.27 feet; discharge, 1,401 second-feet.

July 29, 1904: Width, 185 feet; area, 1,007 square feet; mean velocity, 0.62 foot per second; gage height, 2.56 feet; discharge, 625 second-feet.

A 5-foot section of gage rod is fastened to a tree on the left bank.

Jack River.—A measurement was made near Alaculsy, October 5, 1904, just above the falls, about 5 miles above the mouth of the river and 23 miles from Blue Ridge, Ga.

Width, 7 feet; area, 7 square feet; mean velocity, 1.86 feet per second; discharge, 13 second-feet.

Little Cedar Creek.—This stream enters Big Cedar Creek about 2 miles north of Cavespring, Ga. A measurement was made September 28, 1904, from the bridge near Cavespring. The bench mark is the top of the first floor beam from the right bank, downstream end, 9.00 feet above the datum of the gage.

Width, 30 feet; area, 18 square feet; mean velocity, 1.00 foot per second; gage height, 1.27 feet; discharge, 18 second-feet.

Little Cedar Creek at Cavespring, Ga.—A measurement was made May 14, 1906, at a single-span iron footbridge on the road to the Cave Spring on the main street of the city. The bench mark is the top of the downstream end of the first iron cross beam from

the right end of the bridge; elevation, 8 feet above the datum of the assumed gage.

Width, 32 feet; area, 14.7 square feet; gage height, 1.26 feet; discharge, 21.7 second-feet.

A measurement was made May 14, 1906, at a wagon bridge one-fourth mile north of Cavespring, Ga. The bench mark is the top of the downstream end of the first cross beam from the left end of the bridge; elevation, 7 feet above the datum of the assumed gage.

Width, 31 feet; area, 15 square feet; gage height, 1.01 feet; discharge, 31 second-feet.

Oothkalooga Creek.—This stream is a tributary of Oostanaula River. A measurement was made May 6, 1904, at a bridge about 1 mile from the mouth of the creek and 1 mile west of Calhoun. The bench mark is the downstream end of the top of cross timber on middle bent, 16.00 feet above the datum of the gage.

Width, 45 feet; area, 50 square feet; mean velocity, 0.64 foot per second; gage height, 2.15 feet; discharge, 32 second-feet.

Pinelog Creek.—This stream flows into Sallacoa Creek, a tributary of Coosawattee River. A measurement was made May 5, 1904, at Butler's bridge, about 1 mile above the mouth, near Cash. The bench mark is the top of the downstream end of the cross timber on first bent from left bank, 17.00 feet above the datum of the gage.

Width, 54 feet; area, 150 square feet; mean velocity, 0.27 foot per second; gage height, 2.80 feet; discharge, 41 second-feet.

Sallacoa Creek.—This stream is a tributary of Coosawattee River. A measurement was made May 5, 1904, at Covington's bridge, about 4 miles above the mouth of Pinelog Creek and 4 miles east of Cash, Ga. The bench mark is the upstream end of the top of cross timber over the first bent from the left bank, 16.00 feet above the datum of the gage.

Width, 42 feet; area, 164 square feet; mean velocity, 0.15 foot per second; gage height, 2.60 feet; discharge, 24 second-feet.

Tallapoosa River.—A measurement was made near Tallapoosa, on March 9, 1904, from the wooden bridge near the Southern Railway and one-half mile below Bentley's dam, below the mouth

of Walkers Creek. The bench mark is the top of the upper end of the floor beam on top of wooden pier, 106 feet from the initial point for soundings, 25.00 feet above the datum of the gage.

Width, 89 feet; area, 517 square feet; mean velocity, 0.74 foot per second; gage height, 6.25 feet; discharge, 381 second-feet.

RIVER SURVEYS IN MOBILE RIVER DRAINAGE BASIN

ETOWAH RIVER

The following list of elevations of water surface on Etowah River from Rome up to the mouth of Little River are from a survey made in 1879 by Ernest Ruhl, of the Corps of Engineers, U. S. Army. The elevations are based on an assumed datum, which is about 376 feet above sea level.

Elevations on Etowah River from Rome to mouth of Little River.

Distance	Description of points	Elevation
<i>Miles</i>		<i>Feet</i>
0.0	Rome, Ga., Broad Street Bridge, water surface.....	276
0.3	Rome, Ga., Silver Creek, mouth, water surface.....	276.8
0.5	Rome, Ga., Southern Railway bridge, water surface.....	276.8
1.0	Water surface.....	278
2.5	Water surface.....	282
3.0	Water surface.....	283.1
3.7	Water surface.....	285
4.3	Water surface.....	286
4.7	Water surface.....	286.3
5.5	Water surface.....	288.3
5.7	Water surface.....	288.5
5.8	Water surface.....	290
6.3	Freemans Ferry, water surface.....	292.5
7.0	Water surface.....	295
7.5	Dykes Creek, 0.3 mile below mouth of, water surface.....	296.5
8.0	Water surface.....	298.8
9.0	Water surface.....	299.7
9.3	Water surface.....	301.1
9.5	Water surface.....	302
9.8	Water surface.....	302.5
11.6	Bass Ferry.....	303.2
12.0	Water surface.....	304.5
12.5	Water surface.....	307.7
13.0	Water surface.....	308.5
13.3	Water surface.....	309.5
14.0	Water surface.....	310
14.5	Thomas Creek, 0.3 mile below mouth of, water surface.....	310.1
15.5	Water surface.....	310.5
15.8	Hanleys Ferry, half mile below, water surface.....	311.6
16.5	Water surface.....	313.1
16.7	Water surface.....	317.9
17.0	Water surface.....	319
17.3	Water surface.....	319.5
18.0	Water surface.....	321
18.2	Water surface.....	321.8
19.0	Woolleys Bridge, water surface.....	322.3
19.5	Water surface.....	323.1
20.1	Conasene Creek, water surface.....	324
20.2	Water surface.....	325
20.4	Water surface.....	326.3
20.5	Two Run Creek, mouth of, water surface.....	327.8
21.7	Water surface.....	330
22.0	Water surface.....	331
22.3	Water surface.....	331.1
22.5	Water surface.....	332
22.6	Water surface.....	

Elevations on Etowah River from Rome to mouth of Little River—Continued.

Distance	Description of points	Elevation
<i>Miles</i>		<i>Feet</i>
22.9	Dodds Slough, water surface.....	332.1
23.0	Water surface.....	333
23.2	Water surface.....	333.7
23.5	Water surface.....	340
23.8	Water surface.....	341.7
24.5	Water surface.....	342.5
25.0	Water surface.....	344.4
25.3	Water surface.....	344.9
26.0	Water surface.....	346.6
27.5	Water surface.....	346.7
27.8	Water surface.....	349
28.5	Water surface.....	350.7
29.2	Water surface.....	351.6
29.5	Water surface.....	352
29.7	Water surface.....	354
30.5	Water surface.....	355.53
30.7	Water surface.....	356
31.0	Uharlee Creek, 0.4 mile below mouth of, water surface.....	356.1
31.8	Water surface.....	358.2
32.8	Water surface.....	360
34.0	Water surface.....	362
34.5	Water surface.....	364.2
35.0	Richland Creek, mouth of, water surface.....	367
35.5	Water surface.....	367.3
37.0	Water surface.....	368
37.5	Water surface.....	369
38.6	Rockmart Railroad bridge, water surface.....	369.3
38.8	Pettits Creek, mouth, and Rowlands ferry, 0.2 mile below, water surface.....	371
39.2	Water surface.....	371.5
39.5	Water surface.....	375.5
40.8	Water surface.....	376.7
41.2	Pumpkinvine Creek, 0.7 mile below mouth, water surface.....	377.9
42.2	Water surface.....	380.4
42.5	Water surface.....	383
42.7	Water surface.....	383.5
43.5	Water surface.....	388
43.9	Tumlin milldam in 1879, foot of, water surface.....	388
43.9	Tumlin milldam in 1879, head of, water surface.....	388
44.2	Water surface.....	388.9
44.4	Wagon bridge, water surface.....	390.5
45.0	Jefferson milldam, foot of, water surface.....	395.5
45.0	Jefferson milldam, head of, water surface.....	395.5
45.1	Western and Atlantic Railroad bridge, water surface.....	395.5
46.0	Water surface.....	398
47.0	Small branch, near mouth, water surface.....	400
47.1	Water surface.....	405
47.8	Water surface.....	410.5
48.0	Water surface.....	418.4
48.5	Near mouth of Altona Creek, water surface.....	422
48.8	Water surface.....	435.5
49.0	Near mouth of Stamp Creek, water surface.....	452.3
50.0	Water surface.....	466.3
50.5	Water surface.....	468.1
51.0	Websters Ferry, water surface.....	469.4
51.2	Water surface.....	477.3
52.0	Water surface.....	480
52.4	Water surface.....	486.4
52.8	Illinois Creek, half mile below mouth, water surface.....	488
53.7	Water surface.....	488.3
54.5	Water surface.....	489.2
54.8	Gaults Ferry, half mile below, water surface.....	489.3
55.5	Owl Creek, 0.2 mile below mouth, water surface.....	491
56.7	Water surface.....	491.1
57.2	Water surface.....	491.9
57.7	Water surface.....	494.8
58.0	Lovengoods Bridge, 0.8 mile below, water surface.....	497
59.7	Water surface.....	497.6
59.8	Water surface.....	500.1
60.4	Water surface.....	502.5
60.7	Water surface.....	502.5
61.7	Water surface.....	504.5
62.2	Wheeler's milldam, foot of.....	508
62.3	Wheeler's milldam, head of.....	508
63.0	Little River, mouth, water surface.....	508

SURVEY OF COOSAWATTEE RIVER

From May 29 to July 12, 1900, a survey of a part of Coosawattee River was made, under the supervision of B. M. Hall, resident hydrographer, by Olin P. Hall, who was field assistant, levelman, and topographer. No camp outfit was carried. The levelman read his distances with the stadia, and identified land lines and tributaries from a township or district map of the old State survey. This map embraces two land districts, the eleventh and the twenty-fifth. The eleventh was found to be correct, but the twenty-fifth was incorrect. The survey began at the Geological Survey Gaging station at Carters, with zero of the gages as a level datum, and extended up the river to Ellijay, a distance of 24 miles. The total fall between the two places was found to be 581.6 feet. This 24 miles of river cuts through the Cohutta Mountains and enters the Paleozoic formation at Carter's mill, about 2 miles above the gaging station, which is the head of navigation on the river. It is along a continuous shoal, and the conditions are such that water power can be developed at any point desired. The only utilized power is at Carter's mill, where there is an 8-foot dam across the river.

Elevations on Coosawattee River from Carters to Ellijay.

Distance	Description of points	Elevation above gage datum
<i>Miles</i>		<i>Feet</i>
0.0	Zero of gage at Carters, Ga.....	0.8
0.0	Water surface at gaging station, May 29, 1900.....	1.8
0.3	Mouth of Talking Rock Creek, bench mark.....	15.54
0.3	Mouth of Talking Rock Creek, water surface.....	3.5
1.75	Below Carter's dam, water surface.....	17.56
1.75	Above Carter's dam, water surface.....	25.73
1.75	Small birch on right bank of river.....	28.40
2.25	Mouth of Fishers Creek, water surface.....	26
2.5	County line between Murray and Gilmer counties, water surface.....	49.2
3.25	Mouth of small branch, water surface.....	51.27
3.25	Small maple 30 feet beyond branch.....	55.25
4.2	Mouth of Camp Branch, water surface.....	69.65
4.2	Pine root at mouth of Camp Creek.....	72.35
4.4	Mouth of Harris Creek, water surface.....	79.19
4.4	Root of small poplar opposite mouth of Harris Creek.....	82.61
5.62	Mouth of Wurley Creek, water surface.....	123.52
5.62	Large basswood.....	135.01
5.72	1,000 feet above Wurley Creek, water surface.....	139.37
6.1	Mouth of Crawfords Creek, 37½ feet fall in 2,300 feet, water surface.....	136.89
6.1	Small white oak opposite Crawfords Creek.....	191.83
9.0	Opposite mouth of Tails Creek, water surface.....	316.84
9.0	Large pine 50 feet south of Tails Creek.....	323.44
10.25	Opposite mouth of Flat Creek, water surface.....	344.14
10.25	Small white oak opposite Flat Creek at John Goble's boat landing.....	354.84
10.5	Water surface.....	350.38
10.9	Below bend of river, water surface.....	363.87
11.45	Foot of shoals, water surface.....	375.09
12.25	Mouth of small branch from the west, water surface.....	409.18
13.25	Line between land districts 25 and 11, water surface.....	440.09
14.0	Mouth of Mountaintown Creek, water surface.....	456.87
14.0	Small white oak on north bank of Mountaintown Creek.....	464.97
16.4	Gentry's boat landing, on lot No. 176, water surface.....	510.30
17.65	260 feet below mouth of Early Creek, water surface.....	532.21
18.18	Smith's boat landing, water surface.....	538.91
18.22	Levi Smith's ford, water surface.....	547.13

Elevations on Coosawattee River from Carters to Ellijay—Continued.

Dis- tance	Description of points	Eleva- tion above gage datum
<i>Miles</i>		<i>Feet</i>
18.25	Root of small red oak 220 feet above ford.....	546.81
19.7	Mouth of branch near corner of lots Nos. 103, 104, 113 and 114, in eleventh district, water surface.....	557.08
22.3	Ford 100 feet below mouth of Mill Creek, water surface.....	577.09
23.3	Covered wagon bridge over Coosawattee River at Ellijay, Ga., water surface.....	581.4
23.3	Large oak on north bank 50 feet above bridge.....	590.75
23.6	Junction of Cartecay and Ellijay rivers, water surface.....	581.92
24.0	A. K. and N. R. R. bridge on Cartecay River, water surface.....	583.39
24.0	Center of stone block on top of south pier of railroad bridge.....	603.29
24.0	Base of rail on south end of railroad bridge.....	605.44
24.0	Base of rail on front of A. K. and N. R. R. depot at Ellijay, Ga.....	613.77

WATER POWER IN MOBILE RIVER DRAINAGE BASIN

ETOWAH RIVER

From Rome up to the Western and Atlantic railroad crossing, near Cartersville, a distance of 45 miles, Etowah River is mostly swift, but has no large shoals. The total fall is about 115 feet, which includes numerous small shoals. At a few places the fall is 5 or 6 feet in a mile or less, and at one place near Kingston the fall is 33 feet in $8\frac{1}{2}$ miles. One and one-fourth miles below the railroad bridge, at the old Tumlin mill site, is the large corn mill of the Etowah Milling Company, utilizing about 6 feet of fall.

Immediately below the railroad bridge is an old mill site from which the mill and the 5-foot dam are entirely gone. About 2 miles above the railroad bridge begins a very fine water power, which was once partly developed and, before the Civil War, operated the Cooper Iron Works and a large flour mill. At present only the ruins of what is said to have been "a half-million dollar plant" are to be seen. This power has a fall of 90 feet in about 6 miles. Above this point there are numerous good small power sites, some of which are developed, but no great falls occur until the upper portion of the river is reached.

On Amicalola River, a large tributary of the Etowah, and on Etowah River above the mouth of the Amicalola, there are many excellent shoals having large amounts of fall.

HIWASSEE RIVER DRAINAGE BASIN

DESCRIPTION OF BASIN

Hiwassee River rises in the northern part of Georgia and flows into Tennessee River about 30 miles above Chattanooga, Tenn. Its principal tributaries are the Toccoa (Ocoee) and the Nottely. The United States Geological Survey has maintained, among others in this basin, the following stations: On Toccoa River near Blue Ridge, Ga.; on the Ocoee River at McCays, Tenn.; on Nottely River at Ranger, N. C., and on Hiwassee River at Murphy, N. C. The stations in North Carolina and Tennessee, mentioned above, are included here, as the data regarding the rivers in this basin will be valuable in estimating the flow of these streams at points above.

STREAM FLOW

HIWASSEE RIVER AT MURPHY, N. C.

This station was established July 26, 1896, by E. W. Myers. It is located at the highway bridge in Murphy, N. C., about 80 feet above the Atlanta, Knoxville and Northern Railroad bridge and one-half mile above the mouth of Valley River.

The channel is straight for about 500 feet above and below the station. The right bank is high and rocky and will not overflow. The left bank will overflow for a short distance around the abutment. The bed of the stream is rocky and rough, and makes soundings uncertain. The bed is permanent and the flow is rapid. Discharge measurements are made from the sidewalk on the upstream side of the single-span highway bridge. The bridge is 195 feet long, supported by stone abutments. The initial point for soundings is the end of the iron hand rail on the right bank, upstream side of the bridge.

A standard chain gage is fastened to the top of the downstream end of the first iron floor beam from the right bank in the space between the bridge floor and the lower chords; length of chain, 27.05 feet. It is read once each day by William Mingus. Bench marks were established as follows: (1) The downstream side of the

WATER POWERS OF GEORGIA

top of the stone pier at the right bank; elevation, 22.55 feet. (2)
 The top of the downstream end of the first iron floor beam from
 the right end of the bridge; elevation, 25.05 feet.

Discharge measurements of Hiwassee River at Murphy, N. C.

Date	Gage height	Dis-charge	Date	Gage height	Dis-charge
1896			1901		
June 23.....	<i>Feet</i> 3.82	<i>Sec.-ft.</i> 366	September 20.....	<i>Feet</i> 6.02	<i>Sec.-ft.</i> 1,324
August 10.....	3.95	382	September 20.....	6.02	1,257
September 22.....	4.01	517	September 20.....	6.02	1,166
1897			September 20.....	6.02	1,246
August 20.....	5.33	528	September 20.....	6.03	1,182
October 14.....	4.76	267	November 8.....	5.25	462
October 29.....	4.71	253	December 13.....	5.32	480
1898			1902		
January 21.....	6.05	1,170	August 12.....	4.80	213
September 8.....	6.80	1,620	August 23.....	4.80	186
1899			September 18.....	4.80	198
February 28.....	7.50	2,150	September 18.....	4.80	216
June 23.....	5.17	400	October 24.....	4.87	260
June 23.....	5.30	436	October 24.....	4.90	271
September 28.....	4.93	304	1903		
September 28.....	5.00	345	March 6.....	6.60	1,747
December 7.....	5.10	317	March 28.....	6.75	2,226
December 29.....	5.50	613	April 28.....	6.04	1,302
1900			July 29.....	5.16	435
February 11.....	6.10	1,534	August 17.....	5.19	437
February 14.....	7.95	4,567	August 27.....	5.00	315
April 29.....	6.10	1,466	October 2.....	4.88	217
May 26.....	5.52	755	October 3.....	4.88	220
June 29.....	7.10	3,405	December 3.....	4.88	263
July 8.....	5.30	1,155	1904		
September 9.....	5.05	345	February 22.....	6.63	1,993
November 18.....	5.20	443	February 24.....	6.00	1,133
December 13.....	5.53	762	March 1.....	5.54	661
December 13.....	5.45	698	March 2.....	5.54	644
December 28.....	5.70	865	May 12.....	5.66	754
1901			June 29.....	5.53	639
February 24.....	5.70	725	August 29.....	5.10	344
April 17.....	6.15	1,522	October 6.....	4.80	183
May 12.....	6.40	2,107	December 15.....	5.02	287
July 12.....	5.45	665	1905		
August 16.....	3.00	4,974	April 15.....	5.84	896
September 20.....	6.02	1,106	June 13.....	5.38	517
			October 13.....	5.16	421

Daily gage height, in feet, of Hiwassee River at Murphy, N. C.

Day	July	Aug.	Sept.	Oct.	Nov.	Dec.	Day	July	Aug.	Sept.	Oct.	Nov.	Dec.
1896							1896						
1.....	3.72	4.02	3.65	3.74	3.66	5.2	17.....	4.48	3.78	3.6	3.65	4.5	4.05
2.....	3.7	4.02	3.61	3.63	3.7	4.7	18.....	4.54	3.74	3.6	3.56	3.95	4.0
3.....	3.75	4.11	3.62	3.65	3.72	4.52	19.....	4.35	3.7	3.53	3.5	3.91	4.0
4.....	4.0	3.95	3.61	3.60	4.9	4.52	20.....	4.28	3.63	3.56	3.6	3.9	4.0
5.....	3.9	3.9	3.61	3.62	4.1	4.2	21.....	4.32	3.7	3.56	3.6	3.9	4.0
6.....	4.62	3.9	3.9	3.55	3.9	4.2	22.....	4.6	3.7	3.62	3.56	3.85	4.0
7.....	4.98	3.95	3.66	3.6	3.9	4.15	23.....	5.1	3.65	3.85	3.6	3.8	3.95
8.....	6.72	3.9	3.62	3.51	3.9	4.1	24.....	4.61	3.9	3.6	3.9	3.8	3.95
9.....	6.95	3.86	3.6	3.6	3.92	4.3	25.....	4.4	3.8	3.6	3.7	3.8	3.95
10.....	5.24	4.0	3.6	3.65	3.8	4.1	26.....	4.3	3.72	3.6	3.62	3.84	3.9
11.....	4.75	3.9	3.6	3.65	3.76	4.1	27.....	4.3	3.72	3.6	3.62	4.0	3.9
12.....	4.82	3.81	3.67	3.65	7.53	4.1	28.....	4.25	3.7	3.65	3.65	4.0	3.9
13.....	4.77	3.81	3.56	3.72	5.4	4.05	29.....	4.12	3.7	3.6	3.74	5.03	3.9
14.....	4.65	3.72	3.58	3.65	4.53	4.02	30.....	4.01	3.65	4.2	3.8	6.1	3.9
15.....	4.42	3.75	3.8	3.65	4.3	4.1	31.....	4.02	3.65	3.82	3.9
16.....	4.55	3.92	3.62	3.6	4.12	4.05							

HIWASSEE DRAINAGE BASIN, STREAM FLOW

Daily gage height, in feet, of Hiwassee River at Murphy, N. C.—Continued.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1897												
1.....	3.9	4.8	4.6	5.4	4.8	4.16	3.9	4.2			5.0	5.02
2.....	3.9	5.5	4.5	5.5	4.7	4.15	3.9	4.32			5.4	5.0
3.....	3.9	4.9	4.55	5.38	4.65	4.12	3.9	4.2			5.1	5.1
4.....	3.9	4.62	4.7	6.26	4.6	4.1	3.9	4.1			5.02	5.45
5.....	4.12	4.6	4.6	8.2	4.55	4.3	4.15	4.35			5.0	6.1
6.....	4.02	5.15	9.2	6.12	4.52	4.12	4.0	4.2			5.0	5.5
7.....	4.0	5.4	6.5	5.75	4.5	4.1	4.02	4.2			4.95	5.3
8.....	4.0	5.12	5.65	5.5	4.5	4.1	4.1				5.0	5.2
9.....	3.92	5.1	5.4	6.1	4.5	4.22	4.1				4.98	5.12
10.....	3.92	4.85	5.62	5.35	4.45	4.1	4.25				5.0	5.1
11.....	4.0	4.85	5.5	5.3	4.52	4.02	4.15				5.0	5.1
12.....	3.9	4.82	9.9	5.15	4.4	4.05	4.0				4.95	5.0
13.....	3.92	4.82	6.85	5.05	5.0	4.05	3.98				4.95	5.02
14.....	4.4	4.12	6.7	5.05	4.3	4.0	3.9				5.0	6.2
15.....	4.6	4.7	6.12	5.5	4.6	4.0	3.85				5.0	5.55
16.....	4.15	4.6	7.65	5.05	4.5	4.1	3.9				5.0	5.3
17.....	4.55		5.0		4.5	4.08	4.5				4.95	5.28
18.....	4.4		6.0	4.9	4.42	4.1	4.05				4.95	5.2
19.....	4.4		7.05	4.8	4.4	4.2	5.72				4.95	5.4
20.....	5.1.		6.8	4.8	4.32	4.15	5.0			5.0	4.95	6.0
21.....	4.7	4.8	6.1	4.7	4.36	4.05	4.5			4.75	4.95	7.35
22.....	4.52	4.5	5.8	4.7	4.35	4.0	4.85			4.75	4.95	6.85
23.....	4.4	7.92	5.5	4.7	4.3	4.0	4.34			4.7	4.9	6.15
24.....	4.4	5.5	5.4	4.7	4.26	4.0	4.2			4.7	4.9	5.3
25.....	4.4	5.1	5.3	4.65	4.25	4.0	10.85			4.7	5.0	5.5
26.....	4.2	4.97	5.15	4.7	4.22	4.0	6.2			4.65	4.98	5.85
27.....	4.3	4.7	5.1	4.68	4.2	3.9	5.2			4.66	5.0	5.6
28.....	4.1	4.64	5.0	4.6	4.2	3.9	4.72			4.7	5.05	5.5
29.....	4.15		4.9	4.6	4.2	4.3	4.52			4.72	5.0	5.4
30.....	4.15		5.0	4.68	4.2	4.0	4.4			4.9	5.1	5.4
31.....	4.15		4.9		4.2		4.25			4.87		5.3
1898												
1.....	5.3	5.6	5.22	7.0	5.3	5.12	4.95	5.32	5.4	5.6	5.85	6.0
2.....	5.2	5.45	5.2	6.5	5.3	5.12	4.95	5.6	12.05	5.6	5.85	5.9
3.....	5.1	5.62	5.32	6.21	5.7	5.1	4.9	5.22	13.97	5.5	5.8	5.85
4.....	5.3	5.5	5.3	6.1	5.65	5.1	4.9	9.8	10.1	14.4	5.8	5.9
5.....	5.25	5.5	5.21	8.75	5.65	5.1	5.5	9.35	9.75	11.6	5.8	6.1
6.....	5.3	5.42	5.2	7.0	5.51	5.2	5.2	6.75	7.5	8.3	6.1	6.1
7.....	5.3	5.4	5.2	6.55	5.6	5.1	5.1	6.5	7.1	7.3	5.85	6.1
8.....	5.3	5.4	5.2	6.3	5.6	5.1	5.31	7.02	6.85	7.0	5.8	6.0
9.....	5.2	5.4	5.2	6.11	5.6	5.1	5.1	6.8	6.6	6.7	5.3	5.95
10.....	5.25	5.4	5.2	6.05	5.5	5.1	5.3	8.3	6.6	6.5	5.72	5.9
11.....	5.3	5.4	5.2	6.1	5.5	5.05	5.1	10.0	6.3	6.4	5.9	5.9
12.....	6.0	5.3	5.2	6.0	5.5	5.0	5.0	7.5	6.2	6.32	5.85	5.85
13.....	5.85	5.3	5.2	5.9	5.4	5.0	4.91	7.15	6.12	6.2	5.8	5.8
14.....	5.8	5.3	5.3	5.95	5.4	5.01	5.9	6.81	6.05	6.2	5.9	5.75
15.....	5.6	5.3	5.35	5.95	5.4	5.1	6.12	6.4	6.0	6.05	5.85	5.7
16.....	5.8	5.25	5.32	5.85	5.5	5.15	5.7	6.2	5.9	6.0	5.85	5.7
17.....	5.7	5.25	5.4	5.81	5.4	5.5	5.5	6.2	6.0	6.0	5.85	5.7
18.....	5.6	5.22	5.4	5.8	5.4	5.45	5.3	6.3	5.8	9.2	6.0	5.7
19.....	5.6	5.3	5.4	5.75	5.35	5.2	5.21	6.25	5.7	6.7	6.7	5.7
20.....	5.9	5.25	5.4	5.85	5.3	5.15	5.15	6.1	5.7	6.4	6.4	6.0
21.....	6.1	5.35	5.36	5.7	5.3	5.1	5.01	6.1	5.65	6.23	6.2	5.7
22.....	5.9	5.3	5.35	5.7	5.3	5.1	5.3	5.9	5.7	6.3	6.1	5.7
23.....	6.0	5.3	5.3	6.65	5.35	5.05	5.4	5.75	6.05	6.2	6.5	6.1
24.....	5.78	5.27	5.25	6.2	5.6	5.02	5.6	5.7	5.8	6.1	6.25	6.0
25.....	7.75	5.3	5.4	6.1	5.32	5.05	6.0	5.65	5.7	6.1	6.1	5.9
26.....	7.2	5.22	5.4	5.95	5.25	5.0	5.9	5.8	5.7	6.1	6.1	5.3
27.....	6.5	5.22	5.3	6.2	5.25	5.05	5.6	5.7	5.65	6.05	6.0	5.3
28.....	6.18	5.25	5.3	6.1	5.21	5.01	6.2	5.7	5.6	6.0	6.0	5.7
29.....	6.0		11.1	6.0	5.2	5.0	5.3	5.6	5.6	6.0	6.2	5.7
30.....	5.82		9.4	5.9	5.2	5.95	5.65	5.6	5.6	5.95	6.0	5.7
31.....	5.71		7.7		5.1		6.2	5.6		5.9		5.9

Daily gage height, in feet, of Hiwassee River at Murphy, N. C.—Continued.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1899												
1.....	5.8	5.6	6.9	6.8	5.85	5.3	(a)	5.3	5.4	4.9	4.85	5.1
2.....	5.7	5.7	6.6	6.6	5.82	5.3	(a)	5.2	5.25	4.8	4.9	5.35
3.....	5.7	5.7	6.7	6.55	5.8	5.3	(a)	5.2	5.5	4.85	4.9	5.1
4.....	5.65	14.0	6.82	7.2	5.8	5.25	(a)	5.15	5.3	4.75	4.9	5.1
5.....	5.6	9.6	7.4	6.55	6.1	5.25	(a)	5.12	5.2	4.8	4.9	5.1
6.....	5.7	9.45	6.75	6.55	5.8	5.25	(a)	5.2	5.1	4.9	4.9	5.02
7.....	6.3	9.9	6.5	6.5	5.85	5.1	(a)	5.2	5.1	4.9	4.9	5.0
8.....	6.0	7.85	6.4	6.7	5.7	5.1	5.2	5.2	5.15	5.7	4.9	5.1
9.....	5.9	7.2	6.4	6.6	5.7	5.2	5.1	5.12	5.05	5.15	4.9	5.05
10.....	5.8	6.75	6.3	6.5	5.7	5.15	5.1	5.15	5.0	5.0	4.9	5.1
11.....	5.8	6.6	6.2	6.4	5.62	5.1	5.05	5.15	5.2	5.02	4.9	5.1
12.....	5.8	6.55	6.1	6.3	5.62	5.82	5.0	5.1	5.1	5.0	4.85	9.1
13.....	5.7	6.3	6.1	6.2	5.6	5.3	5.0	5.1	5.0	4.9	4.85	6.3
14.....	5.7	6.4	6.75	6.2	5.55	5.5	5.0	5.05	5.0	4.8	4.9	5.82
15.....	5.75	6.4	10.8	6.1	5.6	5.35	5.0	5.2	5.0	5.0	4.9	5.7
16.....	5.75	6.3	8.75	6.1	5.5	5.25	5.0	5.32	4.9	5.0	4.9	5.5
17.....	5.75	6.25	7.5	6.05	5.5	5.3	5.1	5.2	5.0	5.0	4.9	5.4
18.....	5.7	6.25	7.1	6.0	5.5	5.2	5.3	5.1	5.0	4.95	4.9	5.4
19.....	5.7	6.0	18.4	6.0	5.6	5.2	5.2	5.0	5.0	5.1	4.85	5.3
20.....	5.7	6.1	8.7	6.0	5.5	5.15	5.1	5.0	5.1	5.0	4.85	5.5
21.....	5.7	6.1	7.6	6.0	5.45	5.1	5.3	5.0	5.0	5.0	4.9	5.4
22.....	5.6	6.1	7.2	5.9	5.4	5.1	5.3	5.0	5.0	4.9	4.9	5.35
23.....	5.6	6.0	8.15	5.9	5.4	5.1	5.3	5.0	5.0	4.9	5.4	5.3
24.....	5.52	5.92	7.0	5.9	5.42	4.85	5.2	5.0	5.0	4.9	5.12	6.3
25.....	5.65	6.1	6.8	6.7	5.4	4.95	5.2	5.1	5.0	4.9	5.1	5.7
26.....	5.6	6.0	6.6	6.1	5.4	5.05	6.8	5.05	5.0	4.9	5.75	5.6
27.....	5.6	9.1	6.52	6.0	5.35	5.0	5.75	5.25	5.02	4.9	5.4	5.5
28.....	5.6	7.3	6.5	6.0	5.35	5.0	5.9	5.45	5.0	5.0	5.3	5.55
29.....	5.5	6.9	5.9	5.32	5.0	5.1	5.0	5.1	5.2	5.5
30.....	5.5	6.7	5.9	5.32	5.0	5.1	4.88	4.9	5.1	5.35
31.....	5.9	7.8	5.3	5.7	5.0	5.4
1900												
1.....	5.5	5.12	7.0	5.9	6.1	5.4	6.8	5.8	5.25	5.0	5.2	5.4
2.....	5.2	5.3	6.5	5.9	6.0	5.4	6.6	5.4	5.2	4.9	5.25	5.45
3.....	5.51	5.35	6.25	5.9	6.0	5.6	7.0	5.4	5.15	5.0	6.2	5.4
4.....	5.3	5.4	6.1	6.7	5.9	5.8	6.4	5.4	5.1	5.1	5.6	7.2
5.....	5.3	5.6	6.0	6.1	5.9	5.5	6.2	5.3	5.2	5.1	5.4	6.4
6.....	5.2	5.4	6.0	6.05	5.8	6.1	6.0	5.3	5.15	5.05	5.35	6.0
7.....	5.2	5.4	7.0	6.0	5.7	6.0	5.9	5.3	5.1	5.0	5.35	5.8
8.....	5.2	5.4	7.5	5.9	5.7	6.1	5.8	5.2	5.05	5.3	5.3	5.75
9.....	5.2	6.72	7.4	5.85	5.7	6.1	6.2	5.2	5.05	5.1	5.25	5.6
10.....	5.2	6.02	6.9	5.8	5.7	6.3	5.7	5.2	5.0	5.05	5.25	5.6
11.....	5.3	6.1	6.6	6.1	5.7	6.1	5.7	5.2	5.0	5.0	5.2	5.5
12.....	6.3	6.1	6.4	6.3	5.65	6.1	5.8	5.2	5.0	4.9	5.25	5.5
13.....	5.8	12.6	6.3	6.1	5.6	6.6	5.8	5.2	5.0	5.3	5.2	5.45
14.....	5.6	7.7	6.12	6.0	5.6	6.1	5.7	5.2	5.05	5.1	5.25	5.45
15.....	5.6	7.15	6.05	6.0	5.6	5.8	5.6	5.2	7.0	5.0	5.2	5.4
16.....	5.5	6.5	6.3	5.9	5.5	5.8	5.6	5.1	6.45	5.0	5.15	5.4
17.....	5.4	6.2	6.0	5.8	5.4	6.2	5.6	5.3	5.7	4.9	5.2	5.4
18.....	5.45	5.9	6.0	6.2	5.5	6.0	5.6	5.2	5.45	4.8	5.15	5.3
19.....	5.9	5.9	6.85	6.7	5.7	6.3	5.5	5.1	5.35	5.0	5.2	5.3
20.....	6.6	5.8	7.4	6.4	5.5	6.1	5.5	5.1	5.35	4.9	5.15	5.8
21.....	6.2	6.0	6.9	7.1	5.4	5.9	5.5	5.1	5.25	4.9	5.2	6.7
22.....	5.9	6.4	6.6	6.8	5.4	5.8	5.6	5.1	5.0	5.0	5.3	5.9
23.....	5.8	6.15	6.4	6.7	5.4	6.3	5.7	5.3	5.4	4.9	5.2	5.8
24.....	5.65	6.0	6.35	6.5	5.6	6.6	5.6	5.9	5.2	7.1	5.15	6.0
25.....	5.6	6.0	6.4	6.55	5.5	6.5	5.4	5.3	5.2	6.0	5.3	5.8
26.....	5.6	6.0	6.4	6.55	5.6	7.0	5.5	5.4	5.2	5.7	6.7	5.7
27.....	5.5	5.9	6.3	6.3	5.5	7.2	5.7	5.2	5.15	5.6	6.0	5.65
28.....	5.4	5.85	6.3	6.2	5.5	7.1	5.9	5.15	5.15	5.4	5.7	5.6
29.....	5.4	6.05	6.2	5.4	7.0	5.7	5.15	5.1	5.3	5.6	5.7
30.....	5.4	6.1	6.1	5.4	6.8	5.8	5.15	5.05	5.2	5.5
31.....	5.5	6.0	5.4	5.6	5.15	5.25

a No readings July 1 to 8; gage broken.

HIWASSEE DRAINAGE BASIN, STREAM FLOW

Daily gage height, in feet, of Hiwassee River at Murphy, N. C.—Continued.

Day	Jan.	Feb.	Mar.	April	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1901												
1.....	6.0	6.05	5.6	6.35	6.15	6.35	6.0	5.3	6.7	5.6	5.25	5.2
2.....	5.9	5.95	5.6	7.65	6.1	6.2	5.9	5.25	6.4	5.6	5.25	5.2
3.....	5.3	5.9	5.55	7.6	6.05	6.1	5.65	5.2	6.25	5.6	5.25	5.3
4.....	5.7	7.55	5.55	7.1	6.0	6.05	5.6	5.2	6.2	5.5	5.3	5.35
5.....	5.6	6.75	5.7	6.75	6.0	6.0	5.55	5.2	6.15	5.5	5.3	5.2
6.....	5.6	6.4	5.6	6.75	6.05	5.95	5.7	7.65	6.05	5.5	5.3	5.25
7.....	5.6	6.25	6.1	6.5	5.95	6.1	5.55	7.0	6.0	5.45	5.25	5.2
8.....	5.5	6.15	5.55	6.4	5.85	5.9	5.75	6.05	5.9	5.4	5.25	5.25
9.....	5.5	6.95	5.55	6.25	5.75	5.85	5.55	5.75	5.85	5.45	5.25	5.25
10.....	5.5	5.6	5.6	6.2	5.85	5.3	5.5	5.6	5.8	5.4	5.25	6.15
11.....	5.8	6.4	6.5	6.1	5.8	5.8	5.45	5.85	6.0	5.4	5.25	5.55
12.....	9.2	6.3	6.1	6.1	5.75	5.95	5.45	6.55	5.8	5.4	5.4	5.4
13.....	7.5	6.25	5.95	6.15	5.75	5.85	5.4	5.75	6.0	6.2	5.4	5.4
14.....	6.35	6.15	5.85	6.55	5.7	6.5	5.4	7.95	5.8	5.5	5.3	6.3
15.....	6.5	6.05	5.75	6.35	5.65	6.5	5.45	7.3	5.7	5.45	5.25	9.1
16.....	6.3	6.0	5.75	6.2	5.65	6.35	5.8	7.9	5.9	5.4	5.2	6.8
17.....	6.2	5.9	5.7	6.15	5.65	6.3	5.4	8.15	7.2	5.4	5.2	6.7
18.....	6.1	5.85	5.65	6.1	5.6	6.1	5.4	8.45	6.75	5.4	5.25	6.0
19.....	5.9	5.85	5.6	6.55	6.7	6.0	7.1	7.35	6.2	5.4	5.25	5.9
20.....	5.85	5.3	5.6	11.4	7.2	6.05	5.65	7.05	6.0	5.35	5.25	5.8
21.....	5.85	5.75	5.95	7.9	7.5	5.85	5.45	8.15	5.9	5.35	5.2	5.7
22.....	5.9	5.75	5.75	7.25	10.6	5.8	5.65	8.0	5.8	5.35	5.2	5.75
23.....	5.3	5.75	5.65	6.95	7.75	5.75	5.4	12.7	5.75	5.35	5.25	5.7
24.....	6.05	5.7	5.95	6.7	7.1	5.7	5.35	8.25	5.7	5.3	5.45	5.9
25.....	5.9	6.05	5.8	6.65	6.35	5.7	5.45	7.35	5.65	5.3	5.3	5.85
26.....	5.85	5.7	10.8	6.5	6.55	6.1	5.3	6.95	5.65	5.2	5.2	5.85
27.....	5.9	5.85	8.2	6.4	6.5	5.7	5.65	6.75	5.6	5.3	5.2	7.5
28.....	6.05	5.6	7.2	6.35	6.35	6.2	5.3	6.85	5.6	5.3	5.15	6.55
29.....	5.95	6.8	6.2	6.85	6.05	5.5	7.0	5.75	5.3	5.15	13.3
30.....	6.0	6.6	6.15	6.2	5.75	5.35	6.8	5.6	5.3	5.2	9.1
31.....	6.2	6.5	6.75	5.5	6.7	5.25	7.5
1902												
1.....	6.95	7.8	8.5	6.6	5.7	5.3	5.2	4.9	4.75	5.25	4.9	5.65
2.....	6.6	9.1	7.5	6.5	5.8	5.3	5.2	4.9	4.8	5.15	4.9	5.5
3.....	6.15	7.5	7.05	6.35	5.7	5.3	5.15	5.2	4.8	5.05	4.9	6.65
4.....	6.3	6.9	6.8	6.3	5.65	5.25	5.15	4.95	5.15	5.0	4.9	5.95
5.....	6.15	6.5	7.15	6.25	5.7	5.25	5.15	4.9	4.95	5.0	4.9	5.5
6.....	6.1	6.35	6.8	6.15	5.7	5.2	5.15	4.85	4.85	5.1	5.9	5.65
7.....	6.0	6.25	6.55	6.15	5.6	5.2	5.3	4.85	4.8	5.0	5.2	5.5
8.....	5.95	6.15	6.45	6.65	5.6	5.55	5.15	4.85	4.8	5.0	5.1	5.45
9.....	5.9	6.5	6.75	6.35	5.6	5.55	5.1	4.8	4.8	5.0	5.0	5.4
10.....	5.85	6.0	6.55	6.25	5.5	5.55	5.1	4.8	5.35	4.95	5.05	5.35
11.....	5.85	5.9	6.5	6.15	5.5	5.5	5.1	4.85	4.95	5.0	5.0	5.35
12.....	5.8	5.9	6.4	6.1	5.55	5.5	5.5	4.8	4.9	5.45	5.0	5.3
13.....	5.75	5.85	6.65	6.05	5.55	5.5	5.4	4.8	5.05	5.15	5.0	5.35
14.....	5.7	5.8	6.45	6.0	5.55	5.45	5.25	4.8	5.05	5.45	5.0	5.25
15.....	5.7	5.85	6.4	6.0	5.5	5.5	5.3	4.85	4.9	5.15	4.95	5.25
16.....	5.7	5.9	6.45	6.0	5.55	5.5	5.2	4.8	4.9	5.1	4.95	5.75
17.....	5.65	5.85	6.9	5.95	5.5	5.45	5.15	4.85	4.85	5.05	5.0	6.15
18.....	5.65	5.75	6.6	6.0	5.55	5.4	5.1	4.8	4.85	5.0	5.5	5.9
19.....	5.9	5.75	6.45	5.95	5.5	5.4	5.1	4.8	4.95	4.95	5.15	5.65
20.....	5.7	5.3	6.35	5.9	5.4	5.4	5.05	4.8	5.35	4.95	5.05	5.5
21.....	5.65	6.05	6.3	5.85	5.4	5.35	5.05	4.8	5.05	4.95	5.05	5.3
22.....	5.75	6.25	6.25	5.8	5.35	5.4	5.05	4.75	5.0	4.95	5.0	6.3
23.....	5.65	6.05	6.2	5.8	5.45	5.3	5.05	4.75	4.95	4.95	5.05	5.9
24.....	5.65	6.0	6.15	5.75	5.4	5.3	5.0	4.75	4.9	4.95	5.0	5.75
25.....	5.6	6.05	6.1	5.75	5.5	5.25	5.0	4.75	5.45	4.9	5.5	5.7
26.....	5.6	6.05	6.05	5.75	5.3	5.5	4.95	4.75	5.15	4.9	6.0	5.6
27.....	5.65	6.0	6.1	5.75	5.3	5.55	4.9	4.85	5.35	4.95	5.7	5.4
28.....	5.95	14.15	6.1	5.75	5.25	5.45	4.9	4.95	5.45	4.95	5.5	5.45
29.....	6.05	10.9	5.7	5.25	5.3	4.9	4.9	5.15	4.9	5.4	5.4
30.....	6.1	7.5	5.9	5.3	5.25	4.9	4.85	5.05	4.9	5.4	5.75
31.....	7.2	6.9	5.85	4.9	4.8	4.9	5.5

WATER POWERS OF GEORGIA

Daily gage height, in feet, of Hiwassee River at Murphy, N. C.—Continued.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1908												
1.....	5.05	5.4	8.55	7.1	6.0	6.2	5.4	5.25	4.95	4.85	4.95	4.9
2.....	5.05	5.4	7.35	6.85	5.95	6.25	5.5	6.5	4.95	4.85	4.9	4.9
3.....	5.65	5.5	6.95	6.7	5.9	5.9	5.45	5.7	5.0	4.85	4.9	4.9
4.....	5.85	6.6	6.75	6.95	6.3	5.75	5.4	5.3	5.0	4.9	4.95	4.9
5.....	5.8	6.9	6.55	6.55	5.85	6.4	5.35	6.15	5.0	4.85	5.4	4.9
6.....	5.7	6.25	6.6	6.45	5.85	6.75	5.45	5.4	4.95	4.85	5.05	4.9
7.....	5.6	6.25	6.45	6.4	5.8	6.35	5.65	5.3	4.9	4.85	4.95	4.85
8.....	5.6	7.6	7.95	6.7	5.8	6.5	5.45	5.2	4.9	5.9	4.95	4.85
9.....	5.5	6.9	7.75	6.8	5.75	5.9	5.4	5.15	5.05	5.05	4.9	4.85
10.....	5.5	6.45	7.35	6.55	5.75	5.85	5.65	5.1	4.95	4.9	4.9	4.9
11.....	5.55	7.2	9.95	6.45	5.7	6.3	5.5	5.2	4.9	4.85	4.9	4.9
12.....	5.95	7.35	8.2	6.3	5.7	5.9	6.15	5.1	4.9	4.85	5.15	4.9
13.....	5.7	6.75	7.5	6.5	5.75	5.75	6.1	5.0	4.9	4.85	5.0	4.95
14.....	5.7	6.45	7.1	7.65	5.7	5.65	6.1	5.0	4.9	4.85	4.95	5.05
15.....	5.6	6.25	6.85	7.25	5.7	5.65	5.7	5.1	5.15	4.85	5.0	4.95
16.....	5.55	6.2	6.7	6.9	5.65	5.6	5.55	5.15	5.45	4.85	4.95	4.9
17.....	5.6	9.15	6.55	6.7	5.6	5.55	5.75	5.2	5.1	4.95	5.0	4.85
18.....	5.9	7.3	6.45	6.55	5.6	5.5	5.5	5.2	5.05	5.05	5.45	4.85
19.....	5.4	6.75	6.35	6.45	5.55	5.5	5.45	5.1	4.95	4.9	5.0	4.85
20.....	5.35	6.5	6.25	6.4	5.55	5.5	5.45	5.2	4.95	4.9	5.0	5.05
21.....	5.4	6.35	6.9	6.45	6.1	5.65	5.35	5.1	4.95	4.9	5.0	5.25
22.....	5.35	6.2	7.1	6.25	5.55	5.45	5.35	5.1	4.95	4.85	4.95	5.0
23.....	5.35	6.05	11.8	6.2	5.5	5.5	5.35	5.05	4.9	4.85	4.95	5.0
24.....	5.35	6.0	8.75	6.15	5.5	5.45	5.3	5.05	4.9	4.9	4.95	4.95
25.....	5.4	5.95	7.65	6.1	5.45	5.4	5.25	5.05	4.9	4.85	4.95	4.95
26.....	5.35	5.85	7.15	6.25	5.45	5.45	5.25	5.0	4.85	4.85	4.95	5.0
27.....	5.5	5.8	6.9	6.1	5.45	5.75	5.25	5.0	4.9	4.85	4.95	4.95
28.....	5.35	12.0	6.75	6.05	5.45	5.85	5.25	5.0	4.9	4.85	4.9	5.05
29.....	5.55	6.65	6.0	5.95	5.55	5.3	4.95	4.9	4.85	4.9	5.0
30.....	5.45	7.85	5.95	5.6	5.45	5.35	4.95	4.85	4.9	4.9	4.95
31.....	5.4	7.55	5.8	5.4	4.95	4.95	4.95
1904												
1.....	4.9	5.15	5.5	5.75	5.45	5.5	5.25	5.5	5.2	4.8	4.75	5.15
2.....	4.9	5.1	5.5	5.7	5.4	5.35	5.1	5.2	5.1	4.8	4.75	5.0
3.....	5.05	5.25	5.55	5.6	5.45	5.3	5.1	5.05	5.05	4.8	4.8	5.55
4.....	4.95	5.1	5.55	5.55	5.45	5.25	5.05	5.05	5.3	4.8	5.0	5.15
5.....	4.9	5.1	5.45	5.55	5.5	5.2	5.45	5.05	5.55	4.8	4.95	5.15
6.....	4.85	5.1	5.4	5.5	5.45	5.15	5.1	5.65	5.15	4.8	4.9	5.95
7.....	5.0	5.15	7.8	5.95	5.4	6.35	5.1	5.15	5.1	4.8	4.8	5.4
8.....	4.85	6.0	6.6	6.5	5.55	5.65	5.05	5.85	5.05	4.8	4.8	5.15
9.....	4.9	5.5	6.15	5.95	5.55	5.35	6.15	5.45	5.0	4.75	4.8	5.1
10.....	4.9	5.45	5.9	6.05	6.05	5.25	5.25	5.25	5.0	4.75	4.8	5.15
11.....	4.95	5.4	6.0	5.95	5.8	5.25	5.1	5.65	5.0	4.75	4.8	5.15
12.....	5.05	5.35	5.75	5.8	5.7	5.35	5.1	5.45	4.95	4.75	4.8	5.0
13.....	5.05	5.25	5.7	5.7	5.6	5.2	5.25	5.5	4.95	4.75	5.0	5.05
14.....	5.1	5.2	6.25	5.65	5.55	5.15	5.1	5.25	4.95	4.75	5.0	5.05
15.....	5.0	5.6	6.0	5.6	5.55	5.15	5.0	7.25	4.95	4.75	5.0	5.0
16.....	5.0	5.4	5.75	5.65	5.45	5.1	5.0	5.45	4.9	4.75	4.9	5.0
17.....	5.7	5.3	5.7	5.55	5.45	5.1	5.35	5.25	4.9	4.75	4.8	5.05
18.....	5.35	5.25	5.65	5.55	5.45	5.1	5.35	5.15	4.9	4.75	4.8	5.05
19.....	5.2	5.25	5.6	5.5	5.4	5.1	5.0	5.1	4.85	4.75	4.85	5.05
20.....	5.15	6.05	5.5	5.45	5.35	5.65	4.95	5.45	4.85	4.75	4.85	5.0
21.....	5.1	5.7	5.5	5.6	5.35	5.3	4.95	5.2	4.95	4.75	4.8	4.95
22.....	5.2	6.55	6.5	5.45	5.3	5.2	5.2	5.1	4.9	4.75	4.9	4.95
23.....	6.3	6.4	7.4	5.4	5.3	5.15	5.05	5.1	4.9	4.7	4.9	4.95
24.....	5.7	6.0	7.35	5.4	5.3	5.1	5.05	5.5	4.85	4.75	4.95	5.0
25.....	5.45	5.75	6.5	5.4	5.25	5.05	5.15	5.35	4.85	4.75	4.85	5.25
26.....	5.35	5.6	6.85	5.4	5.25	5.25	5.0	5.1	4.85	4.75	4.85	5.15
27.....	5.25	5.6	6.35	5.75	5.25	5.5	4.95	5.6	4.85	4.75	4.85	5.1
28.....	5.2	6.5	6.1	5.0	5.2	5.1	4.95	6.3	4.85	4.8	4.8	6.45
29.....	5.2	5.45	6.0	5.55	5.2	5.35	5.05	5.15	4.85	4.8	4.8	5.65
30.....	5.05	5.9	5.5	5.2	5.3	5.2	5.1	4.85	4.8	5.25	5.4
31.....	5.20	5.8	6.1	4.95	5.1	4.75	5.3

Daily gage height, in feet, of Hiwassee River at Murphy, N. C.—Continued.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1905												
1.....	5.25	5.3	5.8	5.55	6.3	5.7	5.85	5.2	5.15	5.0	5.0	5.2
2.....	5.2	5.25	5.8	5.55	6.05	5.65	6.0	5.2	5.25	4.95	5.0	5.15
3.....	5.45	5.2	5.7	5.5	5.9	5.55	5.45	5.15	5.3	5.0	5.0	10.0
4.....	5.4	5.2	5.6	5.5	5.9	5.55	5.35	5.15	5.2	5.5	5.0	6.5
5.....	5.35	5.2	5.6	5.65	5.8	5.5	5.65	5.2	5.15	5.1	5.0	5.9
6.....	5.35	5.95	5.6	5.65	6.1	5.5	5.4	5.15	5.1	5.0	5.0	5.65
7.....	5.8	5.75	5.6	5.7	6.2	5.5	5.45	5.15	5.1	5.0	5.1	5.55
8.....	5.5	5.7	5.6	5.6	6.7	5.45	5.35	5.35	5.1	5.0	5.0	5.55
9.....	5.45	8.75	5.6	5.7	6.05	5.4	5.35	5.35	5.1	4.95	5.0	8.7
10.....	5.4	6.95	6.1	5.65	5.9	5.4	6.35	5.25	5.05	5.0	5.0	7.0
11.....	5.4	6.3	6.0	5.6	5.8	5.35	6.55	6.3	5.15	7.55	5.0	6.35
12.....	5.5	6.1	5.8	5.85	5.75	5.4	10.3	5.8	5.15	5.45	5.0	6.05
13.....	6.6	7.0	5.8	5.85	5.9	5.35	6.85	5.75	5.1	5.2	5.0	5.85
14.....	6.55	6.3	5.7	5.75	5.7	5.4	6.15	6.3	5.1	5.1	5.0	5.75
15.....	6.6	6.3	5.6	5.7	5.65	5.8	5.85	5.9	5.05	5.1	5.0	5.85
16.....	5.8	6.0	5.6	5.8	7.2	5.4	5.8	5.75	5.05	5.2	5.0	5.8
17.....	5.65	5.9	5.6	5.7	6.45	5.5	5.65	5.6	5.05	5.1	5.0	5.7
18.....	5.6	5.8	5.6	5.65	6.1	5.4	5.55	5.5	5.0	5.05	5.0	5.85
19.....	5.5	5.7	5.55	5.6	5.95	5.6	5.6	5.45	5.0	5.05	5.0	5.8
20.....	5.6	6.2	5.65	5.55	5.85	5.5	5.5	5.4	5.0	5.05	5.35	5.85
21.....	5.45	8.2	7.0	5.55	5.8	5.5	5.4	5.35	5.0	5.05	5.15	6.6
22.....	5.4	7.2	6.25	5.65	5.85	5.8	5.5	5.3	5.0	5.0	5.1	6.2
23.....	5.35	6.6	6.05	5.5	6.45	6.75	5.4	5.25	5.0	5.0	5.05	6.15
24.....	5.35	6.4	5.9	5.5	6.95	5.55	5.35	6.5	4.95	5.0	5.0	6.4
25.....	5.3	6.2	5.85	5.45	6.35	5.55	5.4	5.5	4.95	5.0	5.15	6.1
26.....	5.25	6.1	5.75	5.5	6.2	5.35	5.3	5.6	4.95	5.3	5.2	5.95
27.....	5.25	6.0	5.7	5.9	6.1	5.35	5.8	5.35	4.95	5.15	5.1	5.8
28.....	5.2	5.9	5.65	5.8	5.95	5.45	5.35	5.3	4.95	5.1	5.1	5.75
29.....	5.15	5.65	5.7	5.85	5.4	5.45	5.25	4.95	5.05	5.1	5.9
30.....	5.3	5.65	6.95	5.8	5.55	5.3	5.2	4.95	5.05	5.2	5.7
31.....	5.2	5.6	5.95	5.25	5.2	5.0	5.85

Rating tables for Hiwassee River at Murphy, N. C.

OCTOBER 20, 1897, TO DECEMBER 31, 1898, AND JANUARY 1 TO DECEMBER 31, 1901.^a

Gage height	Dis-charge						
Feet	Sec.-ft.	Feet	Sec.-ft.	Feet	Sec.-ft.	Feet	Sec.-ft.
4.70	220	4.90	300	5.00	340	5.10	390
4.80	260						

JANUARY 1 TO DECEMBER 31, 1899.^b

4.70	252	5.70	884	7.40	3,660	13.00	13,180
4.80	230	5.80	1,016	7.60	4,000	14.00	14,880
4.90	310	5.90	1,148	7.80	4,340	15.00	16,580
5.00	340	6.00	1,280	8.00	4,680	16.00	18,280
5.10	396	6.20	1,620	8.50	5,530	17.00	19,980
5.20	452	6.40	1,960	9.00	6,380	18.00	21,680
5.30	508	6.60	2,300	9.50	7,230	19.00	23,380
5.40	564	6.80	2,640	10.00	8,080		
5.50	620	7.00	2,980	11.00	9,780		
5.60	752	7.20	3,320	12.00	11,480		

^a Above gage height 5.10 feet use the 1902 rating table.

^b Above gage height 6.0 feet the rating curve is a tangent, the difference being 170 per tenth.

WATER POWERS OF GEORGIA

Rating tables for Hiwassee River at Murphy, N. C.—Continued.

JANUARY 1 TO DECEMBER 31, 1900.^a

Gage height	Dis-charge						
<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>
4.80	310	5.60	861	6.40	2,025	7.40	3,775
4.90	362	5.70	977	6.50	2,200	7.60	4,125
5.00	415	5.80	1,093	6.60	2,375	7.80	4,475
5.10	481	5.90	1,209	6.70	2,550	8.00	4,825
5.20	547	6.00	1,325	6.80	2,725	8.50	5,700
5.30	613	6.10	1,500	6.90	2,900		
5.40	679	6.20	1,675	7.00	3,075		
5.50	745	6.30	1,850	7.20	3,425		

JANUARY 1, 1902, TO DECEMBER 31, 1903.^b

4.80	205	5.90	1,070	7.00	3,000	8.50	5,700
4.90	265	6.00	1,200	7.10	3,180	9.00	6,600
5.00	325	6.10	1,330	7.20	3,360	9.50	7,500
5.10	385	6.20	1,560	7.30	3,540	10.00	8,400
5.20	450	6.30	1,740	7.40	3,720	11.00	10,200
5.30	520	6.40	1,920	7.50	3,900	12.00	12,000
5.40	590	6.50	2,100	7.60	4,080	13.00	13,800
5.50	670	6.60	2,280	7.70	4,260	14.00	15,600
5.60	750	6.70	2,460	7.80	4,440		
5.70	845	6.80	2,640	7.90	4,620		
5.80	940	6.90	2,820	8.00	4,800		

JANUARY 1, 1904, TO DECEMBER 31, 1905.^c

4.70	150	5.60	710	6.50	1,850	7.40	3,540
4.80	190	5.70	800	6.60	2,020	7.50	3,750
4.90	235	5.80	900	6.70	2,190	7.60	3,960
5.00	285	5.90	1,010	6.80	2,370	7.80	4,400
5.10	340	6.00	1,130	6.90	2,550	8.00	4,840
5.20	400	6.10	1,260	7.00	2,740	9.00	7,040
5.30	470	6.20	1,400	7.10	2,930	10.00	9,240
5.40	540	6.30	1,540	7.20	3,130		
5.50	620	6.40	1,690	7.30	3,330		

^a Above gage height 8.5 feet use the rating table for 1901-1903.^b Above gage height 6.0 feet the rating curve is a tangent, the difference being 180 per tenth.^c This table is based on 62 discharge measurements made during 1900-1905. It is well defined between gage heights 4.8 feet and 6.8 feet. The table has been extended beyond these limits. Above 7.6 feet the rating curve is a tangent, the difference being 220 per tenth.

Estimated monthly discharge of Hiwassee River at Murphy, N. C.


[Drainage area, 410 square miles.]

Month	Discharge in second-feet			Run-off	
	Maximum	Minimum	Mean	Sec.-ft. per sq. mile	Depth in inches
1897 ^a					
October 20-31.....	340	200	243	0.593	0.265
November.....	590	300	344	.839	.936
December.....	3,680	340	829	2.02	2.33
1898 ^a					
January.....	4,350	390	1,049	2.56	2.95
February.....	768	464	557	1.86	1.42
March.....	10,400	450	1,171	2.86	3.30
April.....	6,150	795	1,542	3.76	4.20
May.....	940	390	680	1.54	1.78
June.....	670	320	397	.968	1.08
July.....	1,560	300	667	1.63	1.88
August.....	8,400	750	2,306	5.62	6.48
September.....	15,500	590	2,659	6.49	7.24
October.....	16,300	670	2,677	6.53	7.53
November.....	2,460	860	1,240	3.02	3.37
December.....	1,380	840	1,081	2.51	2.89
The year.....	16,300	300	1,327	3.24	44.12

^a Revised estimates.



HURRICANE FALLS, TALLULAH FALLS, GEORGIA



HIWASSEE DRAINAGE BASIN, STREAM FLOW

393

Estimated monthly discharge of Hiwassee River at Murphy, N. C.—Continued.

Month	Discharge in second-feet			Run-off	
	Maximum	Minimum	Mean	Sec.-ft. per sq. mile	Depth in inches
1899					
January.....	1,790	620	878	2.14	2.47
February.....	14,880	720	3,088	7.53	7.84
March.....	22,360	1,450	3,715	9.06	10.45
April.....	3,320	1,120	1,744	4.25	4.74
May.....	1,450	460	719	1.75	2.02
June.....	970	295	440	1.07	1.19
July 8-28.....	2,640	340	556	1.36	1.06
August.....	840	340	404	.99	1.14
September.....	620	310	373	.91	1.01
October.....	840	265	339	.83	.95
November.....	905	295	356	.87	.97
December.....	6,550	340	800	1.95	2.25
1900 ^a					
January.....	2,375	535	858	2.09	2.41
February.....	13,080	475	1,829	4.46	4.64
March.....	3,950	1,325	2,141	5.22	6.01
April.....	3,250	1,030	1,717	4.19	4.67
May.....	1,500	670	877	2.14	2.47
June.....	3,425	670	1,702	4.15	4.63
July.....	3,075	670	1,170	2.85	3.29
August.....	1,165	475	588	1.43	1.65
September.....	3,075	415	664	1.62	1.81
October.....	3,250	310	596	1.45	1.67
November.....	2,550	505	725	1.77	1.98
December.....	3,425	600	1,043	2.54	2.93
The year.....	13,080	310	1,159	2.83	33.16
1901					
January.....	6,660	670	1,599	3.90	4.50
February.....	3,990	750	1,429	3.49	3.63
March.....	9,840	710	1,554	3.79	4.37
April.....	10,920	1,380	2,535	6.18	6.89
May.....	9,480	750	1,941	4.73	5.45
June.....	2,100	840	1,265	3.09	3.45
July.....	3,180	520	829	2.02	2.33
August.....	13,260	450	3,068	7.43	8.62
September.....	3,360	750	1,254	3.06	3.42
October.....	1,560	485	627	1.53	1.76
November.....	630	420	484	1.13	1.32
December.....	14,340	450	1,976	4.82	5.55
The year.....	14,340	420	1,547	3.77	51.29
1902					
January.....	3,360	750	1,203	2.93	3.38
February.....	15,370	892	2,259	5.51	5.74
March.....	10,020	1,290	2,532	6.30	7.26
April.....	2,370	845	1,331	3.25	3.63
May.....	940	485	677	1.65	1.90
June.....	710	450	537	1.43	1.6
July.....	670	265	363	.89	1.03
August.....	450	190	232	.57	.66
September.....	555	190	336	.82	.91
October.....	485	265	347	.85	.98
November.....	1,200	265	450	1.10	1.23
December.....	2,370	520	834	2.03	2.34
The year.....	15,370	190	934	2.28	30.66

^a Low-water estimates for 1900 are probably a few per cent. too high.

WATER POWERS OF GEORGIA

Estimated monthly discharge of Hiwassee River at Murphy, N. C.

Month	Discharge in second-feet			Run-off	
	Maximum	Minimum	Mean	Sec.-ft. per sq. mile	Depth in inches
1903					
January.....	1,135	355	698	1.70	1.96
February.....	12,000	590	2,498	6.09	6.34
March.....	11,640	1,650	3,708	9.04	10.42
April.....	4,170	1,135	2,143	5.23	5.83
May.....	1,740	630	890	2.17	2.50
June.....	2,550	590	1,053	2.57	2.87
July.....	1,470	485	695	1.70	1.96
August.....	2,100	295	500	1.22	1.41
September.....	680	235	304	.74	.83
October.....	1,070	235	280	.68	.78
November.....	680	265	320	.73	.87
December.....	485	235	290	.71	.82
The year.....	12,000	235	1,115	2.72	36.59
1904					
January.....	1,540	212	401	.978	1.13
February.....	1,935	340	671	1.64	1.77
March.....	4,400	540	1,303	3.17	3.66
April.....	1,850	540	777	1.90	2.12
May.....	1,260	400	605	1.43	1.71
June.....	2,460	312	532	1.30	1.45
July.....	1,330	260	380	.927	1.07
August.....	3,230	312	573	1.40	1.61
September.....	665	212	282	.683	.768
October.....	190	150	176	.429	.495
November.....	435	170	224	.546	.609
December.....	1,770	260	438	1.07	1.23
The year.....	4,400	150	530	1.29	17.62
1905					
January.....	2,020	370	695	1.70	1.96
February.....	6,600	400	1,602	3.91	4.07
March.....	2,740	665	907	2.21	2.55
April.....	2,645	580	815	1.99	2.22
May.....	3,130	755	1,232	3.13	3.61
June.....	2,280	470	664	1.62	1.81
July.....	10,500	435	1,102	2.69	3.10
August.....	1,850	370	647	1.53	1.82
September.....	470	260	307	.749	.836
October.....	3,855	260	449	1.10	1.27
November.....	505	235	316	.771	.860
December.....	9,550	370	1,518	3.70	4.27
The year.....	10,500	260	859	2.10	23.33

NOTTELY RIVER AT RANGER, N. C.

This station was established February 16, 1901, by O. P. Hall. It is located at the wooden wagon bridge one-half mile from the railroad station at Ranger, N. C., and one-fourth mile below the Atlanta, Knoxville and Northern Railroad bridge.

The bridge is at a flat bend in the river, the channel curving slightly above and below the station for 600 feet. The right bank is high, rocky, and somewhat wooded and will overflow around the end of the bridge for about 50 feet only. The left bank is low

and will overflow for a distance of 700 feet at a gage height of from 15 to 18 feet. The bed of the stream is of gravel and sand and probably shifts considerably. The current is somewhat broken and irregular, mostly because of the piers. There is a moderate velocity and a depth of from 2 to 5 feet at low stages. Discharge measurements are made from the wagon bridge, a wooden structure of 3 spans supported by 2 wooden piers and 2 stone abutments. The center span is 55 feet long, and the end spans are each 36 feet long. The floor of the bridge is about 20 feet above low water. The initial point for soundings is the inside face of the stone abutment on the right bank.

The gage is a vertical board in two sections, each 8 feet long, fastened to the left side of the first wooden pier from the right bank. The gage is read once each day by A. D. Kilpatrick. Bench marks were established as follows: (1) The heads of large wire nails driven into the top of the downstream end of the wooden cap on the left bent of the wooden pier nearest the right bank of the river; elevation, 20.05 feet. (2) A cut on a maple tree 18 inches in diameter, 25 feet from the upstream side of the bridge on the right bank, 25 feet from the edge of the water; elevation, 15.00 feet.

Discharge measurements of Nottely River at Ranger, N. C.

Date	Gage height	Dis-charge	Date	Gage height	Dis-charge
July 31.....	1900 Feet 2.40	Sec.-ft. 500	August 28.....	1903 Feet 2.88	Sec.-ft. 267
February 16.....	1901 4.20	649	October 2.....	2.62	183
April 4.....	5.40	970	December 5.....	2.68	204
June 28.....	4.12	612	March 1.....	1904 3.40	373
October 31.....	3.40	364	May 14.....	3.35	353
April 24.....	1902 4.20	598	August 30.....	2.75	222
August 14.....	2.70	213	October 7.....	2.30	121
November 21.....	2.75	213	December 16.....	2.58	184
March 19.....	1903 4.74	833	April 17.....	1905 3.48	421
May 15.....	3.95	551	June 20.....	3.51	399
July 30.....	3.42	372	June 21.....	3.98	538
			October 12.....	3.22	315

WATER POWERS OF GEORGIA

Daily gage height, in feet, of Nottely River at Ranger, N. C.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1901												
1.....			3.6	4.8	4.4	6.0	5.0	3.5	6.0	4.1	3.4	3.4
2.....			3.6	8.8	4.3	4.8	5.2	3.4	5.2	4.0	3.4	3.4
3.....			3.6	7.0	4.3	4.6	4.2	3.3	5.0	3.9	3.4	3.4
4.....			3.6	5.6	4.2	5.0	4.1	3.2	4.8	3.9	3.6	3.4
5.....			3.8	5.2	4.2	4.6	4.0	3.1	5.0	3.8	3.4	3.4
6.....			3.7	5.1	4.2	5.4	3.9	9.6	4.8	3.8	3.4	3.4
7.....			3.6	4.9	4.1	4.8	4.8	9.2	4.6	4.0	3.4	3.4
8.....			3.6	4.7	4.1	4.4	4.6	4.8	4.5	3.9	3.4	3.4
9.....			3.8	4.6	4.1	4.2	4.0	4.6	4.8	3.8	3.3	3.4
10.....			5.2	4.5	4.0	4.1	8.8	4.2	4.2	3.8	3.3	6.0
11.....			5.6	4.3	3.9	4.0	3.7	4.8	4.8	3.7	3.3	4.5
12.....			4.2	4.2	3.9	3.9	3.6	4.6	4.4	3.6	3.3	3.7
13.....			4.1	5.2	3.8	4.8	3.5	4.8	5.0	4.6	3.6	3.4
14.....			4.0	5.0	3.8	7.0	3.5	14.4	4.6	4.0	3.4	6.0
15.....			3.9	4.9	3.7	5.6	3.4	9.6	4.4	3.8	3.4	13.0
16.....		4.2	3.9	4.7	3.6	5.8	4.0	9.2	5.0	3.7	3.4	6.0
17.....		4.1	3.8	4.5	3.6	5.4	3.9	10.0	11.0	3.7	3.4	5.0
18.....		4.0	3.8	4.4	3.5	5.6	3.8	10.8	6.2	3.6	3.4	4.5
19.....		4.0	3.7	7.8	4.2	4.8	9.8	8.0	5.0	3.6	3.4	4.0
20.....		3.9	3.7	8.8	6.4	5.0	4.2	6.8	4.8	3.5	3.4	3.4
21.....		3.8	3.6	6.2	11.8	4.6	4.0	10.0	4.6	3.5	3.4	3.4
22.....		3.8	3.6	5.7	15.0	4.4	3.8	11.0	4.4	3.5	3.4	3.4
23.....		3.7	4.8	5.5	8.5	4.2	3.6	15.8	4.3	3.4	3.4	4.0
24.....		3.7	5.4	5.2	5.6	4.1	3.5	8.4	4.2	3.4	4.0	4.5
25.....		3.7	6.2	5.0	5.4	4.0	3.5	6.2	4.1	3.4	3.4	4.0
26.....		3.7	13.5	4.8	5.2	5.2	3.4	6.4	4.0	3.3	3.4	4.0
27.....		3.7	3.2	4.7	5.0	4.1	3.8	6.4	3.9	3.3	3.4	6.5
28.....		3.7	6.2	4.6	4.9	4.0	3.5	6.2	4.2	3.3	3.4	6.0
29.....			5.4	4.5	4.8	4.0	3.8	6.0	4.4	3.3	3.4	20.0
30.....			5.2	4.4	4.7	4.6	3.6	5.8	4.1	3.4	3.4	10.0
31.....			5.2		5.0		3.7	5.6		3.4		6.0
1902												
1.....	5.5	7.0	9.0	5.0	4.1	3.4	3.0	2.8	2.6	2.9	2.3	3.3
2.....	5.0	7.0	7.2	5.0	4.0	3.3	2.9	2.8	2.6	2.9	2.6	3.5
3.....	5.0	9.1	6.1	5.0	4.0	3.3	2.9	3.0	3.0	2.7	2.6	6.2
4.....	4.5	7.8	6.0	5.0	4.0	3.2	2.8	3.3	3.3	2.7	2.6	4.3
5.....	4.8	5.5	6.3	5.1	4.0	3.2	2.8	2.8	2.8	2.7	2.5	4.4
6.....	4.4	5.0	5.8	5.0	4.0	3.2	2.8	2.8	2.6	2.6	2.5	4.3
7.....	4.4	4.9	5.4	4.8	4.0	3.1	2.8	2.6	2.6	2.6	4.0	4.3
8.....	4.4	4.9	5.3	4.2	3.7	3.8	2.8	2.6	2.5	2.5	4.0	3.0
9.....	4.4	4.5	5.2	5.0	3.7	3.6	2.7	2.6	2.7	2.8	2.8	3.0
10.....	4.3	4.3	5.1	5.0	3.7	3.3	3.0	2.6	2.9	2.7	2.8	3.8
11.....	4.2	4.2	5.1	5.0	3.7	3.2	3.0	3.3	2.6	3.0	2.7	3.5
12.....	4.2	4.1	5.0	4.8	3.6	3.1	3.7	3.6	2.5	2.7	2.7	3.4
13.....	4.0	4.0	6.2	4.4	3.6	3.1	4.4	2.6	3.4	2.9	2.7	3.4
14.....	3.8	4.0	5.0	4.4	4.7	3.1	3.6	2.6	3.0	3.3	2.5	3.3
15.....	3.4	4.0	5.0	4.4	4.6	3.1	4.8	2.6	2.8	3.5	2.5	3.3
16.....	3.4	4.1	6.2	4.4	3.8	3.0	4.3	2.6	2.8	3.0	2.5	5.4
17.....	3.2	4.0	5.2	4.6	3.7	3.0	4.0	2.6	2.7	2.9	2.4	4.6
18.....	3.0	4.0	5.8	4.5	3.7	3.0	3.0	2.6	2.7	2.7	3.7	4.6
19.....	4.0	4.0	5.6	4.4	3.7	3.0	3.0	2.6	3.3	2.9	3.2	3.8
20.....	4.0	4.0	5.0	4.2	3.6	3.0	3.0	2.6	3.0	2.8	3.0	3.7
21.....	4.0	4.1	5.0	4.0	3.6	3.3	2.8	2.4	3.0	2.8	2.9	5.4
22.....	4.0	5.0	4.9	4.1	3.5	3.1	2.8	2.4	2.8	2.7	2.8	5.2
23.....	3.8	4.5	4.8	4.1	3.4	3.0	2.8	2.4	2.6	2.7	2.8	4.4
24.....	3.8	4.4	4.7	4.1	3.3	3.0	2.8	2.5	2.6	2.7	2.7	3.8
25.....	3.8	4.8	4.6	4.1	3.3	3.0	2.7	2.5	2.9	2.6	5.3	3.6
26.....	3.8	4.6	4.6	4.0	3.3	3.6	2.7	2.7	2.7	2.5	4.4	3.5
27.....	4.0	4.8	4.7	4.0	3.3	3.6	2.7	3.0	2.6	2.5	3.7	3.6
28.....	4.4	21.0	4.7	4.0	3.4	3.0	2.7	2.8	3.1	2.5	3.1	3.4
29.....	4.5		13.8	4.2	3.4	3.0	2.8	2.8	3.0	2.4	3.0	5.2
30.....	5.0		6.3	4.3	3.4	3.0	2.8	2.7	3.0	2.4	3.0	5.0
31.....	6.3		5.2		3.4		2.8	2.7		2.3		3.4

HIWASSEE DRAINAGE BASIN, STREAM FLOW

Daily gage height, in feet, of Nottely River at Ranger, N. C.—Continued.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1908												
1.....	3.2	3.2	8.8	6.4	4.2	6.0	3.8	7.0	2.8	2.6	2.7	2.5
2.....	3.2	3.5	6.3	6.1	4.4	7.0	3.7	4.4	2.8	2.5	2.7	2.5
3.....	3.0	3.6	5.8	5.7	4.3	6.0	3.6	3.7	2.7	2.5	2.8	2.5
4.....	4.0	9.6	5.4	5.8	4.2	6.4	3.9	3.6	2.7	2.5	2.9	2.5
5.....	3.8	6.0	5.0	5.3	4.2	7.4	3.6	3.5	2.7	2.6	2.9	2.6
6.....	3.7	4.8	4.9	5.2	4.1	7.0	3.6	3.4	2.9	2.6	2.9	2.6
7.....	3.7	6.0	5.0	5.1	4.0	7.5	3.7	3.3	2.8	2.6	2.9	2.6
8.....	3.6	7.6	5.2	5.0	4.0	5.0	3.7	3.2	2.8	4.0	2.9	2.5
9.....	3.6	5.4	6.7	7.0	4.0	5.0	3.8	3.0	3.2	2.8	2.8	2.5
10.....	3.8	4.9	6.2	6.5	4.9	4.9	4.0	3.1	2.9	2.7	2.8	2.5
11.....	3.3	7.6	11.0	5.3	3.9	5.2	3.9	3.4	2.8	2.7	2.7	2.5
12.....	4.8	7.0	7.6	5.0	3.9	5.2	5.0	3.3	2.8	2.7	3.0	2.5
13.....	3.8	5.4	6.2	8.6	3.9	5.0	5.3	3.2	2.7	2.6	2.8	2.5
14.....	3.8	5.0	5.0	3.0	3.9	4.0	5.0	4.0	2.7	2.6	2.7	2.5
15.....	3.7	4.7	5.4	6.6	3.9	4.0	4.0	4.0	2.7	2.3	2.6	2.5
16.....	3.6	4.7	5.1	5.8	3.9	4.0	3.9	3.7	2.7	2.8	2.6	2.5
17.....	3.5	3.0	5.1	5.7	3.8	3.8	4.4	3.3	4.0	2.9	2.8	2.6
18.....	3.6	5.6	5.0	5.5	3.8	3.8	3.7	3.4	3.2	2.8	4.0	2.6
19.....	3.5	5.2	4.9	5.4	3.8	3.8	3.6	3.4	2.9	2.7	3.0	2.7
20.....	3.4	5.0	4.7	5.2	3.8	3.7	4.7	3.3	2.8	2.7	2.8	3.5
21.....	3.4	4.7	7.0	5.0	4.0	3.7	4.0	3.0	2.9	2.7	2.8	3.4
22.....	3.3	4.7	8.0	5.2	3.7	3.6	3.5	3.0	2.8	2.7	2.8	3.4
23.....	3.3	4.6	14.8	4.8	3.5	3.5	3.4	3.2	2.8	2.6	2.7	3.8
24.....	3.3	4.4	8.0	4.7	3.5	3.5	3.3	3.0	2.7	2.6	2.7	3.7
25.....	3.4	4.4	6.2	4.6	3.6	3.5	3.0	3.0	2.7	2.6	2.7	3.6
26.....	3.4	4.3	6.1	4.7	3.6	5.0	3.1	2.9	2.7	2.6	2.6	3.5
27.....	3.3	4.5	5.6	4.7	3.6	5.0	3.1	2.9	2.7	2.6	2.6	3.4
28.....	3.4	17.5	5.2	4.6	3.7	4.7	3.1	2.9	2.7	2.5	2.6	3.2
29.....	3.6	5.0	4.5	3.9	4.0	3.0	2.9	2.6	2.5	2.6	3.1
30.....	3.7	6.4	4.3	5.5	3.8	3.0	2.9	2.6	2.7	2.5	3.0
31.....	3.6	7.7	5.7	4.0	2.8	2.7	2.8
1904												
1.....	2.3	3.0	3.4	3.8	3.3	3.3	2.9	3.4	2.7	2.3	2.2	2.8
2.....	2.3	2.9	3.4	3.7	3.3	3.3	2.7	3.0	2.6	2.3	2.2	2.4
3.....	2.3	2.9	3.3	3.6	3.3	3.0	2.5	2.8	2.6	2.3	2.2	2.4
4.....	2.7	3.4	3.3	3.5	3.3	2.9	2.4	2.8	2.7	2.2	2.4	2.8
5.....	2.7	3.2	3.3	3.4	3.3	2.9	2.4	3.6	4.1	2.2	2.3	4.1
6.....	2.6	3.0	3.2	3.3	3.2	2.8	2.9	3.0	3.0	2.2	2.3	3.6
7.....	2.3	3.0	3.3	4.2	3.2	7.3	2.7	2.8	2.8	2.2	2.3	3.1
8.....	2.7	4.5	5.1	5.6	3.3	4.7	2.7	5.0	2.7	2.2	2.3	3.0
9.....	2.7	3.6	4.5	5.0	4.6	3.7	3.0	3.5	2.6	2.2	2.3	2.9
10.....	2.6	3.2	4.0	4.5	3.9	3.0	2.8	3.1	2.5	2.2	2.3	2.8
11.....	2.6	3.3	4.0	4.0	3.7	2.9	2.6	4.0	2.6	2.2	2.3	2.8
12.....	2.6	3.3	3.8	3.8	3.4	3.0	3.1	3.8	2.6	2.2	2.3	2.8
13.....	2.5	3.1	3.3	3.7	3.4	2.9	2.2	3.4	2.5	2.2	2.4	2.7
14.....	2.5	3.0	4.4	3.6	3.3	2.7	2.7	2.9	2.5	2.2	2.4	2.6
15.....	2.7	3.3	4.0	3.6	3.3	2.7	2.6	3.9	2.4	2.2	2.4	3.0
16.....	2.3	3.1	3.7	3.5	3.1	2.7	2.4	3.1	2.3	2.2	2.4	2.9
17.....	4.0	3.0	3.7	3.4	3.1	2.7	2.6	2.9	2.3	2.2	2.4	2.8
18.....	3.2	3.0	3.7	3.5	3.1	2.7	2.6	2.7	2.3	2.2	2.3	2.7
19.....	3.3	3.0	3.6	3.5	3.1	2.6	2.5	2.7	2.3	2.2	2.3	2.7
20.....	3.0	4.3	3.4	3.5	3.1	2.7	2.4	2.7	2.3	2.2	2.3	2.7
21.....	3.0	3.8	3.3	3.4	3.0	2.9	2.4	2.7	2.2	2.2	2.3	2.7
22.....	3.0	5.6	5.4	3.4	3.0	3.0	4.2	2.7	2.2	2.2	2.3	2.6
23.....	5.0	5.0	6.7	3.4	3.0	2.8	2.3	2.6	2.2	2.2	2.3	2.5
24.....	4.0	4.3	6.4	3.3	2.9	2.7	2.6	3.5	3.0	2.2	2.2	2.7
25.....	3.8	3.8	5.2	3.3	3.0	2.7	3.1	2.9	2.6	2.2	2.2	2.8
26.....	3.4	3.7	5.1	3.8	2.9	2.7	2.8	2.8	2.3	2.2	2.2	2.8
27.....	3.2	3.6	5.0	3.7	2.9	2.8	2.6	2.7	2.3	2.2	2.2	2.8
28.....	3.0	3.5	4.5	3.7	2.9	3.2	2.8	3.2	2.3	2.2	2.2	4.7
29.....	3.0	3.3	4.1	3.4	2.9	4.6	2.6	2.7	2.3	2.2	2.2	3.4
30.....	3.0	3.4	3.4	5.4	3.2	2.6	2.7	2.3	2.2	3.0	3.1
31.....	2.8	3.9	3.8	2.6	2.7	2.2	3.0

WATER POWERS OF GEORGIA

Daily gage height, in feet, of Nottely River at Ranger, N. C.—Continued.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1905												
1.....	3.0	2.9	3.7	3.3	3.9	3.5	3.9	2.7	3.4	2.3	2.6	2.6
2.....	2.9	2.9	3.6	3.3	3.3	3.3	4.1	2.7	3.1	2.3	2.6	2.7
3.....	3.5	2.9	3.6	3.3	3.7	3.5	3.6	2.7	3.0	2.3	2.7	11.8
4.....	3.1	3.0	3.6	3.2	3.6	3.4	3.4	2.7	3.0	3.0	2.7	4.8
5.....	3.1	2.9	3.6	3.4	3.5	3.3	3.1	2.7	2.9	3.0	2.7	3.2
6.....	3.1	4.0	3.5	3.5	5.8	3.2	4.2	2.6	2.9	3.0	2.6	2.9
7.....	3.0	3.9	3.5	3.6	5.6	3.2	4.1	2.8	2.3	2.9	2.6	2.7
8.....	3.5	5.4	3.5	3.5	5.2	3.2	3.9	2.7	2.8	2.5	2.6	9.9
9.....	3.1	10.2	3.4	3.5	4.9	3.1	3.1	3.1	2.6	2.5	2.6	7.2
10.....	3.0	5.2	4.7	3.4	4.2	3.0	3.0	3.9	2.4	2.4	2.6	5.8
11.....	2.9	4.3	4.1	3.4	4.0	3.0	4.5	3.9	2.4	6.6	2.6	4.2
12.....	11.4	4.2	3.3	3.3	3.3	3.0	3.0	4.0	2.6	3.8	2.6	4.0
13.....	7.2	5.9	3.9	3.7	3.7	3.0	5.0	4.2	2.5	3.2	2.5	4.0
14.....	5.3	4.6	3.3	3.6	3.5	3.0	4.1	3.9	2.5	2.8	2.5	3.9
15.....	5.1	4.2	3.5	3.5	3.5	3.1	3.9	3.4	2.4	2.5	2.5	3.9
16.....	4.5	4.0	3.5	3.9	6.6	3.1	3.3	3.3	2.4	2.5	2.4	3.4
17.....	4.5	3.8	3.5	3.5	4.9	3.2	3.5	3.3	2.4	2.5	2.4	3.5
18.....	3.4	3.6	3.4	3.4	4.2	3.0	3.3	3.2	2.4	2.6	2.3	3.5
19.....	3.3	3.7	3.4	3.4	3.9	3.3	3.2	3.0	2.4	2.6	2.3	3.4
20.....	3.3	4.0	3.5	3.4	3.3	3.4	3.4	3.0	2.3	2.6	2.3	4.6
21.....	3.3	7.8	7.5	3.4	3.6	4.0	3.3	2.9	2.3	2.6	2.3	5.9
22.....	3.2	5.2	4.3	3.5	3.4	3.9	3.2	2.8	2.3	2.6	2.4	5.1
23.....	3.2	5.0	4.4	3.4	5.3	5.0	3.0	2.8	2.3	2.5	2.4	5.0
24.....	3.1	4.7	4.2	3.3	5.0	3.6	3.0	2.3	2.4	2.5	2.4	5.4
25.....	3.0	4.6	3.7	3.3	4.7	3.4	2.9	2.7	2.4	2.5	2.3	5.2
26.....	3.0	4.4	3.6	3.4	4.3	3.4	2.8	2.6	2.4	3.2	2.4	4.9
27.....	3.0	3.9	3.6	4.4	4.0	3.3	2.7	2.6	2.3	2.8	2.5	4.7
28.....	2.9	3.3	3.5	3.8	3.9	3.3	2.8	2.7	2.3	2.7	2.5	4.6
29.....	3.4	3.4	3.8	3.8	3.4	3.0	2.7	2.3	2.7	2.7	4.2
30.....	3.1	3.4	4.6	3.6	3.2	3.0	2.6	2.3	2.6	2.7	4.0
31.....	2.9	3.4	4.0	2.8	2.6	2.6	3.5

Rating tables for Nottely River at Ranger, N. C.

FEBRUARY 16, 1901, TO DECEMBER 31, 1903.^a

Gage height	Dis-charge						
Feet	Sec.-ft.	Feet	Sec.-ft.	Feet	Sec.-ft.	Feet	Sec.-ft.
2.30	143	4.10	590	5.90	1,130	9.40	2,130
2.40	155	4.20	620	6.00	1,160	9.60	2,240
2.50	172	4.30	650	6.20	1,220	9.80	2,300
2.60	190	4.40	680	6.40	1,280	10.00	2,360
2.70	209	4.50	710	6.60	1,340	11.00	2,660
2.80	229	4.60	740	6.80	1,400	12.00	2,960
2.90	250	4.70	770	7.00	1,460	13.00	3,260
3.00	272	4.80	800	7.20	1,520	14.00	3,560
b 3.10	296	4.90	830	7.40	1,580	15.00	3,860
b 3.20	322	5.00	860	7.60	1,640	16.00	4,160
3.30	350	5.10	890	7.80	1,700	17.00	4,460
3.40	380	5.20	920	8.00	1,760	18.00	4,760
3.50	410	5.30	950	8.20	1,820	19.00	5,060
3.60	440	5.40	980	8.40	1,880	20.00	5,360
3.70	470	5.50	1,010	8.60	1,940	21.00	5,660
3.80	500	5.60	1,040	8.80	2,000		
3.90	530	5.70	1,070	9.00	2,060		
4.00	560	5.80	1,100	9.20	2,120		

^a Above gage height 3.3 feet the rating curve is a tangent, the difference being 30 per tenth.

^b For 1901, 3.10=290 and 3.20=320.

HIWASSEE DRAINAGE BASIN, STREAM FLOW

Rating tables for Nottely River at Ranger, N. C.—Continued.

JANUARY 1, 1904, TO DECEMBER 31, 1905.^a

Gage height	Dis-charge						
<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>
2.20	101	3.20	320	4.20	624	5.40	1,008
2.30	120	3.30	346	4.30	656	5.60	1,072
2.40	141	3.40	373	4.40	688	5.80	1,136
2.50	162	3.50	402	4.50	720	6.00	1,200
2.60	184	3.60	432	4.60	752	7.00	1,520
2.70	206	3.70	464	4.70	784	8.00	1,840
2.80	228	3.80	496	4.80	816	9.00	2,160
2.90	250	3.90	528	4.90	848	10.00	2,480
3.00	272	4.00	560	5.00	880	11.00	2,800
3.10	295	4.10	592	5.20	944	12.00	3,120

^a This table is based on 22 discharge measurements made during 1901 to 1905, inclusive. It is well defined between gage heights 2.25 feet and 3.50 feet. Above gage height 3.60 feet the rating curve is a tangent, the difference being 32 per tenth.

Estimated monthly discharge of Nottely River at Ranger, N. C.

[Drainage area, 272 square miles.]

Month	Discharge in second-feet			Run-off	
	Maximum	Minimum	Mean	Sec.-ft. per sq. mile	Depth in inches
1901					
February 16-28.....			514	1.89	0.91
March.....	3,410	440	774	2.85	3.29
April.....	2,000	620	956	3.51	3.92
May.....	3,860	410	894	3.29	3.79
June.....	1,460	530	790	2.90	3.24
July.....	2,300	380	639	2.35	2.71
August.....	4,100	290	1,486	5.46	6.29
September.....	2,660	530	823	3.03	3.38
October.....	590	350	463	1.70	1.96
November.....	560	350	386	1.42	1.58
December.....	5,360	380	927	3.41	3.98
1902					
January.....	1,250	272	631	2.32	2.67
February.....	5,660	560	1,006	3.70	3.85
March.....	3,500	740	1,095	4.03	4.64
April.....	890	560	711	2.61	2.91
May.....	770	350	475	1.75	2.02
June.....	500	272	322	1.18	1.32
July.....	800	209	307	1.13	1.30
August.....	500	155	219	.81	.98
September.....	380	172	237	.87	.97
October.....	410	148	221	.81	.98
November.....	950	148	295	1.08	1.20
December.....	1,220	272	576	2.12	2.44
The year.....	5,660	148	508	1.87	25.18
1903					
January.....	800	272	433	1.59	1.83
February.....	4,610	322	1,095	4.03	4.20
March.....	3,300	770	1,289	4.74	5.46
April.....	1,940	650	1,028	3.73	4.22
May.....	1,070	410	572	2.10	2.42
June.....	1,610	410	810	2.98	3.32
July.....	1,100	272	503	1.85	2.13
August.....	1,460	229	389	1.43	1.65
September.....	560	190	238	.88	.98
October.....	560	172	212	.78	.90
November.....	560	172	232	.85	.95
December.....	500	172	254	.93	1.07
The year.....	4,610	172	588	2.16	29.13

WATER POWERS OF GEORGIA

Estimated monthly discharge of Notteley River at Ranger, N. C.—Continued.

Month	Discharge in second-feet			Run-off	
	Maximum	Minimum	Mean	Sec.-ft. per sq. mile	Depth in inches
1904					
January.....	880	162	293	1.08	1.24
February.....	1,072	250	423	1.56	1.68
March.....	1,936	320	656	2.41	2.78
April.....	1,072	346	472	1.74	1.94
May.....	1,008	250	362	1.33	1.53
June.....	1,616	184	334	1.23	1.37
July.....	624	101	210	.772	.890
August.....	880	184	310	1.14	1.31
September.....	592	101	174	.640	.714
October.....	120	101	108	.379	.437
November.....	272	101	124	.456	.509
December.....	784	141	264	.971	1.12
The year.....	1,936	101	310	1.14	15.52
1905					
January.....	2,992	250	501	1.84	2.12
February.....	2,544	250	716	2.63	2.74
March.....	1,680	373	506	1.86	2.14
April.....	752	320	420	1.54	1.72
May.....	1,392	373	640	2.35	2.71
June.....	880	272	364	1.34	1.50
July.....	2,160	206	455	1.67	1.92
August.....	624	184	238	1.06	1.22
September.....	972	120	174	.840	.714
October.....	1,392	120	247	.908	1.05
November.....	206	120	165	.607	.677
December.....	3,056	184	780	2.87	3.31
The year.....	3,056	120	438	1.61	21.82

TOCCOA RIVER NEAR BLUERIDGE.

This stream, called Toccoa River in Georgia and Ocoee River in Tennessee, has its source on the northern slopes of the Blue Ridge Mountains in Georgia and flows northwest into Hiwassee River. The area is covered with a fine growth of oak, hickory, and other hard woods. The station, established by B. M. Hall on November 25, 1898, is located at the Morganton Bridge, about 4 miles east of the town of Blueridge, Ga. The gage is a 14-foot rod, in two 7-foot sections, nailed to a tree on the right bank just below the bridge. It is graduated to feet and tenths and is set to conform to bench marks which were established October 15, 1896, and October 26, 1898. The measurements during 1896 were made at the railroad bridge about 3 miles below, but are referred to the present gage by comparison of the bench marks at the two bridges. The bench mark at the Morganton Bridge is on the top of the bridge floor, on the downstream side, 50 feet from the initial point,

and is 18.0 feet above the zero of the gage. The bridge was a wooden, queen-post, open bridge, in three spans, with a total length between abutments of 153 feet, but it has been remodeled and changed into a closed bridge, not suitable for use in making discharge measurements at such an irregular section. Measurements are now made at McCays, Tenn., where a gage has been established.

The observer was W. E. Rogers, a farmer living about a quarter of a mile east of the gage. The station was discontinued March 31, 1903.

Discharge measurements of Toccoa River near Blueridge.

Date			Gage height	Dis-charge	Date			Gage height	Dis-charge
1898			<i>Feet</i>	<i>Sec.-ft.</i>	1900			<i>Feet</i>	<i>Sec.-ft.</i>
August 26.....			2.95	624	November 28.....		2.95	626	
November 25.....			3.15	797	December 17.....		2.65	419	
1899					1901				
April 28.....			3.50	1,141	January 23.....		3.05	714	
June 16.....			2.70	522	April 5.....		3.50	1,051	
September 18.....			1.98	242	June 26.....		3.44	998	
October 24.....			1.90	222	August 23.....		6.90	4,697	
					October 31.....		2.62	592	
1900					1902				
March 23.....			3.36	967	April 25.....		3.20	749	
May 18.....			2.90	679	November 21.....		2.15	253	
July 19.....			2.90	680					

Daily gage height, in feet, of Toccoa River near Blueridge.

Day	Nov.	Dec.	Day	Nov.	Dec.	Day	Nov.	Dec.	Day	Nov.	Dec.
1898			1898			1898			1898		
1.....		3.1	9.....		3.1	17.....		2.8	25.....		3.1
2.....		3.0	10.....		3.0	18.....		2.8	26.....		3.2
3.....		3.0	11.....		2.9	19.....		2.8	27.....		3.3
4.....		3.2	12.....		2.8	20.....		3.1	28.....		3.4
5.....		3.4	13.....		2.8	21.....		3.0	29.....		3.4
6.....		3.4	14.....		2.8	22.....		2.3	30.....		3.4
7.....		3.1	15.....		2.8	23.....		3.4	31.....		2.8
8.....		3.0	16.....		2.8	24.....		3.1			3.2

WATER POWERS OF GEORGIA

Daily gage height, in feet, of Toccoa River near Blueridge.—Continued.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1899												
1.....	3.1	3.2	4.3	4.2	3.7	3.0	2.5	2.6	2.3	2.0	2.1	2.4
2.....	3.0	3.2	4.0	3.6	3.5	2.1	2.45	2.6	2.4	2.0	2.0	2.2
3.....	2.9	3.3	4.1	3.11	3.5	2.1	2.4	2.5	2.4	1.9	2.0	2.1
4.....	2.9	5.9	4.1	4.6	3.4	2.2	2.4	2.5	2.5	1.9	2.0	2.1
5.....	2.1	6.7	4.0	4.4	3.1	3.0	2.5	2.5	2.4	1.9	2.0	2.1
6.....	3.02	3.9	4.0	3.9	3.6	2.9	2.8	2.5	2.4	2.0	2.0	2.0
7.....	3.04	6.1	3.8	4.5	3.4	2.9	2.7	2.5	2.3	3.0	2.0	2.0
8.....	3.08	5.5	3.7	4.8	3.2	2.9	2.8	2.4	2.3	2.8	2.1	2.0
9.....	3.1	5.0	3.6	4.0	3.2	2.7	2.75	2.3	2.3	2.6	2.1	2.0
10.....	3.1	4.0	3.1	4.0	3.1	2.7	2.75	2.3	2.5	2.3	2.1	2.5
11.....	3.2	3.7	3.0	3.1	3.0	2.7	2.7	2.3	2.6	2.1	2.1	3.6
12.....	3.0	3.8	3.5	3.9	3.0	3.4	2.7	2.6	2.5	2.0	2.1	3.5
13.....	3.0	3.9	4.0	3.8	3.0	3.2	2.8	3.4	2.3	2.0	2.0	3.3
14.....	3.1	4.0	4.0	3.7	3.0	3.0	2.7	3.4	2.3	2.0	2.0	3.9
15.....	3.1	4.0	4.9	3.7	3.0	2.1	2.6	3.4	2.2	2.0	2.1	2.3
16.....	3.1	4.1	6.0	3.6	3.0	2.7	2.4	3.2	2.2	2.0	2.1	2.5
17.....	3.2	3.1	4.4	3.6	3.0	2.6	2.4	2.4	2.1	2.0	2.0	2.4
18.....	3.1	3.3	4.0	3.6	3.0	2.6	2.3	2.4	2.3	2.0	2.0	2.3
19.....	3.0	3.4	4.5	3.6	3.3	2.6	2.7	2.4	2.3	2.0	2.0	2.6
20.....	3.0	3.6	5.0	3.6	3.0	2.6	2.7	2.2	2.0	2.0	2.0	2.6
21.....	2.1	3.5	4.8	3.6	3.2	2.5	2.8	2.2	2.0	2.0	2.0	2.5
22.....	3.0	3.6	4.6	3.6	3.2	2.45	2.3	2.2	2.0	2.0	2.0	2.4
23.....	3.3	3.5	5.6	3.8	3.1	2.5	2.6	2.3	2.0	2.0	2.0	2.5
24.....	3.1	3.4	5.0	4.0	3.1	2.1	2.5	2.2	2.0	2.0	2.0
25.....	3.2	3.4	4.5	5.3	3.1	2.4	2.3	2.3	2.0	2.0	2.0
26.....	3.1	4.0	4.2	4.1	3.1	2.7	2.8	2.2	2.0	2.0	2.3
27.....	2.1	5.8	4.0	4.6	3.1	2.9	3.9	2.4	2.0	2.0	2.6
28.....	2.1	4.9	4.0	3.1	3.0	2.85	3.6	2.6	2.0	2.0	2.3
29.....	2.09	4.0	3.0	3.0	2.7	2.8	2.5	2.0	2.2	3.2
30.....	2.3	4.0	3.3	3.1	2.6	2.3	2.6	2.0	2.4	3.1
31.....	4.0	4.8	3.11	2.3	2.7	2.2
1900												
1.....	3.1	3.6	4.3	3.6	2.6	2.5	3.4	2.6
2.....	3.1	3.5	4.3	3.5	2.6	2.5	3.4	3.0
3.....	3.1	3.5	4.2	3.4	2.6	2.5	3.4	3.6
4.....	3.0	3.4	4.2	3.4	2.6	2.6	3.4	3.6
5.....	3.0	3.5	4.1	3.4	2.6	2.6	3.4	3.5
6.....	3.0	3.5	3.6	3.4	2.6	2.6	3.3	3.5
7.....	3.0	3.4	3.6	3.4	2.6	2.6	3.3	3.4
8.....	3.0	3.4	3.5	3.4	2.6	2.6	3.3	3.4
9.....	3.0	3.4	3.5	3.3	2.6	2.6	3.2	3.3
10.....	3.0	3.3	3.5	3.3	2.6	2.8	3.2	3.3
11.....	3.4	3.1	3.4	3.3	2.6	2.8	3.1	3.2
12.....	3.2	3.0	3.4	3.2	2.6	2.9	3.1	3.2
13.....	3.0	3.0	3.4	3.2	3.0	2.9	3.1	3.0
14.....	3.0	3.0	3.3	3.2	3.4	2.8	3.1	3.0
15.....	3.0	3.0	3.3	3.1	4.0	2.8	3.1	2.3
16.....	3.0	2.8	3.3	2.8	3.6	2.6	3.0	2.3
17.....	3.3	2.8	3.3	2.8	3.4	2.6	3.0	2.3
18.....	3.5	2.6	3.2	2.8	3.4	2.6	3.0	2.3
19.....	3.5	3.6	3.2	2.8	3.2	2.6	3.0	3.3
20.....	3.4	3.2	2.8	3.2	2.6	3.0	2.7
21.....	3.3	3.1	2.8	3.0	2.6	3.0	2.7
22.....	3.3	3.1	3.0	3.0	2.9	2.8	2.6
23.....	3.4	3.3	3.6	3.0	2.3	3.6	2.7	2.6
24.....	3.5	3.2	3.5	3.0	2.3	6.0	2.7	2.6
25.....	3.6	3.5	3.5	2.8	2.6	5.4	2.7	2.6
26.....	3.5	3.5	3.5	2.8	2.5	4.0	2.7	2.6
27.....	3.5	3.6	5.0	4.0	2.5	3.6	2.6	3.0
28.....	3.4	3.5	5.0	4.0	2.5	3.6	2.6	3.0
29.....	3.3	3.4	4.5	3.8	2.7	2.5	3.6	3.0
30.....	3.2	3.6	4.3	3.8	2.7	2.5	3.5	2.3
31.....	3.2	3.6	2.6	3.4	2.3

HIWASSEE DRAINAGE BASIN, STREAM FLOW

Daily gage height, in feet, of Toccoa River near Blueridge.—Continued.

Day	Jan.	Feb	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1901												
1.....	3.0	3.0	3.0	4.0	3.6	4.0	3.0	3.5	4.0	3.2	2.8	2.8
2.....	3.0	3.0	3.0	4.0	3.6	4.0	3.0	3.2	4.0	3.0	2.8	2.8
3.....	3.0	4.0	3.0	4.0	3.5	4.0	3.0	3.0	4.0	3.0	2.7	2.8
4.....	3.0	4.0	3.0	4.0	3.5	4.0	3.0	3.0	4.0	3.0	2.7	2.8
5.....	3.0	3.5	3.0	4.0	3.5	3.8	3.0	6.0	4.0	3.0	2.7	2.8
6.....	3.0	3.5	3.0	4.0	3.5	3.8	3.0	4.0	4.0	3.0	2.7	2.9
7.....	2.8	3.4	3.0	3.8	3.5	3.6	3.0	4.0	4.0	3.0	2.7	3.0
8.....	2.8	3.4	3.0	3.8	3.5	3.6	3.0	4.0	4.0	3.0	2.6	3.0
9.....	3.0	3.0	3.5	3.8	3.4	3.5	3.0	3.5	4.0	3.0	2.6	3.0
10.....	4.0	3.0	3.4	3.8	3.4	3.5	3.0	3.5	3.6	3.0	2.6	3.0
11.....	7.4	3.0	3.3	3.7	3.4	3.5	3.0	3.5	3.6	3.0	2.6	4.0
12.....	5.0	3.0	3.0	3.7	3.2	3.5	3.0	4.0	6.6	3.0	2.6	5.0
13.....	4.0	3.0	3.0	3.7	3.2	3.5	3.0	4.0	3.6	3.0	2.6	5.0
14.....	3.8	3.0	3.0	3.6	3.0	3.5	3.0	4.0	3.5	3.0	2.6	12.0
15.....	3.8	3.0	3.0	3.6	3.0	3.5	3.0	5.0	3.5	3.0	2.6	5.0
16.....	3.6	3.0	3.0	3.6	3.0	3.4	3.0	5.0	3.5	3.0	2.6	4.8
17.....	3.6	3.0	3.0	3.5	3.0	3.4	3.0	5.0	3.4	3.0	2.7	4.8
18.....	3.4	3.0	3.0	3.5	3.0	3.4	4.0	4.5	3.4	2.8	2.7	4.6
19.....	3.4	3.0	3.0	5.5	3.0	3.2	4.0	4.5	3.0	2.8	2.7	4.6
20.....	3.2	2.8	3.0	4.5	11.0	3.2	3.5	4.5	3.0	2.8	2.7	4.6
21.....	3.0	2.8	3.0	4.0	6.0	3.2	3.0	4.0	3.0	2.8	2.7	4.0
22.....	3.0	2.8	3.0	4.0	6.0	3.2	3.0	14.0	3.0	2.8	2.7	4.0
23.....	3.0	2.8	3.0	4.0	5.0	3.0	3.0	8.0	3.0	2.8	2.7	4.0
24.....	3.0	3.0	3.0	4.0	5.0	3.0	3.0	6.0	3.0	2.8	2.7	4.0
25.....	4.0	3.0	7.0	3.8	5.0	3.0	3.0	5.0	3.0	2.8	2.7	4.0
26.....	3.5	3.0	6.0	3.8	4.0	3.0	3.0	4.0	3.0	2.8	2.7	5.0
27.....	3.5	3.0	4.0	3.8	3.6	3.0	3.0	4.0	3.0	2.8	2.7	5.5
28.....	3.2	3.0	4.0	3.6	3.6	3.0	3.0	4.0	4.0	2.8	2.7	6.0
29.....	3.2	4.0	3.6	3.6	3.0	3.0	4.0	4.0	2.8	2.7	10.0
30.....	3.2	4.0	3.6	3.6	3.0	3.0	4.0	3.5	2.8	2.7	6.0
31.....	3.0	4.0	4.0	4.0	4.0	2.8	5.4
1902												
1.....	5.0	4.0	4.0	4.8	3.5	2.8	2.5	2.6	2.8	2.5	2.4	3.0
2.....	5.0	4.0	4.0	4.8	3.5	2.8	2.5	2.6	3.0	2.5	2.4	4.0
3.....	5.0	4.0	4.0	4.6	3.4	2.8	2.5	2.4	3.0	2.5	2.4	4.0
4.....	4.6	4.0	4.0	4.6	3.0	2.8	2.5	2.4	3.0	2.5	2.4	4.0
5.....	4.5	4.0	3.8	4.5	3.0	2.8	2.5	2.4	3.0	2.6	2.4	4.0
6.....	4.3	4.0	3.8	4.0	3.0	2.8	2.5	2.3	2.8	2.6	2.4	3.5
7.....	4.0	4.0	3.7	4.0	3.0	2.8	2.5	2.3	2.8	2.6	3.0	3.5
8.....	4.0	4.0	3.7	4.0	3.0	3.0	2.4	2.3	2.8	2.6	3.0	3.5
9.....	4.0	4.0	4.0	4.0	3.0	3.0	2.4	2.3	2.6	2.6	3.0	3.0
10.....	4.0	4.0	6.0	4.8	3.0	3.0	2.4	2.3	2.6	2.6	2.5	3.0
11.....	4.0	4.0	5.5	4.8	3.0	3.0	2.3	2.3	2.6	2.6	2.5	3.0
12.....	3.6	4.3	5.5	4.0	3.0	3.0	2.6	2.3	3.0	2.6	2.4	3.0
13.....	3.6	4.2	5.0	4.0	3.0	3.0	2.4	2.3	3.0	2.6	2.4	3.0
14.....	3.6	4.0	5.0	3.8	3.0	3.0	2.4	2.3	2.8	2.6	2.4	3.0
15.....	3.5	4.0	5.0	3.8	3.0	2.8	2.4	2.3	2.8	2.5	2.4	3.0
16.....	3.5	4.0	5.0	3.8	3.0	2.8	2.4	2.3	2.8	2.5	2.4	3.0
17.....	3.5	4.0	4.8	3.6	3.0	2.8	2.4	2.2	2.8	2.5	2.4	3.0
18.....	3.5	4.0	4.8	3.6	3.0	2.8	2.4	2.2	2.8	2.5	2.4	3.0
19.....	3.5	6.0	4.6	3.6	3.0	2.7	2.4	2.2	2.8	2.5	2.4	3.0
20.....	3.5	10.0	4.6	3.4	3.0	2.7	2.4	2.2	2.8	2.5	2.4	3.0
21.....	3.4	5.0	4.3	3.4	3.0	2.7	2.4	2.2	2.8	2.5	2.3	3.5
22.....	3.4	5.0	4.0	3.4	3.0	2.6	2.4	2.2	2.7	2.5	2.3	3.5
23.....	3.4	5.0	4.0	3.4	3.0	2.6	2.4	2.2	2.7	2.5	2.3	3.5
24.....	3.4	4.0	4.0	3.2	3.0	2.5	2.4	2.2	2.6	2.5	2.3	3.2
25.....	3.4	4.0	4.0	3.2	3.0	2.5	2.4	2.2	2.6	2.5	4.0	3.0
26.....	4.0	4.0	4.0	3.2	3.0	2.5	2.4	2.2	2.6	2.4	3.0	3.0
27.....	4.0	4.0	4.0	3.4	3.0	2.5	2.4	3.0	2.6	2.4	3.0	3.0
28.....	5.0	4.0	3.8	3.4	3.0	2.5	2.4	3.0	2.5	2.4	3.0	3.0
29.....	5.0	6.0	3.4	2.8	2.5	2.4	3.0	2.5	2.4	3.0	3.0
30.....	4.5	5.0	3.5	2.8	2.5	2.4	2.8	2.5	2.4	3.0	3.0
31.....	4.5	5.0	2.8	2.6	2.8	2.4	3.0

WATER POWERS OF GEORGIA

Daily gage height, in feet, of Toccoa River near Blueridge.—Continued.

Day	Jan.	Feb.	Mar.	Day	Jan.	Feb.	Mar.	Day	Jan.	Feb.	Mar.
1903			1903			1903					
1.....	3.0	3.0	6.0	12.....	2.8	3.8	4.0	22.....	3.0	3.8	4.0
2.....	3.0	3.0	5.0	13.....	2.8	3.6	4.0	23.....	3.0	3.8	4.0
3.....	3.5	4.0	5.0	14.....	2.8	3.6	4.0	24.....	3.0	3.8	4.0
4.....	3.0	5.0	5.0	15.....	2.8	4.0	4.0	25.....	3.0	3.8	4.0
5.....	3.0	4.0	4.8	16.....	2.8	4.0	4.0	26.....	3.0	3.6	4.0
6.....	2.8	4.0	4.8	17.....	2.8	4.0	4.0	27.....	3.0	3.6	3.8
7.....	2.8	4.0	4.6	18.....	2.8	4.0	4.0	28.....	3.0	10.0	3.8
8.....	2.8	3.0	4.5	19.....	2.8	3.8	4.0	29.....	3.0	4.0
9.....	2.8	4.0	4.5	20.....	3.0	3.8	4.0	30.....	3.0	7.0
10.....	2.8	4.0	4.2	21.....	3.0	3.8	4.0	31.....	3.0	6.0
11.....	2.8	3.8	4.2								

Rating tables for Toccoa River near Blueridge.

NOVEMBER 25, 1898, TO DECEMBER 31, 1899.^a

Gage height	Dis-charge						
<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>
1.90	230	3.40	1,064	4.90	2,204	6.80	3,648
2.00	255	3.50	1,140	5.00	2,280	7.00	3,800
2.10	280	3.60	1,216	5.10	2,356	7.20	3,952
2.20	305	3.70	1,292	5.20	2,432	7.40	4,104
2.30	335	3.80	1,368	5.30	2,508	7.60	4,256
2.40	370	3.90	1,444	5.40	2,584	7.80	4,408
2.50	420	4.00	1,520	5.50	2,660	8.00	4,560
2.60	475	4.10	1,596	5.60	2,736	8.20	4,712
2.70	540	4.20	1,672	5.70	2,812	8.40	4,864
2.80	610	4.30	1,748	5.80	2,888	8.60	5,016
2.90	685	4.40	1,824	5.90	2,964	8.80	5,168
3.00	760	4.50	1,900	6.00	3,040	9.00	5,320
3.10	836	4.60	1,976	6.20	3,192		
3.20	912	4.70	2,052	6.40	3,344		
3.30	988	4.80	2,128	6.60	3,496		

JANUARY 1 TO DECEMBER 31, 1900.^b

2.50	423	3.80	1,435	5.10	2,735	6.80	4,435
2.60	460	3.90	1,535	5.20	2,835	7.00	4,635
2.70	502	4.00	1,635	5.30	2,935	7.20	4,835
2.80	550	4.10	1,735	5.40	3,035	7.40	5,035
2.90	605	4.20	1,835	5.50	3,135	7.60	5,235
3.00	675	4.30	1,935	5.60	3,235	7.80	5,435
3.10	750	4.40	2,035	5.70	3,335	8.00	5,635
3.20	837	4.50	2,135	5.80	3,435	8.20	5,835
3.30	935	4.60	2,235	5.90	3,535	8.40	6,035
3.40	1,035	4.70	2,335	6.00	3,635	8.60	6,235
3.50	1,135	4.80	2,435	6.20	3,835		
3.60	1,235	4.90	2,535	6.40	4,035		
3.70	1,335	5.00	2,635	6.60	4,235		

JANUARY 1, 1901, TO MARCH 31, 1903.^c

2.20	270	3.50	1,062	4.80	2,446	7.20	5,014
2.30	312	3.60	1,162	4.90	2,553	7.40	5,223
2.40	355	3.70	1,269	5.00	2,660	7.60	5,442
2.50	400	3.80	1,376	5.20	2,874	7.80	5,656
d 2.60	447	3.90	1,483	5.40	3,088	8.00	5,870
d 2.70	497	4.00	1,590	5.60	3,302	9.00	6,940
d 2.80	550	4.10	1,697	5.80	3,516	10.00	8,010
2.90	606	4.20	1,804	6.00	3,730	11.00	9,080
3.00	666	4.30	1,911	6.20	3,944	12.00	10,150
3.10	732	4.40	2,018	6.40	4,158	13.00	11,220
3.20	804	4.50	2,125	6.60	4,372	14.00	12,290
3.30	883	4.60	2,232	6.80	4,586		
3.40	969	4.70	2,339	7.00	4,800		

^a Above gage height 3.00 feet the rating curve is a tangent, the difference being 76 per tenth.
^b Above gage height 3.30 feet the rating curve is a tangent, the difference being 100 per tenth.
^c Above gage height 3.60 feet the rating curve is a tangent, the difference being 107 per tenth.
^d For 1901, 2.60=460, 2.70=503, 2.80=552.

HIWASSEE DRAINAGE BASIN, STREAM FLOW

Estimated monthly discharge of Toccoa River near Blueridge.

[Drainage area, 281 square miles]

Month	Discharge in second-feet			Run-off	
	Maximum	Minimum	Mean	Sec.-ft. per sq. mile	Depth in inches
1898					
November 25-30.....	1,064	836	988	4.28	0.96
December.....	1,064	610	745	3.23	3.72
1899					
January.....	1,520	280	733	3.17	3.66
February.....	5,244	836	1,759	7.61	7.92
March.....	8,040	760	1,704	7.38	8.51
April.....	2,508	760	1,411	6.11	6.81
May.....	1,292	760	834	3.83	4.41
June.....	1,064	280	545	2.36	2.63
July.....	1,444	370	575	2.49	2.87
August.....	1,064	305	471	2.04	2.36
September.....	610	255	329	1.42	1.58
October.....	760	230	298	1.29	1.49
November.....	912	255	315	1.36	1.52
December 1-23.....	1,216	255	473	2.05	1.75
1900					
March 23-31.....	1,235	837	1,085	4.48	1.50
April.....	1,235	675	878	3.30	4.24
May 1-19.....	1,235	460	900	3.90	2.76
June 27-30.....	2,635	1,985	2,335	10.11	1.50
July.....	1,935	750	1,226	5.21	6.12
August.....	1,235	460	761	3.29	3.79
September.....	1,635	423	829	2.72	3.08
October.....	6,235	423	1,007	4.36	5.03
November.....	1,035	460	723	3.15	3.51
December.....	1,235	460	710	3.07	3.54
1901					
January.....	5,228	552	1,100	4.76	5.49
February.....	1,590	552	765	3.31	3.44
March.....	4,800	666	1,077	4.21	5.37
April.....	3,195	1,062	1,458	6.31	7.04
May.....	9,050	666	1,599	6.92	7.38
June.....	1,590	666	1,011	4.38	4.38
July.....	1,590	666	788	3.32	3.32
August.....	12,290	666	2,248	9.73	11.22
September.....	1,590	666	1,144	4.95	5.52
October.....	804	552	619	2.68	3.09
November.....	552	460	493	2.13	2.38
December.....	10,150	552	2,248	9.73	11.22
The year.....	12,290	460	1,211	5.24	71.45
1902					
January.....	2,660	969	1,602	6.94	8.00
February.....	8,010	1,590	2,029	8.78	9.14
March.....	3,730	1,269	2,104	9.11	10.50
April.....	2,446	804	1,459	6.32	7.05
May.....	1,062	550	690	2.99	3.45
June.....	666	400	530	2.29	2.55
July.....	447	312	370	1.60	1.84
August.....	666	270	361	1.56	1.30
September.....	666	400	531	2.30	2.57
October.....	447	355	406	1.76	2.03
November.....	1,590	312	476	2.06	2.30
December.....	1,590	666	866	3.75	4.32
The year.....	8,010	270	952	4.12	55.55
1903					
January.....	1,062	550	626	2.71	3.12
February.....	8,010	666	1,629	7.05	7.34
March.....	4,800	1,376	2,046	8.36	10.21

OCOEE RIVER AT M'CAYS, TENN.

This station was established March 21, 1903, by O. P. Hall. It is located at a suspension footbridge just below McCays Ferry, at McCays, Tenn., near the Georgia-Tennessee boundary, and one-half mile below the railroad bridge of the Atlanta, Knoxville and Northern Railroad.

The channel is practically straight for about 800 feet above and below the station. The right bank will overflow at about 14 feet gage height for about 500 feet, and the left bank at a gage height 12 to 20 feet for about 400 feet. The water is confined to one channel and the bed is probably constant. The current is fairly swift and the section is good for measurement. Discharge measurements are made from the suspension footbridge.

The gage is in two sections, the inclined section reading from —0.3 to 8.5 feet, set in a trench and held in place by posts driven into the ground. The vertical section, reading from 8 to 18 feet, is attached to the bridge posts on the right bank. The gage is read twice each day by Arch Ballew. Bench marks are established as follows: (1) The head of a large nail in the center of a post at the right-bank end of the footbridge on the downstream side; elevation, 16.10 feet; this post is an anchor post for the cable of the suspension bridge and may be pulled out of place. (2) A copper plug set in a solid rock at the outer edge of the side ditch of the railroad bed, about 800 feet west of the railroad station at McCays, 11 feet north of the center of the track, and slightly higher than the railroad; elevation, 20.98 feet. Elevations refer to the datum of the gage.

Discharge measurements of Ocoee River at McCays, Tenn.

Date	Gage height	Dis-charge	Date	Gage height	Dis-charge
1903	<i>Feet</i>	<i>Sec.-ft.</i>	1904	<i>Feet</i>	<i>Sec.-ft.</i>
March 21.....	3.42	2,063	February 25.....	1.40	701
May 12.....	1.37	992	February 26.....	1.30	669
May 14.....	1.36	990	May 11.....	1.33	629
July 24.....	1.37	727	June 30.....	.32	386
August 21.....	1.17	584	August 26.....	.65	354
October 8.....	1.22	624	October 10.....	.30	214
October 9.....	.55	429			
December 7.....	.53	307	April 10..... 1905	1.22	666
1904			June 19.....	1.13	608
February 22.....	2.80	1,664	October 5.....	.77	413

HIWASSEE DRAINAGE BASIN, STREAM FLOW

407

Daily gage height, in feet, of Ocoee River at McCays, Tenn.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1903												
1.....				3.7	2.3	2.7	1.6	1.4	0.8	0.6	0.7	0.6
2.....				3.5	2.3	3.9	1.6	1.3	.8	.6	.7	.5
3.....				3.3	2.2	2.8	1.6	1.6	.9	.6	.9	.5
4.....				3.6	2.2	2.7	1.7	1.2	.9	.6	.9	.5
5.....				3.1	2.1	4.3	1.5	1.4	.9	.6	1.2	.6
6.....				3.1	2.1	4.1	1.5	1.3	.8	.6	.9	.6
7.....				3.0	2.1	3.1	1.6	1.2	.8	.6	.8	.5
8.....				4.4	2.0	2.6	1.6	1.1	.8	1.5	.7	.5
9.....				3.2	2.0	2.4	1.5	1.1	.9	.9	.7	.5
10.....				3.1	2.0	2.3	1.6	1.1	.9	.7	.6	.6
11.....				2.9	2.0	2.3	2.3	1.6	.8	.7	.6	.6
12.....				2.8	1.9	2.3	1.8	1.1	.8	.7	.9	.5
13.....				3.3	1.9	2.2	3.3	1.1	.7	.6	.7	.7
14.....				3.1	1.9	2.1	2.6	1.0	.7	.6	.7	.6
15.....				3.5	1.9	2.0	1.9	1.8	1.0	.6	.7	.6
16.....				3.2	1.8	2.0	1.7	1.9	1.3	.6	.7	.5
17.....				3.1	1.7	1.8	1.8	1.3	1.0	.9	1.2	.5
18.....				3.1	1.7	1.8	1.6	1.9	.9	.9	1.2	.5
19.....				2.9	1.7	1.7	1.5	1.2	.7	.7	.8	.5
20.....				3.1	1.7	1.7	1.5	2.4	.8	.7	.8	.9
21.....				2.9	1.7	1.7	1.4	1.2	.8	.6	.7	.9
22.....			4.3	2.7	1.6	1.7	1.4	1.1	.8	.6	.7	.8
23.....			5.0	2.6	1.6	1.7	1.4	1.1	.7	.6	.7	.6
24.....			4.6	2.5	1.6	1.6	1.4	1.0	.7	.6	.7	.6
25.....			3.7	2.5	1.5	1.6	1.3	1.0	.7	.6	.6	.6
26.....			3.5	2.6	1.5	1.8	1.3	1.0	.7	.6	.6	.7
27.....			3.3	2.5	1.5	2.2	1.3	.9	.7	.6	.6	.7
28.....			3.2	2.4	1.5	2.6	1.3	.9	.7	.6	.6	.6
29.....			3.4	2.3	1.5	1.8	1.2	.9	.7	.6	.6	.7
30.....			6.4	2.3	1.8	1.6	1.4	.9	.6	.6	.6	.7
31.....			4.3		1.9		1.7	.9		.7		.6
1904												
1.....	0.6	0.9	1.1	1.5	1.2	1.45	.75	1.6	.6	.3	.3	.6
2.....	.6	.8	1.2	1.5	1.25	1.2	.7	.95	.55	.3	.3	.85
3.....	.7	.9	1.2	1.4	1.25	1.0	.7	.75	.55	.35	.4	1.05
4.....	.6	.9	1.2	1.35	1.3	1.0	.65	.75	.55	.35	.5	.6
5.....	.6	.8	1.0	1.3	1.2	.9	.9	1.0	.7	.3	.5	1.35
6.....	.6	.8	1.0	1.35	1.1	.9	.8	.95	.6	.3	.4	1.4
7.....	.7	.8	3.0	1.9	1.1	2.1	.7	1.1	.5	.3	.35	.75
8.....	.6	1.8	2.0	2.3	1.95	1.2	.75	1.7	.5	.3	.3	.5
9.....	.6	.9	1.6	2.1	1.8	.9	.9	1.25	.5	.3	.3	.6
10.....	.6	1.0	1.5	1.7	1.45	.9	.75	1.05	.5	.3	.3	.6
11.....	.8	1.2	1.6	1.65	1.3	.85	.7	1.45	.45	.3	.3	.55
12.....	.7	1.0	1.45	1.55	1.25	.9	1.2	1.1	.45	.3	.35	.5
13.....	.7	.9	1.3	1.5	1.2	.85	1.0	1.2	.45	.3	.55	.5
14.....	.7	.9	2.35	1.4	1.2	.8	.75	.95	.45	.3	.55	.4
15.....	.7	1.0	1.35	1.4	1.2	.8	.65	1.0	.4	.25	.5	.45
16.....	.7	.9	1.4	1.4	1.15	.75	.75	.85	.4	.25	.45	.4
17.....	1.3	.9	1.3	1.35	1.1	.75	.8	.75	.4	.25	.35	.55
18.....	1.0	.8	1.3	1.35	1.1	.7	.6	.7	.4	.25	.3	.5
19.....	.8	.9	1.3	1.3	1.1	.7	.6	.75	.4	.25	.3	.45
20.....	.7	2.0	1.3	1.25	1.15	.8	.55	.8	.35	.25	.3	.4
21.....	.7	2.0	2.25	1.3	1.0	.75	.6	.7	.4	.25	.35	.4
22.....	1.0	2.9	2.25	1.35	1.0	1.2	1.1	.6	.45	.25	.4	.4
23.....	1.7	2.2	3.6	1.25	1.0	.8	.75	.6	.4	.25	.65	.4
24.....	1.4	1.7	2.3	1.2	.9	.7	.7	.75	.35	.25	.4	.45
25.....	1.2	1.4	2.2	1.2	1.0	.65	.9	.7	.35	.25	.4	.75
26.....	1.1	1.3	1.95	1.35	.95	.7	.85	.7	.35	.3	.3	.6
27.....	.9	1.3	2.2	1.5	.9	.7	.65	.95	.35	.3	.3	1.5
28.....	1.0	1.2	1.85	1.35	.9	.7	1.0	.75	.4	.3	.3	2.25
29.....	.9	1.1	1.7	1.3	.9	1.2	.75	.65	.35	.3	.3	1.05
30.....	.9		1.6	1.2	.9	.85	.7	.6	.3	.3	.75	.3
31.....	.8		1.55		2.35		.75	.6		.3		.7

WATER POWERS OF GEORGIA

Daily gage height, in feet, of Ocoee River at McCays, Tenn.—Continued.

Day	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.
1905												
1	0.7	0.77	1.5	1.3	1.45	1.4	1.7	0.9	0.8	0.92	0.63	0.6
2	.7	.8	1.4	1.2	1.35	1.3	1.25	.82	1.7	.7	.6	.6
3	.7	.8	1.4	1.2	1.3	1.3	1.1	.8	1.1	.88	.6	4/6
4	.7	.75	1.4	1.2	1.5	1.25	1.0	.8	.92	1.2	.65	1.6
5	.63	1.0	1.3	1.4	1.4	1.2	1.0	.8	.8	.78	.62	1.4
6	.8	1.55	1.3	1.45	1.65	1.2	1.0	.75	.8	.68	.63	1.2
7	.5	1.25	1.4	1.4	1.7	1.2	1.0	.9	.8	.6	.62	1.2
8	.9	1.45	1.3	1.3	1.7	1.15	1.15	1.25	.8	.6	.6	3/6
9	.8	3.1	1.7	1.2	1.3	1.1	1.0	1.0	.8	.6	.6	3/4
10	.9	2.45	2.0	1.2	1.55	1.0	1.2	1.15	.72	.8	.6	2/4
11	.95	1.85	1.25	1.2	1.4	1.0	1.5	2.15	.75	3.3	.6	1.9
12	6.4	1.65	1.5	1.7	1.35	1.15	4.4	1.75	1.15	1.35	.6	1.65
13	3.5	1.7	1.55	1.35	1.3	1.1	2.0	1.65	.8	.95	.6	1.5
14	2.0	1.85	1.5	1.2	1.2	1.0	1.5	1.8	.73	.8	.6	1.85
15	1.1	1.75	1.4	1.35	1.55	1.5	1.3	1.95	.72	.82	.6	1.7
16	1.1	1.5	1.3	1.4	2.3	1.5	1.45	1.45	.72	.9	.6	1.6
17	1.1	1.5	1.3	1.2	1.3	1.65	1.3	1.4	.7	.8	.6	1.45
18	1.0	1.4	1.3	1.2	1.6	1.3	1.15	1.2	.7	.72	.6	1.4
19	1.0	1.3	1.25	1.2	1.5	1.3	1.4	1.1	.65	.68	.55	1.35
20	1.0	4.2	1.7	1.15	1.5	1.1	1.2	1.0	.7	.6	.8	1.7
21	.98	4.1	3.0	1.15	1.45	1.4	1.1	1.0	.7	.65	.75	2.7
22	.93	3.3	1.95	1.25	1.4	1.25	1.1	1.0	.62	.62	.6	2.0
23	.9	2.25	1.7	1.1	3.0	1.85	1.0	1.1	.6	.65	.6	2.2
24	.83	2.15	1.7	1.1	2.2	1.25	1.0	1.1	.6	.6	.72	2.0
25	.8	2.0	1.6	1.1	1.85	1.2	1.05	1.15	.6	.7	.7	1.7
26	.8	1.85	1.5	1.25	1.8	1.15	.95	1.4	.6	1.2	.62	1.6
27	.75	1.65	1.4	1.7	1.7	1.3	.9	1.0	.55	.85	.62	1.55
28	1.1	1.55	1.4	1.45	1.6	1.5	.9	.95	.55	.75	.6	1.5
29	1.1	1.35	1.5	1.5	1.8	2.15	.85	.55	.7	.65	1.7
30	.9	1.45	1.85	1.45	1.65	1.0	.8	.58	.7	.75	1.5
31	.85	1.3	1.5	1.0	.87	1.45

Rating table for Ocoee River at McCays, Tenn., from March 20, 1903, to December 31, 1905.^a

Gage height	Dis-charge						
<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>
0.20	200	1.30	655	2.30	1,275	3.60	2,200
.30	230	1.40	710	2.40	1,340	3.80	2,350
.40	262	1.50	767	2.50	1,410	4.00	2,500
.50	296	1.60	826	2.60	1,480	4.20	2,650
.60	332	1.70	887	2.70	1,550	4.40	2,800
.70	370	1.80	950	2.80	1,620	4.60	2,950
.80	411	1.90	1,015	2.90	1,690	4.80	3,100
.90	455	2.00	1,080	3.00	1,760	5.00	3,250
1.00	502	2.10	1,145	3.20	1,900	5.50	3,650
1.10	551	2.20	1,210	3.40	2,050	6.00	4,050
1.20	602						

^a This table is based on 18 discharge measurements made during 1903-1905. It is well defined between gage heights 0.25 foot and 3.4 feet.

HIWASSEE DRAINAGE BASIN, STREAM FLOW

Rating table for Ocoee River at McCays, Tenn., for 1906.

Gage height	Dis-charge						
<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>	<i>Feet</i>	<i>Sec.-ft.</i>
1.20	640	2.30	1,315	3.40	2,075	5.00	3,360
1.30	695	2.40	1,380	3.50	2,150	5.20	3,540
1.40	750	2.50	1,445	3.60	2,225	5.40	3,730
1.50	810	2.60	1,510	3.70	2,300	5.60	3,930
1.60	870	2.70	1,580	3.80	2,375	5.80	4,130
1.70	930	2.80	1,650	3.90	2,450	6.00	4,330
1.80	990	2.90	1,720	4.00	2,530	6.20	4,530
1.90	1,055	3.00	1,790	4.20	2,690	6.40	4,740
2.00	1,120	3.10	1,860	4.40	2,850	6.60	4,960
2.10	1,185	3.20	1,930	4.60	3,015	6.80	5,180
2.20	1,250	3.30	2,000	4.80	3,185	7.00	5,400

NOTE.—The above table is applicable only for open-channel conditions. It is based on 4 discharge measurements made during 1906 and on the general form of the earlier curves. It is well defined between gage height 1.0 foot and 3.5 feet. Above gage height 6.5 feet the rating curve is a tangent, the difference being 110 per tenth.

Estimated monthly discharge of Ocoee River at McCays, Tenn.

[Drainage area, 374 square miles.]

Month	Discharge in second-feet			Run-off	
	Maximum	Minimum	Mean	Sec.-ft. per sq. mile	Depth in inches
1903					
March 22-31.....	4,370	1,900	2,634	7.05	0.787
April.....	2,800	1,275	1,772	4.74	5.29
May.....	1,275	767	982	2.63	3.03
June.....	2,725	826	1,806	3.49	3.89
July.....	4,290	602	986	2.50	2.88
August.....	1,340	455	642	1.72	1.98
September.....	655	332	419	1.12	1.25
October.....	767	332	365	.976	1.13
November.....	602	332	398	1.06	1.18
December.....	455	297	340	.909	1.05
1904					
January.....	887	332	435	1.16	1.34
February.....	1,690	411	630	1.68	1.81
March.....	2,200	502	922	2.47	2.85
April.....	1,275	602	745	1.99	2.22
May.....	1,308	455	610	1.63	1.88
June.....	1,145	351	475	1.27	1.42
July.....	602	314	403	1.08	1.24
August.....	887	332	470	1.26	1.45
September.....	370	230	279	.746	.832
October.....	246	215	226	.604	.696
November.....	390	230	261	.698	.779
December.....	1,242	262	407	1.09	1.26
The year.....	2,200	215	488	1.31	17.78
1905					
January.....	4,370	296	649	1.74	2.01
February.....	2,650	390	1,012	2.71	2.82
March.....	1,760	628	786	2.10	2.42
April.....	982	551	663	1.77	1.98
May.....	1,760	602	859	2.30	2.65
June.....	982	502	661	1.77	1.98
July.....	2,800	455	687	1.84	2.12
August.....	1,178	390	592	1.58	1.82
September.....	887	314	401	1.07	1.19
October.....	1,975	332	459	1.23	1.42
November.....	411	314	344	.920	1.03
December.....	2,950	332	991	2.65	3.06
The year.....	4,370	296	675	1.81	24.50

WATER POWERS OF GEORGIA

Estimated monthly discharge of Ocoee River at McCays, Tenn.—Continued.

Month	Discharge in second-feet			Run-off	
	Maximum	Minimum	Mean	Sec.-ft. per sq. mile	Depth in inches
1906					
January.....	4,850	695	1,450	3.88	4.47
February.....	1,180	750	896	2.40	2.50
March.....	3,180	810	1,280	3.42	3.94
April.....	1,720	900	1,160	3.10	3.46
May.....	1,150	640	853	2.28	2.63
June.....	2,530	722	1,050	2.81	3.14
July.....	2,850	695	1,300	3.48	4.01
August.....	2,220	900	1,170	3.13	3.61
September.....	3,020	810	1,200	3.21	3.58
October.....	2,340	870	1,330	3.56	4.10
November.....	18,000	750	1,920	5.13	5.72
December.....	2,850	930	1,150	3.16	3.64
The year.....	18,000	640	1,230	3.29	44.80

NOTE.—Values for 1906 are excellent

FIGHTINGTOWN CREEK AT M'CAYS, TENN.

This station was established August 27, 1904, for the purpose of making miscellaneous measurements. It is located about one-half mile above the mouth of the creek, which flows into Ocoee River about one-half mile below the gaging station at McCays, Tenn. Fightingtown Creek is in Georgia, but its mouth is in Tennessee.

Both banks are open cultivated lands, which will probably overflow. The bed is sandy, and will probably change much. Discharge measurements are made by means of a boat or by wading. The bench mark is two small nails driven into the largest of a cluster of small maple sprouts on the right bank, 40 feet above the mouth of a small branch; elevation, 5.00 feet above datum of assumed gage.

Discharge measurements of Fightingtown Creek at McCays, Tenn.

Date	Gage height	Dis-charge	Date	Gage height	Dis-charge
1904			1905		
May 12.....	<i>Feet</i> 1.25	<i>Sec.-ft.</i> 122	June 20.....	<i>Feet</i> 2.00	<i>Sec.-ft.</i> 123
August 27.....	1.72	79	October 6.....	1.61	59
October 11.....	1.12	40			

^a Gage height given is for the Ocoee River at McCays.

MISCELLANEOUS MEASUREMENTS, HIWASSEE RIVER DRAINAGE
BASIN IN GEORGIA

Fightingtown Creek.—This stream is a tributary of Toccoa River. A measurement was made October 4, 1904, at the Galloway bridge, near Blueridge, above Horseshoe Bend.

Width, 33 feet; area, 25 square feet; mean velocity, 1 foot per second; discharge, 25 second-feet.

Toccoa River.—This stream is a tributary of Hiwassee River, its name becoming Ocoee River in the State of Tennessee. A measurement was made October 3, 1904, from a small boat at Bench Leg Ford, near Blueridge, 1 mile below the Morganton road bridge, and one-fourth mile below the mouth of Weaver Creek.

Width, 110 feet; area, 264 square feet; mean velocity, 0.65 foot per second; discharge, 172 second-feet.

RIVER SURVEYS IN HIWASSEE RIVER DRAINAGE
BASIN

HIWASSEE RIVER

The elevations in the following list are based on an aluminum tablet marked "1984 ATLANTA" at the northeast corner of front vestibule of Towns County court-house, Hiwassee, the elevation of which is accepted as 1,983.634 feet above sea level.

The leveling is adjusted with flying levels on Nottely River to accord with the 1903 adjusted elevation of the primary bench marks at Blairsville and Hiwassee. From the mouth of the Nottely to Apalachia the leveling is a single spur line.

The leveling was done in 1903 by Thomas B. O'Hagan, levelman, under the direction of Carroll Caldwell, field assistant, United States Geological Survey.

Elevations on Hiwassee River from Hiwassee, Ga., to Apalachia, N. C.

Distance	Description of points	Elevation above sea level
Miles		Feet
0.0	Hiwassee, Towns County court-house, at northeast corner of front vestibule, aluminum tablet marked "ATLANTA 1984".....	1,983.634
0.3	Hiddon Bridge, 300 ft. north, edge of county road, white oak tree, nail in west side.....	1,882.30
0.3	Hiddon Bridge, 300 feet north of, water surface.....	1,865
0.3	High-water mark.....	1,882
0.3	Bridge, water surface.....	1,881
0.8	Town Branch, mouth, water surface.....	1,862
1.6	25 feet north of bridge, 20 feet west of river, point on rock bluff.....	1,871.36
1.6	Bridge, water surface.....	1,857
1.6	Bridge floor.....	1,874.3
1.6	High-water mark.....	1,876
1.7	Hog Creek, water surface.....	1,855
1.9	Small rapids, water surface.....	1,854
2.2	Bells Creek, 900 feet north, on east side of river, triple maple tree, nail in side of.....	1,854.14
2.2	Bells Creek, mouth of, water surface.....	1,853
2.3	Small falls, head, water surface.....	1,851
2.3	Small falls, foot, water surface.....	1,847
2.8	Water surface.....	1,838
3.4	Sally Ford, mouth, water surface.....	1,836
3.6	Hog Creek, mouth, water surface.....	1,833
3.7	Water surface.....	1,830
3.8	Gibson Creek, mouth, water surface.....	1,829
4.8	Long Bullet Creek, mouth, water surface.....	1,825
4.8	Pendleton Ford, 25 feet northwest, nail in side of dead stump.....	1,838.2
4.8	Pendleton Ford, water surface.....	1,823
4.8	High-water mark.....	1,835
5.2	Sneaking Creek, mouth, water surface.....	1,820
5.5	Water surface.....	1,819
5.6	Ford, 75 feet northwest, 10 feet west of road, nail in red-oak tree.....	1,830.62
6.1	15 feet north of river, point on rock.....	1,824.63
6.2	Water surface.....	1,811
6.4	Stream, mouth, water surface.....	1,809
6.4	Rough ford, 15 feet north of river, rock bluff, point on rock.....	1,816.34
6.9	Water surface.....	1,807
7.2	Shooting Creek, mouth, water surface.....	1,804
7.9	Barnard Bridge, northeast abutment, point on top.....	1,818.31
7.9	Barnard Bridge, water surface.....	1,797
7.9	Barnard Bridge, bridge floor.....	1,819.7
7.9	Barnard Bridge, high-water mark.....	1,814
8.3	Ford, water surface.....	1,794
8.3	Ford, 50 feet south of ford, 15 feet north of river, nail in side of dogwood tree.....	1,807.39
8.8	Water surface.....	1,790
9.0	Head of island, water surface.....	1,789
9.2	Hyatts Mill Creek, mouth, water surface.....	1,787
9.4	Herbert Ford, on south edge of river at, nail in side of birch tree.....	1,791.19
9.4	High water mark.....	1,799
9.4	Water surface.....	1,787
.....	Blair Creek, mouth, water surface.....	1,787
10.0	12 feet west of river, point on rock.....	1,796.74
10.0	Water surface.....	1,782
10.8	Town Creek, mouth, water surface.....	1,778
11.5	Tusquite Bridge, 250 feet west, on edge of river, nail in root of birch tree.....	1,778.9
11.5	Tusquite Bridge, water surface.....	1,774
11.5	High-water mark.....	1,794
11.8	Martin or Quail Creek, mouth, water surface.....	1,774
12.2	Water surface.....	1,773
12.6	Tusquite Creek, mouth, 150 feet northwest, 10 feet west of river, nail in root of birch tree.....	1,777.93
12.6	Water surface.....	1,771
12.8	Rapids, water surface.....	1,767
13.3	Below rapids, water surface.....	1,760
13.6	Stream, mouth, water surface.....	1,759
14.0	Martin Ford, 125 feet south, on west edge of river, at fish trap, nail in root of birch.....	1,757.74
14.0	Martin Ford, water surface.....	1,756
14.8	Water surface.....	1,742
14.9	Leatherwood Ford, 25 feet northwest, nail in walnut tree.....	1,749.19
14.9	Leatherwood Ford, water surface.....	1,741
16.0	Allbon Creek, mouth, water surface.....	1,741
16.4	Water surface.....	1,722
17.0	Fire Creek, mouth, water surface.....	1,712
17.3	Stream, mouth, water surface.....	1,708
17.5	Passamore Ford, east side of river, in center of ford road, nail in root of gum tree.....	1,709.34
17.5	Passamore Ford, water surface.....	1,707
17.7	Cloud Fire Creek, mouth, water surface.....	1,700

HIWASSEE DRAINAGE BASIN, RIVER SURVEYS

413

Elevations on Hiwassee River from Hiwassee, Ga., to Apalachia, N. C.—Con'd.

Distance	Description of points	Elevation above sea level
<i>Miles</i>		<i>Feet</i>
18.3	Water surface.....	1,690
18.8	Betty Creek, mouth, water surface.....	1,685
19.1	Head of island, water surface.....	1,679
19.4	Sweetwater Creek, mouth, water surface.....	1,673
19.6	Stream, mouth, water surface.....	1,668
20.0	Shallow Ford, 15 feet east of river, nail in side of birch tree.....	1,667.14
20.0	Water surface.....	1,663
20.5	Water surface.....	1,659
20.9	End of island.....	1,649
21.0	Creek, mouth.....	1,642
21.4	Water surface.....	1,632
21.5	Water surface.....	1,629
21.8	Backwater of Cherokee dam, 1,500 feet from, at small rapids, water surface.....	1,624
22.0	Top of Cherokee dam, water surface.....	1,625
22.0	Foot of Cherokee dam, water surface.....	1,614
22.0	Cherokee dam, 25 feet southwest, point on rock.....	1,616.59
22.0	Water surface.....	1,609
22.2	Canewater Ford, water surface.....	1,606
24.0	Rocky Branch, mouth, water surface.....	1,591.4
24.0	North edge of river, nail in side of birch tree.....	1,594.79
24.1	Small rapids, foot, water surface.....	1,590
24.7	Stream mouth, water surface.....	1,586
25.2	Brasstown Creek, mouth, water surface.....	1,576
26.2	Island Ford, 700 feet east, south side of river, point on rock.....	1,666.56
27.6	Peachtree Creek, mouth, water surface.....	1,550
28.0	Horseshoe Ford, water surface.....	1,549
28.0	South side of ford, nail in side of beech tree.....	1,558.06
29.5	20 feet north of river, north side of road, point on rock.....	1,548.7
29.9	Scott Branch, mouth, water surface.....	1,539
30.4	Stream, mouth, water surface.....	1,529
31.3	Martins Creek, mouth, water surface.....	1,520
31.6	Twin beech tree, nail in root.....	1,518.12
31.8	Stream, mouth, water surface.....	1,513
32.1	Murphy, N. C., iron bridge, south abutment, point on rock.....	1,518.3
32.1	Murphy, N. C., iron bridge, water surface.....	1,512
32.1	Bridge floor.....	1,531.9
32.1	High-water mark.....	1,529
32.5	Walley River, mouth, west shore, 20 feet north of, in water, point on rock.....	1,506.85
32.5	Water surface.....	1,506
34.0	Water surface.....	1,491
34.9	Laurel Creek, mouth, water surface.....	1,474
35.3	Johnson Ford, 8 feet south of river, nail in root of large birch tree.....	1,471.95
35.3	Johnson Ford, water surface.....	1,469
35.3	High-water mark.....	1,481
35.9	Hangingsdog Creek, mouth, water surface.....	1,462
36.5	Water surface.....	1,459
37.0	Nottely River, mouth, water surface.....	1,455
37.0	Island projecting between the two rivers, nail in root of birch tree.....	1,459.4
37.0	Nottely River, mouth, south side, nail in root of willow tree.....	1,456.93
38.0	Small rapids, water surface.....	1,448
39.0	Beech Creek, water surface.....	1,438
40.5	Ford, water surface.....	1,425
40.5	Shallow ford, 40 feet southwest, honey bee tree, nail in root.....	1,431.59
41.2	Water surface.....	1,418
42.0	Grape Creek, mouth, water surface.....	1,416
42.5	Small shoals, head, water surface.....	1,415
42.5	Foot of small shoals, water surface.....	1,410
42.9	Water surface.....	1,406
44.1	Persimmon Creek, mouth, water surface.....	1,391
44.8	Foot of large shoals, point on rock.....	1,390.24
44.8	Water surface.....	1,381
45.0	Head of small shoals.....	1,379
46.2	Dennest Creek, mouth, water surface.....	1,365
46.9	Point on rock.....	1,363.58
48.0	Shoals, water surface.....	1,346
48.3	Robertson Ferry, 100 feet below, point on rock.....	1,344.23
48.3	Robertson Ferry, water surface.....	1,343
49.9	Shoals, water surface.....	1,340
50.4	Creek, mouth, water surface.....	1,332
50.6	Water surface.....	1,329
51.2	Chamber Creek, mouth, water surface.....	1,324
51.2	20 feet north of bank, point on rock.....	1,327.94
51.3	Opposite island, water surface.....	1,315
52.5	Beaverdam Creek, mouth, water surface.....	1,304

WATER POWERS OF GEORGIA

Elevations on Hiwassee River from Hiwassee, Ga., to Apalachia, N. C.—Con'd.

Distance	Description of points	Elevation above sea level
<i>Miles</i>		<i>Feet</i>
53.0	Opposite island, water surface.....	1,296
53.9	Laurel Creek, mouth, water surface.....	1,290
54.3	Shoals, water surface.....	1,285
54.3	Foot of shoals, water surface.....	1,277
54.8	Water surface.....	1,269
55.2	Rapids, water surface.....	1,259
56.9	Anderson Creek, mouth, water surface.....	1,248
57.9	Water surface (15 feet above low water).....	1,240
58.5	Shallow ford, 40 feet south, nail in root of gum tree.....	1,239.67
58.5	Water surface.....	1,234
58.5	High-water mark.....	1,241
58.6	Foot of small shoals, water surface.....	1,227
58.9	Shoals Creek, mouth, water surface.....	1,227
59.7	Foot of small rapids, water surface.....	1,218
60.9	Stream, mouth, water surface.....	1,198
61.1	Cane Creek, mouth, water surface.....	1,195
63.0	Water surface.....	1,178
64.2	Camp Creek, mouth, water surface.....	1,175
65.0	Kilpatrick Ferry, 12 feet south, willow tree.....	1,175.14
65.0	Kilpatrick Ferry, water surface.....	1,172
65.2	Taylor Ferry, 60 feet northwest, edge of bank, point on large rock.....	1,169.58
65.2	Taylor Ferry, water surface.....	1,166
66.8	Apalachia, N. C., Sugar Creek, mouth, 100 feet from post-office, 5 feet north of bank of river, triple willow tree.....	1,161.58
66.8	Apalachia, N. C., water surface.....	1,158.2
66.8	High-water mark.....	1,168

SURVEY OF NOTTELY RIVER

The elevations in the following list are based upon a bronze tablet marked "1892 ATLANTA" in the foundation wall at the northwest corner of Union County Court-House, Blairsville, the elevation of which is accepted as 1,891.536 feet above mean sea level. The leveling is adjusted with the Hiwassee River flying levels to accord with the 1903 adjusted elevation of primary bench marks at Blairsville and Hiwassee. The leveling was done in 1903 by Thomas B. O'Hagan, levelman, under the direction of Carroll Caldwell, field assistant, United States Geological Survey.

Elevations on Nottely River from mouth to Blairsville.

Distance	Description of points	Elevation above sea level
<i>Miles</i>		<i>Feet</i>
0.0	Junction of Nottely and Hiwassee rivers, on point of peninsula, nail in side of birch tree.....	1,459.4
0.0	Water surface.....	1,454.52
0.3	At lower ford, water surface.....	1,459
0.3	75 feet north of lower ford, nail in hickory tree.....	1,466.77
1.0	High-water mark.....	1,471
1.0	Upper ford, 50 feet south, nail in root of oak tree.....	1,474.59
1.0	Water surface.....	1,467
1.3	Water surface.....	1,477
1.5	Water surface.....	1,472
1.5	Water surface.....	1,478
1.8	Deep ford, 25 feet north, nail in root of black oak.....	1,487.56
1.8	Water surface.....	1,483
2.0	Water surface.....	1,489

Elevations on Nottely River from mouth to Blairsville—Continued.

Distance	Description of points	Elevation above sea level
<i>Miles</i>		<i>Feet</i>
2.3	High water.....	1,499
2.4	Head of shoals, water surface.....	1,491
2.6	Water surface(rain during night raised water 1.3 feet, lower water surface 1,492.67).....	1,498
2.9	Hall Bridge, 20 feet west, nail in side of apple tree.....	1,500.2
2.9	Hall Bridge, water surface.....	1,498
2.9	High water.....	1,503
4.2	Davis Ford, 20 feet northwest, nail in side of maple tree.....	1,504.43
4.2	Davis Ford, water surface.....	1,499
4.9	Surface of water on rock.....	1,502
5.2	Mouth of Combs Creek, water surface.....	1,505
5.4	Water surface.....	1,505
5.5	Hall Ford, north edge of river, nail in side of water birch tree.....	1,513.02
5.5	Water surface.....	1,505
5.5	High water.....	1,521
5.9	Mouth of branch, water surface.....	1,512
6.0	Water surface.....	1,521
6.6	Water surface.....	1,526
6.9	Opposite island, water surface.....	1,534
7.0	Mouth of Rocky Branch, water surface.....	1,535
7.1	Near old mill, water surface.....	1,538
7.5	Water surface.....	1,542
8.6	Nottely Bridge, 1,800 feet north in old field near barn, nail in side of persimmon tree.....	1,559.54
8.6	Nottely Bridge, water surface.....	1,544
8.9	Nottely Bridge, 100 feet west, 5 feet south of road, nail in side of black oak tree.....	1,560.13
9.6	Water surface.....	1,547
10.5	Mouth of Johnson Branch, water surface.....	1,548
10.9	Water surface.....	1,551
11.5	Jacks Creek, 906 feet south, in bend of river 600 feet west and 600 feet north, in cornfield, nail in root of dead peachtree.....	1,571.83
11.5	Water surface.....	1,554
11.7	Water surface.....	1,555
12.0	Anderson Bridge, 50 feet west, nail in side of sycamore tree.....	1,565.78
12.0	Anderson Bridge, water surface.....	1,556
12.0	High water.....	1,575
12.2	Water surface.....	1,560
12.9	Mouth of branch, water surface.....	1,561
13.3	Ford, 20 feet northwest, nail in side of birch stump.....	1,574.02
13.3	Water surface.....	1,562
13.3	High water.....	1,577
14.2	Water surface.....	1,565
15.1	Water surface.....	1,568
15.4	Landermilk Ford, 1.4 miles below, opposite old fish dam, 50 feet west of river, near small branch, nail in root of black oak tree.....	1,586.77
15.4	Water surface.....	1,573
16.0	Water surface.....	1,580
16.8	Landermilk Ford, 100 feet southwest, 20 feet north of road, nail in root of apple tree.....	1,598.19
16.8	Water surface.....	1,583
16.8	High water.....	1,599
17.2	Mouth of Butler Creek, water surface.....	1,585
17.7	Below fish dam, water surface.....	1,587
17.8	Mouth of Moccasin Creek, water surface.....	1,588
17.8	Moccasin Creek, 200 feet south, 35 feet east of river, east side of road, nail in root of red oak tree.....	1,602.87
18.5	Mouth of branch, water surface.....	1,591
18.6	Mouth of Dooleys Creek, water surface.....	1,591
18.9	Thompson Bridge, 250 feet south, 100 feet southwest of road, nail in root of red oak tree.....	1,611.01
18.9	Water surface.....	1,592
18.9	High water.....	1,601.53
19.1	Water surface.....	1,599
19.6	In shoals, water surface.....	1,611
20.2	Above fish dam, water surface.....	1,617
20.4	Head of fish dam, water surface.....	1,619
20.4	Foot of island, in shoals, water surface.....	1,624
21.0	Water surface.....	1,630
21.4	Chapman Ford, 150 feet north, 2 feet east of road, nail in root of walnut tree.....	1,645.81
21.4	Water surface.....	1,634
21.4	High water.....	1,644
21.4	Just blow fish dam, water surface.....	1,638
21.8	Mouth of Camp Creek, water surface.....	1,639
21.9	Above shoals, water surface.....	1,652
22.6	Mouth of Weasel Creek, water surface.....	1,655
23.0	Mouth of branch, water surface.....	1,656
23.6	In shoals, water surface.....	1,657
23.8		

Elevations on Nottely River from mouth to Blairsville—Continued.

Distance	Description of points	Elevation above sea level
<i>Miles</i>		<i>Feet</i>
23.8	Chamber Ford, 0.4 mile northwest, northeast side of river, point on edge of rock	1,675.88
24.2	Chamber Ford, 200 feet west, nail in root of walnut tree.....	1,671.49
24.2	Water surface.....	1,661
24.2	High water.....	1,678
25.0	Above small shoals, water surface.....	1,669
25.2	Chastain Ford, 50 feet west, nail in side of walnut tree.....	1,683.45
25.2	Water surface.....	1,669
25.5	Foot of large shoals, water surface.....	1,675
25.8	Mouth of Ivy Creek, head of shoals, water surface.....	1,680
26.3	Near house, water surface.....	1,685
26.6	Majners Ford, 75 feet west, on edge of bank, nail in side of corn-bean tree.....	1,690.8
26.6	Water surface.....	1,687
26.8	Meadow Ford, 15 feet north, nail in root of beech tree.....	1,699.17
26.8	Water surface.....	1,689
26.8	High water.....	1,708
27.3	Huggins Ford, 25 feet north, nail in side of corn-bean tree.....	1,707.82
27.3	Water surface.....	1,692
27.5	Shoals.....	1,694
27.8	Water surface.....	1,698
27.9	Above shoals, water surface.....	1,698
28.4	Morgan Ford, 40 feet north, red oak tree, water surface.....	1,714
28.4	Water surface.....	1,702
29.0	Mouth of Young Cour Creek, water surface.....	1,699
29.0	Mouth of Castile Creek, water surface.....	1,709
29.1	Castile Creek, 1,600 feet above, on rock, edge of river, point on rock.....	1,714.2
29.4	Above rapids, water surface.....	1,715
30.0	Above fish dam, water surface.....	1,718
30.3	McBee Ford, 60 feet north, nail in side of red oak tree.....	1,734.37
30.3	Water surface.....	1,721
30.8	Above branch, water surface.....	1,723
31.1	Mouth of Reeses Creek, water surface.....	1,724
31.4	Youngs Ford, 80 feet southwest, red oak tree.....	1,741.02
31.4	Water surface.....	1,727
31.5	Millburn Creek, just below, water surface.....	1,730
31.9	At canal, foot, water surface.....	1,732
31.9	Head of canal, water surface.....	1,735
31.9	Canal cut (cut has a drop of 3.6 feet), 50 feet northeast of river, 15 feet south-west of ford, nail in foot of red oak tree.....	1,741.26
32.2	Above small rapids, water surface.....	1,739
33.0	Mouth of Creek, water surface.....	1,743
33.6	Watkins Bridge, 375 feet above, north edge of river, point on rock.....	1,747.54
33.6	Water surface.....	1,747
33.6	Jarrett mill dam, foot of.....	1,748
33.6	Jarrett mill dam head, (Jarrett mill dam has a drop of 3.79 feet).....	1,752
34.5	Reeds Ford, 150 feet east, nail in root of walnut tree.....	1,766.24
34.5	Water surface.....	1,755
35.0	Above small rapids, water surface.....	1,760
35.9	Blairsville Bridge, 100 feet southeast, mouth of Butternut Creek, 15 feet north, nail in side of red oak tree.....	1,775.94
35.9	Water surface.....	1,769
35.9	High water.....	1,783
37.2	Blairsville court-house, Union County, in wall on west side of building, bronze tablet.....	1,891.536

SURVEY OF TOCCOA RIVER

The elevations in the following list are based upon an aluminum tablet at the Washington street entrance of the State capitol building at Atlanta, marked "1050 M. C.," the elevation of which is now accepted as 1049.546 feet above sea level. They accord with the 1903 adjusted elevations of primary bench marks near Morganton and Shallow Ford. The section, Shallow Ford to McCays Ferry, is a single spur line.

The leveling was done in 1903 by Thomas B. O'Hagan, level-

man, under the direction of Carroll Caldwell, field assistant United States Geological Survey.

Elevations on Toccoa River from Butts Bridge down to the Tennessee line.

Dis- tance	Description of points	Elevation above sea level
<i>Miles</i>		<i>Feet</i>
0.0	Morganton (3 miles east of Dial), forks of Morgan and Ellijay road, in large marble rock, copper bolt marked "1981".....	1,947.821
1.5	Butts Bridge, east side, nail in top of abutment.....	1,874.25
1.5	Butts Bridge, water surface.....	1,858
1.5	High-water mark.....	1,870
2.0	Pigeon Creek, 550 feet east; north side of road, 60 feet north of river, point on rock.....	1,858.35
2.0	Mouth of Pigeon Creek, water surface.....	1,849
2.3	Between rapids, water surface.....	1,845
2.5	Foot of shoals, water surface.....	1,840
2.9	Mouth of Weeks Creek, foot of rapids, water surface.....	1,830
3.1	Dial post-office, Van Zants Bridge, 100 feet north, east side of road, nail in root of red-oak tree.....	1,844.68
3.1	Water surface.....	1,828
3.1	High-water mark.....	1,851
4.0	Mouth of Noontootly Creek, water surface.....	1,825
4.0	Mouth of branch, water surface.....	1,821
4.2	Rogers Ford, 50 feet west, nail in root of tree.....	1,825.14
4.2	Water surface.....	1,820
4.7	Water surface.....	1,815
5.1	In rapids water surface.....	1,813
5.2	Big Creek Ford, 225 feet southeast; 50 feet south of river, nail in root of white-oak tree.....	1,817.74
5.2	Water surface.....	1,810
5.2	In rapids, water surface.....	1,809
5.7	Above rapids, water surface.....	1,802
5.9	Below fish dam, water surface.....	1,799
6.1	Head of shoals, water surface.....	1,795
6.4	Foot of shoals, water surface.....	1,791
6.4	Water surface.....	1,790
7.0	Water surface.....	1,782
7.1	Shallow ford, 1 mile north, north side of road in large rock, copper bolt marked "1859".....	1,826.489

SINGLE FLYING LEVEL SPUR LINE TO M'CAYS FERRY.

7.1	Below rapids, water surface.....	1,779
7.6	In rapids, water surface.....	1,769
8.1	Shallow ford, 100 feet north, nail in root of red oak.....	1,774.93
8.1	Water surface.....	1,763
8.1	High-water mark.....	1,774
8.3	In rapids, water surface.....	1,758
8.6	Water surface.....	1,755
8.8	Mouth of Stanley Creek, water surface.....	1,752
9.1	Rapids, water surface.....	1,747
9.3	Mouth of stream, water surface.....	1,743
9.5	Below rapids, water surface.....	1,738
9.9	Stanley Creek, 1 mile northwest, opposite island, north side of river, point on rock.....	1,738.77
10.0	In rapids, water surface.....	1,729
10.2	Opposite falls in river, 50 feet north of first falls, point on large rock.....	1,744.02
10.2	Head of falls, water surface.....	1,728
10.2	Foot of falls, water surface.....	1,719
10.7	Mouth of branch, water surface.....	1,717
11.0	Below rapids, water surface.....	1,709
11.2	Mouth of Flat Creek, water surface.....	1,705
11.5	In rapids, water surface.....	1,691
11.6	Water surface.....	1,690
11.8	Head of long shoals, water surface.....	1,689
11.8	Rock cliff, south side of river, opposite large shoals, point in side of.....	1,692.11
11.9	Head of island, in shoals, water surface.....	1,679
12.0	Foot of island, in shoals, water surface.....	1,677
12.9	In shoals, water surface.....	1,665
13.3	Foot of large shoals, water surface.....	1,659
13.4	Below rapids, head of more shoals, water surface.....	1,656
13.4	In rapids, water surface.....	1,646
14.0	Foot of shoals, water surface.....	1,640
14.6	Mouth of Persimmon Creek, water surface.....	1,633
14.6	Persimmon Creek, 300 feet east; west side of river, nail in root of large dead stump.....	1,638.06
14.7	Below fish dam, water surface.....	1,629
15.2	Mouth of stream, water surface.....	1,624
15.4	Mouth of Wilsco Creek, water surface.....	1,624
15.8	In shoals, water surface.....	1,616
16.0	Foot of shoals, water surface.....	1,609
16.8	In rapids, water surface.....	1,602

WATER POWERS OF GEORGIA

Elevations on Toccoa River from Butts Bridge down to the Tennessee line—Con.

Dis- tance	Description of points	Elevation above sea level
<i>Miles</i>		<i>Feet</i>
16.8	Wilsco Creek, 1.5 miles west; rock cliff, 18 feet north of river, point on very large rock.....	1,608.96
16.9	In shoals, water surface.....	1,600
17.1	Foot of shoals, water surface.....	1,596
17.3	Tarpley Ford, water surface.....	1,593
17.3	Tarpley Ford, 20 feet west of; nail in root of beech tree.....	1,598.30
17.6	In rapids, water surface.....	1,589
18.2	Mouth of creek, water surface.....	1,576
18.3	Water surface.....	1,571
18.8	Mouth of creek, water surface.....	1,568
19.0	Mouth of Bullfrog Creek, water surface.....	1,565
19.6	Water surface.....	1,559
20.0	Mouth of Charlie Creek, water surface.....	1,555
20.0	Lovingood Ford, 300 feet northwest, nail in side of walnut tree.....	1,564.61
20.0	Water surface.....	1,554
20.0	High-water mark.....	1,569
21.5	Mouth of Starr Creek, water surface.....	1,550
21.6	Below fish dam, water surface.....	1,548
22.0	Mouth of Rogers Branch, water surface.....	1,574
22.4	Toccoa Bridge, water surface.....	1,546
22.4	Toccoa Bridge, 10 feet east, nail in root of beech tree.....	1,557.64
22.9	Mouth of spring stream, water surface.....	1,540
23.5	Below small rapids, water surface.....	1,539
23.6	Mouth of Weavers Creek, water surface.....	1,538
23.9	Benchlog Ford, 20 feet northwest, nail in side of beech tree.....	1,543.47
23.9	Water surface.....	1,538
25.2	Large bend in river, water surface.....	1,528
25.5	Atlanta, Knoxville and Northern Railroad bridge, east side of bridge abutment, point on rock.....	1,536.79
25.5	Water surface.....	1,526
25.5	High-water mark.....	1,541
26.6	Mouth of branch, water surface.....	1,519
26.8	Harts Ford, 100 feet west, stump on edge of bank at canoe landing, nail in side of.....	1,521.90
26.8	Water surface.....	1,516
28.0	Water surface.....	1,510
28.8	Baker Ford, 100 feet southwest, on edge of bank, nail in side of birch tree.....	1,515
28.8	Water surface.....	1,507
29.6	Water surface.....	1,504
30.0	Bend of river, water surface.....	1,502
30.2	Water surface.....	1,498
30.9	Mouth of Sugar Creek, water surface.....	1,494
30.9	Sugar Creek Railroad bridge abutment, point in center of east side of bridge.....	1,508.32
31.2	Below Calloway Ford, water surface.....	1,592
31.5	In shoals, water surface.....	1,589
32.1	200 feet northwest of ford, 4 feet southeast of Atlanta, Knoxville and Northern Railroad track, nail in side peach tree.....	1,562.69
32.1	Water surface.....	1,484
32.5	Canoe landing, water surface.....	1,479
32.8	Hothouse Creek, mouth of, water surface.....	1,476
33.7	Foot of small shoals, near island, water surface.....	1,467
34.0	Mouth of Barker Creek, water surface.....	1,464
34.5	Kyle post-office, 600 feet east, Atlanta, Knoxville and Northern Railroad bridge over Barkers Creek, on southeast end of end bolt.....	1,482.43
34.6	Kyle post-office, 40 feet south, in front of Queen Brothers' store, pile supporting platform, nail in top of.....	1,488.62
34.6	Kyle Ford, water surface.....	1,468
35.0	Below rapids, water surface.....	1,458
35.4	Mouth of Wolf Creek, water surface.....	1,455
35.8	Atlanta, Knoxville and Northern Railroad bridge over Ocoee River, east side of bridge, point on abutment.....	1,471.98
35.8	Water surface.....	1,452
36.1	In bend of river, water surface.....	1,450
36.3	Dillbeck Ford, north edge of river, nail in side of dead birch tree.....	1,451.87
36.3	Water surface.....	1,447
37.5	McCays post-office, Polk County, Tenn., rock supporting southwest corner of, point on.....	1,468.07
37.5	McCays Ferry, north side of river, pile supporting swinging bridge, cartridge shell in top.....	1,460.15
37.5	Water surface.....	1,444
37.5	High-water mark.....	1,469

INDEX

	Page		Page
A			
Adderhold Bridge, discharge data at	377	Augusta, elevations on Tugaloo	
Agricola, discharge data near	114-115	River from head to	85-92
Alaculsy, discharge data near	379	Water power at	100
Albany, discharge data near	279-286, 287-289, 292-294, 297	Austell, discharge data near,	264-266, 303
Alcovy River, discharge data on		B	
Elevations on	146-153, 202	Ballground, discharge data near,	
Survey on	214	323-324, 341-342	
Water power on	213-214	Barnes Shoals, water power at,	219-220
Almon, discharge data at and near		Barnett Shoals, discharge data at	
140-145, 206		160-162	
Altamaha River basin, description		Water power at	223
of	116-117	Beaverdam Creek (of Oconee Riv-	
Discharge data in	117-207	er), discharge data on	202
Source and course of	116	Beaverdam Creek (of Soque Riv-	
Surveys in	207-218	er), discharge data on	296
Water power in	219-223	Berner, discharge data near	204
Amicalola River, discharge data on		Big Cedar Creek, discharge data	
341-342		on	376-378
Water power on	384	Big Potato Creek, discharge data	
Annistown, discharge data at	203	on	286-287, 297
Annistown Shoal, water power at	221	Water power on	322
Anthony Shoals, water power at	101	Blackshear, discharge data near	223
Apalachee River, discharge data on		Blairsville, elevations on Nottely	
189-196		River from mouth to	414-416
Elevations on	218	Blalock, elevations between Tallu-	
Survey of	218	lah Falls and	83-85
Apalachia, N. C., elevation on Hi-		Blue Spring, discharge data of	297
wassee River from Hiwas-		Blueridge, discharge data near	
see to	411-414	400-405, 411	
Apalachicola River, source and		Bowman's Island, water power at	319
character of	224	Brazzell Creek, discharge data on	202
Apalachicola River basin, descrip-		Broad River (of Georgia), discharge	
tion of	224	data on	70-80
Discharge data in	225-304	Elevations on	95-97
Surveys in	304-317	Elevations at junction of Sa-	
Water power in	318-322	vannah River and	91-92
Area Curve, form of	27	Fall on	19
Armour, discharge data at and		Source and course of	31
near	300-301	Survey of	95-97
Artesian wells, value of	21	Water power on	101
Athens, discharge data near	157-159	Broad River, south fork of, dis-	
Water power near	223	charge data on	81
Atlanta, discharge data near	301	Buchanan Bridge, discharge data at	377
Water power near	319	Buck Creek, discharge data on	297
		Buckhead, discharge data near	189-196

	Page		Page
Macon, discharge data at.....	124-139	Norcross, discharge data near.....	231-236
Elevations on Ocmulgee River from junction of South and Yellow to mouth	210-211	Nottely River, discharge data on Elevations on	394-400 414-416
Madison, S. C., discharge data at and near	37-46	Survey of	414-416
Map, drainage, of Georgia	17	O	
Marble, quarrying and manufactur- ing of, water for	24	Oakdale, discharge data at and near	237-248
Methodist Fishery Shoals, water power at	223	Ocmulgee River, discharge data on	120-139, 204
Middle Oconee River, discharge data on	157-159	Elevations on	210-211
Elevations on	217	Fall on	19-20
Survey of	215-217	Source and course of.....	116-117
Middleton Shoals, water power at.	99	Survey of	209-211
Milford, discharge data at.....	294-296	Water power on	219-220
Milledgeville, discharge data at and near	170-176, 204	Oconee River, discharge data on.....	160-189
Elevations on Oconee and Mid- dle Oconee above	216-217	Elevations on	216
Water power at and near.....	222	Fall on	19, 20
Millen, discharge data at and near. 102-104, 113-114	102-104, 113-114	Source and course of	116
Miner's inch, equivalents of.....	23-24	Survey of	215-216
Mining, water for	23-24	Water power on	222-223
Mobile River basin, description of.	323	Ogeechee River, discharge data on	102-104, 115
Discharge data in	323-381	Source and course of	101-102
Surveys in	381-384	Ogeechee River basin, description of	101-102
Water power in	384	Discharge data in	101-115
Molina, discharge data at.....	267	Ohoopsee, discharge data near	204
Montezuma, discharge data near, 276- 278	276-278	Ohoopsee River, discharge data on	196-201, 204
Mores Shoals, water power at....	101	Source and course of	116
Mountaintown Creek, discharge data on	374-375	Ocoee River, discharge data on.....	406-410
Muckalee Creek, discharge data on	287-289	Old Factory Shoals (Soque River), water power at.....	320
Mulberry Creek, discharge data on	266-267	Oostanaula River, discharge data on	351-360
Mulberry Fork of Oconee River, elevations on	218	Oothkaloga Creek, discharge data on	380
Survey of	218	P	
Murphy, N. C., discharge data at.....	385-394	Paleozoic area, extent and char- acter of	20
N			
Nacoochee, elevations on Chatta- hoochee River from Colum- bus to	306-313	Panther Creek, discharge data on.	82
Neal, water power near	322	Peachstone Shoals, water power at	219
Newbridge, water power at	321	Peachtree Creek, discharge data on	301
Newton, discharge data near.....	300	North Fork of, discharge data on	300-301
Newton Factory, discharge data near	202	Peavine Creek, discharge data on.	301
Water power near	221-222	Pendleton Creek, discharge data on.....	204-205
Nickajack Creek, discharge data on	300	Pinelog Creek, discharge data on.	380
		Pole Bridge Creek, discharge data on	205
		Porter Shoals, water power at....	320
		Porterdale, water power at.....	221
		Pumps, use of, in irrigation	22

	Page
Q	
Quarrying, water for	24
R	
Ranger, N. C., discharge data at.	394-400
Rating tables, construction of.	26-28
Red Oak Creek, discharge data on	301-302
Reidsville, discharge data near...	196-201, 202
Resaca, discharge data at.	351-360, 378-379
Rivers, See Streams.	
Riverview, discharge data near....	304
Roberta, elevations to Flint River from Woodbury to river....	317
Rome, discharge data at and near 335-341, 342-350	302
Elevations on Etowah River near	381-382
Roswell, water power near.....	319
Rottenwood Creek, discharge data on	302
Run-off, definition of	28
Russell Bridge, elevations on Chat- tooga River from mouth to.	93-94
S	
Sallacoa Creek, discharge data on.	380
Sandersville, discharge data near.	115
Sanford Creek, discharge data on.	205
Satilla River, discharge data on....	223
Satilla River basin, discharge data in	223
Savannah River, discharge data on	46-69
Elevations on	88-92
Fall on	19-20
Source and course of	30
Survey of	88-92
Water power on	99-100
Savannah River basin, description of	30-31
Discharge data in	31-82
Surveys in	83-97
Water power in	97-101
Scull Shoals, water power at....	223
Second-foot, definition of	28
Seneca River, elevations near junc- tion of Tugaloo River and..	88-89
Source and course of.....	30
Smith's Shoals, water power at...	220
Snapping Shoals, discharge data near	119-120, 205
Water power at	219
Snapping Shoals Creek, discharge data on	205

	Page
Soque River, discharge data on....	260-264, 302
Elevations on	314
Source and course of	224
Survey of	313-314
Water power on	320
South River, discharge data on 117-120, 205	207-209
Elevations on	207-209
Survey of	207-209
Water power on.....	219
Springs, mineral, occurrence of..	24
Stewart, discharge data near..	151-153
Stone Mountain, discharge data at.	140
Streams, character of	17-20
Fall, on	19
Flow of	25-30
Measurement of	25-28
Survey of, map showing.....	17
Sugar Creek, discharge data on....	206
Sweetwater Creek, discharge data on	264-266, 303
Swift Creek, discharge data on....	206

T

Tables, explanation of	28-29
Talking Rock Creek, discharge data on	375
Tallapoosa, discharge data near 376-377, 380-381	376-377, 380-381
Tallapoosa River, discharge data on	376-377, 380-381
Tallulah Falls, discharge data at and near	31-36, 81-82
Elevations on	83-85
Fall on	19
Survey of	83-85
Water power on	98-99
Thomaston, discharge data near....	286-287, 297, 299
Thunder, discharge data near.....	298
Tiger Creek, discharge data on....	82
Toccoa River, discharge data on....	400-405, 411
Elevations on	417-418
Survey of	416-418
See also Ocoee River.	
Tombigbee River, source and course of	323
Topography, description of.....	17-20
Towaliga River, discharge data on. 154-156	214-215
Elevations on	214-215
Fall on	19
Survey of	214-215
Water powers on.....	222
Town Creek, discharge data on....	206

	Page		Page
Trotters Shoals, water power at...	100	Wilcox, discharge data at.....	203, 206
Tugaloo River, discharge data on.	37-46	Williamsburg, discharge data near.	300
Elevations on	86-88	Williamson's Swamp Creek, dis-	
Source and course of.....	30	charge data on.....	104-107, 115
Survey of	85-88	Willow, elevations on Chestatee	
Water power on.....	99	River from mouth to....	315-316
V			
Velocity curve, form of.....	27	Woodbury, discharge data at and	
Vinings, discharge data near...	236-237	near	268-275
W			
Warm Springs, discharge data of..	25	Elevations on Flint River from	
Washington, discharge data near..	82	near Roberta to.....	317
Water, domestic supply of.....	23	Woodlawn, S. C., discharge data at.	54-57
Storage of	21-22	Y	
Uses of	21-25	Yahoola ditch, description of.....	23
Waycross, discharge data near....	223	Yellow Jacket Shoals, water power	
Wells, artesian, value of.....	21	at	321-322
West Point, discharge data at..	249-259	Yellow River, discharge data on...	
White Oak Creek, discharge data on		140-145, 206-207	
303-304		Elevations on	212-213
Whites Shoals, water power near..	221-222	Survey of	211-213
Whitewater Creek, discharge data		Water power on.....	220-221
on	304	Yellow River (P. O.), elevations on	
		Yellow River from mouth to	
		212-213	
		Water power at.....	221

BULLETINS OF THE GEOLOGICAL SURVEY OF GEORGIA

1. Marbles of Georgia, by S. W. McCallie, 1894, 87 pp., 16 pl., and 2 maps. *Out of print.*
1. Marbles of Georgia, Second Edition, Revised and Enlarged, by S. W. McCallie, 1907, 126 pp., 52 pl., and 2 maps. *Postage 13 cents.*
2. Corundum Deposits of Georgia, by Francis P. King, 1894, 133 pp., 6 pl., 1 map. *Postage 9 cents.*
3. A Part of the Water-Powers of Georgia, by C. C. Anderson and B. M. Hall, 1896, 150 pp., 10 pl., and 2 maps. *Postage 9 cents.*
4. A Part of the Gold Deposits of Georgia, by W. S. Yeates, S. W. McCallie and Francis P. King, 1896, 542 pp., 21 pl., and 1 map. *Out of print.*
5. A Part of the Phosphates and Marls of Georgia, by S. W. McCallie, 1896, 98 pp., 3 pl. *Postage 7 cents.*
6. A Part of the Clays of Georgia, by Geo. E. Ladd, 1898, 204 pp., 17 pl. *Postage 11 cents.*
7. Artesian-Well System of Georgia, by S. W. McCallie, 1898, 214 pp., 7 pl., and 2 maps. *Postage 13 cents.*
8. Roads and Road-Building Materials of Georgia, by S. W. McCallie, 1901, 264 pp., 27 pl., and 1 map. *Postage 14 cents.*
9. A Part of the Granites and Gneisses of Georgia, by Thomas L. Watson, 1902, 367 pp., 32 pl., and 4 maps. *Postage 21 cents.*
10. Iron Ores of Polk, Bartow and Floyd Counties, Georgia, by S. W. McCallie, 1900, 190 pp., 8 pl., and 1 map. *Postage 11 cents.*
11. Bauxite Deposits of Georgia, by Thos. L. Watson, 1904, 169 pp., 12 pl., and 1 map. *Postage 10 cents.*
12. Coal Deposits of Georgia, by S. W. McCallie, 1904, 121 pp., 14 pl., and 1 map. *Postage 9 cents.*
13. Ocher Deposits of Georgia, by Thos. L. Watson, 1906, 81 pp., 11 pl., and 3 maps. *Postage 6 cents.*
14. Manganese Deposits of Georgia, by Thomas L. Watson, 1908, 195 pp., 8 pl., and 2 maps. *Postage 12 cents.*
15. Underground Waters of Georgia, by S. W. McCallie, 1908, 376 pp., 29 pl., and 2 maps. *Postage 23 cents.*
16. Water-Powers of Georgia, by B. M. and M. R. Hall, 1908, 424 pp., 14 pl., and 1 map. *Postage 25 cents.*
17. Fossil Iron Ore Deposits of Georgia, by S. W. McCallie, 1908, 194 pp., 24 pl., and 3 maps. *In press.*
18. Clay Deposits of Georgia, by Otto Veatch. *Ready for press.*
19. Gold Deposits of Georgia, by S. P. Jones. *In preparation.*
20. Mineral Springs of Georgia, by S. W. McCallie. *In preparation.*
21. Marls and Limestones of Georgia, by Otto Veatch. *In preparation.*
22. Brown Iron Ores of Georgia, by S. W. McCallie. *In preparation.*

