## GEORGIA ENVIRONMENTAL PROTECTION DIVISION WATER CONSERVATION CERTIFICATION PROGRAM INSPECTION CHECKLIST FOR PERMANENT FACILITY CAR WASHES

Car Wash Certification Number: GACW New	: Re	certificatio	)11;
Location Information (please print)			
Business Name:			<u>_</u>
Contact Person:			
Mailing Address: State Zip code			
Phone: County:			
Physical Location:			
GPS location of car wash (ddd°mm'ss") Latitude: Longitude:			
Source of water for car wash:			
Public water system? (Circle one) Yes No If "Yes", Water System Name:			
Is waste water from the car wash recycled? (Circle one) Yes No			
	No		
Wastewater System Name:			
Inspection Information by Georgia Certified Backflow Tester (please print)			
Tester Name:			
Company:			
City: State: Zip:			
Phone:			
Tester certification number Issued by (circle one) GBPAT, ASSE,	ABPA, or	TREEO	
Vehicle Wash Facility Type (Check All That Apply)			
Self-Serve Facility Conveyor Facility Roll-Over/In-Bay	Han	d Wash	
Self-Serve Facility Conveyor Facility Roll-Over/In-Bay  The Following Items Apply To All Car Wash Facilities:	Han Pass	d Wash Fail	N/A
Self-Serve Facility Conveyor Facility Roll-Over/In-Bay  The Following Items Apply To All Car Wash Facilities:  1. The facility has a back flow prevention device installed on the potable water			N/A
Self-Serve Facility Conveyor Facility Roll-Over/In-Bay  The Following Items Apply To All Car Wash Facilities:  1. The facility has a back flow prevention device installed on the potable water supply.			N/A
Self-Serve Facility Conveyor Facility Roll-Over/In-Bay  The Following Items Apply To All Car Wash Facilities:  1. The facility has a back flow prevention device installed on the potable water supply.  2. All spray nozzles will be changed annually.			N/A
Self-Serve Facility Conveyor Facility Roll-Over/In-Bay  The Following Items Apply To All Car Wash Facilities:  1. The facility has a back flow prevention device installed on the potable water supply.  2. All spray nozzles will be changed annually.  3. All water leaks will be repaired as they occur.			N/A
Self-Serve Facility Conveyor Facility Roll-Over/In-Bay  The Following Items Apply To All Car Wash Facilities:  1. The facility has a back flow prevention device installed on the potable water supply.  2. All spray nozzles will be changed annually.  3. All water leaks will be repaired as they occur.  4. All hoses and faucets will be attended or shut off. All hoses will utilize an			N/A
Self-Serve Facility Conveyor Facility Roll-Over/In-Bay  The Following Items Apply To All Car Wash Facilities:  1. The facility has a back flow prevention device installed on the potable water supply.  2. All spray nozzles will be changed annually.  3. All water leaks will be repaired as they occur.  4. All hoses and faucets will be attended or shut off. All hoses will utilize an automatic shutoff value.			N/A
Self-Serve Facility Conveyor Facility Roll-Over/In-Bay  The Following Items Apply To All Car Wash Facilities:  1. The facility has a back flow prevention device installed on the potable water supply.  2. All spray nozzles will be changed annually.  3. All water leaks will be repaired as they occur.  4. All hoses and faucets will be attended or shut off. All hoses will utilize an automatic shutoff value.  5. All hand-held hoses must have a flow no greater than 3 gallons a minute.			N/A
Self-Serve Facility Conveyor Facility Roll-Over/In-Bay  The Following Items Apply To All Car Wash Facilities:  1. The facility has a back flow prevention device installed on the potable water supply.  2. All spray nozzles will be changed annually.  3. All water leaks will be repaired as they occur.  4. All hoses and faucets will be attended or shut off. All hoses will utilize an automatic shutoff value.			N/A
Self-Serve Facility Conveyor Facility Roll-Over/In-Bay  The Following Items Apply To All Car Wash Facilities:  1. The facility has a back flow prevention device installed on the potable water supply.  2. All spray nozzles will be changed annually.  3. All water leaks will be repaired as they occur.  4. All hoses and faucets will be attended or shut off. All hoses will utilize an automatic shutoff value.  5. All hand-held hoses must have a flow no greater than 3 gallons a minute.			N/A
Self-Serve Facility Conveyor Facility Roll-Over/In-Bay  The Following Items Apply To All Car Wash Facilities:  1. The facility has a back flow prevention device installed on the potable water supply.  2. All spray nozzles will be changed annually.  3. All water leaks will be repaired as they occur.  4. All hoses and faucets will be attended or shut off. All hoses will utilize an automatic shutoff value.  5. All hand-held hoses must have a flow no greater than 3 gallons a minute.  6. Driveways and impervious surfaces may be washed with high pressure, low			N/A
Self-Serve Facility Conveyor Facility Roll-Over/In-Bay  The Following Items Apply To All Car Wash Facilities:  1. The facility has a back flow prevention device installed on the potable water supply.  2. All spray nozzles will be changed annually.  3. All water leaks will be repaired as they occur.  4. All hoses and faucets will be attended or shut off. All hoses will utilize an automatic shutoff value.  5. All hand-held hoses must have a flow no greater than 3 gallons a minute.  6. Driveways and impervious surfaces may be washed with high pressure, low volume systems for health/safety purposes only.			N/A
Self-Serve Facility Conveyor Facility Roll-Over/In-Bay  The Following Items Apply To All Car Wash Facilities:  1. The facility has a back flow prevention device installed on the potable water supply.  2. All spray nozzles will be changed annually.  3. All water leaks will be repaired as they occur.  4. All hoses and faucets will be attended or shut off. All hoses will utilize an automatic shutoff value.  5. All hand-held hoses must have a flow no greater than 3 gallons a minute.  6. Driveways and impervious surfaces may be washed with high pressure, low volume systems for health/safety purposes only.  7. If spot-free reverse osmosis water is present, the reserve osmosis reject water			N/A
Self-Serve Facility Conveyor Facility Roll-Over/In-Bay  The Following Items Apply To All Car Wash Facilities:  1. The facility has a back flow prevention device installed on the potable water supply.  2. All spray nozzles will be changed annually.  3. All water leaks will be repaired as they occur.  4. All hoses and faucets will be attended or shut off. All hoses will utilize an automatic shutoff value.  5. All hand-held hoses must have a flow no greater than 3 gallons a minute.  6. Driveways and impervious surfaces may be washed with high pressure, low volume systems for health/safety purposes only.  7. If spot-free reverse osmosis water is present, the reserve osmosis reject water shall be reused in the vehicle wash process.			N/A
The Following Items Apply To All Car Wash Facilities:  1. The facility has a back flow prevention device installed on the potable water supply.  2. All spray nozzles will be changed annually.  3. All water leaks will be repaired as they occur.  4. All hoses and faucets will be attended or shut off. All hoses will utilize an automatic shutoff value.  5. All hand-held hoses must have a flow no greater than 3 gallons a minute.  6. Driveways and impervious surfaces may be washed with high pressure, low volume systems for health/safety purposes only.  7. If spot-free reverse osmosis water is present, the reserve osmosis reject water shall be reused in the vehicle wash process.  8. For Self-Serve Car Washes, the wash nozzle and pump system will be high-			N/A
The Following Items Apply To All Car Wash Facilities:  1. The facility has a back flow prevention device installed on the potable water supply.  2. All spray nozzles will be changed annually.  3. All water leaks will be repaired as they occur.  4. All hoses and faucets will be attended or shut off. All hoses will utilize an automatic shutoff value.  5. All hand-held hoses must have a flow no greater than 3 gallons a minute.  6. Driveways and impervious surfaces may be washed with high pressure, low volume systems for health/safety purposes only.  7. If spot-free reverse osmosis water is present, the reserve osmosis reject water shall be reused in the vehicle wash process.  8. For Self-Serve Car Washes, the wash nozzle and pump system will be high-pressure and flow at no greater than 3 gallons per minute.			N/A

50% of water utilized will be recycled.

<b>Inspector Notes on Certification Inspection</b>	n:
<b>Deficiencies To Be Corrected For Conforn</b>	nance With Best Management Practices:
Date of Inspection:	
The second secon	
Tester Signature:	
as a permanent facility car wash not consider	erefore I recommend the certification / recertification of this facility red as an outdoor water user.
l ester Signature:	Date:
Instructions to Car Wash Owner:	
<u>Please note</u> : Local jurisdictions may petition the EPD severe drought conditions.	Director for variances to allow more restrictive conditions depending on locally
In order to obtain your certification from EPD, you certified backflow tester) and a check in the amount of	must send a copy of this form (when you have passed your inspection by the $f $50.00 \text{ to}$ :
Car Wash Certification Program Georgia Environmental Protection Div Watershed Protection Branch 2 Martin Luther King, Jr., Drive Suite 1152, East Tower Atlanta, GA 30334	ision
<ul><li>Make check payable to: Georgia Department</li><li>Check Number:</li></ul>	of Natural Resources, Carwash Certification Program
	ter expiration, the certification will no longer be valid. In order to renew your ispected by a certified backflow tester and then resubmit your information and
You will <u>not</u> receive any reminder information from E	CPD.
For Administrative Office Use Only	
Received By:	Date Received:
Approved By:	Date Approved:
Date Certification Letter Sent:	