

Prepared for:

CSI REALTY, LLC
2680 Lakeland Road
Dalton, GA 30721

**VOLUNTARY REMEDIATION PROGRAM
COMPLIANCE STATUS REPORT
(HSI #10831)
Color Spectrum
29 Probasco Street
LaFayette, GA 30728**

Prepared by:



1050 Crown Pointe Parkway, Suite 550
Atlanta, Georgia 30338
Tel: 404-315-9113

November 2014

**VOLUNTARY REMEDIATION PROGRAM
COMPLIANCE STATUS REPORT
(HSI #10831)**

COLOR SPECTRUM
29 Probasco Street
LaFayette, GA 30728

Prepared for:

CSI REALTY, LLC
2680 Lakeland Road
Dalton, Georgia 30721

Prepared By..



1050 Crown Pointe Parkway, Suite 550
Atlanta, Georgia 30338
Tel: 404-315-9113


Justin Vickery, PG
Associate

November 2014

VOLUNTARY REMEDIATION PROGRAM COMPLIANCE STATUS REPORT (HSI #10831)

COLOR SPECTRUM
29 Probasco Street
LaFayette, GA 30728
November 2014

GROUNDWATER SCIENTIST STATEMENT	1
--	----------

1	INTRODUCTION	2
----------	---------------------------	----------

1.1	Background.....	2
1.2	Site Location and Description	2
1.3	Site Use and Development History	3
1.4	Description of Adjacent Properties.....	3
1.5	Source Description and Constituents of Interest.....	4

2	SITE INVESTIGATIVE HISTORY	5
----------	---	----------

2.1	Overview.....	5
2.2	Historical Investigations and Monitoring.....	5
2.2.1	October 11, 2005 Sampling Event	5
2.2.2	October 24, 2005 Sampling Event	5
2.2.3	HSRA Notification	6
2.2.4	July 2006 Sampling Event.....	6
2.2.5	December 19-20, 2006 Sampling Event	7
2.2.6	June 21-28, 2007 Sampling Event	8
2.2.7	October 6-7, 2009 Sampling Event	8
2.2.8	August/November 2011 Sampling Events.....	9
2.2.9	March 2013 Monitoring Well Installation	10
2.2.10	Quarterly Groundwater Monitoring Events	10
2.3	Recent Field Investigation.....	11
2.3.1	August 2014 Monitoring Well Installation and Sampling	11
2.3.2	Well Sampling Results	12

3	CONCEPTUAL SITE MODEL	13
----------	------------------------------------	-----------

3.1	Geology and Hydrogeology	13
3.1.1	Overview	13
3.1.2	Regional Physiography and Topography	13
3.1.3	Site Topography.....	13

3.1.4	Regional and Site Geology	14
3.1.5	Regional and Site Hydrogeology	15
3.1.6	Groundwater Flow Direction and Gradient	16
3.1.7	Hydraulic Conductivity Data	16
3.1.8	Groundwater Flow Velocity	17
3.2	Risk Reduction Standards	18
3.2.1	Soil RRS	18
3.2.2	Groundwater RRSs	18
3.3	Potential Receptors and Exposure Pathways	18
3.3.1	Potential Environmental Receptors	18
3.3.2	Potential Human Receptors	20
4	GROUNDWATER COMPLIANCE.....	23
4.1	Groundwater Delineation	23
4.2	Compliance with Residential and Non-Residential RRSs	23
4.3	Groundwater Modeling.....	24
4.3.1	Introduction	24
4.3.2	Model Development and Calibration	24
4.3.3	Sensitivity Analysis.....	25
4.3.4	PCE Results.....	25
4.3.5	Conclusions	26
4.4	Vapor Intrusion Assessment	26
4.4.1	Non-Residential Exposure Modeling	26
4.4.2	Residential Exposure Modeling.....	27
4.5	Institutional Controls	27
5	REFERENCES	28

APPENDICES

Appendix A: Groundwater Model

Appendix B: Figures

Figure 1	Site Location Map
Figure 2	Site Plan and Site Vicinity Map
Figure 3	USGS Quadrangle Map
Figure 4A	Historical Soil Boring Groundwater Results
Figure 4B	Historical Monitoring Well Results
Figure 4C	Groundwater Sampling Results (March 2013)
Figure 4D	Groundwater Sampling Results (June 2013)
Figure 4E	Groundwater Sampling Results (August 2013)
Figure 4F	Groundwater Sampling Results (December 2013)
Figure 5	Soil Analytical Results
Figure 6	Geologic Map of the Georgia Ridge and Valley
Figure 7A	Geologic Cross-Section Location Map
Figure 7B	Cross-Section A-A'
Figure 7C	Cross-Section B-B'
Figure 8	Potentiometric Surface Map (December 2013)

Appendix C: Tables

Table 1	Summary of Groundwater Analytical Results
Table 2	Summary of Soil Analytical Results
Table 3	Groundwater Elevations
Table 4	Summary of Vapor Intrusion Modeling Results

Appendix D: Laboratory Analytical Reports

Appendix E: Well Development and Well Sampling Forms

Appendix F: Boring Logs and Well Diagrams

Appendix G: Slug Test Data

Appendix H: Risk Reduction Standards Calculations

Appendix I: Wildlife Resources Division Letter

Appendix J: Vapor Intrusion Model

**VOLUNTARY REMEDIATION PROGRAM COMPLIANCE STATUS REPORT
(HSI #10831)**

**COLOR SPECTRUM
29 Probasco Street
LaFayette, GA 30728
November 2014**

GROUNDWATER SCIENTIST STATEMENT

I certify that I am a qualified groundwater scientist who has received a baccalaureate or post-graduate degree in the natural sciences or engineering, and have sufficient training and experience in ground water hydrology and related fields, as demonstrated by state registration and completion of accredited university courses, that enable me to make sound professional judgments regarding groundwater monitoring and contaminant fate and transport. I further certify that this Voluntary Remediation Program Compliance Status Report for Color Spectrum, HSI #10831, was prepared by me and appropriate qualified subordinates working under my direction.

Certified by: _____


Justin D. Vickery, P.G.
Associate
No. 1745

Date: _____

11-20-14

1 INTRODUCTION

1.1 Background

EPS has prepared this Voluntary Remediation Program Compliance Status Report (CSR) on behalf of CSI Realty, LLC for the property located at 29 Probasco Street, LaFayette, Walker County, Georgia, referred to herein as the “Site”. The purpose of this CSR is to demonstrate compliance with the Risk Reduction Standards (RRSs) through the use of a Uniform Environmental Covenant (UEC) and a groundwater model (Appendix A) in order to request that the Site be de-listed from the Hazardous Site Inventory (HSI). The Site was listed on the HSI (#10831) in a letter from the Georgia Environmental Protection Division (GA EPD) dated February 10, 2006 due to a release of volatile organic compounds (VOCs) to groundwater, which occurred prior to CSI Realty’s acquisition of the property. Title to the property is currently held by the Walker County Development Authority as part of a tax abatement agreement with CSI Realty. Numerous investigations have been conducted at the Site, and it has been determined that the Site is in compliance with applicable RRSs. In a letter dated June 24, 2011, the GA EPD concurred that the Site was in compliance with Type 1 RRSs for soil, and therefore, this CSR addresses groundwater compliance.

Although this CSR demonstrates compliance with the RRSs, a Certification of Compliance is not included. The Certification will be submitted with a CSR Addendum once the UEC has been recorded with Walker County.

1.2 Site Location and Description

The Site is located at 29 Probasco Street in LaFayette, Walker County, Georgia at latitude 34° 42’ 45” N and 85° 17’ 19” W, and according to the Walker County Tax Assessor Office, consists of two parcels as follows:

1. Walker County Tax Parcel ID # 1023087, 1.38 Acres; and
2. Portions of the Chattooga and Chickamauga Railway Right-of-Way.

The Site contact is:

CSI Realty, LLC
Tom Watters
P.O. Box 5695
Rome, Georgia 30162
706-290-4179 direct
tomwatters@syntecind.com

The Site is developed with one building, totaling approximately 74,000 square feet, which is used for winding and heat setting yarn. A loading dock and dumpster are located on the east side of the building. A pond is located in the northeastern portion of the Site, and a small stream, the headwaters of the Chattooga River, flows out of the pond to the east of the Site. A Site Location Map is included as Figure 1 (all figures are included in Appendix B), and a Site Vicinity Map, showing the Site and the surrounding properties, is included as Figure 2.

1.3 Site Use and Development History

The first known development of the Site was as a cotton mill which operated from the late 1800s until around 1980 when it was damaged by fire. The operations on the Site were then converted to twisting and heat setting of carpet yarns which has continued to the present day.

Historically, two fuel oil above ground storage tanks (ASTs) and one gasoline underground storage tank (UST) were utilized at the Site. The UST was used for fueling facility vehicles. The ASTs were used as a secondary fuel source for the facility's steam boilers. All tanks were removed in 2006, in accordance with EPD regulations.

The building is located in the area of the property where the former cotton mill was originally constructed. Several expansions have occurred with the most recent being the addition of the warehouse in the mid-1990s.

1.4 Description of Adjacent Properties

Properties immediately adjacent to the Site as shown on Figure 2 are as follows:

- Towards the North: Vacant land, West Indiana Street, and the City of LaFayette maintenance department.
- Towards the South: A related manufacturing facility, followed by a vacant lot and a school (Head Start).
- Towards the East: A railroad right-of-way followed by a wooded, low lying area with an unnamed tributary.

- Towards the West: Residential to the northwest and west, an auto repair shop and auto salvage yard, fire station, and residences to the southwest.

Topographic elevations of the Site and surrounding properties are depicted on a U.S.G.S. Quadrangle Map included as Figure 3.

1.5 Source Description and Constituents of Interest

Based on the location of the groundwater plume, the historical source of impacts appears to have occurred before the current building was constructed, in the vicinity of the current dumpster and the portion of the yarn twisting adjacent to the dumpster. The only known use of chlorinated solvents at the facility were associated with a parts cleaner, which was previously located in the maintenance area. The machine utilized Safety Kleen 105, which was a recycled cleaning solution that may contain up to 0.2 % tetrachloroethene (PCE). However, there has been no record of releases from the parts cleaner, all waste is picked up and recycled by the vendor, and samples in the vicinity of the parts cleaner do not indicate that it is a potential source. Therefore, the source of the VOCs is likely to be historical releases in connection with operations conducted in this area prior to construction of the current building.

Soil and groundwater samples have been collected for analysis of VOCs, polynuclear aromatic hydrocarbon (PAHs), arsenic, and lead. PAH constituents detected were related to a petroleum release from the former ASTs which held diesel fuel. The release from the ASTs was addressed in cooperation with the EPD Water Resources Branch and is not addressed in this CSR. Regulated substances detected in groundwater at the Site consist of 1,1,1-trichloroethane (TCA), 1,1-dichloroethane (DCA), 1,1-dichloroethene (DCE), acetone, Freon-113, Freon-12, isopropylbenzene (IPB), PCE), and lead. The one lead detection in groundwater appears to be a naturally occurring background concentration and not indicative of a release. These constituents and their associated results are summarize on Table 1 (Tables 1 through 4 are included in Appendix C).

2 SITE INVESTIGATIVE HISTORY

2.1 Overview

The findings of the subsurface investigation and monitoring conducted by EPS from October 2005 to August 2014 are discussed in this section. EPS is not aware of any previous environmental investigations performed at the Site. Site sampling was conducted in accordance with the United States Environmental Protection Agency's Field Branches Quality System and Technical Procedures (FBQSTP). Field methods for historical investigations were discussed in previous report submittals. Field methods for the August 2014 work are discussed in Section 2.3.

2.2 Historical Investigations and Monitoring

2.2.1 October 11, 2005 Sampling Event

On October 11, 2005, five soil borings, referred to as SB-1 through SB-5, were advanced to the water table on the Site and an adjacent parcel (refer to Figure 4A). The soil borings were advanced using a truck-mounted direct push drilling device. Soil borings SB-1 through SB-3 were located topographically downgradient (east) of the two primary buildings. Boring SB-4 was located near the southern property boundary and SB-5 was located near the western property boundary, upgradient of the buildings.

A groundwater sample was collected from each soil boring. A surface water sample was also collected from the pond. All samples were analyzed by an independent laboratory for VOCs using EPA Method 8260B.

The laboratory detected TCA, DCA, and PCE in the groundwater sample collected from SB-1 at concentrations of 23 micrograms per liter ($\mu\text{g/L}$), 5.6 $\mu\text{g/L}$, and 6.4 $\mu\text{g/L}$, respectively. VOCs were not detected in the groundwater samples collected from SB-2 through SB-5, or in the pond sample. Sample results are shown on Figure 4A and summarized in Table 1.

2.2.2 October 24, 2005 Sampling Event

On October 24, 2005, six soil borings (SB-6 through SB-11) were advanced near the fuel tanks by direct push technology to assess the extent of the VOC impacts in groundwater detected in the October 11th sampling event. During advancement of the soil borings, No. 2 fuel oil was

observed in the groundwater samples collected from three of the borings. The release of the No. 2 fuel oil was attributed to the ASTs, was addressed in cooperation with Water Resources Branch and is not included as part of this CSR. Each of the six samples collected were analyzed for VOCs. Three of the samples were analyzed for PAHs using EPA Method 8270C. Laboratory results are as follows:

- TCA was detected in three samples, SB-6, SB-9, and SB-10 at concentrations below the Type 1 RRS.
- DCA was detected in SB-11 below the Type 1 RRS.
- Freon-113 was detected in all six samples in concentrations below the Type 1 RRS.
- PAHs were not detected in any samples.

Sample results are shown on Figure 4A and summarized in Table 1.

2.2.3 HSRA Notification

On December 2, 2005, a HSRA Release Notification was submitted for the Site by CSI Realty following its acquisition in November 2005. On February 10, 2006, the Site was added to the HSI.

2.2.4 July 2006 Sampling Event

On July 27, 2006, eight soil borings (SB-12 through SB-19) were advanced by direct push technology to further delineate VOCs in groundwater (refer to Figure 4A). Laboratory results are as follows:

- Freon-113 was detected in SB-13 and SB-15 through SB-18, with the highest concentration being 1,800 µg/L, which is below the Type 1 RRS.
- TCA and DCA detections were below the Type 1 RRS.
- DCE was detected in SB-13 and SB-17 at concentrations of 9.0 µg/L and 7.1 µg/L, respectively, which are both above the Type 1 RRS but below the Type 2 RRS.
- PCE was detected in SB-13 and SB-16 at 7.6 µg/L and 20 µg/L, respectively, which are both above the Type 1 RRS. The detection in SB-16 is above the Type 2 RRS but below the Type 4 RRS.

VOCs were not detected in SB-12 and SB-14. A groundwater sample could not be collected from SB-19. Sample results are shown on Figure 4A and summarized in Table 1. Based on the presence of regulated compounds in the groundwater above laboratory detection limits, additional groundwater delineation was required.

2.2.5 December 19-20, 2006 Sampling Event

On December 19-20, 2006 nine soil borings (SB-20 through SB-28) were advanced by direct push technology to the groundwater table (refer to Figure 4A). Borings (SB-20 through SB-26) were advanced indoors in the vicinity of the maintenance area which housed a parts cleaner until 2009. Borings SB-27 and SB-28 were advanced outdoors to delineate the plume to the north and south. Temporary wells were constructed in borings SB-20 through SB-23, and SB-26 through SB-28 to determine groundwater flow direction. At each well and at three existing monitoring wells, MW-1 through MW-3 (installed to assess the AST fuel oil release), the top-of-casing elevation and groundwater depths were measured. The groundwater flow direction was determined to be to the east-southeast with a hydraulic gradient of 0.04 feet/foot.

After completing the groundwater depth measurements, groundwater samples were collected from each temporary well and MW-1 through MW-3 and analyzed for VOCs. Laboratory results are as follows:

- Freon-113 was detected in all ten samples with a maximum concentration of 27,000 µg/L, which is below the Type 1 RRS.
- TCA was detected in two samples below the Type 1 RRS. TCA was detected in SB-23 at 2,100 µg/L, which is above the Type 1 RRS but below the Type 2 RRS.
- DCA was detected in four samples below the Type 1 RRS.
- DCE was detected in four samples: two of which are below the Type 1 RRS and two of which are above the Type 2 RRS but below the Type 4 RRS.
- PCE was detected in in one sample below the Type 2 RRS and in two samples above the Type 4 RRS.

Sample results are shown on Figure 4A and summarized in Table 1.

During the December 2006 sampling event, soil samples were collected from three boring locations (SB-24, SB-25, SB-26) located adjacent to the PCE parts cleaner, a potential source area. Soil samples were collected continuously from these borings and field screened for VOCs using a photoionization detector (PID). A soil sample was collected for laboratory analysis from each boring where the highest VOC concentration was measured. In borings where VOCs were not detected with a PID, a sample was collected immediately above the water table. Soil borings DMW-1, MW-4 through MW-9, TW-1, and TW-2 were not screened with a PID. VOCs were not detected in any of the samples above background and therefore, samples were collected from 7 feet below the ground surface (ft-bgs), immediately above the groundwater table. Soil sampling results are shown on Figure 5 and are summarized on Table 2.

After completion of the sampling, all temporary wells and soil borings were properly plugged and abandoned.

2.2.6 June 21-28, 2007 Sampling Event

In July 2007, six monitoring wells (MW-4 through MW-9), three temporary wells (TW-1 through TW-3), and one deep well (DW-1) were installed to complete horizontal and vertical delineation of the VOCs in groundwater (refer to Figure 4B and Table 1). The wells were installed by direct push, hand auger, hollow stem auger, or air rotary drilling. Groundwater elevations were measured in monitoring wells MW-1 through MW-9, DW-1, TW-1, and TW-2 to determine groundwater flow direction. TW-3 was advanced off-site in the low-lying area to the east of the railroad right-of-way. Groundwater samples were then collected from each well for VOC analysis. Laboratory results were as follows:

- Freon-113 was detected in seven groundwater samples with a maximum concentration of 3,900 µg/L, which is below the Type 1 RRS.
- TCA and DCA were each detected in two samples at concentrations below the respective Type 1 RRSs.
- DCE was detected in one sample below the Type 2 RRS.
- PCE was detected in two samples below the Type 2 RRS.
- IPB was detected in one sample below the Type 2 RRS.

Twenty soil samples were collected by direct push technology from ten borings (SB-29 through SB-37 and MW-7) to further delineate VOCs in soil. During boring installation, soil cores were continuously collected and field screened with a PID for VOCs. In each boring soil samples were collected from 1 ft-bgs and at an intermediate depth between the ground surface and the water table. Soil sampling results are shown on Figure 5 and summarized in Table 2.

Monitoring well top-of-casing elevations were measured on July 9, 2007 by Wardlaw Land Surveying of LaFayette, Georgia. Horizontal locations were surveyed relative to the state plane coordinates and the elevations were referenced to the National Geodetic Vertical Datum. Top-of-casing elevation data is summarized on Table 3.

2.2.7 October 6-7, 2009 Sampling Event

At the request of the GA EPD, in October 2009, a nested monitoring well pair, MW-10 and MW-11, was installed in the apparent source area to investigate the potential for Freon-113 dense non-aqueous phase liquid (DNAPL) in this area. The wells were installed using hollow stem auger methods. Well MW-10 was screened near the water table (10 – 12.5 ft-bgs) and MW-11 was screened on top of bedrock (17.5 – 20 ft-bgs). The well locations are shown on Figure 4B. Freon-113 was detected in the shallow well at 6,100 µg/L and in the deeper well at 15,000 µg/L. These elevated concentrations suggested the potential presence of DNAPL¹ in this

¹ Freon-113 has a solubility of 170,000 µg/L. As a rule of thumb, DNAPL is potentially present when concentrations exceed 1% of the solubility, or 1,700 µg/L for Freon-113.

area; however, the concentrations are below the Type 1 RRS and no Freon-113 was detected in nearby deep well DW-1.

The groundwater samples were analyzed for VOCs, arsenic, and lead. Constituents detected in the groundwater samples included the following:

- TCA and DCA were detected in MW-10 and MW-11 below the Type 1 RRSs.
- DCE was detected in MW-10 and MW-11 below the Type 2 RRS.
- PCE was detected in MW-10 at a concentration below the Type 4 RRS and in MW-11 at a concentration above the Type 4 RRS.
- IPB was detected in MW-10 and MW-11 below the Type 2 RRS.
- Arsenic was not detected in either groundwater sample. In response to Comment #11 from the GA EPD's letter dated March 30, 2012, the original laboratory report for the samples collected on October 7, 2009 had an arsenic detection limit of 50 µg/L while the Type 1 RRS for arsenic is 10 µg/L. Included in Appendix D are revised data sheets from the original laboratory report showing results down to the method detection limits (MDLs). Arsenic was not detected at an MDL of 4.4 µg/L.
- Lead was detected in MW-11 at 15.6 µg/L; however, due to slow recharge, the well could not be properly developed and the turbidity level was 800 NTUs. The sample is, therefore, not considered to be valid. A filtered sample was also collected from this well and no lead was detected.

Groundwater sample results are shown on Figure 4B and summarized in Table 1.

Six soil samples were collected by direct push technology from six borings (SO-1 through SO-6) to further delineate VOCs in soil. During boring installation, soil samples were continuously collected and field screened with a PID for VOCs. In each boring, soil samples were collected at depths above the water table where PID readings indicated the highest potential VOC concentrations. Soil sampling results are shown on Figure 5 and summarized on Table 2.

2.2.8 August/November 2011 Sampling Events

In August 2011, the groundwater monitoring wells MW-1 through MW-11, DW-1, TW-1 and TW-2 were sampled and analyzed for VOCs. No VOCs were detected in DW-1, MW-4, MW-6, TW-1 and TW-2. Detections in other wells include the following:

- TCA was detected in MW-5, MW-7, MW-8, and MW-10 at concentrations below the Type 1 RRS.
- DCA was detected in MW-8 and MW-10 at concentrations below the Type 1 RRS.
- DCE was detected in MW-5, MW-7, MW-8, and MW-10 at concentrations above the Type 1 RRS but below the Type 4 RRS.

- Freon-113 was detected in MW-1, MW-2, MW-3, MW-5, MW-7, MW-8, MW-9, MW-10, and MW-11 at concentrations below the Type 1 RRS.
- Freon-12 was detected in MW-8 and MW-10 at concentrations below the Type 1 RRS.
- PCE was detected in MW-3, MW-5, MW-7, MW-8, and MW-10. Each of these detections is below the Type 4 RRS with the exception of MW-10.
- IPB was detected in MW-10 at a concentration of below the Type 2 RRS.

There was a significant difference in the Freon-113 concentration in MW-11 from the October 2009 event to the August 2011 event. Thus, on November 15, 2011, MW-10 and MW-11 were re-sampled to confirm the presence or absence of Freon-113 in these wells. No VOCs (including Freon-113) were detected in the deeper of the two wells, MW-11, indicating the absence of a DNAPL. TCA, DCA, DCE, Freon-113, PCE and IPB were detected in MW-10 at concentrations similar to previous detections.

Groundwater sampling results are shown on Figure 4B and summarized in Table 1. In accordance with Comment #7 from the GA EPD's March 30, 2012 letter, monitoring well sampling logs from November 2011 are included in Appendix E.

2.2.9 March 2013 Monitoring Well Installation

On March 6, 2013, two monitoring wells, MW-12 and MW-13, were installed on the Site in accordance with Comment #1 of the GA EPD's letter dated March 30, 2012. The wells were installed using hollow stem auger methods. The locations of these wells were specified in the GA EPD letter and were intended to capture the center of the VOC plume migrating toward the property boundary in the two different groundwater flow directions.

2.2.10 Quarterly Groundwater Monitoring Events

Quarterly groundwater monitoring events were conducted in March 2013, June 2013, August 2013, and December 2013. During these events, monitoring wells MW-2, MW-5, MW-10, TW-1, and newly installed wells MW-12 and MW-13 were sampled.

- VOCs detected in source area well MW-10 included TCA, DCA, DCE, acetone, Freon-113, Freon-12, IPB, and PCE. DCE concentrations were above the Type 2 RRS of 103 µg/L but below the Type 4 of 520 µg/L. PCE was detected above the Type 4 RRS of 98 µg/L.
- VOCs detected in mid-plume well MW-5 included TCA, Freon-113, and PCE. TCA and Freon-133 concentrations were all below the Type 1 RRSs, and PCE was below the Type 2 RRS.
- For downgradient wells MW-2, MW-12, MW-13, and TW-1, no VOCs were detected in MW-2, MW-12, or TW-1 with the exception of some minor Freon-113 detections in

MW-2 and MW-12. TCA and Freon-113 were detected in MW-13 below the Type 1 RRSs. PCE was detected in MW-13 at concentrations below the Type 2 RRS.

VOC concentrations for all wells sampled during the quarterly sampling events remained relatively steady throughout the sampling period. This data is summarized on Table 1 and on Figures 4C, 4D, 4E, and 4F for each of the four events.

2.3 Recent Field Investigation

2.3.1 August 2014 Monitoring Well Installation and Sampling

2.3.1.1 Well Installation

During the 2013 quarterly groundwater sampling events, PCE was detected in well MW-13 at concentrations slightly above the delineation criteria (Type 1 RRS). On August 6, 2014, monitoring well MW-14 was installed downgradient of MW-13 on City of LaFayette property across the Chattooga and Chickamauga Railway Right-of-Way from the Site. Because the location was not accessible with a drill rig, the well was installed using hand auger methods. The proposed well location was due east of MW-13. During the well installation, this area was underwater and the well location was offset to the south. Four hand auger borings reached refusal at a gravel layer at or very near to the water table. After several offsets, the well was finally installed approximately 25 feet south of its proposed location.

The hand auger boring was advanced to 8 ft-bgs. Monitoring well MW-14 was constructed with 5 feet of 2-inch diameter, 0.010-inch slotted PVC screen and 2-inch PVC riser installed to a depth of 8 ft-bgs. Sand was placed in the well annulus from 8 ft-bgs up to 2¼ ft-bgs, and a bentonite seal was placed in the well annulus from 2¼ ft-bgs to 1½ ft-bgs and hydrated. A stick-up well vault was set at 1½ ft-bgs and grouted in place, and a concrete pad was constructed around the stick-up vault. A well cap was placed on the well, and a lock was placed on the vault. The well location and top-of-casing elevation were surveyed.

On August 15, 2014, MW-14 was developed by pumping the well until it was free of visible sediment and until pH, temperature, turbidity, and specific conductivity stabilized. A total of 8¼ gallons of water were purged from the well during development. A well development log is included in Appendix E.

2.3.1.2 Well Sampling

On August 22, 2014, MW-14 was purged and sampled. Prior to purging, the groundwater depth was measured in the well with a water level meter to determine the purge volume.

MW-14 was purged and sampled using a peristaltic pump. Well purging was considered complete when, for three consecutive readings, pH was constant within 0.1 Standard Units,

specific conductance varied no more than 5 percent, and turbidity stabilized below 10 Nephelometric Turbidity Units. A well sampling form is included in Appendix E.

Once the parameters stabilized, the sample was collected using the “soda straw” method. The tubing in the well was filled with groundwater, and the pump was turned off. The tubing was then pulled out of the well and the groundwater in the tubing was drained into the sample bottles. The groundwater sample was collected for VOC analysis in two 40-milliliter glass vials preserved with hydrochloric acid. The sample was placed on ice in a cooler, logged under standard chain-of-custody procedures, and delivered to Analytical Environmental Services in Atlanta, Georgia for VOC analysis by method 8260B.

2.3.2 Well Sampling Results

No VOCs were detected in MW-14 in August 2014. Laboratory analytical results are summarized on Table 1. Figure 4F shows the August 2014 sampling results for MW-14 along with the most recent (December 2013) sampling results from the other wells. The laboratory analytical report is included in Appendix D.

3 CONCEPTUAL SITE MODEL

3.1 Geology and Hydrogeology

3.1.1 Overview

The geologic and hydrogeologic characteristics of the Site and surrounding area are described in this section. This section also includes a discussion of regional physiography and Site topography. The discussion of regional characteristics was derived from published sources. Site specific characteristics were determined based on a review of field data.

3.1.2 Regional Physiography and Topography

A review of the *Physiographic Map of Georgia* (Clark and Zisa, 1976) indicates that Walker County is located in the northwestern portion of the Valley and Ridge Physiographic Province (Figure 6). This physiographic province is generally characterized by a series of linear ridges with elevations in lowland areas about 200 - 800 ft above sea level, but the higher ridges may be above 1,600 ft. Plant species vary from area to area based on local soil type, elevation, moisture, and disturbances (Holder, 1986).

The Ridge and Valley Province is bounded on the south by the Piedmont Province, to the east by the Blue Ridge Province, and on the north and west by the Appalachian Plateau Province. The Valley and Ridge province consists of Paleozoic sedimentary rocks that have been folded and faulted to cause long northeast-southwest trending valleys and ridges that give the region its name.

3.1.3 Site Topography

The topography of the property and surrounding areas was reviewed on a United States Geological Survey (USGS) Quadrangle Map for the LaFayette Quadrangle (Figure 3). The map shows the elevation of the property ranging from 240 to 250 feet above mean sea level. The high point of the Site is located at the western property boundary adjacent to Probasco Street. The grade slopes gently down the parking lots to the eastern property boundary to the drainage ditch on the Chattooga and Chickamauga Railway property. The storm water drainage flows as sheet flow across the property to the drainage ditch. Storm water from the roofs of the two buildings is controlled by gutters/downspouts where it's directed towards the drainage ditch on the eastern

portion of the property. The drainage ditch flows into a small stream which forms the headwaters of the Chattooga River.

The pond located in the northern portion of the property discharges to a small stream which forms the headwaters to the Chattooga River.

3.1.4 Regional and Site Geology

Regional Geology

The strata of the Valley and Ridge include numerous carbonate units, such as the Cambro-Ordovician Knox Dolostone and the Ordovician Chickamauga Limestone, and thus caves and karst terrain exist across large parts of the region. The Chickamauga Valley District is characterized by a series of gently rolling, discontinuous, northeast-trending valleys interrupted by low, linear, parallel ridges. The valley floors are predominantly limestone and dolomite of Cambro-Ordovician age while the ridges are capped by the more resistant cherty units of the Knox Group, also of Cambro-Ordovician age. The ridge tops are approximately 1000 feet in elevation and stand 200-300 feet above the intervening valleys. Rectangular drainage patterns in this district are indicative of structural control.

Residual soils in the Ridge and Valley Province are composed predominantly of Udults with some Ochrepts. Paleudults dominate upland areas underlain by limestone. Hapludults are in valleys underlain by shale. Dystrochrepts are common on side slopes of ridges. Hapludolls and Eutrochrepts are on bottom lands. Soils have an udic moisture regime and thermic or mesic temperature regime. Almost all soils are well drained. Soils range from shallow on sandstone and shale formations to very deep on limestone formations (US Forest Service, 1993). Soils grade into a saprolite or partially weathered bedrock with depth.

A review of the *Geologic Map of Georgia* (Georgia Geological Survey, 1976) indicates that the bedrock underlying LaFayette and nearby areas consists of a Conasauga Group dolostone. Dolostone is a sedimentary carbonate rock that contains a high percentage of the mineral dolomite. It is usually referred to as dolomite rock. Most dolostone formed as a magnesium replacement of limestone or lime mud prior to lithification. It is resistant to erosion and can either contain bedded layers or unbedded layers. It is less soluble than limestone in weakly acidic groundwater, but it can still develop solution features over time.

Site Geology

The Site geology has been investigated through the advancement of soil borings and the installation of shallow and deep monitoring wells. The shallow monitoring wells were installed at depths ranging from 13 ft-bgs to 16 ft-bgs through soil and saprolite residuum. The deep well (DW-1) was installed to a depth of 44 ft-bgs. Boring logs are included in Appendix F.

To illustrate the subsurface geology of the Site, two vertical cross-sections were created using information obtained from the boring logs. Figure 7A shows the locations of cross-section lines A-A' and B-B'. Cross-section A-A' and B-B' are shown on Figures 7B and 7C, respectively. Cross-section A-A' was prepared in an east-west orientation while cross-section B-B' was prepared in a southwest-northeast orientation.

A review of the boring logs and associated cross-sections indicate that the subsurface geology consists of multi-colored clays with some gravel grading to the bedrock. Bedrock was reached in DW-1 at approximately 20 ft-bgs. Based on the hardness of the soils in other borings at the Site, it appears that bedrock exists approximately 20 ft-bgs across the Site.

3.1.5 Regional and Site Hydrogeology

Regional Hydrogeology

The upper boundary of unconfined groundwater in the Ridge and Valley is formed by the water table or surficial water bearing zones. The water table can be loosely defined as the boundary between saturated and unsaturated soil zones. The depth to the water table may range from a few ft-bgs to up to 50 ft-bgs along mountainous terrain. In the Ridge and Valley province, the water table is usually situated within the soil-saprolite residuum and the upper portion of the fractured dolomite bedrock. In areas where saprolite thicknesses are minimal, the water table may reside almost entirely in fractured bedrock. The soil-saprolite residuum generally has a relatively large storage capacity with a moderate transmissivity. The bedrock fracture system generally has a relatively low storage capacity with a high transmissivity where fracture systems are interconnected. If bedrock fracturing is significant, a hydraulic connection between the surficial water bearing zone and deeper groundwater aquifers may occur at varying depths within the bedrock.

Groundwater flow in the soil-saprolite/fractured bedrock zone often mimics the ground surface topography except where controlled by subsurface geologic structures or preferential pathways. These pathways may be caused by heterogeneities in the soil, weathering patterns of the saprolite, foliated bedding planes, faults, fractures, or other relict bedrock features. Groundwater flow is usually unconfined with recharge occurring from rainfall penetrating upland areas and discharge occurring as baseflow to streams and creeks in low lying areas. These flow regimes are commonly referred to as slope aquifer systems. Depending on the interconnection of fracture zones, a downward gradient is commonly observed in upland areas while an upward gradient is generally present in low areas.

Productive groundwater wells in the Ridge and Valley may be located in the saprolite residuum, fractured crystalline bedrock, or a combination of both. Water in the bedrock is transmitted via connected fractures within the rock unit. The quantity, size, and degree of connection between these fractures or discontinuities are generally more significant than the lithology in determining the amount of water available for withdrawal. Rates of withdrawal are often higher along contact zones between rock units. Secondary permeability and fracture size generally decrease

with depth due to overburden pressures except in areas where deep thrust fractures are present. The Ridge and Valley province in the northwestern corner of Georgia is underlain by layers of sandstone, limestone, dolostone, and shale. Wells tapping limestone and dolomite aquifers in this province can be very productive (Tyson, 1993).

Site Hydrogeology

The surficial water bearing zone or uppermost aquifer beneath the Site includes the soil-saprolite unit above the bedrock interface. It is likely that this aquifer is interconnected to the bedrock aquifer beneath it via fractures in the rock. The vertical extent of the bedrock aquifer below 50 ft-bgs has not been investigated.

The groundwater under the Site flows from the high elevation at the western property boundary towards the northeast and the southeast. Considering the surface topography of the Site, the depth the groundwater, and the groundwater flow direction, groundwater at the Site is expected to enter the small stream east of the Site.

3.1.6 Groundwater Flow Direction and Gradient

The depth to groundwater at the Site was measured by EPS personnel in December 2013 in monitoring wells existing at that time. Groundwater elevations were calculated by subtracting the measured depth to groundwater from the surveyed top-of-well casing elevations. The groundwater depths and calculated elevations for the December 2013 sampling event and all previous sampling events are shown in Table 3. A Potentiometric Surface Map for December 2013 is included as Figure 8. As shown on the figure, groundwater flows toward the southeast and northeast, which is consistent with historical data. Based on the December 2013 Potentiometric Surface Map, the average horizontal hydraulic gradient for the Site is 0.03 ft/ft.

Generally, in Ridge and Valley slope aquifer systems an upward vertical flow gradient occurs near creeks or in valley areas and a downward vertical flow gradient occurs on hill sides (Lohman, 1972). The groundwater elevation for MW-7 was 794.12 ft and the elevation for the deeper well DW-1 was 793.62 ft. The lower elevation in DW-1 suggests that a downward vertical gradient may be present between the surficial soil aquifer and deeper bedrock aquifer.

3.1.7 Hydraulic Conductivity Data

On June 28, 2007 EPS performed slug tests on wells MW-4, MW-6, and MW-9 to evaluate the hydraulic conductivity of the upper aquifer. Hydraulic conductivity was determined using the Bower and Rice Graphical Method (Bouwer and Rice, 1976) and the results are shown below.

Well No.	K value (cm/sec)	K value (ft/day)
MW-4	7.4×10^{-5}	0.21
MW-6	1.2×10^{-4}	0.33
MW-9	1.5×10^{-4}	0.42
Average	1.1×10^{-4}	0.32

The average hydraulic conductivity value was calculated to be of 1.1×10^{-4} centimeters per second (cm/sec) or 0.32 feet per day (ft/day). This is consistent with published values for clayey soils. The Bower and Rice graphs are included in Appendix G.

3.1.8 Groundwater Flow Velocity

The seepage velocity or groundwater flow velocity is the average speed of groundwater movement by advective processes in the water-bearing zone. The seepage velocity is calculated by multiplying the hydraulic conductivity by the hydraulic gradient and dividing by the effective porosity. The effective porosity is sometimes referred to as the “drainable porosity” and is considered roughly equivalent to specific yield for sandy soils in unconfined units. This parameter is generally estimated using published values.

The groundwater flow velocity was calculated using the following formula:

$$V = \left[\frac{K \frac{dh}{dl}}{n} \right]$$

Where:

- k = the average hydraulic conductivity (0.32 ft./day)
- dh/dl = the hydraulic gradient (0.032 ft./ft.)
- n = the estimated effective porosity (0.15 from Fetter, 1988)

Using this formula, a calculated groundwater flow velocity of 0.07 ft/day (26 ft/year) was determined. It should be noted that this calculated value was derived under the assumption that groundwater flow at the Site occurs through a homogeneous, isotropic, porous medium. Since groundwater flow beneath the Site likely occurs through a heterogeneous matrix that may contain secondary fracture pathways, this calculated flow value should be considered only an estimate of the actual groundwater flow velocity.

3.2 Risk Reduction Standards

3.2.1 Soil RRS

In a letter dated June 24, 2011, the GA EPD concurred that the Site was in compliance with Residential RRSs for soil based on CSI Realty's December 29, 2009 Revised Compliance Status Report.

3.2.2 Groundwater RRSs

Regulated substances detected in groundwater at the Site consist of TCA, DCA, DCE, acetone, Freon-113, Freon-12, IPB, PCE, and lead. Type 1 RRSs were calculated for these constituents. TCA, DCE, PCE, and IPB were detected at concentrations which exceed the Type 1 RRSs, and Type 2 RRSs were calculated for these constituents. DCE and PCE exceed the Type 2 RRSs, and Type 4 RRSs were calculated for DCE and PCE. PCE is the only constituent that exceeds the Type 4 RRS. Table 1 summarizes Types 1, 2, and 4 RRSs and compares them to the maximum detected concentrations. RRS calculations are shown in Appendix H.

3.3 Potential Receptors and Exposure Pathways

3.3.1 Potential Environmental Receptors

The Site and adjacent properties are located in a predominantly residential and industrial setting. Common environmental receptors in this type of setting may include protected species, wetland areas, public drinking water wells, and surface water bodies.

3.3.1.1 Protected Species

Information compiled by the Georgia Natural Heritage Program was reviewed for Walker County, Georgia to identify sensitive wildlife receptors or protected species near the Site. The protected species identified in the Walker County include the following:

Plants

- Ohio Buckeye
- Purple Foxglove
- Heath Aster
- Phlox-leaved Aster
- Willow-leaf Aster
- Wild Daisy
- Glade Blue Indigo
- Bluehearts
- Wild Hyacinth
- White Bear Lake Sedge
- Broadleaf Sedge
- Purple Sedge
- Tussock Sedge
- Shellbark Hickory
- Alabama Lipfern
- American Smoketree
- Three-flowered Hawthorn
- Pink Ladyslipper
- Tennessee Fragile Fern
- Gattinger Prairie Clover
- Mullein Foxglove
- Cream-flowered Tick-trefoil
- American Dropseed
- Log Fern
- Harbinger-of-spring
- Mountain Witch-alder
- Blue Ash
- Goldenseal
- Glade St. Johnswort
- Twinleaf
- Texas Plains Rush
- Naked-fruit Rush
- Least Gladecress
- Gladecress
- Wood Lily
- Broadleaf Gromwell
- Climbing Fern
- Fraser's Loosestrife
- Limerock Milkvine
- Virginia Bluebells
- Sprouting Muhly
- Alabama Snow-wreath
- Marble-seed
- Limestone Adder-tongue Fern
- American Ginseng
- Silverling
- Miami-mist
- Hairy Mockorange
- Broadleaf Phlox
- Tennessee Leafcup
- Shadow-witch Orchid
- Bigleaf Pondweed
- Granite Gooseberry
- Cumberland Rose Gentian
- Large-flowered Skullcap
- Roundleaf Catchfly
- Virginia Spirea
- Nuttall's Hedge-nettle
- Celandine Poppy
- Silky Aster
- Downy Bush-pea
- Appalachian Filmy Fern
- Dwarf Filmy Fern
- Bent Trillium
- Lanceleaf Trillium
- Barksdale Trillium
- September Elm
- Ozark Bunchflower
- Limerock Arrow-wood
- Glade Violet
- Appalachian Cliff Fern

Animals

- | | | |
|-----------------------------|--------------------------------|------------------------------|
| · Bachman's Sparrow | · Finelined Pocketbook | · Popeye Shiner |
| · Green Salamander | · Four-toed Salamander | · Burrhead Shiner |
| · Chickamauga Crayfish | · Flame Chub | · Telescope Shiner |
| · Chattooga River Crayfish | · Lined Chub | · Yellowfin Madtom |
| · Blackbarred Crayfish | · Tennessee Heelsplitter | · Dusky Darter |
| · Spotfin Shiner | · Spotted Spreadwing | · Red-cockaded Woodpecker |
| · Coosa Darter | · Sweetflag Spreadwing | · Pigeon Mountain Salamander |
| · Blueside Darter | · Scarlet Shiner | · Southern Pigtoe |
| · Greenbreast Darter | · Mountain Shiner | · Skirted Hornsnail |
| · Redline Darter | · Alabama Moccasinshell | · Tapered Cave Beetle |
| · Banded Darter | · Gray Myotis | · Georgian Cave Beetle |
| · Northern Studfish | · Eastern Small-footed Myotis | · Pygmy Shrew |
| · Tennessee Cave Salamander | · Southern Appalachian Woodrat | · Mountain Creekshell |

A letter from the Wildlife Resources Division of the Georgia Department of Natural Resources indicated that there are no records of species of concern within the project area. The letter is attached as Appendix I.

3.3.1.2 Wetlands and Surface Water Bodies

A review of a National Wetland Inventory Map prepared by the U.S. Fish and Wildlife Service, indicates that the Site and adjacent properties are not located in identified wetland areas. A small stream, which forms the headwaters of the Chattooga River enters the Site from the north. The stream is dammed and forms a small pond on the northern end of the Site. The pond discharge then flows off the property to the east. It is likely that groundwater flows into the stream and pond. Based on groundwater flow from the source area, the stream is considered to be a potential receptor of the groundwater plume. In October 2005, a surface water sample was collected from the pond. VOCs were not detected in this sample.

3.3.2 Potential Human Receptors

The Site includes a manufacturing building (approximately 74,000 square feet), a paved parking lot, a gravel drive leading to a paved loading dock, and a small pond. The future use of the Site will likely remain industrial; however, future residential use of the Site is evaluated below. The adjoining properties are used for residential, commercial, and industrial purposes.

3.3.2.1 Water Well Usage

In November 2005, a water well survey was performed by EPS to identify potential nearby private or public water wells. The survey involved a records search of the EPD files, communications with the City of LaFayette Water Department, a drive-by survey of the properties within a mile of the Site, and a USGS database search. The records search of the EPD files did not identify any water wells in the vicinity of the Site. EPS also reviewed the USGS water well database. No wells were identified in the USGS database within a three mile radius of the Site.

On November 28, 2005, EPS performed a drive-by survey of the properties within a one-mile radius of the Site. No private drinking water wells were observed. EPS identified the City of LaFayette drinking water intake as being located approximately 0.4 miles north of the Site.

Mr. Jim Speir, the City of LaFayette Director of Water & Sewer Utilities, confirmed that the intake location for the City of LaFayette's public water supply is located on a spring approximately 0.4 miles north of the Site. Figure 3 shows the location of the City of LaFayette drinking water intake relative to the Site. Mr. Speir stated that he was not aware of any private drinking water wells present within one mile of the Site. No other public water wells or intake locations are present in the City of LaFayette.

The only drinking water source receptor identified during this survey was the City of LaFayette water intake located along a spring approximately 0.4 miles north of the Site. The intake is located topographically upgradient and upstream of the Site and therefore, human exposure to the VOCs in the groundwater appears unlikely.

3.3.2.2 Underground Utilities

Underground utilities can act as conveyances by intercepting migrating regulated substances through a vapor phase or dissolved phase in the groundwater. In both cases, accumulation may occur inside a hollow pipe or along a preferential pathway created from permeable backfill materials used during placement of the utilities. Human exposures may occur in large diameter utility pipes, manholes, culverts, storm grates, or related access points.

The location of underground utilities in the vicinity of the groundwater plume is shown on Figure 2. The utilities identified include electrical conduits and small diameter roof drain storm water pipes. These utilities are likely located at depths between 2 and 3 ft-bgs. Based on the measured depth to groundwater of 4-5 ft-bgs, these underground utilities could intercept the groundwater table during periods of high groundwater levels.

3.3.2.3 Potential On and Off-Site Receptors

Current/Future Site Worker: Facility workers are expected to work approximately 40 hours per week at the Site. Because the soil has been certified to Residential RRS, and a UEC is being recorded for the Site limiting groundwater use, the only exposure pathway for facility workers is

vapor intrusion from the groundwater plume to the indoor air. As discussed in Section 4.4, a vapor intrusion health risk is not present at the site.

Current/Future Groundskeeper: The grounds are currently maintained by a landscaping contractor on an as-needed basis, and landscaping activity is likely to be required for any future use scenarios. Since the soil has been certified to Residential RRSs, groundskeeper exposure to the VOCs at concentrations greater than Residential RRSs is not likely.

Future Construction/Utility Worker: No construction or utility work activities are currently planned at the Site. However, it is possible that these activities could be conducted in the future. These workers could potentially have short-term (<1 year) exposure to chemicals in groundwater via ingestion, dermal contact, and inhalation of volatiles.

Future On-Site Resident: The Site is currently used for industrial purposes and will likely remain industrial in the future. However, if the Site were to be used for residential purposes in the future, the soils are protective of residential use, and groundwater usage will be prohibited through the use of a UEC.

Potential Off-Site Receptors: There are no potential off-site human receptors. The property immediately downgradient of the Site is the Chattooga and Chickamauga Railway Right-of-Way and further downgradient is a stream and a lower lying area owned by the City of LaFayette. As discussed in Section 4.3.3, it is not likely that the groundwater plume will migrate to the stream.

4 GROUNDWATER COMPLIANCE

4.1 Groundwater Delineation

Groundwater has been delineated to the Type 1 RRSs. Figures 4C through 4F show the data from the four quarterly groundwater monitoring events conducted in 2013. All four compounds (TCA, DCE, IPB, and PCE) detected above the Type 1 RRSs are shown to be delineated on these figures.

4.2 Compliance with Residential and Non-Residential RRSs

Each of the regulated constituents detected in groundwater are in compliance with the Residential RRSs with the exception of DCE and PCE. DCE is in compliance with Non-Residential RRSs while PCE is not. Although Freon-113 was not detected above its Type 1 RRS, the compound was investigated further due to elevated concentrations, and it was determined that a Freon-113 DNAPL was not present. Table 1 summarizes the constituents detected in groundwater and compares them to the RRSs.

- DCE was detected in two soil borings, located inside of the building footprint, in 2006 and more recently in MW-10, located inside the building, above the Type Residential RRS of 103 µg/L. The maximum concentration of DCE detected was 290 µg/L, which is below the Type 4 RRS of 520 µg/L.
- PCE was detected above the Residential RRSs in groundwater samples from three borings and above the Non-Residential RRSs in two of these borings in 2006. More recent sampling results indicate PCE is above the Non-Residential RRS in only one monitoring well, MW-10, with concentrations fluctuating around 150 µg/L.
- Freon-113 has not been detected above the Residential RRS in groundwater. However, in 2006, it was detected at 27,000 µg/L in groundwater samples from borings SB-22 and SB-23 located inside the building, and the GA EPD was concerned of the potential presence of Freon-113 DNAPL. Monitoring wells MW-10 and MW-11 were installed in the vicinity of SB-22 and SB-23 as a nested well pair, with MW-10 screened near the water table (10-12.5 ft-bgs) and MW-11 screened on top of bedrock (17.5-20 ft-bgs). Although initial sampling results from MW-11 indicated elevated concentrations (15,000 and 21,000 µg/L) of Freon-113, follow-up sampling results were much lower (27 µg/L and non-detect). It is therefore believed that the initial elevated concentrations were the result of poor well development (due to slow recharge). Because significantly higher concentrations of Freon-113 exist in the shallow well (MW-10) and because the Freon-

113 concentrations in the deeper well (MW-11) are minor, it does not appear that Freon-113 exists as a DNAPL.

4.3 Groundwater Modeling

4.3.1 Introduction

BIOCHLOR Natural Attenuation Decision Support System (version 2.2) was used to model biodegradation of PCE at the Property. BIOCHLOR is an analytical model approved by the U.S. Environmental Protection Agency that is used to simulate the degradation of chlorinated ethenes and ethanes. It is an Excel-based program based on the Domenico analytical solute transport model. BIOCHLOR simulates advection, 3-D dispersion, linear adsorption and biotransformation via reductive dechlorination.

The primary purpose of this modeling is to predict concentrations at the hypothetical Point of Exposure 1000 ft downgradient of the plume edge and compare the model predictions to the Type 1 RRS (5 µg/L) for PCE. A secondary purpose is to estimate concentrations that may theoretically reach the nearby headwater stream of the Chattooga River and compare the predicted concentrations to the Georgia In-Stream Water Quality Standard (ISWQ).

4.3.2 Model Development and Calibration

The groundwater at the Property flows in two different directions (see Figure 8). Accordingly, two different models were developed and calibrated to simulate each of these flow directions. The highest concentrations of PCE in groundwater were observed at borings SB-22 and SB-23. Thus, the zero distance area (or “initial concentrations”, model variable C_0) was considered to be in the area of SB-22 and SB-23 (which also includes wells MW-8, MW-10 and MW-11) flowing in two different directions. Flow path A is to the southeast and includes wells MW-2, MW-3, MW-13, MW-14, and borings SB-1 and SB-13. Following flow path A, the headwater of the Chattooga River is encountered approximately 288 ft from the zero distance. Flow path B is to the north-east and includes wells MW-5, MW-7, MW-12, TW-1 and borings SB-16 and SB-27. Following flow path B, the headwaters of the Chattooga River is encountered approximately 160 ft from the zero distance.

The input parameters used in the model are presented in Table A of Appendix A. The advection parameters (e.g., hydraulic conductivity) were based on site-specific values. The dispersion and adsorption parameters were primarily based on default values available in the model documentation. The biotransformation decay coefficients were not used as biodegradation does not appear to be a primary factor at this Site. The model assumes that there is a continuous source since 1980 when the facility converted to yarn twisting.

The modeled C_0 concentrations were developed during model calibration. Historical groundwater data (from 2005 through 2013) were used to adjust the C_0 concentrations and decay coefficients to develop a model that best represented the conditions at the Site. The C_0 concentrations were chosen primarily to model the data from 2006, when the highest concentration of PCE was observed in groundwater. The highest PCE concentration observed in groundwater was 0.35 mg/L at SB-23; the C_0 concentration was rounded up to 0.4 mg/L.

4.3.3 Sensitivity Analysis

A sensitivity analysis was conducted to evaluate the influence or relative importance of key input variables and assumptions on the predicted concentrations. The parameters evaluated in the sensitivity analysis included the retardation factor, hydraulic conductivity and porosity. This analysis was run for model year 2006 and 2043 (30 years from the last groundwater sampling event). For Flow Path A the sensitivity analysis was conducted at two distances: 72 feet (MW-13) and 170 feet (MW-14). For Flow Path B the sensitivity was conducted at 118 ft (MW-12).

The predicted concentrations (shown in Table B and Table C for 2006 and 2043, respectively) at each of these distances were determined for three different conditions for each parameter being considered: (1) baseline, (2) a value higher than baseline, and (3) a value lower than baseline. The resulting concentrations are also compared to the Type 1 RRS for an additional frame of reference.

Changes in the retardation factor, porosity and hydraulic conductivity did not make an appreciable difference in the concentrations. It is important to note that in all of these simulations, the concentrations did not exceed the Type 1 RRS.

4.3.4 PCE Results

Chart Group 1 in Appendix A shows PCE output screens from the BIOCHLOR model for each year that data was collected from 2005 through 2013 and for year 2043 (30 years after the last groundwater sampling event) for the two different flow paths (Flow Path A and Flow Path B). The boxes on these charts represent analytical data collected from groundwater in that year. In year 2013 groundwater was collected quarterly, thus the high and low concentrations observed in 2013 are both shown on the chart to represent the range of concentrations observed.

These charts show that the model, although not perfect, is a good representation of conditions at the Site and can be used to predict future concentrations. The model actually over predicts concentrations most years indicating that the model is conservative. Thus, the model will conservatively estimate the concentrations of PCE into the future.

The projected concentrations for year 2043 show that the modeled PCE concentrations at the point of demonstration wells (MW-12, MW-13, and MW-14) and the hypothetical Point of Exposure (1000 ft) will not exceed the Type 1 RRS. In addition, the projected concentrations for

year 2043 show that the modeled PCE concentrations at the headwaters for the Chattooga River do not exceed the ISWQ. The PCE plume does not reach the stream following Flow Path A. For Flow Path B, the PCE plume does not reach the stream at concentrations exceeding the ISWQ. Therefore, in response to Comment #3 in the GA EPD's letter dated March 30, 2014, the combination of the two flow paths does not cause PCE concentrations entering the stream at concentrations which exceed the ISWQs (3.3 µg/L).

4.3.5 Conclusions

Comparison of the model predictions to actual groundwater results at the Site indicates that the model can be used to conservatively predict future concentrations. According to the modeling results for the most recent year sampled (2013) and thirty years from then (2043), the concentrations at the Point of Demonstration wells and at the hypothetical Point of Exposure (1000 ft) do not exceed the Type 1 RRS. Thus, the model predicts that groundwater concentrations at the Point of Exposure will not exceed Type 1 RRSs. Additionally, the model predicts that the concentrations of PCE in groundwater at the points it reaches the headwater of the Chattooga River are less than the ISWQ.

4.4 Vapor Intrusion Assessment

In 2009, potential risks associated with PCE and Freon-113 vapor intrusion were assessed using advanced versions of the 2004 Johnson and Ettinger Model specific to soil and groundwater sources. The models were recently updated in accordance with Comments #9 and #10 of the GA EPD's March 30, 2012 letter. This model, published by the US EPA Office of Emergency and Remedial Response, is an enhanced implementation of the US EPA Office of Solid Waste and Emergency Response's Subsurface Vapor Intrusion Guidance (2002).

Vapor intrusion was assessed using the highest soil and groundwater concentrations detected for Freon-113 and PCE under the existing building during all previous sampling events. Exposure parameters listed in Appendix J were derived from Table 3 of Appendix III of the Hazardous Site Response Rule (391-3-19). The default air exchange rate of 0.25 volumes per hour was used in the models.

4.4.1 Non-Residential Exposure Modeling

For non-residential exposure modeling, incremental risk associated with vapor intrusion of PCE was assessed using the maximum concentrations detected in soil (0.024 mg/kg) and groundwater (350 µg/L) beneath the building. The cancer risk associated with groundwater was 5.5×10^{-8} , and the associated hazard quotient was 1.5×10^{-2} . Modeling of measured concentrations of PCE in soil resulted in a cancer risk value of 3.9×10^{-9} and a hazard quotient of 1.1×10^{-3} . Neither the target cancer risk value of 1.0×10^{-5} nor the target hazard quotient of 1.0 was exceeded.

Since Freon-113 is not considered a potent carcinogen, the cancer risk determination is not applicable. The hazard quotient was estimated using the maximum groundwater (27,000 µg/L) and soil (4.2 mg/kg) concentrations detected beneath the building. Model results estimated hazard quotients of 3.0×10^{-2} for Freon-113 in groundwater and 7.8×10^{-4} for Freon-113 in soil. Neither of these hazard quotients exceeded the target hazard quotient of 1.0. Model results are summarized in Table 4. Model parameters can be found in Appendix J.

4.4.2 Residential Exposure Modeling

For residential exposure modeling, incremental risk associated with vapor intrusion of PCE was assessed using the maximum concentrations detected in soil (0.3 mg/kg) and groundwater (350 µg/L) at the Site. The cancer risk associated with groundwater was 3.2×10^{-7} , and the associated hazard quotient was 7.3×10^{-2} . Modeling of measured concentrations of PCE in soil resulted in a cancer risk value of 3.2×10^{-7} and a hazard quotient of 7.1×10^{-2} . Neither the target cancer risk value of 1.0×10^{-6} nor the target hazard quotient of 1.0 was exceeded.

Since Freon-113 is not considered a potent carcinogen, the cancer risk determination is not applicable. The hazard quotient was estimated using the maximum groundwater (27,000 µg/L) and soil (6.3 mg/kg) concentrations detected at the Site. Model results estimated hazard quotients of 1.4×10^{-1} for Freon-113 in groundwater and 4.0×10^{-3} for Freon-113 in soil. Neither of these hazard quotients exceeded the target hazard quotient of 1.0. Model results are summarized in Table 4. Model parameters can be found in Appendix J.

4.5 Institutional Controls

Pursuant to Section 12-8-107(h) of the VRP Act, a UEC has been prepared and was submitted in draft to the EPD On October 28, 2014, to restrict groundwater use.

5 REFERENCES

- Bouwer, H. and Rice, R.C., 1976, *A Slug Test Method for Determining Hydraulic Conductivity of Unconfined Aquifers with Completely or Partially Penetrating Wells*, Water Resources Research, 12-3, pp. 423-428.
- Bouwer, H., 1989, *The Bouwer and Rice Slug Test - An Update*, Groundwater, vol. 24, no. 3, pp. 304-309.
- Clark & Zisa, *A Physiographic Map of Georgia*, Department of Natural Resources, Georgia Geologic Survey, 1987.
- Fetter, C. W., 1988, *Applied Hydrogeology*, 2nd Edition, Macmillan Publishing Company, New York, 592 p.
- Lohman, S. W., 1972, *Ground-Water Hydraulics*, Professional Paper 708, U.S. Department of the Interior, Geological Survey, 67 p.
- U.S. Forest Service, Ecological Subregions of the U.S., November 5, 1993
<http://www.fs.fed.us/land/pubs/ecoregions/ch20.html#231D>
- Tyson, Anthony W., 1993 Georgia's Ground Water Resources, University of Georgia College of Agricultural and Environmental Sciences, Bulletin 1096 October 1993.
- U.S. Environmental Protection Agency, Region 4, *Field Branches Quality System and Technical Procedures*, Athens, Georgia.


APPENDIX A

Groundwater Model

Chart Group 1 PCE Modeling Results


2005 PCE

Flow Path A




Flow Path B


2006 PCE



2006 PCE



2007 PCE



2007 PCE





Chart Group 1 PCE Modeling Results


2009 PCE

Flow Path A




Flow Path B


2011 PCE



2011 PCE



2013 PCE



2013 PCE





Chart Group 1 PCE Modeling Results



0.0033

Table A. Input Parameters for the BIOCHLOR Model

Mechanism	Parameter	Value	Units	Basis
Advection	Hydraulic Conductivity	1.10E-04	cm/s	Average hydraulic conductivity presented in the 2009 Revised CSR (EPS, 2009)
	Hydraulic Gradient (direction a)	0.015	ft/ft	Based on MW-10 to MW-13
	Hydraulic Gradient (direction b)	0.02	ft/ft	Based on MW-7 to MW-12
	Effective Porosity	0.15	unitless	Typical value for lithological formation (EPA, 2000) and used historically for the Property
Dispersion	Alpha X	6.2711	ft/ft	Modified Xu Eckstein (L approx 85 ft)
	Alpha Y/Alpha X	0.1	unitless	EPA model default
	Alpha Z/Alpha X	5.00E-02	unitless	EPA model default
Adsorption	Soil Bulk Density	1.7	kg/L	EPA model default
	Fraction Organic Carbon	0.001	unitless	EPA model default
	Organic Carbon Partitioning Coefficients			
	PCE	426	L/kg	EPA model default
	TCE	130	L/kg	EPA model default
	DCE	125	L/kg	EPA model default
	VC	30	L/kg	EPA model default
	Ethenes	302	L/kg	EPA model default
	Retardation Factor	2.47		Calculated based on above values
Biotransformation	1st Order Decay Coefficients			
	TCA->DCA		1/yr	
	DCA->CA		1/yr	
	PCE->TCE		1/yr	
	TCE->DCE		1/yr	
	DCE->VC		1/yr	
	VC->Ethene		1/yr	
General	Simulation Time	varies	yr	Assuming the source began in 1980
	Modeled Area Width	700	ft	Assumption
	Modeled Area Length	1085	ft	Assumption
	Zone length	1085	ft	Assuming one-zone
Source Contribution	Type	Continuous		Assumes continuous source concentrations throughout time
	Source Thickness in Saturated Zone	15	ft	Approximate thickness of aquifer
	Source Width	0.1	ft	Based on model calibration
	Source Concentrations			
	PCE	400	mg/L	Based on model calibration (highest value observed in groundwater was 350 mg/L)

EPA,2000: BIOCHLOR Natural Attenuation Decision Support System. User's Manual Version 1.0 USEPA. January 2000

EPA,2002: BIOCHLOR Natural Attenuation Decision Support System. User's Manual Addendum. USEPA. March 2002.

Table B. Sensitivity Analysis (Year 2006)

Retardation Factor										
	Concentrations (mg/L) at 72 ft (A)			Concentrations (mg/L) at 170 ft (A)			Concentrations (mg/L) at 118 ft (B)			Type 1 RRS
	R=5	R=2.47 (Baseline)	R=1.4	R=5	R=2.47 (Baseline)	R=1.4	R=5	R=2.47 (Baseline)	R=1.4	
PCE	0.003	0.005	0.005	<0.001	<0.001	<0.001	0.001	0.001	0.0015	0.005
Hydraulic Conductivity (cm/s)										
	Concentrations (mg/L) at 72 ft (A)			Concentrations (mg/L) at 170 ft (A)			Concentrations (mg/L) at 118 ft (B)			Type 1 RRS
	K=7.4e-5	K=1.1e-4 (Baseline)	K=1.5e-4	K=7.4e-5	K=1.1e-4 (Baseline)	K=1.5e-4	K=7.4e-5	K=1.1e-4 (Baseline)	K=1.5e-4	
PCE	0.005	0.005	0.005	<0.001	<0.001	<0.001	<0.001	0.001	0.001	0.005
Porosity										
	Concentrations (mg/L) at 72 ft (A)			Concentrations (mg/L) at 170 ft (A)			Concentrations (mg/L) at 118 ft (B)			Type 1 RRS
	n=0.2	n=0.15 (Baseline)	n=0.01	n=0.2	n=0.15 (Baseline)	n=0.01	n=0.2	n=0.15 (Baseline)	n=0.01	
PCE	0.005	0.005	0.005	<0.001	<0.001	<0.001	<0.001	0.001	0.001	0.005

Basis for values selected:

Retardation Factor - R-1.4 based on the example presented in the 2000 Guidance, R=5 is slightly higher than that presented in the 2000 Guidance because the baseline value is higher than that shown in the Guidance.

Hydraulic Conductivity - based on the lowest and highest values calculated at the Site (from the 2009 CAP)

Porosity - based on low and high values reasonable for the lithological formation (EPA, 2000)

Table C. Sensitivity Analysis (Year 2043)

Retardation Factor										
	Concentrations (mg/L) at 72 ft (A)			Concentrations (mg/L) at 170 ft (A)			Concentrations (mg/L) at 118 ft (B)			Type 1 RRS
	R=5	R=2.47 (Baseline)	R=1.4	R=5	R=2.47 (Baseline)	R=1.4	R=5	R=2.47 (Baseline)	R=1.4	
PCE	0.005	0.005	0.005	<0.001	0.001	0.001	0.001	0.001	0.0015	0.005
Hydraulic Conductivity (cm/s)										
	Concentrations (mg/L) at 72 ft (A)			Concentrations (mg/L) at 170 ft (A)			Concentrations (mg/L) at 118 ft (B)			Type 1 RRS
	K=7.4e-5	K=1.1e-4 (Baseline)	K=1.5e-4	K=7.4e-5	K=1.1e-4 (Baseline)	K=1.5e-4	K=7.4e-5	K=1.1e-4 (Baseline)	K=1.5e-4	
PCE	0.005	0.005	0.005	<0.001	0.001	0.001	0.001	0.001	0.0015	0.005
Porosity										
	Concentrations (mg/L) at 72 ft (A)			Concentrations (mg/L) at 170 ft (A)			Concentrations (mg/L) at 118 ft (B)			Type 1 RRS
	n=0.2	n=0.15 (Baseline)	n=0.01	n=0.2	n=0.15 (Baseline)	n=0.01	n=0.2	n=0.15 (Baseline)	n=0.01	
PCE	0.005	0.005	0.005	0.001	0.001	0.001	<0.001	0.001	0.0015	0.005

Basis for values selected:


Retardation Factor - R-1.4 based on the example presented in the 2000 Guidance, R=5 is slightly higher than that presented in the 2000 Guidance because the baseline value is higher than that shown in the Guidance.

Hydraulic Conductivity - based on the lowest and highest values calculated at the Site (from the 2009 CAP)

Porosity - based on low and high values reasonable for the lithological formation (EPA, 2000)

APPENDIX B

Figures



SOURCE: GOOGLE EARTH

Approximate Site Boundary



1050 Crown Pointe Pkwy
Suite: 550
Atlanta, GA 30338
404.315.9113



Drawn by: JDD


Date: October 2014

Color Spectrum
29 Probasco Street
LaFayette, GA 30728

SITE LOCATION MAP

FIGURE

1



LEGEND

- ===== Railroad Tracks
- - - - - Fence Line
- Water Flow Direction
- - - - - Site



1050 Crown Pointe Parkway
Suite 350
Atlanta, GA 30338
(404) 315-9113

DRN: JDD


DATE: October 2014

Color Spectrum
29 Probasco Street
LaFayette, GA 30728

Site Plan and Site
Vicinity Map

FIGURE

2



Scale shown above

Source: USGS Quadrangle Map Lafayette, Georgia



1050 Crown Pointe Pkwy
Suite: 550
Atlanta, GA 30338
404.315.9113



Drawn by: JDD

Date: October 2014

Color Spectrum
29 Probasco Street
LaFayette, GA 30728

USGS QUADRANGLE MAP

FIGURE

3





MILL STREET

PROBASCO STREET

LEGEND

	Groundwater Monitoring Well Location
	Temporary Monitoring Well Location
	Abandoned Temporary Monitoring Well Location
	Fenceline
1,1,1-TCA	1,1,1-Trichloroethane
1,1-DCA	1,1-Dichloroethane
1,1-DCE	1,1-Dichloroethene
PCE	Tetrachloroethene
VOC	Volatile Organic Compound
ND	Non-Detect
ug/L	micrograms per liter




1050 Crown Pointe Parkway
Suite 350
Atlanta, GA 30338
(404) 315-9113


DRN: JDV DATE: October 2014

Color Spectrum
29 Probasco Street
LaFayette, GA 30728

Historical Soil Boring
Groundwater Results

FIGURE
4A









 1050 Crown Pointe Parkway Suite 350 Atlanta, GA 30338 (404) 315-9113	DRN: JDD	DATE: October 2014
	Color Spectrum 29 Probasco Street LaFayette, GA 30728	
	Groundwater Sampling Results (March 2013)	

FIGURE 4C



 1050 Crown Pointe Parkway Suite 350 Atlanta, GA 30338 (404) 315-9113	DRN: JDD	DATE: October 2014	FIGURE 4D
	Color Spectrum 29 Probasco Street LaFayette, GA 30728		
	Groundwater Sampling Results (June 2013)		







MILL STREET

PROBASCO STREET

MILL POND

CONC. PAD

CONC. PAD

CHATTAUGA & CHICKAMAUGA RAILWAY

LEGEND



Groundwater Monitoring Well Location




Soil Boring (December 2006)



Soil Boring (June 2007)



Soil Boring (October 2009)



Fenceline

SB-34			
Date	6/21/07		
Depth	1 ft	7 ft	
Freon-113	0.68	4.2	
DCA	ND	0.0073	
DCE	ND	0.039	
TCA	ND	0.0073	
PCE	ND	0.039	
Acetone	ND	0.039	

ND

Not Detected

BDL

Below Detection Limit

Sample Name

Sample Date

Sample Depth

Freon-113 (mg/kg)

1,1-Dichloroethane (mg/kg)

1,1-Dichloroethene (mg/kg)

1,1,1-Trichloroethane (mg/kg)

Tetrachloroethene (mg/kg)

0 20 40
Feet



1050 Crown Pointe Parkway
Suite 350
Atlanta, GA 30338
(404) 315-9113

DRN: JDV

DATE: October 2014

Color Spectrum
29 Probasco Street
LaFayette, GA 30728

Soil Analytical Results

FIGURE

5

Geologic Map of Georgia -- Ridge and Valley

Georgia Geologic Survey
1977

David E. Lawton



0 7.5 15
Miles



PENNSYLVANIAN
ROCKS



MISSISSIPPIAN
ROCKS



DEVONIAN ROCKS



CAMBRIAN AND
ORDOVICIAN ROCKS



CAMBRIAN ROCKS



CAMBRIAN-
preCAMBRIAN ROCKS



1050 Crown Pointe Pkwy
Suite: 550
Atlanta, GA 30338
404.315.9113



Drawn by: JDD


Date: October 2014


Color Spectrum
29 Probasco Street
LaFayette, GA 30728


GEOLOGIC MAP OF THE GEORGIA RIDGE AND VALLEY


FIGURE

6




 1050 Crown Pointe Parkway Suite 350 Atlanta, GA 30338 (404) 315-9113	DRN: JDD	DATE: October 2014	FIGURE 7A
	Color Spectrum 29 Probasco Street LaFayette, GA 30728		
	Geologic Cross Section Location Map		





<p>1050 Crown Pointe Parkway Suite 350 Atlanta, GA 30338 (404) 315-9113</p>	DRN: JDD	DATE: October 2014	<p>FIGURE</p> <p>7C</p>
	<p>Color Spectrum 29 Probasco Street LaFayette, GA 30728</p>		
	<p>Cross Section B-B'</p>		



APPENDIX C

Tables

Table 1
Summary of Groundwater Analytical Results
Color Spectrum
LaFayette, Georgia

Sample Location	Sample Date	1,1,1-TCA (µg/L)	1,1-DCA (µg/L)	1,1-DCE (µg/L)	Acetone (µg/L)	Freon-113 (µg/L)	Freon-12 (µg/L)	IPB (µg/L)	PCE (µg/L)	Arsenic (µg/L)	Lead (µg/L)
	Type 1 RRS	200	4,000	7	4,000	1,000,000	1,000	5*	5	10	15
	Type 2 RRS	2,720	NC	103	NC	NC	NC	207	19	NC	NC
	Type 4 RRS	13,600	NC	520	NC	NC	NC	1,050	98	NC	NC***
Minimum Detected Value		5.5	5.0	5.5	95	10	110	6	5	ND	15.6
Maximum Detected Value		2,100	280	290	140	27,000	680	46	350	ND	15.6
MW-1	12/19/06	<5.0	<5.0	<5.0	--	60	<10	<5.0	<5.0	--	--
	06/28/07	<5.0	<5.0	<5.0	--	63	<10	<5.0	<5.0	--	--
	08/17/11	<5.0	<5.0	<5.0	<50	28	<10	<5.0	<5.0	--	--
MW-2	12/19/06	<5.0	<5.0	<5.0	--	54	<10	<5.0	<5.0	--	--
	06/28/07	<5.0	<5.0	<5.0	--	44	<10	<5.0	<5.0	--	--
	08/17/11	<5.0	<5.0	<5.0	<50	11	<10	<5.0	<5.0	--	--
Duplicate	03/12/13	<5.0	<5.0	<5.0	<50	<10	<10	<5.0	<5.0	--	--
	03/12/13	<5.0	<5.0	<5.0	<50	<10	<10	<5.0	<5.0	--	--
	06/19/13	<5.0	<5.0	<5.0	<50	<10	<10	<5.0	<5.0	--	--
Duplicate	08/30/13	<5.0	<5.0	<5.0	<50	37	<10	<5.0	<5.0	--	--
	08/30/13	<5.0	<5.0	<5.0	<50	36	<10	<5.0	<5.0	--	--
	12/03/13	<5.0	<5.0	<5.0	<50	<10	<10	<5.0	<5.0	--	--
MW-3	12/19/06	<5.0	8.5	5.5	--	390	<10	<5.0	8.7	--	--
	06/28/07	<5.0	7.8	<5.0	--	360	<10	<5.0	7.6	--	--
	08/17/11	<5.0	<5.0	<5.0	<50	230	<10	<5.0	5.2	--	--
MW-4	06/27/07	<5.0	<5.0	<5.0	--	10	<10	<5.0	<5.0	--	--
	08/17/11	<5.0	<5.0	<5.0	<50	<5.0	<10	<5.0	<5.0	--	--
MW-5	06/27/07	40	<5.0	<5.0	--	880	<10	<5.0	18	--	--
	08/17/11	25	<5.0	7.6	<50	940	<10	<5.0	19	--	--
	03/12/13	12	<5.0	<5.0	<50	520	<10	<5.0	6.9	--	--
Duplicate	06/19/13	12	<5.0	<5.0	<50	500	<10	<5.0	6.2	--	--
	08/29/13	9.2	<5.0	<5.0	<50	410	<10	<5.0	6.6	--	--
	12/03/13	6.8	<5.0	<5.0	<50	470	<10	<5.0	7.0	--	--
Duplicate	12/03/13	6.6	<5.0	<5.0	<50	480	<10	<5.0	7.2	--	--
MW-6	06/27/07	<5.0	<5.0	<5.0	--	<10	<10	46	<5.0	--	--
	08/17/11	<5.0	<5.0	<5.0	<50	<10	<10	<5.0	<5.0	--	--
	08/17/11	<5.0	<5.0	<5.0	<50	<10	<10	<5.0	<5.0	--	--
MW-7	06/27/07	14	<5.0	<5.0	--	180	<10	<5.0	<5.0	--	--
	08/16/11	31	<5.0	9.5	<50	1,100	<10	<5.0	8.6	--	--
MW-8	06/27/07	<5.0	5.9	22	--	3,900	<10	<5.0	<5.0	--	--
	08/16/11	5.5	30	76	<50	8,200	110	<5.0	32	--	--
MW-9	06/27/07	<5.0	<5.0	<5.0	--	<10	<10	<5.0	<5.0	--	--
	08/16/11	<5.0	<5.0	<5.0	<50	18	<10	<5.0	<5.0	--	--
MW-10	10/07/09	10	170	96	<50	6,100	<10	12	54	<4.4**	<10
	10/07/09	7.2	240	110	<50	6,200	<10	10	42	<4.4**	<10
	08/16/11	33	250	280	<50	15,000	680	8.4	130	--	--
Duplicate	11/15/11	28	260	160	<50	11,000	<10	7.6	120	--	--
	03/12/13	36	220	97	140	14,000	190	<5.0	120	--	--
	06/19/13	34	250	160	<50	17,000	<10	5.8	120	--	--
Duplicate	06/19/13	48	280	280	<50	12,000	<10	8.2	160	--	--
	08/29/13	40	250	180	95	16,000	400	9.7	140	--	--
	12/03/13	42	240	140	<50	15,000	<10	10	150	--	--
MW-11	10/07/09	7.6	29	94	<50	15,000	<10	7.7	120	<4.4**	15.6***
MW-11(F)	10/07/09	11	33	100	<50	21,000	<10	7.5	64	<4.4**	<10
Duplicate	08/16/11	<5.0	<5.0	<5.0	<50	27	<10	<5.0	<5.0	--	--
	11/15/11	<5.0	<5.0	<5.0	<50	<10	<10	<5.0	<5.0	--	--
	08/30/13	--	--	--	--	--	--	--	--	--	<10
Duplicate	08/30/13	--	--	--	--	--	--	--	--	--	<10

Table 1
Summary of Groundwater Analytical Results
Color Spectrum
LaFayette, Georgia

Sample Location	Sample Date	1,1,1-TCA (µg/L)	1,1-DCA (µg/L)	1,1-DCE (µg/L)	Acetone (µg/L)	Freon-113 (µg/L)	Freon-12 (µg/L)	IPB (µg/L)	PCE (µg/L)	Arsenic (µg/L)	Lead (µg/L)
	Type 1 RRS	200	4,000	7	4,000	1,000,000	1,000	5*	5	10	15
	Type 2 RRS	2,720	NC	103	NC	NC	NC	207	19	NC	NC
	Type 4 RRS	13,600	NC	520	NC	NC	NC	1,050	98	NC	NC***
MW-12	03/12/13	<5.0	<5.0	<5.0	<50	<10	<10	<5.0	<5.0	--	--
	06/19/13	<5.0	<5.0	<5.0	<50	11	<10	<5.0	<5.0	--	--
	08/30/13	<5.0	<5.0	<5.0	<50	<10	<10	<5.0	<5.0	--	--
	12/03/13	<5.0	<5.0	<5.0	<50	<10	<10	<5.0	<5.0	--	--
MW-13	03/12/13	<5.0	<5.0	<5.0	<50	160	<10	<5.0	<5.0	--	--
	06/19/13	9.3	<5.0	<5.0	<50	450	<10	<5.0	7.3	--	--
	08/30/13	6.8	<5.0	<5.0	<50	360	<10	<5.0	8.6	--	--
	12/03/13	<5.0	<5.0	<5.0	<50	330	<10	<5.0	7.0	--	--
MW-14	08/22/14	<5.0	<5.0	<5.0	<50	<10	<10	<5.0	<5.0	--	--
DW-1	06/27/07	<5.0	<5.0	<5.0	--	<10	<10	<5.0	<5.0	--	--
	08/16/11	<5.0	<5.0	<5.0	<50	<10	<10	<5.0	<5.0	--	--
TW-1	06/27/07	<5.0	<5.0	<5.0	--	<10	<10	<5.0	<5.0	--	--
	08/17/11	<5.0	<5.0	<5.0	<50	<10	<10	<5.0	<5.0	--	--
	03/12/13	<5.0	<5.0	<5.0	<50	<10	<10	<5.0	<5.0	--	--
	06/19/13	<5.0	<5.0	<5.0	<50	<10	<10	<5.0	<5.0	--	--
	08/29/13	<5.0	<5.0	<5.0	<50	<10	<10	<5.0	<5.0	--	--
	12/03/13	<5.0	<5.0	<5.0	<50	<10	<10	<5.0	<5.0	--	--
TW-2	06/27/07	<5.0	<5.0	<5.0	--	<10	<10	<5.0	<5.0	--	--
	08/16/11	<5.0	<5.0	<5.0	<50	<10	<10	<5.0	<5.0	--	--
TW-3	06/27/07	<5.0	<5.0	<5.0	--	<10	<10	<5.0	<5.0	--	--
SB-1	10/11/05	23	5.6	<5.0	<50	<10	<10	<5.0	6.4	--	--
SB-2	10/11/05	<5.0	<5.0	<5.0	<50	<10	<10	<5.0	<5.0	--	--
SB-3	10/11/05	<5.0	<5.0	<5.0	<50	<10	<10	<5.0	<5.0	--	--
SB-4	10/11/05	<5.0	<5.0	<5.0	<50	<10	<10	<5.0	<5.0	--	--
SB-5	10/11/05	<5.0	<5.0	<5.0	<50	<10	<10	<5.0	<5.0	--	--
SB-6	10/24/05	14	<5.0	<5.0	<50	190	<10	<5.0	<5.0	--	--
SB-7	10/24/05	<5.0	<5.0	<5.0	<50	11	<10	<5.0	<5.0	--	--
SB-8	10/24/05	<5.0	<5.0	<5.0	<50	40	<10	<5.0	<5.0	--	--
SB-9	10/24/05	14	<5.0	<5.0	<50	97	<10	<5.0	<5.0	--	--
SB-10	10/24/05	13	<5.0	<5.0	<50	370	<10	<5.0	<5.0	--	--
SB-11	10/24/05	<5.0	5.0	<5.0	<50	54	<10	<5.0	<5.0	--	--
SB-12	07/27/06	<5.0	<5.0	<5.0	<50	<10	<10	<5.0	<5.0	--	--
SB-13	07/27/06	<5.0	<5.0	9.0	<50	580	<10	<5.0	7.6	--	--
SB-14	07/27/06	<5.0	<5.0	<5.0	<50	<10	<10	<5.0	<5.0	--	--
SB-15	07/27/06	<5.0	<5.0	<5.0	<50	80	<10	8.5	<5.0	--	--
SB-16	07/27/06	23	11	<5.0	<50	1,800	<10	<5.0	20	--	--
SB-17	07/27/06	<5.0	<5.0	7.1	<50	510	<10	<5.0	<5.0	--	--
SB-18	07/27/06	<5.0	<5.0	<5.0	<50	17	<10	<5.0	<5.0	--	--
SB-19	07/27/06	NS	NS	NS	NS	NS	NS	NS	NS	--	--
SB-20	12/20/06	<5.0	<5.0	<5.0	--	160	<10	<5.0	<5.0	--	--
SB-21	12/20/06	<5.0	<5.0	<5.0	--	49	<10	<5.0	<5.0	--	--
SB-22	12/20/06	30	32	120	--	27,000	<10	<5.0	150	--	--
SB-23	12/20/06	2,100	230	290	--	27,000	<10	<5.0	350	--	--
SB-26	12/20/06	<5.0	<5.0	<5.0	--	36	<10	<5.0	<5.0	--	--
Duplicate	12/20/06	<5.0	<5.0	<5.0	--	22	<10	<5.0	<5.0	--	--
SB-27	12/20/06	34	<5.0	<5.0	--	1,100	<10	<5.0	9.8	--	--
SB-28	12/20/06	<5.0	5.4	6.2	--	270	<10	8.3	<5.0	--	--
POND	10/11/05	<5.0	<5.0	<5.0	<50	<10	<10	<5.0	<5.0	--	--
Field Blank	12/20/06	<5.0	<5.0	<5.0	--	<10	<10	<5.0	<5.0	--	--

Table 1
Summary of Groundwater Analytical Results
Color Spectrum
LaFayette, Georgia

Sample Location	Sample Date	1,1,1-TCA (µg/L)	1,1-DCA (µg/L)	1,1-DCE (µg/L)	Acetone (µg/L)	Freon-113 (µg/L)	Freon-12 (µg/L)	IPB (µg/L)	PCE (µg/L)	Arsenic (µg/L)	Lead (µg/L)
	Type 1 RRS	200	4,000	7	4,000	1,000,000	1,000	5*	5	10	15
	Type 2 RRS	2,720	NC	103	NC	NC	NC	207	19	NC	NC
	Type 4 RRS	13,600	NC	520	NC	NC	NC	1,050	98	NC	NC***
Trip Blank	10/24/05	<5.0	<5.0	<5.0	<50	<10	<10	<5.0	<5.0	--	--
	12/20/06	<5.0	<5.0	<5.0	--	<10	<10	<5.0	<5.0	--	--
	06/29/07	<5.0	<5.0	<5.0	--	<10	<10	<5.0	<5.0	--	--
	10/07/09	<5.0	<5.0	<5.0	<50	<10	<10	<5.0	<5.0	--	--
	08/18/11	<5.0	<5.0	<5.0	<50	<10	<10	<5.0	<5.0	--	--
	03/11/13	<5.0	<5.0	<5.0	<50	<10	<10	<5.0	<5.0	--	--
	08/29/13	<5.0	<5.0	<5.0	<50	<10	<10	<5.0	<5.0	--	--
	12/03/13	<5.0	<5.0	<5.0	<50	<10	<10	<5.0	<5.0	--	--
Rinsate	10/07/09	<5.0	<5.0	<5.0	<50	<10	<10	<5.0	<5.0	--	--
	08/17/11	<5.0	<5.0	<5.0	<50	<11	<10	<5.0	<5.0	--	--

Notes:

ug/L = micrograms per liter

<5.0 = constituent was not detected above the detection limit.

NS = not sampled

* A value does not exist on Table 1 of Appendix III for this compound.

The Reporting Limit was used for the Type 1 RRS.

** This result is reported down to the Method Detection Limit because the Reporting Limit was greater than the Type 1 RRS.

*** The well could not be fully developed due to slow recharge.

The result represents a highly turbid sample and is not considered valid. Lead was not detected in a filtered sample collected from the same well.

NC = Not Calculated

1,1,1-TCA = 1,1,1-Trichloroethane

1,1-DCA = 1,1-Dichloroethane

1,1-DCE = 1,1-Dichloroethene

PCE = Tetrachloroethene

IPB = Isopropylbenzene

-- = Constituent Not Analyzed

NR = Not Regulated

(F) = Filtered



 Above Residential RRS (Type 1/2 RRS)
 Above Non-Residential RRS (Type 4 RRS)

Table 2
Summary of Soil Analytical Results
Color Spectrum
LaFayette, Georgia

Sample Location	Depth (feet)	Sample Date	1,1,1-TCA (mg/Kg)	1,1-DCA (mg/Kg)	1,1-DCE (mg/Kg)	Acetone (mg/Kg)	Freon-113 (mg/Kg)	PCE (mg/Kg)	Arsenic (mg/Kg)	Lead (mg/Kg)
SB-24	7	12/19/06	<0.0035	<0.0035	<0.0035	NS	0.11	<0.0035	--	--
SB-25	7	12/19/06	<0.0024	0.0029	0.0042	NS	0.57	<0.0024	--	--
SB-26	7	12/19/06	<0.0033	<0.0033	<0.0033	NS	0.25	<0.0033	--	--
SB-29	1	06/22/07	<0.0046	<0.0046	<0.0046	<0.092	0.038	<0.0046	--	--
SB-29	4	06/22/07	<0.0038	<0.0038	<0.0038	<0.076	0.094	<0.0038	--	--
SB-30	1	06/22/07	<0.0030	<0.0030	<0.0030	<0.061	0.077	<0.0030	--	--
SB-30	6	06/22/07	<0.0035	<0.0035	<0.0035	<0.070	0.22	<0.0035	--	--
SB-31	1	06/22/07	<0.0044	<0.0044	<0.0044	<0.087	0.078	<0.0044	--	--
SB-31	7	06/22/07	<0.0036	<0.0036	<0.0036	0.19	0.034	<0.0036	--	--
SB-32	1	06/22/07	<0.0035	<0.0035	<0.0035	<0.069	0.98	<0.0035	--	--
SB-32	4	06/22/07	<0.0031	<0.0031	<0.0031	0.32	0.57	<0.0031	--	--
SB-33	1	06/21/07	<0.0028	<0.0028	<0.0028	0.16	0.32	0.0033	--	--
SB-33	4	06/21/07	<0.0027	<0.0027	<0.0027	0.19	0.34	0.0028	--	--
SB-34	1	06/21/07	<0.0033	<0.0033	<0.0033	<0.066	0.68	<0.0033	--	--
SB-34	7	06/21/07	<0.0027	0.0073	0.039	<0.054	4.2	<0.0027	--	--
SB-35	1	06/21/07	<0.0034	<0.0034	<0.0034	0.18	0.028	<0.0034	--	--
SB-35	4	06/21/07	<0.0041	<0.0041	<0.0041	<0.082	0.61	<0.0041	--	--
SB-36	1	06/21/07	<0.0046	<0.0046	<0.0046	<0.092	<0.0092	<0.0046	--	--
SB-36	4	06/21/07	<0.0038	<0.0038	0.020	<0.077	2.3	0.0091	--	--
SB-37	1	06/26/07	<0.0039	<0.0039	<0.0039	<0.077	0.99	0.024	--	--
SB-37	3	06/26/07	0.012	0.0068	0.08	<0.059	6.3	0.30	--	--
MW-7	1	06/26/07	<0.0032	<0.0032	<0.0032	<0.064	0.32	<0.0032	--	--
MW-7	4	06/26/07	<0.0031	<0.0031	0.011	<0.061	0.79	<0.0031	--	--
SO-1	2	10/06/09	<0.0031	<0.0031	<0.0031	<0.063	0.25	0.0041	14.4	16.5
SO-2	2	10/06/09	<0.0030	<0.0030	<0.0030	<0.061	0.39	0.014	17.6	18
SO-3	2	10/06/09	<0.0032	<0.0032	<0.0032	<0.064	0.52	<0.0032	22.4	25.5
SO-4	5	10/06/09	<0.0042	0.0079	<0.0042	<0.084	1.2	0.015	11.9	12.6
SO-5	4	10/06/09	<0.0044	<0.0044	<0.0044	<0.087	2.1	<0.0044	13.4	14.7
Duplicate	4	10/06/09	<0.0037	<0.0037	<0.0037	<0.074	1.6	<0.0037	12.7	10.8
SO-6	4	10/06/09	<0.0066	<0.0066	<0.0066	<0.13	0.29	0.007	10.3	11.4

Notes:

mg/Kg = milligrams per kilogram

<0.0035 = constituent was not detected above the detection limit.

NS = Not Sampled

1,1,1-TCA = 1,1,1-Trichloroethane

1,1-DCA = 1,1-Dichloroethane

1,1-DCE = 1,1-Dichloroethene

PCE = Tetrachloroethene

NC = Not Calculated

-- = Constituent Not Analyzed

Table 3
Groundwater Elevations
Color Spectrum
LaFayette, Georgia

Well Location	Date	Ground Surface Elevation (ft above NGVD)	TOC Elevation (ft above NGVD)	Screened Interval (ft below TOC)	Depth to Groundwater (ft below TOC)	Depth to Product (ft below TOC)	Groundwater Elevation (ft above NGVD)
MW-1	6/28/2007	796.96	796.64	2-12	5.06	ND	791.58
	8/16/2011				5.58	ND	791.06
	3/12/2013		796.34		3.56	ND	792.78
	8/29/2013		4.51		ND	791.83	
	12/3/2013		3.65		ND	792.69	
MW-2*	6/28/2007	796.43	796.06	2-12	5.48	NM	790.58
	8/16/2011		5.20		5.15	791.27	
	3/12/2013		3.70		3.65	792.77	
	6/19/2013		4.10		3.00	793.27	
	8/29/2013		5.36		4.36	791.92	
12/3/2013	4.65	4.64	791.79				
MW-3	6/28/2007	797.46	797.14	2-15	5.45	ND	791.69
	8/16/2011		5.59		ND	791.55	
	3/12/2013		NM		NM	NM	
	8/29/2013		NM		NM	NM	
	12/3/2013		NM		NM	NM	
MW-4	6/28/2007	795.58	795.43	6-16	4.48	ND	790.95
	8/16/2011		4.82		ND	790.61	
	3/12/2013		4.26		ND	791.17	
	8/29/2013		4.39		ND	791.04	
	12/3/2013		4.33		ND	791.10	
MW-5	6/28/2007	797.46	797.19	3-13	5.10	ND	792.09
	8/16/2011		4.65		ND	792.54	
	3/12/2013		3.82		ND	793.37	
	6/19/2013		3.84		ND	793.35	
	8/29/2013		4.01		ND	793.18	
12/3/2013	3.99	ND	793.20				
MW-6	6/28/2007	796.92	796.62	3-13	4.45	ND	792.17
	8/16/2011		4.83		ND	791.79	
	3/12/2013		3.90		ND	792.72	
	8/29/2013		3.81		ND	792.81	
	12/3/2013		4.33		ND	792.29	
MW-7	6/28/2007	797.89	797.52	3.5-13.5	3.69	ND	793.83
	8/16/2011		3.63		ND	793.89	
	3/12/2013		3.28		ND	794.24	
	8/29/2013		3.30		ND	794.22	
	12/3/2013		3.40		ND	794.12	
MW-8	6/28/2007	801.96	801.74	4-14	12.17	ND	789.57
	8/16/2011		9.27		ND	792.47	
	3/12/2013		8.47		ND	793.27	
	8/29/2013		8.45		ND	793.29	
	12/3/2013		8.91		ND	792.83	

Table 3
Groundwater Elevations
Color Spectrum
LaFayette, Georgia

Well Location	Date	Ground Surface Elevation (ft above NGVD)	TOC Elevation (ft above NGVD)	Screened Interval (ft below TOC)	Depth to Groundwater (ft below TOC)	Depth to Product (ft below TOC)	Groundwater Elevation (ft above NGVD)
MW-9	6/28/2007	801.97	801.53	4-14	7.45	ND	794.08
	8/16/2011				7.41	ND	794.12
	3/12/2013				7.02	ND	794.51
	8/29/2013				6.98	ND	794.55
	12/3/2013				7.15	ND	794.38
MW-10	10/6/2009	801.96	801.62	10-12.5	9.24	ND	792.38
	8/16/2011				8.78	ND	792.84
	3/12/2013				8.06	ND	793.56
	6/19/2013				8.04	ND	793.58
	8/29/2013				7.81	ND	793.81
MW-11	10/6/2009	801.96	801.75	17.5-20	8.31	ND	793.31
	8/16/2011				14.21	ND	787.54
	3/12/2013				9.35	ND	792.40
	6/19/2013				8.65	ND	793.10
	8/29/2013				8.65	ND	793.10
MW-12	10/6/2009	801.96	801.75	17.5-20	7.96	ND	793.79
	8/16/2011				9.00	ND	792.75
	3/12/2013				3.78	ND	791.51
	6/19/2013				3.65	ND	791.64
	8/29/2013				3.76	ND	791.53
MW-13	10/6/2009	801.96	801.75	17.5-20	3.78	ND	791.51
	8/16/2011				3.57	ND	792.67
	3/12/2013				3.63	ND	792.61
	6/19/2013				4.41	ND	791.83
	8/29/2013				4.12	ND	792.12
MW-14	8/22/2014	NM	796.34		5.46	ND	790.88
TW-1	6/28/2007	795.01	794.73	6-16	3.81	ND	790.92
	8/16/2011				4.10	ND	790.63
	3/12/2013				3.05	ND	791.68
	6/19/2013				3.49	ND	791.24
	8/29/2013				3.65	ND	791.08
TW-2	10/6/2009	801.96	801.75	17.5-20	3.61	ND	791.12
	8/16/2011				7.36	ND	794.38
	3/12/2013				6.89	ND	794.85
	8/29/2013				NM	NM	NM
	12/3/2013				NM	NM	NM
DW-1	6/28/2007	798.10	797.72	35.6-45.6	5.92	ND	795.82
	8/16/2011				4.70	ND	793.02
	3/12/2013				4.45	ND	793.27
	8/29/2013				3.45	ND	794.27
	12/3/2013				3.77	ND	793.95
					4.10	ND	793.62

Notes

ft = feet

NGVD = National Geodetic Vertical Datum

*= corrected for free product, measurements are approximate

TOC = top of casing

NM = not measured

A specific gravity correction factor of 0.85 was used to adjust potentiometric surface elevations for MW-2.

Table 4
Summary of Vapor Intrusion Modeling Results
Color Spectrum
LaFayette, Georgia

Property Use Scenario	Compound	Matrix	Estimated Area Volume ft ³	Modeled Air Exchange (AE) Volume (1/h)	Sample Location	Concentration µg/L (GW) mg/kg (soil)	Cancer Risk*	Hazard Quotient**
Non-Residential	Freon-113	GW	1,628,000	0.25	SB-23	27,000	--	3.0E-02
		Soil	1,628,000	0.25	SB-34	4.2	--	7.8E-04
	PCE	GW	1,628,000	0.25	SB-23	350	5.5E-08	1.5E-02
		Soil	1,628,000	0.25	SB-33	0.024	3.9E-09	1.1E-03
Residential	Freon-113	GW	8,611	0.25	SB-23	27,000	--	1.4E-01
		Soil	8,611	0.25	SB-34	6.3	--	4.0E-03
	PCE	GW	8,611	0.25	SB-23	350	3.2E-07	7.3E-02
		Soil	8,611	0.25	SB-33	0.3	3.2E-07	7.1E-02

Notes:

µg/L = micrograms per liter

PCE = Tetrachloroethene

1/hr = 1 building volume per hour

* = Estimated Risk is calculated based on measured groundwater and soil PCE concentrations

**= The hazard quotient is calculated based on measured groundwater and soil concentrations of PCE and/or Freon-113.

APPENDIX D

Laboratory Analytical Reports

Analytical Environmental Services, Inc.

Date: 21-Oct-14

CLIENT: Environmental Planning Specialists, Inc.
Lab Order: 0910778
Project: Color Spectrum
Lab ID: 0910778-011

Client Sample ID: 09280-MW-10
Collection Date: 10/7/2009 11:40:00 AM
Matrix: GROUNDWATER

Analyses	Result	Qual	MDL	Rpt. Limit	Units	BatchID	DF	Date Analyzed
METALS, TOTAL SW6010C				(SW3010A)				Analyst: JY
Arsenic	BRL		0.0044	0.0500	mg/L	119718	1	10/12/2009 2:32:15 PM
Lead	BRL		0.0022	0.0100	mg/L	119718	1	10/12/2009 2:32:15 PM
TCL VOLATILE ORGANICS SW8260B				(SW5030B)				Analyst: JCT
1,1,1-Trichloroethane	10		0.14	5.0	ug/L	119752	1	10/11/2009 3:02:00 AM
1,1,2,2-Tetrachloroethane	BRL		0.16	5.0	ug/L	119752	1	10/11/2009 3:02:00 AM
1,1,2-Trichloroethane	BRL		0.15	5.0	ug/L	119752	1	10/11/2009 3:02:00 AM
1,1-Dichloroethane	170		0.13	5.0	ug/L	119752	1	10/11/2009 3:02:00 AM
1,1-Dichloroethene	96		0.27	5.0	ug/L	119752	1	10/11/2009 3:02:00 AM
1,2,4-Trichlorobenzene	BRL		0.21	5.0	ug/L	119752	1	10/11/2009 3:02:00 AM
1,2-Dibromo-3-chloropropane	BRL		0.28	5.0	ug/L	119752	1	10/11/2009 3:02:00 AM
1,2-Dibromoethane	BRL		0.24	5.0	ug/L	119752	1	10/11/2009 3:02:00 AM
1,2-Dichlorobenzene	BRL		0.16	5.0	ug/L	119752	1	10/11/2009 3:02:00 AM
1,2-Dichloroethane	BRL		0.12	5.0	ug/L	119752	1	10/11/2009 3:02:00 AM
1,2-Dichloropropane	BRL		0.17	5.0	ug/L	119752	1	10/11/2009 3:02:00 AM
1,3-Dichlorobenzene	BRL		0.13	5.0	ug/L	119752	1	10/11/2009 3:02:00 AM
1,4-Dichlorobenzene	BRL		0.11	5.0	ug/L	119752	1	10/11/2009 3:02:00 AM
2-Butanone	BRL		5.4	50	ug/L	119752	1	10/11/2009 3:02:00 AM
2-Hexanone	BRL		0.21	10	ug/L	119752	1	10/11/2009 3:02:00 AM
4-Methyl-2-pentanone	BRL		0.41	10	ug/L	119752	1	10/11/2009 3:02:00 AM
Acetone	BRL		5.5	50	ug/L	119752	1	10/11/2009 3:02:00 AM
Benzene	0.91	J	0.13	5.0	ug/L	119752	1	10/11/2009 3:02:00 AM
Bromodichloromethane	BRL		0.13	5.0	ug/L	119752	1	10/11/2009 3:02:00 AM
Bromoform	BRL		0.30	5.0	ug/L	119752	1	10/11/2009 3:02:00 AM
Bromomethane	BRL		1.9	5.0	ug/L	119752	1	10/11/2009 3:02:00 AM
Carbon disulfide	BRL		0.19	5.0	ug/L	119752	1	10/11/2009 3:02:00 AM
Carbon tetrachloride	BRL		0.18	5.0	ug/L	119752	1	10/11/2009 3:02:00 AM
Chlorobenzene	BRL		0.088	5.0	ug/L	119752	1	10/11/2009 3:02:00 AM
Chloroethane	BRL		0.20	10	ug/L	119752	1	10/11/2009 3:02:00 AM
Chloroform	1.3	J	0.15	5.0	ug/L	119752	1	10/11/2009 3:02:00 AM
Chloromethane	BRL		0.15	10	ug/L	119752	1	10/11/2009 3:02:00 AM
cis-1,2-Dichloroethene	BRL		0.070	5.0	ug/L	119752	1	10/11/2009 3:02:00 AM
cis-1,3-Dichloropropene	BRL		0.17	5.0	ug/L	119752	1	10/11/2009 3:02:00 AM
Cyclohexane	BRL		0.80	5.0	ug/L	119752	1	10/11/2009 3:02:00 AM
Dibromochloromethane	BRL		0.12	5.0	ug/L	119752	1	10/11/2009 3:02:00 AM
Dichlorodifluoromethane	BRL		0.21	10	ug/L	119752	1	10/11/2009 3:02:00 AM
Ethylbenzene	BRL		0.085	5.0	ug/L	119752	1	10/11/2009 3:02:00 AM
Freon-113	6100		16	1000	ug/L	119752	100	10/12/2009 7:13:00 PM
Isopropylbenzene	12		0.069	5.0	ug/L	119752	1	10/11/2009 3:02:00 AM
m,p-Xylene	BRL		0.092	10	ug/L	119752	1	10/11/2009 3:02:00 AM
Methyl acetate	BRL		0.31	5.0	ug/L	119752	1	10/11/2009 3:02:00 AM

Qualifiers:	*	Value exceeds Maximum Contaminant Level	<	Less than Result value
	>	Greater than Result value	B	Analyte detected in the associated Method Blank
	E	Estimated value above quantitation range	H	Holding times for preparation or analysis exceeded
	J	Estimated value detected below Reporting Limit	N	Analyte not NELAC certified

Analytical Environmental Services, Inc.

Date: 21-Oct-14

CLIENT: Environmental Planning Specialists, Inc.
Lab Order: 0910778
Project: Color Spectrum
Lab ID: 0910778-011

Client Sample ID: 09280-MW-10
Collection Date: 10/7/2009 11:40:00 AM

Matrix: GROUNDWATER

Analyses	Result	Qual	MDL	Rpt. Limit	Units	BatchID	DF	Date Analyzed
TCL VOLATILE ORGANICS SW8260B				(SW5030B)				Analyst: JCT
Methyl tert-butyl ether	2.7	J	0.073	5.0	ug/L	119752	1	10/11/2009 3:02:00 AM
Methylcyclohexane	BRL		0.13	5.0	ug/L	119752	1	10/11/2009 3:02:00 AM
Methylene chloride	BRL		0.96	5.0	ug/L	119752	1	10/11/2009 3:02:00 AM
o-Xylene	BRL		0.053	5.0	ug/L	119752	1	10/11/2009 3:02:00 AM
Styrene	BRL		0.12	5.0	ug/L	119752	1	10/11/2009 3:02:00 AM
Tetrachloroethene	54		0.17	5.0	ug/L	119752	1	10/11/2009 3:02:00 AM
Toluene	BRL		0.15	5.0	ug/L	119752	1	10/11/2009 3:02:00 AM
trans-1,2-Dichloroethene	BRL		0.20	5.0	ug/L	119752	1	10/11/2009 3:02:00 AM
trans-1,3-Dichloropropene	BRL		0.098	5.0	ug/L	119752	1	10/11/2009 3:02:00 AM
Trichloroethene	BRL		0.12	5.0	ug/L	119752	1	10/11/2009 3:02:00 AM
Trichlorofluoromethane	BRL		0.17	5.0	ug/L	119752	1	10/11/2009 3:02:00 AM
Vinyl chloride	BRL		0.19	2.0	ug/L	119752	1	10/11/2009 3:02:00 AM
Surr: 4-Bromofluorobenzene	84.3		0	61.3-128	%REC	119752	100	10/12/2009 7:13:00 PM
Surr: 4-Bromofluorobenzene	92.9		0	61.3-128	%REC	119752	1	10/11/2009 3:02:00 AM
Surr: Dibromofluoromethane	105		0	67.8-130	%REC	119752	1	10/11/2009 3:02:00 AM
Surr: Dibromofluoromethane	95.5		0	67.8-130	%REC	119752	100	10/12/2009 7:13:00 PM
Surr: Toluene-d8	89.2		0	70.6-121	%REC	119752	1	10/11/2009 3:02:00 AM
Surr: Toluene-d8	83.9		0	70.6-121	%REC	119752	100	10/12/2009 7:13:00 PM

Qualifiers:	*	Value exceeds Maximum Contaminant Level	<	Less than Result value
	>	Greater than Result value	B	Analyte detected in the associated Method Blank
	E	Estimated value above quantitation range	H	Holding times for preparation or analysis exceeded
	J	Estimated value detected below Reporting Limit	N	Analyte not NELAC certified

Analytical Environmental Services, Inc.

Date: 21-Oct-14

CLIENT: Environmental Planning Specialists, Inc.
Lab Order: 0910778
Project: Color Spectrum
Lab ID: 0910778-012

Client Sample ID: 09280-MW-11
Collection Date: 10/7/2009 2:35:00 PM

Matrix: GROUNDWATER

Analyses	Result	Qual	MDL	Rpt. Limit	Units	BatchID	DF	Date Analyzed
METALS, TOTAL SW6010C				(SW3010A)				Analyst: JY
Arsenic	BRL		0.0044	0.0500	mg/L	119718	1	10/12/2009 2:35:58 PM
Lead	0.0156		0.0022	0.0100	mg/L	119718	1	10/12/2009 2:35:58 PM
TCL VOLATILE ORGANICS SW8260B				(SW5030B)				Analyst: JCT
1,1,1-Trichloroethane	7.6		0.14	5.0	ug/L	119752	1	10/11/2009 3:30:00 AM
1,1,2,2-Tetrachloroethane	BRL		0.16	5.0	ug/L	119752	1	10/11/2009 3:30:00 AM
1,1,2-Trichloroethane	BRL		0.15	5.0	ug/L	119752	1	10/11/2009 3:30:00 AM
1,1-Dichloroethane	29		0.13	5.0	ug/L	119752	1	10/11/2009 3:30:00 AM
1,1-Dichloroethene	94		0.27	5.0	ug/L	119752	1	10/11/2009 3:30:00 AM
1,2,4-Trichlorobenzene	BRL		0.21	5.0	ug/L	119752	1	10/11/2009 3:30:00 AM
1,2-Dibromo-3-chloropropane	BRL		0.28	5.0	ug/L	119752	1	10/11/2009 3:30:00 AM
1,2-Dibromoethane	BRL		0.24	5.0	ug/L	119752	1	10/11/2009 3:30:00 AM
1,2-Dichlorobenzene	BRL		0.16	5.0	ug/L	119752	1	10/11/2009 3:30:00 AM
1,2-Dichloroethane	BRL		0.12	5.0	ug/L	119752	1	10/11/2009 3:30:00 AM
1,2-Dichloropropane	BRL		0.17	5.0	ug/L	119752	1	10/11/2009 3:30:00 AM
1,3-Dichlorobenzene	BRL		0.13	5.0	ug/L	119752	1	10/11/2009 3:30:00 AM
1,4-Dichlorobenzene	BRL		0.11	5.0	ug/L	119752	1	10/11/2009 3:30:00 AM
2-Butanone	BRL		5.4	50	ug/L	119752	1	10/11/2009 3:30:00 AM
2-Hexanone	BRL		0.21	10	ug/L	119752	1	10/11/2009 3:30:00 AM
4-Methyl-2-pentanone	BRL		0.41	10	ug/L	119752	1	10/11/2009 3:30:00 AM
Acetone	BRL		5.5	50	ug/L	119752	1	10/11/2009 3:30:00 AM
Benzene	BRL		0.13	5.0	ug/L	119752	1	10/11/2009 3:30:00 AM
Bromodichloromethane	BRL		0.13	5.0	ug/L	119752	1	10/11/2009 3:30:00 AM
Bromoform	BRL		0.30	5.0	ug/L	119752	1	10/11/2009 3:30:00 AM
Bromomethane	BRL		1.9	5.0	ug/L	119752	1	10/11/2009 3:30:00 AM
Carbon disulfide	BRL		0.19	5.0	ug/L	119752	1	10/11/2009 3:30:00 AM
Carbon tetrachloride	BRL		0.18	5.0	ug/L	119752	1	10/11/2009 3:30:00 AM
Chlorobenzene	BRL		0.088	5.0	ug/L	119752	1	10/11/2009 3:30:00 AM
Chloroethane	BRL		0.20	10	ug/L	119752	1	10/11/2009 3:30:00 AM
Chloroform	BRL		0.15	5.0	ug/L	119752	1	10/11/2009 3:30:00 AM
Chloromethane	BRL		0.15	10	ug/L	119752	1	10/11/2009 3:30:00 AM
cis-1,2-Dichloroethene	BRL		0.070	5.0	ug/L	119752	1	10/11/2009 3:30:00 AM
cis-1,3-Dichloropropene	BRL		0.17	5.0	ug/L	119752	1	10/11/2009 3:30:00 AM
Cyclohexane	BRL		0.80	5.0	ug/L	119752	1	10/11/2009 3:30:00 AM
Dibromochloromethane	BRL		0.12	5.0	ug/L	119752	1	10/11/2009 3:30:00 AM
Dichlorodifluoromethane	BRL		0.21	10	ug/L	119752	1	10/11/2009 3:30:00 AM
Ethylbenzene	BRL		0.085	5.0	ug/L	119752	1	10/11/2009 3:30:00 AM
Freon-113	15000		16	1000	ug/L	119752	100	10/12/2009 7:41:00 PM
Isopropylbenzene	7.7		0.069	5.0	ug/L	119752	1	10/11/2009 3:30:00 AM
m,p-Xylene	BRL		0.092	10	ug/L	119752	1	10/11/2009 3:30:00 AM
Methyl acetate	BRL		0.31	5.0	ug/L	119752	1	10/11/2009 3:30:00 AM

Qualifiers:	*	Value exceeds Maximum Contaminant Level	<	Less than Result value
	>	Greater than Result value	B	Analyte detected in the associated Method Blank
	E	Estimated value above quantitation range	H	Holding times for preparation or analysis exceeded
	J	Estimated value detected below Reporting Limit	N	Analyte not NELAC certified

Analytical Environmental Services, Inc.

Date: 21-Oct-14

CLIENT: Environmental Planning Specialists, Inc.
Lab Order: 0910778
Project: Color Spectrum
Lab ID: 0910778-012

Client Sample ID: 09280-MW-11
Collection Date: 10/7/2009 2:35:00 PM

Matrix: GROUNDWATER

Analyses	Result	Qual	MDL	Rpt. Limit	Units	BatchID	DF	Date Analyzed
TCL VOLATILE ORGANICS SW8260B				(SW5030B)				Analyst: JCT
Methyl tert-butyl ether	1.4	J	0.073	5.0	ug/L	119752	1	10/11/2009 3:30:00 AM
Methylcyclohexane	BRL		0.13	5.0	ug/L	119752	1	10/11/2009 3:30:00 AM
Methylene chloride	BRL		0.96	5.0	ug/L	119752	1	10/11/2009 3:30:00 AM
o-Xylene	BRL		0.053	5.0	ug/L	119752	1	10/11/2009 3:30:00 AM
Styrene	BRL		0.12	5.0	ug/L	119752	1	10/11/2009 3:30:00 AM
Tetrachloroethene	120		0.17	5.0	ug/L	119752	1	10/11/2009 3:30:00 AM
Toluene	BRL		0.15	5.0	ug/L	119752	1	10/11/2009 3:30:00 AM
trans-1,2-Dichloroethene	BRL		0.20	5.0	ug/L	119752	1	10/11/2009 3:30:00 AM
trans-1,3-Dichloropropene	BRL		0.098	5.0	ug/L	119752	1	10/11/2009 3:30:00 AM
Trichloroethene	BRL		0.12	5.0	ug/L	119752	1	10/11/2009 3:30:00 AM
Trichlorofluoromethane	BRL		0.17	5.0	ug/L	119752	1	10/11/2009 3:30:00 AM
Vinyl chloride	BRL		0.19	2.0	ug/L	119752	1	10/11/2009 3:30:00 AM
Surr: 4-Bromofluorobenzene	83.7		0	61.3-128	%REC	119752	100	10/12/2009 7:41:00 PM
Surr: 4-Bromofluorobenzene	85.6		0	61.3-128	%REC	119752	1	10/11/2009 3:30:00 AM
Surr: Dibromofluoromethane	106		0	67.8-130	%REC	119752	1	10/11/2009 3:30:00 AM
Surr: Dibromofluoromethane	96.2		0	67.8-130	%REC	119752	100	10/12/2009 7:41:00 PM
Surr: Toluene-d8	87.5		0	70.6-121	%REC	119752	1	10/11/2009 3:30:00 AM
Surr: Toluene-d8	86.3		0	70.6-121	%REC	119752	100	10/12/2009 7:41:00 PM

Qualifiers:	*	Value exceeds Maximum Contaminant Level	<	Less than Result value
	>	Greater than Result value	B	Analyte detected in the associated Method Blank
	E	Estimated value above quantitation range	H	Holding times for preparation or analysis exceeded
	J	Estimated value detected below Reporting Limit	N	Analyte not NELAC certified

Analytical Environmental Services, Inc.

Date: 21-Oct-14

CLIENT: Environmental Planning Specialists, Inc.
Lab Order: 0910778
Project: Color Spectrum
Lab ID: 0910778-013

Client Sample ID: 09280-MW-11 F
Collection Date: 10/7/2009 2:30:00 PM

Matrix: GROUNDWATER

Analyses	Result	Qual	MDL	Rpt. Limit	Units	BatchID	DF	Date Analyzed
METALS, TOTAL SW6010C				(SW3010A)				Analyst: JY
Arsenic	BRL		0.0044	0.0500	mg/L	119718	1	10/12/2009 2:39:34 PM
Lead	0.0039	J	0.0022	0.0100	mg/L	119718	1	10/12/2009 2:39:34 PM
TCL VOLATILE ORGANICS SW8260B				(SW5030B)				Analyst: JCT
1,1,1-Trichloroethane	11		0.14	5.0	ug/L	119752	1	10/11/2009 4:27:00 AM
1,1,2,2-Tetrachloroethane	BRL		0.16	5.0	ug/L	119752	1	10/11/2009 4:27:00 AM
1,1,2-Trichloroethane	BRL		0.15	5.0	ug/L	119752	1	10/11/2009 4:27:00 AM
1,1-Dichloroethane	33		0.13	5.0	ug/L	119752	1	10/11/2009 4:27:00 AM
1,1-Dichloroethene	100		0.27	5.0	ug/L	119752	1	10/11/2009 4:27:00 AM
1,2,4-Trichlorobenzene	BRL		0.21	5.0	ug/L	119752	1	10/11/2009 4:27:00 AM
1,2-Dibromo-3-chloropropane	BRL		0.28	5.0	ug/L	119752	1	10/11/2009 4:27:00 AM
1,2-Dibromoethane	BRL		0.24	5.0	ug/L	119752	1	10/11/2009 4:27:00 AM
1,2-Dichlorobenzene	BRL		0.16	5.0	ug/L	119752	1	10/11/2009 4:27:00 AM
1,2-Dichloroethane	BRL		0.12	5.0	ug/L	119752	1	10/11/2009 4:27:00 AM
1,2-Dichloropropane	BRL		0.17	5.0	ug/L	119752	1	10/11/2009 4:27:00 AM
1,3-Dichlorobenzene	BRL		0.13	5.0	ug/L	119752	1	10/11/2009 4:27:00 AM
1,4-Dichlorobenzene	BRL		0.11	5.0	ug/L	119752	1	10/11/2009 4:27:00 AM
2-Butanone	BRL		5.4	50	ug/L	119752	1	10/11/2009 4:27:00 AM
2-Hexanone	BRL		0.21	10	ug/L	119752	1	10/11/2009 4:27:00 AM
4-Methyl-2-pentanone	BRL		0.41	10	ug/L	119752	1	10/11/2009 4:27:00 AM
Acetone	BRL		5.5	50	ug/L	119752	1	10/11/2009 4:27:00 AM
Benzene	BRL		0.13	5.0	ug/L	119752	1	10/11/2009 4:27:00 AM
Bromodichloromethane	BRL		0.13	5.0	ug/L	119752	1	10/11/2009 4:27:00 AM
Bromoform	BRL		0.30	5.0	ug/L	119752	1	10/11/2009 4:27:00 AM
Bromomethane	BRL		1.9	5.0	ug/L	119752	1	10/11/2009 4:27:00 AM
Carbon disulfide	BRL		0.19	5.0	ug/L	119752	1	10/11/2009 4:27:00 AM
Carbon tetrachloride	BRL		0.18	5.0	ug/L	119752	1	10/11/2009 4:27:00 AM
Chlorobenzene	BRL		0.088	5.0	ug/L	119752	1	10/11/2009 4:27:00 AM
Chloroethane	BRL		0.20	10	ug/L	119752	1	10/11/2009 4:27:00 AM
Chloroform	BRL		0.15	5.0	ug/L	119752	1	10/11/2009 4:27:00 AM
Chloromethane	BRL		0.15	10	ug/L	119752	1	10/11/2009 4:27:00 AM
cis-1,2-Dichloroethene	BRL		0.070	5.0	ug/L	119752	1	10/11/2009 4:27:00 AM
cis-1,3-Dichloropropene	BRL		0.17	5.0	ug/L	119752	1	10/11/2009 4:27:00 AM
Cyclohexane	BRL		0.80	5.0	ug/L	119752	1	10/11/2009 4:27:00 AM
Dibromochloromethane	BRL		0.12	5.0	ug/L	119752	1	10/11/2009 4:27:00 AM
Dichlorodifluoromethane	BRL		0.21	10	ug/L	119752	1	10/11/2009 4:27:00 AM
Ethylbenzene	2.7	J	0.085	5.0	ug/L	119752	1	10/11/2009 4:27:00 AM
Freon-113	21000	E	0.16	10	ug/L	119752	1	10/11/2009 4:27:00 AM
Isopropylbenzene	7.5		0.069	5.0	ug/L	119752	1	10/11/2009 4:27:00 AM
m,p-Xylene	1.5	J	0.092	10	ug/L	119752	1	10/11/2009 4:27:00 AM
Methyl acetate	BRL		0.31	5.0	ug/L	119752	1	10/11/2009 4:27:00 AM

Qualifiers:	*	Value exceeds Maximum Contaminant Level	<	Less than Result value
	>	Greater than Result value	B	Analyte detected in the associated Method Blank
	E	Estimated value above quantitation range	H	Holding times for preparation or analysis exceeded
	J	Estimated value detected below Reporting Limit	N	Analyte not NELAC certified

Analytical Environmental Services, Inc.**Date:** 21-Oct-14

CLIENT: Environmental Planning Specialists, Inc.
Lab Order: 0910778
Project: Color Spectrum
Lab ID: 0910778-013

Client Sample ID: 09280-MW-11 F
Collection Date: 10/7/2009 2:30:00 PM

Matrix: GROUNDWATER

Analyses	Result	Qual	MDL	Rpt. Limit	Units	BatchID	DF	Date Analyzed
TCL VOLATILE ORGANICS SW8260B				(SW5030B)				Analyst: JCT
Methyl tert-butyl ether	1.6	J	0.073	5.0	ug/L	119752	1	10/11/2009 4:27:00 AM
Methylcyclohexane	BRL		0.13	5.0	ug/L	119752	1	10/11/2009 4:27:00 AM
Methylene chloride	BRL		0.96	5.0	ug/L	119752	1	10/11/2009 4:27:00 AM
o-Xylene	3.0	J	0.053	5.0	ug/L	119752	1	10/11/2009 4:27:00 AM
Styrene	BRL		0.12	5.0	ug/L	119752	1	10/11/2009 4:27:00 AM
Tetrachloroethene	64		0.17	5.0	ug/L	119752	1	10/11/2009 4:27:00 AM
Toluene	5.2		0.15	5.0	ug/L	119752	1	10/11/2009 4:27:00 AM
trans-1,2-Dichloroethene	BRL		0.20	5.0	ug/L	119752	1	10/11/2009 4:27:00 AM
trans-1,3-Dichloropropene	BRL		0.098	5.0	ug/L	119752	1	10/11/2009 4:27:00 AM
Trichloroethene	BRL		0.12	5.0	ug/L	119752	1	10/11/2009 4:27:00 AM
Trichlorofluoromethane	BRL		0.17	5.0	ug/L	119752	1	10/11/2009 4:27:00 AM
Vinyl chloride	BRL		0.19	2.0	ug/L	119752	1	10/11/2009 4:27:00 AM
Surr: 4-Bromofluorobenzene	92.4		0	61.3-128	%REC	119752	1	10/11/2009 4:27:00 AM
Surr: Dibromofluoromethane	100		0	67.8-130	%REC	119752	1	10/11/2009 4:27:00 AM
Surr: Toluene-d8	86.8		0	70.6-121	%REC	119752	1	10/11/2009 4:27:00 AM

Qualifiers:	*	Value exceeds Maximum Contaminant Level	<	Less than Result value
	>	Greater than Result value	B	Analyte detected in the associated Method Blank
	E	Estimated value above quantitation range	H	Holding times for preparation or analysis exceeded
	J	Estimated value detected below Reporting Limit	N	Analyte not NELAC certified

Analytical Environmental Services, Inc.

Date: 21-Oct-14

CLIENT: Environmental Planning Specialists, Inc.
Lab Order: 0910778
Project: Color Spectrum
Lab ID: 0910778-014

Client Sample ID: 09280-DUP
Collection Date: 10/7/2009

Matrix: GROUNDWATER

Analyses	Result	Qual	MDL	Rpt. Limit	Units	BatchID	DF	Date Analyzed
METALS, TOTAL SW6010C				(SW3010A)				Analyst: JY
Arsenic	BRL		0.0044	0.0500	mg/L	119718	1	10/12/2009 2:43:06 PM
Lead	BRL		0.0022	0.0100	mg/L	119718	1	10/12/2009 2:43:06 PM
TCL VOLATILE ORGANICS SW8260B				(SW5030B)				Analyst: JCT
1,1,1-Trichloroethane	7.2		0.14	5.0	ug/L	119752	1	10/11/2009 5:52:00 AM
1,1,2,2-Tetrachloroethane	BRL		0.16	5.0	ug/L	119752	1	10/11/2009 5:52:00 AM
1,1,2-Trichloroethane	BRL		0.15	5.0	ug/L	119752	1	10/11/2009 5:52:00 AM
1,1-Dichloroethane	240		1.3	50	ug/L	119752	10	10/13/2009 1:47:00 AM
1,1-Dichloroethene	110		0.27	5.0	ug/L	119752	1	10/11/2009 5:52:00 AM
1,2,4-Trichlorobenzene	BRL		0.21	5.0	ug/L	119752	1	10/11/2009 5:52:00 AM
1,2-Dibromo-3-chloropropane	BRL		0.28	5.0	ug/L	119752	1	10/11/2009 5:52:00 AM
1,2-Dibromoethane	BRL		0.24	5.0	ug/L	119752	1	10/11/2009 5:52:00 AM
1,2-Dichlorobenzene	BRL		0.16	5.0	ug/L	119752	1	10/11/2009 5:52:00 AM
1,2-Dichloroethane	1.0	J	0.12	5.0	ug/L	119752	1	10/11/2009 5:52:00 AM
1,2-Dichloropropane	BRL		0.17	5.0	ug/L	119752	1	10/11/2009 5:52:00 AM
1,3-Dichlorobenzene	BRL		0.13	5.0	ug/L	119752	1	10/11/2009 5:52:00 AM
1,4-Dichlorobenzene	BRL		0.11	5.0	ug/L	119752	1	10/11/2009 5:52:00 AM
2-Butanone	BRL		5.4	50	ug/L	119752	1	10/11/2009 5:52:00 AM
2-Hexanone	BRL		0.21	10	ug/L	119752	1	10/11/2009 5:52:00 AM
4-Methyl-2-pentanone	BRL		0.41	10	ug/L	119752	1	10/11/2009 5:52:00 AM
Acetone	BRL		5.5	50	ug/L	119752	1	10/11/2009 5:52:00 AM
Benzene	1.1	J	0.13	5.0	ug/L	119752	1	10/11/2009 5:52:00 AM
Bromodichloromethane	BRL		0.13	5.0	ug/L	119752	1	10/11/2009 5:52:00 AM
Bromoform	BRL		0.30	5.0	ug/L	119752	1	10/11/2009 5:52:00 AM
Bromomethane	BRL		1.9	5.0	ug/L	119752	1	10/11/2009 5:52:00 AM
Carbon disulfide	BRL		0.19	5.0	ug/L	119752	1	10/11/2009 5:52:00 AM
Carbon tetrachloride	BRL		0.18	5.0	ug/L	119752	1	10/11/2009 5:52:00 AM
Chlorobenzene	BRL		0.088	5.0	ug/L	119752	1	10/11/2009 5:52:00 AM
Chloroethane	BRL		0.20	10	ug/L	119752	1	10/11/2009 5:52:00 AM
Chloroform	BRL		0.15	5.0	ug/L	119752	1	10/11/2009 5:52:00 AM
Chloromethane	BRL		0.15	10	ug/L	119752	1	10/11/2009 5:52:00 AM
cis-1,2-Dichloroethene	BRL		0.070	5.0	ug/L	119752	1	10/11/2009 5:52:00 AM
cis-1,3-Dichloropropene	BRL		0.17	5.0	ug/L	119752	1	10/11/2009 5:52:00 AM
Cyclohexane	BRL		0.80	5.0	ug/L	119752	1	10/11/2009 5:52:00 AM
Dibromochloromethane	BRL		0.12	5.0	ug/L	119752	1	10/11/2009 5:52:00 AM
Dichlorodifluoromethane	BRL		0.21	10	ug/L	119752	1	10/11/2009 5:52:00 AM
Ethylbenzene	BRL		0.085	5.0	ug/L	119752	1	10/11/2009 5:52:00 AM
Freon-113	6200		16	1000	ug/L	119752	100	10/12/2009 8:37:00 PM
Isopropylbenzene	10		0.069	5.0	ug/L	119752	1	10/11/2009 5:52:00 AM
m,p-Xylene	0.46	J	0.092	10	ug/L	119752	1	10/11/2009 5:52:00 AM
Methyl acetate	BRL		0.31	5.0	ug/L	119752	1	10/11/2009 5:52:00 AM

Qualifiers:	*	Value exceeds Maximum Contaminant Level	<	Less than Result value
	>	Greater than Result value	B	Analyte detected in the associated Method Blank
	E	Estimated value above quantitation range	H	Holding times for preparation or analysis exceeded
	J	Estimated value detected below Reporting Limit	N	Analyte not NELAC certified

Analytical Environmental Services, Inc.

Date: 21-Oct-14

CLIENT: Environmental Planning Specialists, Inc.
Lab Order: 0910778
Project: Color Spectrum
Lab ID: 0910778-014

Client Sample ID: 09280-DUP
Collection Date: 10/7/2009

Matrix: GROUNDWATER

Analyses	Result	Qual	MDL	Rpt. Limit	Units	BatchID	DF	Date Analyzed
TCL VOLATILE ORGANICS SW8260B				(SW5030B)				Analyst: JCT
Methyl tert-butyl ether	4.6	J	0.073	5.0	ug/L	119752	1	10/11/2009 5:52:00 AM
Methylcyclohexane	BRL		0.13	5.0	ug/L	119752	1	10/11/2009 5:52:00 AM
Methylene chloride	BRL		0.96	5.0	ug/L	119752	1	10/11/2009 5:52:00 AM
o-Xylene	BRL		0.053	5.0	ug/L	119752	1	10/11/2009 5:52:00 AM
Styrene	BRL		0.12	5.0	ug/L	119752	1	10/11/2009 5:52:00 AM
Tetrachloroethene	42		0.17	5.0	ug/L	119752	1	10/11/2009 5:52:00 AM
Toluene	0.73	J	0.15	5.0	ug/L	119752	1	10/11/2009 5:52:00 AM
trans-1,2-Dichloroethene	BRL		0.20	5.0	ug/L	119752	1	10/11/2009 5:52:00 AM
trans-1,3-Dichloropropene	BRL		0.098	5.0	ug/L	119752	1	10/11/2009 5:52:00 AM
Trichloroethene	BRL		0.12	5.0	ug/L	119752	1	10/11/2009 5:52:00 AM
Trichlorofluoromethane	BRL		0.17	5.0	ug/L	119752	1	10/11/2009 5:52:00 AM
Vinyl chloride	BRL		0.19	2.0	ug/L	119752	1	10/11/2009 5:52:00 AM
Surr: 4-Bromofluorobenzene	81.3		0	61.3-128	%REC	119752	10	10/13/2009 1:47:00 AM
Surr: 4-Bromofluorobenzene	83.7		0	61.3-128	%REC	119752	100	10/12/2009 8:37:00 PM
Surr: 4-Bromofluorobenzene	89.6		0	61.3-128	%REC	119752	1	10/11/2009 5:52:00 AM
Surr: Dibromofluoromethane	101		0	67.8-130	%REC	119752	10	10/13/2009 1:47:00 AM
Surr: Dibromofluoromethane	99.8		0	67.8-130	%REC	119752	100	10/12/2009 8:37:00 PM
Surr: Dibromofluoromethane	100		0	67.8-130	%REC	119752	1	10/11/2009 5:52:00 AM
Surr: Toluene-d8	86.5		0	70.6-121	%REC	119752	10	10/13/2009 1:47:00 AM
Surr: Toluene-d8	83.5		0	70.6-121	%REC	119752	1	10/11/2009 5:52:00 AM
Surr: Toluene-d8	84.4		0	70.6-121	%REC	119752	100	10/12/2009 8:37:00 PM

Qualifiers:	*	Value exceeds Maximum Contaminant Level	<	Less than Result value
	>	Greater than Result value	B	Analyte detected in the associated Method Blank
	E	Estimated value above quantitation range	H	Holding times for preparation or analysis exceeded
	J	Estimated value detected below Reporting Limit	N	Analyte not NELAC certified



ANALYTICAL ENVIRONMENTAL SERVICES, INC.

August 29, 2014

Justin Vickery
Environmental Planning Specialists, Inc.
1050 Crown Pointe Parkway
Atlanta GA 30338

TEL: (404) 315-9113
FAX: (404) 315-8509

RE: Color Spectrum

Dear Justin Vickery:

Order No: 1408K76

Analytical Environmental Services, Inc. received 2 samples on 8/22/2014 3:55:00 PM for the analyses presented in following report.

No problems were encountered during the analyses. Additionally, all results for the associated Quality Control samples were within EPA and/or AES established limits. Any discrepancies associated with the analyses contained herein will be noted and submitted in the form of a project Case Narrative.

AES' certifications are as follows:

- NELAC/Florida Certification number E87582 for analysis of Environmental Water, soil/hazardous waste, and Drinking Water Microbiology, effective 07/01/14-06/30/15.
- AIHA-LAP, LLC Laboratory ID: 100671 for Industrial Hygiene samples (Organics, Inorganics), Environmental Lead (Paint, Soil, Dust Wipes, Air), and Environmental Microbiology (Fungal) Direct Examination, effective until 09/01/15.

These results relate only to the items tested. This report may only be reproduced in full.

If you have any questions regarding these test results, please feel free to call.

James Forrest
Project Manager



TEL.: (770) 457-8177 / TOLL-FREE (800) 972-4889 / FAX: (770) 457-8188

Work Order: 1408K76

Date: 8-22-14 Page 1 of 1

[illegible]

White Copy - Original; Yellow Copy - Client

Analytical Environmental Services, Inc
Date: 29-Aug-14

Client: Environmental Planning Specialists, Inc.
Project Name: Color Spectrum
Lab ID: 1408K76-001

Client Sample ID: 14234-MW-14
Collection Date: 8/22/2014 11:06:00 AM
Matrix: Groundwater

Analyses	Result	Reporting Limit	Qual	Units	BatchID	Dilution Factor	Date Analyzed	Analyst
Volatile Organic Compounds by GC/MS SW8260B					(SW5030B)			
1,1,1-Trichloroethane	BRL	5.0		ug/L	195485	1	08/28/2014 15:09	NP
1,1,2,2-Tetrachloroethane	BRL	5.0		ug/L	195485	1	08/28/2014 15:09	NP
1,1,2-Trichloroethane	BRL	5.0		ug/L	195485	1	08/28/2014 15:09	NP
1,1-Dichloroethane	BRL	5.0		ug/L	195485	1	08/28/2014 15:09	NP
1,1-Dichloroethene	BRL	5.0		ug/L	195485	1	08/28/2014 15:09	NP
1,2,4-Trichlorobenzene	BRL	5.0		ug/L	195485	1	08/28/2014 15:09	NP
1,2-Dibromo-3-chloropropane	BRL	5.0		ug/L	195485	1	08/28/2014 15:09	NP
1,2-Dibromoethane	BRL	5.0		ug/L	195485	1	08/28/2014 15:09	NP
1,2-Dichlorobenzene	BRL	5.0		ug/L	195485	1	08/28/2014 15:09	NP
1,2-Dichloroethane	BRL	5.0		ug/L	195485	1	08/28/2014 15:09	NP
1,2-Dichloropropane	BRL	5.0		ug/L	195485	1	08/28/2014 15:09	NP
1,3-Dichlorobenzene	BRL	5.0		ug/L	195485	1	08/28/2014 15:09	NP
1,4-Dichlorobenzene	BRL	5.0		ug/L	195485	1	08/28/2014 15:09	NP
1,4-Dioxane	BRL	150		ug/L	195485	1	08/28/2014 15:09	NP
2-Butanone	BRL	50		ug/L	195485	1	08/28/2014 15:09	NP
2-Hexanone	BRL	10		ug/L	195485	1	08/28/2014 15:09	NP
4-Methyl-2-pentanone	BRL	10		ug/L	195485	1	08/28/2014 15:09	NP
Acetone	BRL	50		ug/L	195485	1	08/28/2014 15:09	NP
Benzene	BRL	5.0		ug/L	195485	1	08/28/2014 15:09	NP
Bromodichloromethane	BRL	5.0		ug/L	195485	1	08/28/2014 15:09	NP
Bromoform	BRL	5.0		ug/L	195485	1	08/28/2014 15:09	NP
Bromomethane	BRL	5.0		ug/L	195485	1	08/28/2014 15:09	NP
Carbon disulfide	BRL	5.0		ug/L	195485	1	08/28/2014 15:09	NP
Carbon tetrachloride	BRL	5.0		ug/L	195485	1	08/28/2014 15:09	NP
Chlorobenzene	BRL	5.0		ug/L	195485	1	08/28/2014 15:09	NP
Chloroethane	BRL	10		ug/L	195485	1	08/28/2014 15:09	NP
Chloroform	BRL	5.0		ug/L	195485	1	08/28/2014 15:09	NP
Chloromethane	BRL	10		ug/L	195485	1	08/28/2014 15:09	NP
cis-1,2-Dichloroethene	BRL	5.0		ug/L	195485	1	08/28/2014 15:09	NP
cis-1,3-Dichloropropene	BRL	5.0		ug/L	195485	1	08/28/2014 15:09	NP
Cyclohexane	BRL	5.0		ug/L	195485	1	08/28/2014 15:09	NP
Dibromochloromethane	BRL	5.0		ug/L	195485	1	08/28/2014 15:09	NP
Dichlorodifluoromethane	BRL	10		ug/L	195485	1	08/28/2014 15:09	NP
Ethylbenzene	BRL	5.0		ug/L	195485	1	08/28/2014 15:09	NP
Freon-113	BRL	10		ug/L	195485	1	08/28/2014 15:09	NP
Isopropylbenzene	BRL	5.0		ug/L	195485	1	08/28/2014 15:09	NP
Methyl acetate	BRL	5.0		ug/L	195485	1	08/28/2014 15:09	NP
Methyl tert-butyl ether	BRL	5.0		ug/L	195485	1	08/28/2014 15:09	NP
Methylcyclohexane	BRL	5.0		ug/L	195485	1	08/28/2014 15:09	NP
Methylene chloride	BRL	5.0		ug/L	195485	1	08/28/2014 15:09	NP
Styrene	BRL	5.0		ug/L	195485	1	08/28/2014 15:09	NP

Qualifiers: * Value exceeds maximum contaminant level
 BRL Below reporting limit
 H Holding times for preparation or analysis exceeded
 N Analyte not NELAC certified
 B Analyte detected in the associated method blank
 > Greater than Result value

E Estimated (value above quantitation range)
 S Spike Recovery outside limits due to matrix
 Narr See case narrative
 NC Not confirmed
 < Less than Result value
 J Estimated value detected below Reporting Limit

Analytical Environmental Services, Inc
Date: 29-Aug-14

Client: Environmental Planning Specialists, Inc.
Project Name: Color Spectrum
Lab ID: 1408K76-001

Client Sample ID: 14234-MW-14
Collection Date: 8/22/2014 11:06:00 AM
Matrix: Groundwater

Analyses	Result	Reporting Limit	Qual	Units	BatchID	Dilution Factor	Date Analyzed	Analyst
Volatile Organic Compounds by GC/MS SW8260B				(SW5030B)				
Tetrachloroethene	BRL	5.0		ug/L	195485	1	08/28/2014 15:09	NP
Toluene	BRL	5.0		ug/L	195485	1	08/28/2014 15:09	NP
trans-1,2-Dichloroethene	BRL	5.0		ug/L	195485	1	08/28/2014 15:09	NP
trans-1,3-Dichloropropene	BRL	5.0		ug/L	195485	1	08/28/2014 15:09	NP
Trichloroethene	BRL	5.0		ug/L	195485	1	08/28/2014 15:09	NP
Trichlorofluoromethane	BRL	5.0		ug/L	195485	1	08/28/2014 15:09	NP
Vinyl chloride	BRL	2.0		ug/L	195485	1	08/28/2014 15:09	NP
Xylenes, Total	BRL	5.0		ug/L	195485	1	08/28/2014 15:09	NP
Surr: 4-Bromofluorobenzene	81.9	66.2-120		%REC	195485	1	08/28/2014 15:09	NP
Surr: Dibromofluoromethane	105	79.5-121		%REC	195485	1	08/28/2014 15:09	NP
Surr: Toluene-d8	103	77-117		%REC	195485	1	08/28/2014 15:09	NP

Qualifiers: * Value exceeds maximum contaminant level
 BRL Below reporting limit
 H Holding times for preparation or analysis exceeded
 N Analyte not NELAC certified
 B Analyte detected in the associated method blank
 > Greater than Result value

E Estimated (value above quantitation range)
 S Spike Recovery outside limits due to matrix
 Narr See case narrative
 NC Not confirmed
 < Less than Result value
 J Estimated value detected below Reporting Limit

Analytical Environmental Services, Inc
Date: 29-Aug-14

Client: Environmental Planning Specialists, Inc.
Project Name: Color Spectrum
Lab ID: 1408K76-002

Client Sample ID: TRIP BLANK
Collection Date: 8/22/2014
Matrix: Aqueous

Analyses	Result	Reporting Limit	Qual	Units	BatchID	Dilution Factor	Date Analyzed	Analyst
Volatile Organic Compounds by GC/MS SW8260B				(SW5030B)				
1,1,1-Trichloroethane	BRL	5.0		ug/L	195485	1	08/28/2014 14:45	NP
1,1,2,2-Tetrachloroethane	BRL	5.0		ug/L	195485	1	08/28/2014 14:45	NP
1,1,2-Trichloroethane	BRL	5.0		ug/L	195485	1	08/28/2014 14:45	NP
1,1-Dichloroethane	BRL	5.0		ug/L	195485	1	08/28/2014 14:45	NP
1,1-Dichloroethene	BRL	5.0		ug/L	195485	1	08/28/2014 14:45	NP
1,2,4-Trichlorobenzene	BRL	5.0		ug/L	195485	1	08/28/2014 14:45	NP
1,2-Dibromo-3-chloropropane	BRL	5.0		ug/L	195485	1	08/28/2014 14:45	NP
1,2-Dibromoethane	BRL	5.0		ug/L	195485	1	08/28/2014 14:45	NP
1,2-Dichlorobenzene	BRL	5.0		ug/L	195485	1	08/28/2014 14:45	NP
1,2-Dichloroethane	BRL	5.0		ug/L	195485	1	08/28/2014 14:45	NP
1,2-Dichloropropane	BRL	5.0		ug/L	195485	1	08/28/2014 14:45	NP
1,3-Dichlorobenzene	BRL	5.0		ug/L	195485	1	08/28/2014 14:45	NP
1,4-Dichlorobenzene	BRL	5.0		ug/L	195485	1	08/28/2014 14:45	NP
1,4-Dioxane	BRL	150		ug/L	195485	1	08/28/2014 14:45	NP
2-Butanone	BRL	50		ug/L	195485	1	08/28/2014 14:45	NP
2-Hexanone	BRL	10		ug/L	195485	1	08/28/2014 14:45	NP
4-Methyl-2-pentanone	BRL	10		ug/L	195485	1	08/28/2014 14:45	NP
Acetone	BRL	50		ug/L	195485	1	08/28/2014 14:45	NP
Benzene	BRL	5.0		ug/L	195485	1	08/28/2014 14:45	NP
Bromodichloromethane	BRL	5.0		ug/L	195485	1	08/28/2014 14:45	NP
Bromoform	BRL	5.0		ug/L	195485	1	08/28/2014 14:45	NP
Bromomethane	BRL	5.0		ug/L	195485	1	08/28/2014 14:45	NP
Carbon disulfide	BRL	5.0		ug/L	195485	1	08/28/2014 14:45	NP
Carbon tetrachloride	BRL	5.0		ug/L	195485	1	08/28/2014 14:45	NP
Chlorobenzene	BRL	5.0		ug/L	195485	1	08/28/2014 14:45	NP
Chloroethane	BRL	10		ug/L	195485	1	08/28/2014 14:45	NP
Chloroform	BRL	5.0		ug/L	195485	1	08/28/2014 14:45	NP
Chloromethane	BRL	10		ug/L	195485	1	08/28/2014 14:45	NP
cis-1,2-Dichloroethene	BRL	5.0		ug/L	195485	1	08/28/2014 14:45	NP
cis-1,3-Dichloropropene	BRL	5.0		ug/L	195485	1	08/28/2014 14:45	NP
Cyclohexane	BRL	5.0		ug/L	195485	1	08/28/2014 14:45	NP
Dibromochloromethane	BRL	5.0		ug/L	195485	1	08/28/2014 14:45	NP
Dichlorodifluoromethane	BRL	10		ug/L	195485	1	08/28/2014 14:45	NP
Ethylbenzene	BRL	5.0		ug/L	195485	1	08/28/2014 14:45	NP
Freon-113	BRL	10		ug/L	195485	1	08/28/2014 14:45	NP
Isopropylbenzene	BRL	5.0		ug/L	195485	1	08/28/2014 14:45	NP
Methyl acetate	BRL	5.0		ug/L	195485	1	08/28/2014 14:45	NP
Methyl tert-butyl ether	BRL	5.0		ug/L	195485	1	08/28/2014 14:45	NP
Methylcyclohexane	BRL	5.0		ug/L	195485	1	08/28/2014 14:45	NP
Methylene chloride	BRL	5.0		ug/L	195485	1	08/28/2014 14:45	NP
Styrene	BRL	5.0		ug/L	195485	1	08/28/2014 14:45	NP

Qualifiers: * Value exceeds maximum contaminant level
 BRL Below reporting limit
 H Holding times for preparation or analysis exceeded
 N Analyte not NELAC certified
 B Analyte detected in the associated method blank
 > Greater than Result value

E Estimated (value above quantitation range)
 S Spike Recovery outside limits due to matrix
 Narr See case narrative
 NC Not confirmed
 < Less than Result value
 J Estimated value detected below Reporting Limit

Analytical Environmental Services, Inc
Date: 29-Aug-14

Client: Environmental Planning Specialists, Inc.
Project Name: Color Spectrum
Lab ID: 1408K76-002

Client Sample ID: TRIP BLANK
Collection Date: 8/22/2014
Matrix: Aqueous

Analyses	Result	Reporting Limit	Qual	Units	BatchID	Dilution Factor	Date Analyzed	Analyst
Volatile Organic Compounds by GC/MS SW8260B				(SW5030B)				
Tetrachloroethene	BRL	5.0		ug/L	195485	1	08/28/2014 14:45	NP
Toluene	BRL	5.0		ug/L	195485	1	08/28/2014 14:45	NP
trans-1,2-Dichloroethene	BRL	5.0		ug/L	195485	1	08/28/2014 14:45	NP
trans-1,3-Dichloropropene	BRL	5.0		ug/L	195485	1	08/28/2014 14:45	NP
Trichloroethene	BRL	5.0		ug/L	195485	1	08/28/2014 14:45	NP
Trichlorofluoromethane	BRL	5.0		ug/L	195485	1	08/28/2014 14:45	NP
Vinyl chloride	BRL	2.0		ug/L	195485	1	08/28/2014 14:45	NP
Xylenes, Total	BRL	5.0		ug/L	195485	1	08/28/2014 14:45	NP
Surr: 4-Bromofluorobenzene	82.6	66.2-120		%REC	195485	1	08/28/2014 14:45	NP
Surr: Dibromofluoromethane	107	79.5-121		%REC	195485	1	08/28/2014 14:45	NP
Surr: Toluene-d8	105	77-117		%REC	195485	1	08/28/2014 14:45	NP

Qualifiers: * Value exceeds maximum contaminant level
 BRL Below reporting limit
 H Holding times for preparation or analysis exceeded
 N Analyte not NELAC certified
 B Analyte detected in the associated method blank
 > Greater than Result value

E Estimated (value above quantitation range)
 S Spike Recovery outside limits due to matrix
 Narr See case narrative
 NC Not confirmed
 < Less than Result value
 J Estimated value detected below Reporting Limit

Analytical Environmental Services, Inc.

Sample/Cooler Receipt Checklist

Client Env. Planning Specialists Work Order Number 1408K76

Checklist completed by Toana Pacurar 8/22/14
Signature Date

Carrier name: FedEx ☐ UPS ☐ Courier ☐ Client ☒ US Mail ☐ Other ☐

Shipping container/cooler in good condition? Yes ☒ No ☐ Not Present ☐

Custody seals intact on shipping container/cooler? Yes ☐ No ☐ Not Present ☒

Custody seals intact on sample bottles? Yes ☐ No ☐ Not Present ☒

Container/Temp Blank temperature in compliance? ($0^{\circ} \leq 6^{\circ}C$) * Yes ☒ No ☐

Cooler #1 34°C Cooler #2 ☐ Cooler #3 ☐ Cooler #4 ☐ Cooler #5 ☐ Cooler #6 ☐

Chain of custody present? Yes ☒ No ☐

Chain of custody signed when relinquished and received? Yes ☒ No ☐

Chain of custody agrees with sample labels? Yes ☒ No ☐

Samples in proper container/bottle? Yes ☒ No ☐

Sample containers intact? Yes ☒ No ☐

Sufficient sample volume for indicated test? Yes ☒ No ☐

All samples received within holding time? Yes ☒ No ☐

Was TAT marked on the COC? Yes ☒ No ☐

Proceed with Standard TAT as per project history? Yes ☐ No ☐ Not Applicable ☒

Water - VOA vials have zero headspace? No VOA vials submitted ☐ Yes ☒ No ☐

Water - pH acceptable upon receipt? Yes ☒ No ☐ Not Applicable ☐

Adjusted? ☐ Checked by ☐

Sample Condition: Good ☒ Other(Explain) ☐

(For diffusive samples or AIHA lead) Is a known blank included? Yes ☒ No ☐

See Case Narrative for resolution of the Non-Conformance.

* Samples do not have to comply with the given range for certain parameters.

\\Aes_server\\Sample Receipt\\My Documents\\COCs and pH Adjustment Sheet\\Sample_Cooler_Recipt_Checklist_Rev1.rtf

Client: Environmental Planning Specialists, Inc.
Project Name: Color Spectrum
Workorder: 1408K76

ANALYTICAL QC SUMMARY REPORT**BatchID: 195485**

Sample ID: MB-195485	Client ID:				Units: ug/L	Prep Date: 08/27/2014	Run No: 274624				
SampleType: MBLK	TestCode: Volatile Organic Compounds by GC/MS SW8260B				BatchID: 195485	Analysis Date: 08/27/2014	Seq No: 5795611				
Analyte	Result	RPT Limit	SPK value	SPK Ref Val	%REC	Low Limit	High Limit	RPD Ref Val	%RPD	RPD Limit	Qual

1,1,1-Trichloroethane	BRL	5.0
1,1,2,2-Tetrachloroethane	BRL	5.0
1,1,2-Trichloroethane	BRL	5.0
1,1-Dichloroethane	BRL	5.0
1,1-Dichloroethene	BRL	5.0
1,2,4-Trichlorobenzene	BRL	5.0
1,2-Dibromo-3-chloropropane	BRL	5.0
1,2-Dibromoethane	BRL	5.0
1,2-Dichlorobenzene	BRL	5.0
1,2-Dichloroethane	BRL	5.0
1,2-Dichloropropane	BRL	5.0
1,3-Dichlorobenzene	BRL	5.0
1,4-Dichlorobenzene	BRL	5.0
2-Butanone	BRL	50
2-Hexanone	BRL	10
4-Methyl-2-pentanone	BRL	10
Acetone	BRL	50
Benzene	BRL	5.0
Bromodichloromethane	BRL	5.0
Bromoform	BRL	5.0
Bromomethane	BRL	5.0
Carbon disulfide	BRL	5.0
Carbon tetrachloride	BRL	5.0
Chlorobenzene	BRL	5.0
Chloroethane	BRL	10
Chloroform	BRL	5.0
Chloromethane	BRL	10

Qualifiers:	>	Greater than Result value	<	Less than Result value	B	Analyte detected in the associated method blank
	BRL	Below reporting limit	E	Estimated (value above quantitation range)	H	Holding times for preparation or analysis exceeded
	J	Estimated value detected below Reporting Limit	N	Analyte not NELAC certified	R	RPD outside limits due to matrix
	Rpt Lim	Reporting Limit	S	Spike Recovery outside limits due to matrix		

Client: Environmental Planning Specialists, Inc.
Project Name: Color Spectrum
Workorder: 1408K76

ANALYTICAL QC SUMMARY REPORT**BatchID: 195485**

Sample ID: MB-195485	Client ID:					Units: ug/L	Prep Date: 08/27/2014	Run No: 274624			
SampleType: MBLK	TestCode: Volatile Organic Compounds by GC/MS SW8260B					BatchID: 195485	Analysis Date: 08/27/2014	Seq No: 5795611			
Analyte	Result	RPT Limit	SPK value	SPK Ref Val	%REC	Low Limit	High Limit	RPD Ref Val	%RPD	RPD Limit	Qual
cis-1,2-Dichloroethene	BRL	5.0									
cis-1,3-Dichloropropene	BRL	5.0									
Cyclohexane	BRL	5.0									
Dibromochloromethane	BRL	5.0									
Dichlorodifluoromethane	BRL	10									
Ethylbenzene	BRL	5.0									
Freon-113	BRL	10									
Isopropylbenzene	BRL	5.0									
Methyl acetate	BRL	5.0									
Methyl tert-butyl ether	BRL	5.0									
Methylcyclohexane	BRL	5.0									
Methylene chloride	BRL	5.0									
Styrene	BRL	5.0									
Tetrachloroethene	BRL	5.0									
Toluene	BRL	5.0									
trans-1,2-Dichloroethene	BRL	5.0									
trans-1,3-Dichloropropene	BRL	5.0									
Trichloroethene	BRL	5.0									
Trichlorofluoromethane	BRL	5.0									
Vinyl chloride	BRL	2.0									
Xylenes, Total	BRL	5.0									
Surr: 4-Bromofluorobenzene	42.71	0	50.00		85.4	66.2	120				
Surr: Dibromofluoromethane	50.65	0	50.00		101	79.5	121				
Surr: Toluene-d8	50.65	0	50.00		101	77	117				

Qualifiers:	>	Greater than Result value	<	Less than Result value	B	Analyte detected in the associated method blank
	BRL	Below reporting limit	E	Estimated (value above quantitation range)	H	Holding times for preparation or analysis exceeded
	J	Estimated value detected below Reporting Limit	N	Analyte not NELAC certified	R	RPD outside limits due to matrix
	Rpt Lim	Reporting Limit	S	Spike Recovery outside limits due to matrix		

Client: Environmental Planning Specialists, Inc.
Project Name: Color Spectrum
Workorder: 1408K76

ANALYTICAL QC SUMMARY REPORT**BatchID: 195485**

Sample ID: LCS-195485	Client ID:					Units: ug/L	Prep Date: 08/27/2014	Run No: 274624			
SampleType: LCS	TestCode: Volatile Organic Compounds by GC/MS SW8260B					BatchID: 195485	Analysis Date: 08/27/2014	Seq No: 5795610			
Analyte	Result	RPT Limit	SPK value	SPK Ref Val	%REC	Low Limit	High Limit	RPD Ref Val	%RPD	RPD Limit	Qual

1,1-Dichloroethene	52.29	5.0	50.00		105	63.1	140				
Benzene	51.45	5.0	50.00		103	74.2	129				
Chlorobenzene	45.89	5.0	50.00		91.8	70	129				
Toluene	52.63	5.0	50.00		105	74.2	129				
Trichloroethene	51.22	5.0	50.00		102	71.2	135				
Surr: 4-Bromofluorobenzene	43.23	0	50.00		86.5	66.2	120				
Surr: Dibromofluoromethane	48.48	0	50.00		97.0	79.5	121				
Surr: Toluene-d8	50.83	0	50.00		102	77	117				

Sample ID: 1408K90-022AMS	Client ID:				Units: ug/L	Prep Date: 08/27/2014	Run No: 274624				
SampleType: MS	TestCode: Volatile Organic Compounds by GC/MS SW8260B				BatchID: 195485	Analysis Date: 08/27/2014	Seq No: 5795623				
Analyte	Result	RPT Limit	SPK value	SPK Ref Val	%REC	Low Limit	High Limit	RPD Ref Val	%RPD	RPD Limit	Qual

1,1-Dichloroethene	635500	50000	500000		127	60.2	159				
Benzene	560300	50000	500000		112	70.2	138				
Chlorobenzene	491400	50000	500000		98.3	70.1	133				
Toluene	586400	50000	500000		117	70	139				
Trichloroethene	552100	50000	500000		110	70.1	144				
Surr: 4-Bromofluorobenzene	421200	0	500000		84.2	66.2	120				
Surr: Dibromofluoromethane	506400	0	500000		101	79.5	121				
Surr: Toluene-d8	505900	0	500000		101	77	117				

Sample ID: 1408K90-022AMSD	Client ID:				Units: ug/L	Prep Date: 08/27/2014	Run No: 274624				
SampleType: MSD	TestCode: Volatile Organic Compounds by GC/MS SW8260B				BatchID: 195485	Analysis Date: 08/27/2014	Seq No: 5795624				
Analyte	Result	RPT Limit	SPK value	SPK Ref Val	%REC	Low Limit	High Limit	RPD Ref Val	%RPD	RPD Limit	Qual

1,1-Dichloroethene	630900	50000	500000		126	60.2	159	635500	0.726	19.2	
Benzene	550700	50000	500000		110	70.2	138	560300	1.73	20	

Qualifiers:	>	Greater than Result value	<	Less than Result value	B	Analyte detected in the associated method blank
	BRL	Below reporting limit	E	Estimated (value above quantitation range)	H	Holding times for preparation or analysis exceeded
	J	Estimated value detected below Reporting Limit	N	Analyte not NELAC certified	R	RPD outside limits due to matrix
	Rpt Lim	Reporting Limit	S	Spike Recovery outside limits due to matrix		

Client: Environmental Planning Specialists, Inc.
Project Name: Color Spectrum
Workorder: 1408K76

ANALYTICAL QC SUMMARY REPORT

BatchID: 195485

Sample ID: 1408K90-022AMSD	Client ID:					Units: ug/L	Prep Date: 08/27/2014	Run No: 274624			
SampleType: MSD	TestCode: Volatile Organic Compounds by GC/MS SW8260B					BatchID: 195485	Analysis Date: 08/27/2014	Seq No: 5795624			
Analyte	Result	RPT Limit	SPK value	SPK Ref Val	%REC	Low Limit	High Limit	RPD Ref Val	%RPD	RPD Limit	Qual
Chlorobenzene	489600	50000	500000		97.9	70.1	133	491400	0.367	20	
Toluene	578000	50000	500000		116	70	139	586400	1.44	20	
Trichloroethene	542400	50000	500000		108	70.1	144	552100	1.77	20	
Surr: 4-Bromofluorobenzene	419900	0	500000		84.0	66.2	120	421200	0	0	
Surr: Dibromofluoromethane	508400	0	500000		102	79.5	121	506400	0	0	
Surr: Toluene-d8	514500	0	500000		103	77	117	505900	0	0	

Qualifiers:	>	Greater than Result value	<	Less than Result value	B	Analyte detected in the associated method blank
	BRL	Below reporting limit	E	Estimated (value above quantitation range)	H	Holding times for preparation or analysis exceeded
	J	Estimated value detected below Reporting Limit	N	Analyte not NELAC certified	R	RPD outside limits due to matrix
	Rpt Lim	Reporting Limit	S	Spike Recovery outside limits due to matrix		

APPENDIX E

Well Development and Well Sampling Forms

Monitoring Well Sampling Form

EPS

EPS Project: <u>Color Spectrum</u>		Date: <u>08/15/2014</u>	
Well ID: <u>MW-14</u>		Field Conditions: <u>Clear, ~73°F</u>	
Sampling Performed By: <u>William Crowe</u>		General Condition of Well: <u>Good</u>	
Well Construction: <u>Stick up</u>		Condition of surrounding area: <u>Good</u>	
Well Labeled: <u>N</u>	Well Cap: <u>Y</u>	Well Locked: <u>X</u>	Depth to Water from TOC: <u>4.43</u>
Well depth from TOC: <u>10.94</u>		Method of measure: <u>WLM</u>	
Well Diameter (in): <u>2"</u>		<u>6.51</u>	
Height (Ht) of water in well (Well depth from TOC - Static level from TOC):			
Volume of water in well (Ht. x (.16 for 2") (.653 for 4") (1.469 for 6")):		<u>1.04</u>	
Purging Method: <u>bauler / Per Pump</u>	Time @ Start of Purge: <u>1001</u>		Three Well Volumes (gal): <u>3.12</u>
Sample Method:	Sample Parameters:		

[illegible]

Ferrous Iron (Fe²⁺)= **mg/L**

Technician Signature





Monitoring Well Sampling Form

EPS Project: <u>Color Spectrum</u>		Date: <u>8-22-14</u>
Well ID: <u>MW-14</u>	Field Conditions: <u>77° F, clear</u>	
Sampling Performed By: <u>Alex Testa</u>	General Condition of Well: <u>good</u>	
Well Construction: <u>N/A</u>	Condition of surrounding area: <u>forested</u>	
Well Labeled: <u>NO</u>	Well Cap: <u>YES</u>	Well Locked: <u>YES</u>
Well depth from TOC: <u>8.0</u>	Depth to Water from TOC: <u>3-46</u>	
Well Diameter (in): <u>2"</u>	Method of measure: <u>WLM</u>	
Height (Ht) of water in well (Well depth from TOC - Static level from TOC): <u>0.40</u>	Three Well Volumes (gal): <u>1-23</u>	
Volume of water in well (Ht. x(.16 for 2")(.653 for 4") (1.469 for 6")):	Time @ Start of Purge: <u>1038</u>	
Purging Method: <u>peristaltic pump</u>	Sample Parameters: <u>VOC</u>	
Sample Method: <u>direct</u>		

[illegible]

Temp probe ID:

Ferrous Iron (Fe²⁺)= **mg/L**

Sample ID: 14234-MW-14

Time Collected: 1106

Technician Signature Ally Smith

APPENDIX F

Boring Logs and Well Diagrams


APPENDIX G

Slug Test Data

Color Spectrum

Bouwer and Rice Graph

MW-4



Analysis by Starpoint Software

H_o is 0.846 feet at 28.38 Seconds

Report Date: 7/2/2007 11:51
Report User Name: amodi
Report Computer Name: EPS-DIM-2400

Log File Properties

File Name MW4 2007-06-28 09.57.08.wsl
Create Date 6/28/2007 12:56

Device Properties

Device LevelTroll 700
Site color spectrum mw-4
Device Name MW4
Serial Number 114123
Firmware Version 2.04

Log Configuration

Log Name MW4
Created By Unknown
Computer Name Pocket PC
Application WinSituMobile.exe
Application Version 5.1.0.11
Create Date 6/28/2007 11:45
Notes Size(bytes) 4096
Type True Logarithmic
Overwrite when full Disabled
Scheduled Start Manual Start
Scheduled Stop No Stop Time
Max Interval Days: 0 Hours: 00 Mins: 20 Secs: 00

Level Reference Settings At Log Creation

Level Measurement Mode Depth
Specific Gravity 0.999

Log Notes:

Date and Time Note
6/28/2007 11:45 Manual Start Command
6/28/2007 12:56 Suspend Command
6/28/2007 12:56 Manual Stop Command

Log Data:

Record Count 139

Date and Time	Elapsed Time Seconds	Sensor: Pres 15G SN#: 114123 Pressure (PSI)	Sensor: Pres 15G SN#: 114123 Depth (ft)	Sensor: Pres 15G SN#: 114123 Temperature (F)
6/28/2007 11:45	0	3.498	8.077	68.414
6/28/2007 11:45	0.251	3.499	8.08	68.442
6/28/2007 11:45	0.502	3.5	8.082	68.464
6/28/2007 11:45	0.751	3.499	8.079	68.478
6/28/2007 11:45	1.001	3.499	8.079	68.485

6/28/2007 11:45	1.251	3.499	8.078	68.491
6/28/2007 11:45	1.501	3.499	8.078	68.501
6/28/2007 11:45	1.751	3.498	8.076	68.505
6/28/2007 11:45	2.001	3.499	8.078	68.509
6/28/2007 11:45	2.251	3.498	8.077	68.509
6/28/2007 11:45	2.501	3.498	8.078	68.513
6/28/2007 11:45	2.751	3.499	8.078	68.513
6/28/2007 11:45	3.001	3.498	8.078	68.511
6/28/2007 11:45	3.251	3.498	8.076	68.508
6/28/2007 11:45	3.501	3.498	8.077	68.508
6/28/2007 11:45	3.751	3.499	8.079	68.512
6/28/2007 11:45	4.001	3.498	8.077	68.505
6/28/2007 11:45	4.251	3.498	8.077	68.506
6/28/2007 11:45	4.501	3.498	8.077	68.51
6/28/2007 11:45	4.751	3.498	8.076	68.502
6/28/2007 11:45	5.001	3.498	8.077	68.505
6/28/2007 11:45	5.251	3.498	8.077	68.495
6/28/2007 11:45	5.501	3.499	8.079	68.494
6/28/2007 11:45	5.751	3.497	8.075	68.491
6/28/2007 11:45	6.001	3.498	8.077	68.492
6/28/2007 11:45	6.361	3.498	8.078	68.471
6/28/2007 11:45	6.721	3.498	8.077	68.457
6/28/2007 11:45	7.141	3.499	8.078	68.437
6/28/2007 11:45	7.561	3.498	8.077	68.423
6/28/2007 11:45	7.981	3.499	8.08	68.42
6/28/2007 11:45	8.461	3.498	8.078	68.403
6/28/2007 11:45	9.001	3.498	8.077	68.386
6/28/2007 11:45	9.481	3.499	8.079	68.376
6/28/2007 11:45	10.081	3.498	8.078	68.359
6/28/2007 11:45	10.681	3.499	8.078	68.348
6/28/2007 11:45	11.281	3.498	8.077	68.335
6/28/2007 11:45	12.074	3.499	8.078	68.308
6/28/2007 11:45	12.66	3.498	8.077	68.336
6/28/2007 11:45	13.441	3.499	8.079	68.301
6/28/2007 11:45	14.221	3.499	8.079	68.283
6/28/2007 11:45	15.061	3.5	8.08	68.259
6/28/2007 11:45	15.961	3.499	8.078	68.242
6/28/2007 11:45	16.92	3.499	8.08	68.228
6/28/2007 11:45	17.88	3.5	8.081	68.206
6/28/2007 11:45	18.961	3.501	8.083	68.184
6/28/2007 11:45	20.101	3.503	8.088	68.164
6/28/2007 11:45	21.301	3.504	8.09	68.147
6/28/2007 11:45	22.561	3.381	7.807	68.124
6/28/2007 11:45	23.88	3.612	8.34	68.131
6/28/2007 11:45	25.321	3.859	8.91	68.084
6/28/2007 11:45	26.821	3.726	8.603	68.063
6/28/2007 11:45	28.38	3.864	8.923	68.041
6/28/2007 11:45	30.061	3.801	8.776	68.008
6/28/2007 11:45	31.86	3.751	8.66	67.975
6/28/2007 11:45	33.721	3.795	8.763	67.974
6/28/2007 11:46	35.761	3.795	8.762	67.93
6/28/2007 11:46	37.86	3.516	8.118	67.891
6/28/2007 11:46	40.081	3.709	8.563	67.869
6/28/2007 11:46	42.481	3.725	8.602	67.826
6/28/2007 11:46	45	3.721	8.592	67.805

6/28/2007 11:46	47.64	3.719	8.588	67.763
6/28/2007 11:46	50.461	3.718	8.584	67.722
6/28/2007 11:46	53.473	3.716	8.58	67.715
6/28/2007 11:46	56.64	3.714	8.576	67.646
6/28/2007 11:46	60.001	3.711	8.569	67.599
6/28/2007 11:46	63.6	3.71	8.565	67.58
6/28/2007 11:46	67.2	3.708	8.561	67.515
6/28/2007 11:46	71.401	3.706	8.556	67.455
6/28/2007 11:46	75.6	3.703	8.551	67.417
6/28/2007 11:46	79.8	3.703	8.549	67.359
6/28/2007 11:46	84.6	3.7	8.544	67.311
6/28/2007 11:46	90	3.699	8.54	67.247
6/28/2007 11:46	94.8	3.697	8.536	67.204
6/28/2007 11:47	100.801	3.695	8.532	67.137
6/28/2007 11:47	106.8	3.693	8.527	67.081
6/28/2007 11:47	112.801	3.692	8.526	67.016
6/28/2007 11:47	119.4	3.69	8.521	66.956
6/28/2007 11:47	126.6	3.688	8.516	66.891
6/28/2007 11:47	134.4	3.686	8.511	66.835
6/28/2007 11:47	142.201	3.684	8.507	66.761
6/28/2007 11:47	150.601	3.683	8.504	66.694
6/28/2007 11:48	159.6	3.68	8.497	66.635
6/28/2007 11:48	169.201	3.678	8.492	66.559
6/28/2007 11:48	178.801	3.677	8.489	66.498
6/28/2007 11:48	189.6	3.674	8.483	66.43
6/28/2007 11:48	201.001	3.672	8.478	66.359
6/28/2007 11:48	213.049	3.668	8.468	66.292
6/28/2007 11:49	225.6	3.666	8.465	66.226
6/28/2007 11:49	238.801	3.664	8.459	66.158
6/28/2007 11:49	253.237	3.661	8.454	66.144
6/28/2007 11:49	268.2	3.659	8.449	66.029
6/28/2007 11:50	283.8	3.656	8.441	65.98
6/28/2007 11:50	300.6	3.653	8.436	65.899
6/28/2007 11:50	318.6	3.651	8.43	65.842
6/28/2007 11:51	337.2	3.648	8.422	65.779
6/28/2007 11:51	357.6	3.645	8.416	65.72
6/28/2007 11:51	378.6	3.643	8.412	65.666
6/28/2007 11:52	400.8	3.641	8.407	65.609
6/28/2007 11:52	424.8	3.636	8.396	65.561
6/28/2007 11:52	450	3.634	8.391	65.503
6/28/2007 11:53	476.4	3.632	8.386	65.46
6/28/2007 11:53	504.6	3.629	8.379	65.422
6/28/2007 11:54	534.6	3.624	8.369	65.375
6/28/2007 11:54	566.4	3.623	8.366	65.322
6/28/2007 11:55	600	3.619	8.356	65.281
6/28/2007 11:56	636	3.616	8.35	65.252
6/28/2007 11:56	672	3.613	8.342	65.21
6/28/2007 11:57	714.179	3.609	8.334	65.209
6/28/2007 11:58	756	3.607	8.328	65.147
6/28/2007 11:58	798	3.604	8.321	65.114
6/28/2007 11:59	846	3.6	8.313	65.087
6/28/2007 12:00	900	3.596	8.303	65.056
6/28/2007 12:01	948	3.594	8.298	65.037
6/28/2007 12:02	1008	3.59	8.29	65.007
6/28/2007 12:03	1068	3.587	8.281	64.988


6/28/2007 12:04	1128	3.583	8.272	64.97
6/28/2007 12:05	1194.057	3.579	8.264	64.984
6/28/2007 12:06	1266	3.575	8.254	64.934
6/28/2007 12:07	1344.115	3.571	8.245	64.943
6/28/2007 12:09	1422	3.568	8.237	64.894
6/28/2007 12:10	1506	3.564	8.229	64.888
6/28/2007 12:12	1596	3.56	8.22	64.875
6/28/2007 12:13	1692	3.557	8.214	64.85
6/28/2007 12:15	1788	3.554	8.206	64.84
6/28/2007 12:17	1896	3.551	8.199	64.83
6/28/2007 12:18	2010	3.547	8.19	64.816
6/28/2007 12:20	2130	3.545	8.186	64.797
6/28/2007 12:23	2256	3.542	8.179	64.788
6/28/2007 12:25	2388	3.335	7.701	64.772
6/28/2007 12:27	2532	3.376	7.796	64.745
6/28/2007 12:30	2682	3.4	7.85	64.744
6/28/2007 12:32	2838	3.42	7.896	64.788
6/28/2007 12:35	3006	3.436	7.934	64.934
6/28/2007 12:38	3186	3.451	7.968	65.066
6/28/2007 12:41	3372	3.461	7.992	65.069
6/28/2007 12:45	3576	3.472	8.016	65.061
6/28/2007 12:48	3786	3.479	8.033	64.985
6/28/2007 12:52	4008	3.488	8.053	64.928
6/28/2007 12:56	4248	3.493	8.066	64.884

Color Spectrum

LaFayette, GA June 28, 2007

Bouwer and Rice Graph

MW-6



Analysis by Starpoint Software

H_o is 0.583 feet at 112.8 Seconds

Report Date: 7/2/2007 11:52
Report User Name: amodi
Report Computer Name: EPS-DIM-2400

Log File Properties

File Name MW6 2007-06-28 11.22.20.wsl
Create Date 6/28/2007 14:22

Device Properties

Device LevelTroll 700
Site color spectrum mw-4
Device Name MW4
Serial Number 114123
Firmware Version 2.04

Log Configuration

Log Name MW6
Created By Unknown
Computer Name Pocket PC
Application WinSituMobile.exe
Application Version 5.1.0.11
Create Date 6/28/2007 13:38
Notes Size(bytes) 4096
Type True Logarithmic
Overwrite when full Disabled
Scheduled Start Manual Start
Scheduled Stop No Stop Time
Max Interval Days: 0 Hours: 00 Mins: 20 Secs: 00

Level Reference Settings At Log Creation

Level Measurement Mode Depth
Specific Gravity 0.999

Log Notes:

Date and Time Note
6/28/2007 13:38 Manual Start Command
6/28/2007 14:22 Manual Stop Command

Log Data:

Record Count 130

Date and Time	Elapsed Time Seconds	Sensor: Pres 15G SN#: 114123 Pressure (PSI)	Sensor: Pres 15G SN#: 114123 Depth (ft)	Sensor: Pres 15G SN#: 114123 Temperature (F)
6/28/2007 13:38		0	3.869	8.933
6/28/2007 13:38		0.25	3.869	8.933
6/28/2007 13:38		0.501	3.869	8.934
6/28/2007 13:38		0.794	3.881	8.961
6/28/2007 13:38		1.002	3.868	8.931
6/28/2007 13:38		1.25	3.869	8.933
6/28/2007 13:38		1.5	3.869	8.934

6/28/2007 13:38	1.75	3.869	8.933	71.489
6/28/2007 13:38	2	3.868	8.931	71.486
6/28/2007 13:38	2.25	3.868	8.93	71.486
6/28/2007 13:38	2.5	3.869	8.932	71.485
6/28/2007 13:38	2.75	3.869	8.933	71.484
6/28/2007 13:38	3	3.868	8.932	71.481
6/28/2007 13:38	3.25	3.869	8.933	71.476
6/28/2007 13:38	3.5	3.867	8.93	71.472
6/28/2007 13:38	3.75	3.868	8.931	71.471
6/28/2007 13:38	4	3.868	8.931	71.468
6/28/2007 13:38	4.25	3.867	8.929	71.463
6/28/2007 13:38	4.5	3.868	8.931	71.461
6/28/2007 13:38	4.75	3.869	8.933	71.457
6/28/2007 13:38	5.176	3.868	8.931	71.425
6/28/2007 13:38	5.379	3.869	8.934	71.468
6/28/2007 13:38	5.712	3.867	8.93	71.424
6/28/2007 13:38	6.103	3.867	8.93	71.441
6/28/2007 13:38	6.306	3.867	8.93	71.438
6/28/2007 13:38	6.511	3.867	8.93	71.441
6/28/2007 13:38	6.716	3.868	8.931	71.441
6/28/2007 13:38	7.14	3.868	8.93	71.395
6/28/2007 13:38	7.56	3.867	8.928	71.379
6/28/2007 13:38	7.98	3.868	8.931	71.354
6/28/2007 13:38	8.46	3.867	8.93	71.329
6/28/2007 13:38	9	3.868	8.932	71.306
6/28/2007 13:38	9.48	3.867	8.928	71.292
6/28/2007 13:38	10.08	3.867	8.93	71.268
6/28/2007 13:38	10.68	3.868	8.931	71.24
6/28/2007 13:38	11.28	3.868	8.931	71.224
6/28/2007 13:38	11.94	3.868	8.931	71.208
6/28/2007 13:38	12.66	3.868	8.932	71.187
6/28/2007 13:38	13.44	3.867	8.93	71.164
6/28/2007 13:38	14.22	3.868	8.931	71.14
6/28/2007 13:38	15.06	3.868	8.931	71.112
6/28/2007 13:38	15.96	3.867	8.929	71.09
6/28/2007 13:38	16.92	3.868	8.931	71.093
6/28/2007 13:38	17.88	3.868	8.931	71.048
6/28/2007 13:38	18.96	3.869	8.933	71.014
6/28/2007 13:38	20.1	3.869	8.934	70.981
6/28/2007 13:38	21.3	3.868	8.931	70.949
6/28/2007 13:38	22.56	3.869	8.933	70.919
6/28/2007 13:38	23.88	3.869	8.932	70.879
6/28/2007 13:38	25.32	3.868	8.932	70.844
6/28/2007 13:38	26.82	3.868	8.931	70.837
6/28/2007 13:38	28.38	3.868	8.931	70.78
6/28/2007 13:38	30.06	3.868	8.931	70.738
6/28/2007 13:38	31.86	3.868	8.932	70.688
6/28/2007 13:38	33.72	3.868	8.931	70.644
6/28/2007 13:39	35.76	3.868	8.932	70.597
6/28/2007 13:39	37.86	3.868	8.931	70.564
6/28/2007 13:39	40.08	3.869	8.934	70.5
6/28/2007 13:39	42.48	3.869	8.933	70.454
6/28/2007 13:39	45	3.869	8.933	70.405
6/28/2007 13:39	47.64	3.868	8.932	70.355
6/28/2007 13:39	50.46	3.869	8.933	70.281
6/28/2007 13:39	53.46	3.868	8.93	70.217

6/28/2007 13:39	56.649	3.868	8.93	70.189
6/28/2007 13:39	60	3.868	8.931	70.115
6/28/2007 13:39	63.6	3.868	8.932	70.024
6/28/2007 13:39	67.199	3.868	8.931	69.952
6/28/2007 13:39	71.4	3.867	8.929	69.886
6/28/2007 13:39	75.6	3.867	8.929	69.794
6/28/2007 13:39	79.8	3.868	8.931	69.723
6/28/2007 13:39	84.6	3.867	8.929	69.641
6/28/2007 13:39	90.023	3.867	8.93	69.548
6/28/2007 13:40	94.8	3.868	8.932	69.481
6/28/2007 13:40	100.8	3.866	8.927	69.401
6/28/2007 13:40	106.8	3.872	8.94	69.288
6/28/2007 13:40	112.8	4.121	9.516	69.2
6/28/2007 13:40	119.4	4.081	9.423	69.106
6/28/2007 13:40	126.6	4.045	9.339	69.007
6/28/2007 13:40	134.399	4.026	9.296	68.896
6/28/2007 13:40	142.199	4.025	9.294	68.8
6/28/2007 13:40	150.6	4.016	9.273	68.714
6/28/2007 13:41	159.6	4.012	9.263	68.581
6/28/2007 13:41	169.2	4.009	9.257	68.473
6/28/2007 13:41	178.8	4.006	9.25	68.377
6/28/2007 13:41	189.599	4.004	9.245	68.264
6/28/2007 13:41	201	4	9.235	68.174
6/28/2007 13:41	213	3.997	9.229	68.07
6/28/2007 13:42	225.599	3.995	9.224	67.965
6/28/2007 13:42	238.8	3.992	9.218	67.871
6/28/2007 13:42	253.199	3.991	9.214	67.777
6/28/2007 13:42	268.2	3.987	9.205	67.676
6/28/2007 13:43	283.799	3.985	9.201	67.589
6/28/2007 13:43	300.599	3.982	9.195	67.522
6/28/2007 13:43	318.599	3.981	9.193	67.399
6/28/2007 13:44	337.2	3.977	9.182	67.309
6/28/2007 13:44	357.599	3.974	9.176	67.221
6/28/2007 13:44	378.599	3.971	9.168	67.149
6/28/2007 13:45	400.799	3.968	9.161	67.104
6/28/2007 13:45	424.799	3.964	9.153	67.006
6/28/2007 13:45	450.041	3.961	9.147	66.945
6/28/2007 13:46	476.399	3.958	9.14	66.885
6/28/2007 13:46	504.599	3.955	9.131	66.835
6/28/2007 13:47	534.599	3.95	9.121	66.78
6/28/2007 13:47	566.4	3.949	9.117	66.73
6/28/2007 13:48	600.1	3.944	9.107	66.685
6/28/2007 13:49	636	3.941	9.101	66.638
6/28/2007 13:49	672	3.939	9.095	66.603
6/28/2007 13:50	713.999	3.935	9.086	66.567
6/28/2007 13:51	756	3.932	9.078	66.533
6/28/2007 13:51	797.999	3.929	9.073	66.501
6/28/2007 13:52	845.999	3.936	9.087	66.462
6/28/2007 13:53	900.114	3.923	9.058	66.444
6/28/2007 13:54	948	3.921	9.053	66.421
6/28/2007 13:55	1008	3.918	9.045	66.391
6/28/2007 13:56	1068	3.915	9.039	66.36
6/28/2007 13:57	1128	3.913	9.035	66.328
6/28/2007 13:58	1193.999	3.91	9.028	66.311
6/28/2007 13:59	1265.999	3.907	9.021	66.287
6/28/2007 14:00	1343.999	3.905	9.016	66.259


6/28/2007 14:02	1421.999	3.734	8.621	66.241
6/28/2007 14:03	1505.999	3.755	8.669	66.177
6/28/2007 14:05	1596	3.767	8.699	66.116
6/28/2007 14:06	1691.999	3.778	8.723	66.095
6/28/2007 14:08	1788	3.787	8.743	66.057
6/28/2007 14:10	1896	3.795	8.762	66.038
6/28/2007 14:11	2010.024	3.803	8.78	66.022
6/28/2007 14:13	2130.032	3.808	8.793	66.003
6/28/2007 14:16	2256	3.814	8.808	65.987
6/28/2007 14:18	2388	3.82	8.821	65.96
6/28/2007 14:20	2531.999	3.825	8.833	65.944

Color Spectrum

LaFayette, GA June 28, 2007

Bouwer and Rice Graph

MW-9



Analysis by Starpoint Software

H_o is 0.131 feet at 63.6 Seconds

Report Date: 7/2/2007 11:52
Report User Name: amodi
Report Computer Name: EPS-DIM-2400

Log File Properties

File Name MW 9-[2] 2007-06-28 11.50.41.wsl
Create Date 6/28/2007 14:50

Device Properties

Device LevelTroll 700
Site color spectrum mw-4
Device Name MW4
Serial Number 114123
Firmware Version 2.04

Log Configuration

Log Name MW 9-[2]
Created By Unknown
Computer Name Pocket PC
Application WinSituMobile.exe
Application Version 5.1.0.11
Create Date 6/28/2007 14:41
Notes Size(bytes) 4096
Type True Logarithmic
Overwrite when full Disabled
Scheduled Start Manual Start
Scheduled Stop No Stop Time
Max Interval Days: 0 Hours: 00 Mins: 20 Secs: 00

Level Reference Settings At Log Creation

Level Measurement Mode Depth
Specific Gravity 0.999

Log Notes:

Date and Time Note
6/28/2007 14:42 Manual Start Command
6/28/2007 14:50 Suspend Command
6/28/2007 14:50 Manual Stop Command

Log Data:

Record Count 101

Date and Time	Elapsed Time Seconds	Sensor: Pres 15G SN#: 114123 Pressure (PSI)	Sensor: Pres 15G SN#: 114123 Depth (ft)	Sensor: Pres 15G SN#: 114123 Temperature (F)
6/28/2007 14:42	0	2.829	6.533	73.21
6/28/2007 14:42	0.25	2.829	6.533	73.245
6/28/2007 14:42	0.501	2.831	6.538	73.274
6/28/2007 14:42	0.966	2.841	6.56	73.269
6/28/2007 14:42	1.17	2.841	6.56	73.296
6/28/2007 14:42	1.374	2.829	6.531	73.31
6/28/2007 14:42	1.581	2.829	6.532	73.328

6/28/2007 14:42	1.785	2.829	6.532	73.342
6/28/2007 14:42	2	2.829	6.533	73.35
6/28/2007 14:42	2.25	2.829	6.532	73.346
6/28/2007 14:42	2.5	2.829	6.532	73.353
6/28/2007 14:42	2.75	2.829	6.532	73.35
6/28/2007 14:42	3	2.829	6.532	73.36
6/28/2007 14:42	3.25	2.829	6.532	73.363
6/28/2007 14:42	3.5	2.829	6.533	73.366
6/28/2007 14:42	3.75	2.83	6.533	73.372
6/28/2007 14:42	4	2.828	6.531	73.366
6/28/2007 14:42	4.25	2.829	6.531	73.377
6/28/2007 14:42	4.5	2.829	6.531	73.37
6/28/2007 14:42	4.75	2.828	6.53	73.378
6/28/2007 14:42	5	2.828	6.53	73.382
6/28/2007 14:42	5.389	2.829	6.532	73.366
6/28/2007 14:42	5.592	2.829	6.531	73.41
6/28/2007 14:42	5.925	2.829	6.531	73.38
6/28/2007 14:42	6.316	2.83	6.535	73.396
6/28/2007 14:42	6.521	2.829	6.532	73.403
6/28/2007 14:42	6.726	2.829	6.532	73.413
6/28/2007 14:42	7.14	2.828	6.529	73.375
6/28/2007 14:42	7.56	2.829	6.533	73.361
6/28/2007 14:42	7.98	2.829	6.531	73.356
6/28/2007 14:42	8.46	2.829	6.531	73.349
6/28/2007 14:42	9	2.828	6.53	73.331
6/28/2007 14:42	9.48	2.828	6.531	73.333
6/28/2007 14:42	10.08	2.829	6.532	73.325
6/28/2007 14:42	10.68	2.829	6.532	73.348
6/28/2007 14:42	11.28	2.828	6.531	73.324
6/28/2007 14:42	11.94	2.829	6.532	73.317
6/28/2007 14:42	12.66	2.83	6.535	73.306
6/28/2007 14:42	13.44	2.829	6.532	73.3
6/28/2007 14:42	14.22	2.829	6.531	73.295
6/28/2007 14:42	15.06	2.829	6.532	73.294
6/28/2007 14:42	15.96	2.829	6.531	73.288
6/28/2007 14:42	16.92	2.829	6.532	73.283
6/28/2007 14:42	17.88	2.828	6.531	73.285
6/28/2007 14:42	18.96	2.829	6.532	73.281
6/28/2007 14:42	20.1	2.83	6.533	73.275
6/28/2007 14:42	21.467	2.829	6.533	73.297
6/28/2007 14:42	22.56	2.829	6.533	73.279
6/28/2007 14:42	23.88	2.829	6.532	73.267
6/28/2007 14:42	25.32	2.829	6.532	73.264
6/28/2007 14:42	26.82	2.829	6.532	73.261
6/28/2007 14:42	28.38	2.83	6.534	73.257
6/28/2007 14:42	30.06	2.83	6.535	73.257
6/28/2007 14:42	31.86	2.829	6.533	73.279
6/28/2007 14:42	33.72	2.83	6.535	73.25
6/28/2007 14:42	35.76	2.83	6.535	73.247
6/28/2007 14:42	37.86	2.829	6.533	73.245
6/28/2007 14:42	40.08	2.83	6.535	73.243
6/28/2007 14:42	42.48	2.83	6.534	73.246
6/28/2007 14:42	45	2.83	6.535	73.241
6/28/2007 14:43	47.64	2.831	6.537	73.231
6/28/2007 14:43	50.46	2.835	6.545	73.235
6/28/2007 14:43	53.46	3.15	7.274	73.237
6/28/2007 14:43	56.64	2.908	6.715	73.227

6/28/2007 14:43	60	2.939	6.785	73.222
6/28/2007 14:43	63.6	2.886	6.664	73.228
6/28/2007 14:43	67.199	2.877	6.644	73.223
6/28/2007 14:43	71.472	2.867	6.62	73.249
6/28/2007 14:43	75.6	2.86	6.603	73.217
6/28/2007 14:43	79.8	2.856	6.595	73.212
6/28/2007 14:43	84.6	2.854	6.59	73.212
6/28/2007 14:43	90	2.852	6.586	73.21
6/28/2007 14:43	94.8	2.851	6.583	73.21
6/28/2007 14:43	100.99	2.851	6.583	73.204
6/28/2007 14:43	106.8	2.85	6.58	73.206
6/28/2007 14:44	112.8	2.85	6.581	73.217
6/28/2007 14:44	119.4	2.851	6.582	73.208
6/28/2007 14:44	126.6	2.85	6.58	73.209
6/28/2007 14:44	134.399	2.85	6.581	73.208
6/28/2007 14:44	142.199	2.851	6.582	73.218
6/28/2007 14:44	150.6	2.85	6.58	73.202
6/28/2007 14:44	159.6	2.85	6.58	73.198
6/28/2007 14:45	169.2	2.85	6.582	73.197
6/28/2007 14:45	178.8	2.851	6.582	73.189
6/28/2007 14:45	189.6	2.85	6.581	73.183
6/28/2007 14:45	201.045	2.85	6.581	73.185
6/28/2007 14:45	213	2.85	6.581	73.188
6/28/2007 14:45	225.599	2.85	6.581	73.174
6/28/2007 14:46	238.8	2.85	6.58	73.178
6/28/2007 14:46	253.199	2.85	6.58	73.186
6/28/2007 14:46	268.199	2.85	6.58	73.181
6/28/2007 14:46	283.799	2.85	6.58	73.196
6/28/2007 14:47	300.6	2.85	6.581	73.199
6/28/2007 14:47	318.599	2.849	6.579	73.206
6/28/2007 14:47	337.2	2.85	6.58	73.216
6/28/2007 14:48	357.6	2.85	6.579	73.217
6/28/2007 14:48	378.599	2.85	6.581	73.22
6/28/2007 14:48	400.98	2.85	6.581	73.26
6/28/2007 14:49	424.799	2.79	6.441	73.231
6/28/2007 14:49	450	2.846	6.571	73.225
6/28/2007 14:50	476.399	2.847	6.574	73.229

APPENDIX H

Risk Reduction Standards Calculations

Table I Georgia Specific Values

Parameter	CASText	NC (mg/kg)	Table 2 Soil (mg/kg)	Table 1 GW (mg/L)	GA MCL (mg/L)
1,1,1-Trichloroethane	71-55-6	5.44		0.2	0.2
1,1-Dichloroethane	75-34-3	0.03		4	
1,1-Dichloroethene	75-35-4	0.36		0.007	0.007
Acetone	67-64-1	2.74		4	
Arsenic	7440-38-2	41	20	0.01	0.01
Freon-113	76-13-1	6.92		1000	
Freon-12	75-71-8	1.49		1	
Isopropylbenzene	98-82-8	21.88			
Lead	7439-92-1	400	75	0.015	
Tetrachloroethene	127-18-4	0.18		0.005	0.005

HSRA: Hazardous Site Response Act's Hazardous Site Response Rules ("Rules")

NC: Notification Concentration - Appendix I of the Rules

Table 2 Soil: Appendix III Table 2 of the Rules

Table 1 GW: Appendix III Table 1 of the Rules

GA MCL: Georgia Maximum Contaminant Level (Rules for Safe Drinking Water)

Table II Toxicity Factors

Analyte	CAS	NonCancer Toxicity Values			Cancer Toxicity Values				VOC
		Oral RfD	Inhalation RFC	Inhalation RfD	Oral CSF	Inhalation Unit Risk	Inhalation CSF	Cancer Class	
		mg/kg-day	mg/m3	mg/kg-day	per mg/kg-day	per ug/m3	per mg/kg-day		
1,1,1-Trichloroethane	71-55-6	2	5	1.4					V
1,1-Dichloroethane	75-34-3	0.2			0.0057	0.0000016	0.0056	C	V
1,1-Dichloroethene	75-35-4	0.05	0.2	0.057					V
Acetone	67-64-1	0.9	31	8.9					V
Arsenic	7440-38-2	0.0003	0.000015	0.0000043	1.5	0.0043	15	A	
Freon-113	76-13-1	30	30	8.6					V
Freon-12	75-71-8	0.2	0.1	0.029					V
Isopropylbenzene	98-82-8	0.1	0.4	0.11					V
Lead	7439-92-1								
Tetrachloroethene	127-18-4	0.006	0.04	0.011	0.0021	2.6E-07	0.00091	B	V

Values are from the EPA Regional Screening Level Summary Table (May 2014), except where noted

IRIS: Integrated Risk Information System (www.epa.gov/IRIS/)

Table III Groundwater Risk Calculations

Analyte	CAS	Volatile?	Oral CSF per mg/kg- day	Inhalation CSF per mg/kg- day	RAGS Eqn. 1								
					Adult			Child			Worker		
					Ingestion	Inhalation	Total	Ingestion	Inhalation	Total	Ingestion	Inhalation	Total
					mg/L	mg/L	mg/L	mg/L	mg/L	mg/L	mg/L	mg/L	mg/L
1,1,1-Trichloroethane	71-55-6	V											
1,1-Dichloroethane	75-34-3	V	0.0057	0.0056	0.15	0.041	0.032	0.32	0.043	0.038	0.50	0.051	0.046
1,1-Dichloroethene	75-35-4	V											
Acetone	67-64-1	V											
Arsenic	7440-38-2		1.5	15	0.00057		0.00057	0.0012		0.0012	0.0019		0.0019
Freon-113	76-13-1	V											
Freon-12	75-71-8	V											
Isopropylbenzene	98-82-8	V											
Lead	7439-92-1												
Tetrachloroethene	127-18-4	V	0.0021	0.00091	0.41	0.25	0.15	0.87	0.27	0.20	1.4	0.31	0.26

$$\text{Ingestion/Oral C (mg/kg)} = \frac{\text{TR} \times \text{BW} \times \text{AT}}{\text{EF} \times \text{ED} \times (\text{SfO} \times \text{IRw})}$$

$$\text{Inhalation C (mg/kg)} = \frac{\text{TR} \times \text{BW} \times \text{AT}}{\text{EF} \times \text{ED} \times (\text{SFi} \times \text{K} \times \text{IRa})}$$

Note: Inhalation pathway not calculated if not volatile

$$\text{RAGS Eqn 1} = \frac{\text{TR} \times \text{BW} \times \text{AT}}{\text{EF} \times \text{ED} \times [(\text{SfO} \times \text{IRw}) + (\text{SFi} \times \text{K} \times \text{IRa})]}$$

Parameter			Adult		Child		Worker	
			Value	Source	Value	Source	Value	Source
Body Weight, Adult (kg)	BW		70	1	15	2	70	1
Exposure Frequency, Resident Adult (d/yr)	EF		350	1	350	1	250	1
Exposure Duration, Resident Adult (yr)	ED		30	1	6	2	25	1
Soil Ingestion, Resident Adult (mg/d)	IRs		114	1	200	2	50	1
Water ingestion, Resident Adult (L/d)	IRw		2	1	1	1	1	1
Inhalation Rate, Resident Adult (m ³ /d)	IRa		15	1	15	2	20	1
Averaging Time, Cancer, Adult (d)	AT		25550	1	25550	1	25550	1
Target Risk	TR		1E-05	1	1E-05	1	1E-05	1
Water-to-air volatilization factor (L/m3)	K		0.5	1	0.5	1	0.5	1
Particulate Emission Factor (m3/kg)	PEF		4630000000	1	4630000000	1	4630000000	1

Notes:

Source 1 - GaEPD Reg 391-3-19 Appendix III, Table 3

Source 2 - HSRA Guidance <http://www.georgiaepd.org/Documents/hsraguideCSRRTS.html>

Table IV Groundwater Hazard Calculations

Analyte	CAS	Volatile?	Oral RfD	Inhalation RfD	RAGS Eqn. 2								
					Adult			Child			Worker		
					Ingestion	Inhalation	Total	Ingestion	Inhalation	Total	Ingestion	Inhalation	Total
					mg/L	mg/L	mg/L	mg/L	mg/L	mg/L	mg/L	mg/L	mg/L
1,1,1-Trichloroethane	71-55-6	V	2	1.4	73	14	12	31	3.0	2.7	204	15	14
1,1-Dichloroethane	75-34-3	V	0.2		7.3		7.3	3.1		3.1	20		20
1,1-Dichloroethene	75-35-4	V	0.05	0.057	1.8	0.56	0.43	0.78	0.12	0.10	5.1	0.58	0.52
Acetone	67-64-1	V	0.9	8.9	33	86	24	14	18	8.0	92	91	46
Arsenic	7440-38-2		0.0003	4.29E-06	0.011		0.011	0.0047		0.0047	0.031		0.031
Freon-113	76-13-1	V	30	8.6	1095	83	78	469	18	17	3066	88	85
Freon-12	75-71-8	V	0.2	0.029	7.3	0.28	0.27	3.1	0.060	0.058	20	0.29	0.29
Isopropylbenzene	98-82-8	V	0.1	0.11	3.7	1.1	0.85	1.6	0.24	0.21	10	1.2	1.0
Lead	7439-92-1												
Tetrachloroethene	127-18-4	V	0.006	0.011	0.22	0.11	0.074	0.094	0.024	0.019	0.61	0.12	0.098

Lead GSL based on Appendix III concentration

$$\text{Ingestion/Oral C (mg/kg)} = \frac{\text{THI} \times \text{BW} \times \text{AT}}{\text{EF} \times \text{ED} \times (1/\text{RfDo} \times \text{IRw})}$$

$$\text{Inhalation C (mg/kg)} = \frac{\text{THI} \times \text{BW} \times \text{AT}}{\text{EF} \times \text{ED} \times (1/\text{RfDi} \times \text{K} \times \text{IRa})}$$

Note: Inhalation pathway not calculated if not volatile

$$\text{RAGS Eqn 2} = \frac{\text{THI} \times \text{BW} \times \text{AT}}{\text{EF} \times \text{ED} \times [(1/\text{RfDo} \times \text{IRw}) + (1/\text{RfDi} \times \text{K} \times \text{IRa})]}$$

Parameter		Adult		Child		Worker	
		Value	Source	Value	Source	Value	Source
Body Weight, Adult (kg)	BW	70	1	15	2	70	1
Exposure Frequency, Resident Adult (d/yr)	EF	350	1	350	1	250	1
Exposure Duration, Resident Adult (yr)	ED	30	1	6	2	25	1
Soil Ingestion, Resident Adult (mg/d)	IRs	114	1	200	2	50	1
Water ingestion, Resident Adult (L/d)	IRw	2	1	1	1	1	1
Inhalation Rate, Resident Adult (m ³ /d)	IRa	15	1	15	2	20	1
Averaging Time, Noncancer, Adult (d)	AT	10950	1	2190	1	9125	1
Target hazard quotient	THQ	1	1	1	1	1	1
Water-to-air volatilization factor (L/m ³)	K	0.5	1	0.5	1	0.5	1
Particulate Emission Factor (m ³ /kg)	PEF	4630000000	1	4630000000	1	4630000000	1

Exposure Duration x 365 days

Notes:

Source 1 - GaEPD Reg 391-3-19 Appendix III, Table 3

Source 2 - HSRA Guidance <http://www.georgiaepd.org/Documents/hsraguideCSRRTS.html>

Table V Groundwater Residential Risk Reduction Standards

Analyte	CAS	TYPE 1 GW RRS				TYPE 2 GW RRS								Residential GW RRS - higher of Type 1 and 2 mg/L
		Rule 391-3-19-.07(6)(b) and Guidance: The lesser of Table 1 App III and GA MCL (or where NA, the higher of DL or Bkg)				Rule 391-3-19-.07(7)(b): The lesser of Items 1 and 2 (or where NA, the higher of Table 1 App III, background or DL)								
						Item 1: RAGS Eqn 2 (NC)		Item 2: RAGS Eqn 1 (C)		Lesser of Items 1 and 2	Alternate, if NA		Type 2 GW RRS mg/L	
Table 1, App III mg/L	GA MCL mg/L	Bkg* mg/L	Type 1 GW RRS mg/L	Adult mg/L	Child mg/L	Adult mg/L	Child mg/L	Table 1, App III mg/L	Bkg* mg/L					
1,1,1-Trichloroethane	71-55-6	0.2	0.2		0.2	12	2.7			2.7	0.2		2.7	2.7
1,1-Dichloroethane	75-34-3	4			4	7.3	3.1	0.032	0.038	0.032	4		0.032	4
1,1-Dichloroethene	75-35-4	0.007	0.007		0.007	0.43	0.10			0.10	0.007		0.10	0.10
Acetone	67-64-1	4			4	24	8.0			8.0	4		8.0	8.0
Arsenic	7440-38-2	0.01	0.01		0.01	0.011	0.0047	0.00057	0.00122	0.00057	0.01		0.00057	0.01
Freon-113	76-13-1	1000			1000	78	17			17	1000		17	1000
Freon-12	75-71-8	1			1	0.27	0.058			0.058	1		0.058	1
Isopropylbenzene	98-82-8				0.005 *	0.85	0.21			0.21			0.21	0.21
Lead	7439-92-1	0.015			0.015						0.015		0.015	0.015
Tetrachloroethene	127-18-4	0.005	0.005		0.005	0.074	0.019	0.15	0.20	0.019	0.005		0.019	0.019

* Method detection limit

Table VI Groundwater Industrial Risk Reduction Standards

Analyte	CAS	TYPE 3 GW RRS	TYPE 4 GW RRS				
		Rule 391-3-19-.07(8)(c) Same as Type 1 GW RRS mg/L	Rule 391-3-19-.07(9)(c): The lesser of Items 1 and 2 (or where NA, the higher of Table 1 App III, background and DL)				
			Item 1 RAGS Eqn 2 (NC) mg/L	Item 2 RAGS Eqn 1 (C) mg/L	Lesser of Items 1 and 2 mg/L	Alternate Table 1 App III mg/L	Type 4 GW RRS mg/L
1,1-Dichloroethene	75-35-4	0.007	0.52		0.52	0.007	0.52
Tetrachloroethene	127-18-4	0.005	0.098	0.26	0.098	0.005	0.098

Non-Residential RRS - higher of Type 3 and 4 mg/L
0.52
0.098

Table VII Summary of Risk Reduction Standards

Analyte	CAS	Maximum Detected Concentration On-Site µg/L	Groundwater					
			Type 1 RRS µg/L	Type 2 RRS µg/L	Residential RRS µg/L	Type 3 RRS µg/L	Type 4 RRS µg/L	Non- Residential RRS µg/L
1,1,1-Trichloroethane	71-55-6	2,100	200	2,720	2,720			
1,1-Dichloroethane	75-34-3	280	4,000	32	4,000			
1,1-Dichloroethene	75-35-4	290	7	103	103	7	524	524
Acetone	67-64-1	140	4,000	7,990	7,990			
Arsenic	7440-38-2	ND	10	0.57	10			
Freon-113	76-13-1	27,000	1,000,000	17,221	1,000,000			
Freon-12	75-71-8	680	1,000	58	1,000			
Isopropylbenzene	98-82-8	46	5	207	207			
Lead	7439-92-1	15.6*	15	15	15			
Tetrachloroethene	127-18-4	350	5.0	19	19	5.0	98	98

* This detection was in 2009 when the well could not be fully developed due to slow recharge, represents a highly turbid sample, and is not considered valid. Lead was not detected in a filtered sample in 2009 nor was it detected in an unfiltered sample in 2013.

Bold - exceeds Residential or Non-Residential RRS

APPENDIX I

Wildlife Resources Division Letter

Georgia Department of Natural Resources
Wildlife Resources Division

Nongame Conservation Section
2065 U.S. Highway 278, S.E., Social Circle, Georgia 30025-4743
(770) 918 6411

December 6, 2007

Justin Vickery, Senior Geologist
EPS
900 Ashwood Parkway
Atlanta, GA 30338

**Subject: Known Occurrences of Conservation Areas and Special Concern Animals
and Plants On or Near EPD Hazardous Site Compliance Status Report, T&E
Species Review, Walker County, Georgia**

Dear Mr. Vickery:

This is in response to your request of November 27, 2007. According to our records, within a three-mile radius of the project site there are the following Natural Heritage Database occurrences:

Aesculus glabra (Ohio Buckeye) approx. 2.5 mi. W of site
GA *Aneides aeneus* (Green Salamander) approx. 3.0 mi. W of site
Carya laciniosa (Shellbark Hickory) approx. 3.0 mi. W of site
GA *Crataegus triflora* (Three-flowered Hawthorn) approx. 3.0 mi. W of site
Etheostoma coosae (Coosa Darter) approx. 1.0 mi. SE of site in Town Creek
Etheostoma coosae (Coosa Darter) approx. 2.5 mi. N of site in Dry Creek
Etheostoma coosae (Coosa Darter) approx. 2.5 mi. W of site in Duck Creek
Fraxinus quadrangulata (Blue Ash) approx. 3.0 mi. W of site
GA *Jeffersonia diphylla* (Twinleaf) approx. 3.0 mi. W of site
GA *Neviusia alabamensis* (Alabama Snow-wreath) approx. 3.0 mi. W of site
Phacelia purshii (Miami-mist) approx. 2.5 mi. W of site
Ponthieva racemosa (Shadow-witch Orchid) approx. 3.0 mi. W of site
Potamogeton amplifolius (Bigleaf Pondweed) approx. 1.0 mi. N of site
Blue Hole [Cave] approx. 3.0 mi. W of site
Chattooga River [High Priority Stream] approx. 1.0 mi. SE of site
Crockford-Pigeon Mountain WMA [GA DNR] approx. 2.5 mi. W of site
Duck Creek [High Priority Stream] approx. 2.0 mi. SW of site
Wayne's Dudhole [Cave] approx. 3.0 mi. W of site

* Entries above preceded by "US" indicates species with federal status in Georgia (Protected or Candidate). Species that are federally protected in Georgia are also state protected; "GA" indicates Georgia protected species.

Recommendations:

We have no records of species of concern within the project area. Please encourage strict measures to protect the important aquatic resources near this site. This site occurs near Duck

Creek and the Chattooga River, both high priority streams. As part of an effort to develop a comprehensive wildlife conservation strategy for the state of Georgia, the Wildlife Resources division has developed and mapped a list of streams that are important to the protection or restoration of rare aquatic species and aquatic communities. High priority waters and their surrounding watersheds are a high priority for a broad array of conservation activities, but do not receive any additional legal protections. We now have GIS ESRI shapefiles of GA high priority waters available on our website (<http://www.georgiawildlife.com/content/displaycontent.asp?txtDocument=89&txtPage=13>). Please contact the Georgia Natural Heritage Program if you would like additional information on high priority waters.

New Data Available on the Nongame Conservation Section Website

We have recently updated the Nongame Conservation Section Website!!! You can view the updated rare species and natural community information by Quarter Quad, County and HUC8 Watershed. To access this information, please visit our GA Rare Species and Natural Community Information page at:

<http://georgiawildlife.dnr.state.ga.us/content/displaycontent.asp?txtDocument=89>

An updated ESRI shape file of our rare species and natural community data by quarter quad and county is also available. It can be downloaded from:


<http://georgiawildlife.dnr.state.ga.us/assets/documents/gnhp/gnhpds.zip>

Disclaimer:

Please keep in mind the limitations of our database. The data collected by the Nongame Conservation Section comes from a variety of sources, including museum and herbarium records, literature, and reports from individuals and organizations, as well as field surveys by our staff biologists. In most cases the information is not the result of a recent on-site survey by our staff. Many areas of Georgia have never been surveyed thoroughly. Therefore, the Nongame Conservation Section can only occasionally provide definitive information on the presence or absence of rare species on a given site. Our files are updated constantly as new information is received. **Thus, information provided by our program represents the existing data in our files at the time of the request and should not be considered a final statement on the species or area under consideration.**

If you know of populations of special concern species that are not in our database, please fill out the appropriate data collection form and send it to our office. Forms can be obtained through our web site (<http://www.georgiawildlife.com>) or by contacting our office. If I can be of further assistance, please let me know.

Sincerely,






Katrina Morris
Environmental Review Coordinator

APPENDIX J





Vapor Intrusion Model

PROJECT: Syntec Industries, Inc.		Log of Boring No. MW-1	
SITE LOCATION: La Fayette, GA		TOP OF CASING ELEVATION (ft): N/A	
DRILLING CONTRACTOR: Atlas Geo-Sampling		DATE STARTED: 6/20/06	DATE FINISHED: 6/20/06
DRILLING METHOD: Direct Push		TOTAL DEPTH (ft.): 12	SCREEN INTERVAL (ft.): 2-12
DRILLING EQUIPMENT: AMS Power Probe		DEPTH TO WATER AT TIME OF BORING (ft.):	CASING (ft.): 0-2
SAMPLING METHOD: Macrocore w/ Acetate Liner		BOREHOLE DIAMETER (In.): 7.25	WELL DIAMETER (In.): 2
LOGGED BY: K. Moore			

DEPTH (feet)	SAMPLES		PID Reading	DESCRIPTION		WELL CONSTRUCTION DETAILS AND/OR DRILLING REMARKS
	Sample No.	Location				
				Top of Casing Elevation (ft): N/A		
0						 Terminated at 12 ft-bls.
5			0.2	Tan orange sandy clay crumbles easily (fill)		
				Tan orange sandy clay (fill) some petroleum odor at 7 ft at transition		
10			6.2			
			2	Gray brown clayey coarse grain sand - saprolite		
15						
20						
25						
30						
35						
40						
45						
50						




PROJECT: Syntec Industries, Inc.		Log of Boring No. MW-2	
SITE LOCATION: La Fayette, GA		TOP OF CASING ELEVATION (ft): N/A	
DRILLING CONTRACTOR: Atlas Geo-Sampling		DATE STARTED: 6/20/06	DATE FINISHED: 6/20/06
DRILLING METHOD: Direct Push		TOTAL DEPTH (ft.): 12	SCREEN INTERVAL (ft.): 2-12
DRILLING EQUIPMENT: AMS Power Probe		DEPTH TO WATER AT TIME OF BORING (ft.):	CASING (ft.): 0-2
SAMPLING METHOD: Macrocore w/ Acetate Liner		BOREHOLE DIAMETER (In.): 7.25	WELL DIAMETER (In.): 2
LOGGED BY: K. Moore			

DEPTH (feet)	SAMPLES			PID Reading	DESCRIPTION			WELL CONSTRUCTION DETAILS AND/OR DRILLING REMARKS	
	Sample No.	Location	Blows/ Foot		Top of Casing Elevation (ft): N/A				
0				0		Tan orange sandy clay (fill)		Terminated at 12 ft-bls.	
5				0.5		Tan orange sandy clay (fill) transition to native at 7 ft.			
10				5.5		Tan gray clayey coarse grain sand with some foliation - saprolite			
15									
20									
25									
30									
35									
40									
45									
50									









PROJECT: Syntec Industries, Inc.		Log of Boring No. MW-3	
SITE LOCATION: La Fayette, GA		TOP OF CASING ELEVATION (ft): N/A	
DRILLING CONTRACTOR: Atlas Geo-Sampling		DATE STARTED: 6/20/06	DATE FINISHED: 6/20/06
DRILLING METHOD: Direct Push		TOTAL DEPTH (ft.): 15	SCREEN INTERVAL (ft.): 2-15
DRILLING EQUIPMENT: AMS Power Probe		DEPTH TO WATER AT TIME OF BORING (ft.):	CASING (ft.): 0-2
SAMPLING METHOD: Macrocore w/ Acetate Liner		BOREHOLE DIAMETER (In.): 7.25	WELL DIAMETER (In.): 2
LOGGED BY: K. Moore			

DEPTH (feet)	SAMPLES			PID Reading	DESCRIPTION			WELL CONSTRUCTION DETAILS AND/OR DRILLING REMARKS	
	Sample No.	Location	Blows/ Foot		Top of Casing Elevation (ft): N/A				
0						Gray brown clayey medium grain sand			Terminated at 15 ft-bls.
0.5						Gray brown clayey medium grain sand (moist)			
0.2						Tan gray clayey course grain quartz sands - saprolite			
0.1						Gray brown clayey course grain sand - saprolite			
0									
15									
20									
25									
30									
35									
40									
45									
50									



PROJECT: Syntec Industries, Inc.		Log of Boring No. MW-4	
SITE LOCATION: La Fayette, GA		TOP OF CASING ELEVATION (ft): 795.43	
DRILLING CONTRACTOR: Atlas Geo-Sampling		DATE STARTED: 6/21/07	DATE FINISHED: 6/21/07
DRILLING METHOD: Direct Push and HSA		TOTAL DEPTH (ft.): 16	SCREEN INTERVAL (ft.): 6-16
DRILLING EQUIPMENT: GeoProbe		DEPTH TO WATER AT TIME OF BORING (ft.): 4.48	CASING (ft.): 0-6
SAMPLING METHOD: Macrocore Acetate Liner		BOREHOLE DIAMETER (In.): 7.25	WELL DIAMETER (In.): 2
LOGGED BY: N/A G. Henry			

DEPTH (feet)	SAMPLES		PID Reading	DESCRIPTION		WELL CONSTRUCTION DETAILS AND/OR DRILLING REMARKS
	Sample No.	Location				
				Top of Casing Elevation (ft): 795.43		
0						Terminated at 16 ft-bls.
				Dark brown clayey sand with gravel		
						
				Black weathered rock		
5						
				Tan clay with some gravel (wet)		
10						
				Tan weathered rock with come clay (wet)		
						
15				Tan clay with rock		
20						
25						
30						
35						
40						
45						
50						










PROJECT: Syntec Industries, Inc.		Log of Boring No. MW-5	
SITE LOCATION: La Fayette, GA		TOP OF CASING ELEVATION (ft): 797.19	
DRILLING CONTRACTOR: Atlas Geo-Sampling		DATE STARTED: 6/21/07	DATE FINISHED: 6/21/07
DRILLING METHOD: Hollow Stem Auger		TOTAL DEPTH (ft.): 13	SCREEN INTERVAL (ft.): 3-13
DRILLING EQUIPMENT: Deitrich		DEPTH TO WATER AT TIME OF BORING (ft.): 5.1	CASING (ft.): 0-3
SAMPLING METHOD: Split Spoon		BOREHOLE DIAMETER (In.): 7.25	WELL DIAMETER (In.): 2
LOGGED BY: N/A G. Henry			

DEPTH (feet)	SAMPLES		PID Reading	DESCRIPTION		WELL CONSTRUCTION DETAILS AND/OR DRILLING REMARKS
	Sample No.	Location				
				Top of Casing Elevation (ft): 797.19		
0				Gravel		
				Red clay with gravel		
				Dark brown clay with some rock gravel and black deposits		
5				Black clay with some weathered rock		
				Red clay with interbedded grey clay and some gravel		
				Dark red clay with some black clay deposits		
10				Orange-red clay with rock gravel and sands		
15						
20						
25						
30						
35						
40						
45						
50						




Terminated at 13ft-bls.

PROJECT: Syntec Industries, Inc.		Log of Boring No. MW-6	
SITE LOCATION: La Fayette, GA		TOP OF CASING ELEVATION (ft): 796.62	
DRILLING CONTRACTOR: Atlas Geo-Sampling		DATE STARTED: 6/21/07	DATE FINISHED: 6/21/07
DRILLING METHOD: Hollow Stem Auger		TOTAL DEPTH (ft.): 13	SCREEN INTERVAL (ft.): 3-13
DRILLING EQUIPMENT: Deitrich		DEPTH TO WATER AT TIME OF BORING (ft.): 4.45	CASING (ft.): 0-3
SAMPLING METHOD: Split Spoon		BOREHOLE DIAMETER (In.): 7.25	WELL DIAMETER (In.): 2
LOGGED BY: N/A G. Henry			


DEPTH (feet)	SAMPLES		PID Reading	DESCRIPTION		WELL CONSTRUCTION DETAILS AND/OR DRILLING REMARKS
	Sample No.	Location				
				Top of Casing Elevation (ft): 796.62		
0				Gravel		Terminated at 13ft-bls.
				Red-orange clay with some rock and silts		
				Brown-black clay with some rock and silts		
				Black clay and silt with some rock gravel		
5				Brown-tan clay with some grey clay and gravel		
				Tan clay with some black sands and gravel		
10				Tan-gray clay with some gravel and black striations		
				Orange clay with some gray clay deposits and gravel		
				Green-gray clay		
15						
20						
25						
30						
35						
40						
45						
50						

PROJECT: Syntec Industries, Inc.		Log of Boring No. MW-7	
SITE LOCATION: La Fayette, GA		TOP OF CASING ELEVATION (ft): 797.52	
DRILLING CONTRACTOR: Atlas Geo-Sampling		DATE STARTED: 6/26/07	DATE FINISHED: 6/26/07
DRILLING METHOD: Direct Push and HSA		TOTAL DEPTH (ft.): 13.5	SCREEN INTERVAL (ft.): 3.5-13.5
DRILLING EQUIPMENT: GeoProbe		DEPTH TO WATER AT TIME OF BORING (ft.): 3.69	CASING (ft.): 0-3.5
SAMPLING METHOD: Macrocore Acetate Liner		BOREHOLE DIAMETER (In.): 7.25	WELL DIAMETER (In.): 2
LOGGED BY: N/A G. Henry			

DEPTH (feet)	SAMPLES		PID Reading	DESCRIPTION		WELL CONSTRUCTION DETAILS AND/OR DRILLING REMARKS
	Sample No.	Location				
				Top of Casing Elevation (ft): 797.52		
0				Rock gravel		Terminated at 13.5ft-bls.
				Red clay with gravel		
5						
				Red clay with rock layers (wet)		
10						
15						
20						
25						
30						
35						
40						
45						
50						




PROJECT: Syntec Industries, Inc.		Log of Boring No. MW-8	
SITE LOCATION: La Fayette, GA		TOP OF CASING ELEVATION (ft): 801.96	
DRILLING CONTRACTOR: Atlas Geo-Sampling		DATE STARTED: 6/22/07	DATE FINISHED: 6/22/07
DRILLING METHOD: Direct Push and HSA		TOTAL DEPTH (ft.): 14	SCREEN INTERVAL (ft.): 4-14
DRILLING EQUIPMENT: GeoProbe		DEPTH TO WATER AT TIME OF BORING (ft.): 12.17	CASING (ft.): 0-4
SAMPLING METHOD: Macrocore Acetate Liner		BOREHOLE DIAMETER (In.): 7.25	WELL DIAMETER (In.): 2
LOGGED BY: N/A G. Henry			

DEPTH (feet)	SAMPLES		PID Reading	DESCRIPTION		WELL CONSTRUCTION DETAILS AND/OR DRILLING REMARKS
	Sample No.	Location				
				Top of Casing Elevation (ft): 801.96		
0				Concrete		
5				Red clay with gravel		
10				Grey-brown clay with some rock		
15						Terminated at 14ft-bls.
20						
25						
30						
35						
40						
45						
50						



PROJECT: Syntec Industries, Inc.		Log of Boring No. MW-9	
SITE LOCATION: La Fayette, GA		TOP OF CASING ELEVATION (ft): 801.93	
DRILLING CONTRACTOR: Atlas Geo-Sampling		DATE STARTED: 6/22/07	DATE FINISHED: 6/22/07
DRILLING METHOD: Direct Push and HSA		TOTAL DEPTH (ft.): 14	SCREEN INTERVAL (ft.): 4-14
DRILLING EQUIPMENT: GeoProbe		DEPTH TO WATER AT TIME OF BORING (ft.): 7.45	CASING (ft.): 0-4
SAMPLING METHOD: Macrocore Acetate Liner		BOREHOLE DIAMETER (In.): 7.25	WELL DIAMETER (In.): 2
LOGGED BY: N/A G. Henry			

DEPTH (feet)	SAMPLES		PID Reading	DESCRIPTION		WELL CONSTRUCTION DETAILS AND/OR DRILLING REMARKS
	Sample No.	Location				
				Top of Casing Elevation (ft): 801.93		
0				Concrete		Terminated at 14ft-bls.
				Red clay with gravel		
5				Red-brown clay with gravel		
				Rock layer		
10				Gray-brown clay with some rock		
15						
20						
25						
30						
35						
40						
45						
50						




PROJECT:	Color Spectrum	Log of Boring No. MW-11	
SITE LOCATION:	LaFayette, GA	TOP OF CASING ELEVATION (ft): N/A	
DRILLING CONTRACTOR:	Atlas Geo-Sampling	DATE STARTED: 10/6/09	DATE FINISHED: 10/6/09
DRILLING METHOD:	Hollow Stem Auger	TOTAL DEPTH (ft.): 20	SCREEN INTERVAL (ft.): 17.5-20
DRILLING EQUIPMENT:	AMS Power Probe	DEPTH TO WATER AT TIME OF BORING (ft.): 14.21	CASING (ft.): 17.5
SAMPLING METHOD:	None	BOREHOLE DIAMETER (In.): 7.25	WELL DIAMETER (In.): 2
LOGGED BY:	R. Jones		

DEPTH (feet)	SAMPLES			PID Reading	DESCRIPTION		WELL CONSTRUCTION DETAILS AND/OR DRILLING REMARKS
	Sample No.	Location	Blows/ Foot				
0							
5							
10					No soils collected		
15							
20							Boring terminated at 20-ft below land surface. Installed well using 2-inch screen. Gauged and collected groundwater sample on 10/7/09.




PROJECT:	Color Spectrum	Log of Boring No. MW-12
SITE LOCATION:	LaFayette, GA	TOP OF CASING ELEVATION (ft): 795.29
DRILLING CONTRACTOR:	Geo Lab	DATE STARTED: 3/6/2013 DATE FINISHED: 3/6/2013
DRILLING METHOD:	Hollow Stem Auger	TOTAL DEPTH (ft.): 13 SCREEN INTERVAL (ft.): 3-13
DRILLING EQUIPMENT:	Geoprobe	DEPTH TO WATER AT TIME OF BORING (ft.): N/A CASING (ft.): 0-3
SAMPLING METHOD:	N/A	BOREHOLE DIAMETER (In.): 7.25 WELL DIAMETER (In.): 2

LOGGED BY: B. Crowe

DEPTH (feet)	SAMPLES			PID Reading	DESCRIPTION			WELL CONSTRUCTION DETAILS AND/OR DRILLING REMARKS	
	Sample No.	Location	Blows/ Foot						
					Ground Surface Elevation (ft): N/A				
0									Flush mounted vault set in concrete Grout 1-1.5 Bentonite 1.5-2.5 ft-bls
5									
10									Filter Sand 2.5-13 ft-bls.
15									
20									Boring terminated at 13 ft-bls.






PROJECT: <div>Color Spectrum</div>		Log of Boring No. MW-13	
SITE LOCATION: LaFayette, GA		TOP OF CASING ELEVATION (ft): 796.24	
DRILLING CONTRACTOR: Geo Lab		DATE STARTED: 3/6/2013	DATE FINISHED: 3/6/2013
DRILLING METHOD: Hollow Stem Auger		TOTAL DEPTH (ft.): 13	SCREEN INTERVAL (ft.): 3-13
DRILLING EQUIPMENT: Geoprobe		DEPTH TO WATER AT TIME OF BORING (ft.): N/A	CASING (ft.): 0-3
SAMPLING METHOD: N/A		BOREHOLE DIAMETER (In.): 7.25	WELL DIAMETER (In.): 2

LOGGED BY: B. Crowe

DEPTH (feet)	SAMPLES			PID Reading	DESCRIPTION			WELL CONSTRUCTION DETAILS AND/OR DRILLING REMARKS	
	Sample No.	Location	Blows/ Foot		Ground Surface Elevation (ft):				
					N/A				
0									Flush mounted vault set in concrete Grout 1-1.5 Bentonite 1.5-2.5 ft-bls
5									
10									Filter Sand 2.5-13 ft-bls.
15									
20									Boring terminated at 13 ft-bls.

PROJECT: Syntec Industries, Inc.		Log of Boring No. MW-14	
SITE LOCATION: La Fayette, GA		TOP OF CASING ELEVATION (ft): N/A	
DRILLING CONTRACTOR: N/A		DATE STARTED: 8/6/2014	DATE FINISHED: 8/6/2014
DRILLING METHOD: Hand Auger		TOTAL DEPTH (ft.): 8	SCREEN INTERVAL (ft.): 3-8
DRILLING EQUIPMENT: Hand Auger		DEPTH TO WATER AT TIME OF BORING (ft.): 2.5	CASING (ft.): 0-3
SAMPLING METHOD: N/A		BOREHOLE DIAMETER (In.): 4	WELL DIAMETER (In.): 2






LOGGED BY: Ben Crowe / Alex Testoff

DEPTH (feet)	SAMPLES			PID Reading	DESCRIPTION			WELL CONSTRUCTION DETAILS AND/OR DRILLING REMARKS	
	Sample No.	Location	Blows/ Foot		Top of Casing Elevation (ft): N/A				
0						sand and roots		Grout Bentonite Filter Sand Terminated at 8 ft-bls.	
					clayey sand				
5					sandy gravel				
					clay				
10									
15									
20									
25									
30									
35									
40									
45									
50									

PROJECT: Syntec Industries, Inc.		Log of Boring No. DW-1	
SITE LOCATION: La Fayette, GA		TOP OF CASING ELEVATION (ft): N/A	
DRILLING CONTRACTOR: ESN Southeast		DATE STARTED: 6/21/07	DATE FINISHED: 6/22/07
DRILLING METHOD: Hollow Stem Auger		TOTAL DEPTH (ft.): 46	SCREEN INTERVAL (ft.): 36-46
DRILLING EQUIPMENT: Deitrich		DEPTH TO WATER AT TIME OF BORING (ft.):	CASING (ft.): 0-36
SAMPLING METHOD: N/A		BOREHOLE DIAMETER (In.):	WELL DIAMETER (In.):
LOGGED BY: N/A G. Henry			

DEPTH (feet)	SAMPLES		PID Reading	DESCRIPTION		WELL CONSTRUCTION DETAILS AND/OR DRILLING REMARKS
	Sample No.	Location				
				Top of Casing Elevation (ft): N/A		
0				Gravel		Bore hole dia: 10.25 in Well dia: 4 in
				Red clay and gravel		
5				Brown to dark grey clay with silt		
10				Brown-tan clay with silt		
15				Brown clay		
20				Bedrock with some fractures and unconsolidated materials		Outer Casing installed from 0 to 20ft-bl. Bore hole dia: 4 in Well dia: 2 in
25						
30						
35						
40						
45						Refusal encountered at 50ft-bl. Cave in occurred from 45.5 to 50ft-bl.
50						



PROJECT: Color Spectrum		Log of Boring No. TW-1	
SITE LOCATION: 15 Probasco Street, LaFayette, GA		TOP OF CASING ELEVATION (ft): 794.73	
DRILLING CONTRACTOR: Atlas Geo-Sampling		DATE STARTED: 6/21/2007	DATE FINISHED: 6/21/2007
DRILLING METHOD: Direct Push and HSA		TOTAL DEPTH (ft.): 16	SCREEN INTERVAL (ft.): 5.5-15.5
DRILLING EQUIPMENT: AMS Power Probe		DEPTH TO WATER AT TIME OF BORING (ft.): 3.81	CASING (ft.): 0-5.5
SAMPLING METHOD: Macrocore with Acetate Liner		BOREHOLE DIAMETER (In.): 3.5	WELL DIAMETER (In.): 1
LOGGED BY: G.Henry			

DEPTH (feet)	SAMPLES			PID Reading	DESCRIPTION			WELL CONSTRUCTION DETAILS AND/OR DRILLING REMARKS	
	Sample No.	Location	Blows/ Foot		Top of Casing Elevation (ft): 794.73				
0						Dark brown clayey sand			Terminated at 16 ft-bls.
5						Weathered rock			
10						Dark brown clayey sand (very wet)			
15						Green to tan clay with rock			
20									
25									
30									
35									
40									
45									
50									

PROJECT:		Color Spectrum		Log of Boring No. TW-2	
SITE LOCATION:		15 Probasco Street, LaFayette, GA		TOP OF CASING ELEVATION (ft): 801.74	
DRILLING CONTRACTOR:		Atlas Geo-Sampling		DATE STARTED:	DATE FINISHED:
				6/22/2007	6/22/2007
DRILLING METHOD:		Direct Push and HSA		TOTAL DEPTH (ft.):	SCREEN INTERVAL (ft.):
				14	3.5-13.5
DRILLING EQUIPMENT:		AMS Power Probe		DEPTH TO WATER AT TIME OF BORING (ft.):	CASING (ft.):
				5.48	0-3.5
SAMPLING METHOD:		Macrocore with Acetate Liner		BOREHOLE DIAMETER (In.):	WELL DIAMETER (In.):
				3.5	1
LOGGED BY: G.Henry					

DEPTH (feet)	SAMPLES			PID Reading	DESCRIPTION		WELL CONSTRUCTION DETAILS AND/OR DRILLING REMARKS
	Sample No.	Location	Blows/ Foot		Top of Casing Elevation (ft): 801.74		
0					<div><div>Concrete</div><div>Red clay with gravel</div><div>Red-brown clay with some rock</div></div>	<div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></</div></div>	

PROJECT: Syntec Industries, Inc.		Log of Boring No. TW-3	
SITE LOCATION: La Fayette, GA		TOP OF CASING ELEVATION (ft): N/A	
DRILLING CONTRACTOR: N/A		DATE STARTED: 6/27/09	DATE FINISHED: 6/27/09
DRILLING METHOD: Direct Push		TOTAL DEPTH (ft.): 4	SCREEN INTERVAL (ft.): 0-4
DRILLING EQUIPMENT: Hand Auger		DEPTH TO WATER AT TIME OF BORING (ft.):	CASING (ft.): N/A
SAMPLING METHOD: N/A		BOREHOLE DIAMETER (In.): 4	WELL DIAMETER (In.): 1
LOGGED BY: G. Henry			

DEPTH (feet)	SAMPLES			PID Reading	DESCRIPTION			WELL CONSTRUCTION DETAILS AND/OR DRILLING REMARKS	
	Sample No.	Location	Blows/ Foot		Top of Casing Elevation (ft): N/A				
0						Organic material			Terminated at 4 ft-bls. <input type="checkbox"/> Well abandoned immediately after sampling.
5									
10									
15									
20									
25									
30									
35									
40									
45									
50									




PROJECT: Color Spectrum Inc.		Log of Boring No. SB-1 to SB-19	
PROJECT LOCATION: La Fayette, GA		GROUND SURFACE ELEVATION AND DATUM: N/M	
DRILLING CONTRACTOR: Atlas Geo-Sampling		DATE INSTALLED: 12/19/06	
DRILLING METHOD: Direct Push		TOTAL DEPTH (ft.): 15 (average)	SCREEN INTERVAL (ft.): N/A
DRILLING EQUIPMENT: AMS Powerprobe		DEPTH TO WATER: ~5	FIRST: N/M COMPL.: N/A CASING: N/A
SAMPLING METHOD: N/S		LOGGED BY: K. Moore / G. Henry	

DEPTH (feet)	SAMPLES			PID Reading	DESCRIPTION	WELL CONSTRUCTION DETAILS AND/OR DRILLING REMARKS	
	Sample No.	Sample	Blows/ Foot				
0					Top of Casing Elevation: N/M		
1							
2							
3							
4							
5							
6							
7							
8							
9							
10							
11							
12							
13							
14							
15							
16							

No soils collected,
groundwater collected with
screen point sampler.
Borings were abandoned
after sampling.





PROJECT: Color Spectrum Inc.		Log of Boring No. SB-20	
PROJECT LOCATION: La Fayette, GA		GROUND SURFACE ELEVATION AND DATUM: N/M	
DRILLING CONTRACTOR: ESN Southeast		DATE INSTALLED: 12/19/06	
DRILLING METHOD: Direct Push		TOTAL DEPTH (ft.): 14	SCREEN INTERVAL (ft.): 9-14
DRILLING EQUIPMENT: GeoProbe		DEPTH TO WATER: ~10	FIRST: 8.51 COMPL.: 0-9
SAMPLING METHOD: N/S		LOGGED BY: K. Moore	

DEPTH (feet)	SAMPLES			PID Reading	DESCRIPTION	WELL CONSTRUCTION DETAILS AND/OR DRILLING REMARKS
	Sample No.	Sample	Blows/ Foot		Top of Casing Elevation: N/M	
0					No Soil Samples Collected	
1						
2						
3						
4						
5						
6						
7						
8						
9						
10						
11						
12						
13						
14						
15						
16						

Boring terminated at 14 ft-bls. Temporary well abandoned after collection of groundwater sample.



PROJECT: Color Spectrum Inc.					Log of Boring No. SB-21				
PROJECT LOCATION: La Fayette, GA					GROUND SURFACE ELEVATION AND DATUM: N/M				
DRILLING CONTRACTOR: ESN Southeast					DATE INSTALLED: 12/19/06				
DRILLING METHOD: Direct Push					TOTAL DEPTH (ft.): 15			SCREEN INTERVAL (ft.): 10-15	
DRILLING EQUIPMENT: GeoProbe					DEPTH TO WATER: ~14.5	COMPL. 14.45	CASING: 0-10		
SAMPLING METHOD: N/S					LOGGED BY: K. Moore				
DEPTH (feet)	SAMPLES			PID Reading	DESCRIPTION		WELL CONSTRUCTION DETAILS AND/OR DRILLING REMARKS		
	Sample No.	Sample	Blows/ Foot		Top of Casing Elevation: N/M				
0					No Soil Samples Collected				
1									
2									
3									
4									
5									
6									
7									
8									
9									
10									
11									
12									
13									
14									
15									
16									

PROJECT: Color Spectrum Inc.					Log of Boring No. SB-22				
PROJECT LOCATION: La Fayette, GA					GROUND SURFACE ELEVATION AND DATUM: N/M				
DRILLING CONTRACTOR: ESN Southeast					DATE INSTALLED: 12/19/06				
DRILLING METHOD: Direct Push					TOTAL DEPTH (ft.): 15			SCREEN INTERVAL (ft.): 10-15	
DRILLING EQUIPMENT: GeoProbe					DEPTH TO WATER:	FIRST: ~13	COMPL. 11.39	CASING: 0-10	
SAMPLING METHOD: N/S					LOGGED BY: K. Moore				
DEPTH (feet)	SAMPLES			PID Reading	DESCRIPTION		WELL CONSTRUCTION DETAILS AND/OR DRILLING REMARKS		
	Sample No.	Sample	Blows/ Foot		Top of Casing Elevation: N/M				
0					No Soil Samples Collected				
1									
2									
3									
4									
5									
6									
7									
8									
9									
10									
11									
12									
13									
14									
15									
16									

PROJECT:	Color Spectrum Inc.	Log of Boring No.	SB-24
PROJECT LOCATION:	La Fayette, GA	GROUND SURFACE ELEVATION AND DATUM: N/A	
DRILLING CONTRACTOR:	ESN Southeast	DATE STARTED: 12/19/06	DATE FINISHED: 12/19/06
DRILLING METHOD:	Direct Push	TOTAL DEPTH (ft.): 15	SCREEN INTERVAL (ft.): 5-15
DRILLING EQUIPMENT:	GeoProbe	DEPTH TO WATER:	FIRST: 8 COMPL. 8.07 CASING: 0-5
SAMPLING METHOD:	Macrocore Acetate Liner	LOGGED BY: K. Moore	

DEPTH (feet)	SAMPLES			PID Reading	DESCRIPTION	WELL CONSTRUCTION DETAILS AND/OR DRILLING REMARKS	
	Sample No.	Sample	Blows/ Foot		Top of Casing Elevation: 106.64		
0							
1					Concrete/concrete base-no recovery		
2							
3					Red orange fine grain sandy clay with gravel inclusions (fill)		
4				0			
5					Red orange medium grain sandy clay with gravel size dolomite inclusions		
6				1			
7	SB-24				Red orange coarse grain sandy clay with gravel size dolomite		
8				1.1			
9					Orange red clay with yellow mottling-satured-tight trace dolomite gravel		
10							
11							
12							
13					No recovery-saturated		
14							
15							Terminate boring at 15 ft-bls
16							



PROJECT:	Color Spectrum Inc.	Log of Boring No.	SB-26
PROJECT LOCATION:	La Fayette, GA	GROUND SURFACE ELEVATION AND DATUM: N/A	
DRILLING CONTRACTOR:	ESN Southeast	DATE STARTED: 12/19/06	DATE FINISHED: 12/19/06
DRILLING METHOD:	Direct Push	TOTAL DEPTH (ft.): 15	SCREEN INTERVAL (ft.): 5-15
DRILLING EQUIPMENT:	GeoProbe	DEPTH TO WATER: 8	FIRST: 8 COMPL. 7.87 CASING: 0-5
SAMPLING METHOD:	Macrocore Acetate Liner	LOGGED BY: K. Moore	

DEPTH (feet)	SAMPLES			PID Reading	DESCRIPTION	WELL CONSTRUCTION DETAILS AND/OR DRILLING REMARKS
	Sample No.	Sample	Blows/ Foot		Top of Casing Elevation: 106.41	
0						
1					Concrete with large concrete aggregate	
2						
3					Orange brown fine grain sandy clay-tight	
4				0		
5					Red orange coarse grain sandy clay with medium dolomite inclusions 1-2 cm-tight	
6				0		
7	SB-26				Red orange medium grain sandy clay with yellow mottling - dry-tight	
8				1.5		
9					Yellow orange red fine grain sandy clay with large dolomite inclusions > 2 cm - saturated and loose	
10						
11						
12					No recovery	
13						
14						
15						Terminate boring at 15 ft-bls
16						



PROJECT:	Color Spectrum Inc.	Log of Boring No.	SB-28
PROJECT LOCATION:	La Fayette, GA	GROUND SURFACE ELEVATION AND DATUM: N/A	
DRILLING CONTRACTOR:	ESN Southeast	DATE STARTED: 12/19/06	DATE FINISHED: 12/19/06
DRILLING METHOD:	Direct Push	TOTAL DEPTH (ft.): 10	SCREEN INTERVAL (ft.): 5-10
DRILLING EQUIPMENT:	GeoProbe	DEPTH TO WATER:	FIRST: 6 COMPL. 7.75 CASING: 0-5
SAMPLING METHOD:	Macrocore Acetate Liner	LOGGED BY: K. Moore	



DEPTH (feet)	SAMPLES			PID Reading	DESCRIPTION	WELL CONSTRUCTION DETAILS AND/OR DRILLING REMARKS	
	Sample No.	Sample	Blows/ Foot		Top of Casing Elevation: 99.84		
0							
1					Yellow orange silty clay with gravel size dolomite inclusions <2 cm		
2					Black charred/organics from burning		
3					Terra cotta fragments		
4					Brown black organic rich silty clay - tight		
5							
6					Brown black organic rich silty clay - tight		
7							
8							
9					Yellow orange tan mottled medium grain sandy clay		
10							

Bore hole dia: 3.5 in
Well dia: 1 in

Terminate boring at 10 ft-bls





PROJECT:		Color Spectrum		Log of Boring No. SB-29	
SITE LOCATION:		15 Probasco Street, LaFayette, GA		TOP OF CASING ELEVATION (ft): N/A	
DRILLING CONTRACTOR:		Atlas Geo-Sampling		DATE STARTED:	DATE FINISHED:
				6/22/2007	6/22/2007
DRILLING METHOD:		Direct Push and HSA		TOTAL DEPTH (ft.):	SCREEN INTERVAL (ft.):
				8	N/A
DRILLING EQUIPMENT:		AMS Power Probe		DEPTH TO WATER AT TIME OF BORING (ft.):	CASING (ft.):
				N/A	N/A
SAMPLING METHOD:		Macrocore with Acetate Liner		BOREHOLE DIAMETER (In.):	WELL DIAMETER (In.):
				3.5	N/A
LOGGED BY: G.Henry					

DEPTH (feet)	SAMPLES			PID Reading	DESCRIPTION		WELL CONSTRUCTION DETAILS AND/OR DRILLING REMARKS	
	Sample No.	Location	Blows/ Foot		Top of Casing Elevation (ft):			
					N/A			
0	SB-29 (4) SB-29 (1)			17.5			Terminated at 8ft-bls.	
				13.9				
5				12.6				
10								
15								
20								
25								
30								
35								
40								
45								
50								






PROJECT: Color Spectrum		Log of Boring No. SB-30	
SITE LOCATION: 15 Probasco Street, LaFayette, GA		TOP OF CASING ELEVATION (ft): N/A	
DRILLING CONTRACTOR: Atlas Geo-Sampling		DATE STARTED: 6/22/2007	DATE FINISHED: 6/22/2007
DRILLING METHOD: Direct Push and HSA		TOTAL DEPTH (ft.): 8	SCREEN INTERVAL (ft.): N/A
DRILLING EQUIPMENT: AMS Power Probe		DEPTH TO WATER AT TIME OF BORING (ft.): N/A	CASING (ft.): N/A
SAMPLING METHOD: Macrocore with Acetate Liner		BOREHOLE DIAMETER (In.): 3.5	WELL DIAMETER (In.): N/A
LOGGED BY: G.Henry			

DEPTH (feet)	SAMPLES			PID Reading	DESCRIPTION		WELL CONSTRUCTION DETAILS AND/OR DRILLING REMARKS
	Sample No.	Location	Blows/ Foot		Top of Casing Elevation (ft): N/A		
0	SB-30 (4) SB-30 (1)			1.1		Concrete	Terminated at 8ft-bls.
				1.6		Red clay with gravel	
5				1.5			
10							
15							
20							
25							
30							
35							
40							
45							
50							





PROJECT:		Color Spectrum		Log of Boring No. SB-31	
SITE LOCATION:		15 Probasco Street, LaFayette, GA		TOP OF CASING ELEVATION (ft): N/A	
DRILLING CONTRACTOR:		Atlas Geo-Sampling		DATE STARTED:	DATE FINISHED:
				6/22/2007	6/22/2007
DRILLING METHOD:		Direct Push and HSA		TOTAL DEPTH (ft.):	SCREEN INTERVAL (ft.):
				8	N/A
DRILLING EQUIPMENT:		AMS Power Probe		DEPTH TO WATER AT TIME OF BORING (ft.):	CASING (ft.):
				N/A	N/A
SAMPLING METHOD:		Macrocore with Acetate Liner		BOREHOLE DIAMETER (In.):	WELL DIAMETER (In.):
				3.5	N/A
LOGGED BY: G.Henry					

DEPTH (feet)	SAMPLES			PID Reading	DESCRIPTION		WELL CONSTRUCTION DETAILS AND/OR DRILLING REMARKS	
	Sample No.	Location	Blows/ Foot		Top of Casing Elevation (ft):			
0	SB-31 (1)			2.3			Terminated at 8ft-bls.	
				1.8				
5	SB-31 (7)		2.8					
10								
15								
20								
25								
30								
35								
40								
45								
50								



PROJECT: Color Spectrum		Log of Boring No. SB-32	
SITE LOCATION: 15 Probasco Street, LaFayette, GA		TOP OF CASING ELEVATION (ft): N/A	
DRILLING CONTRACTOR: Atlas Geo-Sampling		DATE STARTED: 6/22/2007	DATE FINISHED: 6/22/2007
DRILLING METHOD: Direct Push and HSA		TOTAL DEPTH (ft.): 8	SCREEN INTERVAL (ft.): N/A
DRILLING EQUIPMENT: AMS Power Probe		DEPTH TO WATER AT TIME OF BORING (ft.): N/A	CASING (ft.): N/A
SAMPLING METHOD: Macrocore with Acetate Liner		BOREHOLE DIAMETER (In.): 3.5	WELL DIAMETER (In.): N/A
LOGGED BY: G.Henry			

DEPTH (feet)	SAMPLES			PID Reading	DESCRIPTION		WELL CONSTRUCTION DETAILS AND/OR DRILLING REMARKS
	Sample No.	Location	Blows/ Foot		Top of Casing Elevation (ft): N/A		
0	SB-32 (4) SB-32 (1)			8.8		Concrete	Terminated at 8ft-bls.
5				3		Red clay with gravel	
10							
15							
20							
25							
30							
35							
40							
45							
50							





PROJECT:		Color Spectrum		Log of Boring No. SB-33	
SITE LOCATION:		15 Probasco Street, LaFayette, GA		TOP OF CASING ELEVATION (ft): N/A	
DRILLING CONTRACTOR:		Atlas Geo-Sampling		DATE STARTED:	DATE FINISHED:
				6/21/2007	6/21/2007
DRILLING METHOD:		Direct Push and HSA		TOTAL DEPTH (ft.):	SCREEN INTERVAL (ft.):
				12	N/A
DRILLING EQUIPMENT:		AMS Power Probe		DEPTH TO WATER AT TIME OF BORING (ft.):	CASING (ft.):
				N/A	N/A
SAMPLING METHOD:		Macrocore with Acetate Liner		BOREHOLE DIAMETER (In.):	WELL DIAMETER (In.):
				3.5	N/A
LOGGED BY: G.Henry					

DEPTH (feet)	SAMPLES			PID Reading	DESCRIPTION		WELL CONSTRUCTION DETAILS AND/OR DRILLING REMARKS	
	Sample No.	Location	Blows/ Foot					
					Top of Casing Elevation (ft):			
0	SB-33 (4) SB-33 (1)			0.8	<div><div></div></div>		Terminated at 12ft-bls.	
				0.4				
5				0.3	<div><div></div></div>	Red clay with gravel		
10								
15								
20								
25								
30								
35								
40								
45								
50								









PROJECT:		Color Spectrum		Log of Boring No. SB-34	
SITE LOCATION:		15 Probasco Street, LaFayette, GA		TOP OF CASING ELEVATION (ft): N/A	
DRILLING CONTRACTOR:		Atlas Geo-Sampling		DATE STARTED:	DATE FINISHED:
				6/21/2007	6/21/2007
DRILLING METHOD:		Direct Push and HSA		TOTAL DEPTH (ft.):	SCREEN INTERVAL (ft.):
				8	N/A
DRILLING EQUIPMENT:		AMS Power Probe		DEPTH TO WATER AT TIME OF BORING (ft.):	CASING (ft.):
				N/A	N/A
SAMPLING METHOD:		Macrocore with Acetate Liner		BOREHOLE DIAMETER (In.):	WELL DIAMETER (In.):
				3.5	N/A
LOGGED BY: G.Henry					

DEPTH (feet)	SAMPLES			PID Reading	DESCRIPTION		WELL CONSTRUCTION DETAILS AND/OR DRILLING REMARKS	
	Sample No.	Location	Blows/ Foot					
					Top of Casing Elevation (ft): N/A			
0	SB-34 (1)			2		Concrete		Terminated at 8ft-bls.
5				3				
	SB-34 (7)			3.4				
10								
15								
20								
25								
30								
35								
40								
45								
50								




PROJECT: Color Spectrum		Log of Boring No. SB-35	
SITE LOCATION: 15 Probasco Street, LaFayette, GA		TOP OF CASING ELEVATION (ft): N/A	
DRILLING CONTRACTOR: Atlas Geo-Sampling		DATE STARTED: 6/21/2007	DATE FINISHED: 6/21/2007
DRILLING METHOD: Direct Push and HSA		TOTAL DEPTH (ft.): 12	SCREEN INTERVAL (ft.): N/A
DRILLING EQUIPMENT: AMS Power Probe		DEPTH TO WATER AT TIME OF BORING (ft.): 4.5	CASING (ft.): N/A
SAMPLING METHOD: Macrocore with Acetate Liner		BOREHOLE DIAMETER (In.): 3.5	WELL DIAMETER (In.): N/A
LOGGED BY: G.Henry			

DEPTH (feet)	SAMPLES			PID Reading	DESCRIPTION		WELL CONSTRUCTION DETAILS AND/OR DRILLING REMARKS	
	Sample No.	Location	Blows/ Foot					
					Top of Casing Elevation (ft):			
0	SB-35 (4BB-35 (1))			0			Terminated at 12ft-bls.	
				0.2				
5				0				
10								
15								
20								
25								
30								
35								
40								
45								
50								



PROJECT: Color Spectrum		Log of Boring No. SB-36	
SITE LOCATION: 15 Probasco Street, LaFayette, GA		TOP OF CASING ELEVATION (ft): N/A	
DRILLING CONTRACTOR: Atlas Geo-Sampling		DATE STARTED: 6/21/2007	DATE FINISHED: 6/21/2007
DRILLING METHOD: Direct Push and HSA		TOTAL DEPTH (ft.): 12	SCREEN INTERVAL (ft.): N/A
DRILLING EQUIPMENT: AMS Power Probe		DEPTH TO WATER AT TIME OF BORING (ft.): N/A	CASING (ft.): N/A
SAMPLING METHOD: Macrocore with Acetate Liner		BOREHOLE DIAMETER (In.): 3.5	WELL DIAMETER (In.): N/A
LOGGED BY: G.Henry			

DEPTH (feet)	SAMPLES			PID Reading	DESCRIPTION		WELL CONSTRUCTION DETAILS AND/OR DRILLING REMARKS
	Sample No.	Location	Blows/ Foot				
					Top of Casing Elevation (ft):		
0	SB-36 (4) SB-36 (1)			0.6	 Concrete		Terminated at 12ft-bls.
				0.6	Red clay with gravel		
5							
				0			
10							
15							
20							
25							
30							
35							
40							
45							
50							







PROJECT:		Color Spectrum		Log of Boring No. SB-37	
SITE LOCATION:		15 Probasco Street, LaFayette, GA		TOP OF CASING ELEVATION (ft): N/A	
DRILLING CONTRACTOR:		Atlas Geo-Sampling		DATE STARTED:	DATE FINISHED:
				6/26/2007	6/26/2007
DRILLING METHOD:		Direct Push and HSA		TOTAL DEPTH (ft.):	SCREEN INTERVAL (ft.):
				8	N/A
DRILLING EQUIPMENT:		AMS Power Probe		DEPTH TO WATER AT TIME OF BORING (ft.):	CASING (ft.):
				4	N/A
SAMPLING METHOD:		Macrocore with Acetate Liner		BOREHOLE DIAMETER (In.):	WELL DIAMETER (In.):
				7	2
LOGGED BY: G.Henry					

DEPTH (feet)	SAMPLES			PID Reading	DESCRIPTION		WELL CONSTRUCTION DETAILS AND/OR DRILLING REMARKS	
	Sample No.	Location	Blows/ Foot		Top of Casing Elevation (ft):			
					N/A			
0	SB-37 (SB-37 (1))			2.3	<div></div>		Terminated at 8ft-bls.	
						Concrete and rock		
						Red-orange clay with some rock		
5					Red-brown clay with some rock (wet)			
10								
15								
20								
25								
30								
35								
40								
45								
50								







PROJECT: Color Spectrum		Log of Boring No. SO-1	
SITE LOCATION: LaFayette, GA		TOP OF CASING ELEVATION (ft): N/A	
DRILLING CONTRACTOR: Atlas Geo-Sampling		DATE STARTED: 10/6/09	DATE FINISHED: 10/6/09
DRILLING METHOD: Direct Push		TOTAL DEPTH (ft.): 3	SCREEN INTERVAL (ft.): N/A
DRILLING EQUIPMENT: AMS Power Probe		DEPTH TO WATER AT TIME OF BORING (ft.): N/A	CASING (ft.): N/A
SAMPLING METHOD: Macrocore w/ Acetate Liner		BOREHOLE DIAMETER (In.): 3	WELL DIAMETER (In.): N/A
LOGGED BY: R. Jones			

DEPTH (feet)	SAMPLES			PID Reading	DESCRIPTION		WELL CONSTRUCTION DETAILS AND/OR DRILLING REMARKS	
	Sample No.	Location	Blows/ Foot		Ground Surface Elevation (ft): N/A			
0	09279-SO-1-2			0 0 0		Gravel, gray sand		Boring terminated at 3-ft below land surface.
						Red clay with rock (quartz)		
						Red clay with sand and weathered rock		
5								
10								
15								
20								





PROJECT: Color Spectrum		Log of Boring No. SO-2	
SITE LOCATION: LaFayette, GA		TOP OF CASING ELEVATION (ft): N/A	
DRILLING CONTRACTOR: Atlas Geo-Sampling		DATE STARTED: 10/6/09	DATE FINISHED: 10/6/09
DRILLING METHOD: Direct Push		TOTAL DEPTH (ft.): 3	SCREEN INTERVAL (ft.): N/A
DRILLING EQUIPMENT: AMS Power Probe		DEPTH TO WATER AT TIME OF BORING (ft.): N/A	CASING (ft.): N/A
SAMPLING METHOD: Macrocore w/ Acetate Liner		BOREHOLE DIAMETER (In.): 3	WELL DIAMETER (In.): N/A
LOGGED BY: R. Jones			

DEPTH (feet)	SAMPLES			PID Reading	DESCRIPTION		WELL CONSTRUCTION DETAILS AND/OR DRILLING REMARKS	
	Sample No.	Location	Blows/ Foot		Ground Surface Elevation (ft): N/A			
0	09279-SO-2-2			0 0 0		Gravel, gray sand		Boring terminated at 3-ft below land surface.
						Red clay with rock (quartz)		
						Red clay with sand and weathered rock		
5								
10								
15								
20								








PROJECT:		Color Spectrum		Log of Boring No. SO-3	
SITE LOCATION:		LaFayette, GA		TOP OF CASING ELEVATION (ft): N/A	
DRILLING CONTRACTOR:		Atlas Geo-Sampling		DATE STARTED:	DATE FINISHED:
				10/6/09	10/6/09
DRILLING METHOD:		Direct Push		TOTAL DEPTH (ft.):	SCREEN INTERVAL (ft.):
				8	N/A
DRILLING EQUIPMENT:		AMS Power Probe		DEPTH TO WATER AT TIME OF BORING (ft.):	CASING (ft.):
				7	N/A
SAMPLING METHOD:		Macrocore w/ Acetate Liner		BOREHOLE DIAMETER (In.):	WELL DIAMETER (In.):
				3	N/A
LOGGED BY: R. Jones					

DEPTH (feet)	SAMPLES		Blows/ Foot	PID Reading	DESCRIPTION		WELL CONSTRUCTION DETAILS AND/OR DRILLING REMARKS
	Sample No.	Location			Ground Surface Elevation (ft): N/A		
0	09279-SO-3-2				Concrete, gravel and gray sand		Boring terminated at 8-ft below land surface.
					Sand with clay and weathered rock		
					Red clay with sand and weathered rock		
					Red clay with weathered rock		
5							
10							
15							
20							








PROJECT: Color Spectrum		Log of Boring No. SO-4	
SITE LOCATION: LaFayette, GA		TOP OF CASING ELEVATION (ft): N/A	
DRILLING CONTRACTOR: Atlas Geo-Sampling		DATE STARTED: 10/6/09	DATE FINISHED: 10/6/09
DRILLING METHOD: Direct Push		TOTAL DEPTH (ft.): 8	SCREEN INTERVAL (ft.): N/A
DRILLING EQUIPMENT: AMS Power Probe		DEPTH TO WATER AT TIME OF BORING (ft.): 7	CASING (ft.): N/A
SAMPLING METHOD: Macrocore w/ Acetate Liner		BOREHOLE DIAMETER (In.): 3	WELL DIAMETER (In.): N/A
LOGGED BY: R. Jones			

DEPTH (feet)	SAMPLES		PID Reading	DESCRIPTION		WELL CONSTRUCTION DETAILS AND/OR DRILLING REMARKS
	Sample No.	Location				
				Ground Surface Elevation (ft): N/A		
0	09279-SO-4-5				Concrete, gravel and gray sand	Boring terminated at 8-ft below land surface.
			2.9		Sand with clay and weathered rock	
			3			
			2.7		Red clay with sand and weathered rock	
5			2.7			
			6.4		Red clay with weathered rock	
			6.7			
			1.7			
10						
15						
20						



PROJECT: Color Spectrum		Log of Boring No. SO-6	
SITE LOCATION: LaFayette, GA		TOP OF CASING ELEVATION (ft): N/A	
DRILLING CONTRACTOR: Atlas Geo-Sampling		DATE STARTED: 10/6/09	DATE FINISHED: 10/6/09
DRILLING METHOD: Direct Push		TOTAL DEPTH (ft.): 8	SCREEN INTERVAL (ft.): N/A
DRILLING EQUIPMENT: AMS Power Probe		DEPTH TO WATER AT TIME OF BORING (ft.): 7	CASING (ft.): N/A
SAMPLING METHOD: Macrocore w/ Acetate Liner		BOREHOLE DIAMETER (In.): 3	WELL DIAMETER (In.): N/A
LOGGED BY: R. Jones			

DEPTH (feet)	SAMPLES			PID Reading	DESCRIPTION		WELL CONSTRUCTION DETAILS AND/OR DRILLING REMARKS
	Sample No.	Location	Blows/ Foot		Ground Surface Elevation (ft): N/A		
0	09279-SO-6-4				Concrete, gravel and gray sand		Boring terminated at 8-ft below land surface.
4.1					Sand with clay and weathered rock		
4.2							
5.1					Red clay with sand and weathered rock		
5.2							
4.1					Red clay with weathered rock		
4.5							



**Non-Residential
Freon-113
Groundwater**

DATA ENTRY SHEET

GW-ADV
Version 3.1; 02/04

CALCULATE RISK-BASED GROUNDWATER CONCENTRATION (enter "X" in "YES" box)

YES

Reset to
Defaults

OR

CALCULATE INCREMENTAL RISKS FROM ACTUAL GROUNDWATER CONCENTRATION (enter "X" in "YES" box and initial groundwater conc. below)

YES

ENTER Chemical CAS No. (numbers only, no dashes)		ENTER Initial groundwater conc., C_W ($\mu\text{g/L}$)		Chemical								
76131	2.70E+04	1,1,2-Trichloro-1,2,2-trifluoroethane										
ENTER Average soil/ groundwater temperature, T_S ($^{\circ}\text{C}$)	ENTER Depth below grade to bottom of enclosed space floor, L_F (cm)	ENTER Depth below grade to water table, L_{WT} (cm)	ENTER Totals must add up to value of L_{WT} (cell G28) Thickness of soil stratum A, h_A (cm)			ENTER Thickness of soil stratum B, (Enter value or 0) h_B (cm)	ENTER Thickness of soil stratum C, (Enter value or 0) h_C (cm)	ENTER Soil stratum directly above water table, (Enter A, B, or C)	ENTER SCS soil type directly above water table	ENTER Soil stratum A SCS soil type (used to estimate soil vapor permeability)	OR	ENTER User-defined stratum A soil vapor permeability, k_v (cm^2)
20	15	213.36	213.36	0	0		A	SC	SC			

MORE
↓

ENTER Stratum A SCS soil type Lookup Soil Parameters	ENTER Stratum A soil dry bulk density, ρ_b^A (g/cm^3)	ENTER Stratum A soil total porosity, n^A (unitless)	ENTER Stratum A soil water-filled porosity, θ_w^A (cm^3/cm^3)	ENTER Stratum B SCS soil type Lookup Soil Parameters	ENTER Stratum B soil dry bulk density, ρ_b^B (g/cm^3)	ENTER Stratum B soil total porosity, n^B (unitless)	ENTER Stratum B soil water-filled porosity, θ_w^B (cm^3/cm^3)	ENTER Stratum C SCS soil type Lookup Soil Parameters	ENTER Stratum C soil dry bulk density, ρ_b^C (g/cm^3)	ENTER Stratum C soil total porosity, n^C (unitless)	ENTER Stratum C soil water-filled porosity, θ_w^C (cm^3/cm^3)
SC	1.63	0.385	0.197	SC	1.63	0.385	0.197	SC	1.63	0.385	0.197

MORE
↓

ENTER Enclosed space floor thickness, L_{crack} (cm)	ENTER Soil-bldg. pressure differential, ΔP (g/cm-s^2)	ENTER Enclosed space floor length, L_B (cm)	ENTER Enclosed space floor width, W_B (cm)	ENTER Enclosed space height, H_B (cm)	ENTER Floor-wall seam crack width, w (cm)	ENTER Indoor air exchange rate, ER (1/h)	ENTER Average vapor flow rate into bldg. OR Leave blank to calculate Q_{soil} (L/m)
10	40	15036.8	4572	670.56	0.1	0.25	5

MORE
↓

ENTER Averaging time for carcinogens, AT_C (yrs)	ENTER Averaging time for noncarcinogens, AT_{NC} (yrs)	ENTER Exposure duration, ED (yrs)	ENTER Exposure frequency, EF (days/yr)	ENTER Target risk for carcinogens, TR (unitless)	ENTER Target hazard quotient for noncarcinogens, THQ (unitless)
70	25	25	250	1.0E-05	1

MORE
↓

END

Used to calculate risk-based
groundwater concentration.

CHEMICAL PROPERTIES SHEET

Diffusivity in air, D_a (cm ² /s)	Diffusivity in water, D_w (cm ² /s)	Henry's law constant at reference temperature, H (atm-m ³ /mol)	Henry's law constant reference temperature, T_R (°C)	Enthalpy of vaporization at the normal boiling point, $\Delta H_{v,b}$ (cal/mol)	Normal boiling point, T_B (°K)	Critical temperature, T_C (°K)	Organic carbon partition coefficient, K_{oc} (cm ³ /g)	Pure component water solubility, S (mg/L)	Unit risk factor, URF (µg/m ³) ⁻¹	Reference conc., RfC (mg/m ³)
7.80E-02	8.20E-06	4.80E-01	25	6,463	320.70	487.30	1.11E+04	1.70E+02	0.0E+00	3.0E+01

END

INTERMEDIATE CALCULATIONS SHEET

Exposure duration, τ (sec)	Source-building separation, L_T (cm)	Stratum A soil air-filled porosity, θ_a^A (cm ³ /cm ³)	Stratum B soil air-filled porosity, θ_a^B (cm ³ /cm ³)	Stratum C soil air-filled porosity, θ_a^C (cm ³ /cm ³)	Stratum A effective total fluid saturation, S_{ie} (cm ³ /cm ³)	Stratum A soil intrinsic permeability, k_i (cm ²)	Stratum A soil relative air permeability, k_{rg} (cm ²)	Stratum A soil effective vapor permeability, k_v (cm ²)	Thickness of capillary zone, L_{cz} (cm)	Total porosity in capillary zone, n_{cz} (cm ³ /cm ³)	Air-filled porosity in capillary zone, $\theta_{a,cz}$ (cm ³ /cm ³)	Water-filled porosity in capillary zone, $\theta_{w,cz}$ (cm ³ /cm ³)	Floor-wall seam perimeter, X_{crack} (cm)
7.88E+08	198.36	0.188	0.188	0.188	0.299	1.77E-09	0.837	1.48E-09	30.00	0.385	0.030	0.355	39,218

Bldg. ventilation rate, $Q_{building}$ (cm ³ /s)	Area of enclosed space below grade, A_B (cm ²)	Crack-to-total area ratio, η (unitless)	Crack depth below grade, Z_{crack} (cm)	Enthalpy of vaporization at ave. groundwater temperature, $\Delta H_{v,TS}$ (cal/mol)	Henry's law constant at ave. groundwater temperature, H_{TS} (atm-m ³ /mol)	Henry's law constant at ave. groundwater temperature, H'_{TS} (unitless)	Vapor viscosity at ave. soil temperature, μ_{TS} (g/cm-s)	Stratum A effective diffusion coefficient, D_A^{eff} (cm ² /s)	Stratum B effective diffusion coefficient, D_B^{eff} (cm ² /s)	Stratum C effective diffusion coefficient, D_C^{eff} (cm ² /s)	Capillary zone effective diffusion coefficient, D_{cz}^{eff} (cm ² /s)	Total overall effective diffusion coefficient, D_T^{eff} (cm ² /s)	Diffusion path length, L_d (cm)
3.20E+06	6.93E+07	5.66E-05	15	6,840	3.94E-01	1.64E+01	1.78E-04	2.01E-03	0.00E+00	0.00E+00	4.65E-06	3.04E-05	198.36

Convection path length, L_p (cm)	Source vapor conc., C_{source} (μg/m ³)	Crack radius, r_{crack} (cm)	Average vapor flow rate into bldg., Q_{soil} (cm ³ /s)	Crack effective diffusion coefficient, D^{crack} (cm ² /s)	Area of crack, A_{crack} (cm ²)	Exponent of equivalent foundation Peclet number, $\exp(Pe^f)$ (unitless)	Infinite source indoor attenuation coefficient, α (unitless)	Infinite source bldg. conc., $C_{building}$ (μg/m ³)	Unit risk factor, URF (μg/m ³) ⁻¹	Reference conc., RfC (mg/m ³)
15	4.42E+08	0.10	8.33E+01	2.01E-03	3.92E+03	6.52E+45	2.94E-06	1.30E+03	NA	3.0E+01

END

RESULTS SHEET

RISK-BASED GROUNDWATER CONCENTRATION CALCULATIONS:

Indoor exposure groundwater conc., carcinogen (µg/L)	Indoor exposure groundwater conc., noncarcinogen (µg/L)	Risk-based indoor exposure groundwater conc., (µg/L)	Pure component water solubility, S (µg/L)	Final indoor exposure groundwater conc., (µg/L)
NA	NA	NA	1.70E+05	NA

INCREMENTAL RISK CALCULATIONS:

Incremental risk from vapor intrusion to indoor air, carcinogen (unitless)	Hazard quotient from vapor intrusion to indoor air, noncarcinogen (unitless)
NA	3.0E-02

MESSAGE AND ERROR SUMMARY BELOW: (DO NOT USE RESULTS IF ERRORS ARE PRESENT)

SCROLL
DOWN
TO "END"

END

**Non-Residential
Freon-113
Soil**

SL-ADV
Version 3.1; 02/04

CALCULATE RISK-BASED SOIL CONCENTRATION (enter "X" in "YES" box)

YES

OR

CALCULATE INCREMENTAL RISKS FROM ACTUAL SOIL CONCENTRATION (enter "X" in "YES" box and initial soil conc. below)

YES

X

Reset to
DefaultsENTER
Chemical
CAS No.
(numbers only,
no dashes)ENTER
Initial
soil
conc.,
 C_R
($\mu\text{g/kg}$)

Chemical

76131

4.20E+03

1,1,2-Trichloro-1,2,2-trifluoroethane

MORE
↓

ENTER Average soil temperature, T_s ($^{\circ}\text{C}$)	ENTER Depth below grade to bottom of enclosed space floor, L_f (cm)	ENTER Depth below grade to top of contamination, L_i (cm)	ENTER Depth below grade to bottom of contamination, (enter value of 0 if value is unknown) L_o (cm)	ENTER Thickness of soil stratum A, h_A (cm)	ENTER Thickness of soil stratum B, (Enter value or 0) h_B (cm)	ENTER Thickness of soil stratum C, (Enter value or 0) h_C (cm)	ENTER Soil stratum A SCS soil type (used to estimate soil vapor permeability)	OR	ENTER User-defined stratum A soil vapor permeability, k_v (cm^2)
20	15	30.48	213.36	30.48	0	0	SC		

MORE
↓

ENTER Stratum A SCS soil type Lookup Soil Parameters	ENTER Stratum A soil dry bulk density, ρ_b^A (g/cm^3)	ENTER Stratum A soil total porosity, n^A (unitless)	ENTER Stratum A soil water-filled porosity, θ_w^A (cm^3/cm^3)	ENTER Stratum A soil organic carbon fraction, f_{oc}^A (unitless)	ENTER Stratum B SCS soil type Lookup Soil Parameters	ENTER Stratum B soil dry bulk density, ρ_b^B (g/cm^3)	ENTER Stratum B soil total porosity, n^B (unitless)	ENTER Stratum B soil water-filled porosity, θ_w^B (cm^3/cm^3)	ENTER Stratum B soil organic carbon fraction, f_{oc}^B (unitless)	ENTER Stratum C SCS soil type Lookup Soil Parameters	ENTER Stratum C soil dry bulk density, ρ_b^C (g/cm^3)	ENTER Stratum C soil total porosity, n^C (unitless)	ENTER Stratum C soil water-filled porosity, θ_w^C (cm^3/cm^3)	ENTER Stratum C soil organic carbon fraction, f_{oc}^C (unitless)
SC	1.63	0.385	0.197	0.002	SC	1.63	0.385	0.197	0.002	SC	1.63	0.385	0.197	0.002

MORE
↓

ENTER Enclosed space floor thickness, L_{crack} (cm)	ENTER Soil-bldg. pressure differential, ΔP ($\text{g/cm} \cdot \text{s}^2$)	ENTER Enclosed space floor length, L_B (cm)	ENTER Enclosed space floor width, W_B (cm)	ENTER Enclosed space height, H_B (cm)	ENTER Floor-wall seam crack width, w (cm)	ENTER Indoor air exchange rate, ER (1/h)	ENTER Average vapor flow rate into bldg. OR Leave blank to calculate Q_{vair} (L/m)
10	40	15036.8	4572	670.56	0.1	0.25	5

ENTER Averaging time for carcinogens, AT_C (yrs)	ENTER Averaging time for noncarcinogens, AT_{NC} (yrs)	ENTER Exposure duration, ED (yrs)	ENTER Exposure frequency, EF (days/yr)	ENTER Target risk for carcinogens, TR (unitless)	ENTER Target hazard quotient for noncarcinogens, THQ (unitless)
70	25	25	250	1.0E-05	1

END

Used to calculate risk-based
soil concentration.

CHEMICAL PROPERTIES SHEET

Diffusivity in air, D_a (cm ² /s)	Diffusivity in water, D_w (cm ² /s)	Henry's law constant at reference temperature, H (atm-m ³ /mol)	Henry's law constant reference temperature, T_R (°C)	Enthalpy of vaporization at the normal boiling point, $\Delta H_{v,b}$ (cal/mol)	Normal boiling point, T_B (°K)	Critical temperature, T_C (°K)	Organic carbon partition coefficient, K_{oc} (cm ³ /g)	Pure component water solubility, S (mg/L)	Unit risk factor, URF (µg/m ³) ⁻¹	Reference conc., RfC (mg/m ³)	Physical state at soil temperature, (S,L,G)
7.80E-02	8.20E-06	4.80E-01	25	6,463	320.70	487.30	1.11E+04	1.70E+02	0.0E+00	3.0E+01	L

END

INTERMEDIATE CALCULATIONS SHEET

Exposure duration, τ (sec)	Source-building separation, L_T (cm)	Stratum A soil air-filled porosity, θ_a^A (cm ³ /cm ³)	Stratum B soil air-filled porosity, θ_a^B (cm ³ /cm ³)	Stratum C soil air-filled porosity, θ_a^C (cm ³ /cm ³)	Stratum A effective total fluid saturation, S_{fe} (cm ³ /cm ³)	Stratum A soil intrinsic permeability, k_i (cm ²)	Stratum A soil relative air permeability, k_{rg} (cm ²)	Stratum A soil effective vapor permeability, k_v (cm ²)	Floor-wall seam perimeter, X_{crack} (cm)	Initial soil concentration used, C_R (µg/kg)	Bldg. ventilation rate, $Q_{building}$ (cm ³ /s)
7.88E+08	15.48	0.188	0.188	0.188	0.299	1.77E-09	0.837	1.48E-09	39,218	4.20E+03	3.20E+06

Area of enclosed space below grade, A_B (cm ²)	Crack-to-total area ratio, η (unitless)	Crack depth below grade, Z_{crack} (cm)	Enthalpy of vaporization at ave. soil temperature, $\Delta H_{v,TS}$ (cal/mol)	Henry's law constant at ave. soil temperature, H_{TS} (atm-m ³ /mol)	Henry's law constant at ave. soil temperature, H'_{TS} (unitless)	Vapor viscosity at ave. soil temperature, μ_{TS} (g/cm-s)	Stratum A effective diffusion coefficient, D^{eff}_A (cm ² /s)	Stratum B effective diffusion coefficient, D^{eff}_B (cm ² /s)	Stratum C effective diffusion coefficient, D^{eff}_C (cm ² /s)	Total overall effective diffusion coefficient, D^{eff}_T (cm ² /s)	Diffusion path length, L_d (cm)	Convection path length, L_p (cm)
6.93E+07	5.66E-05	15	6,840	3.94E-01	1.64E+01	1.78E-04	2.01E-03	0.00E+00	0.00E+00	2.01E-03	15.48	15

Soil-water partition coefficient, K_d (cm ³ /g)	Source vapor conc., C_{source} (µg/m ³)	Crack radius, r_{crack} (cm)	Average vapor flow rate into bldg., Q_{soil} (cm ³ /s)	Crack effective diffusion coefficient, D^{crack} (cm ² /s)	Area of crack, A_{crack} (cm ²)	Exponent of equivalent Peclet number, $\exp(Pe^d)$ (unitless)	Infinite source indoor attenuation coefficient, α (unitless)	Infinite source bldg. conc., $C_{building}$ (µg/m ³)	Finite source β term (unitless)	Finite source ψ term (sec) ⁻¹	Time for source depletion, τ_D (sec)	Exposure duration > time for source depletion (YES/NO)
2.23E+01	2.83E+06	0.10	8.33E+01	2.01E-03	3.92E+03	6.52E+45	NA	NA	1.09E+02	3.48E-06	3.91E+08	YES

Finite source indoor attenuation coefficient, < α > (unitless)	Mass limit bldg. conc., $C_{building}$ (µg/m ³)	Finite source bldg. conc., $C_{building}$ (µg/m ³)	Final finite source bldg. conc., $C_{building}$ (µg/m ³)	Unit risk factor, URF (µg/m ³) ⁻¹	Reference conc., RfC (mg/m ³)
NA	3.44E+01	NA	3.44E+01	NA	3.0E+01

END

RESULTS SHEET

RISK-BASED SOIL CONCENTRATION CALCULATIONS:

Indoor exposure soil conc., carcinogen (µg/kg)	Indoor exposure soil conc., noncarcinogen (µg/kg)	Risk-based indoor exposure soil conc., (µg/kg)	Soil saturation conc., C _{sat} (µg/kg)	Final indoor exposure soil conc., (µg/kg)
NA	NA	NA	4.13E+06	NA

INCREMENTAL RISK CALCULATIONS:

Incremental risk from vapor intrusion to indoor air, carcinogen (unitless)	Hazard quotient from vapor intrusion to indoor air, noncarcinogen (unitless)
NA	7.8E-04

MESSAGE AND ERROR SUMMARY BELOW: (DO NOT USE RESULTS IF ERRORS ARE PRESENT)

SCROLL
DOWN
TO "END"

END

**Non-Residential
Tetrachloroethene
Groundwater**

DATA ENTRY SHEET

GW-ADV
Version 3.1; 02/04

CALCULATE RISK-BASED GROUNDWATER CONCENTRATION (enter "X" in "YES" box)

YES

Reset to
Defaults

OR

CALCULATE INCREMENTAL RISKS FROM ACTUAL GROUNDWATER CONCENTRATION (enter "X" in "YES" box and initial groundwater conc. below)

YES

ENTER Chemical CAS No. (numbers only, no dashes)		ENTER Initial groundwater conc., C_W ($\mu\text{g/L}$)		Chemical							
127184	3.50E+02			Tetrachloroethylene							
ENTER Average soil/ groundwater temperature, T_S ($^{\circ}\text{C}$)	ENTER Depth below grade to bottom of enclosed space floor, L_F (cm)	ENTER Depth below grade to water table, L_{WT} (cm)	ENTER Totals must add up to value of L_{WT} (cell G28)			ENTER Soil stratum directly above water table, (Enter A, B, or C)	ENTER SCS soil type directly above water table	ENTER Soil stratum A SCS soil type (used to estimate soil vapor permeability)		OR	ENTER User-defined stratum A soil vapor permeability, k_v (cm^2)
Thickness of soil stratum A, h_A (cm)	Thickness of soil stratum B, (Enter value or 0) h_B (cm)	Thickness of soil stratum C, (Enter value or 0) h_C (cm)									
20	15	213.56	213.56	0	0	A	SC	SC			

MORE
↓

ENTER Stratum A SCS soil type Lookup Soil Parameters	ENTER Stratum A soil dry bulk density, ρ_b^A (g/cm^3)	ENTER Stratum A soil total porosity, n^A (unitless)	ENTER Stratum A soil water-filled porosity, θ_w^A (cm^3/cm^3)	ENTER Stratum B SCS soil type Lookup Soil Parameters	ENTER Stratum B soil dry bulk density, ρ_b^B (g/cm^3)	ENTER Stratum B soil total porosity, n^B (unitless)	ENTER Stratum B soil water-filled porosity, θ_w^B (cm^3/cm^3)	ENTER Stratum C SCS soil type Lookup Soil Parameters	ENTER Stratum C soil dry bulk density, ρ_b^C (g/cm^3)	ENTER Stratum C soil total porosity, n^C (unitless)	ENTER Stratum C soil water-filled porosity, θ_w^C (cm^3/cm^3)
SC	1.63	0.385	0.197	SC	1.63	0.385	0.197	SC	1.63	0.385	0.197

MORE
↓

ENTER Enclosed space floor thickness, L_{crack} (cm)	ENTER Soil-bldg. pressure differential, ΔP (g/cm-s^2)	ENTER Enclosed space floor length, L_B (cm)	ENTER Enclosed space floor width, W_B (cm)	ENTER Enclosed space height, H_B (cm)	ENTER Floor-wall seam crack width, w (cm)	ENTER Indoor air exchange rate, ER (1/h)	ENTER Average vapor flow rate into bldg. OR Leave blank to calculate Q_{soil} (L/m)
10	40	15036.8	4572	670.56	0.1	0.25	5

MORE
↓

ENTER Averaging time for carcinogens, AT_C (yrs)	ENTER Averaging time for noncarcinogens, AT_{NC} (yrs)	ENTER Exposure duration, ED (yrs)	ENTER Exposure frequency, EF (days/yr)	ENTER Target risk for carcinogens, TR (unitless)	ENTER Target hazard quotient for noncarcinogens, THQ (unitless)
70	25	25	250	1.0E-05	1

MORE
↓

END

Used to calculate risk-based
groundwater concentration.

CHEMICAL PROPERTIES SHEET

Diffusivity in air, D_a (cm^2/s)	Diffusivity in water, D_w (cm^2/s)	Henry's law constant at reference temperature, H ($\text{atm}\cdot\text{m}^3/\text{mol}$)	Henry's law constant reference temperature, T_R ($^\circ\text{C}$)	Enthalpy of vaporization at the normal boiling point, $\Delta H_{v,b}$ (cal/mol)	Normal boiling point, T_B ($^\circ\text{K}$)	Critical temperature, T_C ($^\circ\text{K}$)	Organic carbon partition coefficient, K_{oc} (cm^3/g)	Pure component water solubility, S (mg/L)	Unit risk factor, URF ($\mu\text{g}/\text{m}^3$) ⁻¹	Reference conc., RfC (mg/m^3)
7.20E-02	8.20E-06	1.84E-02	25	8,288	394.40	620.20	1.55E+02	2.00E+02	2.6E-07	4.0E-02

END

INTERMEDIATE CALCULATIONS SHEET

Exposure duration, τ (sec)	Source-building separation, L_T (cm)	Stratum A soil air-filled porosity, θ_a^A (cm ³ /cm ³)	Stratum B soil air-filled porosity, θ_a^B (cm ³ /cm ³)	Stratum C soil air-filled porosity, θ_a^C (cm ³ /cm ³)	Stratum A effective total fluid saturation, S_{ie} (cm ³ /cm ³)	Stratum A soil intrinsic permeability, k_i (cm ²)	Stratum A soil relative air permeability, k_{rg} (cm ²)	Stratum A soil effective vapor permeability, k_v (cm ²)	Thickness of capillary zone, L_{cz} (cm)	Total porosity in capillary zone, n_{cz} (cm ³ /cm ³)	Air-filled porosity in capillary zone, $\theta_{a,cz}$ (cm ³ /cm ³)	Water-filled porosity in capillary zone, $\theta_{w,cz}$ (cm ³ /cm ³)	Floor-wall seam perimeter, X_{crack} (cm)
7.88E+08	198.56	0.188	0.188	0.188	0.299	1.77E-09	0.837	1.48E-09	30.00	0.385	0.030	0.355	39,218

Bldg. ventilation rate, $Q_{building}$ (cm ³ /s)	Area of enclosed space below grade, A_B (cm ²)	Crack-to-total area ratio, η (unitless)	Crack depth below grade, Z_{crack} (cm)	Enthalpy of vaporization at ave. groundwater temperature, $\Delta H_{v,TS}$ (cal/mol)	Henry's law constant at ave. groundwater temperature, H_{TS} (atm-m ³ /mol)	Henry's law constant at ave. groundwater temperature, H'_{TS} (unitless)	Vapor viscosity at ave. soil temperature, μ_{TS} (g/cm-s)	Stratum A effective diffusion coefficient, D_A^{eff} (cm ² /s)	Stratum B effective diffusion coefficient, D_B^{eff} (cm ² /s)	Stratum C effective diffusion coefficient, D_C^{eff} (cm ² /s)	Capillary zone effective diffusion coefficient, D_{cz}^{eff} (cm ² /s)	Total overall effective diffusion coefficient, D_T^{eff} (cm ² /s)	Diffusion path length, L_d (cm)
3.20E+06	6.93E+07	5.66E-05	15	9,451	1.40E-02	5.81E-01	1.78E-04	1.86E-03	0.00E+00	0.00E+00	7.21E-06	4.67E-05	198.56

Convection path length, L_p (cm)	Source vapor conc., C_{source} (μg/m ³)	Crack radius, r_{crack} (cm)	Average vapor flow rate into bldg., Q_{soil} (cm ³ /s)	Crack effective diffusion coefficient, D^{crack} (cm ² /s)	Area of crack, A_{crack} (cm ²)	Exponent of equivalent foundation Peclet number, $\exp(Pe^f)$ (unitless)	Infinite source indoor attenuation coefficient, α (unitless)	Infinite source bldg. conc., $C_{building}$ (μg/m ³)	Unit risk factor, URF (μg/m ³) ⁻¹	Reference conc., RfC (mg/m ³)
15	2.03E+05	0.10	8.33E+01	1.86E-03	3.92E+03	4.18E+49	4.26E-06	8.67E-01	2.6E-07	4.0E-02

END

RESULTS SHEET

RISK-BASED GROUNDWATER CONCENTRATION CALCULATIONS:

Indoor exposure groundwater conc., carcinogen (µg/L)	Indoor exposure groundwater conc., noncarcinogen (µg/L)	Risk-based indoor exposure groundwater conc., (µg/L)	Pure component water solubility, S (µg/L)	Final indoor exposure groundwater conc., (µg/L)
NA	NA	NA	2.00E+05	NA

INCREMENTAL RISK CALCULATIONS:

Incremental risk from vapor intrusion to indoor air, carcinogen (unitless)	Hazard quotient from vapor intrusion to indoor air, noncarcinogen (unitless)
5.5E-08	1.5E-02

MESSAGE AND ERROR SUMMARY BELOW: (DO NOT USE RESULTS IF ERRORS ARE PRESENT)

SCROLL
DOWN
TO "END"

END

**Non-Residential
Tetrachloroethene
Soil**

SL-ADV
Version 3.1; 02/04

CALCULATE RISK-BASED SOIL CONCENTRATION (enter "X" in "YES" box)

YES

OR

CALCULATE INCREMENTAL RISKS FROM ACTUAL SOIL CONCENTRATION (enter "X" in "YES" box and initial soil conc. below)

YES

X

Reset to
DefaultsENTER
Chemical
CAS No.
(numbers only,
no dashes)ENTER
Initial
soil
conc.,
 C_R
($\mu\text{g/kg}$)

Chemical

127184

1.50E+01

Tetrachloroethylene

MORE
↓ENTER
Average
soil
temperature,
 T_s
($^{\circ}\text{C}$)ENTER
Depth
below grade
to bottom
of enclosed
space floor,
 L_f
(cm)ENTER
Depth below
grade to top
of contamination,
 L_t
(cm)ENTER
Depth below
grade to bottom
of contamination,
(enter value of 0
if value is unknown)
 L_b
(cm)ENTER
Thickness
of soil
stratum A,
 h_A
(cm)ENTER
Thickness
of soil
stratum B,
(Enter value or 0)
 h_B
(cm)ENTER
Thickness
of soil
stratum C,
(Enter value or 0)
 h_C
(cm)ENTER
Soil
stratum A
SCS
soil type
(used to estimate
soil vapor
permeability)

OR

ENTER
User-defined
stratum A
soil vapor
permeability,
 k_v
(cm^2)

20

15

60.96

152.4

60.96

0

0

SC

MORE
↓ENTER
Stratum A
SCS
soil type
Lookup Soil
ParametersENTER
Stratum A
soil dry
bulk density,
 ρ_b^A
(g/cm^3)ENTER
Stratum A
soil total
porosity,
 n^A
(unitless)ENTER
Stratum A
soil water-filled
porosity,
 θ_w^A
(cm^3/cm^3)ENTER
Stratum A
soil organic
carbon fraction,
 f_{oc}^A
(unitless)ENTER
Stratum B
SCS
soil type
Lookup Soil
ParametersENTER
Stratum B
soil dry
bulk density,
 ρ_b^B
(g/cm^3)ENTER
Stratum B
soil total
porosity,
 n^B
(unitless)ENTER
Stratum B
soil water-filled
porosity,
 θ_w^B
(cm^3/cm^3)ENTER
Stratum B
soil organic
carbon fraction,
 f_{oc}^B
(unitless)ENTER
Stratum C
SCS
soil type
Lookup Soil
ParametersENTER
Stratum C
soil dry
bulk density,
 ρ_b^C
(g/cm^3)ENTER
Stratum C
soil total
porosity,
 n^C
(unitless)ENTER
Stratum C
soil water-filled
porosity,
 θ_w^C
(cm^3/cm^3)ENTER
Stratum C
soil organic
carbon fraction,
 f_{oc}^C
(unitless)

SC

1.63

0.385

0.197

0.002

SC

1.63

0.385

0.197

0.002

SC

1.63

0.385

0.197

0.002

MORE
↓ENTER
Enclosed
space
floor
thickness,
 L_{crack}
(cm)ENTER
Soil-bldg.
pressure
differential,
 ΔP
($\text{g/cm} \cdot \text{s}^2$)ENTER
Enclosed
space
floor
length,
 L_b
(cm)ENTER
Enclosed
space
floor
width,
 W_b
(cm)ENTER
Enclosed
space
height,
 H_b
(cm)ENTER
Floor-wall
seam crack
width,
 w
(cm)ENTER
Indoor
air exchange
rate,
 ER
(1/h)ENTER
Average vapor
flow rate into bldg.
OR
Leave blank to calculate
 Q_{vair}
(L/m)

10

40

15036.8

4572

670.56

0.1

0.25

5

ENTER
Averaging
time for
carcinogens,
 AT_C
(yrs)ENTER
Averaging
time for
noncarcinogens,
 AT_{NC}
(yrs)ENTER
Exposure
duration,
 ED
(yrs)ENTER
Exposure
frequency,
 EF
(days/yr)ENTER
Target
risk for
carcinogens,
 TR
(unitless)ENTER
Target hazard
quotient for
noncarcinogens,
 THQ
(unitless)

70

25

25

250

1.0E-05

1

END

Used to calculate risk-based
soil concentration.

CHEMICAL PROPERTIES SHEET

Diffusivity in air, D_a (cm ² /s)	Diffusivity in water, D_w (cm ² /s)	Henry's law constant at reference temperature, H (atm-m ³ /mol)	Henry's law constant reference temperature, T_R (°C)	Enthalpy of vaporization at the normal boiling point, $\Delta H_{v,b}$ (cal/mol)	Normal boiling point, T_B (°K)	Critical temperature, T_C (°K)	Organic carbon partition coefficient, K_{oc} (cm ³ /g)	Pure component water solubility, S (mg/L)	Unit risk factor, URF (µg/m ³) ⁻¹	Reference conc., RfC (mg/m ³)	Physical state at soil temperature, (S,L,G)
7.20E-02	8.20E-06	1.84E-02	25	8,288	394.40	620.20	1.55E+02	2.00E+02	2.6E-07	4.0E-02	L

END

INTERMEDIATE CALCULATIONS SHEET

Exposure duration, τ (sec)	Source-building separation, L_T (cm)	Stratum A soil air-filled porosity, θ_a^A (cm ³ /cm ³)	Stratum B soil air-filled porosity, θ_a^B (cm ³ /cm ³)	Stratum C soil air-filled porosity, θ_a^C (cm ³ /cm ³)	Stratum A effective total fluid saturation, S_{fe} (cm ³ /cm ³)	Stratum A soil intrinsic permeability, k_i (cm ²)	Stratum A soil relative air permeability, k_{rg} (cm ²)	Stratum A soil effective vapor permeability, k_v (cm ²)	Floor-wall seam perimeter, X_{crack} (cm)	Initial soil concentration used, C_R (μg/kg)	Bldg. ventilation rate, $Q_{building}$ (cm ³ /s)
7.88E+08	45.96	0.188	0.188	0.188	0.299	1.77E-09	0.837	1.48E-09	39,218	1.50E+01	3.20E+06

Area of enclosed space below grade, A_B (cm ²)	Crack-to-total area ratio, η (unitless)	Crack depth below grade, Z_{crack} (cm)	Enthalpy of vaporization at ave. soil temperature, $\Delta H_{v,TS}$ (cal/mol)	Henry's law constant at ave. soil temperature, H_{TS} (atm-m ³ /mol)	Henry's law constant at ave. soil temperature, H'_{TS} (unitless)	Vapor viscosity at ave. soil temperature, μ_{TS} (g/cm-s)	Stratum A effective diffusion coefficient, D^{eff}_A (cm ² /s)	Stratum B effective diffusion coefficient, D^{eff}_B (cm ² /s)	Stratum C effective diffusion coefficient, D^{eff}_C (cm ² /s)	Total overall effective diffusion coefficient, D^{eff}_T (cm ² /s)	Diffusion path length, L_d (cm)	Convection path length, L_p (cm)
6.93E+07	5.66E-05	15	9,451	1.40E-02	5.81E-01	1.78E-04	1.86E-03	0.00E+00	0.00E+00	1.86E-03	45.96	15

Soil-water partition coefficient, K_d (cm ³ /g)	Source vapor conc., C_{source} (μg/m ³)	Crack radius, r_{crack} (cm)	Average vapor flow rate into bldg., Q_{soil} (cm ³ /s)	Crack effective diffusion coefficient, D^{crack} (cm ² /s)	Area of crack, A_{crack} (cm ²)	Exponent of equivalent foundation Peclet number, $\exp(Pe^f)$ (unitless)	Infinite source indoor attenuation coefficient, α (unitless)	Infinite source bldg. conc., $C_{building}$ (μg/m ³)	Finite source β term (unitless)	Finite source ψ term (sec) ⁻¹	Time for source depletion, τ_D (sec)	Exposure duration > time for source depletion (YES/NO)
3.10E-01	1.75E+04	0.10	8.33E+01	1.86E-03	3.92E+03	4.18E+49	NA	NA	3.47E+01	6.31E-07	1.13E+08	YES

Finite source indoor attenuation coefficient, < α > (unitless)	Mass limit bldg. conc., $C_{building}$ (μg/m ³)	Finite source bldg. conc., $C_{building}$ (μg/m ³)	Final finite source bldg. conc., $C_{building}$ (μg/m ³)	Unit risk factor, URF (μg/m ³) ⁻¹	Reference conc., RfC (mg/m ³)
NA	6.14E-02	NA	6.14E-02	2.6E-07	4.0E-02

END

RESULTS SHEET

RISK-BASED SOIL CONCENTRATION CALCULATIONS:

Indoor exposure soil conc., carcinogen (µg/kg)	Indoor exposure soil conc., noncarcinogen (µg/kg)	Risk-based indoor exposure soil conc., (µg/kg)	Soil saturation conc., C _{sat} (µg/kg)	Final indoor exposure soil conc., (µg/kg)
NA	NA	NA	9.96E+04	NA

INCREMENTAL RISK CALCULATIONS:

Incremental risk from vapor intrusion to indoor air, carcinogen (unitless)	Hazard quotient from vapor intrusion to indoor air, noncarcinogen (unitless)
3.9E-09	1.1E-03

MESSAGE AND ERROR SUMMARY BELOW: (DO NOT USE RESULTS IF ERRORS ARE PRESENT)

SCROLL
DOWN
TO "END"

END

**Residential
Freon-113
Groundwater**

DATA ENTRY SHEET

GW-ADV
Version 3.1; 02/04

CALCULATE RISK-BASED GROUNDWATER CONCENTRATION (enter "X" in "YES" box)

YES

Reset to
Defaults

OR

CALCULATE INCREMENTAL RISKS FROM ACTUAL GROUNDWATER CONCENTRATION (enter "X" in "YES" box and initial groundwater conc. below)

YES

ENTER Chemical CAS No. (numbers only, no dashes)		ENTER Initial groundwater conc., C_W ($\mu\text{g/L}$)		Chemical							
76131	2.70E+04			1,1,2-Trichloro-1,2,2-trifluoroethane							
ENTER Average soil/ groundwater temperature, T_S ($^{\circ}\text{C}$)	ENTER Depth below grade to bottom of enclosed space floor, L_F (cm)	ENTER Depth below grade to water table, L_{WT} (cm)	ENTER Totals must add up to value of L_{WT} (cell G28)			ENTER Soil stratum directly above water table, (Enter A, B, or C)	ENTER SCS soil type directly above water table	ENTER Soil stratum A SCS soil type (used to estimate soil vapor permeability)		OR	ENTER User-defined stratum A soil vapor permeability, k_v (cm^2)
Thickness of soil stratum A, h_A (cm)	Thickness of soil stratum B, (Enter value or 0) h_B (cm)	Thickness of soil stratum C, (Enter value or 0) h_C (cm)									
20	15	91.44	91.44	0	0	A	SC	SC			

MORE
↓

ENTER Stratum A SCS soil type Lookup Soil Parameters	ENTER Stratum A soil dry bulk density, ρ_b^A (g/cm^3)	ENTER Stratum A soil total porosity, n^A (unitless)	ENTER Stratum A soil water-filled porosity, θ_w^A (cm^3/cm^3)	ENTER Stratum B SCS soil type Lookup Soil Parameters	ENTER Stratum B soil dry bulk density, ρ_b^B (g/cm^3)	ENTER Stratum B soil total porosity, n^B (unitless)	ENTER Stratum B soil water-filled porosity, θ_w^B (cm^3/cm^3)	ENTER Stratum C SCS soil type Lookup Soil Parameters	ENTER Stratum C soil dry bulk density, ρ_b^C (g/cm^3)	ENTER Stratum C soil total porosity, n^C (unitless)	ENTER Stratum C soil water-filled porosity, θ_w^C (cm^3/cm^3)
SC	1.63	0.385	0.197	SC	1.63	0.385	0.197	SC	1.63	0.385	0.197

MORE
↓

ENTER Enclosed space floor thickness, L_{crack} (cm)	ENTER Soil-bldg. pressure differential, ΔP (g/cm-s^2)	ENTER Enclosed space floor length, L_B (cm)	ENTER Enclosed space floor width, W_B (cm)	ENTER Enclosed space height, H_B (cm)	ENTER Floor-wall seam crack width, w (cm)	ENTER Indoor air exchange rate, ER (1/h)	ENTER Average vapor flow rate into bldg. OR Leave blank to calculate Q_{soil} (L/m)
10	40	1000	1000	244	0.1	0.25	5

MORE
↓

ENTER Averaging time for carcinogens, AT_C (yrs)	ENTER Averaging time for noncarcinogens, AT_{NC} (yrs)	ENTER Exposure duration, ED (yrs)	ENTER Exposure frequency, EF (days/yr)	ENTER Target risk for carcinogens, TR (unitless)	ENTER Target hazard quotient for noncarcinogens, THQ (unitless)
70	30	30	350	1.0E-06	1

MORE
↓

END

Used to calculate risk-based
groundwater concentration.

CHEMICAL PROPERTIES SHEET

Diffusivity in air, D_a (cm ² /s)	Diffusivity in water, D_w (cm ² /s)	Henry's law constant at reference temperature, H (atm-m ³ /mol)	Henry's law constant reference temperature, T_R (°C)	Enthalpy of vaporization at the normal boiling point, $\Delta H_{v,b}$ (cal/mol)	Normal boiling point, T_B (°K)	Critical temperature, T_C (°K)	Organic carbon partition coefficient, K_{oc} (cm ³ /g)	Pure component water solubility, S (mg/L)	Unit risk factor, URF (µg/m ³) ⁻¹	Reference conc., RfC (mg/m ³)
7.80E-02	8.20E-06	4.80E-01	25	6,463	320.70	487.30	1.11E+04	1.70E+02	0.0E+00	3.0E+01

END

INTERMEDIATE CALCULATIONS SHEET

Exposure duration, τ (sec)	Source-building separation, L_T (cm)	Stratum A soil air-filled porosity, θ_a^A (cm ³ /cm ³)	Stratum B soil air-filled porosity, θ_a^B (cm ³ /cm ³)	Stratum C soil air-filled porosity, θ_a^C (cm ³ /cm ³)	Stratum A effective total fluid saturation, S_{ie} (cm ³ /cm ³)	Stratum A soil intrinsic permeability, k_i (cm ²)	Stratum A soil relative air permeability, k_{rg} (cm ²)	Stratum A soil effective vapor permeability, k_v (cm ²)	Thickness of capillary zone, L_{cz} (cm)	Total porosity in capillary zone, n_{cz} (cm ³ /cm ³)	Air-filled porosity in capillary zone, $\theta_{a,cz}$ (cm ³ /cm ³)	Water-filled porosity in capillary zone, $\theta_{w,cz}$ (cm ³ /cm ³)	Floor-wall seam perimeter, X_{crack} (cm)
9.46E+08	76.44	0.188	0.188	0.188	0.299	1.77E-09	0.837	1.48E-09	30.00	0.385	0.030	0.355	4,000

Bldg. ventilation rate, $Q_{building}$ (cm ³ /s)	Area of enclosed space below grade, A_B (cm ²)	Crack-to-total area ratio, η (unitless)	Crack depth below grade, Z_{crack} (cm)	Enthalpy of vaporization at ave. groundwater temperature, $\Delta H_{v,TS}$ (cal/mol)	Henry's law constant at ave. groundwater temperature, H_{TS} (atm-m ³ /mol)	Henry's law constant at ave. groundwater temperature, H'_{TS} (unitless)	Vapor viscosity at ave. soil temperature, μ_{TS} (g/cm-s)	Stratum A effective diffusion coefficient, D_A^{eff} (cm ² /s)	Stratum B effective diffusion coefficient, D_B^{eff} (cm ² /s)	Stratum C effective diffusion coefficient, D_C^{eff} (cm ² /s)	Capillary zone effective diffusion coefficient, D_{cz}^{eff} (cm ² /s)	Total overall effective diffusion coefficient, D_T^{eff} (cm ² /s)	Diffusion path length, L_d (cm)
1.69E+04	1.06E+06	3.77E-04	15	6,840	3.94E-01	1.64E+01	1.78E-04	2.01E-03	0.00E+00	0.00E+00	4.65E-06	1.18E-05	76.44

Convection path length, L_p (cm)	Source vapor conc., C_{source} (μg/m ³)	Crack radius, r_{crack} (cm)	Average vapor flow rate into bldg., Q_{soil} (cm ³ /s)	Crack effective diffusion coefficient, D^{crack} (cm ² /s)	Area of crack, A_{crack} (cm ²)	Exponent of equivalent foundation Peclet number, $\exp(Pe^f)$ (unitless)	Infinite source indoor attenuation coefficient, α (unitless)	Infinite source bldg. conc., $C_{building}$ (μg/m ³)	Unit risk factor, URF (μg/m ³) ⁻¹	Reference conc., RfC (mg/m ³)
15	4.42E+08	0.10	8.33E+01	2.01E-03	4.00E+02	#NUM!	9.64E-06	4.26E+03	NA	3.0E+01

END

RESULTS SHEET

RISK-BASED GROUNDWATER CONCENTRATION CALCULATIONS:

Indoor exposure groundwater conc., carcinogen (µg/L)	Indoor exposure groundwater conc., noncarcinogen (µg/L)	Risk-based indoor exposure groundwater conc., (µg/L)	Pure component water solubility, S (µg/L)	Final indoor exposure groundwater conc., (µg/L)
NA	NA	NA	1.70E+05	NA

INCREMENTAL RISK CALCULATIONS:

Incremental risk from vapor intrusion to indoor air, carcinogen (unitless)	Hazard quotient from vapor intrusion to indoor air, noncarcinogen (unitless)
NA	1.4E-01

MESSAGE AND ERROR SUMMARY BELOW: (DO NOT USE RESULTS IF ERRORS ARE PRESENT)

SCROLL
DOWN
TO "END"

END

**Residential
Freon-113
Soil**

SL-ADV
Version 3.1; 02/04

CALCULATE RISK-BASED SOIL CONCENTRATION (enter "X" in "YES" box)

YES

OR

CALCULATE INCREMENTAL RISKS FROM ACTUAL SOIL CONCENTRATION (enter "X" in "YES" box and initial soil conc. below)

YES

X

Reset to
DefaultsENTER
Chemical
CAS No.
(numbers only,
no dashes)ENTER
Initial
soil
conc.,
 C_R
($\mu\text{g/kg}$)

Chemical

76131

6.34E+03

1,1,2-Trichloro-1,2,2-trifluoroethane

MORE
↓

ENTER Average soil temperature, T_s ($^{\circ}\text{C}$)	ENTER Depth below grade to bottom of enclosed space floor, L_f (cm)	ENTER Depth below grade to top of contamination, L_i (cm)	ENTER Depth below grade to bottom of contamination, (enter value of 0 if value is unknown) L_o (cm)	ENTER Thickness of soil stratum A, h_A (cm)	ENTER Thickness of soil stratum B, (Enter value or 0) h_B (cm)	ENTER Thickness of soil stratum C, (Enter value or 0) h_C (cm)	ENTER Soil stratum A SCS soil type (used to estimate soil vapor permeability)	OR	ENTER User-defined stratum A soil vapor permeability, k_v (cm^2)
20	15	30.48	213.36	30.48	0	0	SC		

MORE
↓

ENTER Stratum A SCS soil type Lookup Soil Parameters	ENTER Stratum A soil dry bulk density, ρ_b^A (g/cm^3)	ENTER Stratum A soil total porosity, n^A (unitless)	ENTER Stratum A soil water-filled porosity, θ_w^A (cm^3/cm^3)	ENTER Stratum A soil organic carbon fraction, f_{oc}^A (unitless)	ENTER Stratum B SCS soil type Lookup Soil Parameters	ENTER Stratum B soil dry bulk density, ρ_b^B (g/cm^3)	ENTER Stratum B soil total porosity, n^B (unitless)	ENTER Stratum B soil water-filled porosity, θ_w^B (cm^3/cm^3)	ENTER Stratum B soil organic carbon fraction, f_{oc}^B (unitless)	ENTER Stratum C SCS soil type Lookup Soil Parameters	ENTER Stratum C soil dry bulk density, ρ_b^C (g/cm^3)	ENTER Stratum C soil total porosity, n^C (unitless)	ENTER Stratum C soil water-filled porosity, θ_w^C (cm^3/cm^3)	ENTER Stratum C soil organic carbon fraction, f_{oc}^C (unitless)
SC	1.63	0.385	0.197	0.002	SC	1.63	0.385	0.197	0.002	SC	1.63	0.385	0.197	0.002

MORE
↓

ENTER Enclosed space floor thickness, L_{crack} (cm)	ENTER Soil-bldg. pressure differential, ΔP (g/cm-s^2)	ENTER Enclosed space floor length, L_B (cm)	ENTER Enclosed space floor width, W_B (cm)	ENTER Enclosed space height, H_B (cm)	ENTER Floor-wall seam crack width, w (cm)	ENTER Indoor air exchange rate, ER (1/h)	ENTER Average vapor flow rate into bldg. OR Leave blank to calculate Q_{vbl} (L/m)
10	40	1000	1000	244	0.1	0.25	5

ENTER Averaging time for carcinogens, AT_C (yrs)	ENTER Averaging time for noncarcinogens, AT_{NC} (yrs)	ENTER Exposure duration, ED (yrs)	ENTER Exposure frequency, EF (days/yr)	ENTER Target risk for carcinogens, TR (unitless)	ENTER Target hazard quotient for noncarcinogens, THQ (unitless)
70	30	30	350	1.0E-06	1

END

Used to calculate risk-based
soil concentration.

CHEMICAL PROPERTIES SHEET

Diffusivity in air, D_a (cm ² /s)	Diffusivity in water, D_w (cm ² /s)	Henry's law constant at reference temperature, H (atm-m ³ /mol)	Henry's law constant reference temperature, T_R (°C)	Enthalpy of vaporization at the normal boiling point, $\Delta H_{v,b}$ (cal/mol)	Normal boiling point, T_B (°K)	Critical temperature, T_C (°K)	Organic carbon partition coefficient, K_{oc} (cm ³ /g)	Pure component water solubility, S (mg/L)	Unit risk factor, URF (µg/m ³) ⁻¹	Reference conc., RfC (mg/m ³)	Physical state at soil temperature, (S,L,G)
7.80E-02	8.20E-06	4.80E-01	25	6,463	320.70	487.30	1.11E+04	1.70E+02	0.0E+00	3.0E+01	L

END

INTERMEDIATE CALCULATIONS SHEET

Exposure duration, τ (sec)	Source-building separation, L_T (cm)	Stratum A soil air-filled porosity, θ_a^A (cm ³ /cm ³)	Stratum B soil air-filled porosity, θ_a^B (cm ³ /cm ³)	Stratum C soil air-filled porosity, θ_a^C (cm ³ /cm ³)	Stratum A effective total fluid saturation, S_{fe} (cm ³ /cm ³)	Stratum A soil intrinsic permeability, k_i (cm ²)	Stratum A soil relative air permeability, k_{rg} (cm ²)	Stratum A soil effective vapor permeability, k_v (cm ²)	Floor-wall seam perimeter, X_{crack} (cm)	Initial soil concentration used, C_R (μg/kg)	Bldg. ventilation rate, $Q_{building}$ (cm ³ /s)
9.46E+08	15.48	0.188	0.188	0.188	0.299	1.77E-09	0.837	1.48E-09	4,000	6.34E+03	1.69E+04

Area of enclosed space below grade, A_B (cm ²)	Crack-to-total area ratio, η (unitless)	Crack depth below grade, Z_{crack} (cm)	Enthalpy of vaporization at ave. soil temperature, $\Delta H_{v,TS}$ (cal/mol)	Henry's law constant at ave. soil temperature, H_{TS} (atm-m ³ /mol)	Henry's law constant at ave. soil temperature, H'_{TS} (unitless)	Vapor viscosity at ave. soil temperature, μ_{TS} (g/cm-s)	Stratum A effective diffusion coefficient, D_{eff}^A (cm ² /s)	Stratum B effective diffusion coefficient, D_{eff}^B (cm ² /s)	Stratum C effective diffusion coefficient, D_{eff}^C (cm ² /s)	Total overall effective diffusion coefficient, D_{eff}^T (cm ² /s)	Diffusion path length, L_d (cm)	Convection path length, L_p (cm)
1.06E+06	3.77E-04	15	6,840	3.94E-01	1.64E+01	1.78E-04	2.01E-03	0.00E+00	0.00E+00	2.01E-03	15.48	15

Soil-water partition coefficient, K_d (cm ³ /g)	Source vapor conc., C_{source} (μg/m ³)	Crack radius, r_{crack} (cm)	Average vapor flow rate into bldg., Q_{soil} (cm ³ /s)	Crack effective diffusion coefficient, D_{crack}^{eff} (cm ² /s)	Area of crack, A_{crack} (cm ²)	Exponent of equivalent foundation Peclet number, $\exp(Pe^f)$ (unitless)	Infinite source indoor attenuation coefficient, α (unitless)	Infinite source bldg. conc., $C_{building}$ (μg/m ³)	Finite source β term (unitless)	Finite source ψ term (sec) ⁻¹	Time for source depletion, τ_D (sec)	Exposure duration > time for source depletion (YES/NO)
2.23E+01	4.27E+06	0.10	8.33E+01	2.01E-03	4.00E+02	#NUM!	NA	NA	2.66E+00	3.48E-06	2.91E+07	YES

Finite source indoor attenuation coefficient, < α > (unitless)	Mass limit bldg. conc., $C_{building}$ (μg/m ³)	Finite source bldg. conc., $C_{building}$ (μg/m ³)	Final finite source bldg. conc., $C_{building}$ (μg/m ³)	Unit risk factor, URF (μg/m ³) ⁻¹	Reference conc., RfC (mg/m ³)
NA	1.25E+02	NA	1.25E+02	NA	3.0E+01

END

RESULTS SHEET

RISK-BASED SOIL CONCENTRATION CALCULATIONS:

Indoor exposure soil conc., carcinogen (µg/kg)	Indoor exposure soil conc., noncarcinogen (µg/kg)	Risk-based indoor exposure soil conc., (µg/kg)	Soil saturation conc., C _{sat} (µg/kg)	Final indoor exposure soil conc., (µg/kg)
NA	NA	NA	4.13E+06	NA

INCREMENTAL RISK CALCULATIONS:

Incremental risk from vapor intrusion to indoor air, carcinogen (unitless)	Hazard quotient from vapor intrusion to indoor air, noncarcinogen (unitless)
NA	4.0E-03

MESSAGE AND ERROR SUMMARY BELOW: (DO NOT USE RESULTS IF ERRORS ARE PRESENT)

SCROLL
DOWN
TO "END"

END

**Residential
Tetrachloroethene
Groundwater**

DATA ENTRY SHEET

GW-ADV
Version 3.1; 02/04

CALCULATE RISK-BASED GROUNDWATER CONCENTRATION (enter "X" in "YES" box)

YES

Reset to
Defaults

OR

CALCULATE INCREMENTAL RISKS FROM ACTUAL GROUNDWATER CONCENTRATION (enter "X" in "YES" box and initial groundwater conc. below)

YES

ENTER Chemical CAS No. (numbers only, no dashes)		ENTER Initial groundwater conc., C_W ($\mu\text{g/L}$)		Chemical							
127184	3.50E+02			Tetrachloroethylene							
ENTER Average soil/ groundwater temperature, T_S ($^{\circ}\text{C}$)	ENTER Depth below grade to bottom of enclosed space floor, L_F (cm)	ENTER Depth below grade to water table, L_{WT} (cm)	ENTER Totals must add up to value of L_{WT} (cell G28)			ENTER Soil stratum directly above water table, (Enter A, B, or C)	ENTER SCS soil type directly above water table	ENTER Soil stratum A SCS soil type (used to estimate soil vapor permeability)		OR	ENTER User-defined stratum A soil vapor permeability, k_v (cm^2)
Thickness of soil stratum A, h_A (cm)	Thickness of soil stratum B, (Enter value or 0) h_B (cm)	Thickness of soil stratum C, (Enter value or 0) h_C (cm)									
20	15	91.44	91.44	0	0	A	SC	SC			

MORE
↓

ENTER Stratum A SCS soil type Lookup Soil Parameters	ENTER Stratum A soil dry bulk density, ρ_b^A (g/cm^3)	ENTER Stratum A soil total porosity, n^A (unitless)	ENTER Stratum A soil water-filled porosity, θ_w^A (cm^3/cm^3)	ENTER Stratum B SCS soil type Lookup Soil Parameters	ENTER Stratum B soil dry bulk density, ρ_b^B (g/cm^3)	ENTER Stratum B soil total porosity, n^B (unitless)	ENTER Stratum B soil water-filled porosity, θ_w^B (cm^3/cm^3)	ENTER Stratum C SCS soil type Lookup Soil Parameters	ENTER Stratum C soil dry bulk density, ρ_b^C (g/cm^3)	ENTER Stratum C soil total porosity, n^C (unitless)	ENTER Stratum C soil water-filled porosity, θ_w^C (cm^3/cm^3)
SC	1.63	0.385	0.197	SC	1.63	0.385	0.197	SC	1.63	0.385	0.197

MORE
↓

ENTER Enclosed space floor thickness, L_{crack} (cm)	ENTER Soil-bldg. pressure differential, ΔP (g/cm-s^2)	ENTER Enclosed space floor length, L_B (cm)	ENTER Enclosed space floor width, W_B (cm)	ENTER Enclosed space height, H_B (cm)	ENTER Floor-wall seam crack width, w (cm)	ENTER Indoor air exchange rate, ER (1/h)	ENTER Average vapor flow rate into bldg. OR Leave blank to calculate Q_{soil} (L/m)
10	40	1000	1000	244	0.1	0.25	5

MORE
↓

ENTER Averaging time for carcinogens, AT_C (yrs)	ENTER Averaging time for noncarcinogens, AT_{NC} (yrs)	ENTER Exposure duration, ED (yrs)	ENTER Exposure frequency, EF (days/yr)	ENTER Target risk for carcinogens, TR (unitless)	ENTER Target hazard quotient for noncarcinogens, THQ (unitless)
70	30	30	350	1.0E-06	1

MORE
↓

END

Used to calculate risk-based
groundwater concentration.

CHEMICAL PROPERTIES SHEET

Diffusivity in air, D_a (cm^2/s)	Diffusivity in water, D_w (cm^2/s)	Henry's law constant at reference temperature, H ($\text{atm}\cdot\text{m}^3/\text{mol}$)	Henry's law constant reference temperature, T_R ($^{\circ}\text{C}$)	Enthalpy of vaporization at the normal boiling point, $\Delta H_{v,b}$ (cal/mol)	Normal boiling point, T_B ($^{\circ}\text{K}$)	Critical temperature, T_C ($^{\circ}\text{K}$)	Organic carbon partition coefficient, K_{oc} (cm^3/g)	Pure component water solubility, S (mg/L)	Unit risk factor, URF ($\mu\text{g}/\text{m}^3$) ⁻¹	Reference conc., RfC (mg/m^3)
7.20E-02	8.20E-06	1.84E-02	25	8,288	394.40	620.20	1.55E+02	2.00E+02	2.6E-07	4.0E-02

END

INTERMEDIATE CALCULATIONS SHEET

Exposure duration, τ (sec)	Source-building separation, L_T (cm)	Stratum A soil air-filled porosity, θ_a^A (cm ³ /cm ³)	Stratum B soil air-filled porosity, θ_a^B (cm ³ /cm ³)	Stratum C soil air-filled porosity, θ_a^C (cm ³ /cm ³)	Stratum A effective total fluid saturation, S_{ie} (cm ³ /cm ³)	Stratum A soil intrinsic permeability, k_i (cm ²)	Stratum A soil relative air permeability, k_{rg} (cm ²)	Stratum A soil effective vapor permeability, k_v (cm ²)	Thickness of capillary zone, L_{cz} (cm)	Total porosity in capillary zone, n_{cz} (cm ³ /cm ³)	Air-filled porosity in capillary zone, $\theta_{a,cz}$ (cm ³ /cm ³)	Water-filled porosity in capillary zone, $\theta_{w,cz}$ (cm ³ /cm ³)	Floor-wall seam perimeter, X_{crack} (cm)
9.46E+08	76.44	0.188	0.188	0.188	0.299	1.77E-09	0.837	1.48E-09	30.00	0.385	0.030	0.355	4,000

Bldg. ventilation rate, $Q_{building}$ (cm ³ /s)	Area of enclosed space below grade, A_B (cm ²)	Crack-to-total area ratio, η (unitless)	Crack depth below grade, Z_{crack} (cm)	Enthalpy of vaporization at ave. groundwater temperature, $\Delta H_{v,TS}$ (cal/mol)	Henry's law constant at ave. groundwater temperature, H_{TS} (atm-m ³ /mol)	Henry's law constant at ave. groundwater temperature, H'_{TS} (unitless)	Vapor viscosity at ave. soil temperature, μ_{TS} (g/cm-s)	Stratum A effective diffusion coefficient, D_A^{eff} (cm ² /s)	Stratum B effective diffusion coefficient, D_B^{eff} (cm ² /s)	Stratum C effective diffusion coefficient, D_C^{eff} (cm ² /s)	Capillary zone effective diffusion coefficient, D_{cz}^{eff} (cm ² /s)	Total overall effective diffusion coefficient, D_T^{eff} (cm ² /s)	Diffusion path length, L_d (cm)
1.69E+04	1.06E+06	3.77E-04	15	9,451	1.40E-02	5.81E-01	1.78E-04	1.86E-03	0.00E+00	0.00E+00	7.21E-06	1.83E-05	76.44

Convection path length, L_p (cm)	Source vapor conc., C_{source} (μg/m ³)	Crack radius, r_{crack} (cm)	Average vapor flow rate into bldg., Q_{soil} (cm ³ /s)	Crack effective diffusion coefficient, D^{crack} (cm ² /s)	Area of crack, A_{crack} (cm ²)	Exponent of equivalent foundation Peclet number, $\exp(Pe^f)$ (unitless)	Infinite source indoor attenuation coefficient, α (unitless)	Infinite source bldg. conc., $C_{building}$ (μg/m ³)	Unit risk factor, URF (μg/m ³) ⁻¹	Reference conc., RfC (mg/m ³)
15	2.03E+05	0.10	8.33E+01	1.86E-03	4.00E+02	#NUM!	1.49E-05	3.03E+00	2.6E-07	4.0E-02

END

RESULTS SHEET

RISK-BASED GROUNDWATER CONCENTRATION CALCULATIONS:

Indoor exposure groundwater conc., carcinogen (µg/L)	Indoor exposure groundwater conc., noncarcinogen (µg/L)	Risk-based indoor exposure groundwater conc., (µg/L)	Pure component water solubility, S (µg/L)	Final indoor exposure groundwater conc., (µg/L)
NA	NA	NA	2.00E+05	NA

INCREMENTAL RISK CALCULATIONS:

Incremental risk from vapor intrusion to indoor air, carcinogen (unitless)	Hazard quotient from vapor intrusion to indoor air, noncarcinogen (unitless)
3.2E-07	7.3E-02

MESSAGE AND ERROR SUMMARY BELOW: (DO NOT USE RESULTS IF ERRORS ARE PRESENT)

SCROLL
DOWN
TO "END"

END

**Residential
Tetrachloroethene
Soil**

SL-ADV
Version 3.1; 02/04

CALCULATE RISK-BASED SOIL CONCENTRATION (enter "X" in "YES" box)

YES

OR

CALCULATE INCREMENTAL RISKS FROM ACTUAL SOIL CONCENTRATION (enter "X" in "YES" box and initial soil conc. below)

YES

X

Reset to
DefaultsENTER
Chemical
CAS No.
(numbers only,
no dashes)ENTER
Initial
soil
conc.,
 C_R
($\mu\text{g/kg}$)

Chemical

127184

3.00E+02

Tetrachloroethylene

MORE
↓

ENTER Average soil temperature, T_s ($^{\circ}\text{C}$)	ENTER Depth below grade to bottom of enclosed space floor, L_f (cm)	ENTER Depth below grade to top of contamination, L_i (cm)	ENTER Depth below grade to bottom of contamination, (enter value of 0 if value is unknown) L_b (cm)	ENTER Thickness of soil stratum A, h_A (cm)	ENTER Thickness of soil stratum B, (Enter value or 0) h_B (cm)	ENTER Thickness of soil stratum C, (Enter value or 0) h_C (cm)	ENTER Soil stratum A SCS soil type (used to estimate soil vapor permeability)	OR	ENTER User-defined stratum A soil vapor permeability, k_v (cm^2)
20	15	60.96	152.4	60.96	0	0	SC		

MORE
↓

ENTER Stratum A SCS soil type Lookup Soil Parameters	ENTER Stratum A soil dry bulk density, ρ_b^A (g/cm^3)	ENTER Stratum A soil total porosity, n^A (unitless)	ENTER Stratum A soil water-filled porosity, θ_w^A (cm^3/cm^3)	ENTER Stratum A soil organic carbon fraction, f_{oc}^A (unitless)	ENTER Stratum B SCS soil type Lookup Soil Parameters	ENTER Stratum B soil dry bulk density, ρ_b^B (g/cm^3)	ENTER Stratum B soil total porosity, n^B (unitless)	ENTER Stratum B soil water-filled porosity, θ_w^B (cm^3/cm^3)	ENTER Stratum B soil organic carbon fraction, f_{oc}^B (unitless)	ENTER Stratum C SCS soil type Lookup Soil Parameters	ENTER Stratum C soil dry bulk density, ρ_b^C (g/cm^3)	ENTER Stratum C soil total porosity, n^C (unitless)	ENTER Stratum C soil water-filled porosity, θ_w^C (cm^3/cm^3)	ENTER Stratum C soil organic carbon fraction, f_{oc}^C (unitless)
SC	1.63	0.385	0.197	0.002	SC	1.63	0.385	0.197	0.002	SC	1.63	0.385	0.197	0.002

MORE
↓

ENTER Enclosed space floor thickness, L_{crack} (cm)	ENTER Soil-bldg. pressure differential, ΔP ($\text{g/cm} \cdot \text{s}^2$)	ENTER Enclosed space floor length, L_b (cm)	ENTER Enclosed space floor width, W_b (cm)	ENTER Enclosed space height, H_b (cm)	ENTER Floor-wall seam crack width, w (cm)	ENTER Indoor air exchange rate, ER (1/h)	ENTER Average vapor flow rate into bldg. OR Leave blank to calculate Q_{vair} (L/m)
10	40	1000	1000	244	0.1	0.25	5

ENTER Averaging time for carcinogens, AT_C (yrs)	ENTER Averaging time for noncarcinogens, AT_{NC} (yrs)	ENTER Exposure duration, ED (yrs)	ENTER Exposure frequency, EF (days/yr)	ENTER Target risk for carcinogens, TR (unitless)	ENTER Target hazard quotient for noncarcinogens, THQ (unitless)
70	30	30	350	1.0E-06	1

END

Used to calculate risk-based
soil concentration.

CHEMICAL PROPERTIES SHEET

Diffusivity in air, D_a (cm^2/s)	Diffusivity in water, D_w (cm^2/s)	Henry's law constant at reference temperature, H ($\text{atm}\cdot\text{m}^3/\text{mol}$)	Henry's law constant reference temperature, T_R ($^{\circ}\text{C}$)	Enthalpy of vaporization at the normal boiling point, $\Delta H_{v,b}$ (cal/mol)	Normal boiling point, T_B ($^{\circ}\text{K}$)	Critical temperature, T_C ($^{\circ}\text{K}$)	Organic carbon partition coefficient, K_{oc} (cm^3/g)	Pure component water solubility, S (mg/L)	Unit risk factor, URF ($\mu\text{g}/\text{m}^3$) ⁻¹	Reference conc., RfC (mg/m^3)	Physical state at soil temperature, (S,L,G)
7.20E-02	8.20E-06	1.84E-02	25	8,288	394.40	620.20	1.55E+02	2.00E+02	2.6E-07	4.0E-02	L

END

INTERMEDIATE CALCULATIONS SHEET

Exposure duration, τ (sec)	Source-building separation, L_T (cm)	Stratum A soil air-filled porosity, θ_a^A (cm ³ /cm ³)	Stratum B soil air-filled porosity, θ_a^B (cm ³ /cm ³)	Stratum C soil air-filled porosity, θ_a^C (cm ³ /cm ³)	Stratum A effective total fluid saturation, S_{fe} (cm ³ /cm ³)	Stratum A soil intrinsic permeability, k_i (cm ²)	Stratum A soil relative air permeability, k_{rg} (cm ²)	Stratum A soil effective vapor permeability, k_v (cm ²)	Floor-wall seam perimeter, X_{crack} (cm)	Initial soil concentration used, C_R (µg/kg)	Bldg. ventilation rate, $Q_{building}$ (cm ³ /s)
9.46E+08	45.96	0.188	0.188	0.188	0.299	1.77E-09	0.837	1.48E-09	4,000	3.00E+02	1.69E+04

Area of enclosed space below grade, A_B (cm ²)	Crack-to-total area ratio, η (unitless)	Crack depth below grade, Z_{crack} (cm)	Enthalpy of vaporization at ave. soil temperature, $\Delta H_{v,TS}$ (cal/mol)	Henry's law constant at ave. soil temperature, H_{TS} (atm-m ³ /mol)	Henry's law constant at ave. soil temperature, H'_{TS} (unitless)	Vapor viscosity at ave. soil temperature, μ_{TS} (g/cm-s)	Stratum A effective diffusion coefficient, D^{eff}_A (cm ² /s)	Stratum B effective diffusion coefficient, D^{eff}_B (cm ² /s)	Stratum C effective diffusion coefficient, D^{eff}_C (cm ² /s)	Total overall effective diffusion coefficient, D^{eff}_T (cm ² /s)	Diffusion path length, L_d (cm)	Convection path length, L_p (cm)
1.06E+06	3.77E-04	15	9,451	1.40E-02	5.81E-01	1.78E-04	1.86E-03	0.00E+00	0.00E+00	1.86E-03	45.96	15

Soil-water partition coefficient, K_d (cm ³ /g)	Source vapor conc., C_{source} (µg/m ³)	Crack radius, r_{crack} (cm)	Average vapor flow rate into bldg., Q_{soil} (cm ³ /s)	Crack effective diffusion coefficient, D^{crack} (cm ² /s)	Area of crack, A_{crack} (cm ²)	Exponent of equivalent foundation Peclet number, $\exp(Pe^f)$ (unitless)	Infinite source indoor attenuation coefficient, α (unitless)	Infinite source bldg. conc., $C_{building}$ (µg/m ³)	Finite source β term (unitless)	Finite source ψ term (sec) ⁻¹	Time for source depletion, τ_D (sec)	Exposure duration > time for source depletion (YES/NO)
3.10E-01	3.50E+05	0.10	8.33E+01	1.86E-03	4.00E+02	#NUM!	NA	NA	1.51E+00	6.31E-07	7.92E+06	YES

Finite source indoor attenuation coefficient, < α > (unitless)	Mass limit bldg. conc., $C_{building}$ (µg/m ³)	Finite source bldg. conc., $C_{building}$ (µg/m ³)	Final finite source bldg. conc., $C_{building}$ (µg/m ³)	Unit risk factor, URF (µg/m ³) ⁻¹	Reference conc., RfC (mg/m ³)
NA	2.96E+00	NA	2.96E+00	2.6E-07	4.0E-02

END

RESULTS SHEET

RISK-BASED SOIL CONCENTRATION CALCULATIONS:

Indoor exposure soil conc., carcinogen (µg/kg)	Indoor exposure soil conc., noncarcinogen (µg/kg)	Risk-based indoor exposure soil conc., (µg/kg)	Soil saturation conc., C _{sat} (µg/kg)	Final indoor exposure soil conc., (µg/kg)
NA	NA	NA	9.96E+04	NA

INCREMENTAL RISK CALCULATIONS:

Incremental risk from vapor intrusion to indoor air, carcinogen (unitless)	Hazard quotient from vapor intrusion to indoor air, noncarcinogen (unitless)
3.2E-07	7.1E-02

MESSAGE AND ERROR SUMMARY BELOW: (DO NOT USE RESULTS IF ERRORS ARE PRESENT)

SCROLL
DOWN
TO "END"

END